#### **NAME**

xzcmp, xzdiff, lzcmp, lzdiff – compare compressed files

## **SYNOPSIS**

```
xzcmp [cmp_options] file1 [file2]
xzdiff [diff_options] file1 [file2]
lzcmp [cmp_options] file1 [file2]
lzdiff [diff_options] file1 [file2]
```

# **DESCRIPTION**

**xzcmp** and **xzdiff** invoke  $\mathbf{cmp}(1)$  or  $\mathbf{diff}(1)$  on files compressed with  $\mathbf{xz}(1)$ ,  $\mathbf{lzma}(1)$ ,  $\mathbf{gzip}(1)$ , or  $\mathbf{bzip2}(1)$ . All options specified are passed directly to  $\mathbf{cmp}(1)$  or  $\mathbf{diff}(1)$ . If only one file is specified, then the files compared are  $\mathit{file1}$  (which must have a suffix of a supported compression format) and  $\mathit{file1}$  from which the compression format suffix has been stripped. If two files are specified, then they are uncompressed if necessary and fed to  $\mathbf{cmp}(1)$  or  $\mathbf{diff}(1)$ . The exit status from  $\mathbf{cmp}(1)$  or  $\mathbf{diff}(1)$  is preserved.

The names **lzcmp** and **lzdiff** are provided for backward compatibility with LZMA Utils.

## **SEE ALSO**

```
cmp(1), diff(1), xz(1), gzip(1), bzip2(1), zdiff(1)
```

### **BUGS**

Messages from the  $\mathbf{cmp}(1)$  or  $\mathbf{diff}(1)$  programs refer to temporary filenames instead of those specified.

Tukaani 2010-09-27 1