
CRS1414

CRS1414 Interlaced Disc Roller Screen

150 t/h coal classifying screen with 14 interlaced disc shafts and ≤ 8 mm undersize; stable with wet and sticky coal.



TECHNICAL SPECIFICATIONS

Capacity	150 t/h
Number of shafts	14
Screen width	1400 mm
Feed size	≤ 200 mm
Undersize (discharge)	≤ 8 mm
Motors	14 × 3.0 kW
Shaft speed	85 rpm
Screening efficiency	≥ 80 – 85 % (depending on moisture)
Dimensions (L × W × H)	3740 × 2587 × 1555 mm
Weight	≈ 10,000 kg

APPLICATIONS

Raw coal, power-plant coal and bauxite. Supplied for the coal screening system of the thermal power unit, Lam Dong alumina plant.

KEY FEATURES

- Wear-resistant alloy discs for long service life
- Hard-tooth-surface gear reducers for stable operation
- Cleaning combs prevent clogging with sticky material
- Low, compact frame that fits existing lines

VAN PHONG SERVICES

- Advice on the right configuration for your needs
- Genuine products with full CO/CQ documents
- Delivery, installation, commissioning and user training
- Warranty, maintenance, repair and spare parts

Specifications are based on manufacturer documents and actual supply records and may change with the model version. Please contact us for the exact configuration and quotation.

VAN PHONG TECHNICAL AND TRADING CO., LTD.
No. 34, Lane 36A Tran Dien, Phuong Liet Ward, Hanoi, Vietnam

Hotline / WhatsApp: +84 899 990 683
info@vanphongtechco.com.vn · www.vanphongtechco.com.vn