
CRS1414

# CRS1414 Interlaced Disc Roller Screen

150 t/h coal classifying screen with 14 interlaced disc shafts and ≤ 8 mm undersize; stable with wet and sticky coal.



## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| Capacity | 150 t/h |
| Number of shafts | 14 |
| Screen width | 1400 mm |
| Feed size | ≤ 200 mm |
| Undersize (discharge) | ≤ 8 mm |
| Motors | 14 × 3.0 kW |
| Shaft speed | 85 rpm |
| Screening efficiency | ≥ 80 – 85 % (depending on moisture) |
| Dimensions (L × W × H) | 3740 × 2587 × 1555 mm |
| Weight | ≈ 10,000 kg |

## APPLICATIONS

Raw coal, power-plant coal and bauxite. Supplied for the coal screening system of the thermal power unit, Lam Dong alumina plant.

## KEY FEATURES

- Wear-resistant alloy discs for long service life
- Hard-tooth-surface gear reducers for stable operation
- Cleaning combs prevent clogging with sticky material
- Low, compact frame that fits existing lines

## VAN PHONG SERVICES

- Advice on the right configuration for your needs
- Genuine products with full CO/CQ documents
- Delivery, installation, commissioning and user training
- Warranty, maintenance, repair and spare parts

*Specifications are based on manufacturer documents and actual supply records and may change with the model version. Please contact us for the exact configuration and quotation.*

**VAN PHONG TECHNICAL AND TRADING CO., LTD.**
No. 34, Lane 36A Tran Dien, Phuong Liet Ward, Hanoi, Vietnam

Hotline / WhatsApp: +84 899 990 683
info@vanphongtechco.com.vn · www.vanphongtechco.com.vn