

Thiết lập DNS giữa 2 máy UBuntu

- ## 1. Cấu hình 2 máy

DNS Server IP : 192.168.56.10

a, Trên máy Server:

```
options {  
    directory "/var/cache/bind";  
  
    recursion yes;  
  
    dnssec-validation auto;  
  
    listen-on { any; };  
    listen-on-v6 { any; };  
};
```

"/etc/bind/named.conf.options" 10L, 145B 9,4-8 All

```
sudo vim /etc/bind/named.conf.local
```

```
//
// Do any local configuration here
//

// Consider adding the 1918 zones here, if they are not used in your
// organization
//include "/etc/bind/zones.rfc
zone "56.168.192.in-addr.arpa" {
    type master;
    file "/etc/bind/db.192.168.56";
};
zone "lab.demo" {
    type master;
    file "/etc/bind/db.lab.demo";
};
```

```
sudo vim /etc/bind/db.lab.demo
```

```

;
; BIND data file for local loopback interface
;
$TTL      604800
@         IN      SOA      ns1.lab.demo. admin.lab.demo. (
                        2          ; Serial
                        604800     ; Refresh
                        86400      ; Retry
                        2419200    ; Expire
                        604800 )   ; Negative Cache TTL
;
@         IN      NS       ns1.lab.demo.
ns1       IN      A        192.168.56.10
server    IN      A        192.168.56.10
client    IN      A        192.168.56.20

```

sudo vim /etc/bind/db.192.168.56

```
;
; BIND reverse data file for local loopback interface
;
$TTL      604800
@         IN      SOA      ns1.lab.demo. admin.lab.demo. (
                        1      ; Serial
                        604800  ; Refresh
                        86400   ; Retry
                        2419200 ; Expire
                        604800 ) ; Negative Cache TTL
;
@         IN      NS       ns1.lab.demo.
10        IN      PTR      ns1.lab.demo.
20        IN      PTR      client.lab.demo.
; ===== DNS Servers =====
ns1       IN      A        192.168.56.10
ns2       IN      A        192.168.56.11
; ===== Hosts =====
server    IN      A        192.168.56.10
client    IN      A        192.168.56.20
; ===== Alias =====
www       IN      CNAME     server.lab.demo.
; ===== Mail =====
mail      IN      A        192.168.56.30
@         IN      MX 10     mail.lab.demo.
; ===== FTP =====
ftp       IN      CNAME     server.lab.demo.
; ===== IPv6 =====
server6   IN      AAAA     2001:db8::10
; ===== TXT =====
@         IN      TXT      "Lab DNS Server"
spf       IN      TXT      "v=spf1 ip4:192.168.56.30 -all"
; ===== SRV =====
_ldap._tcp IN SRV 0 5 389 dc1.lab.demo.
dc1       IN      A        192.168.56.40
~
```

sudo vim 50-cloud-init.yaml

```
network:
  version: 2
  ethernets:
    enp0s3:
      dhcp4: false
      addresses:
        - 192.168.56.10/24
      routes:
        - to: default
          via: 192.168.56.1
      nameservers:
        addresses:
          - 192.168.56.10
    enp0s8:
      dhcp4: true
```

2. Kiểm tra DNS

Trên Client :

```
ubuntu@ubuntu1:/etc$ nslookup server.lab.demo
Server:      192.168.56.10
Address:     192.168.56.10#53

Name:   server.lab.demo
Address: 192.168.56.10

ubuntu@ubuntu1:/etc$ nslookup client.lab.demo
Server:      192.168.56.10
Address:     192.168.56.10#53

Name:   client.lab.demo
Address: 192.168.56.20

ubuntu@ubuntu1:/etc$ ping server.lab.demo
PING server.lab.demo (192.168.56.10) 56(84) bytes of data:
64 bytes from ns1.lab.demo (192.168.56.10): icmp_seq=1 ttl=64 time=0.586 ms
64 bytes from ns1.lab.demo (192.168.56.10): icmp_seq=2 ttl=64 time=1.51 ms
64 bytes from ns1.lab.demo (192.168.56.10): icmp_seq=3 ttl=64 time=1.57 ms
64 bytes from ns1.lab.demo (192.168.56.10): icmp_seq=4 ttl=64 time=1.23 ms
^C
-- server.lab.demo ping statistics --
4 packets transmitted, 4 received, 0% packet loss, time 3004ms
rtt min/avg/max/mdev = 0.586/1.224/1.574/0.390 ms
ubuntu@ubuntu1:/etc$ _
```

Chạy lệnh nslookup và ping đều có phản hồi từ phía server : 192.168.56.10