

Programmable **SMS API** helps you to add robust messaging capabilities to your application

Using SMS API, you can send,

- Bulk SMS
- OTP SMS
- Flash SMS
- SMS with Unicode

Base URL

<https://api.aoc-portal.com/v1/sms>

Parameters and Variables:

The following table describes the parameters used in the SMS API request.

Headers

Name	Type	Description
Content-Type	String	application/json
apikey	String	API Key generated by panel.digimiles.in, i.e : 7cP0XXXXXXb8rcQBCXXXX XXA2tHKRc'

Request Body

Attribute Name	Type	Required	Description	Sample Value
sender	String	Yes	Originator/Alphanumeric ID Senderid	DIGIML
to	String	Yes	Recipient's MSISDN	91XXXXXXXXXX
text	String	Yes	Originator/Alphanumeric ID Senderid	DIGIML
type	String	Yes	Route type	TRANS
templateId	String	Optional	Unique ID of the template.	120716XXXXXX XXXXXX
unicode	Integer	Optional	To specify that the message to be sent is in unicode format.	1

Post Request (Send single message)

```
{
  "sender": "AOC-PORTAL",
  "to": "916xxxxxx",
  "text": "this is test message",
  "type": "TRANS"
}
```

Success Response

```
{
  "id": "58d63c02-XXXX-XXXX-XXXX-XXXXbb39453",
  "data": [
    {
      "recipient": "91XXXXXXXXXX",
      "messageId": "58d63c02-XXXX-XXXX-XXXX-XXXX9bb39453:1"
    }
  ],
  "totalCount": 1,
  "message": "Message Sent Successfully!",
  "error": null
}
```

Failed Response

```
{
  "error": true,
  "message": "Api Key not found"
}
```

Post Request (Send bulk message)

```
{
  "sender": "AOC-PORTAL",
  "to": "91XXXXXXXXXX1, 91XXXXXXXXXXXX2, 91XXXXXXXXXXXX3",
  "text": "this is test message",
  "type": "TRANS"
}
```

Success Response

```
{
  "id": "58d63c02-XXXX-XXXX-XXXX-XXXXbb39453",
  "data": [
    {
      "recipient": "91XXXXXXXXXX1",
      "messageId": "58d63c02-XXXXX-XXXXX-XXXXX-XXXX9bb39453:1"
    },
    {
      "recipient": "91XXXXXXXXXX2",
      "messageId": "58d63c02-XXXXX-XXXXX-XXXXX-XXXX9bb39453:2"
    },
    {
      "recipient": "91XXXXXXXXXX3",
      "messageId": "58d63c02-XXXXX-XXXXX-XXXXX-XXXX9bb39453:3"
    }
  ],
  "totalCount": 3,
  "message": "Message Sent Successfully!",
  "error": null
}
```

Failed Response

```
{
  "error": true,
  "message": "Api Key not found"
}
```

Post Curl Request

```
curl --location 'https://api.aoc-portal.com/v1/sms' \
--header 'apikey: 7cP0XXXXXXb8rcQBCXXXXXXA2tHKRc' \
--header 'Content-Type: application/json' \
--data '{
  "sender": "DIGIML",
  "to": "91XXXXXXXXXX1, 91XXXXXXXXXX2, 91XXXXXXXXXX3",
  "text": "this is test template",
  "type": "TRANS"
}'
```

GET Curl Request

```
curl --location 'https://api.aoc-portal.com/v1/sms?sender=DIGIML&to=91XXXXXXXXXX&text=this%20is%20test%20message&type=TRANS' \
--header 'Content-Type: application/json' \
--header 'apikey: 7cP0XXXXXXb8rcQBCXXXXXXA2tHKRc'
```

Generate and verify OTP API Service

1. Generate OTP

Generate OTP API Base URL

<https://api.aoc-portal.com/v1/verify>

Parameters and Variables:

The following table describes the parameters used in the SMS API request.

Headers

Name	Type	Description
Content-Type	String	application/json
apikey	String	API Key generated by panel.digimiles.in, i.e : <u>7cP0XXXXXXXXb8rcQBCXXXX</u> <u>XXA2tHKRc'</u>

Request Body

Attribute Name	Type	Required	Description	Sample Value
configId	String	Yes	ID of the verification configuration based on which the OTP will be generated.	a73cd9ae-XXXX-XXXX-XXXX-7f73XXXX4064
to	String	Yes	Recipient's MSISDN	91XXXXXXXXXX

Request

```
{  
  "configId": "a73cd9ae-XXXX-XXXX-XXXX-7f73XXXX4064",  
  "to": "91XXXXXXXXXX"  
}
```

Success Response

```
{  
  "messageId": "35c035fc-XXXX-XXXX-XXXX-fbbd31b85307",  
  "verifyId": "40196bab-XXXX-XXXX-XXXX-39556a0ad8be",  
  "to": "91XXXXXXXXXX",  
  "configId": "a73cd9xe-XXXX-XXXX-XXXX-7f731bcf4y64",  
  "message": "Message Sent Successfully!",  
}
```

```
"error": null
}
```

Failed Response

```
{
  "error": true,
  "message": "Invalid API Key or Expired!"
}
```

Post Curl Request

```
curl --location 'https://api.aoc-portal.com/v1/verify/' \
--header 'apikey: 77cP0XXXXXXXXb8rcQBCXXXXXXXXA2tHKRc' \
--header 'Content-Type: application/json' \
--data '{
  "configId": " a73cd9xe-XXXX-XXXX-XXXX-7f731bcf4y64",
  "to": "91XXXXXXXXXXXX "
}'
```

2. Verify and validate generated OTP

Verify and validate **OTP Base URL**

<https://api.aoc-portal.com/v1/verify/validate>

Parameters and Variables:

The following table describes the parameters used in the SMS API request.

Headers

Name	Type	Description
Content-Type	String	application/json
apikey	String	API Key generated by panel.digimiles.in, i.e : <u>7cP0XXXXXXXXb8rcQBCXXXX</u> <u>XXA2tHKRc'</u>

Request Body

Attribute Name	Type	Required	Description	Sample Value
verifyId	String	Yes	The Verify ID which was sent in the Generate OTP API response..	a73cd9ae-XXXX-XXXX-XXXX-7f73XXXX4064

otp	String	Yes	One Time Password which was sent to the users to validate them.	XXXX
-----	--------	-----	---	------

Request

```
{
  "verifyId": "33888968-XXXX-XXXX-XXXX-3010e0069668",
  "otp": "XXXXXXX"
}
```

Success Response

```
{
  "data": "33888968-XXXX-XXXX-XXXX-3010e0069668",
  "error": null,
  "message": "OTP Verified Successfully!"
}
```

Failed Response

```
{
  "error": true,
  "message": "OTP has been Already Verified"
}
```

Post Curl Request

```
curl --location 'https://api.aoc-portal.com/v1/verify/validate' \
--header 'apikey: 77cP0XXXXXXXXb8rcQBCXXXXXXXXA2tHKRc' \
--header 'Content-Type: application/json' \
--data '{
  "verifyId": "33888968-XXXX-XXXX-XXXX-3010e0069668",
  "otp": "XXXXXXX"
}'
```