Optically Addressed, Scalable Acoustic Phase Matrix for Multimodal Matter and Sensory Stimulus Control

Proposed Title of the Invention

The invention is formally designated as the Optically Addressed, Scalable Acoustic Phase Matrix for Multimodal Matter and Sensory Stimulus Control.[1] In broader commercial and urban infrastructure contexts, particularly concerning its application in atmospheric remediation and autonomous vehicle support, the technology is alternatively identified as the Sonic Air Grid or the Sonic Visor.[1] This dual nomenclature reflects the system's inherent versatility, functioning both as a precision laboratory instrument for matter manipulation and as a large-scale environmental engineering solution for visibility enhancement.[1]

Area and Field of the Invention

The present invention is situated at the convergence of several highly specialized technical domains, including high-intensity acoustics, optoelectronics, and autonomous system sensor optimization.[1] Primarily, it falls within the field of airborne ultrasonic phased arrays used for mid-air haptic feedback and acoustic levitation.[3] However, its unique architectural reliance on optical control planes also places it within the realm of light-modulated signal processing and analog-computational metasurfaces.[2]

In the industrial sector, the invention pertains to micro-assembly and containerless processing, specifically targeting the manipulation of delicate components such as Micro-LEDs and Micro-Electro-Mechanical Systems (MEMS).[1] In the public infrastructure and safety domain, it addresses the technical requirements for "Hyper-Local Smog Clearance," leveraging acoustic agglomeration to restore the functional integrity of Advanced Driver Assistance Systems (ADAS) under hazardous environmental conditions.[1] Consequently, the invention is relevant to the automotive, pharmaceutical, semiconductor, and smart-city infrastructure industries.[1]

Technical Problem Solved

The development of the Sonic Air Grid addresses a series of critical bottlenecks that have hindered the transition of acoustic manipulation technology from controlled laboratory environments to large-scale industrial and urban applications.[1] Historically, the primary constraint in ultrasonic phased arrays has been the electrical addressing bottleneck.[2] Conventional phased arrays utilize electronically wired architectures where each individual transducer requires its own unique control channel for phase modulation.[1] As the size of these

arrays grows to achieve higher spatial resolution, the system's complexity increases exponentially, requiring thousands of individual wires, driver integrated circuits (ICs), and digital-to-analog converters (DACs).[1] This leads to prohibitive manufacturing costs, massive power consumption, and significant spatial constraints.[1]

Furthermore, the invention solves the fundamental physical limitation known as "acoustic collapse".[8] In typical acoustic levitation systems, particles suspended by sound interact via secondary scattering forces that are inherently attractive at close ranges.[6] This causes multiple levitated objects to merge into a single dense cluster, preventing the maintenance of complex multi-particle lattices or the independent manipulation of individual objects in proximity.[8]

In real-world operational environments, existing acoustic systems are frequently compromised by physical occlusions.[1] When a hand or a tool obstructs the acoustic wavefront, the pressure trap typically collapses, resulting in the loss of the levitated object or the failure of haptic feedback.[1] Existing systems are often "blind" to these environmental changes, lacking the real-time adaptive intelligence required to maintain stable operation during physical interference.[1]

Finally, the invention addresses the failure of autonomous sensors in dense particulate environments.[1] Standard ADAS components, such as Cameras and LiDAR, experience severe performance degradation in smog or fog, as high concentrations of PM2.5 particles scatter and absorb signal energy, rendering autonomous navigation unreliable.[1] The Sonic Air Grid provides a proactive solution to this by actively clearing the path rather than merely attempting to filter noisy sensor data.[1]

Novelty of the Invention

The novelty of the Sonic Air Grid is defined by its radical departure from the wired electronic paradigm that has characterized phased array transducers (PATs) for over half a century.[2] The primary novel feature is the Optically Programmable Acoustic Transducer (OPAT) architecture, which utilizes light-activated phase shifters (LAPS) to control the phase of each transducer element.[2] By replacing the individual electronic driver channels with a global RF excitation signal and an optical control plane, the invention enables $O(n)$ linear scaling, allowing for the creation of massive arrays without the associated wiring complexity.[1]

The invention further introduces the "Mermaid Potential," a novel hybrid electro-acoustic stabilization mechanism.[8] By combining acoustic radiation forces with controlled electrostatic repulsion, the system achieves a state of equilibrium that was previously unattainable in purely acoustic traps.[8] This allows for the stable levitation and manipulation of thousands of independent particles at a "cloud scale," a capability that distinguishes it from traditional "acoustic tweezers" which are limited to a small number of simultaneous traps.[1]

Additionally, the modular tiled architecture of the system is uniquely self-orienting and self-calibrating.[1] Independent tiles can synchronize via optical and acoustic signals to form a unified, industrial-scale surface without requiring centralized electronic coordination.[1] This modularity, combined with occlusion-adaptive operation—where the acoustic field is reconfigured in real-time to "bend" around obstacles—represents a paradigm shift in the robustness of acoustic manipulation technology.[1]

Inventive Step

The inventive step lies in the non-obvious convergence of optics, acoustics, and electrostatics to bypass established physical and electrical engineering limitations.[1] Traditional experts in acoustic manipulation have focused on optimizing digital focal laws and increasing the power of individual transducers.[4] The idea of using a projected light image as a high-bandwidth, wireless phase-control signal represents a significant cognitive leap, connecting two previously distinct domains of wave manipulation.[1] This allows the spatial resolution of the acoustic field to be governed by the resolution of the optical projector, enabling continuous analog phase control rather than discrete digital steps (e.g., 4-bit or 8-bit).[1]

The second inventive step involves the counterintuitive application of electrostatic charging to levitated matter.[8] While electrostatics are often viewed as a source of interference in clean-room manufacturing or aerosol science, the inventors have harnessed these forces to counteract the r^{-4} decay of acoustic scattering forces.[8] The mathematical realization that the r^{-2} decay of Coulombic repulsion can be tuned to dominate at the exact range where acoustic attraction leads to collapse is a fundamental breakthrough in many-particle physics.[8]

The following table contrasts the performance and architectural metrics of the present invention against conventional electronic phased arrays:

Metric	**Conventional Electronic PAT**	**Sonic Air Grid (Invention)**
Addressing Method	Individual Electronic Wiring ($O(n^2)$)	Optical Broadcast Addressing ($O(n)$) [1]
Phase Resolution	Discrete Digital (e.g., 4-8 bit)	Continuous Analog (Optical Intensity) [1]
Scalability Limit	Low (High cost/complexity	High (Modular, tiled

	bottleneck)	architecture) [1]
Multi-Particle Stability	Prone to "Acoustic Collapse"	Hybrid Electro-Acoustic Stability [1]
Environmental Adaptation	Static/Semi-static (fails at occlusion)	Occlusion-Adaptive Holography [1]
Operational Flexibility	Single-Mode (Haptics OR Levitation)	Multi-Modal (Frequency-Agnostic) [1]

Detailed Description of the Invention

The OPAT and LAPS Core Mechanisms

The heart of the invention is the Optically Programmable Acoustic Transducer (OPAT) array, which functions as a smart surface capable of synthesizing arbitrary 3D ultrasonic pressure fields.[2] The system utilizes a universal radio frequency (RF) generator that produces a continuous and uniform ultrasonic wave distributed to all transducers in the modular grid.[1] Unlike traditional systems that modulate this signal digitally, each tile in the Sonic Air Grid contains a series of Light-Activated Phase Shifters (LAPS).[2]

The LAPS circuitry is an analog network composed of photo-sensitive impedance devices—specifically photoresistors integrated into a dual-cascaded RC network.[2] When incident light from an optical projector strikes these elements, it alters their electrical impedance, which in turn shifts the phase of the RF signal driving the transducer.[5] By projecting a dynamic, grey-scale "phase hologram," the system can independently control the phase of every transducer in the array simultaneously.[1] This optoelectronic coupling allows the acoustic field to be updated at the refresh rate of the projector (e.g., 100 Hz), enabling rapid steering of focus points, the generation of acoustic vortices, and the projection of complex tactile textures.[2]

Hybrid Force Stabilization and the Mermaid Potential

To enable the manipulation of multiple objects without them clumping together, the invention incorporates a hybrid electro-acoustic level.[1] This layer consists of a clear electrical conductor (such as Indium Tin Oxide) and a particle charging device.[1] Suspended objects are imbued with evenly dispersed electric charges, inducing a state where they repel one another via Coulombic forces.[8]

The physics of this "Mermaid Potential" is governed by the balance of two primary forces:

1. **Acoustic Scattering Force (F_{sc}):** An attractive force that scales as $F_{sc} \propto -a^6 E_{ac} r^{-4}$, dominating at very short distances.[11]
2. **Electrostatic Repulsion (F_C):** A repulsive force that scales as $F_C = \frac{Q^2}{4\pi\epsilon_0 r^2}$, decaying more slowly and thus dominating at longer distances.[11]

By precisely controlling the charge Q and the acoustic energy density E_{ac}, the system can switch between "expanded" structures (where particles are separated) and "collapsed" structures (where they are in contact), or maintain hybrid configurations that are stable in mid-air.[8] This constitutes a degree of freedom entirely independent of the acoustic field shaping, allowing for the assembly of complex many-particle systems that evade the limitations of traditional standing-wave traps.[10]

Occlusion-Adaptive Holography and Environmental Intelligence

The invention integrates high-fidelity depth sensing and computer vision to monitor the operational space.[1] In a typical deployment, such as a mid-air haptic interface for a vehicle, the system must account for the presence of the user's hand, which inevitably blocks and scatters the ultrasonic waves.[1] The "Smart Brain" of the system—often an ESP32 or similar AI-capable controller—uses LiDAR backscatter analysis and RGB camera inputs to detect these occlusions in real-time.[1]

Upon detection, the system recomputes the phase hologram using a heterogeneous angular spectrum approach (HASA).[13] This adaptive algorithm redirects the acoustic energy around the obstruction, synthesizing a corrected pressure field that maintains the stability of the trap or the intensity of the haptic sensation.[1] This process is effectively a "soft-tissue" or "obstacle-aware" acoustic correction that mirrors the advanced wavefront engineering found in transcranial ultrasound or high-resolution AR displays.[12]

Acoustic Agglomeration for Atmospheric Remediation

When configured as the "Sonic Visor" for urban infrastructure, the grid is optimized for high-intensity acoustic clearing of PM2.5 particulates.[1] This application leverages the principle of acoustic agglomeration, where high-frequency sound waves (20 kHz to 40 kHz) induce rapid collisions among suspended aerosol particles.[1]

The process flow in this mode is as follows:

1. **Smog Detection:** IoT nodes monitor PM levels. When air quality degrades or visibility drops below 20 meters, the AI triggers a precise acoustic response.[1]
2. **Wave Activation:** The emitters, utilizing PZT-8 piezoelectric ceramics and stepped-plate radiators, generate alternating high- and low-pressure zones.[1]

3. **Agglomeration Mechanism:** The sound vibrations push small particles to move at different amplitudes and phases (orthokinetic and hydrodynamic interactions), causing them to collide and bond via Van der Waals forces.[1]
4. **Gravitational Settling:** Once the particles reach a threshold mass (e.g., PM10 or PM50), they are no longer buoyed by air currents and fall out of the breathing zone.[1]
5. **Final Collection:** The settled dust is subsequently removed from road surfaces by mechanical street sweepers, effectively purifying the hyper-local air column.[1]

Applications

The multimodal nature of the Sonic Air Grid allows it to serve a vast array of high-value applications across several sectors, ranging from micro-manufacturing to public safety infrastructure.[1]

Mid-Air Haptics and Non-Contact Interaction

The ability to project focused pressure gradients directly onto human skin enables a new generation of tactile interfaces.[1]

- **Automotive Control:** Creating virtual buttons and sliders in 3D space that provide "texture" and "click" feedback to drivers, allowing them to adjust settings without taking their eyes off the road.[1]
- **Sterile Public Interfaces:** Implementation in ATMs, ticket kiosks, and hospital displays to eliminate physical contact with surfaces, thereby reducing the transmission of pathogens.[1]
- **Augmented and Virtual Reality:** Providing realistic tactile sensations that synchronize with virtual objects, enhancing immersion in gaming and training simulations.[1]

Micro-Assembly and Precision Manufacturing

The invention provides a "soft," non-contact alternative to traditional robotic grippers, which often damage or contaminate micro-components.[1]

- **Semiconductor Handling:** Contactless pick-and-place manipulation of Micro-LEDs and MEMS components, ensuring micron-level positional accuracy without mechanical stress.[1]
- **Pharmaceutical Crystallization:** Levitating droplets and powders in a containerless environment to prevent heterogeneous nucleation, allowing for the production of high-purity crystalline structures.[1]
- **Biomedical Research:** Non-contact manipulation of biological samples, such as cell cultures, within standard labware, reducing the risk of mechanical damage or cross-contamination.[1]

Urban Visibility and Infrastructure Safety

The "Sonic Visor" implementation targets critical visibility issues in megacities like Delhi, where

smog and fog create severe safety hazards.[1]

- **ADAS and Autonomous Vehicle Support:** Restoring the reliability of LiDAR and cameras in hazardous visibility conditions by clearing a hyper-local path of particulates.[1]
- **Highway and Toll Plaza Safety:** Deploying fixed grid units at high-risk corridors and toll booths to prevent multi-vehicle pileups and traffic gridlocks during winter fog events.[1]
- **Aviation Visibility:** Mitigating flight delays at airports by dissipating dense fog and mist in the vicinity of runways and taxiing areas.[1]

Volumetric Displays and Data Visualization

By manipulating large arrays of levitated particles, the system can create dynamic, 3D physical shapes in mid-air.[1]

- **Physical Holography:** Generating interactive volumetric displays for educational, medical, and commercial purposes.[1]
- **3D Dynamic Signage:** Creating floating, moving icons or text for use in high-traffic commercial environments.[1]

Diagrams and Illustrations

The invention is supported by a series of technical drawings and process flowcharts that illustrate the synergy between its optical and acoustic components.[1]

System Layout and Operational Logic (Figure 1)

Figure 1 illustrates the fundamental architecture of the Sonic Air Grid.[1] It depicts the scalable acoustic phase matrix being addressed by a projected light source.[1] The visual representation highlights the modular tiles, each functioning as an independently addressable surface element.[1] The diagram shows the path of the universal RF signal as it is distributed to each tile and modulated by the optical phase hologram.[1] This illustration also captures the functional output of the grid, showing the generation of high-resolution acoustic fields capable of both haptic feedback and multi-particle levitation.[1]

Detailed Mechanics and Hybrid Stabilization (Figure 2)

Figure 2 focuses on the internal working of the invention, specifically the phase control and stabilization loops.[1] It details the LAPS photo-sensitive impedance devices and their role in translating grey-scale optical images into phase-shifted ultrasonic waves.[1] The drawing also includes the hybrid electro-acoustic level, showing the clear conductor layer and the electrostatic repulsion mechanism used to counteract acoustic collapse.[1] A crucial component of Figure 2 is the sensory feedback loop, illustrating how depth sensors detect occlusions and how the AI reconfigures the hologram to redirect energy.[1]

Smog Clearance and Agglomeration Process

The illustrations within the Sonic Visor documentation describe the transition from detection to clearing.[1]

- **Detection & Activation:** A process flowchart showing IoT nodes monitoring air opacity and triggering acoustic bursts from PZT-8 emitters.[1]
- **Acoustic Agglomeration Visuals:** Diagrams showing PM2.5 particles entering the ultrasonic field, vibrating, and bonding into larger PM50 clusters.[1]
- **Settling and Collection Schematic:** A visual of the gravitational settling of particles onto road dividers, leading to a "sweepable dust layer".[1]
- **Mini Chamber Prototype (Sky-Sweep):** A schematic of the demonstration chamber, showing the incense smoke source, the laser/LDR opacity detector, and the live pollution graph displayed on a Streamlit dashboard.[1]

Hardware and Performance Specifications

The efficacy of the Sonic Air Grid is contingent upon the use of advanced materials and high-precision electronic components.[1]

Transducer and Radiator Selection

The system utilizes PZT-8 piezoelectric ceramics for its transducers.[1] PZT-8 is a "hard" piezoceramic material favored for high-power resonant applications because of its high mechanical quality factor (Q_m).[18] Compared to PZT-4, which is often used for signal transmission and sensing, PZT-8 provides significantly better stability at high preloads and drive levels, which is critical for continuous-wave operation in atmospheric clearing.[25]

To maximize acoustic radiation efficiency in air, the system employs stepped-plate radiators.[1] These radiators are designed to compensate for discrete phase differences across the vibrating plate, enabling the projection of high-directional, high-intensity sound beams.[19] Titanium alloys are typically used for these radiators due to their high fatigue strength and favorable acoustic impedance matching.[27]

Sensing and Control Intelligence

The "Smart Brain" of the Sonic Air Grid is built around a modular architecture capable of processing environmental data and holographic computations in real-time.[1]

Feature	Specification / Requirement	Functional Implication

Primary Controller	ESP32 / High-performance IoT Node [1]	Low-latency processing of sensor data and AI logic.[1]
Acoustic Frequency	20 kHz to 40 kHz [1]	High enough for effective PM2.5 clearing; remains inaudible/less intrusive to humans.[1]
Sound Pressure Level	140 dB to 165 dB [20]	Threshold required for significant acoustic agglomeration in open environments.[1]
Detection Methods	LiDAR + RGB Camera + Laser/LDR [1]	Redundant sensing of particulate density and physical occlusions.[1]
Wait-Time (Residence)	2 to 8 seconds [28]	Time required for particles to undergo significant collision and growth.[28]
Clearing Efficiency	Up to 92.5% reduction in PM [20]	Proven effectiveness in industrial flue gas and ambient air tests.[20]

Safety and Environmental Impact

The Sonic Air Grid is designed to operate safely within urban and industrial environments, adhering to occupational health standards and ecological guidelines.[31]

Human Health and Noise Regulation

While the 20-40 kHz range is classified as ultrasound and is generally inaudible to humans, high-intensity sound can still present risks.[29] OSHA guidelines mandate a permissible exposure limit (PEL) of 90 dBA for an 8-hour workday, with an action level (AL) of 85 dBA.[31] The Sonic Air Grid mitigates excessive exposure through its intelligent logic, which only activates acoustic bursts when visibility is compromised.[1] Furthermore, the directional nature of the stepped-plate radiators ensures that the acoustic energy is focused precisely where it is needed—on the smog-clearing column or the haptic interface—minimizing "acoustic leakage" into surrounding areas.[19]

Ecological Impact and Animal Welfare

The auditory ranges of various urban species must be considered in the deployment of the Sonic Air Grid.[33]

- **Domestic Animals:** Dogs can hear up to 45 kHz, and cats up to 64 kHz.[29] Many dog whistles operate in the 23-54 kHz range.[29]
- **Urban Wildlife:** Mice and other rodents have high sensitivity in the 10-20 kHz range but also show secondary sensitivity at 50 kHz.[33] Bats utilize ultrasonic echolocation up to 200 kHz.[29]
- **Aquatic Life:** Research on ultrasonic algae control suggests that many fish and zooplankton species are generally unaffected by frequencies in the 20-40 kHz range, as their peak sensitivities are typically much lower.[29]

The invention's "targeted burst" strategy and real-time environmental monitoring ensure that high-intensity ultrasound is not a continuous pollutant, thereby minimizing the potential for anxiety or cardiovascular stress in urban animal populations.[1]

Conclusion and Future Outlook

The Optically Addressed, Scalable Acoustic Phase Matrix represents a transformative leap in wave-matter interaction technology.[1] By fundamentally decoupling the phase-control layer from the electrical wiring, the invention effectively resolves the scalability crisis that has plagued traditional phased array transducers for decades.[2] The integration of hybrid electro-acoustic stabilization through the Mermaid Potential expands the utility of acoustic levitation from simple point-trapping to complex, multi-particle assembly at an industrial scale.[8]

Furthermore, the technology's application as a Sonic Visor for atmospheric remediation offers a direct, proactive response to the urban visibility crises in regions like Delhi.[1] The ability to restore ADAS reliability and enhance highway safety through hyper-local smog clearance demonstrates the invention's capacity to integrate into the next generation of smart city infrastructure.[1] As the system moves from prototype to industrial implementation, its multimodal flexibility—allowing the same hardware to serve as a haptic interface, a micro-assembly tool, and an air purification grid—positions it as a cornerstone of 21st-century environmental and industrial engineering.[1]

Works cited

1. Sonic Visor final.docx
2. Optically Programmable Array of Transducers | Research Communities by Springer Nature, accessed on February 23, 2026, https://communities.springernature.com/posts/optically-programmable-array-of-transducers
3. Review of Progress in Acoustic Levitation - ResearchGate, accessed on February 23, 2026,

https://www.researchgate.net/publication/322143783_Review_of_Progress_in_Acoustic_Levitation
4. Phased array ultrasonics - Wikipedia, accessed on February 23, 2026, https://en.wikipedia.org/wiki/Phased_array_ultrasonics
5. (PDF) All-optically controlled phased-array for ultrasonics - ResearchGate, accessed on February 23, 2026, https://www.researchgate.net/publication/395032744_All-optically_controlled_phased-array_for_ultrasonics
6. Non-contact handling in microassembly: Acoustical levitation | Request PDF - ResearchGate, accessed on February 23, 2026, https://www.researchgate.net/publication/223824179_Non-contact_handling_in_microassembly_Acoustical_levitation
7. Agglomeration of particulate matter in chimneys using acoustic flow - PMC, accessed on February 23, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC10847651/
8. Electrostatics overcome acoustic collapse to assemble, adapt, and activate levitated matter | Request PDF - ResearchGate, accessed on February 23, 2026, https://www.researchgate.net/publication/393332970_Electrostatics_overcome_acoustic_collapse_to_assemble_adapt_and_activate_levitated_matter
9. Sue Shi's research works | Institute of Science and Technology Austria and other places, accessed on February 23, 2026, https://www.researchgate.net/scientific-contributions/Sue-Shi-2318008672
10. Electrostatics overcome acoustic collapse to assemble, adapt, and activate levitated matter - arXiv, accessed on February 23, 2026, https://arxiv.org/html/2507.01739v1
11. Electrostatics overcome acoustic collapse to assemble, adapt, and activate levitated matter | PNAS, accessed on February 23, 2026, https://www.pnas.org/doi/10.1073/pnas.2516865122
12. SNU researchers develop holographic AR display with enhanced realism via occlusion effect | EurekAlert!, accessed on February 23, 2026, https://www.eurekalert.org/news-releases/1105625
13. Acoustic Holography in the Megahertz Frequency Range with Optimal Lens Topologies and Nonlinear Acoustic Feedback - arXiv, accessed on February 23, 2026, https://arxiv.org/html/2508.07103v2
14. Introduction to phased array ultrasonic testing - Evident, accessed on February 23, 2026, https://ims.evidentscientific.com/en/learn/ndt-tutorials/intro/ut
15. (PDF) Real-time acoustic holography with physics-reinforced contrastive learning for acoustic field reconstruction - ResearchGate, accessed on February 23, 2026, https://www.researchgate.net/publication/377202362_Real-time_acoustic_holography_with_physics-reinforced_contrastive_learning_for_acoustic_field_reconstruction
16. Enhanced transcranial ultrasound transmission using acoustic double-negative metamaterials, accessed on February 23, 2026, https://www.jac.ac.cn/en/article/cstr/32049.14.11-2065.2025234
17. Ultrasonic aerosol agglomeration: Manipulation of particle deposition and its

impact on air filter pressure drop - DR-NTU, accessed on February 23, 2026, https://dr.ntu.edu.sg/server/api/core/bitstreams/19b98513-280e-4b26-8aed-8c498cabe2ff/content
18. (PDF) Performance of PZT8 Versus PZT4 Piezoceramic Materials in Ultrasonic Transducers, accessed on February 23, 2026, https://www.researchgate.net/publication/311938135_Performance_of_PZT8_Versus_PZT4_Piezoceramic_Materials_in_Ultrasonic_Transducers
19. Power Efficiency Calculation of Acoustic Energy Transmission by a Stepped-Plate Radiator, accessed on February 23, 2026, https://www.scirp.org/journal/paperinformation?paperid=75630
20. (PDF) Investigation of the acoustic agglomeration on ultrafine particles chamber built into the exhaust system of an internal combustion engine from renewable fuel mixture and diesel - ResearchGate, accessed on February 23, 2026, https://www.researchgate.net/publication/371154719_Investigation_of_the_acoustic_agglomeration_on_ultrafine_particles_chamber_built_into_the_exhaust_system_of_an_internal_combustion_engine_from_renewable_fuel_mixture_and_diesel
21. investigation of acoustic agglomeration efficiency using different working conditions of acoustic chamber - VILNIUS TECH Conferences, accessed on February 23, 2026, https://conferences.vilniustech.lt/index.php/ENVIRO/article/view/1261/1261
22. Ultrasonic aerosol agglomeration: Manipulation of particle deposition and its impact on air filter pressure drop - PMC, accessed on February 23, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC10832610/
23. Multifrequency ultrasonic transducer with stepped-plate disk - SciSpace, accessed on February 23, 2026, https://scispace.com/pdf/multifrequency-ultrasonic-transducer-with-stepped-plate-disk-2qukvxxgrm.pdf
24. Performance Of PZT8 Versus PZT4 Piezoceramic Materials In Ultrasonic Transducers, accessed on February 23, 2026, https://www.yhpiezo.com/aboutus/23253.html
25. Performance Of PZT8 Versus PZT4 Piezoceramic - Sino Sonics, accessed on February 23, 2026, https://www.sino-sonics.com/uncategorized/performance-of-pzt8-versus-pzt4-piezoceramic/
26. The Engineer's Guide to PZT-8: Choosing a High-Performance Hard Ceramic Manufacturer for Power Applications - Yujie Piezoelectric, accessed on February 23, 2026, https://yujiepiezo.com/blog/engineer-guide-pzt8-hard-ceramic-manufacturer-power-applications/
27. development of industrial models of high-power stepped-plate sonic and ultrasonic transducers for, accessed on February 23, 2026, http://www.yjcorp.co.kr/aaproduct/sonics/paper/deform_1.pdf
28. Ultrasonic agglomeration of fine particles emitted from heating facilities fired by solid biofuel - SSRN, accessed on February 23, 2026, https://papers.ssrn.com/sol3/Delivery.cfm/d05afffd-a131-4e6f-9173-f2675ee09ec

c-MECA.pdf?abstractid=5164651&mirid=1
29. Role and Outcomes of Ultrasound in Humans and Animals | Open Access Journals, accessed on February 23, 2026, https://www.rroij.com/open-access/role-and-outcomes-of-ultrasound-in-humans-and-animals.php?aid=91805
30. Influence of Acoustic Streams on the Efficiency of Ultrasonic Particle Agglomeration - MDPI, accessed on February 23, 2026, https://www.mdpi.com/2076-3417/14/2/559
31. Temporary Worker Initiative | Noise Exposure and Hearing Conservation - OSHA, accessed on February 23, 2026, https://www.osha.gov/sites/default/files/publications/OSHA3953.pdf
32. The Impact of Ultrasound on Animals in Water Treatment - LG Sonic, accessed on February 23, 2026, https://www.lgsonic.com/insights-the-impact-of-ultrasound-technology-on-animals/
33. Investigating audible and ultrasonic noise in modern animal facilities - PMC - NIH, accessed on February 23, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC9334837/
34. Occupational noise measurements - SVANTEK, accessed on February 23, 2026, https://svantek.com/applications/occupational-noise-measurements/
35. 1910.95 - Occupational noise exposure. | Occupational Safety and Health Administration - OSHA, accessed on February 23, 2026, https://www.osha.gov/laws-regs/regulations/standardnumber/1910/1910.95
36. Effects of Noise on Wildlife and Other Animals - epa nepis, accessed on February 23, 2026, https://nepis.epa.gov/Exe/ZyPURL.cgi?Dockey=9101NNCV.TXT
37. Investigating audible and ultrasonic noise in modern animal facilities - PubMed, accessed on February 23, 2026, https://pubmed.ncbi.nlm.nih.gov/35949916/