

Page 1 – Cover / Intro Page

College Name: Bharati Vidyapeeth College of Engineering,
Paschim Vihar

Department: Department of Applied Sciences

Subject: Circuit and System

Topic:

Submitted by: Vanshika Bansal

Dhruv kumar

Shivanshu Jha

Roll Number: 01411503024,90111503025,01511503024

Branch: ICE (Instrumentation and Control Engineering)

Date of Submission: 20/11/25

Submitted to: Mr. Manish Talwar

Temperature and Humidity Detector Report

1. Introduction

Temperature and humidity are two essential environmental parameters widely monitored in

industrial,

commercial, and domestic applications. A temperature and humidity detector is an electronic

system designed

to sense, measure, and display these atmospheric conditions. These systems are commonly used

in weather

monitoring stations, agricultural fields, laboratories, HVAC systems, and smart home applications.

The purpose of this report is to describe the working principle, components, circuit design,

methodology,

and applications of a temperature and humidity detector. This document outlines both hardware

and software

aspects to provide a complete understanding of the system.

2. Objective

The primary objective of this project is to design and study a temperature and humidity detector

capable of

manner.

accurately sensing environmental conditions and presenting the measured values in a user-friendly

Secondary objectives include:

- Understanding the working of temperature and humidity sensors such as DHT11, DHT22, or LM35 (temperature only).
- Developing a functional circuit using a microcontroller or basic electronic components.
- Displaying the measured values on an LCD or serial monitor.
- Analyzing the role of each hardware component in the overall system.

3. Components Used

1. Sensor Module:

- **DHT11/DHT22**: Combined temperature and humidity sensor.
- **LM35** (if used): Analog temperature sensor.

2. Controller:

- **Arduino Uno / ESP8266 / PIC / 8051** (depending on design).

3. Display Unit:

- **16x2 LCD** or **OLED Display**.

- #### 4. Power Supply:
- 5V regulated supply or USB.

5. Additional Components:

- Resistors
- Wires
- Breadboard
- PCB (optional).

4. Working Principle

The working of a temperature and humidity detector involves the following steps:

1. **Sensing the Environment**:

The DHT11/DHT22 sensor continuously monitors the temperature and humidity of the surrounding environment.

- Humidity is measured using a moisture-holding substrate.
- Temperature is measured using a thermistor or semiconductor-based sensing mechanism.

2. ****Signal Processing****:

The sensor internally processes raw data and sends digital output signals to the microcontroller.

3. ****Data Interpretation****:

The microcontroller reads the sensor output through a single-wire communication protocol. The

data packets

contain separate segments for temperature and humidity values.

4. ****Display/Output****:

The final processed readings are shown on a display such as a 16x2 LCD or printed on a serial

monitor.

In advanced systems, data logging and IoT-based cloud updates are also possible.

The detector provides real-time monitoring with an accuracy dependent on the type of sensor used.

5. Circuit Description

The circuit consists of the DHT sensor connected to the microcontroller.

The typical connections

are:

- VCC pin of the sensor $\square$ 5V

- GND pin □ Ground
- Data pin □ Digital Pin (e.g., D2 in Arduino)
- A 10kΩ pull-up resistor is usually added between the data and VCC pin for stable signal transmission.


The microcontroller runs a program that reads the digital output of the sensor and processes the timing-based signal.

An LCD is connected using either 4-bit or 8-bit mode to display temperature and humidity values.

6. Applications

Temperature and humidity detectors are used in various fields including:

- Smart homes and IoT monitoring
- Agricultural environment monitoring
- Greenhouse and soil moisture management
- Weather forecasting stations
- Cold storage and warehouse management
- Medical and laboratory monitoring systems
- HVAC systems



7. Advantages and Limitations

Advantages:

- Low-cost and easy to implement
- Accurate digital output
- Low power consumption
- Suitable for IoT applications

Limitations:

- DHT11 has lower accuracy compared to DHT22
- Slower sampling rate

- Not suitable for high-precision laboratory applications

8. Conclusion

The temperature and humidity detector is a highly useful system for environmental monitoring. By

integrating

provides

form

sensor modules with microcontrollers, accurate and real-time data can be obtained. The project

a practical understanding of sensors, circuits, microcontrollers, and display units. Such systems

the foundation of modern automation, IoT devices, and climate monitoring technologies.