An Interpretable Multi-Modal Spam Detection Framework Using Explainable AI and Machine Learning

Sonam Juneja
Computer Science and Engineering
Chandigarh University
Mohali, Punjab, India
sonam.december@gmail.com

Vanshit Kumar
Computer Science and Engineering
Chandigarh University
Mohali, Punjab, India
rubbervanshit@gmail.com

Aariz Amaan
Computer Science and Engineering
Chandigarh University
Mohali, Punjab, India
aarizamaan2006@gmail.com

Naman
Computer Science and Engineering
Chandigarh University
Mohali, Punjab, India
namanluthra70@gmail.com

Aditi Arya
Computer Science and Engineering
Chandigarh University
Mohali, Punjab, India
aryaaditi1511@gmail.com

Avish Kumar Dubey
Computer Science and Engineering
Chandigarh University
Mohali, Punjab, India
dubeyavish79@gmail.com

***Abstract*—Scam messages reach users through several channels, yet the machine-learning filters that intercept them usually return a verdict without a reason. We present an interpretable multi-modal framework that detects fraudulent SMS and e-mail messages and explains every decision. Each channel has a specialist pipeline that maps URLs, phone numbers and money amounts to readable placeholder tokens, combines TF–IDF features with fifteen stylometric statistics, and fuses Logistic Regression, Random Forest and XGBoost by F1-weighted soft voting; LIME explains the full ensemble and exact TreeSHAP the boosted component. On held-out splits of the UCI SMS Spam Collection and the Enron-Spam corpus, the ensemble reaches 98.55% accuracy (ROC-AUC 0.9941) on SMS and 98.25% (ROC-AUC 0.9983) on e-mail. Paired McNemar and DeLong tests show that it significantly outperforms both tree learners on e-mail ($p \leq 0.003$) and ties Logistic Regression, and a word-deletion test confirms that LIME's explanations are faithful. Global attributions show that stylometric features dominate SMS decisions and expose a corpus shortcut: the token `enron` occurs in 42% of legitimate test e-mails and in no spam, and appending it to spam e-mails flips 35.5% of the ensemble's detections (91.7% for XGBoost alone).**

***Index Terms*—Spam detection, smishing, phishing, explainable artificial intelligence, SHAP, LIME, ensemble learning, shortcut learning, stylometry.**

I. Introduction

Fraudulent messaging is the most frequently reported form of cybercrime: in 2025 the FBI's Internet Crime Complaint Center logged more than one million complaints and US$20.9 billion in losses, with phishing and spoofing again the largest category (191,561 complaints) [1]. Large language models (LLMs) now let attackers write persuasive, personalised phishing at negligible cost [2], [3], and scams have followed banking and one-time-password traffic onto SMS [4].

Most of this traffic is caught by machine-learning filters, yet these filters typically operate as black boxes: a message gets blocked, and no one can explain the reason. Strong accuracy figures may conceal shortcuts, spurious cues that happen to split the classes in a particular dataset [5]. Explainable AI (XAI) now provides a wide range of tools [6], but in spam filtering the explanations are usually presented as illustrations; they are rarely checked for faithfulness [7] or applied to audit the model itself. In addition, most detectors handle only one channel, even though SMS and e-mail are very different (in the corpora used here, the median length is 12 versus 155 words and the spam share is 12% versus 48%), and comparisons on nearly saturated benchmarks seldom report any uncertainty.

This paper tackles these gaps with an interpretable multi-modal framework, in which *modality* refers to the messaging channel (SMS or e-mail). Our contributions are:

1) a CPU-only pipeline with one specialist per channel: readable placeholder tokens, TF–IDF plus fifteen named stylometric features, and Logistic Regression (LR), Random Forest (RF) and XGBoost (XGB) fused by F1-weighted soft voting;
2) a statistically grounded evaluation with bootstrap confidence intervals, McNemar and DeLong tests, and an end-to-end evaluation of channel routing and cross-channel transfer;
3) a dual explanation layer (LIME for the full ensemble, exact TreeSHAP for XGBoost) whose faithfulness is tested by word deletion; and
4) an explanation-driven audit that uncovers and quantifies a corpus shortcut, and a sparse-versus-dense pitfall that silently invalidates SHAP explanations of XGBoost text models.

II. Related Work

SMS spam and smishing. Reproducible SMS research rests on the UCI SMS Spam Collection [8]. Recent detectors are mostly deep or transformer models, such as a smishing detector designed to reduce false positives [4] and a transformer detector with an explainability analysis [9]; Hur *et al.* found LLMs robust and effective for SMS spam [10]. Şahin *et al.* benchmarked classical learners across text representations on the same corpus and found the representation more decisive than classifier complexity [11]. Work on other languages such as Swahili is growing [12], and Salman *et al.* released a new dataset and analysed spammers' evasive techniques [13].

E-mail spam and phishing. The Enron-Spam corpus [14] remains a standard e-mail benchmark. Recent studies are dominated by fine-tuned transformers and LLMs [15]–[18]. Meléndez *et al.* reported that transformers beat traditional models on phishing e-mail, though only by a small margin [19], while ensembles built on meta-learners are still competitive [20]. Hadi *et al.* cover both channels using a hybrid of deep and shallow models [21]. LLMs are capable of producing convincing phishing messages at scale [2], and Opara *et al.* demonstrated that such messages slip past major webmail filters yet can still be detected using stylometric features [22].

Explainability and shortcuts. LIME builds a local surrogate model around a single prediction [23], whereas SHAP provides additive Shapley attributions [24], which TreeSHAP computes exactly for tree models [25]. Explanations have been attached to smishing detectors [26], [27], used to guide feature selection for spam [28], and compared across boosting models, where SHAP proved more stable at the global level than LIME [29]. Such explanations cannot simply be trusted: their faithfulness has to be measured [7], different explainers frequently disagree [30], and several challenges are still unresolved [6]. Shortcut learning, where a model exploits spurious cues in the dataset, is well known in NLP [5], [31], and spam corpora are especially exposed to it because the legitimate mail often originates from a single organisation.

Table I compares representative recent studies. The majority deal with one channel only and treat explanations mainly as illustrations. In contrast, we pair two channel specialists with a dual explanation layer, verify its faithfulness, employ it to audit the model, and compare the learners using paired significance tests.

III. Proposed Framework

Fig. 1 shows the architecture. A message is routed to the specialist of its channel; each specialist has its own normalisation, feature space and ensemble, and returns a label, a spam probability and explanations.

A. Normalisation and Features

Text is lower-cased, HTML tags are stripped, and high-signal entities are *mapped* rather than deleted: URLs become `httpaddr`, e-mail addresses `emailaddr`, currency amounts `moneysymb`, phone numbers `phonenumbr` and other numbers `numbr`. These are among the strongest scam signals, and as readable tokens they can appear in an explanation; no stemming is applied, so every explained token is a recognisable word. The text is vectorised with sublinear TF–IDF over uni- and bi-grams (3,000 terms with $\mathrm{df} \geq 2$ for SMS, 5,000 with $\mathrm{df} \geq 3$ for e-mail). Fifteen stylometric statistics are computed on the *raw* message (Table II), divided by their maximum on the training set and appended to the vector, yielding 3,015 and 5,015 dimensions; because their names are written in upper case, they remain clearly separate from vocabulary terms in every explanation.

B. Base Learners and Weighted Soft Voting

Three learners with different inductive biases provide diversity: LR (liblinear, $C = 1$) and RF [32] (250 trees, minimum leaf size 2) with balanced class weights, and XGBoost [33] (300 trees, depth 6, learning rate 0.1, subsampling 0.9/0.8) with $\mathrm{scale_pos_weight} = N_{\mathrm{ham}}/N_{\mathrm{spam}}$. Re-weighting was preferred to synthetic oversampling so that every training example remains a real, explainable message. The ensemble averages the learners' probabilities,

$$p(\mathrm{spam} \mid x) = \sum_{m=1}^{3} w_m \, p_m(\mathrm{spam} \mid x), \tag{1}$$

with w_m proportional to each learner's mean F1 in stratified 5-fold cross-validation on the training split, and predicts spam when $p \geq 0.5$. The resulting weights are 0.3329/0.3331/0.3340 (LR/RF/XGB) on SMS and 0.3356/0.3311/0.3333 on e-mail, so whatever gain the ensemble achieves stems from the diversity of its members rather than from any single dominant one.

C. Channel Router

A transparent rule selects the specialist: a message is treated as e-mail if it exceeds 280 characters, contains a line break or contains a cue word (*subject*, *dear*, *regards*, *sincerely*, *unsubscribe*, *attached*), and as SMS otherwise. Users can override the choice in the application.

D. Explanation Layer

LIME [23] removes words from the raw message, re-scores 1,000 perturbations through the *entire* pipeline and fits a local linear surrogate, so it explains the complete ensemble through its ten most influential words. For XGBoost, SHAP values decompose the log-odds output additively, $f(x) = \phi_0 + \sum_j \phi_j(x)$ [24], and are computed exactly by TreeSHAP [25]; global importance is the mean $|\phi_j|$ over 800 held-out messages. One implementation detail is critical: XGBoost treats entries absent from a sparse matrix as *missing*, whereas a densified copy turns them into zeros that follow different branches. Densifying the input before explaining therefore explains a different function: it changes the XGBoost verdict for 729 of 1,032 SMS and 1,182 of 2,400 e-mail test messages. Every attribution reported here is therefore obtained with XGBoost's built-in TreeSHAP, applied to the same sparse matrix that the model actually scores.

TABLE I
REPRESENTATIVE RECENT STUDIES COMPARED WITH THIS WORK

Study	Year	Channel	Approach	Explanation
Salman *et al.* [13]	2024	SMS	ML/DL models under evasive techniques; new dataset	–
Roumeliotis *et al.* [16]	2024	E-mail	Fine-tuned LLMs, NLP models and CNNs	–
Meléndez *et al.* [19]	2024	E-mail (phishing)	Traditional ML vs. transformers	–
Uddin *et al.* [9]	2025	SMS	Transformer language model	Post-hoc explainability analysis
Kshirsagar *et al.* [20]	2025	E-mail	Meta-learner ensembles	Interpretability-oriented
Uddin *et al.* [17]	2026	E-mail (phishing)	Fine-tuned transformer	Post-hoc explanations
Koide *et al.* [18]	2026	E-mail (phishing)	LLM-based detection	LLM-generated rationale
Jasim *et al.* [27]	2026	SMS	Fuzzy logic + BiLSTM	Fuzzy rules
Prince *et al.* [26]	2026	SMS (smishing)	Hybrid transformer feature fusion	Post-hoc XAI
Hadi *et al.* [21]	2026	SMS + e-mail (evaluated on SMS)	Shallow lexical + deep contextual features	–
This work	2026	SMS + e-mail (routed specialists)	TF–IDF + stylometry; LR, RF, XGB fused by F1-weighted soft voting	LIME (full ensemble) + exact TreeSHAP; deletion faithfulness test; shortcut audit




Fig. 1. Architecture of the proposed framework. Each channel has its own normalisation, feature space and ensemble; the explanation layer returns a local explanation with every verdict and global summaries of each model.

TABLE II
ENGINEERED STYLOMETRIC FEATURES (COMPUTED ON THE RAW MESSAGE)

Feature	Description
`CHAR_COUNT`, `WORD_COUNT`	Length in characters / words
`AVG_WORD_LEN`	Mean word length
`DIGIT_RATIO`	Share of characters that are digits
`UPPERCASE_RATIO`	Share of letters in upper case
`ALLCAPS_WORDS`	Words written fully in capitals
`PUNCT_RATIO`	Share of punctuation characters
`SPECIAL_CHAR_RATIO`	Share of non-alphanumeric characters
`NUM_EXCLAMATIONS`	Count of "!"
`NUM_QUESTIONS`	Count of "?"
`NUM_CURRENCY`	Currency symbols and money amounts
`NUM_URLS`, `NUM_EMAILS`	Detected links / e-mail addresses
`NUM_PHONES`	Detected phone numbers
`SPAM_KEYWORDS`	Hits in a 46-word, human-auditable scam lexicon

TABLE III
CORPORA AFTER CLEANING AND DE-DUPLICATION

Channel	Messages	Spam	Median words	Train	Test
SMS [8]	5,158	642 (12.4%)	12	4,126	1,032
E-mail [14]	12,000	5,792 (48.3%)	155	9,600	2,400

IV. EXPERIMENTAL SETUP

The UCI SMS Spam Collection [8] is used in full, and a class-stratified sample of 12,000 messages (subject and body) is drawn from the Enron-Spam corpus [14], after removing empty and duplicate messages (Table III). Each corpus is split 80/20 with stratification (seed 42); all fitting, including the cross-validated ensemble weights, uses the training split only, and the test split is used once. We report accuracy, precision, recall, F1, MCC, ROC-AUC, PR-AUC and the Brier score, with 95% bootstrap confidence intervals (2,000 resamples). The ensemble is compared with each base learner on the same messages using the exact McNemar test [34] and DeLong's test for correlated ROC curves [35], Holm-corrected within each channel.

We further evaluate (i) the router on the pooled test sets (3,432 messages) and each specialist on the other channel; (ii) LIME faithfulness, by deleting the top-k LIME words ($k \in \{1, 3, 5\}$) from 60 SMS and 25 e-mail correctly detected spam messages and comparing the drop in spam probability with that from deleting k random words; and (iii) the shortcut surfaced by the global attributions, by deleting the token from legitimate test e-mails and inserting it into spam. The framework is implemented in Python with scikit-learn, XGBoost, SHAP and LIME and served through a four-tab Streamlit application; a 13-check smoke test covers the whole pipeline, and re-running training reproduces all metrics exactly. Timings use a 10-core ARM64 CPU without a GPU.

TABLE IV
HELD-OUT TEST PERFORMANCE WITH 95% BOOTSTRAP CONFIDENCE INTERVALS (SMS: $n = 1{,}032$; E-MAIL: $n = 2{,}400$). LOWER BRIER IS BETTER.

Channel	Model	Accuracy	Precision	Recall	F1	MCC	ROC-AUC	PR-AUC	Brier
SMS	LR	0.9855 [.978, .992]	0.9520 [.911, .984]	0.9297 [.882, .970]	0.9407 [.910, .967]	0.9325 [.898, .963]	0.9941 [.989, .998]	0.9768 [.959, .992]	0.0148 [.011, .019]
	RF	0.9845 [.977, .991]	0.9516 [.905, .985]	0.9219 [.869, .965]	0.9365 [.902, .964]	0.9278 [.890, .959]	0.9929 [.985, .998]	0.9770 [.958, .992]	0.0184 [.015, .023]
	XGB	0.9845 [.977, .991]	0.9667 [.928, .992]	0.9062 [.849, .954]	0.9355 [.902, .963]	0.9273 [.890, .959]	0.9941 [.989, .998]	0.9739 [.954, .989]	0.0135 [.008, .021]
	Ensemble	**0.9855** [.978, .992]	**0.9669** [.929, .992]	**0.9141** [.860, .960]	**0.9398** [.907, .967]	**0.9320** [.895, .962]	**0.9941** [.988, .999]	**0.9790** [.961, .993]	**0.0130** [.009, .018]
E-mail	LR	0.9833 [.978, .988]	0.9753 [.966, .984]	0.9905 [.984, .996]	0.9829 [.978, .988]	0.9668 [.957, .977]	0.9979 [.997, .999]	0.9976 [.996, .999]	0.0210 [.018, .024]
	RF	0.9746 [.968, .980]	0.9629 [.951, .973]	0.9853 [.978, .992]	0.9740 [.967, .980]	0.9494 [.937, .961]	0.9973 [.996, .998]	0.9970 [.996, .998]	0.0380 [.035, .041]
	XGB	0.9750 [.969, .981]	0.9645 [.954, .975]	0.9845 [.977, .991]	0.9744 [.968, .981]	0.9502 [.938, .963]	0.9969 [.996, .998]	0.9965 [.995, .998]	0.0189 [.015, .023]
	Ensemble	**0.9825** [.977, .988]	**0.9705** [.961, .980]	**0.9940** [.989, .998]	**0.9821** [.977, .987]	**0.9652** [.955, .975]	**0.9983** [.997, .999]	**0.9980** [.997, .999]	**0.0213** [.019, .024]

TABLE V
PAIRED TESTS: ENSEMBLE VS. BASE LEARNERS. b/c: MESSAGES ONLY THE ENSEMBLE / ONLY THE BASE LEARNER CLASSIFIES CORRECTLY. p-VALUES HOLM-CORRECTED.

		McNemar		DeLong (ROC-AUC)		
Ch.	**Comparison**	b/c	p	ΔAUC	z	p
SMS	Ens. vs. LR	4/4	1.000	+0.0000	0.02	1.000
	Ens. vs. RF	2/1	1.000	+0.0012	1.15	0.754
	Ens. vs. XGB	1/0	1.000	-0.0000	-0.01	1.000
E-mail	Ens. vs. LR	11/13	0.839	+0.0004	1.26	0.208
	Ens. vs. RF	24/5	0.002	+0.0009	3.14	0.003
	Ens. vs. XGB	22/4	0.002	+0.0014	3.66	$<$0.001

TABLE VI
ROUTING AND CROSS-CHANNEL TRANSFER OF THE ENSEMBLES (POOLED TEST SET: 3,432 MESSAGES)

Setting	Acc.	F1	MCC	AUC	FPR
Oracle routing (pooled)	0.9834	0.9780	0.9648	0.9978	0.0182
Automatic routing (pooled)	0.9216	0.8921	0.8317	0.9687	0.0443
SMS model $\rightarrow$ e-mail test	0.5208	0.5287	0.0442	0.5290	0.5129
E-mail model $\rightarrow$ SMS test	0.2209	0.2299	0.0594	0.6707	0.8805

V. RESULTS

A. Classification Performance and Significance

Table IV and Fig. 2 report all four systems. On SMS the ensemble reaches 98.55% accuracy with the highest precision (0.9669), only 4 false positives among 904 legitimate messages and the best PR-AUC and Brier score; on e-mail it reaches 98.25% with the highest recall (0.9940; 7 of 1,158 spam messages missed) and ROC-AUC (0.9983). The SMS specialist favours precision, which suits a channel where a blocked message may be a one-time password; the e-mail specialist favours recall. LR is a strong baseline: it matches the ensemble's SMS accuracy and slightly exceeds its SMS F1 and e-mail accuracy.

The paired tests (Table V) resolve these small differences. On SMS none is significant. On e-mail the ensemble beats both tree models (McNemar: 24 vs. 5 discordant messages against RF and 22 vs. 4 against XGB, $p = 0.002$; DeLong $p \leq 0.003$) but is statistically indistinguishable from LR (11 vs. 13, $p = 0.84$).

B. Routing and Cross-Channel Transfer

The specialists do not transfer (Table VI): the SMS model is at chance on e-mail (ROC-AUC 0.53), and the e-mail model flags 88% of legitimate SMS as spam. The router sends 96.4% of SMS and 85.1% of e-mails to the right specialist, but misrouted e-mails (short, without cue words) are classified correctly only 42.3% of the time, so pooled accuracy falls from 98.34% with oracle routing to 92.16% with automatic routing. The heuristic router, not the classifiers, is the weakest component, hence the manual override.

C. Local and Global Explanations

Fig. 3 explains an illustrative smishing SMS written by the authors and absent from both corpora: "URGENT! You have WON a £2,000 cash prize GUARANTEED. Call 09061701461 now or visit www.claim-your-prize.com to claim!" All learners vote spam (ensemble 0.996). LIME ranks the premium-rate number highest, followed by the money amount and scam vocabulary; TreeSHAP attributes the decision mainly to stylometry (digit ratio, word length, lexicon hits, capitals) and the `httpaddr` and `phonenumbr` placeholders. LIME speaks in the user's words, SHAP in the model's features.

Globally (Fig. 4), eight of the ten most important SMS features are stylometric, and the fifteen engineered features (0.5% of the dimensions) carry 74.5% of the attribution mass: a short scam is betrayed by its *shape* as much as by its words. On e-mail a single word, `enron`, dominates with about three times the attribution of the next feature.

D. Faithfulness of the Local Explanations

On SMS, deleting the top LIME word lowers the ensemble's spam probability 8.6 times more than deleting a random word (Table VII); deleting the top five lowers it by 0.455 and flips 52% of the verdicts. E-mail drops are smaller in absolute terms, because long messages contain redundant evidence, but






Fig. 2. ROC curves of the four systems on the held-out SMS (left) and e-mail (right) test sets. All systems exceed 0.99 AUC; differences are resolved by the paired tests in Table V.



(a) LIME weight towards spam (full ensemble)

(b) Exact TreeSHAP contribution to XGBoost log-odds

Fig. 3. Local explanations of the illustrative smishing SMS (ensemble spam probability 0.996): (a) LIME weights over the full ensemble; (b) the ten largest exact TreeSHAP contributions of the XGBoost component (base value 0.50 log-odds). Upper-case names are stylometric features.



(a) SMS: mean $|\phi_j|$ (log-odds)

(b) E-mail: mean $|\phi_j|$ (log-odds)

Fig. 4. Global importance (exact TreeSHAP, XGBoost component, 800 held-out messages per channel): the ten most important features for (a) SMS and (b) e-mail.

TABLE VII
DELETION TEST OF LIME FAITHFULNESS: MEAN DROP IN ENSEMBLE SPAM PROBABILITY AFTER REMOVING THE TOP-k LIME WORDS / k RANDOM WORDS

Channel	$k=1$	$k=3$	$k=5$	**Flips** (k=5)
SMS ($n=60$)	0.106 / 0.012	0.291 / 0.043	0.455 / 0.081	52%
E-mail ($n=25$)	0.043 / 0.002	0.133 / 0.005	0.198 / 0.010	24%

about 20 times larger than random. LIME therefore points at words on which the decision genuinely depends.

E. Explanations as an Audit Tool: A Corpus Shortcut

The token `enron` appears in 44.4% of the legitimate training e-mails and 42.1% of the legitimate test e-mails, but never in spam: since all legitimate messages are internal Enron correspondence, the company name acts as a one-sided proxy for ham. Its average TreeSHAP contribution is -3.95 log-odds when the token is present and $+0.66$ when it is absent; other identity cues, such as the first name *vince*, also rank near the top, and the token does not appear in any of the ensemble's 35 false positives. Table VIII puts a number on the risk. Removing the token from 523 legitimate e-mails changes only 11 verdicts, whereas *adding* this one word to spam messages overturns 409 of 1,151 detections (35.5%). XGBoost alone is evaded on 91.7% of messages, RF on 25.3% and LR on 4.5%, so the heterogeneous ensemble is far more robust than its boosted member, yet not immune. The shortcut is invisible in Tables IV and V; only the explanations revealed it.

TABLE VIII
SHORTCUT PROBE ON THE E-MAIL TEST SET: INSERTING "ENRON" INTO DETECTED SPAM AND DELETING IT FROM LEGITIMATE MAIL

	Insertion into spam		Deletion from ham	
Model	**Flips to ham**	$\overline{\Delta p}$	**Flips**	$\overline{\Delta p}$
LR	52/1147 (4.5%)	-0.066	2/523	+0.032
RF	289/1141 (25.3%)	-0.301	10/523	+0.053
XGB	1045/1140 (91.7%)	-0.763	19/523	+0.052
Ensemble	409/1151 (35.5%)	-0.376	11/523	+0.046

TABLE IX
COMPUTATIONAL COST ON A 10-CORE ARM64 CPU (NO GPU)

Channel	**Train** (s)	**Verdict** (ms)	**Batch** (msg/s)	**SHAP** (ms)	**LIME** (ms)
SMS	14.3	14.7	14,897	0.86	76
E-mail	76.8	14.8	1,967	0.75	210

F. Computational Cost

Training both specialists, including cross-validation, takes about 1.5 minutes on a CPU (Table IX). A verdict takes about 15 ms, a TreeSHAP attribution under 1 ms and a LIME explanation 0.08–0.21 s, so every prediction can be explained interactively.

VI. DISCUSSION AND LIMITATIONS

Every learner reaches more than 97% accuracy, and a regularised linear model trained on well-designed features matches the ensemble's accuracy, which agrees with the observation that, for SMS spam, the representation matters more than the complexity of the classifier [11]. What the ensemble adds is stronger ranking metrics, a precision-first profile on SMS, significant improvements over both tree models on e-mail and, most importantly, resistance to the shortcut attack. The `enron` shortcut belongs to the corpus rather than to the pipeline, but a black-box deployment would have shipped it without anyone noticing. Global explanations are therefore an auditing instrument, but they must themselves be validated [7]: the sparse/dense pitfall yields plausible SHAP plots of a function the deployed model never computes. We recommend computing tree attributions on the exact input the model scores, validating explanations by deletion, screening global attributions for corpus identifiers, and evaluating routing as well as classification.

The corpora are English and date from 2000–2012, so modern and code-mixed smishing and LLM-generated phishing [22] are not covered, and the shortcut means e-mail accuracy overstates performance on other organisations' mail. Results come from one stratified split, the router is heuristic, SHAP covers only the boosted component, and neither transformer or LLM detectors nor adversarial obfuscation [13] were evaluated.

VII. CONCLUSION

We presented an interpretable multi-modal framework that detects scam SMS and e-mail with channel-specific ensembles of LR, RF and XGBoost and explains every verdict with LIME and exact TreeSHAP. It reaches 98.55% (SMS) and 98.25% (e-mail) accuracy, significantly outperforms both tree learners on e-mail and trains in minutes on a CPU. Its explanations are faithful, show that stylometry rivals vocabulary on SMS, and exposed a corpus shortcut that a one-word insertion can exploit. Future work will test cross-corpus generalisation and remove identity shortcuts, extend the framework to multilingual and code-mixed data including Indian languages, learn the router, and benchmark transformer and LLM detectors under the same protocol.

REFERENCES

[1] Federal Bureau of Investigation, "Internet Crime Report 2025," Internet Crime Complaint Center (IC3), Washington, DC, USA, Tech. Rep., Apr. 2026, [Online]. Available: https://www.ic3.gov/AnnualReport/Reports/2025_IC3Report.pdf.

[2] F. Heiding, B. Schneier, A. Vishwanath, J. Bernstein, and P. S. Park, "Devising and detecting phishing emails using large language models," *IEEE Access*, vol. 12, pp. 42 131–42 146, 2024, doi: 10.1109/ACCESS.2024.3375882.

[3] Y. Yao, J. Duan, K. Xu, Y. Cai, Z. Sun, and Y. Zhang, "A survey on large language model (LLM) security and privacy: The good, the bad, and the ugly," *High-Confidence Computing*, vol. 4, no. 2, Jun. 2024, art. no. 100211, doi: 10.1016/j.hcc.2024.100211.

[4] M. K. Mehmood, H. Arshad, M. Alawida, and A. Mehmood, "Enhancing smishing detection: A deep learning approach for improved accuracy and reduced false positives," *IEEE Access*, vol. 12, pp. 137 176–137 193, 2024, doi: 10.1109/ACCESS.2024.3463871.

[5] M. Du, F. He, N. Zou, D. Tao, and X. Hu, "Shortcut learning of large language models in natural language understanding," *Communications of the ACM*, vol. 67, no. 1, pp. 110–120, Jan. 2024, doi: 10.1145/3596490.

[6] L. Longo *et al.*, "Explainable artificial intelligence (XAI) 2.0: A manifesto of open challenges and interdisciplinary research directions," *Information Fusion*, vol. 106, Jun. 2024, art. no. 102301, doi: 10.1016/j.inffus.2024.102301.

[7] Q. Lyu, M. Apidianaki, and C. Callison-Burch, "Towards faithful model explanation in NLP: A survey," *Computational Linguistics*, vol. 50, no. 2, pp. 657–723, Jun. 2024, doi: 10.1162/coli_a_00511.

[8] T. A. Almeida, J. M. G. Hidalgo, and A. Yamakami, "Contributions to the study of SMS spam filtering: New collection and results," in *Proc. 11th ACM Symp. Document Engineering (DocEng)*, Mountain View, CA, USA, 2011, pp. 259–262, doi: 10.1145/2034691.2034742.

[9] M. A. Uddin, M. N. Islam, L. Maglaras, H. Janicke, and I. H. Sarker, "ExplainableDetector: Exploring transformer-based language modeling approach for SMS spam detection with explainability analysis," *Digital Communications and Networks*, vol. 11, no. 5, pp. 1504–1518, Oct. 2025, doi: 10.1016/j.dcan.2025.07.008.

[10] M. Hur, S. Seo, J. Hwang, and M. Min, "Are large language models effective for detecting spam messages?" *International Journal of Information Security*, vol. 25, no. 4, Jul. 2026, art. no. 127, doi: 10.1007/s10207-026-01283-5.

[11] M. S. Şahin, D. Özkan Şahin, and A. F. Salah, "Revisiting SMS spam detection: The impact of feature representation on classical machine learning models," *Electronics*, vol. 15, no. 4, Feb. 2026, art. no. 894, doi: 10.3390/electronics15040894.

[12] I. S. Mambina, J. D. Ndibwile, D. Uwimpuhwe, and K. F. Michael, "Uncovering SMS spam in Swahili text using deep learning approaches," *IEEE Access*, vol. 12, pp. 25 164–25 175, 2024, doi: 10.1109/ACCESS.2024.3365193.

[13] M. Salman, M. Ikram, and M. A. Kaafar, "Investigating evasive techniques in SMS spam filtering: A comparative analysis of machine learning models," *IEEE Access*, vol. 12, pp. 24 306–24 324, 2024, doi: 10.1109/ACCESS.2024.3364671.

[14] V. Metsis, I. Androutsopoulos, and G. Paliouras, "Spam filtering with naive Bayes—which naive Bayes?" in *Proc. 3rd Conf. Email and Anti-Spam (CEAS)*, Mountain View, CA, USA, 2006.

[15] S. Jamal, H. Wimmer, and I. H. Sarker, "An improved transformer-based model for detecting phishing, spam and ham emails: A large language model approach," *SECURITY AND PRIVACY*, vol. 7, no. 5, Sep. 2024, art. no. e402, doi: 10.1002/spy2.402.

[16] K. I. Roumeliotis, N. D. Tselikas, and D. K. Nasiopoulos, "Next-generation spam filtering: Comparative fine-tuning of LLMs, NLPs, and CNN models for email spam classification," *Electronics*, vol. 13, no. 11, May 2024, art. no. 2034, doi: 10.3390/electronics13112034.

[17] M. A. Uddin, M. Mahiuddin, and I. H. Sarker, "An explainable transformer-based model for phishing email detection: A large language model approach," *Computer Networks*, vol. 277, Mar. 2026, art. no. 112061, doi: 10.1016/j.comnet.2026.112061.

[18] T. Koide, H. Nakano, and D. Chiba, "ChatSpamDetector: Large language model-based phishing email detection," *IEEE Access*, vol. 14, pp. 93 498–93 514, 2026, doi: 10.1109/ACCESS.2026.3704566.

[19] R. Meléndez, M. Ptaszynski, and F. Masui, "Comparative investigation of traditional machine-learning models and transformer models for phishing email detection," *Electronics*, vol. 13, no. 24, Dec. 2024, art. no. 4877, doi: 10.3390/electronics13244877.

[20] M. Kshirsagar, V. Rathi, and C. Ryan, "Meta-learner-based frameworks for interpretable email spam detection," *Frontiers in Artificial Intelligence*, vol. 8, Oct. 2025, art. no. 1569804, doi: 10.3389/frai.2025.1569804.

[21] A. Hadi, M. Mosleh, and K. Mohebbi, "Improved detection of email and SMS spam using a hybrid deep and shallow learning model," *Scientific Reports*, vol. 16, no. 1, Oct. 2026, art. no. 33674, doi: 10.1038/s41598-026-74463-x.

[22] C. Opara, P. Modesti, and L. Golightly, "Evaluating spam filters and stylometric detection of AI-generated phishing emails," *Expert Systems with Applications*, vol. 276, Jun. 2025, art. no. 127044, doi: 10.1016/j.eswa.2025.127044.

[23] M. T. Ribeiro, S. Singh, and C. Guestrin, ""Why should I trust you?": Explaining the predictions of any classifier," in *Proc. 22nd ACM SIGKDD Int. Conf. Knowledge Discovery and Data Mining (KDD)*, San Francisco, CA, USA, 2016, pp. 1135–1144, doi: 10.1145/2939672.2939778.

[24] S. M. Lundberg and S.-I. Lee, "A unified approach to interpreting model predictions," in *Proc. Advances in Neural Information Processing Systems (NeurIPS)*, vol. 30, 2017, pp. 4765–4774.

[25] S. M. Lundberg *et al.*, "From local explanations to global understanding with explainable AI for trees," *Nature Machine Intelligence*, vol. 2, no. 1, pp. 56–67, 2020, doi: 10.1038/s42256-019-0138-9.

[26] M. A. H. Prince, G. M. S. Hossain, T. Mahmud, M. A. Rahman, M. S. Hossain, and K. Andersson, "An explainable hybrid transformer-based feature fusion approach for smishing detection in cybersecurity," *IEEE Access*, vol. 14, pp. 106 124–106 147, 2026, doi: 10.1109/ACCESS.2026.3712173.

[27] A. kadhim Jasim, F. A. Al-Ibraheemi, and H. A. Alkaabi, "Explainable AI for SMS spam filtering: A novel hybrid architecture combining fuzzy logic and bidirectional LSTM networks," *Franklin Open*, vol. 14, Mar. 2026, art. no. 100466, doi: 10.1016/j.fraope.2025.100466.

[28] Q. Shambour, M. Al-Zyoud, and O. Almomani, "Quantum-inspired hybrid metaheuristic feature selection with SHAP for optimized and explainable spam detection," *Symmetry*, vol. 17, no. 10, Oct. 2025, art. no. 1716, doi: 10.3390/sym17101716.

[29] S. Panthi, M. Patidar, K. Zalawadia, D. Vekariya, and V. Vekariya, "A performance analysis of SHAP and LIME for interpreting boosting models in phishing URL detection," *Scientific Reports*, vol. 16, no. 1, Aug. 2026, art. no. 33730, doi: 10.1038/s41598-026-66800-x.

[30] S. Krishna, T. Han, A. Gu, S. Wu, S. Jabbari, and H. Lakkaraju, "The disagreement problem in explainable machine learning: A practitioner's perspective," *Transactions on Machine Learning Research*, 2024.

[31] V. Dogra, S. Verma, Kavita, M. Woźniak, J. Shafi, and M. F. Ijaz, "Shortcut learning explanations for deep natural language processing: A survey on dataset biases," *IEEE Access*, vol. 12, pp. 26 183–26 195, 2024, doi: 10.1109/ACCESS.2024.3360306.

[32] L. Breiman, "Random forests," *Machine Learning*, vol. 45, no. 1, pp. 5–32, 2001, doi: 10.1023/A:1010933404324.

[33] T. Chen and C. Guestrin, "XGBoost: A scalable tree boosting system," in *Proc. 22nd ACM SIGKDD Int. Conf. Knowledge Discovery and Data Mining (KDD)*, San Francisco, CA, USA, 2016, pp. 785–794, doi: 10.1145/2939672.2939785.

[34] Q. McNemar, "Note on the sampling error of the difference between correlated proportions or percentages," *Psychometrika*, vol. 12, no. 2, pp. 153–157, 1947, doi: 10.1007/BF02295996.

[35] E. R. DeLong, D. M. DeLong, and D. L. Clarke-Pearson, "Comparing the areas under two or more correlated receiver operating characteristic curves: A nonparametric approach," *Biometrics*, vol. 44, no. 3, pp. 837–845, 1988, doi: 10.2307/2531595.