

POORNIMA COLLEGE OF ENGINEERING

Nutshell of Samfling and Quantigation

Sonner Senner Digitize Photograph Hard disk you can process

Sampling + Quantisation = Digitisation

Image - 20 9 x onch & y and Jory)

20-ordinate &

Sampling - x-axis Quantization -> Y- axis amplitude



FOORIVIT COLLEGE OF ENGINEERIN

DETAILED LECTURE NOTES


Sampling & Chantisation

- mostly the output of image sensors is in the John of analog signal. This is due to the fact that we on not releatify analog signal. In Digital smage procentry signal aptured from the real word need to be translated just digital formules "Disitisation" procen.


-) I digital image f(x,y) consists of (oordinates & and

y Additionally it contains the function amplitude.

Quantization oregen to digitizing the amplitude, while sampling oregen to digitizing the word hate Value.




Ontinous image Digital smage



nono Chrone, grayscel image and color image.

The pixel value of binary image at specific location usually holds the value of for black or 1 for white.



ed world trops and permutation doston a L - vest Amions to as an amognet neng enful Ser. for Livere rool original distited Analog Image (Actual image (Pibital Image has a is continous) finite of pixels and levels) Samp ling

and permutation dorm



POORNIMA COLLEGE OF ENGINEERING

DETAILED LECTURE NOTES

E CO

Sumpling and Quantisation - Base term

A OIP sensor - Continous vy

I (convert -) (continous semed data -) digital form

Hnough digitizing.


I mage I (ontinous -) of & y

L) Amplitude


1 Digital form - Sample - x cy Li Amplitude

-> Digitising (o-ordinate Values Called Values
Sampling

Digitising Amplitude Value (alled autisation



(a) Grenerating a digital



(6) Confinuous Pmage

Sampling L Quantization (d) digital

(a) contineous mage

Digitized image (b) after Sampling and Quantization