vboxuser@VM-1: ~ — nano file22.sh

```
 GNU nano 8.7.1                                file22.sh
#!/bin/bash

for file in "$@"
do
    upper=$(echo "$file" | tr '[:lower:]' '[:upper:]')
    mv "$file" "$upper"
done
```

vboxuser@VM-1: ~

```
vboxuser@VM-1:~$ nano 20.sh
vboxuser@VM-1:~$ bash 20.sh Linus
Linus does not exist
vboxuser@VM-1:~$ ls
20.sh      Downloads  Public     file.sh     file111.txt    file4.txt  file8.sh  snap
21.sh      HELLO.TXT  Templates  file.txt    file2.sh       file5.sh   file9.sh  test.txt
24.sh      Linus.txt  Turner     file1.sh    file2.sh.save  file5.txt  for.sh    test0.txt
DATA.TXT   Music      Videos     file1.txt   file2.txt      file6.txt  home      who.txt
Desktop    NOTES.TXT  clear      file11.sh   file22.sh      file7.sh   home.txt
Documents  Pictures   exp3a.sh   file111.sh  file3.sh       file7.txt  name.txt
vboxuser@VM-1:~$ bash 20.sh Documents
Documents is a directory
vboxuser@VM-1:~$ bash 20.sh Turner
Turner is a file
vboxuser@VM-1:~$
```

vboxuser@VM-1: ~ — nano 20.sh

```
 GNU nano 8.7.1                                  20.sh
#!/bin/bash

if [ -f "$1" ]
then
    echo "$1 is a file"
elif [ -d "$1" ]
then
    echo "$1 is a directory"
else
    echo "$1 does not exist"
fi
```

vboxuser@VM-1: ~

```
vboxuser@VM-1:~$ cat hello.txt
Hello World
vboxuser@VM-1:~$ cat notes.txt
These are my notes
vboxuser@VM-1:~$ cat data.txt
This is sample data
vboxuser@VM-1:~$ bash file22.sh hello.txt notes.txt data.txt
vboxuser@VM-1:~$ ls
20.sh      Downloads  Pictures   exp3a.sh   file111.sh     file3.sh   file7.txt  name.txt
21.sh      HELLO.TXT  Public     file.sh    file111.txt    file4.txt  file8.sh   snap
24.sh      Hello      Templates  file.txt   file2.sh       file5.sh   file9.sh   test.txt
DATA.TXT   Linus.txt  Turner     file1.sh   file2.sh.save  file5.txt  for.sh     test0.txt
Desktop    Music      Videos     file1.txt  file2.txt      file6.txt  home       who.txt
Documents  NOTES.TXT  clear      file11.sh  file22.sh      file7.sh   home.txt
vboxuser@VM-1:~$
```