# DATASET: **COMPANYDB**

## Table1:Employees

Description->

```
mysql> create database labwork;
Query OK, 1 row affected (0.03 sec)

mysql> use labwork;
Database changed
mysql> use labwork;
Database changed
mysql>  create table Employee(emp_id varchar(20) Primary Key,emp_name varchar(20) NOT NULL,dept_id varchar(15) NOT NULL,salary int NOT NULL,hire_date date N
OT NULL, city char(20) NOT NULL);
Query OK, 0 rows affected (0.06 sec)

mysql> desc Employee;
+-----------+-------------+------+-----+---------+-------+
| Field     | Type        | Null | Key | Default | Extra |
+-----------+-------------+------+-----+---------+-------+
| emp_id    | varchar(20) | NO   | PRI | NULL    |       |
| emp_name  | varchar(20) | NO   |     | NULL    |       |
| dept_id   | varchar(15) | NO   |     | NULL    |       |
| salary    | int         | NO   |     | NULL    |       |
| hire_date | date        | NO   |     | NULL    |       |
| city      | char(20)    | NO   |     | NULL    |       |
+-----------+-------------+------+-----+---------+-------+
6 rows in set (0.01 sec)

mysql> |
```

Insert_Data->

```
mysql> INSERT INTO Employee VALUES(101,'Anuj',1,50000,'2022-01-10','Delhi'),(102,'Ravi',2,60000,'2021-03-15','Mumbai'),(103,'Neha',1,55000,'2020-07-20','Del
hi'),(104,'Amit',3,70000,'2019-11-01','Pune'),(105,'Sneha',2,65000,'2023-05-12','Mumbai'),(106,'Karan',3,72000,'2018-08-25','Bangalore'),(107,'Pooja',1,4800
0,'2022-09-30','Delhi'),(108,'Raj',2,52000,'2021-12-11','Chennai'),(109,'Meena',3,68000,'2020-02-14','Pune'),(110,'Vikas',1,51000,'2023-01-18','Delhi');
Query OK, 10 rows affected (0.04 sec)
Records: 10  Duplicates: 0  Warnings: 0

mysql> select* from Employee;
+--------+----------+---------+--------+------------+-----------+
| emp_id | emp_name | dept_id | salary | hire_date  | city      |
+--------+----------+---------+--------+------------+-----------+
| 101    | Anuj     | 1       |  50000 | 2022-01-10 | Delhi     |
| 102    | Ravi     | 2       |  60000 | 2021-03-15 | Mumbai    |
| 103    | Neha     | 1       |  55000 | 2020-07-20 | Delhi     |
| 104    | Amit     | 3       |  70000 | 2019-11-01 | Pune      |
| 105    | Sneha    | 2       |  65000 | 2023-05-12 | Mumbai    |
| 106    | Karan    | 3       |  72000 | 2018-08-25 | Bangalore |
| 107    | Pooja    | 1       |  48000 | 2022-09-30 | Delhi     |
| 108    | Raj      | 2       |  52000 | 2021-12-11 | Chennai   |
| 109    | Meena    | 3       |  68000 | 2020-02-14 | Pune      |
| 110    | Vikas    | 1       |  51000 | 2023-01-18 | Delhi     |
+--------+----------+---------+--------+------------+-----------+
10 rows in set (0.00 sec)
```

## Table2:Departments

Description->

```
mysql> create table Departments(dept_id INT PRIMARY KEY,dept_name varchar(20) NOT NULL);
Query OK, 0 rows affected (0.06 sec)

mysql> desc Departments;
+-----------+-------------+------+-----+---------+-------+
| Field     | Type        | Null | Key | Default | Extra |
+-----------+-------------+------+-----+---------+-------+
| dept_id   | int         | NO   | PRI | NULL    |       |
| dept_name | varchar(20) | NO   |     | NULL    |       |
+-----------+-------------+------+-----+---------+-------+
2 rows in set (0.03 sec)
```

Insert_Data->

```
mysql> INSERT INTO Departments VALUES(1, 'HR'),(2, 'Sales'),(3, 'IT');
Query OK, 3 rows affected (0.03 sec)
Records: 3  Duplicates: 0  Warnings: 0

mysql> select * from Departments;
+---------+-----------+
| dept_id | dept_name |
+---------+-----------+
|       1 | HR        |
|       2 | Sales     |
|       3 | IT        |
+---------+-----------+
3 rows in set (0.00 sec)
```

## Table3:Projects

Description->

```
mysql>  create table Projects(project_id int PRIMARY KEY,project_name char(20) NOT NULL,dept_id int NOT NULL,budget int NOT NULL);
Query OK, 0 rows affected (0.07 sec)

mysql> desc Projects;
+--------------+----------+------+-----+---------+-------+
| Field        | Type     | Null | Key | Default | Extra |
+--------------+----------+------+-----+---------+-------+
| project_id   | int      | NO   | PRI | NULL    |       |
| project_name | char(20) | NO   |     | NULL    |       |
| dept_id      | int      | NO   |     | NULL    |       |
| budget       | int      | NO   |     | NULL    |       |
+--------------+----------+------+-----+---------+-------+
4 rows in set (0.01 sec)
```

Insert_Data->

```
mysql> INSERT INTO Projects VALUES (201,'Alpha',1,100000),(202,'Beta',2,150000),(203,'Gamma',3,200000),
    -> (204,'Delta',2,120000);
Query OK, 4 rows affected (0.04 sec)
Records: 4  Duplicates: 0  Warnings: 0

mysql> select * from Projects;
+------------+--------------+---------+--------+
| project_id | project_name | dept_id | budget |
+------------+--------------+---------+--------+
|        201 | Alpha        |       1 | 100000 |
|        202 | Beta         |       2 | 150000 |
|        203 | Gamma        |       3 | 200000 |
|        204 | Delta        |       2 | 120000 |
+------------+--------------+---------+--------+
4 rows in set (0.03 sec)
```

## Table4:Attendance

Description->

```
mysql> create table Attendance(emp_id int PRIMARY KEY,date date NOT NULL,status char(20) NOT NULL);
Query OK, 0 rows affected (0.09 sec)

mysql> DESC Attendance;
+--------+----------+------+-----+---------+-------+
| Field  | Type     | Null | Key | Default | Extra |
+--------+----------+------+-----+---------+-------+
| emp_id | int      | NO   | PRI | NULL    |       |
| date   | date     | NO   |     | NULL    |       |
| status | char(20) | NO   |     | NULL    |       |
+--------+----------+------+-----+---------+-------+
3 rows in set (0.01 sec)
```

Insert_Data->

```
mysql> INSERT INTO Attendance VALUES(101,'2024-03-01','Present'),(102,'2024-03-01','Absent'),(103,'2024-03-01','Present'),(104,'2024-03-01','Present'),(105
'2024-03-01','Absent'),(106,'2024-03-01','Present'),(107,'2024-03-01','Present'),(108,'2024-03-01','Present'),(109,'2024-03-01','Absent'),(110,'2024-03-01'
'Present');
Query OK, 10 rows affected (0.04 sec)
Records: 10  Duplicates: 0  Warnings: 0

mysql> select* from Attendance;
+--------+------------+---------+
| emp_id | date       | status  |
+--------+------------+---------+
|    101 | 2024-03-01 | Present |
|    102 | 2024-03-01 | Absent  |
|    103 | 2024-03-01 | Present |
|    104 | 2024-03-01 | Present |
|    105 | 2024-03-01 | Absent  |
|    106 | 2024-03-01 | Present |
|    107 | 2024-03-01 | Present |
|    108 | 2024-03-01 | Present |
|    109 | 2024-03-01 | Absent  |
|    110 | 2024-03-01 | Present |
+--------+------------+---------+
10 rows in set (0.00 sec)
```

# SQL Questions:

1. Retrieve all employees.

```
mysql> select * from Employee;
+--------+----------+---------+--------+------------+-----------+
| emp_id | emp_name | dept_id | salary | hire_date  | city      |
+--------+----------+---------+--------+------------+-----------+
| 101    | Anuj     | 1       |  50000 | 2022-01-10 | Delhi     |
| 102    | Ravi     | 2       |  60000 | 2021-03-15 | Mumbai    |
| 103    | Neha     | 1       |  55000 | 2020-07-20 | Delhi     |
| 104    | Amit     | 3       |  70000 | 2019-11-01 | Pune      |
| 105    | Sneha    | 2       |  65000 | 2023-05-12 | Mumbai    |
| 106    | Karan    | 3       |  72000 | 2018-08-25 | Bangalore |
| 107    | Pooja    | 1       |  48000 | 2022-09-30 | Delhi     |
| 108    | Raj      | 2       |  52000 | 2021-12-11 | Chennai   |
| 109    | Meena    | 3       |  68000 | 2020-02-14 | Pune      |
| 110    | Vikas    | 1       |  51000 | 2023-01-18 | Delhi     |
+--------+----------+---------+--------+------------+-----------+
10 rows in set (0.00 sec)
```

2. Display only emp_name and salary.

```
mysql> select emp_name,salary from Employee;
+----------+--------+
| emp_name | salary |
+----------+--------+
| Anuj     |  50000 |
| Ravi     |  60000 |
| Neha     |  55000 |
| Amit     |  70000 |
| Sneha    |  65000 |
| Karan    |  72000 |
| Pooja    |  48000 |
| Raj      |  52000 |
| Meena    |  68000 |
| Vikas    |  51000 |
+----------+--------+
10 rows in set (0.01 sec)
```

3. Find employees working in department 1.

```
mysql> select * from Employee where dept_id=1;
+--------+----------+---------+--------+------------+-------+
| emp_id | emp_name | dept_id | salary | hire_date  | city  |
+--------+----------+---------+--------+------------+-------+
| 101    | Anuj     | 1       |  50000 | 2022-01-10 | Delhi |
| 103    | Neha     | 1       |  55000 | 2020-07-20 | Delhi |
| 107    | Pooja    | 1       |  48000 | 2022-09-30 | Delhi |
| 110    | Vikas    | 1       |  51000 | 2023-01-18 | Delhi |
+--------+----------+---------+--------+------------+-------+
4 rows in set (0.03 sec)
```

4. List employees from Delhi.

```
mysql> select * from Employee where city='Delhi';
+--------+----------+---------+--------+------------+-------+
| emp_id | emp_name | dept_id | salary | hire_date  | city  |
+--------+----------+---------+--------+------------+-------+
| 101    | Anuj     | 1       |  50000 | 2022-01-10 | Delhi |
| 103    | Neha     | 1       |  55000 | 2020-07-20 | Delhi |
| 107    | Pooja    | 1       |  48000 | 2022-09-30 | Delhi |
| 110    | Vikas    | 1       |  51000 | 2023-01-18 | Delhi |
+--------+----------+---------+--------+------------+-------+
4 rows in set (0.00 sec)
```

5. Show employees with salary greater than 60000.

```
mysql> select * from Employee where salary>60000;
+--------+----------+---------+--------+------------+-----------+
| emp_id | emp_name | dept_id | salary | hire_date  | city      |
+--------+----------+---------+--------+------------+-----------+
| 104    | Amit     | 3       |  70000 | 2019-11-01 | Pune      |
| 105    | Sneha    | 2       |  65000 | 2023-05-12 | Mumbai    |
| 106    | Karan    | 3       |  72000 | 2018-08-25 | Bangalore |
| 109    | Meena    | 3       |  68000 | 2020-02-14 | Pune      |
+--------+----------+---------+--------+------------+-----------+
4 rows in set (0.03 sec)
```

6. Find employees hired after 2021.

```
mysql> SELECT * FROM Employee WHERE hire_date > '2021-12-31';
+--------+----------+---------+--------+------------+--------+
| emp_id | emp_name | dept_id | salary | hire_date  | city   |
+--------+----------+---------+--------+------------+--------+
| 101    | Anuj     | 1       |  50000 | 2022-01-10 | Delhi  |
| 105    | Sneha    | 2       |  65000 | 2023-05-12 | Mumbai |
| 107    | Pooja    | 1       |  48000 | 2022-09-30 | Delhi  |
| 110    | Vikas    | 1       |  51000 | 2023-01-18 | Delhi  |
+--------+----------+---------+--------+------------+--------+
4 rows in set (0.03 sec)
```

7. Display unique cities.

```
mysql> SELECT DISTINCT city FROM Employee;
+------------+
| city       |
+------------+
| Delhi      |
| Mumbai     |
| Pune       |
| Bangalore  |
| Chennai    |
+------------+
5 rows in set (0.03 sec)
```

8. Sort employees by salary (descending).

```
mysql> SELECT * FROM Employee ORDER BY salary DESC;
+--------+----------+---------+--------+------------+-----------+
| emp_id | emp_name | dept_id | salary | hire_date  | city      |
+--------+----------+---------+--------+------------+-----------+
| 106    | Karan    | 3       |  72000 | 2018-08-25 | Bangalore |
| 104    | Amit     | 3       |  70000 | 2019-11-01 | Pune      |
| 109    | Meena    | 3       |  68000 | 2020-02-14 | Pune      |
| 105    | Sneha    | 2       |  65000 | 2023-05-12 | Mumbai    |
| 102    | Ravi     | 2       |  60000 | 2021-03-15 | Mumbai    |
| 103    | Neha     | 1       |  55000 | 2020-07-20 | Delhi     |
| 108    | Raj      | 2       |  52000 | 2021-12-11 | Chennai   |
| 110    | Vikas    | 1       |  51000 | 2023-01-18 | Delhi     |
| 101    | Anuj     | 1       |  50000 | 2022-01-10 | Delhi     |
| 107    | Pooja    | 1       |  48000 | 2022-09-30 | Delhi     |
+--------+----------+---------+--------+------------+-----------+
10 rows in set (0.00 sec)
```

9. Count total employees.

```
mysql> SELECT COUNT(*) FROM Employee;
+----------+
| COUNT(*) |
+----------+
|       10 |
+----------+
1 row in set (0.03 sec)
```

10. Find average salary.

```
mysql> SELECT AVG(salary) FROM Employee;
+-------------+
| AVG(salary) |
+-------------+
|  59100.0000 |
+-------------+
1 row in set (0.04 sec)
```

11. Find total salary paid per department.

```
mysql> SELECT dept_id, SUM(salary) AS total_salary
    -> FROM Employee
    -> GROUP BY dept_id;
+---------+--------------+
| dept_id | total_salary |
+---------+--------------+
| 1       |       204000 |
| 2       |       177000 |
| 3       |       210000 |
+---------+--------------+
3 rows in set (0.00 sec)
```

12. Count employees in each department.

```
mysql> SELECT dept_id, COUNT(*) AS total_emp
    -> FROM Employee
    -> GROUP BY dept_id;
+---------+-----------+
| dept_id | total_emp |
+---------+-----------+
| 1       |         4 |
| 2       |         3 |
| 3       |         3 |
+---------+-----------+
3 rows in set (0.00 sec)
```

13. Find highest salary in each department.

```
mysql> SELECT dept_id, MAX(salary) AS highest_salary
    -> FROM Employee
    -> GROUP BY dept_id;
+---------+----------------+
| dept_id | highest_salary |
+---------+----------------+
| 1       |          55000 |
| 2       |          65000 |
| 3       |          72000 |
+---------+----------------+
3 rows in set (0.05 sec)
```

14. Display employees along with department names.

```
mysql> SELECT e.emp_name, d.dept_name
    -> FROM Employee e
    -> JOIN Departments d
    -> ON e.dept_id = d.dept_id;
+----------+-----------+
| emp_name | dept_name |
+----------+-----------+
| Anuj     | HR        |
| Ravi     | Sales     |
| Neha     | HR        |
| Amit     | IT        |
| Sneha    | Sales     |
| Karan    | IT        |
| Pooja    | HR        |
| Raj      | Sales     |
| Meena    | IT        |
| Vikas    | HR        |
+----------+-----------+
10 rows in set (0.05 sec)
```

15. List employees working on Sales department.

```
mysql> SELECT e.*
    -> FROM Employee e
    -> JOIN Departments d
    -> ON e.dept_id = d.dept_id
    -> WHERE d.dept_name = 'Sales';
+--------+----------+---------+--------+------------+---------+
| emp_id | emp_name | dept_id | salary | hire_date  | city    |
+--------+----------+---------+--------+------------+---------+
| 102    | Ravi     | 2       |  60000 | 2021-03-15 | Mumbai  |
| 105    | Sneha    | 2       |  65000 | 2023-05-12 | Mumbai  |
| 108    | Raj      | 2       |  52000 | 2021-12-11 | Chennai |
+--------+----------+---------+--------+------------+---------+
3 rows in set (0.00 sec)
```

16. Find employees whose name starts with 'A'.

```
mysql> SELECT * FROM Employee WHERE emp_name LIKE 'A%';
+--------+----------+---------+--------+------------+-------+
| emp_id | emp_name | dept_id | salary | hire_date  | city  |
+--------+----------+---------+--------+------------+-------+
| 101    | Anuj     | 1       |  50000 | 2022-01-10 | Delhi |
| 104    | Amit     | 3       |  70000 | 2019-11-01 | Pune  |
+--------+----------+---------+--------+------------+-------+
2 rows in set (0.03 sec)
```

17. Get employees with salary between 50000 and 70000.

```
mysql> SELECT * FROM Employee
    -> WHERE salary BETWEEN 50000 AND 70000;
+--------+----------+---------+--------+------------+---------+
| emp_id | emp_name | dept_id | salary | hire_date  | city    |
+--------+----------+---------+--------+------------+---------+
| 101    | Anuj     | 1       |  50000 | 2022-01-10 | Delhi   |
| 102    | Ravi     | 2       |  60000 | 2021-03-15 | Mumbai  |
| 103    | Neha     | 1       |  55000 | 2020-07-20 | Delhi   |
| 104    | Amit     | 3       |  70000 | 2019-11-01 | Pune    |
| 105    | Sneha    | 2       |  65000 | 2023-05-12 | Mumbai  |
| 108    | Raj      | 2       |  52000 | 2021-12-11 | Chennai |
| 109    | Meena    | 3       |  68000 | 2020-02-14 | Pune    |
| 110    | Vikas    | 1       |  51000 | 2023-01-18 | Delhi   |
+--------+----------+---------+--------+------------+---------+
8 rows in set (0.02 sec)
```

18. Find employees not from Mumbai.

```
mysql> SELECT * FROM Employee WHERE city != 'Mumbai';
+--------+----------+---------+--------+------------+----------+
| emp_id | emp_name | dept_id | salary | hire_date  | city     |
+--------+----------+---------+--------+------------+----------+
| 101    | Anuj     | 1       |  50000 | 2022-01-10 | Delhi    |
| 103    | Neha     | 1       |  55000 | 2020-07-20 | Delhi    |
| 104    | Amit     | 3       |  70000 | 2019-11-01 | Pune     |
| 106    | Karan    | 3       |  72000 | 2018-08-25 | Bangalore |
| 107    | Pooja    | 1       |  48000 | 2022-09-30 | Delhi    |
| 108    | Raj      | 2       |  52000 | 2021-12-11 | Chennai  |
| 109    | Meena    | 3       |  68000 | 2020-02-14 | Pune     |
| 110    | Vikas    | 1       |  51000 | 2023-01-18 | Delhi    |
+--------+----------+---------+--------+------------+----------+
8 rows in set (0.00 sec)
```

19. Show employees hired in 2022.

```
mysql> SELECT * FROM Employee
    -> WHERE YEAR(hire_date) = 2022;
+--------+----------+---------+--------+------------+-------+
| emp_id | emp_name | dept_id | salary | hire_date  | city  |
+--------+----------+---------+--------+------------+-------+
| 101    | Anuj     | 1       |  50000 | 2022-01-10 | Delhi |
| 107    | Pooja    | 1       |  48000 | 2022-09-30 | Delhi |
+--------+----------+---------+--------+------------+-------+
2 rows in set (0.00 sec)
```

20. Find top 3 highest paid employees.

```
mysql> SELECT * FROM Employee
    -> ORDER BY salary DESC
    -> LIMIT 3;
+--------+----------+---------+--------+------------+-----------+
| emp_id | emp_name | dept_id | salary | hire_date  | city      |
+--------+----------+---------+--------+------------+-----------+
| 106    | Karan    | 3       |  72000 | 2018-08-25 | Bangalore |
| 104    | Amit     | 3       |  70000 | 2019-11-01 | Pune      |
| 109    | Meena    | 3       |  68000 | 2020-02-14 | Pune      |
+--------+----------+---------+--------+------------+-----------+
3 rows in set (0.00 sec)
```

21. INNER JOIN Employees and Departments.

```
mysql> SELECT e.emp_name, d.dept_name
    -> FROM Employee e
    -> INNER JOIN Departments d
    -> ON e.dept_id = d.dept_id;
+----------+-----------+
| emp_name | dept_name |
+----------+-----------+
| Anuj     | HR        |
| Ravi     | Sales     |
| Neha     | HR        |
| Amit     | IT        |
| Sneha    | Sales     |
| Karan    | IT        |
| Pooja    | HR        |
| Raj      | Sales     |
| Meena    | IT        |
| Vikas    | HR        |
+----------+-----------+
10 rows in set (0.00 sec)
```

22. LEFT JOIN to show all employees with department names.

```
mysql> SELECT e.emp_name, d.dept_name
    -> FROM Employee e
    -> LEFT JOIN Departments d
    -> ON e.dept_id = d.dept_id;
+----------+-----------+
| emp_name | dept_name |
+----------+-----------+
| Anuj     | HR        |
| Ravi     | Sales     |
| Neha     | HR        |
| Amit     | IT        |
| Sneha    | Sales     |
| Karan    | IT        |
| Pooja    | HR        |
| Raj      | Sales     |
| Meena    | IT        |
| Vikas    | HR        |
+----------+-----------+
10 rows in set (0.03 sec)
```

23. Find employees working in IT department.

```
mysql> SELECT e.*
    -> FROM Employee e
    -> JOIN Departments d
    -> ON e.dept_id = d.dept_id
    -> WHERE d.dept_name = 'IT';
+--------+----------+---------+--------+------------+-----------+
| emp_id | emp_name | dept_id | salary | hire_date  | city      |
+--------+----------+---------+--------+------------+-----------+
| 104    | Amit     | 3       |  70000 | 2019-11-01 | Pune      |
| 106    | Karan    | 3       |  72000 | 2018-08-25 | Bangalore |
| 109    | Meena    | 3       |  68000 | 2020-02-14 | Pune      |
+--------+----------+---------+--------+------------+-----------+
3 rows in set (0.00 sec)
```

24. Show project names with department names.

```
mysql> SELECT p.project_name, d.dept_name
    -> FROM Projects p
    -> JOIN Departments d
    -> ON p.dept_id = d.dept_id;
+--------------+-----------+
| project_name | dept_name |
+--------------+-----------+
| Alpha        | HR        |
| Beta         | Sales     |
| Gamma        | IT        |
| Delta        | Sales     |
+--------------+-----------+
4 rows in set (0.00 sec)
```

25. Find employees and their project budgets (via department).

```
mysql> SELECT e.emp_name, p.budget
    -> FROM Employee e
    -> JOIN Projects p
    -> ON e.dept_id = p.dept_id;
+----------+--------+
| emp_name | budget |
+----------+--------+
| Anuj     | 100000 |
| Ravi     | 120000 |
| Ravi     | 150000 |
| Neha     | 100000 |
| Amit     | 200000 |
| Sneha    | 120000 |
| Sneha    | 150000 |
| Karan    | 200000 |
| Pooja    | 100000 |
| Raj      | 120000 |
| Raj      | 150000 |
| Meena    | 200000 |
| Vikas    | 100000 |
+----------+--------+
13 rows in set (0.00 sec)
```

26. Find second highest salary.

```
mysql> SELECT MAX(salary)
    -> FROM Employee
    -> WHERE salary < (SELECT MAX(salary) FROM Employee);
+-------------+
| MAX(salary) |
+-------------+
|       70000 |
+-------------+
1 row in set (0.04 sec)
```

27. Rank employees by salary.

```
mysql> SELECT emp_name, salary,
    -> RANK() OVER (ORDER BY salary DESC) AS rank_no
    -> FROM Employee;
+----------+--------+---------+
| emp_name | salary | rank_no |
+----------+--------+---------+
| Karan    |  72000 |       1 |
| Amit     |  70000 |       2 |
| Meena    |  68000 |       3 |
| Sneha    |  65000 |       4 |
| Ravi     |  60000 |       5 |
| Neha     |  55000 |       6 |
| Raj      |  52000 |       7 |
| Vikas    |  51000 |       8 |
| Anuj     |  50000 |       9 |
| Pooja    |  48000 |      10 |
+----------+--------+---------+
10 rows in set (0.01 sec)
```

28. Find employees earning above average salary.

```
mysql> SELECT *
    -> FROM Employee
    -> WHERE salary > (SELECT AVG(salary) FROM Employee);
+--------+----------+---------+--------+------------+----------+
| emp_id | emp_name | dept_id | salary | hire_date  | city     |
+--------+----------+---------+--------+------------+----------+
| 102    | Ravi     | 2       |  60000 | 2021-03-15 | Mumbai   |
| 104    | Amit     | 3       |  70000 | 2019-11-01 | Pune     |
| 105    | Sneha    | 2       |  65000 | 2023-05-12 | Mumbai   |
| 106    | Karan    | 3       |  72000 | 2018-08-25 | Bangalore |
| 109    | Meena    | 3       |  68000 | 2020-02-14 | Pune     |
+--------+----------+---------+--------+------------+----------+
5 rows in set (0.00 sec)
```

29. Get department with highest total salary.

```
mysql> SELECT dept_id, SUM(salary) AS total_salary
    -> FROM Employee
    -> GROUP BY dept_id
    -> ORDER BY total_salary DESC
    -> LIMIT 1;
+---------+--------------+
| dept_id | total_salary |
+---------+--------------+
| 3       |       210000 |
+---------+--------------+
1 row in set (0.00 sec)
```

30. Find employees who were absent on 2024-03-01.

```
mysql> SELECT e.emp_name
    -> FROM Employee e
    -> JOIN Attendance a
    -> ON e.emp_id = a.emp_id
    -> WHERE a.status = 'Absent'
    -> AND a.date = '2024-03-01';
+----------+
| emp_name |
+----------+
| Ravi     |
| Sneha    |
| Meena    |
+----------+
3 rows in set (0.00 sec)
```