

# Mapping Pointclouds to OSM Building Outlines


Anurag Sai Vempati, Wolf Vollprecht  
 Supervised by: Torsten Sattler  
 March 6, 2015

## GROUP MEMBERS

Anurag Sai  
Vempati



Wolf Vollprecht



## I. DESCRIPTION OF THE PROJECT

The project aims to map pointcloud data of outdoor city environments to *OpenStreetMap*<sup>1</sup> (OSM) building outlines. The pointcloud data is generated by using the Structure-from-Motion technique to extract 3D data from multiple photographs taken from different viewpoints. The photographs are taken by consumer grade cameras and processed by software like VisualSFM.

To enrich the pointcloud data we want to map the facade outlines of the pointcloud to rich data that we get from OpenStreetMaps. This will allow us to identify, for example, shops and to tag different houses which might not work correctly without OSM data.

Furthermore, it is in the scope of the project to automatically extract building heights from the pointcloud data. Once the data is aligned to OSM, it will be possible to get absolute lengths from the pointcloud data. As OSM is a collaborative effort, the software might enable us to contribute back the building height data.

## II. WORK PACKAGES AND TIMELINE

The project has been broken down to two basic tasks. The implementation details and the expected outcomes are as follows:

- **Segmenting the Point Cloud:-**

We start with parsing the point cloud data from the bundler files [1] and use point cloud library [1] to do the further processing. For getting a 2-D outline of the buildings, we need to be able to segment out the point clouds into parts that belong to a plane which is up-right (and hence shows up as a line in the 2-D map) and the parts that are outliers to these planes.

To be able to do this, we first estimate the up-vector which is coplanar with the facades of the building and is normal to the ground. The data we will be working upon, mostly includes pictures taken from ground level. So, the smallest eigenvector of the covariance matrix generated from the camera positions should be vertical to the ground and a reasonable approximation for the up-right vector. Even in the cases where we might not have a fully flat ground, one could break it down into piece-wise flat areas and estimate up-right vectors at each of these regions.

Next thing to do would be to find the normal vector corresponding to each 3-D point by taking a patch in the point cloud around each of these points and calculating the smallest eigenvector of the covariance matrix

<sup>1</sup>osm.org

obtained from the points belonging to this patch. The direction of the normal vectors can be used to estimate the probability of each point being normal to the up-right vector.

Thresholding upon this probability measure helps in segmenting out the outliers and get the part of the point cloud that can be used to generate a 2-D outline that can be used in the next phase.

Anurag will be working on this part and plans to build a catkin package in C++ which can run on 64-bit Linux machines.

The idea for matching the outlines is to break it down to a 2D problem and use the Iterative Closest Point technique to find the best match between the building outlines and the pointcloud. For that, the pointcloud will be reduced to a two dimensional pointcloud and the building outlines will be discretized to a number of points (i.e. a pointcloud will be interpolated from the polygons that are existing in OSM). A state-of-the-art ICP, such as libpointmatcher [2] will then be used to align those two pointclouds.

Investigations will be made on how well the complexity of OSM data can be reduced i.e., by removing holes and separations between buildings.

The first workpackage will be to use arbitrary GPS coordinates, build a simple interface to input data and automatically download an OSM file.

### III. OUTCOMES AND DEMONSTRATION

Give detailed information on the expected outcome of your project and the experiments you plan to test your implementation. If applicable, describe the online or offline demo you plan to present at the end of the semester.

#### Instructions:

- The document should not exceed two pages including the references.
- Please name the document **3DPhoto\_Proposal\_Surname1\_Surname2.pdf** and send it to Yağız in an email titled **[3DPhoto] Project Proposal - Surname1 Surname2**, filling in your surnames.

#### REFERENCES

- [1] John Doe and Jane Doe. A closely related paper. In *an awesome conference*, 2014.
- [2] François Pomerleau, Francis Colas, Roland Siegwart, and Stéphane Magnenat. Comparing ICP Variants on Real-World Data Sets. *Autonomous Robots*, 34(3):133–148, February 2013.