

# rarray: Multidimensional Runtime Arrays for C++

Ramses van Zon

February, 2023 (version 2.5.0)

## 1 For the impatient: the what, why and how of rarray

### What:

Rarray provides multidimensional arrays with dimensions determined at runtime.

### What not:

No linear algebra, overloaded operators etc.

### Why:

Usually faster than alternatives,

Uses the same accessors as compile-time (automatic) arrays,

Data is guaranteed to be contiguous for easy interfacing with libraries (CBLAS, LAPACKE).

### How:

The header file rarray provides the type `rarray<T,R>`, where T is any type and R is the rank. Element access uses repeated square brackets. Copying rarrays or passing them to functions mean shallow copies, unless explicitly asking for a deep copy. Streaming I/O is also part of the rarray header.

Define a $n \times m \times k$ array of floats:	<code>rarray&lt;float,3&gt; b(n,m,k);</code>
Define a $n \times m \times k$ array of floats with data pre-allocated at a pointer ptr:	<code>rarray&lt;float,3&gt; c(ptr,n,m,k);</code>
Element $i,j,k$ of the array b:	<code>b[i][j][k]</code>
Pointer to the contiguous data in b:	<code>b.data()</code>
Extent in the $i$ th dimension in b:	<code>b.extent(i)</code>
Shallow, reference-counted copy of the array:	<code>rarray&lt;float,3&gt; d=b;</code>
Deep copy of the array:	<code>rarray&lt;float,3&gt; e=b.copy();</code>
A rarray using an existing automatic array:	<code>float f[10][20][8]={...}; rarray&lt;float,3&gt; g=RARRAY(f);</code>
A rarray copy of an existing automatic array:	<code>rarray&lt;float,3&gt; h=RARRAY(f).copy();</code>
Output a rarray to screen:	<code>std::cout &lt;&lt; h &lt;&lt; std::endl;</code>
Read a rarray from keyboard:	<code>std::cin &gt;&gt; h;</code>

## Contents

1	For the impatient: the what, why and how of rarray	1
2	Introduction	3
3	Using rarrays	5
4	Comparison with standard alternatives	9
5	Class definition	9
6	I/O	11
7	Utilities: xrange and linspace	12
8	Performance	14
9	Working with libraries	15
10	Conversions	16
A	Installation	21
B	History	22

## 2 Introduction

While C and thus C++ has some support for multidimensional arrays whose sizes are known at compile time, the support for arrays with sizes that are known only at runtime, is limited. For one-dimensional arrays, C++ has a reasonable allocation construction in the operators `new` and `delete`. A standard way to allocate a one-dimensional array is as follows:

```
float* a;
int n = 1000;
a = new float[n];
a[40] = 2.4;
delete[] a;
```

It is important to note that this code also works if `n` was not known yet, e.g., if it was passed as a function argument or read in as input.

In the above code snippet, the `new/delete` construct assigns the address of the array to a pointer. This pointer does not remember its size, so this is not really an 'array'. The standard C++ library does provide a one-dimensional array that remembers its size in the form of the `std::vector`, e.g.

```
const int n = 1000;
std::vector a(n);
a[40] = 2.4;
a.clear();
```

Multi-dimensional runtime-allocated arrays are not supported by C++. The textbook C++ solution for multidimensional arrays that are dynamically allocated during runtime, is as follows:

```
float*** a;
a = new float**[dim0];
for (int i=0; i<dim0; i++) {
    a[i] = new float*[dim1];
    for (int j=0; j<dim1; j++)
        a[i][j] = new float[dim2];
}
```

Drawbacks of this solution are:

- the non-contiguous buffer for the elements, making it unusable for many numerical libraries,
- having to keep track of array dimensions,
- having the intermediate pointers be non-const, so the internal pointer structure can be changed (conceptually, `a` ought to be of type `float*const*const*`, which would prevent this, but then one wouldn't be able to assign to be intermediate pointers in the above code, and therefore wouldn't be able to create the array except with some delicate `const` casts<sup>1</sup>).

---

<sup>1</sup>Truth be told, the `rarray` library does that, but only internally

At first, there seems to be no shortage of libraries to fill this lack of C++ support for dynamic multi-dimensional arrays, such as

- Blitz++;
- The Boost Multidimensional Array Library (`boost::multiarray`);
- Eigen;
- Armadillo; and
- Nested vectors from the Standard Template Library.

These typically do have some runtime overhead compared to the above textbook solution, or do not allow arbitrary ranks. In contrast, the purpose of the `rarray` library is to be a minimal interface for runtime multidimensional arrays of arbitrary rank with *minimal to no performance overhead* compared to the textbook solution.

**Example:**

```
#include <rarray>
int main()
{
    rtensor<float> a(256, 256, 256);
    a[1][2][3] = 105;
}
```

**Design Points of `rarray`**

1. To have dynamically allocated multidimensional arrays that combine the convenience of automatic C++ arrays with that of the typical textbook dynamically allocated pointer-to-pointer structure.  
The compatibility requirement with pointer-to-pointer structures is achieved by allocating a pointer-to-pointer structure. This structure accounts for most of the memory overhead from using `rarray`.
2. To be as fast as pointer-to-pointer structures.
3. To have `rarrays` know their sizes, so that can be passed to functions as a single argument.
4. To enable interplay with libraries such as BLAS and LAPACK: this is achieved by guaranteeing contiguous elements in the multi-dimensional array, and a way to get this data out.  
Relatedly, it should be allowed to use an existing buffer.  
The guarantee of contiguity means strided arrays are not supported.
5. To avoid some of the cluttered semantics around `const` correctness when converting to pointer-to-pointer structures.

**Features of `rarray`:**

- Can use any data type `T` and any rank `R`.
- Elements are accessible using repeated square brackets, like C/C++ arrays.
- Views on pre-allocated contiguous arrays.

- Does shallow, (atomic) reference counted, copies by default, but also has a deep copy method.
- Use of c++11 move semantics for efficiency (from version 2.0 onwards, rarray requires c++11).
- Can be emptied with the `clear` method.
- Can be filled with a uniform value with the `fill` method.
- Can be reshaped.
- Automatic C-style arrays can be converted to rarrays using `RARRAY`.
- Checks index bounds if the preprocessor constant `RA_BOUNDSCHECK` is defined.
- A method `empty` to check if the rarray is uninitialized.
- A method to get the number of elements in each dimension (`extent`), or in all dimensions (`shape`).
- A method to obtain the total number of elements in the array (`size`).
- A method to make the data type of the array `const` (`const_ref`).
- Conversion methods using the member function `data()` for conversions to a `T*` or `const T*`, using the method `ptr_array()` for conversions to `T*const*` or `const T*const*`, and using the method `noconst_ptr_array()` for the conversion to a `T**`.
- Streaming input and output.

## 3 Using rarrays

### 3.1 Defining a multidimensional rarray

To use rarray, first include the header file:

```
#include <rarray>
```

This defines the (template) classes `rarray<T,R>`, where `T` is the element type, and `R` is the rank (a positive integer). Instances can now be declared as follows:

```
rarray<float,3> s(256,256,256);  
s[1][2][3] = 105;  
// do whatever you need with s
```

or, using an external, pre-allocated buffer, as

```
float* pre_alloc_data=new float[256*256*256];  
rarray<float,3> s(pre_alloc_data,256,256,256);  
s[1][2][3] = 105;  
// do whatever you need with s  
delete[] pre_alloc_data;  
s.clear();
```

Without the `delete[]` statement in the latter example, there would be a memory leak. This reflects that `rarray` is in this case not responsible for the content. The data pointer can also be retrieved using `s.data()`. The `s.clear()` statement ensures there are no dangling references to this data left in `s`.

In the former case (`rarray<float,3> s(256,256,256)`), calling `s.clear()` before the `rarray` goes out of scope would release the memory of this array.

The construction specifying a number of extents as arguments works for arrays with rank up to and including 11. For arrays with larger rank, you have to pass an pointer to the array of extents.

### 3.2 Shorthand rarray types: rvector, rmatrix, rtensor

When compiling in `c++11` mode, there are short cut types for one-dimensional, two dimensional and three dimensional arrays, called `rvector`, `rmatrix` and `rtensor`, respectively. The following equivalences hold:

```
rvector<T> = rarray<T,1>
rmatrix<T> = rarray<T,2>
rtensor<T> = rarray<T,3>
```

for any type `T`.

### 3.3 Accessing the elements

The elements of `rarray` objects are accessed using the repeated square bracket notation as for automatic C++ arrays. Thus, if `s` is a `rarray` of rank `R`, the elements are accessed using `R` times an index of the form `[ni]`, i.e. `s[n0][n1]...[nR-1]`. For example:

```
for (int i=0;i<s.extent(0);i++)
  for (int j=0;j<s.extent(1);j++)
    for (int k=0;k<s.extent(2);k++)
      s[i][j][k] = i+j+k;
```

In addition to the explicit assignment of each element, there is an alternative way to assign values to the elements of an `rarray` using a comma separate form, as follows

```
rarray<double,2> matrix(3,3);
matrix = 1,2,3,
        4,5,6,
        7,8,9;
```

This is usefully mostly for small matrices (as in tests), as entering large `rarrays` in this way is rather impractical.

### 3.4 Copying and function arguments

In C++, when we copy a variable of a built-in type to a new variable, the new copy is completely independent of the old variable. Likewise, the default way of passing arguments to a function involves a complete copy for built-in types. For C-style arrays, however, only the pointer to the first element gets copied, not the whole array. The latter is called a shallow copy. Rarrays use shallow copies much like pointers, but uses atomic reference counting to know when memory can be released (similar to the `std::shared_ptr<T>` of C++11).

What does this essentially mean? Well:

1. You can pass rarrays by value to function, which is as if you were passing a pointer. (Passing by reference also works.)
2. When you assign one rarray to another, the other simply points to the old one.
3. If you wish to do a deep copy, i.e., create a new array independent of the old array, you need to use the copy method.

### 3.5 Returning a rarray from a function

Because rarray uses atomic reference counting and implements move semantics, returning an rarray from a function poses no problems.

Consider the function `zeros` used in `main()`:

```
#include <rarray>
rarray<double,2> zeros(int n, int m) {
    rarray<double,2> r(n,m);
    r.fill(0.0);
    return r;
}
int main() {
    rarray<double,2> s = zeros(100,100);
    return s[99][99];
}
```

In line 2, a rarray `r` is created, and filled, on line 3, with zeros. On line 4, `r` gets moved out of the function and into `s`, using C++11's move semantics. Move semantics cause `r` to be left in an empty state that will not deallocate the memory associated with the array `s`.

### 3.6 Reshaping the rarray

To use the data in an rarray but access it in a different 'shape', one can

1. create a new rarray which uses the data from the first rarray. E.g.

```
void dump(const rarray<double,3>& r) {
    rarray<double,1> rflat(r.data(), r.size());
    for (int i=0;i<r.size();i++)
        std::cout << rflat[i] << ' ';
    std::cout << std::endl;
}
```

2. or one can reshape the existing rarray with the desired dimensions. E.g.

```
void dump(rarray<double,3> r) {
    r.reshape(1, 1, r.size());
    for (int i=0;i<r.size();i++)
        std::cout << r[0][0][i] << ' ';
    std::cout << std::endl;
}
```

The latter only works if the new and old shape have the same ranks and the number of elements stays the same. It is possible to reshape an rarray to have less elements, but only by explicitly passing a last parameter `ra::RESIZE::ALLOWED`, e.g.

```
void dump(rarray<double,3> r) {
    r.reshape(1, 1, r.size()/2, ra::RESIZE::ALLOWED);
    for (int i=0;i<r.size();i++)
        std::cout << r[0][0][i] << ' ';
    std::cout << std::endl;
}
```

It should be stressed that the last example has no side effects for the shape of the original rarray that was passed to the function, because the rarray was passed by value, which implies a shallow copy; the original array retains its shape. If the array was passed by reference, the original array would of course be changed.

It is never possible to do a reshape that leads to more elements, because, by design, the reshape method should not allocated any memory.

### 3.7 Optional bounds checking

If the preprocessor constant `RA_BOUNDSCHECK` is defined, an `out_of_bounds` exception is thrown if

- an index is too small or too large;
- the size of dimension is requested that does not exist (in a call to `extent(int i)`);
- a constructor is called with a zero pointer for the buffer or for the dimensions array;

`RA_BOUNDSCHECK` can be defined by adding the `-DRA_BOUNDSCHECK` argument to the compilation command, or by `#define RA_BOUNDSCHECK` before the `#include <rarray>` in the source.



## 4 Comparison with standard alternatives

Compared to the textbook method (page 3) or the rarray method (page 4) of declaring an array, the more-or-less equivalent automatic array version

```
float arr[256][256][256];
arr[1][2][3] = 105;
```

is a little simpler, but automatic arrays are allocated on the stack, which is typically of limited size. Another big drawback is that this array cannot be passed to functions that do not hard-code exact matching dimensions except for the last one.

Using rarray also has benefits over another common C++ solution, i.e. using the Standard Template Library:

```
#include <vector>
int main() {
    using std::vector;
    int n = 256;                // size per dimension
    vector<vector<vector<float>>> v(n); // allocate for top dimension
    for (int i=0;i<n;i++) {
        v[i].resize(n);         // allocate vectors for middle dimension
        for (int j=0;j<n;j++)
            v[i][j].resize(n);  // allocate elements in last dimension
    }
    v[1][2][3] = 105;           // assign to element (for example)
}
```

which is complicated, is non-contiguous in memory, and likely slower.

## 5 Class definition

### 5.1 Interface

Effectively, the interface part of a rarray object is defined as follows:

```
template<typename T, int R>
class rarray {
public:
    rarray();                // create uninitialized array
    rarray(size_type extent0, ...); // constructor for R<=11
    rarray(const size_type* extents); // alternative: extents in array
    rarray(T* data, size_type extent0, ...); // construct with existing data
    rarray(T* data, const size_type* extents); // alternative: extents in array
```

```

rarray(const rarray<T,R> &a);           // shallow copy constructor
~rarray();                             // destructor
void reshape(size_type extent0, ...);   // change copy's shape (not data)
void reshape(const int* size_type);     // change copy's shape (not data)
void clear();                           // release memory
void fill(const T& value);               // fill with uniform value
bool empty() const;                     // check if uninitialized;
rarray<T,R> copy() const;                // deep copy
const size_type* shape() const;          // all extents as C-style array
size_type extent(int i) const;           // extent in dimension i
size_type size() const;                 // total number of elements
T* data() const;                        // start of internal buffer
T*const*... ptr_array() const;           // convert to a T*const*...
T**... noconst_ptr_array() const;        // converts to a T**...
rarray<const T,R>& const_ref() const;     // convert to const elements
rarray<T,R>& operator=(const rarray<T,R> &a); // shallow assignment
operator T*const*... ();                 // enables element access for assignment
operator const T*const*... () const;     // enables element access with []
};

```

## 5.2 Methods

**Definition:** `int extent(int i) const;`

This method returns the size of dimension *i*.

**Definition:** `const int* shape() const;`

This method returns the size of all dimensions as a c array.

**Definition:** `int size() const;`

This method returns the total number of elements.

**Definition:** `T* data() const;`

This method returns a pointer to the first element of the array.

**Definition:** `T*const*... ptr_array() const;`

This method returns a pointer to a `T*const*...`. Note that rarrays have an automatic conversion to this type.

**Definition:** `T**... noconst_ptr_array() const;`

This method returns a pointer to a `T**...` (This conversion breaks const-correctness.)

**Definition:** `rarray<const T,R>& const_ref() const;`

This method creates reference to this with const elements.

**Definition:** `void reshape(int extent0, ...);`

This method can be used to change the shape of the rarray. The data in the underlying buffer

will not change. Note that the number of dimensions (i.e., the rank) must remain the same and the total new size must be less or equal to the old size. This works only for arrays with rank up to and including 11.

**Definition:** `void reshape(const int* extents);`

Same as the previous reshape method, but takes an array of new dimensions as an argument. This is the only way to reshape an array of rank twelve or higher.

**Definition:** `void clear();`

This method release memory the memory associated with the rarray. If the rarray was created by providing a pre-existing buffer for the data, the memory of this buffer does not released.

**Definition:** `void fill(const T& value);`

This method fills the array with a uniform value value.

**Definition:** `bool empty();`

Checks if the rarray is in an uninitialized state.

**Definition:** `rarray<T,R> copy() const;`

This method creates deep copy of the rarray, i.e., an independent rarray with the same dimensions are the original rarray and with its content a copy of the original rarray's content.

## 6 I/O

### 6.1 Streaming input and output

Although it is usually preferable to store large arrays in binary, rarray does provide streaming operators << and >> to read and write to standard C++ iostreams.

The output produced by the output streaming operator is like that of automatic arrays initializers: Each dimension is started and ended by { and } and components are comma separated. Except for the inner dimension, newlines are included in the output, but no spaces, and no trailing newline. E.g.:

```
#include <iostream>
#include <rarray>
int main() {
    int buf[6] = {1,2,3,4,5,6};
    rarray<int,2> arr(buf,3,2);
    std::cout << arr;
}
```

will print the following:

```
{
{1,2},
{3,4},
{5,6}
}
```

Apart from inserting curly braces, commas, and newlines, the streaming operators use the streaming operators of the element types.

The streaming operators are designed such that the format that is written out by the << operator, should be readable by the >> operator. Without further formatting rules, reading would not be unambiguous for some types, e.g. for `std::string`, that can contain the syntactic elements '{', '}', ',', or '#'. If these elements are found in the output of an element, the element is prepended with a string that encodes the string length of the output. This prepending string starts with a '#' character, then the length of the string output for the element (excluding the prepended part), followed by a ':' character.

An exception to the '#' formatting rule exists for types that stream out such that the first output character is '(' and the last is ')', with no other ')' characters intervening. Such output does not require the '#' formatting. Complex numbers are a prime example of a type with such output and input.

Note that while the input stream operators expect the same format as the output produces by the output streams, they but will not care if newlines are not there. However, there should not be any extraneous whitespace in the input.

## 7 Utilities: xrange and linspace

The rarray library contains a few more utilities.

### 7.1 xrange

The xrange function returns an iterable generator, which can produce numbers from a starting point, with some step size, up to but not including an end point. In the simplest case, this can be used as a counter, e.g.:

```
#include <iostream>
#include <rarray>
int main() {
    for (int i: xrange(1000))
        std::cout << i << " ";
    std::cout << std::endl;
}
```

will print the numbers 0 to 999, which are generated in succession, i.e., no integer array of size 1000 containing these numbers is ever created. The return type of the xrange function is an `ra::Xrange<T>` object, with T equal to `int` in the above example. This is an iterable object that can be used in a range-based for. It could also be used as the source of a copy, and thus to initialize an rarray, e.g. you could get an array with values 0, 2, 4, ..., 998, as follows

```
#include <rarray>
#include <algorithm>
int main() {
```

---

```

ra::Xrange<int> in = xrange(0,1000,2);
rvector<int> r(500);
std::copy(in.begin(), in.end(), r.begin());
...
}

```

(replacing the type `ra::Xrange<int>` with `c++11`'s `auto` seems like a good idea here).

The general form of the range function is

```

ra::Xrange<T> xrange(T endvalue)
ra::Xrange<T> xrange(T beginvalue, T endvalue, T stepsize=1)

```

In the first form, the begin value is 0 and the stepsize is 1. These are template functions, where `T` can be any type that can be converted to a double, although the most useful cases are those where `T` is an integer. In all cases, the first generated value is exactly `beginvalue`, each subsequent value is one stepsize larger, and the endvalue is the first value that is not generated (to be precise, the number of numbers generated is `ceil(beginvalue-endvalue)/stepsize`, using floating point division).

The case where `endvalue` is less than `beginvalue`, or for which stepsize is negative, are, in the current rarray version, 2.1, undefined.

## 7.2 linspace

The `linspace` function returns a `rvector` with a specified number of points between two given values, inclusively. The general form of the function is

```

rvector<T> linspace(T x1, T x2, int n, bool end_incl=true);

```

Here, `x1` is the (guaranteed) first value, `x2` the (guaranteed) last value, and `n` is the number of values. If the latter is not given or is set to zero, the number of values is such that the stepsize is as close to one as possible. If `end_incl` is set to false, the generated values are such as if the number of points is `n+1` but the last value is omitted.

For example, to create an `rvector` with 101 equally spaced values between `-1.0` and `1.0`, one would do

```

#include <rarray>
int main() {
    rvector<int> r = linspace(-1.0, 1.0, 101);
    ...
}

```

The first argument of `linspace` is allowed to be greater than the last, in which case, decreasing values are generated. The two arguments are allowed to be equal as well, and generates a vector with all equal values. In that case, `end_incl` can not be set to false. The case where the number of points is 1 and `end_incl=false` is ill defined.

Note that for integer types, using `linspace` without specifying their number (i.e. `linspace(n1,n2)`) gives the same values as are generated by the range function without a stepsize and with the end-value one higher (i.e., `xrange(n1,n2+1)`).

## 8 Performance

### 8.1 General performance consideration

rarray is written specifically with performance in mind. However, the way it manages to mimic the natural c and c++ way of using multi-dimensional arrays, i.e. with (repeated) square brackets, would come at a high cost of function calls and temporary objects. The rarray library tries to inline most function calls to avoid this cost, but it needs the c++ compiler's optimization capabilities to help out. Even the lowest optimization levels, such as obtained with the `-O1` flag, will enable this.

Rarray is meant to be used with higher levels of optimization. When compiled with higher optimization levels, such as `-O3 -fstrict-aliasing` for g++, inlining should make the rarray objects at least as fast as the textbook solution for multidimensional arrays mentioned in the introduction.

### 8.2 Debugging

When debugging a code with a symbolic debugger (e.g. `gdb`), in addition to compiling with an option to include symbols<sup>2</sup> into the executable (e.g. `-g`), one usually switches off the compiler's optimization capabilities (`-O0`), because it can change the order of instructions in the code, which makes debugging very difficult. As explained above, when working with rarray, turning of the compiler's optimization options, can cause the program to become quite a bit slower, which can also hamper debugging. If the bug is unlikely to occur in rarray, it may be worth trying build with a mild optimization level such as `-O1` for debugging.

If, on the other hand, the bug is in rarray, one likely needs to switch off optimization to see what is going on. In addition to the `-O0` flag, this also requires switching off forced inlining, using the `-DRA_INLINE=inline` flag.

### 8.3 Profiling

Sampling profiling tools (such as `gprof`) work by periodically recording the state and call stack of the program as it runs. They can be very useful for performance analysis. When using these tools with rarray, it is advisable to compile with a minimum level of optimization `-O1`. Otherwise, a lot of the internal function calls of rarray that could simply be optimized away, and would pollute the sampling.

A hint regarding the current state of `gprof` and `gcc` (Mar 2016): the newer gcc compilers encode symbols differently than earlier versions, and `gprof` relies on the earlier format. This can impede e.g. profiling by line number. Compiling (and linking) with the `-gstabs` flags enables the earlier way of encoding symbols in the application, and allows for `gprof` to function fully.

### 8.4 Memory overhead using the rarray class

The memory overhead here comes from having to store the dimensions and a pointer-to-pointer structure. The latter account for most of the memory overhead. A rarray object of  $100 \times 100 \times 100 \times 100$

---

<sup>2</sup>Names of functions and other information regarding the code such as line numbers and file names are collectively called "symbols".

doubles on a 64-bit machine will have a memory overhead of a bit over 1%. In general, the memory overhead as a percentage is roughly 100% divided by the last dimension. Therefore, avoid rarrays with a small last dimension such as  $100 \times 100 \times 100 \times 2$ .

## 8.5 Compilation overhead using the rarray class

There is an overhead in the compilation stage, but this is very compiler dependent.

## 9 Working with libraries

Performance was one reason for writing the rarray library. Being able to pass such arrays to numerical libraries was another.

Many numerical libraries, such as BLAS, LAPACK and FFTW, are C or fortran based and their API requires that

1. the array elements are stored contiguously in memory,
2. one passes the pointer to the first element, and
3. one passes the dimensions of the array explicitly.

Rarray helps in satisfying these requirement as follows:

1. Elements of a rarray are always stored contiguously in memory.
2. The pointer to the first elements of the array can be found with the member function `data()`.
3. The dimensions of the arrays can be found from the `extent` or `shape` member functions of rarray (or, for one-dimensional arrays, also with the `size` member function).

Here is an example to call the matrix-matrix multiplication routine from blas, using the cblas interface:

```
#include <iostream>
#include <rarray>
#include <cblas.h>
int main() {
    int m=2, k=3, n=4;
    rmatrix<double> a(m,k), b(k,n), c(m,n);
    a = 1,-2,3,
        2,-1,0;
    b = -1,3,-2,1,
        -2,1,-3,2,
        -3,2,-1,3;
    cblas_dgemm(CblasRowMajor, CblasNoTrans, CblasNoTrans,
```

```

        c.extent(0), c.extent(1), a.extent(1), 1.0,
        a.data(), a.extent(1),
        b.data(), b.extent(1),
        1.0,
        c.data(), c.extent(1));
std::cout << "a=" << a << '\n'
          << "a=" << b << '\n'
          << "c=a*b=" << c << '\n';
}

```

See the blas documentation, for the precise meaning and operation of (c)blas.

Especially when working with complex data, an extra conversion may be required. For instance, working with the library called FFTW3, the following is a way to compute the fourier transform of a complex rarray:

```

#include <iostream>
#include <complex>
#include <rarray>
#include <fftw3.h>
int main() {
    int n = 4;
    rvector<std::complex<double>> a(n), b(n);
    a = 1.3+5.0i, 1.0, 5.0i, 2.0-5.0i;
    fftw_plan plan = fftw_plan_dft_1d(a.size(),
                                     (fftw_complex*)a.data(), (fftw_complex*)b.data(),
                                     FFTW_FORWARD, FFTW_ESTIMATE);
    fftw_execute(plan);
    fftw_destroy_plan(plan);
    std::cout << "a=" << a << '\n' << "FT(a)=" << b << '\n';
}

```

Note that this example uses the concise c++14 notation for complex variables (compile with `-std=c++14` or equivalent). Again, for the precise meaning of the fftw function call, see the documentation of that library.

Finally, it is worth noting that many numerical libraries care about the “alignment” of the data. Rarray currently does not have any way of facilitating alignment, but a user can allocate aligned data and pass it as a pre-existing buffer to the rarray constructor (see 3.1).

## 10 Conversions

### 10.1 Converting automatic C-style arrays to rarrays

It is possible to convert C-style automatic arrays to rarrays using the RARRAY macro (which calls some templated functions under the hood). You can apply RARRAY to any automatic array of rank



six or less. The main convenience of this is that one can write functions that take rarray argument(s) and pass automatic arrays to them. Another use is in initializing a rarray. For example:

```
#include <iostream>
#include <rarray>
void print2d(const rarray<float,2> &s) {
    for (int i=0; i<s.extent(0); i++) {
        for (int j=0; j<s.extent(1); j++)
            std::cout << s[i][j] << ' ';
        std::cout << std::endl;
    }
}
int main() {
    float printme[4][4] = { { 1.0, 1.2, 1.4, 1.6},
                           { 2.0, 2.2, 2.4, 2.6},
                           { 3.0, 3.2, 3.4, 3.6},
                           { 4.0, 4.2, 4.4, 4.6} };
    print2d(RARRAY(printme));
    rarray<float,2> a = RARRAY(printme).copy();
    print2d(a);
}
```

## 10.2 Conversions for function arguments

A function might take a `rarray<const T,R>` parameter if elements are not changed by it. Because C++ cannot convert a reference to a `rarray<T,R>` to a `rarray<const T,R>`, one has to use the `const_ref` method to do this for you. For example:

```
float add(const rarray<const float,2> &s) {
    float x = 0.0;
    for (int i=0; i<s.extent(0); i++)
        for (int j=0; j<s.extent(1); j++)
            x += s[i][j];
    return x;
}
int main() {
    rarray<float,2> s(40, 40);
    float z = add(s.const_ref()); // because add() takes <const float>
}
```

rarray objects are also easy to pass to function that do not use rarrays. Because there are, by design, no automatic conversions of a rarray, this is done using methods.

There are two main ways that such functions expect a multidimensional array to be passed: either as a pointer (a `T*`) to the first element of the internal buffer composed of all elements, or as

a pointer-to-pointer structure (a T\*\* . . .). In the former case, it may be important to know that a rarray stores elements in row-major format.

With the `const` keyword, the number of useful C++ forms for multidimensional array arguments has grown to about six. In the case of a two-dimensional array these take the forms: `T*`, `const T*`, `T*const*`, `const T*const*`, `T**`, and `const T**`. Using the `rarray` library, `const`-correct argument passing requires the `data` or `ptr_array` method but `non-const`-correct argument passing will require the `noconst_ptr_array` function, possibly combined with `const_ref`. We will briefly look at these cases separately now.

### 10.3 Conversion to a T\* or a const T\*

A function may expect a multidimensional array to be passed as a simple pointer to the first element, of the form `T*`, or of the form `const T*`. This is the case for most `c` or `fortran` libraries, as discussed above in 9. A `rarray` object `s` of type `rarray<T,I>` can be passed to these functions using the syntax `s.data()`, which yields a `T*`.

**Example 1:**

```
void fill1(float* a, int n1, int n2, float z) {
    for (int i=0; i<n1*n2; i++)
        a[i] = z;
}

int main() {
    rarray<float,2> s(40, 40);
    fill1(s.data(), s.extent(0), s.extent(1), 3.14);
}
```

**Example 2:**

```
float add2(const float* a, int n1, int n2) {
    float x = 0.0;
    for (int i=0; i<n1*n2; i++)
        x += a[i];
    return x;
}

int main() {
    rarray<float,2> s(40, 40);
    float z = add2(s.data(), s.extent(0), s.extent(1));
}
```

C++ accepts a `float*` instead of a `const float*`, so `data()` can be used in the latter example.

**10.4 Conversion to a T\*const\* or a const T\*const\***

In T\*const\*, the middle const means that one cannot reassign the row pointers. The rarray classes can be converted to this type using the ptr\_array() method, but rarrays also an automatic conversion to this type. For higher dimensions, this case generalizes to T\*const\*const\*, T\*const\*const\*const\*, etc.

**Example 1:**

```
void fill3(float*const* a, int n1, int n2, float z) {
    for (int i=0; i<n1; i++)
        for (int j=0; j<n2; j++)
            a[i][j] = z;
}

int main() {
    rarray<float,2> s(40, 40);
    fill3(s.ptr_array(), s.extent(0), s.extent(1), 3.14);
    // or, since rarray 2.0:
    fill3(s, s.extent(0), s.extent(1), 3.14);
}
```

**Example 2:**

```
float add4(const float*const* a, int n1, int n2) {
    float x = 0.0;
    for (int i=0; i<n1; i++)
        for (int j=0; j<n2; j++)
            x += a[i][j];
    return x;
}

int main() {
    rarray<float,2> s(40, 40);
    float z = add4(s.ptr_array(), 40, 40);
    // or,, since rarray 2.0,  z = add4(s, 40, 40);
}
```

C++ accepts a T\*const\* where a const T\*const\* is expected, so here one can again use the method ptr\_array(). This extends to its generalizations const T\*const\*const\*, const T\*const\*const\*const\*, etc., as well.

**10.5 Conversion to a T\*\***

Generating a T\*\* from a rarray object, one could change the internal structure of that rarray object through the double pointer. This is therefore considered a not const-correct. It is however commonly needed, so rarray does have a function for it, called noconst\_ptr\_array.

**Example:**

```
void fill5(float** a, int n1, int n2, float z) {
    for (int i=0; i<n1; i++)
        for (int j=0; j<n2; j++)
            a[i][j] = z;
}

int main() {
    rarray<float,2> s(40, 40);
    fill5(s.noconst_ptr_array(), s.extent(0), s.extent(1), 3.14);
}
```

## 10.6 Conversion to a const T\*\*

C++ does not allow conversion from T\*\* to const T\*\*. To convert to a const T\*\*, one first needs to convert the rarray<T,R> to a rarray<const T,R> using const\_ref(), after which one can use the noconst\_ptr\_array function.

**Example:**

```
float add6(const float** a, int n1, int n2) {
    float x = 0.0;
    for (int i=0; i<n1; i++)
        for (int j=0; j<n2; j++)
            x += a[i][j];
    return x;
}

int main() {
    rarray<float,2> s(40, 40);
    float z = add6(s.const_ref().noconst_ptr_array(), 40, 40);
}
```

## A Installation

Rarray is a header-only library, so you could just copy the header `rarray` to the directory `/usr/include` or some other directory that your C++ compiler searches for header files. Alternatively, you could use the command

```
make install PREFIX=[BASEDIR]
```

This installs the header file in the `[BASEDIR]/include` directory, and the documentation in `[BASEDIR]/share/doc`. If you have `sudo` permissions, you can also do

```
sudo make install
```

to install the header and documentation to `/usr/include` and `/usr/share/doc`, respectively. Note that this will fail on recent MacOS versions, in which case, try `sudo make install PREFIX=/usr/local`.

To modify `rarray`, do not edit these file separately. Instead, you should edit the files in the `headersources` directory. You can use the included Makefile to assemble the `rarray` headers with

```
make headers
```

If you're editing the documentation (this file), you need `pdflatex`, and you should edit `rarraydoc.tex` and then do

```
make doc
```

The Makefile can also be used to compile and run the unit tests and benchmarks. Simply do:

```
./configure  
make test  
make benchmarks
```

The `configure` command should work under Linux if you have a recent `gnu`, `intel`, `ibm` or `clang` compiler. Note that to pick your compiler, you may have to set the `CXX` environment variable point to the right compiler command (e.g. `export CXX=clang++`) before running `configure`.

If the include directory is not in the compiler's search path, you will need to pass an option to the compiler directing to that directory (i.e. `-I[BASEDIR]/include`) or, for `gcc` and `intel` compilers, set the `CPATH` environment variable.

## B History

Dec 2013:

First implementation of the header-only library `rarray` for runtime multidimensional arrays.

Jan 2014: Version 1.0

Code put on github

Mar 2015: Version 1.1

Changed the text output format used to use newlines

Feb 2017: Version 1.2

Added C++11 aliases `rvector`, `rmatrix` and `rtensor`. Eliminated the need for `rarraymacros.h` and `rarraydelmacros.h` in the installed version of `rarray`.

Oct 2019: Version 2.0

Prompted by a deeply rooted memory leak, this version is a full rewrite of `rarray` from the ground up, leaving most of the application interface unchanged. `Rarray` now **requires** C++11. The optional but expensive capability to do index range checking has partially been lost in the rewrite. `Rarray` comes with its own unit testing library now, `'rut'`.

Jan 2020: Version 2.1

Reference counting of `rarray` data is now done atomically, so copying `rarrays` should now be thread-safe. One-character names of substructures, used in debugging `rarray` itself, were removed. Streaming operators for `rarrays` moved to the `ra` namespace.

Feb 2020: Version 2.2

Several bug fixed with running and installing `rarray` on MacOS. The `rarray` unit test library `'rut'` was dropped in favour of `'catch2'`, which does everything that `'rut'` was intended to do, but better. Since `'catch2'` is header only, this makes running the tests on different platforms much easier.

Jan 2022: Version 2.3

Streaming I/O now part of the `rarray` header. `rarrayio` header is obsolete, but kept for backwards compatibility.

Dec 2022: Version 2.4

Internal refactoring focussed on eliminating warnings, dead code, version tracking in code, and exception safety. Fixed bug for compound data types. Support added for Intel OneAPI's icpx C++ compiler.

Dec 2022: Version 2.5

Optional bounds checking is back.

`is_clear` renamed to `empty`.

Can now get a subarray with square brackets.

`Rarray` objects no longer automatically convert into `T*const*`... pointers.

More extensive unit and coverage tests.