VAPTOR Security Assessment Report

Organization: VAPTOR001
Scan ID: SCAN20260411144452
Generated (UTC): 2026-04-12 08:20:49

1) Executive Summary

This assessment summarizes discovered assets, exposed services, and validated findings. MAC addresses are included where available to help correlate devices across scans in DHCP/dynamic IP environments.

Metric	Value
Assets assessed	30
Total vulnerabilities	97
Impact score	33/100
Overall control compliance	0% (0/74)

Severity breakdown

Severity	Count
Critical	2

Severity	Count
High	28
Medium	17
Low	15
Info	35

Assets Scanned

AssetUID	Asset IP	Asset MAC	Open Ports	Vuln Count
VAPTOR001A0001	44.228.249.3	—	—	0
VAPTOR001A0002	44.238.29.244	—	80	41
VAPTOR001A0003	10.0.0.132	B8:27:EB:74:F2:6C	22, 7070	2
VAPTOR001A0004	10.0.0.103	3C:0A:F3:3C:C1:A7	—	1
VAPTOR001A0005	10.0.0.128	16:41:0F:EC:FD:25	—	0
VAPTOR001A0006	10.0.0.254	70:F8:2B:1B:A3:68	53, 80, 443, 1990	3
VAPTOR001A0007	10.0.0.108	74:40:BB:72:FB:C5	—	0

End-of-Life Operating Systems

The following hosts are running operating systems that have reached end-of-life and no longer receive security patches. These represent a critical compliance and security risk and should be upgraded or isolated immediately.

Host IP	Operating System	EOL Since	Recommended Action
10.0.0.132	Linux 4.15 - 5.19	2023-05-31	MEDIUM: Upgrade to 20.04 or 22.04 LTS. If staying on 18.04, enable Ubuntu Pro ESM.
44.238.29.244	Microsoft Windows Server 2012 or Windows Server 2012 R2	2023-10-10	HIGH: Windows Server 2012 is EOL. Migrate to Server 2019/2022. Consider ESU if migration delayed.

Watchdog Answers

- **What is exposed?** 30 assets with 7 open TCP ports; 3 high-risk exposed service(s).
- **What is vulnerable?** 97 validated finding(s) (Critical 2, High 28, Medium 17).
  Top findings: CRITICAL: Unsanitized user input in XML External Entity; CRITICAL: Usage of hard-coded secret; HIGH: Clear-Text Protocol - HTTP
- **What is the evidence?** Evidence snippets present for 38/97 finding(s). See per-asset finding notes for captured headers, fingerprints, and observed behaviors.
- **What is the risk/impact?** Impact score 33/100. Compliance posture: 7% control coverage and 0% vuln-to-control mapping.
- **What should we do next?** Prioritize CRITICAL/HIGH fixes first, then reduce high-risk exposure and re-scan to confirm closure.

Top actions: Restrict exposure of 10.0.0.132:22 (HIGH). Implement key-based authentication only. Disable password authentication. Use fail2ban. Restrict access by IP. Enable 2FA.; Restrict exposure of 10.0.0.254:80 (HIGH). Redirect all traffic to HTTPS (port 443). Disable HTTP or use only for redirect. Implement HSTS headers.; Restrict exposure of 44.238.29.244:80 (HIGH). Redirect all traffic to HTTPS (port 443). Disable HTTP or use only for redirect. Implement HSTS headers.

2) Technical Summary

Key technical metrics derived from discovery artifacts and assessment outputs:

Metric	Value
Impact score	33/100
Assets discovered	30
Open TCP ports discovered (state=open)	7

Scanner Execution Status

This section records which scanners executed, were skipped, or were unavailable for this run.

Scanner	Status
VAPTORAPI — Vaptor Intelligence	Completed
VAPTORSCOUT — Discovery	Completed

Scanner	Status
VAPTORRECON — Vulnerability Assessment	Completed
VAPTORWEB — Web Scanner	Completed
VAPTORSQL — SQL Verification	Completed
VAPTORMSF — Exploit Verification	Completed
VAPTORFW — Firewall / IDS Monitoring	Skipped
VAPTORWIFI — WiFi Channel Security Scan	Reserved
VAPTORSET — Social Engineering Assessment	Completed
VAPTORMAST — Mobile Application Security Testing	Completed
VAPTORDAST — Dynamic Application Security Testing	Completed with Errors
VAPTORSAST — Static Application Security Testing	Completed
VAPTORSHARK — Vaptor Network Shark	Completed
VAPTORAI — Vaptor AI Enhancement	Completed
VAPTOREXT — External Scanner Import	Skipped
VAPTORSNIPER — Sn1per Attack Surface Scanner	Completed

Scanner	Status
VAPTORBURP — Burp Suite Web Application Scanner	Completed

Validation summary

Stage	Status	Targets	Scanners	Issues	Warnings
Overall	Valid	7	VAPTORMSF, VAPTORSQL, VAPTORWEB	0	0
Vulnerability assessment	Valid	7	VAPTORWEB	0	0
Penetration test	Valid	7	VAPTORMSF, VAPTORSQL	0	0

CMDB Summary

Inventory baseline derived from CMDB tables (MAC-canonical internal devices, IP-canonical external exposure).

Metric	Value
New devices (this scan)	5
New IPs (this scan)	5
IP changes (this scan)	0
Internal devices (total)	5

Metric	Value
Internal devices (seen this scan)	5
Internal devices (unknown vendor)	1
Internal current IPs	5
External IPs (total)	2
External IPs (seen this scan)	2

Top vendors (OUI)

Vendor	Count
CLOUD NETWORK TECHNOLOGY SINGAPORE PTE. LTD.	1
DWnet Technologies(Suzhou) Corporation	1
Hon Hai Precision Ind. Co.,Ltd.	1
Raspberry Pi Foundation	1

Web Recon

Best-effort web content inventory (login hints, emails, paths). Some endpoints may block or return non-standard HTTP.

Metric	Value
Endpoints attempted	2
Endpoints reachable	2
Login hints	2
Emails found	0
Unique paths discovered	17

Endpoint	Status	Login	Emails	Paths	Notes
http://testasp.vulnweb.com/	200	Yes	0	8 (/Default.asp, /Images/logo.gif, /Login.asp)	—
http://testaspnet.vulnweb.com/	200	Yes	0	10 (/Comments.aspx, /ReadNews.aspx, /Signup.aspx)	—

Enrichment

Domain Registration (WHOIS)

IP	Domain	Registrar	Expiration
44.228.249.3	AMAZONAWS.COM	MarkMonitor, Inc.	['2027-01-16T04:59:59+00:00', '2027-01-16T00:00:00+00:00']

IP	Domain	Registrar	Expiration
44.238.29.244	AMAZONAWS.COM	MarkMonitor, Inc.	['2027-01-16T04:59:59+00:00', '2027-01-16T00:00:00+00:00']

BuiltWith Technology Profile

http://testhtml5.vulnweb.com:

http://testphp.vulnweb.com:

http://testasp.vulnweb.com:

Category	Technologies
Editors	DreamWeaver
Operating Systems	Windows Server
Web Servers	IIS

http://testaspnet.vulnweb.com:

Category	Technologies
Operating Systems	Windows Server
Web Frameworks	Microsoft ASP.NET

Category	Technologies
Web Servers	IIS

BuiltWith data powered by external API enrichment.

Verification

Verification runs are scoped to discovered open TCP ports and use non-exploit auxiliary probes (service-aware).

Metric	Value
Status	completed
Checks attempted	5
Targets	completed=3, failed=0

Recon (VAPTORSHARK)

Metric	Value
Capture artifacts present	Yes
Artifact count	6
Total artifact size (bytes)	14429640

Metric	Value
Capture interface	eth0
Packets captured	154953
Packets dropped	—
Drop rate	—
PCAP files	1
PCAP total bytes	0
Capture timestamp	2026-04-11T17:03:49.267777Z

Note: Reports intentionally do not include intercepted content (e.g., URLs, credentials) to reduce sensitive-data exposure. Review capture artifacts directly when authorized.

MITM Artifacts (artifacts/mitm)

File	Kind	Bytes
pcap_summary.json	json	723
recon_observations.json	json	15645
VAPTORARP20260411185825.log	log	14412307

File	Kind	Bytes
VAPTORARP20260411185849.log	log	433
VAPTORCAP20260411185848.pcapng	pcap	0
VAPTORPCAP20260411185848.log	log	532

Visited domains (top)

Domain	Count
logs.netflix.com	10415
array609.prod.do.dsp.mp.microsoft.com	4787
epns.eset.com	3995
web.ws.prod.cloud.netflix.com	3153
test-gateway.instagram.com	2056
web.whatsapp.com	1586
z-p4-gateway-fallback.facebook.com	1561
tvx.adgrx.com	1345
nrdp.ws.prod.cloud.netflix.com	1318

Domain	Count
prd-euw1-ucs.aibixby.com	1254
unagi-eu.amazon.com	1245
ipv4-c057-jnb001-ix.1.oca.nflxvideo.net	1104
osb-v2.samsungqbe.com	1065
mesu-cdn.origin-apple.com.akadns.net	1000
ipv4-c064-jnb001-ix.1.oca.nflxvideo.net	950
connectivitycheck.platform.hihonorcloud.com	943
euro02.azure-devices.net	926
apm-ap.yun.hihonor.com	917
configuration-lb.ls-apple.com.akadns.net	842
ipv4-c062-jnb001-ix.1.oca.nflxvideo.net	652
crl3.digicert.com	633
chat.cdn.whatsapp.net	606
tvp-ads-log.samsungads.com	601

Domain	Count
connectivitycheck.platform.hicloud.com	599
developers.google.cn	598

Observed public IPs (top)

IP	Count
102.132.99.62	17825
40.83.252.19	11784
105.255.1.136	8209
54.217.229.70	3392
54.76.138.123	3371
102.132.99.56	3150
3.255.31.202	3097
105.255.1.135	3028
102.132.99.142	2686
150.138.37.168	1753

IP	Count
40.104.14.210	1713
57.144.238.192	1516
41.0.194.75	1256
102.132.99.1	1179
54.229.239.201	1118
172.67.140.99	1101
105.255.1.137	1078
104.18.30.173	1016
54.76.212.68	1012
34.160.212.185	953
45.57.4.130	945
41.21.238.162	871
102.132.99.60	835
45.57.40.1	819

IP	Count
129.134.94.122	774

Hostname enrichment (reverse DNS)

IP	Hostname	Count
54.217.229.70	ec2-54-217-229-70.eu-west-1.compute.amazonaws.com	3392
54.76.138.123	ec2-54-76-138-123.eu-west-1.compute.amazonaws.com	3371
102.132.99.56	edge-z-p3-shv-01-cpt1.facebook.com	3150
3.255.31.202	ec2-3-255-31-202.eu-west-1.compute.amazonaws.com	3097
102.132.99.142	edge-ig-dgw-shv-01-cpt1.facebook.com	2686
57.144.238.192	instagram-p3-shv-01-lhr6.fbcdn.net	1516
41.0.194.75	vc-vb-41-0-194-75.ens.vodacom.co.za	1256
102.132.99.1	edge-star-shv-01-cpt1.facebook.com	1179
54.229.239.201	ec2-54-229-239-201.eu-west-1.compute.amazonaws.com	1118
54.76.212.68	ec2-54-76-212-68.eu-west-1.compute.amazonaws.com	1012
34.160.212.185	185.212.160.34.bc.googleusercontent.com	953

IP	Hostname	Count
45.57.4.130	ipv4-c051-jnb001-ix.1.oca.nflxvideo.net	945
102.132.99.60	whatsapp-cdn-shv-01-cpt1.fbcdn.net	835
45.57.40.1	ftl.netflix.com	819
129.134.94.122	msw1ac.01.cpt1.tfbnw.net	774
142.251.168.108	wh-in-f108.1e100.net	746
102.132.99.37	whatsapp-chatd-msgr-mini-edge-shv-01-cpt1.facebook.com	642
34.200.71.76	ec2-34-200-71-76.compute-1.amazonaws.com	605

SAST - Static Application Security Testing

Source path: /home/***/vaptor/be/tests/VulnerableApp-master/VulnerableApp-master

Scan timestamp: 2026-04-11T17:18:53.200054

Total findings: 50

Tool Results

Tool	Status	Findings
bearer	completed	50

Tool	Status	Findings
bandit	completed	0
gitleaks	completed	0

VAPTORSAST Code Security Findings (Bearer)

Severity	Finding	CWE	Location
CRITICAL	Usage of hard-coded secret	798	...rg/sasanlabs/service/vulnerability/jwt/bean/JWTUtils.java:44
CRITICAL	Usage of hard-coded secret	798	...rg/sasanlabs/service/vulnerability/jwt/bean/JWTUtils.java:48
CRITICAL	Unsanitized user input in XML External Entity	611	...sasanlabs/service/vulnerability/xxe/XXEVulnerability.java:75
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	...nerability/staticResources/LEVEL_1/SampleVulnerability.js:22
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	...es/static/templates/CommandInjection/LEVEL_1/CI_Level1.js:14
HIGH		79	

Severity	Finding	CWE	Location
	Unsanitized user input in dynamic HTML insertion (XSS)		...es/CryptographicFailures/LEVEL_1/CryptographicFailures.js:8
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	...es/CryptographicFailures/LEVEL_1/CryptographicFailures.js:44
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	...es/CryptographicFailures/LEVEL_1/CryptographicFailures.js:47
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	...dSQLInjectionVulnerability/LEVEL_1/SQLInjection_Level1.js:17
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	...s/static/templates/JWTVulnerability/LEVEL_1/JWT_Level1.js:25
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	...ates/JWTVulnerability/LEVEL_13/HeaderInjection_Level13.js:24
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	...ates/JWTVulnerability/LEVEL_13/HeaderInjection_Level13.js:30
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	...s/static/templates/JWTVulnerability/LEVEL_2/JWT_Level2.js:24
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	...s/static/templates/JWTVulnerability/LEVEL_2/JWT_Level2.js:30

Severity	Finding	CWE	Location
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	...es/static/templates/JWTVulnerability/LEVEL_7/JWT_Level.js:35
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	...es/static/templates/JWTVulnerability/LEVEL_7/JWT_Level.js:41
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	...s/static/templates/PathTraversal/LEVEL_1/PathTraversal.js:35
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	...sistentXSSInHTMLTagVulnerability/LEVEL_1/PersistentXSS.js:17
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	...sistentXSSInHTMLTagVulnerability/LEVEL_1/PersistentXSS.js:22
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	...ources/static/templates/SSRFVulnerability/LEVEL_1/SSRF.js:24
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	...plates/SampleVulnerability/LEVEL_1/SampleVulnerability.js:22
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	...dSQLInjectionVulnerability/LEVEL_1/SQLInjection_Level1.js:16
HIGH		79	

Severity	Finding	CWE	Location
	Unsanitized user input in dynamic HTML insertion (XSS)		...ic/templates/UnrestrictedFileUpload/LEVEL_1/FileUpload.js:14
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	...rces/static/templates/XSSInImgTagAttribute/LEVEL_1/XSS.js:16
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	...s/static/templates/XSSWithHtmlTagInjection/LEVEL_1/XSS.js:15
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	.../templates/XSSWithNullBytesImgTagAttribute/LEVEL_1/XSS.js:14
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	...esources/static/templates/XXEVulnerability/LEVEL_1/XXE.js:18
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	...esources/static/templates/XXEVulnerability/LEVEL_1/XXE.js:22
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	...esources/static/templates/XXEVulnerability/LEVEL_1/XXE.js:26
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	...esources/static/templates/XXEVulnerability/LEVEL_1/XXE.js:30
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	...esources/static/templates/XXEVulnerability/LEVEL_1/XXE.js:34

Severity	Finding	CWE	Location
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	...esources/static/templates/XXEVulnerability/LEVEL_1/XXE.js:78
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	src/main/resources/static/vulnerableApp.js:57
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	src/main/resources/static/vulnerableApp.js:71
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	src/main/resources/static/vulnerableApp.js:107
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	src/main/resources/static/vulnerableApp.js:162
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	src/main/resources/static/vulnerableApp.js:168
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	79	src/main/resources/static/vulnerableApp.js:312
MEDIUM	Missing HTTP Only option in cookie configuration	1004	...nlabs/service/vulnerability/idor/IDORLoginController.java:50
MEDIUM		614	

Severity	Finding	CWE	Location
	Missing Secure option in cookie configuration		...nlabs/service/vulnerability/idor/IDORLoginController.java:50
MEDIUM	Usage of insufficient random value	330	...vice/vulnerability/fileupload/UnrestrictedFileUpload.java:53
MEDIUM	Observable Timing Discrepancy	208	...tographicFailures/CryptographicFailuresVulnerability.java:90
MEDIUM	Observable Timing Discrepancy	208	...tographicFailures/CryptographicFailuresVulnerability.java:132
MEDIUM	Observable Timing Discrepancy	208	...tographicFailures/CryptographicFailuresVulnerability.java:175
MEDIUM	Observable Timing Discrepancy	208	...tographicFailures/CryptographicFailuresVulnerability.java:215
MEDIUM	Observable Timing Discrepancy	208	...tographicFailures/CryptographicFailuresVulnerability.java:266
MEDIUM	Observable Timing Discrepancy	208	...asanlabs/service/vulnerability/jwt/impl/JWTValidator.java:52
MEDIUM	Usage of trusted and untrusted data inside the same data structure	501	...nlabs/service/vulnerability/idor/IDORLoginController.java:36

Severity	Finding	CWE	Location
LOW	Leakage of information in logger message	532	...s/static/templates/JWTVulnerability/LEVEL_1/JWT_Level1.js:14
LOW	Leakage of information in logger message	532	...s/static/templates/JWTVulnerability/LEVEL_1/JWT_Level1.js:15

50 Bearer findings. Ref: artifacts/sast/bearer_results.json

Note: SAST results provide static code analysis findings. Review detailed artifacts under artifacts/sast/ for remediation guidance.

DAST - Dynamic Application Security Testing

Targets scanned: 7

Scan timestamp: 2026-04-11T17:19:23.608250

Total findings: 0

Tool Results

Tool	Status	Targets	Findings
VAPTORRECON	timeout	—	0
VAPTORDAST	completed	7	0

Note: DAST results provide dynamic vulnerability assessment findings. Review detailed artifacts under artifacts/dast/ for specific CVE/misconfig details.

VAPTORMAST - Mobile Application Security Testing

App file: /home/***/vaptor/be/tests/pivaa.apk

Package: com.htbridge.pivaa

Version: 1.0 **Min SDK:** 19 **Target SDK:** 26

Scan timestamp: 2026-04-11T18:55:37.956644

Findings: 4 (Critical: 1, High: 1, Medium: 2, Low: 0)

Security Flags

- **debuggable:** True
- **allowBackup:** True

Dangerous Permissions (8)

- android.permission.ACCESS_COARSE_LOCATION
- android.permission.READ_CONTACTS
- android.permission.WRITE_EXTERNAL_STORAGE
- android.permission.CAMERA
- android.permission.RECORD_AUDIO
- android.permission.GET_ACCOUNTS
- android.permission.READ_EXTERNAL_STORAGE
- android.permission.ACCESS_FINE_LOCATION

MAST Findings

Severity	Category	Finding	Detail
HIGH	permissions	Dangerous permissions requested (8)	android.permission.ACCESS_COARSE_LOCATION, android.permission.READ_CONTACTS, android.permission.WRITE_EXTERNAL_STORAGE,
CRITICAL	manifest	Application is marked debuggable (android:debuggable=true)	ADB shell access to app private data is possible without root
MEDIUM	manifest	ADB backup allowed (android:allowBackup=true)	ADB backup can extract app data without root access
MEDIUM	certificate	Self-signed certificate	Self-signed certificate

Note: MAST results are from androguard static analysis. Review full results in artifacts/app/appsec_summary.json and artifacts/app/static_analysis.json

VAPTORSET - Social Engineering Assessment

Authorization: ✓ Acknowledged **Actor:** Vaptor **Timestamp:** 2026-04-12T05:59:53.440869+00:00

Credential Captures

Timestamp	Template / Campaign	Source IP / MAC	Offenses	Username
2026-04-12T05:56:32.058877+00:00	office365	10.0.0.130	3	test
2026-04-12T05:58:53.516490+00:00	gmail	10.0.0.130	3	***EMAIL***
2026-04-12T06:00:10.393871+00:00	router_login	10.0.0.130	3	admin

Errors: Port 8080 is already in use — campaign aborted to avoid conflict with VAPTORWEB or other listeners.

Note: Review full results in artifacts/vaptorset/set_summary.json

VAPTORSNIPER - Attack Surface Scanner

Mode: nuke **Target:** 7 targets **Workspace:** VAPTOR_VAPTOR001_20260411144454

Timestamp: 2026-04-12T06:17:42.489440Z **Elapsed:** 7166s **Status:** completed **Total findings:** 49

Sniper Findings

Severity	Type	Host	Detail
HIGH	Clear-Text Protocol - HTTP	http://ec2-44-238-29-244.us-west-2.compute.amazonaws.com:80/	P2 - HIGH, Clear-Text Protocol - HTTP, http://ec2-44-238-29-244.us-

Severity	Type	Host	Detail
			west-2.compute.amazonaws.com:80/, HTTP/1.1 200 OK
MEDIUM	Components with Known Vulnerabilities - VAPTORDISCOVERY	10.0.0.132	P3 - MEDIUM, Components with Known Vulnerabilities - VAPTORDISCOVERY, 10.0.0.132, CVE-2026-35385 7.5 https://vulners.com/cve/CVE-20
MEDIUM	Components with Known Vulnerabilities - VAPTORDISCOVERY	10.0.0.132	P3 - MEDIUM, Components with Known Vulnerabilities - VAPTORDISCOVERY, 10.0.0.132, CVE-2026-35386 3.6 https://vulners.com/cve/CVE-20
MEDIUM	Components with Known Vulnerabilities - VAPTORDISCOVERY	10.0.0.132	P3 - MEDIUM, Components with Known Vulnerabilities - VAPTORDISCOVERY, 10.0.0.132, CVE-2026-35387 3.1 https://vulners.com/cve/CVE-20
MEDIUM	Components with Known	10.0.0.132	P3 - MEDIUM, Components with Known Vulnerabilities - VAPTORDISCOVERY, 10.0.0.132,

Severity	Type	Host	Detail
	Vulnerabilities - VAPTORDISCOVERY		CVE-2026-35388 2.5 https://vulners.com/cve/CVE-20
MEDIUM	Components with Known Vulnerabilities - VAPTORDISCOVERY	10.0.0.132	P3 - MEDIUM, Components with Known Vulnerabilities - VAPTORDISCOVERY, 10.0.0.132, CVE-2026-35414 8.1 https://vulners.com/cve/CVE-20
MEDIUM	Components with Known Vulnerabilities - VAPTORDISCOVERY	ec2-44-238-29-244.us-west-2.compute.amazonaws.com	P3 - MEDIUM, Components with Known Vulnerabilities - VAPTORDISCOVERY, ec2-44-238-29-244.us-west-2.compute.amazonaws.com, CVE-2014-4
MEDIUM	Components with Known Vulnerabilities - VAPTORDISCOVERY	www.adsl.vf	P3 - MEDIUM, Components with Known Vulnerabilities - VAPTORDISCOVERY, www.adsl.vf, 54E54B28-6154-5E4D-8DFA-D9BB3D53034A 4.3 https:/
MEDIUM	Components with Known	www.adsl.vf	P3 - MEDIUM, Components with Known Vulnerabilities -

Severity	Type	Host	Detail
	Vulnerabilities - VAPTORDISCOVERY		VAPTORDISCOVERY, www.adsl.vf, CBF3EF2D-3A5B-5110-A374-4A5ADE9AC91A 4.3 https:/
MEDIUM	Components with Known Vulnerabilities - VAPTORDISCOVERY	www.adsl.vf	P3 - MEDIUM, Components with Known Vulnerabilities - VAPTORDISCOVERY, www.adsl.vf, CVE-2017-15107 7.5 https://vulners.com/cve/CVE-2
MEDIUM	Components with Known Vulnerabilities - VAPTORDISCOVERY	www.adsl.vf	P3 - MEDIUM, Components with Known Vulnerabilities - VAPTORDISCOVERY, www.adsl.vf, CVE-2019-14834 4.3 https://vulners.com/cve/CVE-2
MEDIUM	Components with Known Vulnerabilities - VAPTORDISCOVERY	www.adsl.vf	P3 - MEDIUM, Components with Known Vulnerabilities - VAPTORDISCOVERY, www.adsl.vf, CVE-2020-25681 8.3 https://vulners.com/cve/CVE-2
MEDIUM	Components with Known	www.adsl.vf	P3 - MEDIUM, Components with Known Vulnerabilities -

Severity	Type	Host	Detail
	Vulnerabilities - VAPTORDISCOVERY		VAPTORDISCOVERY, www.adsl.vf, CVE-2020-25682 8.3 https://vulners.com/cve/CVE-2
MEDIUM	Components with Known Vulnerabilities - VAPTORDISCOVERY	www.adsl.vf	P3 - MEDIUM, Components with Known Vulnerabilities - VAPTORDISCOVERY, www.adsl.vf, CVE-2020-25683 7.1 https://vulners.com/cve/CVE-2
MEDIUM	Components with Known Vulnerabilities - VAPTORDISCOVERY	www.adsl.vf	P3 - MEDIUM, Components with Known Vulnerabilities - VAPTORDISCOVERY, www.adsl.vf, CVE-2020-25684 4.3 https://vulners.com/cve/CVE-2
MEDIUM	Components with Known Vulnerabilities - VAPTORDISCOVERY	www.adsl.vf	P3 - MEDIUM, Components with Known Vulnerabilities - VAPTORDISCOVERY, www.adsl.vf, CVE-2020-25685 4.3 https://vulners.com/cve/CVE-2
MEDIUM	Components with Known	www.adsl.vf	P3 - MEDIUM, Components with Known Vulnerabilities -

Severity	Type	Host	Detail
	Vulnerabilities - VAPTORDISCOVERY		VAPTORDISCOVERY, www.adsl.vf, CVE-2020-25686 4.3 https://vulners.com/cve/CVE-2
MEDIUM	Components with Known Vulnerabilities - VAPTORDISCOVERY	www.adsl.vf	P3 - MEDIUM, Components with Known Vulnerabilities - VAPTORDISCOVERY, www.adsl.vf, CVE-2020-25687 7.1 https://vulners.com/cve/CVE-2
MEDIUM	Components with Known Vulnerabilities - VAPTORDISCOVERY	www.adsl.vf	P3 - MEDIUM, Components with Known Vulnerabilities - VAPTORDISCOVERY, www.adsl.vf, CVE-2021-3448 4.3 https://vulners.com/cve/CVE-20
MEDIUM	Components with Known Vulnerabilities - VAPTORDISCOVERY	www.adsl.vf	P3 - MEDIUM, Components with Known Vulnerabilities - VAPTORDISCOVERY, www.adsl.vf, CVE-2022-0934 7.5 https://vulners.com/cve/CVE-20
MEDIUM	Components with Known	www.adsl.vf	P3 - MEDIUM, Components with Known Vulnerabilities -

Severity	Type	Host	Detail
	Vulnerabilities - VAPTORDISCOVERY		VAPTORDISCOVERY, www.adsl.vf, CVE-2023-28450 7.5 https://vulners.com/cve/CVE-2
MEDIUM	Components with Known Vulnerabilities - VAPTORDISCOVERY	www.adsl.vf	P3 - MEDIUM, Components with Known Vulnerabilities - VAPTORDISCOVERY, www.adsl.vf, CVE-2023-50387 7.5 https://vulners.com/cve/CVE-2
LOW	Strict Tranposrt Security Not Enforced	https://10.0.0.103:443//	P4 - LOW, Strict Tranposrt Security Not Enforced, https://10.0.0.103:443//,
LOW	Strict Tranposrt Security Not Enforced	https://www.adsl.vf:443//	P4 - LOW, Strict Tranposrt Security Not Enforced, https://www.adsl.vf:443//,
INFORMATIONAL	Interesting Ports Found	10.0.0.132	P5 - INFO, Interesting Ports Found, 10.0.0.132, 22
INFORMATIONAL	Interesting Ports Found	www.adsl.vf	P5 - INFO, Interesting Ports Found, www.adsl.vf, 53
INFORMATIONAL		[caa-fingerprint]	

Severity	Type	Host	Detail
	VAPTORRECON Vulnerability Scan		P5 - INFO, VAPTORRECON Vulnerability Scan, [caa-fingerprint], ec2-44-238-29-244.us-west-2.compute.amazonaws.com
INFORMATIONAL	VAPTORRECON Vulnerability Scan	[default-windows-server-page]	P5 - INFO, VAPTORRECON Vulnerability Scan, [default-windows-server-page], http://ec2-44-238-29-244.us-west-2.compute.amazonaw
INFORMATIONAL	VAPTORRECON Vulnerability Scan	[ec2-detection]	P5 - INFO, VAPTORRECON Vulnerability Scan, [ec2-detection], ec2-44-238-29-244.us-west-2.compute.amazonaws.com [ec2-44-238-29-
INFORMATIONAL	VAPTORRECON Vulnerability Scan	[http-missing-security-headers:clear-site-data]	P5 - INFO, VAPTORRECON Vulnerability Scan, [http-missing-security-headers:clear-site-data], http://ec2-44-238-29-244.us-west-
INFORMATIONAL	VAPTORRECON Vulnerability Scan	[http-missing-security-headers:content-security-policy]	P5 - INFO, VAPTORRECON Vulnerability Scan, [http-missing-

Severity	Type	Host	Detail
			security-headers:content-security-policy], http://ec2-44-238-29-244.
INFORMATIONAL	VAPTORRECON Vulnerability Scan	[http-missing-security-headers:cross-origin-embedder-policy]	P5 - INFO, VAPTORRECON Vulnerability Scan, [http-missing-security-headers:cross-origin-embedder-policy], http://ec2-44-238-29
INFORMATIONAL	VAPTORRECON Vulnerability Scan	[http-missing-security-headers:cross-origin-opener-policy]	P5 - INFO, VAPTORRECON Vulnerability Scan, [http-missing-security-headers:cross-origin-opener-policy], http://ec2-44-238-29-2
INFORMATIONAL	VAPTORRECON Vulnerability Scan	[http-missing-security-headers:cross-origin-resource-policy]	P5 - INFO, VAPTORRECON Vulnerability Scan, [http-missing-security-headers:cross-origin-resource-policy], http://ec2-44-238-29
INFORMATIONAL	VAPTORRECON Vulnerability Scan	[http-missing-security-headers:missing-content-type]	P5 - INFO, VAPTORRECON Vulnerability Scan, [http-missing-security-headers:missing-content-type], http://ec2-44-238-29-244.us-

Severity	Type	Host	Detail
INFORMATIONAL	VAPTORRECON Vulnerability Scan	[http-missing-security-headers:permissions-policy]	P5 - INFO, VAPTORRECON Vulnerability Scan, [http-missing-security-headers:permissions-policy], http://ec2-44-238-29-244.us-we
INFORMATIONAL	VAPTORRECON Vulnerability Scan	[http-missing-security-headers:referrer-policy]	P5 - INFO, VAPTORRECON Vulnerability Scan, [http-missing-security-headers:referrer-policy], http://ec2-44-238-29-244.us-west-
INFORMATIONAL	VAPTORRECON Vulnerability Scan	[http-missing-security-headers:strict-transport-security]	P5 - INFO, VAPTORRECON Vulnerability Scan, [http-missing-security-headers:strict-transport-security], http://ec2-44-238-29-24
INFORMATIONAL	VAPTORRECON Vulnerability Scan	[http-missing-security-headers:x-content-type-options]	P5 - INFO, VAPTORRECON Vulnerability Scan, [http-missing-security-headers:x-content-type-options], http://ec2-44-238-29-244.u
INFORMATIONAL	VAPTORRECON Vulnerability Scan	[http-missing-security-headers:x-frame-options]	P5 - INFO, VAPTORRECON Vulnerability Scan, [http-missing-security-headers:x-frame-options], http://ec2-44-238-29-244.us-west-

Severity	Type	Host	Detail
INFORMATIONAL	VAPTORRECON Vulnerability Scan	[http-missing-security-headers:x-permitted-cross-domain-policies]	P5 - INFO, VAPTORRECON Vulnerability Scan, [http-missing-security-headers:x-permitted-cross-domain-policies], http://ec2-44-2
INFORMATIONAL	VAPTORRECON Vulnerability Scan	[microsoft-iis-version]	P5 - INFO, VAPTORRECON Vulnerability Scan, [microsoft-iis-version], http://ec2-44-238-29-244.us-west-2.compute.amazonaws.com:
INFORMATIONAL	VAPTORRECON Vulnerability Scan	[options-method]	P5 - INFO, VAPTORRECON Vulnerability Scan, [options-method], http://ec2-44-238-29-244.us-west-2.compute.amazonaws.com:80 [OPT
INFORMATIONAL	VAPTORRECON Vulnerability Scan	[tech-detect:ms-iis]	P5 - INFO, VAPTORRECON Vulnerability Scan, [tech-detect:ms-iis], http://ec2-44-238-29-244.us-west-2.compute.amazonaws.com:80
INFORMATIONAL	VAPTORRECON Vulnerability Scan	[tls-version]	P5 - INFO, VAPTORRECON Vulnerability Scan, [tls-version], www.adsl.vf:443 [tls13]

Severity	Type	Host	Detail
INFORMATIONAL	VAPTORRECON Vulnerability Scan	[waf-detect:aspgeneric]	P5 - INFO, VAPTORRECON Vulnerability Scan, [waf-detect:aspgeneric], http://ec2-44-238-29-244.us-west-2.compute.amazonaws.com:
INFORMATIONAL	VAPTORRECON Vulnerability Scan	[waf-detect:modsecurity]	P5 - INFO, VAPTORRECON Vulnerability Scan, [waf-detect:modsecurity], http://ec2-44-238-29-244.us-west-2.compute.amazonaws.com
INFORMATIONAL	VAPTORRECON Vulnerability Scan	[weak-csp-detect:unsafe-default-src]	P5 - INFO, VAPTORRECON Vulnerability Scan, [weak-csp-detect:unsafe-default-src], http://www.adsl.vf:80 [default-src 'self' 'u
INFORMATIONAL	Server Header Disclosure - HTTP	http://ec2-44-238-29-244.us-west-2.compute.amazonaws.com:80//	P5 - INFO, Server Header Disclosure - HTTP, http://ec2-44-238-29-244.us-west-2.compute.amazonaws.com:80//, Server: Micro

Note: Review full loot in artifacts/sniper/loot/ and sniper_summary.json

3) Technical Details (Per Asset)

Asset: VAPTOR001A0001

Asset fingerprint

Field	Value
MAC Address	N/A
IP	44.228.249.3
Hostname	ec2-44-228-249-3.us-west-2.compute.amazonaws.com
OS fingerprint	N/A

Open ports

None recorded.

Watchdog mini-recap

- **Exposed:** 0 open port(s), 0 high-risk service(s).
- **Vulnerable:** 0 finding(s) (Critical 0, High 0, Medium 0).

- **Evidence:** 0/0 finding(s) include evidence snippets.
- **Remediation:** 0/0 finding(s) include remediation guidance.

Vulnerabilities

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

None found.

Asset: VAPTOR001A0002

Asset fingerprint

Field	Value
MAC Address	N/A
IP	44.238.29.244
Hostname	ec2-44-238-29-244.us-west-2.compute.amazonaws.com
OS fingerprint	Microsoft Windows Server 2012 or Windows Server 2012 R2

Open ports

Proto	Port	Service	Risk
tcp	80	http	HIGH

High-risk port notes (VaptorAI / Intel DB)

Port exposure notes (VaptorAI): tcp/80 http [HIGH]

Narrative

```
# Port Exposure: tcp/80

## Summary
An Internet-accessible service was detected on tcp/80. Exposed management and remote-
access ports are frequently targeted for credential attacks and exploitation.

## Why this matters (Risk)
- Increases attack surface and brute-force exposure
- May permit remote code execution if vulnerable and unpatched
- Often enables lateral movement once credentials are obtained

## Recommended actions (Remediation)
- Restrict access (VPN/jump host/allowlist)
- Enforce MFA and strong authentication policies
- Patch the exposed service and disable legacy/insecure options
```

```
## Evidence
- Observed open: tcp/80
```

Port exposure notes: tcp/80 http [HIGH]

Why this matters Unencrypted web traffic; web application vulnerabilities, MitM attacks

Common attacksSQL Injection, XSS, CSRF, Directory Traversal, Man-in-the-Middle, Session Hijacking

Notable CVEsCVE-2021-44228, CVE-2017-5638, CVE-2014-0160

Recommended action Redirect all traffic to HTTPS (port 443). Disable HTTP or use only for redirect. Implement HSTS headers.

Watchdog mini-recap

- **Exposed:** 1 open port(s), 1 high-risk service(s).
  Top: tcp/80 http [HIGH]
- **Vulnerable:** 41 finding(s) (Critical 0, High 9, Medium 9).
- **Evidence:** 38/41 finding(s) include evidence snippets.
- **Remediation:** 36/41 finding(s) include remediation guidance.
  Suggested: Do not trust client side input, even if there is client side validation in place.In general, type check all data on the server side.If the application uses JDBC, use PreparedSta...; Do not trust client side

input, even if there is client side validation in place.In general, type check all data on the server side.If the application uses JDBC, use PreparedSta...

Vulnerabilities (41)

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

Severity	Title	CVE	CVSS
HIGH	Clear-Text Protocol - HTTP	—	8.0
HIGH	SQL Injection - MsSQL (Time Based)	—	8.0
HIGH	SQL Injection	—	8.0
HIGH	Cross Site Scripting (Reflected)	—	8.0
HIGH	SQL Injection - MsSQL (Time Based)	—	8.0
HIGH	SQL Injection	—	8.0
HIGH	Path Traversal	—	8.0
HIGH	External Redirect	—	8.0
HIGH	Cross Site Scripting (Reflected)	—	8.0
MEDIUM	Components with Known Vulnerabilities - VAPTORDISCOVERY	—	5.0

Severity	Title	CVE	CVSS
MEDIUM	Missing Anti-clickjacking Header	—	5.0
MEDIUM	HTTP Only Site	—	5.0
MEDIUM	Content Security Policy (CSP) Header Not Set	—	5.0
MEDIUM	Absence of Anti-CSRF Tokens	—	5.0
MEDIUM	Missing Anti-clickjacking Header	—	5.0
MEDIUM	HTTP Only Site	—	5.0
MEDIUM	Content Security Policy (CSP) Header Not Set	—	5.0
MEDIUM	Absence of Anti-CSRF Tokens	—	5.0
LOW	X-Content-Type-Options Header Missing	—	2.5
LOW	X-AspNet-Version Response Header	—	2.5
LOW	Server Leaks Version Information via "Server" HTTP Response Header Field	—	2.5
LOW	Server Leaks Information via "X-Powered-By" HTTP Response Header Field(s)	—	2.5
LOW	Cookie without SameSite Attribute	—	2.5
LOW	X-Content-Type-Options Header Missing	—	2.5

Severity	Title	CVE	CVSS
LOW	Server Leaks Version Information via "Server" HTTP Response Header Field	—	2.5
LOW	Server Leaks Information via "X-Powered-By" HTTP Response Header Field(s)	—	2.5
LOW	Information Disclosure - Debug Error Messages	—	2.5
LOW	Cookie without SameSite Attribute	—	2.5
LOW	Cookie No HttpOnly Flag	—	2.5
LOW	Application Error Disclosure	—	2.5
INFO	Server Header Disclosure - HTTP	—	0.0
INFO	User Controllable HTML Element Attribute (Potential XSS)	—	0.0
INFO	User Agent Fuzzer	—	0.0
INFO	Session Management Response Identified	—	0.0
INFO	GET for POST	—	0.0
INFO	Charset Mismatch (Header Versus Meta Content-Type Charset)	—	0.0
INFO	Authentication Request Identified	—	0.0
INFO	User Agent Fuzzer	—	0.0

Severity	Title	CVE	CVSS
INFO	Session Management Response Identified	—	0.0
INFO	Modern Web Application	—	0.0
INFO	Information Disclosure - Suspicious Comments	—	0.0

Finding notes: SQL Injection - MsSQL (Time Based)

Description

```
SQL injection may be possible.
```

Evidence

```
Target: http://testaspnet.vulnweb.com/ReadNews.aspx?NewsAd=ads/def.html&id=2 | Finding:
SQL Injection - MsSQL (Time Based) | Reported Severity: high
```

Remediation

```
Do not trust client side input, even if there is client side validation in place.In
general, type check all data on the server side.If the application uses JDBC, use
PreparedStatement or CallableStatement, with parameters passed by '?'If the application
uses ASP, use ADO Command Objects with strong type checking and parameterized queries.If
database Stored Procedures can be used, use them.Do *not* concatenate strings into
queries in the stored procedure, or use 'exec', 'exec immediate', or equivalent
functionality!Do not create dynamic SQL queries using simple string concatenation.Escape
```

```
all data received from the client.Apply an 'allow list' of allowed characters, or a 'deny
list' of disallowed characters in user input.Apply the principle of least privilege by
using the least privileged database user possible.In particular, avoid using the 'sa' or
'db-owner' database users. This does not eliminate SQL injection, but minimizes its
impact.Grant the minimum database access that is necessary for the application.
```

Remediation (detailed)

Effort: 4-8 hours per affected query
Business impact: CRITICAL - Can lead to complete data breach, data manipulation, or system compromise

1. Use parameterized queries (prepared statements) for all database interactions
2. Implement input validation with whitelist approach
3. Apply principle of least privilege for database accounts
4. Enable database query logging and monitoring
5. Use ORM frameworks with proper configuration

Verification:

- Test with common SQL injection payloads (e.g., ' OR '1'='1)
- Use automated scanners (VAPTORSQL, Burp Suite) to verify fix
- Review code for dynamic query construction
- Implement automated security testing in CI/CD pipeline

References:

- https://cheatsheetseries.owasp.org/cheatsheets/SQL_Injection_Prevention_Cheat_Sheet.html
- https://owasp.org/www-community/attacks/SQL_Injection
- https://cwe.mitre.org/data/definitions/89.html

Finding notes: SQL Injection

Description

```
SQL injection may be possible.
```

Evidence

```
Target: http://testaspnet.vulnweb.com/Comments.aspx?id=4-2 | Finding: SQL Injection |
Reported Severity: high
```

Remediation

```
Do not trust client side input, even if there is client side validation in place.In
general, type check all data on the server side.If the application uses JDBC, use
PreparedStatement or CallableStatement, with parameters passed by '?'If the application
uses ASP, use ADO Command Objects with strong type checking and parameterized queries.If
database Stored Procedures can be used, use them.Do *not* concatenate strings into
queries in the stored procedure, or use 'exec', 'exec immediate', or equivalent
functionality!Do not create dynamic SQL queries using simple string concatenation.Escape
all data received from the client.Apply an 'allow list' of allowed characters, or a 'deny
list' of disallowed characters in user input.Apply the principle of least privilege by
using the least privileged database user possible.In particular, avoid using the 'sa' or
'db-owner' database users. This does not eliminate SQL injection, but minimizes its
impact.Grant the minimum database access that is necessary for the application.
```

Remediation (detailed)

Effort: 4-8 hours per affected query
Business impact: CRITICAL - Can lead to complete data breach, data manipulation, or system compromise

1. Use parameterized queries (prepared statements) for all database interactions
2. Implement input validation with whitelist approach
3. Apply principle of least privilege for database accounts
4. Enable database query logging and monitoring
5. Use ORM frameworks with proper configuration

Verification:

- Test with common SQL injection payloads (e.g., ' OR '1'='1)
- Use automated scanners (VAPTORSQL, Burp Suite) to verify fix
- Review code for dynamic query construction
- Implement automated security testing in CI/CD pipeline

References:

- https://cheatsheetseries.owasp.org/cheatsheets/SQL_Injection_Prevention_Cheat_Sheet.html
- https://owasp.org/www-community/attacks/SQL_Injection
- https://cwe.mitre.org/data/definitions/89.html

Finding notes: Cross Site Scripting (Reflected)

Description

```
Cross-site Scripting (XSS) is an attack technique that involves echoing attacker-supplied
code into a user's browser instance. A browser instance can be a standard web browser
```

client, or a browser object embedded in a software product such as the browser within WinAmp, an RSS reader, or an email client. The code itself is usually written in HTML/JavaScript, but may also extend to VBScript, ActiveX, Java, Flash, or any other browser-supported technology.When an attacker gets a user's browser to execute his/her code, the code will run within the security context (or zone) of the hosting web site. With this level of privilege, the code has the ability to read, modify and transmit any sensitive data accessible by the browser. A Cross-site Scripted user could have his/her account hijacked (cookie theft), their browser redirected to another location, or possibly shown fraudulent content delivered by the web site they are visiting. Cross-site Scripting attacks essentially compromise the trust relationship between a user and the web site. Applications utilizing browser object instances which load content from the file system may execute code under the local machine zone allowing for system compromise.There are three types of Cross-site Scripting attacks: non-persistent, persistent and DOM-based.Non-persistent attacks and DOM-based attacks require a user to either visit a specially crafted link laced with malicious code, or visit a malicious web page containing a web form, which when posted to the vulnerable site, will mount the attack. Using a malicious form will oftentimes take place when the vulnerable resource only accepts HTTP POST requests. In such a case, the form can be submitted automatically, without the victim's knowledge (e.g. by using JavaScript). Upon clicking on the malicious link or submitting the malicious form, the XSS payload will get echoed back and will get interpreted by the user's browser and execute. Another technique to send almost arbitrary requests (GET and POST) is by using an embedded client, such as Adobe Flash.Persistent attacks occur when the malicious code is submitted to a web site where it's stored for a period of time. Examples of a...

Evidence

```
Target: http://testaspnet.vulnweb.com/ReadNews.aspx?
NewsAd=javascript%3Aalert%281%29%3B&id=2 | Finding: Cross Site Scripting (Reflected) |
Reported Severity: high
```

Remediation

```
Phase: Architecture and DesignUse a vetted library or framework that does not allow this
weakness to occur or provides constructs that make this weakness easier to avoid.Examples
of libraries and frameworks that make it easier to generate properly encoded output
include Microsoft's Anti-XSS library, the OWASP ESAPI Encoding module, and Apache
Wicket.Phases: Implementation; Architecture and DesignUnderstand the context in which
your data will be used and the encoding that will be expected. This is especially
important when transmitting data between different components, or when generating outputs
that can contain multiple encodings at the same time, such as web pages or multi-part
mail messages. Study all expected communication protocols and data representations to
determine the required encoding strategies.For any data that will be output to another
web page, especially any data that was received from external inputs, use the appropriate
encoding on all non-alphanumeric characters.Consult the XSS Prevention Cheat Sheet for
more details on the types of encoding and escaping that are needed.Phase: Architecture
and DesignFor any security checks that are performed on the client side, ensure that
these checks are duplicated on the server side, in order to avoid CWE-602. Attackers can
bypass the client-side checks by modifying values after the checks have been performed,
or by changing the client to remove the client-side checks entirely. Then, these modified
```

```
values would be submitted to the server.If available, use structured mechanisms that
automatically enforce the separati...
```

Remediation (detailed)

Effort: Variable
Business impact: Depends on vulnerability context

1. Phase: Architecture and DesignUse a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid.Examples of libraries and frameworks that make it easier to generate properly encoded output include Microsoft's Anti-XSS library, the OWASP ESAPI Encoding module, and Apache Wicket.Phases: Implementation; Architecture and DesignUnderstand the con...

References:

- https://owasp.org/www-community/attacks/xss/
- https://cwe.mitre.org/data/definitions/79.html

Finding notes: SQL Injection - MsSQL (Time Based)

Description

```
SQL injection may be possible.
```

Evidence

```
Target: http://testasp.vulnweb.com/Login.asp?RetURL=%2Fshowthread%2Easp%3Fid%3D3 |
Finding: SQL Injection - MsSQL (Time Based) | Reported Severity: high
```

Remediation

```
Do not trust client side input, even if there is client side validation in place.In
general, type check all data on the server side.If the application uses JDBC, use
PreparedStatement or CallableStatement, with parameters passed by '?'If the application
uses ASP, use ADO Command Objects with strong type checking and parameterized queries.If
database Stored Procedures can be used, use them.Do *not* concatenate strings into
queries in the stored procedure, or use 'exec', 'exec immediate', or equivalent
functionality!Do not create dynamic SQL queries using simple string concatenation.Escape
all data received from the client.Apply an 'allow list' of allowed characters, or a 'deny
list' of disallowed characters in user input.Apply the principle of least privilege by
using the least privileged database user possible.In particular, avoid using the 'sa' or
'db-owner' database users. This does not eliminate SQL injection, but minimizes its
impact.Grant the minimum database access that is necessary for the application.
```

Remediation (detailed)

Effort: 4-8 hours per affected query
Business impact: CRITICAL - Can lead to complete data breach, data manipulation, or system compromise

1. Use parameterized queries (prepared statements) for all database interactions
2. Implement input validation with whitelist approach
3. Apply principle of least privilege for database accounts
4. Enable database query logging and monitoring

5. Use ORM frameworks with proper configuration

Verification:

- Test with common SQL injection payloads (e.g., ' OR '1'='1)
- Use automated scanners (VAPTORSQL, Burp Suite) to verify fix
- Review code for dynamic query construction
- Implement automated security testing in CI/CD pipeline

References:

- https://cheatsheetseries.owasp.org/cheatsheets/SQL_Injection_Prevention_Cheat_Sheet.html
- https://owasp.org/www-community/attacks/SQL_Injection
- https://cwe.mitre.org/data/definitions/89.html

Finding notes: SQL Injection

Description

```
SQL injection may be possible.
```

Evidence

```
Target: http://testasp.vulnweb.com/Search.asp?tfSearch=VAPTORWEB%27 | Finding: SQL
Injection | Reported Severity: high
```

Remediation

```
Do not trust client side input, even if there is client side validation in place.In
general, type check all data on the server side.If the application uses JDBC, use
PreparedStatement or CallableStatement, with parameters passed by '?'If the application
uses ASP, use ADO Command Objects with strong type checking and parameterized queries.If
database Stored Procedures can be used, use them.Do *not* concatenate strings into
queries in the stored procedure, or use 'exec', 'exec immediate', or equivalent
functionality!Do not create dynamic SQL queries using simple string concatenation.Escape
all data received from the client.Apply an 'allow list' of allowed characters, or a 'deny
list' of disallowed characters in user input.Apply the principle of least privilege by
using the least privileged database user possible.In particular, avoid using the 'sa' or
'db-owner' database users. This does not eliminate SQL injection, but minimizes its
impact.Grant the minimum database access that is necessary for the application.
```

Remediation (detailed)

Effort: 4-8 hours per affected query
Business impact: CRITICAL - Can lead to complete data breach, data manipulation, or system compromise

1. Use parameterized queries (prepared statements) for all database interactions
2. Implement input validation with whitelist approach
3. Apply principle of least privilege for database accounts
4. Enable database query logging and monitoring
5. Use ORM frameworks with proper configuration

Verification:

- Test with common SQL injection payloads (e.g., ' OR '1'='1)

- Use automated scanners (VAPTORSQL, Burp Suite) to verify fix
- Review code for dynamic query construction
- Implement automated security testing in CI/CD pipeline

References:

- https://cheatsheetseries.owasp.org/cheatsheets/SQL_Injection_Prevention_Cheat_Sheet.html
- https://owasp.org/www-community/attacks/SQL_Injection
- https://cwe.mitre.org/data/definitions/89.html

Finding notes: Path Traversal

Description

```
The Path Traversal attack technique allows an attacker access to files, directories, and
commands that potentially reside outside the web document root directory. An attacker may
manipulate a URL in such a way that the web site will execute or reveal the contents of
arbitrary files anywhere on the web server. Any device that exposes an HTTP-based
interface is potentially vulnerable to Path Traversal.Most web sites restrict user access
to a specific portion of the file-system, typically called the "web document root" or
"CGI root" directory. These directories contain the files intended for user access and
the executable necessary to drive web application functionality. To access files or
execute commands anywhere on the file-system, Path Traversal attacks will utilize the
ability of special-characters sequences.The most basic Path Traversal attack uses the
"../" special-character sequence to alter the resource location requested in the URL.
Although most popular web servers will prevent this technique from escaping the web
```

```
document root, alternate encodings of the "../" sequence may help bypass the security
filters. These method variations include valid and invalid Unicode-encoding ("..%u2216"
or "..%c0%af") of the forward slash character, backslash characters ("..\") on Windows-
based servers, URL encoded characters "%2e%2e%2f"), and double URL encoding ("..%255c")
of the backslash character.Even if the web server properly restricts Path Traversal
attempts in the URL path, a web application itself may still be vulnerable due to
improper handling of user-supplied input. This is a common problem of web applications
that use template mechanisms or load static text from files. In variations of the attack,
the original URL parameter value is substituted with the file name of one of the web
application's dynamic scripts. Consequently, the results can reveal source code because
the file is interpreted as text instead of an executable script. These techniques often
employ additional special characters such as the dot (".") to reveal the listing of the
current working directory, or "%00" NULL characters in order to bypass rudimentary file
extension checks.
```

Evidence

```
Target: http://testasp.vulnweb.com/Register.asp?RetURL=%2Fshowthread%2Easp%3Fid%3D3 |
Finding: Path Traversal | Reported Severity: high
```

Remediation

```
Assume all input is malicious. Use an "accept known good" input validation strategy,
i.e., use an allow list of acceptable inputs that strictly conform to specifications.
Reject any input that does not strictly conform to specifications, or transform it into
something that does. Do not rely exclusively on looking for malicious or malformed inputs
```

```
(i.e., do not rely on a deny list). However, deny lists can be useful for detecting
potential attacks or determining which inputs are so malformed that they should be
rejected outright.When performing input validation, consider all potentially relevant
properties, including length, type of input, the full range of acceptable values, missing
or extra inputs, syntax, consistency across related fields, and conformance to business
rules. As an example of business rule logic, "boat" may be syntactically valid because it
only contains alphanumeric characters, but it is not valid if you are expecting colors
such as "red" or "blue."For filenames, use stringent allow lists that limit the character
set to be used. If feasible, only allow a single "." character in the filename to avoid
weaknesses, and exclude directory separators such as "/". Use an allow list of allowable
file extensions.Warning: if you attempt to cleanse your data, then do so that the end
result is not in the form that can be dangerous. A sanitizing mechanism can remove
characters such as '.' and ';' which may be required for some exploits. An attacker can
try to fool the sanitizing mechanism into "cleaning" data into a dangerous form. Suppose
the attacker injects a '.' ...
```

Remediation (detailed)

Effort: 2-4 hours
Business impact: HIGH - Prevents unauthorized file access and information disclosure

1. Validate and sanitize all file path inputs
2. Use whitelist of allowed files/directories
3. Avoid passing user input directly to file system APIs
4. Use path canonicalization to resolve relative paths
5. Implement proper access controls on file system

Verification:

- Test with ../../../etc/passwd
- Test with URL-encoded traversal: ..%2F..%2F..%2Fetc%2Fpasswd
- Test with double encoding
- Verify whitelist is enforced

References:

- https://owasp.org/www-community/attacks/Path_Traversal
- https://cwe.mitre.org/data/definitions/22.html

Finding notes: External Redirect

Description

```
URL redirectors represent common functionality employed by web sites to forward an
incoming request to an alternate resource. This can be done for a variety of reasons and
is often done to allow resources to be moved within the directory structure and to avoid
breaking functionality for users that request the resource at its previous location. URL
redirectors may also be used to implement load balancing, leveraging abbreviated URLs or
recording outgoing links. It is this last implementation which is often used in phishing
attacks as described in the example below. URL redirectors do not necessarily represent a
direct security vulnerability but can be abused by attackers trying to social engineer
victims into believing that they are navigating to a site other than the true
destination.
```

Evidence

```
Target: http://testasp.vulnweb.com/Logout.asp?
RetURL=https%3A%2F%2F5141385043261541070.owasp.org | Finding: External Redirect |
Reported Severity: high
```

Remediation

```
Assume all input is malicious. Use an "accept known good" input validation strategy,
i.e., use an allow list of acceptable inputs that strictly conform to specifications.
Reject any input that does not strictly conform to specifications, or transform it into
something that does. Do not rely exclusively on looking for malicious or malformed inputs
(i.e., do not rely on a deny list). However, deny lists can be useful for detecting
potential attacks or determining which inputs are so malformed that they should be
rejected outright.When performing input validation, consider all potentially relevant
properties, including length, type of input, the full range of acceptable values, missing
or extra inputs, syntax, consistency across related fields, and conformance to business
rules. As an example of business rule logic, "boat" may be syntactically valid because it
only contains alphanumeric characters, but it is not valid if you are expecting colors
such as "red" or "blue."Use an allow list of approved URLs or domains to be used for
redirection.Use an intermediate disclaimer page that provides the user with a clear
warning that they are leaving your site. Implement a long timeout before the redirect
occurs, or force the user to click on the link. Be careful to avoid XSS problems when
generating the disclaimer page.When the set of acceptable objects, such as filenames or
URLs, is limited or known, create a mapping from a set of fixed input values (such as
```

```
numeric IDs) to the actual filenames or URLs, and reject all other inputs.For example, ID
1 could map to "/login.asp" and ID ...
```

Remediation (detailed)

Effort: Variable
Business impact: Depends on vulnerability context

1. Assume all input is malicious. Use an "accept known good" input validation strategy, i.e., use an allow list of acceptable inputs that strictly conform to specifications. Reject any input that does not strictly conform to specifications, or transform it into something that does. Do not rely exclusively on looking for malicious or malformed inputs (i.e., do not rely on a deny list). However, deny lists can be usefu...

References:

- https://cheatsheetseries.owasp.org/cheatsheets/Unvalidated_Redirects_and_Forwards_Cheat_Sheet.html
- https://cwe.mitre.org/data/definitions/601.html

Finding notes: Cross Site Scripting (Reflected)

Description

```
Cross-site Scripting (XSS) is an attack technique that involves echoing attacker-supplied
code into a user's browser instance. A browser instance can be a standard web browser
client, or a browser object embedded in a software product such as the browser within
WinAmp, an RSS reader, or an email client. The code itself is usually written in HTML/
JavaScript, but may also extend to VBScript, ActiveX, Java, Flash, or any other browser-
```

supported technology.When an attacker gets a user's browser to execute his/her code, the code will run within the security context (or zone) of the hosting web site. With this level of privilege, the code has the ability to read, modify and transmit any sensitive data accessible by the browser. A Cross-site Scripted user could have his/her account hijacked (cookie theft), their browser redirected to another location, or possibly shown fraudulent content delivered by the web site they are visiting. Cross-site Scripting attacks essentially compromise the trust relationship between a user and the web site. Applications utilizing browser object instances which load content from the file system may execute code under the local machine zone allowing for system compromise.There are three types of Cross-site Scripting attacks: non-persistent, persistent and DOM-based.Non-persistent attacks and DOM-based attacks require a user to either visit a specially crafted link laced with malicious code, or visit a malicious web page containing a web form, which when posted to the vulnerable site, will mount the attack. Using a malicious form will oftentimes take place when the vulnerable resource only accepts HTTP POST requests. In such a case, the form can be submitted automatically, without the victim's knowledge (e.g. by using JavaScript). Upon clicking on the malicious link or submitting the malicious form, the XSS payload will get echoed back and will get interpreted by the user's browser and execute. Another technique to send almost arbitrary requests (GET and POST) is by using an embedded client, such as Adobe Flash.Persistent attacks occur when the malicious code is submitted to a web site where it's stored for a period of time. Examples of a...

Evidence

```
Target: http://testasp.vulnweb.com/Search.asp?
tfSearch=%3C%2Fdiv%3E%3CscrIpt%3Ealert%281%29%3B%3C%2FscRipt%3E%3Cdiv%3E | Finding: Cross
Site Scripting (Reflected) | Reported Severity: high
```

Remediation

```
Phase: Architecture and DesignUse a vetted library or framework that does not allow this
weakness to occur or provides constructs that make this weakness easier to avoid.Examples
of libraries and frameworks that make it easier to generate properly encoded output
include Microsoft's Anti-XSS library, the OWASP ESAPI Encoding module, and Apache
Wicket.Phases: Implementation; Architecture and DesignUnderstand the context in which
your data will be used and the encoding that will be expected. This is especially
important when transmitting data between different components, or when generating outputs
that can contain multiple encodings at the same time, such as web pages or multi-part
mail messages. Study all expected communication protocols and data representations to
determine the required encoding strategies.For any data that will be output to another
web page, especially any data that was received from external inputs, use the appropriate
encoding on all non-alphanumeric characters.Consult the XSS Prevention Cheat Sheet for
more details on the types of encoding and escaping that are needed.Phase: Architecture
and DesignFor any security checks that are performed on the client side, ensure that
these checks are duplicated on the server side, in order to avoid CWE-602. Attackers can
bypass the client-side checks by modifying values after the checks have been performed,
or by changing the client to remove the client-side checks entirely. Then, these modified
```

```
values would be submitted to the server.If available, use structured mechanisms that
automatically enforce the separati...
```

Remediation (detailed)

Effort: Variable
Business impact: Depends on vulnerability context

1. Phase: Architecture and DesignUse a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid.Examples of libraries and frameworks that make it easier to generate properly encoded output include Microsoft's Anti-XSS library, the OWASP ESAPI Encoding module, and Apache Wicket.Phases: Implementation; Architecture and DesignUnderstand the con...

References:

- https://owasp.org/www-community/attacks/xss/
- https://cwe.mitre.org/data/definitions/79.html

Finding notes: Missing Anti-clickjacking Header

Description

```
The response does not protect against 'ClickJacking' attacks. It should include either
Content-Security-Policy with 'frame-ancestors' directive or X-Frame-Options.
```

Evidence

```
Target: http://testaspnet.vulnweb.com | Finding: Missing Anti-clickjacking Header |
Reported Severity: medium
```

Remediation

```
Modern Web browsers support the Content-Security-Policy and X-Frame-Options HTTP headers.
Ensure one of them is set on all web pages returned by your site/app.If you expect the
page to be framed only by pages on your server (e.g. it's part of a FRAMESET) then you'll
want to use SAMEORIGIN, otherwise if you never expect the page to be framed, you should
use DENY. Alternatively consider implementing Content Security Policy's "frame-ancestors"
directive.
```

Remediation (detailed)

Effort: Variable
Business impact: Depends on vulnerability context

1. Modern Web browsers support the Content-Security-Policy and X-Frame-Options HTTP headers. Ensure one of them is set on all web pages returned by your site/app.If you expect the page to be framed only by pages on your server (e.g. it's part of a FRAMESET) then you'll want to use SAMEORIGIN, otherwise if you never expect the page to be framed, you should use DENY. Alternatively consider implementing Content Security...

References:

- https://developer.mozilla.org/en-US/docs/Web/HTTP/Reference/Headers/X-Frame-Options

Finding notes: HTTP Only Site

Description

```
The site is only served under HTTP and not HTTPS.
```

Evidence

```
Target: http://testaspnet.vulnweb.com/Comments.aspx?id=0 | Finding: HTTP Only Site |
Reported Severity: medium
```

Remediation

```
Configure your web or application server to use SSL (https).
```

Remediation (detailed)

Effort: Variable
Business impact: Depends on vulnerability context

1. Configure your web or application server to use SSL (https).

References:

- https://cheatsheetseries.owasp.org/cheatsheets/Transport_Layer_Protection_Cheat_Sheet.html
- https://letsencrypt.org/

Asset: VAPTOR001A0003

Asset fingerprint

Field	Value
MAC Address	B8:27:EB:74:F2:6C
IP	10.0.0.132
Hostname	10.0.0.132
OS fingerprint	Linux 4.15 - 5.19

Open ports

Proto	Port	Service	Risk
tcp	22	ssh	HIGH
tcp	7070	realserver	—

High-risk port notes (VaptorAI / Intel DB)

Port exposure notes (VaptorAI): tcp/22 ssh [HIGH]

Narrative

```
# Port Exposure: tcp/22

## Summary
An Internet-accessible service was detected on tcp/22. Exposed management and remote-
access ports are frequently targeted for credential attacks and exploitation.

## Why this matters (Risk)
- Increases attack surface and brute-force exposure
- May permit remote code execution if vulnerable and unpatched
- Often enables lateral movement once credentials are obtained

## Recommended actions (Remediation)
- Restrict access (VPN/jump host/allowlist)
- Enforce MFA and strong authentication policies
- Patch the exposed service and disable legacy/insecure options

## Evidence
- Observed open: tcp/22
```

Port exposure notes: tcp/22 ssh [HIGH]

Why this matters Remote shell access; brute-force, key reuse, weak credentials

Common attacks Brute Force, Credential Stuffing, Private Key Theft, Man-in-the-Middle

Notable CVEsCVE-2016-20012, CVE-2018-15473, CVE-2021-28041

Recommended action Implement key-based authentication only. Disable password authentication. Use fail2ban. Restrict access by IP. Enable 2FA.

Watchdog mini-recap

- **Exposed:** 2 open port(s), 1 high-risk service(s).
  Top: tcp/22 ssh [HIGH]; tcp/7070 realserver
- **Vulnerable:** 2 finding(s) (Critical 0, High 0, Medium 1).
- **Evidence:** 0/2 finding(s) include evidence snippets.
- **Remediation:** 0/2 finding(s) include remediation guidance.

Vulnerabilities (2)

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

Severity	Title	CVE	CVSS
MEDIUM	Components with Known Vulnerabilities - VAPTORDISCOVERY	—	5.0
INFO	Interesting Ports Found	—	0.0

Asset: VAPTOR001A0004

Asset fingerprint

Field	Value
MAC Address	3C:0A:F3:3C:C1:A7
IP	10.0.0.103
Hostname	10.0.0.103
OS fingerprint	N/A

Open ports

None recorded.

Watchdog mini-recap

- **Exposed:** 0 open port(s), 0 high-risk service(s).
- **Vulnerable:** 1 finding(s) (Critical 0, High 0, Medium 0).
- **Evidence:** 0/1 finding(s) include evidence snippets.
- **Remediation:** 0/1 finding(s) include remediation guidance.

Vulnerabilities (1)

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

Severity	Title	CVE	CVSS
LOW	Strict Tranposrt Security Not Enforced	—	2.5

Asset: VAPTOR001A0005

Asset fingerprint

Field	Value
MAC Address	16:41:0F:EC:FD:25
IP	10.0.0.128
Hostname	N/A
OS fingerprint	N/A

Open ports

None recorded.

Watchdog mini-recap

- **Exposed:** 0 open port(s), 0 high-risk service(s).
- **Vulnerable:** 0 finding(s) (Critical 0, High 0, Medium 0).
- **Evidence:** 0/0 finding(s) include evidence snippets.
- **Remediation:** 0/0 finding(s) include remediation guidance.

Vulnerabilities

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

None found.

Asset: VAPTOR001A0006

Asset fingerprint

Field	Value
MAC Address	70:F8:2B:1B:A3:68
IP	10.0.0.254
Hostname	www.adsl.vf
OS fingerprint	Linux 2.6.32 - 3.13

Open ports

Proto	Port	Service	Risk
tcp	53	domain	MEDIUM
tcp	80	http	HIGH
tcp	443	https	MEDIUM
tcp	1990	stun-p1	—

High-risk port notes (VaptorAI / Intel DB)

Port exposure notes (VaptorAI): tcp/80 http [HIGH]

Narrative

```
# Port Exposure: tcp/80

## Summary
An Internet-accessible service was detected on tcp/80. Exposed management and remote-
access ports are frequently targeted for credential attacks and exploitation.

## Why this matters (Risk)
- Increases attack surface and brute-force exposure
- May permit remote code execution if vulnerable and unpatched
```

```
- Often enables lateral movement once credentials are obtained

## Recommended actions (Remediation)
- Restrict access (VPN/jump host/allowlist)
- Enforce MFA and strong authentication policies
- Patch the exposed service and disable legacy/insecure options

## Evidence
- Observed open: tcp/80
```

Port exposure notes: tcp/80 http [HIGH]

Why this matters Unencrypted web traffic; web application vulnerabilities, MitM attacks

Common attacksSQL Injection, XSS, CSRF, Directory Traversal, Man-in-the-Middle, Session Hijacking

Notable CVEsCVE-2021-44228, CVE-2017-5638, CVE-2014-0160

Recommended action Redirect all traffic to HTTPS (port 443). Disable HTTP or use only for redirect. Implement HSTS headers.

Watchdog mini-recap

- **Exposed:** 4 open port(s), 1 high-risk service(s).
  Top: tcp/53 domain [MEDIUM]; tcp/80 http [HIGH]; tcp/443 https [MEDIUM]
- **Vulnerable:** 3 finding(s) (Critical 0, High 0, Medium 1).

- **Evidence:** 0/3 finding(s) include evidence snippets.
- **Remediation:** 0/3 finding(s) include remediation guidance.

Vulnerabilities (3)

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

Severity	Title	CVE	CVSS
MEDIUM	Components with Known Vulnerabilities - VAPTORDISCOVERY	—	5.0
LOW	Strict Tranposrt Security Not Enforced	—	2.5
INFO	Interesting Ports Found	—	0.0

Asset: VAPTOR001A0007

Asset fingerprint

Field	Value
MAC Address	74:40:BB:72:FB:C5
IP	10.0.0.108
Hostname	N/A

Field	Value
OS fingerprint	N/A

Open ports

None recorded.

Watchdog mini-recap

- **Exposed:** 0 open port(s), 0 high-risk service(s).
- **Vulnerable:** 0 finding(s) (Critical 0, High 0, Medium 0).
- **Evidence:** 0/0 finding(s) include evidence snippets.
- **Remediation:** 0/0 finding(s) include remediation guidance.

Vulnerabilities

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

None found.

Asset: VAPTOR001A0008

Asset fingerprint

Field	Value
MAC Address	N/A
IP	N/A
Hostname	VulnerableApp-master
OS fingerprint	N/A

Open ports

None recorded.

Watchdog mini-recap

- **Exposed:** 0 open port(s), 0 high-risk service(s).
- **Vulnerable:** 28 finding(s) (Critical 2, High 19, Medium 6).
- **Evidence:** 0/28 finding(s) include evidence snippets.
- **Remediation:** 0/28 finding(s) include remediation guidance.

Vulnerabilities (28)

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

Severity	Title	CVE	CVSS
CRITICAL	Unsanitized user input in XML External Entity	—	9.8
CRITICAL	Usage of hard-coded secret	—	9.8
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	—	8.0
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	—	8.0
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	—	8.0
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	—	8.0
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	—	8.0
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	—	8.0
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	—	8.0
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	—	8.0
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	—	8.0
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	—	8.0
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	—	8.0

Severity	Title	CVE	CVSS
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	—	8.0
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	—	8.0
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	—	8.0
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	—	8.0
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	—	8.0
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	—	8.0
HIGH	Unsanitized user input in dynamic HTML insertion (XSS)	—	8.0
MEDIUM	Usage of trusted and untrusted data inside the same data structure	—	5.0
MEDIUM	Observable Timing Discrepancy	—	5.0
MEDIUM	Observable Timing Discrepancy	—	5.0
MEDIUM	Usage of insufficient random value	—	5.0
MEDIUM	Missing Secure option in cookie configuration	—	5.0
MEDIUM	Missing HTTP Only option in cookie configuration	—	5.0
LOW	Leakage of information in logger message	—	2.5

Asset: VAPTOR001A0009

Asset fingerprint

Field	Value
MAC Address	N/A
IP	N/A
Hostname	[caa-fingerprint]
OS fingerprint	N/A

Open ports

None recorded.

Watchdog mini-recap

- **Exposed:** 0 open port(s), 0 high-risk service(s).
- **Vulnerable:** 1 finding(s) (Critical 0, High 0, Medium 0).
- **Evidence:** 0/1 finding(s) include evidence snippets.
- **Remediation:** 0/1 finding(s) include remediation guidance.

Vulnerabilities (1)

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

Severity	Title	CVE	CVSS
INFO	VAPTORRECON Vulnerability Scan	—	0.0

Asset: VAPTOR001A0010

Asset fingerprint

Field	Value
MAC Address	N/A
IP	N/A
Hostname	[default-windows-server-page]
OS fingerprint	N/A

Open ports

None recorded.

Watchdog mini-recap

- **Exposed:** 0 open port(s), 0 high-risk service(s).
- **Vulnerable:** 1 finding(s) (Critical 0, High 0, Medium 0).
- **Evidence:** 0/1 finding(s) include evidence snippets.
- **Remediation:** 0/1 finding(s) include remediation guidance.

Vulnerabilities (1)

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

Severity	Title	CVE	CVSS
INFO	VAPTORRECON Vulnerability Scan	—	0.0

Asset: VAPTOR001A0011

Asset fingerprint

Field	Value
MAC Address	N/A
IP	N/A

Field	Value
Hostname	[ec2-detection]
OS fingerprint	N/A

Open ports

None recorded.

Watchdog mini-recap

- **Exposed:** 0 open port(s), 0 high-risk service(s).
- **Vulnerable:** 1 finding(s) (Critical 0, High 0, Medium 0).
- **Evidence:** 0/1 finding(s) include evidence snippets.
- **Remediation:** 0/1 finding(s) include remediation guidance.

Vulnerabilities (1)

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

Severity	Title	CVE	CVSS
INFO	VAPTORRECON Vulnerability Scan	—	0.0

Asset: VAPTOR001A0012

Asset fingerprint

Field	Value
MAC Address	N/A
IP	N/A
Hostname	[http-missing-security-headers:clear-site-data]
OS fingerprint	N/A

Open ports

None recorded.

Watchdog mini-recap

- **Exposed:** 0 open port(s), 0 high-risk service(s).
- **Vulnerable:** 1 finding(s) (Critical 0, High 0, Medium 0).

- **Evidence:** 0/1 finding(s) include evidence snippets.
- **Remediation:** 0/1 finding(s) include remediation guidance.

Vulnerabilities (1)

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

Severity	Title	CVE	CVSS
INFO	VAPTORRECON Vulnerability Scan	—	0.0

Asset: VAPTOR001A0013

Asset fingerprint

Field	Value
MAC Address	N/A
IP	N/A
Hostname	[http-missing-security-headers:content-security-policy]
OS fingerprint	N/A

Open ports

None recorded.

Watchdog mini-recap

- **Exposed:** 0 open port(s), 0 high-risk service(s).
- **Vulnerable:** 1 finding(s) (Critical 0, High 0, Medium 0).
- **Evidence:** 0/1 finding(s) include evidence snippets.
- **Remediation:** 0/1 finding(s) include remediation guidance.

Vulnerabilities (1)

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

Severity	Title	CVE	CVSS
INFO	VAPTORRECON Vulnerability Scan	—	0.0

Asset: VAPTOR001A0014

Asset fingerprint

Field	Value
MAC Address	N/A

Field	Value
IP	N/A
Hostname	[http-missing-security-headers:cross-origin-embedder-policy]
OS fingerprint	N/A

Open ports

None recorded.

Watchdog mini-recap

- **Exposed:** 0 open port(s), 0 high-risk service(s).
- **Vulnerable:** 1 finding(s) (Critical 0, High 0, Medium 0).
- **Evidence:** 0/1 finding(s) include evidence snippets.
- **Remediation:** 0/1 finding(s) include remediation guidance.

Vulnerabilities (1)

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

Severity	Title	CVE	CVSS
INFO	VAPTORRECON Vulnerability Scan	—	0.0

Asset: VAPTOR001A0015

Asset fingerprint

Field	Value
MAC Address	N/A
IP	N/A
Hostname	[http-missing-security-headers:cross-origin-opener-policy]
OS fingerprint	N/A

Open ports

None recorded.

Watchdog mini-recap

- **Exposed:** 0 open port(s), 0 high-risk service(s).
- **Vulnerable:** 1 finding(s) (Critical 0, High 0, Medium 0).

- **Evidence:** 0/1 finding(s) include evidence snippets.
- **Remediation:** 0/1 finding(s) include remediation guidance.

Vulnerabilities (1)

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

Severity	Title	CVE	CVSS
INFO	VAPTORRECON Vulnerability Scan	—	0.0

Asset: VAPTOR001A0016

Asset fingerprint

Field	Value
MAC Address	N/A
IP	N/A
Hostname	[http-missing-security-headers:cross-origin-resource-policy]
OS fingerprint	N/A

Open ports

None recorded.

Watchdog mini-recap

- **Exposed:** 0 open port(s), 0 high-risk service(s).
- **Vulnerable:** 1 finding(s) (Critical 0, High 0, Medium 0).
- **Evidence:** 0/1 finding(s) include evidence snippets.
- **Remediation:** 0/1 finding(s) include remediation guidance.

Vulnerabilities (1)

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

Severity	Title	CVE	CVSS
INFO	VAPTORRECON Vulnerability Scan	—	0.0

Asset: VAPTOR001A0017

Asset fingerprint

Field	Value
MAC Address	N/A

Field	Value
IP	N/A
Hostname	[http-missing-security-headers:missing-content-type]
OS fingerprint	N/A

Open ports

None recorded.

Watchdog mini-recap

- **Exposed:** 0 open port(s), 0 high-risk service(s).
- **Vulnerable:** 1 finding(s) (Critical 0, High 0, Medium 0).
- **Evidence:** 0/1 finding(s) include evidence snippets.
- **Remediation:** 0/1 finding(s) include remediation guidance.

Vulnerabilities (1)

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

Severity	Title	CVE	CVSS
INFO	VAPTORRECON Vulnerability Scan	—	0.0

Asset: VAPTOR001A0018

Asset fingerprint

Field	Value
MAC Address	N/A
IP	N/A
Hostname	[http-missing-security-headers:permissions-policy]
OS fingerprint	N/A

Open ports

None recorded.

Watchdog mini-recap

- **Exposed:** 0 open port(s), 0 high-risk service(s).
- **Vulnerable:** 1 finding(s) (Critical 0, High 0, Medium 0).

- **Evidence:** 0/1 finding(s) include evidence snippets.
- **Remediation:** 0/1 finding(s) include remediation guidance.

Vulnerabilities (1)

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

Severity	Title	CVE	CVSS
INFO	VAPTORRECON Vulnerability Scan	—	0.0

Asset: VAPTOR001A0019

Asset fingerprint

Field	Value
MAC Address	N/A
IP	N/A
Hostname	[http-missing-security-headers:referrer-policy]
OS fingerprint	N/A

Open ports

None recorded.

Watchdog mini-recap

- **Exposed:** 0 open port(s), 0 high-risk service(s).
- **Vulnerable:** 1 finding(s) (Critical 0, High 0, Medium 0).
- **Evidence:** 0/1 finding(s) include evidence snippets.
- **Remediation:** 0/1 finding(s) include remediation guidance.

Vulnerabilities (1)

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

Severity	Title	CVE	CVSS
INFO	VAPTORRECON Vulnerability Scan	—	0.0

Asset: VAPTOR001A0020

Asset fingerprint

Field	Value
MAC Address	N/A

Field	Value
IP	N/A
Hostname	[http-missing-security-headers:strict-transport-security]
OS fingerprint	N/A

Open ports

None recorded.

Watchdog mini-recap

- **Exposed:** 0 open port(s), 0 high-risk service(s).
- **Vulnerable:** 1 finding(s) (Critical 0, High 0, Medium 0).
- **Evidence:** 0/1 finding(s) include evidence snippets.
- **Remediation:** 0/1 finding(s) include remediation guidance.

Vulnerabilities (1)

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

Severity	Title	CVE	CVSS
INFO	VAPTORRECON Vulnerability Scan	—	0.0

Asset: VAPTOR001A0021

Asset fingerprint

Field	Value
MAC Address	N/A
IP	N/A
Hostname	[http-missing-security-headers:x-content-type-options]
OS fingerprint	N/A

Open ports

None recorded.

Watchdog mini-recap

- **Exposed:** 0 open port(s), 0 high-risk service(s).
- **Vulnerable:** 1 finding(s) (Critical 0, High 0, Medium 0).

- **Evidence:** 0/1 finding(s) include evidence snippets.
- **Remediation:** 0/1 finding(s) include remediation guidance.

Vulnerabilities (1)

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

Severity	Title	CVE	CVSS
INFO	VAPTORRECON Vulnerability Scan	—	0.0

Asset: VAPTOR001A0022

Asset fingerprint

Field	Value
MAC Address	N/A
IP	N/A
Hostname	[http-missing-security-headers:x-frame-options]
OS fingerprint	N/A

Open ports

None recorded.

Watchdog mini-recap

- **Exposed:** 0 open port(s), 0 high-risk service(s).
- **Vulnerable:** 1 finding(s) (Critical 0, High 0, Medium 0).
- **Evidence:** 0/1 finding(s) include evidence snippets.
- **Remediation:** 0/1 finding(s) include remediation guidance.

Vulnerabilities (1)

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

Severity	Title	CVE	CVSS
INFO	VAPTORRECON Vulnerability Scan	—	0.0

Asset: VAPTOR001A0023

Asset fingerprint

Field	Value
MAC Address	N/A

Field	Value
IP	N/A
Hostname	[http-missing-security-headers:x-permitted-cross-domain-policies]
OS fingerprint	N/A

Open ports

None recorded.

Watchdog mini-recap

- **Exposed:** 0 open port(s), 0 high-risk service(s).
- **Vulnerable:** 1 finding(s) (Critical 0, High 0, Medium 0).
- **Evidence:** 0/1 finding(s) include evidence snippets.
- **Remediation:** 0/1 finding(s) include remediation guidance.

Vulnerabilities (1)

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

Severity	Title	CVE	CVSS
INFO	VAPTORRECON Vulnerability Scan	—	0.0

Asset: VAPTOR001A0024

Asset fingerprint

Field	Value
MAC Address	N/A
IP	N/A
Hostname	[microsoft-iis-version]
OS fingerprint	N/A

Open ports

None recorded.

Watchdog mini-recap

- **Exposed:** 0 open port(s), 0 high-risk service(s).
- **Vulnerable:** 1 finding(s) (Critical 0, High 0, Medium 0).

- **Evidence:** 0/1 finding(s) include evidence snippets.
- **Remediation:** 0/1 finding(s) include remediation guidance.

Vulnerabilities (1)

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

Severity	Title	CVE	CVSS
INFO	VAPTORRECON Vulnerability Scan	—	0.0

Asset: VAPTOR001A0025

Asset fingerprint

Field	Value
MAC Address	N/A
IP	N/A
Hostname	[options-method]
OS fingerprint	N/A

Open ports

None recorded.

Watchdog mini-recap

- **Exposed:** 0 open port(s), 0 high-risk service(s).
- **Vulnerable:** 1 finding(s) (Critical 0, High 0, Medium 0).
- **Evidence:** 0/1 finding(s) include evidence snippets.
- **Remediation:** 0/1 finding(s) include remediation guidance.

Vulnerabilities (1)

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

Severity	Title	CVE	CVSS
INFO	VAPTORRECON Vulnerability Scan	—	0.0

Asset: VAPTOR001A0026

Asset fingerprint

Field	Value
MAC Address	N/A

Field	Value
IP	N/A
Hostname	[tech-detect:ms-iis]
OS fingerprint	N/A

Open ports

None recorded.

Watchdog mini-recap

- **Exposed:** 0 open port(s), 0 high-risk service(s).
- **Vulnerable:** 1 finding(s) (Critical 0, High 0, Medium 0).
- **Evidence:** 0/1 finding(s) include evidence snippets.
- **Remediation:** 0/1 finding(s) include remediation guidance.

Vulnerabilities (1)

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

Severity	Title	CVE	CVSS
INFO	VAPTORRECON Vulnerability Scan	—	0.0

Asset: VAPTOR001A0027

Asset fingerprint

Field	Value
MAC Address	N/A
IP	N/A
Hostname	[tls-version]
OS fingerprint	N/A

Open ports

None recorded.

Watchdog mini-recap

- **Exposed:** 0 open port(s), 0 high-risk service(s).
- **Vulnerable:** 1 finding(s) (Critical 0, High 0, Medium 0).

- **Evidence:** 0/1 finding(s) include evidence snippets.
- **Remediation:** 0/1 finding(s) include remediation guidance.

Vulnerabilities (1)

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

Severity	Title	CVE	CVSS
INFO	VAPTORRECON Vulnerability Scan	—	0.0

Asset: VAPTOR001A0028

Asset fingerprint

Field	Value
MAC Address	N/A
IP	N/A
Hostname	[waf-detect:aspgeneric]
OS fingerprint	N/A

Open ports

None recorded.

Watchdog mini-recap

- **Exposed:** 0 open port(s), 0 high-risk service(s).
- **Vulnerable:** 1 finding(s) (Critical 0, High 0, Medium 0).
- **Evidence:** 0/1 finding(s) include evidence snippets.
- **Remediation:** 0/1 finding(s) include remediation guidance.

Vulnerabilities (1)

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

Severity	Title	CVE	CVSS
INFO	VAPTORRECON Vulnerability Scan	—	0.0

Asset: VAPTOR001A0029

Asset fingerprint

Field	Value
MAC Address	N/A

Field	Value
IP	N/A
Hostname	[waf-detect:modsecurity]
OS fingerprint	N/A

Open ports

None recorded.

Watchdog mini-recap

- **Exposed:** 0 open port(s), 0 high-risk service(s).
- **Vulnerable:** 1 finding(s) (Critical 0, High 0, Medium 0).
- **Evidence:** 0/1 finding(s) include evidence snippets.
- **Remediation:** 0/1 finding(s) include remediation guidance.

Vulnerabilities (1)

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

Severity	Title	CVE	CVSS
INFO	VAPTORRECON Vulnerability Scan	—	0.0

Asset: VAPTOR001A0030

Asset fingerprint

Field	Value
MAC Address	N/A
IP	N/A
Hostname	[weak-csp-detect:unsafe-default-src]
OS fingerprint	N/A

Open ports

None recorded.

Watchdog mini-recap

- **Exposed:** 0 open port(s), 0 high-risk service(s).
- **Vulnerable:** 1 finding(s) (Critical 0, High 0, Medium 0).

- **Evidence:** 0/1 finding(s) include evidence snippets.
- **Remediation:** 0/1 finding(s) include remediation guidance.

Vulnerabilities (1)

CVE/CVSS are shown when available; CVSS may be estimated from severity when not provided by the source.

Severity	Title	CVE	CVSS
INFO	VAPTORRECON Vulnerability Scan	—	0.0

3b) Audit (AI) - Log Analysis

AI-assisted analysis of uploaded security logs for this scan. Reports list audit artifacts only (not raw log contents) to reduce sensitive-data exposure.

Analysis Summary

Analysis completed: 2026-04-12 08:20:49 UTC

Files processed: 60

Vulnerabilities found: 3

Threats detected: 4

Recommendations: 4

Analyzed 25 scan-folder artifact files. Found 13 vulnerabilities, 10 threats, and 33 recommendations.

Security Vulnerabilities Identified (3)

Title	Severity	Description	Source Artifact
Vulnerability mention	MEDIUM	Vulnerability mention	sniper_output.txt, vulnerability-report-10.0.0.103.txt, sniper_summary.json, sniper-ec2-44-238-29-244.us-west-2.compute.amazonaws.com-nuke-202604120943.txt, sc0pe-all-vulnerabilities-sorted.txt, vulnerability-report-ec2-44-238-29-244.us-west-2.compute.amazonaws.com.txt
CVE reference found	HIGH	CVE reference found	sniper_summary.json, sniper_output.txt, sniper-ec2-44-238-29-244.us-west-2.compute.amazonaws.com-nuke-202604120943.txt, sc0pe-all-vulnerabilities-sorted.txt, vulnerability-report-ec2-44-238-29-244.us-west-2.compute.amazonaws.com.txt
Weak configuration/ credential	MEDIUM	Weak configuration/ credential	sniper_summary.json, sniper_output.txt, sc0pe-all-vulnerabilities-sorted.txt

Security Threats Detected (4)

Threat	Severity	Category	Source Artifact
Access denied events found	MEDIUM	denied	pcap_summary.json, VAPTORPCAP20260411185848.log
Potential attack indicators	MEDIUM	attack	scanner_execution.json, sniper_output.txt, sniper-ec2-44-238-29-244.us-west-2.compute.amazonaws.com-nuke-202604120943.txt
Exploit attempt signatures	MEDIUM	exploit	scanner_execution.json, sniper_summary.json, sniper_output.txt, sniper-ec2-44-238-29-244.us-west-2.compute.amazonaws.com-nuke-202604120943.txt, sc0pe-all-vulnerabilities-sorted.txt
Injection attempt patterns	MEDIUM	injection	sniper_output.txt, sniper-ec2-44-238-29-244.us-west-2.compute.amazonaws.com-nuke-202604120943.txt

Security Recommendations (4)

Priority	Category	Recommended Action	Source File
HIGH	Security	Investigate threat indicators immediately	—

HIGH	Patching	Apply patches and security updates for identified vulnerabilities	—
MEDIUM	Monitoring	Review anomalies for potential system or security issues	—
LOW	Monitoring	Continue regular monitoring and log review	—

4) Compliance Evaluation & Score

This section is informational and helps triage findings against control frameworks. It is not a formal compliance audit. Controls are marked **Non-Compliant** when mapped findings exist for this scan; controls only become **Compliant** when audit evidence (vaptaudit) explicitly marks them as PASS.

Metric	Value
Percent compliant	4% (Low)
Control coverage	5/74 (7%)
Vulnerability-to-control mapping	0/97 (0%)
Auto mapping (bootstrap)	No

Compliance Summary by Framework

Framework	Compliant	Non-Compliant	Unmapped
HIPAA	0/57 (0%)	4	53
ISO-27001	0/5 (0%)	0	5
NIST-CSF	0/7 (0%)	1	6
PCI-DSS	0/5 (0%)	0	5

Compliance Controls (Addendum)

Status legend: **Compliant**=Informational: vaptaudit provided PASS evidence for this control for this scan.; **Non-Compliant**=Informational: a mapped finding impacts this control for this scan (or vaptaudit marked FAIL).; **Unmapped**=Informational: no mapped findings for this control and no vaptaudit PASS evidence.

Framework	Control Title	Affected AssetUID	Status
HIPAA	Security Management Process	VAPTOR001A0002	Non-Compliant
HIPAA	Security Management Process - Risk Analysis	VAPTOR001A0002	Non-Compliant

Framework	Control Title	Affected AssetUID	Status
HIPAA	Security Management Process - Risk Management	—	Unmapped
HIPAA	Security Management Process - Sanction Policy	—	Unmapped
HIPAA	Security Management Process - Information System Activity Review	—	Unmapped
HIPAA	Assigned Security Responsibility	—	Unmapped
HIPAA	Workforce Security	—	Unmapped
HIPAA	Workforce Security - Authorization and Supervision	—	Unmapped
HIPAA	Workforce Security - Clearance Procedure	—	Unmapped
HIPAA	Workforce Security - Termination Procedures	—	Unmapped
HIPAA	Information Access Management	—	Unmapped
HIPAA	Information Access Management - Access Authorization	—	Unmapped
HIPAA	Information Access Management - Access Establishment and Modification	—	Unmapped
HIPAA	Security Awareness and Training	—	Unmapped

Framework	Control Title	Affected AssetUID	Status
HIPAA	Security Awareness and Training	—	Unmapped
HIPAA	Security Awareness and Training - Security Reminders	—	Unmapped
HIPAA	Security Awareness and Training - Protection from Malicious Software	—	Unmapped
HIPAA	Security Awareness and Training - Log-in Monitoring	—	Unmapped
HIPAA	Security Awareness and Training - Password Management	—	Unmapped
HIPAA	Security Incident Procedures	—	Unmapped
HIPAA	Security Incident Procedures - Response and Reporting	VAPTOR001A0002	Non-Compliant
HIPAA	Contingency Plan	—	Unmapped
HIPAA	Contingency Plan - Data Backup	—	Unmapped
HIPAA	Contingency Plan - Disaster Recovery	—	Unmapped
HIPAA	Contingency Plan - Emergency Mode Operation	—	Unmapped
HIPAA	Contingency Plan - Testing and Revision	—	Unmapped

Framework	Control Title	Affected AssetUID	Status
HIPAA	Evaluation	—	Unmapped
HIPAA	Business Associate Contracts	—	Unmapped
HIPAA	Facility Access Controls	—	Unmapped
HIPAA	Facility Access Controls - Contingency Operations	—	Unmapped
HIPAA	Facility Access Controls - Facility Security Plan	—	Unmapped
HIPAA	Facility Access Controls - Access Control and Validation	—	Unmapped
HIPAA	Facility Access Controls - Maintenance Records	—	Unmapped
HIPAA	Workstation Use	VAPTOR001A0002	Non-Compliant
HIPAA	Workstation Security	—	Unmapped
HIPAA	Device and Media Controls - Disposal	—	Unmapped
HIPAA	Device and Media Controls - Media Re-use	—	Unmapped
HIPAA	Device and Media Controls - Accountability	—	Unmapped
HIPAA	Device and Media Controls - Data Backup and Storage	—	Unmapped

Framework	Control Title	Affected AssetUID	Status
HIPAA	Access Control	—	Unmapped
HIPAA	Access Control - Unique User Identification	—	Unmapped
HIPAA	Access Control - Emergency Access Procedure	—	Unmapped
HIPAA	Access Control - Automatic Logoff	—	Unmapped
HIPAA	Access Control - Encryption and Decryption	—	Unmapped
HIPAA	Audit Controls	—	Unmapped
HIPAA	Integrity	—	Unmapped
HIPAA	Integrity - Mechanism to Authenticate ePHI	—	Unmapped
HIPAA	Person or Entity Authentication	—	Unmapped
HIPAA	Transmission Security	—	Unmapped
HIPAA	Transmission Security - Integrity Controls	—	Unmapped
HIPAA	Transmission Security - Encryption	—	Unmapped
HIPAA	Business Associate Contracts - Written Contract	—	Unmapped

Framework	Control Title	Affected AssetUID	Status
HIPAA	Requirements for Group Health Plans	—	Unmapped
HIPAA	Policies and Procedures	—	Unmapped
HIPAA	Documentation - Time Limit	—	Unmapped
HIPAA	Documentation - Availability	—	Unmapped
HIPAA	Documentation - Updates	—	Unmapped
ISO-27001	Policies for information security	—	Unmapped
ISO-27001	Screening	—	Unmapped
ISO-27001	Physical security perimeters	—	Unmapped
ISO-27001	User endpoint devices	—	Unmapped
ISO-27001	Privileged access rights	—	Unmapped
NIST-CSF	Networks are monitored	—	Unmapped
NIST-CSF	Asset inventories are maintained	—	Unmapped
NIST-CSF	Software platforms are inventoried	VAPTOR001A0002	Non-Compliant

Framework	Control Title	Affected AssetUID	Status
NIST-CSF	Identities are managed	—	Unmapped
NIST-CSF	Remote access is managed	—	Unmapped
NIST-CSF	Recovery plan is executed	—	Unmapped
NIST-CSF	Response plan is executed	—	Unmapped
PCI-DSS	Firewall configuration standards	—	Unmapped
PCI-DSS	Change default passwords	—	Unmapped
PCI-DSS	CHD retention policy	—	Unmapped
PCI-DSS	Strong cryptography for CHD transmission	—	Unmapped
PCI-DSS	Secure development processes	—	Unmapped

Vulnerability → Control Trace (This Scan)

This links findings to impacted controls so users can see why a control is flagged as Non-Compliant.

AssetUID	Severity	Finding	Impacted Controls
VAPTOR001A0002	INFORMATIONAL		HIPAA: Workstation Use

AssetUID	Severity	Finding	Impacted Controls
		User Controllable HTML Element Attribute (Potential XSS)	
VAPTOR001A0002	INFORMATIONAL	User Agent Fuzzer	HIPAA: Security Management Process
VAPTOR001A0002	INFORMATIONAL	Session Management Response Identified	HIPAA: Security Management Process
VAPTOR001A0002	INFORMATIONAL	GET for POST	HIPAA: Security Management Process
VAPTOR001A0002	INFORMATIONAL	Charset Mismatch (Header Versus Meta Content-Type Charset)	HIPAA: Security Management Process
VAPTOR001A0002	INFORMATIONAL	Authentication Request Identified	HIPAA: Security Management Process
VAPTOR001A0002	LOW	X-Content-Type-Options Header Missing	HIPAA: Security Management Process
VAPTOR001A0002	LOW	X-AspNet-Version Response Header	HIPAA: Security Incident Procedures - Response and Reporting
VAPTOR001A0002	LOW		

AssetUID	Severity	Finding	Impacted Controls
		Server Leaks Version Information via "Server" HTTP Response Header Field	HIPAA: Security Management Process - Risk Analysis
VAPTOR001A0002	LOW	Server Leaks Information via "X-Powered-By" HTTP Response Header Field(s)	HIPAA: Security Management Process - Risk Analysis
VAPTOR001A0002	LOW	Cookie without SameSite Attribute	HIPAA: Workstation Use
VAPTOR001A0002	MEDIUM	Missing Anti-clickjacking Header	HIPAA: Security Management Process
VAPTOR001A0002	MEDIUM	HTTP Only Site	HIPAA: Security Management Process
VAPTOR001A0002	MEDIUM	Content Security Policy (CSP) Header Not Set	HIPAA: Security Management Process
VAPTOR001A0002	MEDIUM	Absence of Anti-CSRF Tokens	HIPAA: Security Management Process
VAPTOR001A0002	HIGH	SQL Injection - MsSQL (Time Based)	HIPAA: Security Management Process
VAPTOR001A0002	HIGH	SQL Injection	HIPAA: Security Management Process

AssetUID	Severity	Finding	Impacted Controls
VAPTOR001A0002	HIGH	Cross Site Scripting (Reflected)	HIPAA: Security Management Process
VAPTOR001A0002	INFORMATIONAL	User Agent Fuzzer	HIPAA: Security Management Process
VAPTOR001A0002	INFORMATIONAL	Session Management Response Identified	HIPAA: Security Management Process
VAPTOR001A0002	INFORMATIONAL	Modern Web Application	HIPAA: Security Management Process
VAPTOR001A0002	INFORMATIONAL	Information Disclosure - Suspicious Comments	HIPAA: Security Management Process - Risk Analysis
VAPTOR001A0002	LOW	X-Content-Type-Options Header Missing	HIPAA: Security Management Process
VAPTOR001A0002	LOW	Server Leaks Version Information via "Server" HTTP Response Header Field	HIPAA: Security Management Process - Risk Analysis
VAPTOR001A0002	LOW	Server Leaks Information via "X-Powered-By" HTTP Response Header Field(s)	HIPAA: Security Management Process - Risk Analysis

AssetUID	Severity	Finding	Impacted Controls
VAPTOR001A0002	LOW	Information Disclosure - Debug Error Messages	HIPAA: Security Management Process - Risk Analysis
VAPTOR001A0002	LOW	Cookie without SameSite Attribute	HIPAA: Workstation Use
VAPTOR001A0002	LOW	Cookie No HttpOnly Flag	HIPAA: Security Management Process
VAPTOR001A0002	LOW	Application Error Disclosure	NIST-CSF: Software platforms are inventoried
VAPTOR001A0002	MEDIUM	Missing Anti-clickjacking Header	HIPAA: Security Management Process
VAPTOR001A0002	MEDIUM	HTTP Only Site	HIPAA: Security Management Process
VAPTOR001A0002	MEDIUM	Content Security Policy (CSP) Header Not Set	HIPAA: Security Management Process
VAPTOR001A0002	MEDIUM	Absence of Anti-CSRF Tokens	HIPAA: Security Management Process
VAPTOR001A0002	HIGH	SQL Injection - MsSQL (Time Based)	HIPAA: Security Management Process

AssetUID	Severity	Finding	Impacted Controls
VAPTOR001A0002	HIGH	SQL Injection	HIPAA: Security Management Process
VAPTOR001A0002	HIGH	Path Traversal	HIPAA: Security Management Process
VAPTOR001A0002	HIGH	External Redirect	HIPAA: Security Management Process
VAPTOR001A0002	HIGH	Cross Site Scripting (Reflected)	HIPAA: Security Management Process

5) Remediation & Compliance Roadmap

1. Restrict exposure of 10.0.0.132:22 (HIGH). Implement key-based authentication only. Disable password authentication. Use fail2ban. Restrict access by IP. Enable 2FA.
2. Restrict exposure of 10.0.0.254:80 (HIGH). Redirect all traffic to HTTPS (port 443). Disable HTTP or use only for redirect. Implement HSTS headers.
3. Restrict exposure of 44.238.29.244:80 (HIGH). Redirect all traffic to HTTPS (port 443). Disable HTTP or use only for redirect. Implement HSTS headers.
4. Patch or mitigate CRITICAL/HIGH vulnerabilities first; validate fixes with a re-scan.
5. Harden authentication: enforce MFA where possible, disable default credentials, and add account lockout policies for remote services.

6. Compliance: ensure control mappings are configured (set `compliance.default_control_id`) and remediate items mapped to highest-priority controls first.

Appendix A — Exploit Verification Evidence

VAPTORMSF evidence captures indexed per discovered asset. Evidence is included only when RC scripts and corresponding output files are present in the scan artifacts.

10.0.0.132 (verification)

Field	Value
AssetUID	VAPTOR001A0003
IP Address	10.0.0.132
MAC Address	B8:27:EB:74:F2:6C
Port(s)	22, 7070
Risk	HIGH
Vulnerable	Yes

RC Script

```
setg RHOSTS 10.0.0.132
setg VERBOSE false
```

```
use auxiliary/scanner/portscan/tcp
set RHOSTS 10.0.0.132
set PORTS 22,7070
set THREADS 50
run
back
use auxiliary/scanner/ssh/ssh_enumusers
set RHOSTS 10.0.0.132
set RPORT 22
run
back
exit
```

Output

```
[*] Processing /home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_132.rc for ERB
directives.
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_132.rc)> setg RHOSTS
10.0.0.132
RHOSTS => 10.0.0.132
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_132.rc)> setg VERBOSE
false
VERBOSE => false
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_132.rc)> use auxiliary/
scanner/portscan/tcp
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_132.rc)> set RHOSTS
10.0.0.132
RHOSTS => 10.0.0.132
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_132.rc)> set PORTS
```

```
22,7070
PORTS => 22,7070
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_132.rc)> set THREADS 50
THREADS => 50
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_132.rc)> run
[+] 10.0.0.132            - 10.0.0.132:22 - TCP OPEN
[+] 10.0.0.132            - 10.0.0.132:7070 - TCP OPEN
[*] 10.0.0.132            - Scanned 1 of 1 hosts (100% complete)
[*] Auxiliary module execution completed
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_132.rc)> back
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_132.rc)> use auxiliary/
scanner/ssh/ssh_enumusers
[*] Setting default action Malformed Packet - view all 2 actions with the show actions command
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_132.rc)> set RHOSTS
10.0.0.132
RHOSTS => 10.0.0.132
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_132.rc)> set RPORT 22
RPORT => 22
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_132.rc)> run
[-] Auxiliary aborted due to failure: bad-config: Please populate DB_ALL_USERS, USER_FILE, USERNAME
[*] Auxiliary module execution completed
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_132.rc)> back
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_132.rc)> exit
```

10.0.0.254 (verification)

Field	Value
AssetUID	VAPTOR001A0006

Field	Value
IP Address	10.0.0.254
MAC Address	70:F8:2B:1B:A3:68
Port(s)	53, 80, 443, 1990
Risk	HIGH
Vulnerable	Yes

RC Script

```
setg RHOSTS 10.0.0.254
setg VERBOSE false
use auxiliary/scanner/portscan/tcp
set RHOSTS 10.0.0.254
set PORTS 53,80,443,1990
set THREADS 50
run
back
use auxiliary/scanner/dns/dns_amp
set RHOSTS 10.0.0.254
set RPORT 53
run
back
use auxiliary/scanner/http/http_version
set RHOSTS 10.0.0.254
```

```
set RPORT 80
run
back
use auxiliary/scanner/http/dir_scanner
set RHOSTS 10.0.0.254
set RPORT 80
run
back
use auxiliary/scanner/http/cert
set RHOSTS 10.0.0.254
set RPORT 443
run
back
exit
```

Output

```
[*] Processing /home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc for ERB
directives.
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> setg RHOSTS
10.0.0.254
RHOSTS => 10.0.0.254
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> setg VERBOSE
false
VERBOSE => false
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> use auxiliary/
scanner/portscan/tcp
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> set RHOSTS
10.0.0.254
```

```
RHOSTS => 10.0.0.254
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> set PORTS
53,80,443,1990
PORTS => 53,80,443,1990
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> set THREADS 50
THREADS => 50
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> run
[+] 10.0.0.254            - 10.0.0.254:80 - TCP OPEN
[+] 10.0.0.254            - 10.0.0.254:443 - TCP OPEN
[+] 10.0.0.254            - 10.0.0.254:1990 - TCP OPEN
[+] 10.0.0.254            - 10.0.0.254:53 - TCP OPEN
[*] 10.0.0.254            - Scanned 1 of 1 hosts (100% complete)
[*] Auxiliary module execution completed
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> back
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> use auxiliary/
scanner/dns/dns_amp
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> set RHOSTS
10.0.0.254
RHOSTS => 10.0.0.254
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> set RPORT 53
RPORT => 53
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> run
[*] Sending DNS probes to 10.0.0.254->10.0.0.254 (1 hosts)
[*] Sending 67 bytes to each host using the IN ANY isc.org request
[+] 10.0.0.254:53 - Response is 67 bytes [1.0x Amplification]
[*] Scanned 1 of 1 hosts (100% complete)
[*] Auxiliary module execution completed
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> back
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> use auxiliary/
scanner/http/http_version
```

```
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> set RHOSTS
10.0.0.254
RHOSTS => 10.0.0.254
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> set RPORT 80
RPORT => 80
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> run
[+] 10.0.0.254:80
[*] Scanned 1 of 1 hosts (100% complete)
[*] Auxiliary module execution completed
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> back
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> use auxiliary/
scanner/http/dir_scanner
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> set RHOSTS
10.0.0.254
RHOSTS => 10.0.0.254
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> set RPORT 80
RPORT => 80
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> run
[*] Detecting error code
[*] Using first 256 bytes of the response as 404 string for 10.0.0.254
[*] Scanned 1 of 1 hosts (100% complete)
[*] Auxiliary module execution completed
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> back
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> use auxiliary/
scanner/http/cert
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> set RHOSTS
10.0.0.254
RHOSTS => 10.0.0.254
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> set RPORT 443
RPORT => 443
```

```
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> run
[*] 10.0.0.254:443        - 10.0.0.254 - '192.168.0.1' : '2019-04-22 07:43:20 UTC' - '2029-04-19 07:43:20 UTC'
[*] 10.0.0.254:443        - Scanned 1 of 1 hosts (100% complete)
[*] Auxiliary module execution completed
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> back
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_10_0_0_254.rc)> exit
```

44.238.29.244 (verification)

Field	Value
AssetUID	VAPTOR001A0002
IP Address	44.238.29.244
MAC Address	—
Port(s)	80
Risk	HIGH
Vulnerable	Yes

RC Script

```
setg RHOSTS 44.238.29.244
setg VERBOSE false
use auxiliary/scanner/portscan/tcp
set RHOSTS 44.238.29.244
```

```
set PORTS 80
set THREADS 50
run
back
use auxiliary/scanner/http/http_version
set RHOSTS 44.238.29.244
set RPORT 80
run
back
use auxiliary/scanner/http/dir_scanner
set RHOSTS 44.238.29.244
set RPORT 80
run
back
exit
```

Output

```
[*] Processing /home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_44_238_29_244.rc for ERB
directives.
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_44_238_29_244.rc)> setg RHOSTS
44.238.29.244
RHOSTS => 44.238.29.244
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_44_238_29_244.rc)> setg
VERBOSE false
VERBOSE => false
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_44_238_29_244.rc)> use
auxiliary/scanner/portscan/tcp
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_44_238_29_244.rc)> set RHOSTS
```

```
44.238.29.244
RHOSTS => 44.238.29.244
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_44_238_29_244.rc)> set PORTS
80
PORTS => 80
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_44_238_29_244.rc)> set THREADS
50
THREADS => 50
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_44_238_29_244.rc)> run
[*] 44.238.29.244         - Scanned 1 of 1 hosts (100% complete)
[*] Auxiliary module execution completed
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_44_238_29_244.rc)> back
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_44_238_29_244.rc)> use
auxiliary/scanner/http/http_version
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_44_238_29_244.rc)> set RHOSTS
44.238.29.244
RHOSTS => 44.238.29.244
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_44_238_29_244.rc)> set RPORT
80
RPORT => 80
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_44_238_29_244.rc)> run
[+] 44.238.29.244:80 Microsoft-IIS/8.5 ( Powered by ASP.NET )
[*] Scanned 1 of 1 hosts (100% complete)
[*] Auxiliary module execution completed
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_44_238_29_244.rc)> back
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_44_238_29_244.rc)> use
auxiliary/scanner/http/dir_scanner
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_44_238_29_244.rc)> set RHOSTS
44.238.29.244
RHOSTS => 44.238.29.244
```

```
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_44_238_29_244.rc)> set RPORT
80
RPORT => 80
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_44_238_29_244.rc)> run
[*] Detecting error code
[*] Using code '404' as not found for 44.238.29.244
[+] Found http://44.238.29.244:80/aspnet_client/ 404 (44.238.29.244)
[*] Scanned 1 of 1 hosts (100% complete)
[*] Auxiliary module execution completed
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_44_238_29_244.rc)> back
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/VAPTORMSF/auto_44_238_29_244.rc)> exit
```

10.0.0.132 (auth)

Field	Value
AssetUID	VAPTOR001A0003
IP Address	10.0.0.132
MAC Address	B8:27:EB:74:F2:6C
Port(s)	22, 7070
Risk	HIGH
Vulnerable	No

RC Script

```
setg RHOSTS 10.0.0.132
setg VERBOSE false
setg STOP_ON_SUCCESS true
setg BLANK_PASSWORDS false
setg USERPASS_FILE /home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/metasploit_auth/
userpass_trimmed.userpass.txt
use auxiliary/scanner/ssh/ssh_login
set RHOSTS 10.0.0.132
set RPORT 22
set THREADS 10
run
back
exit
```

Output

```
[*] Processing /home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/metasploit_auth/auth_10_0_0_132.rc for
ERB directives.
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/metasploit_auth/auth_10_0_0_132.rc)> setg
RHOSTS 10.0.0.132
RHOSTS => 10.0.0.132
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/metasploit_auth/auth_10_0_0_132.rc)> setg
VERBOSE false
VERBOSE => false
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/metasploit_auth/auth_10_0_0_132.rc)> setg
STOP_ON_SUCCESS true
STOP_ON_SUCCESS => true
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/metasploit_auth/auth_10_0_0_132.rc)> setg
```

```
BLANK_PASSWORDS false
BLANK_PASSWORDS => false
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/metasploit_auth/auth_10_0_0_132.rc)> setg
USERPASS_FILE /home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/metasploit_auth/
userpass_trimmed.userpass.txt
USERPASS_FILE => /home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/metasploit_auth/
userpass_trimmed.userpass.txt
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/metasploit_auth/auth_10_0_0_132.rc)> use
auxiliary/scanner/ssh/ssh_login
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/metasploit_auth/auth_10_0_0_132.rc)> set
RHOSTS 10.0.0.132
RHOSTS => 10.0.0.132
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/metasploit_auth/auth_10_0_0_132.rc)> set
RPORT 22
RPORT => 22
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/metasploit_auth/auth_10_0_0_132.rc)> set
THREADS 10
THREADS => 10
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/metasploit_auth/auth_10_0_0_132.rc)> run
[*] 10.0.0.132:22         - Starting bruteforce
[*] 10.0.0.132:22 SSH - Testing User/Pass combinations
[*] Scanned 1 of 1 hosts (100% complete)
[*] Auxiliary module execution completed
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/metasploit_auth/auth_10_0_0_132.rc)> back
resource (/home/***/vaptor/be/scans/VAPTOR001/20260411144454/artifacts/metasploit_auth/auth_10_0_0_132.rc)> exit
```

Appendix B — Scan Artifact Index

Complete inventory of scan artifacts generated during this assessment.

Artifact Path	Size (bytes)
artifacts/ai_ready_summary.json	24,972
artifacts/api_scan.json	386
artifacts/app/apkleaks_results.json	0
artifacts/app/appsec_summary.json	3,916
artifacts/app/static_analysis.json	2,939
artifacts/VAPTORDISCOVERY.txt	281
artifacts/burp/burp_project_options.json	246
artifacts/burp/burp_summary.json	405
artifacts/consolidated_vulnerabilities.json	135,272
artifacts/consolidated_vulnerabilities_penetration_test.json	1,312

Artifact Path	Size (bytes)
artifacts/consolidated_vulnerabilities_vulnerability_assessment.json	135,257
artifacts/dast/dast_summary.json	649
artifacts/dast/nuclei_results.json	0
artifacts/dast/nuclei_targets.txt	180
artifacts/dast/wapiti_1_http_testhtml5.vulnweb.com/wapiti_results.json	42,217
artifacts/dast/wapiti_2_http_testphp.vulnweb.com/wapiti_results.json	42,215
artifacts/dast/wapiti_3_http_testasp.vulnweb.com/wapiti_results.json	42,215
artifacts/dast/wapiti_4_http_testaspnet.vulnweb.com/wapiti_results.json	42,218
artifacts/dast/wapiti_5_http_10.0.0.254_80/wapiti_results.json	42,206
artifacts/dast/wapiti_6_https_10.0.0.254_443/wapiti_results.json	42,207
artifacts/dast/wapiti_7_http_44.238.29.244_80/wapiti_results.json	42,209
artifacts/dast/wapiti_summary.json	1,921
artifacts/discovery/_nmap_chunks/VAPTORDISCOVERY-part-1.xml	135,085

Artifact Path	Size (bytes)
artifacts/discovery/discovery.csv	350
artifacts/discovery/discovery.json	24,488
artifacts/discovery/discovery.yaml	631
artifacts/discovery/httpx_targets.txt	181
artifacts/discovery/httpx_web.jsonl	1,875
artifacts/discovery/VAPTORDISCOVERY.xml	133,207
artifacts/discovery/websites.json	1,933
artifacts/discovery.csv	350
artifacts/discovery.json	24,488
artifacts/enrichment/1990.json	1,901
artifacts/enrichment/22.json	1,874
artifacts/enrichment/443.json	1,892
artifacts/enrichment/53.json	1,886

Artifact Path	Size (bytes)
artifacts/enrichment/7070.json	1,895
artifacts/enrichment/80.json	1,996
artifacts/enrichment/builtwith.json	806
artifacts/enrichment/vuln_0a7c8d77a2ad.json	2,123
artifacts/enrichment/vuln_0e9970a5a838.json	2,181
artifacts/enrichment/vuln_16e3f4fbfede.json	2,317
artifacts/enrichment/vuln_27d6e876416c.json	2,277
artifacts/enrichment/vuln_2c5100794604.json	2,154
artifacts/enrichment/vuln_2ffdea09c85b.json	2,124
artifacts/enrichment/vuln_31642d28952d.json	2,226
artifacts/enrichment/vuln_31dc0d77dec2.json	2,258
artifacts/enrichment/vuln_3a1cd8478be6.json	2,271
artifacts/enrichment/vuln_3e9181c589a1.json	2,158

Artifact Path	Size (bytes)
artifacts/enrichment/vuln_3ebdb84b8df2.json	2,150
artifacts/enrichment/vuln_3fac5882ca63.json	2,304
artifacts/enrichment/vuln_47bcd63bc4cb.json	2,141
artifacts/enrichment/vuln_4cca3d24577f.json	2,225
artifacts/enrichment/vuln_502fc3efdcbb.json	2,215
artifacts/enrichment/vuln_538c9058204b.json	2,368
artifacts/enrichment/vuln_5805db5e0f3b.json	2,130
artifacts/enrichment/vuln_5b6ec304f664.json	2,276
artifacts/enrichment/vuln_6aab9e532f4d.json	2,205
artifacts/enrichment/vuln_797f39e3a2a8.json	2,259
artifacts/enrichment/vuln_7b0599c6dafd.json	2,256
artifacts/enrichment/vuln_839f9fdf2ecd.json	2,144
artifacts/enrichment/vuln_87d369c2db70.json	2,132

Artifact Path	Size (bytes)
artifacts/enrichment/vuln_8f025c43e29a.json	2,166
artifacts/enrichment/vuln_a4e671335191.json	2,384
artifacts/enrichment/vuln_a9606ca282c8.json	2,238
artifacts/enrichment/vuln_aacfa6183616.json	2,143
artifacts/enrichment/vuln_b2dd3660ea63.json	2,195
artifacts/enrichment/vuln_b3ff91233170.json	2,247
artifacts/enrichment/vuln_bb575fa50bd5.json	2,355
artifacts/enrichment/vuln_c26719976948.json	2,114
artifacts/enrichment/vuln_cc2f12f5d425.json	2,156
artifacts/enrichment/vuln_d25b833c8ea7.json	2,175
artifacts/enrichment/vuln_d8df761fc465.json	2,145
artifacts/enrichment/vuln_e160cb1a2d5b.json	2,133
artifacts/enrichment/vuln_ecc9aaa3b751.json	2,189

Artifact Path	Size (bytes)
artifacts/enrichment/vuln_fe80fd3fe58c.json	2,250
artifacts/enrichment/vuln_fedc956996ce.json	2,167
artifacts/enrichment/whois.json	3,428
artifacts/enrichment.json	2,346
artifacts/VAPTORMSF/auto_10_0_0_132.rc	230
artifacts/VAPTORMSF/auto_10_0_0_254.rc	475
artifacts/VAPTORMSF/auto_44_238_29_244.rc	320
artifacts/VAPTORMSF/msf_10_0_0_132.txt	2,416
artifacts/VAPTORMSF/msf_10_0_0_254.txt	4,996
artifacts/VAPTORMSF/msf_44_238_29_244.txt	3,164
artifacts/metasploit_auth/auth_10_0_0_132.rc	324
artifacts/metasploit_auth/msf_auth_10_0_0_132.txt	2,191
artifacts/metasploit_auth/userpass_trimmed.userpass.txt	7,068

Artifact Path	Size (bytes)
artifacts/mitm/VAPTORARP20260411185825.log	14,412,307
artifacts/mitm/VAPTORARP20260411185849.log	433
artifacts/mitm/VAPTORCAP20260411185848.pcapng	0
artifacts/mitm/VAPTORPCAP20260411185848.log	532
artifacts/mitm/pcap_summary.json	723
artifacts/mitm/recon_observations.json	15,645
artifacts/msf_auth.json	1,568
artifacts/msf_verification.json	2,572
artifacts/VAPTORDISCOVERY.txt	90
artifacts/phases_summary.json	1,868
artifacts/sast/.gitleaks.toml	541
artifacts/sast/bandit_results.json	407
artifacts/sast/bearer_results.json	86,421

Artifact Path	Size (bytes)
artifacts/sast/gitleaks_results.json	3
artifacts/sast/sast_summary.json	779
artifacts/scan_events.jsonl	1,664
artifacts/scanner_execution.json	3,825
artifacts/scanner_validation.json	570
artifacts/scanner_validation_penetration_test.json	540
artifacts/scanner_validation_vulnerability_assessment.json	258
artifacts/sniper/loot/credentials/brutex-10.0.0.103.txt	1,717
artifacts/sniper/loot/credentials/brutex-10.0.0.108.txt	1,718
artifacts/sniper/loot/credentials/brutex-10.0.0.128.txt	1,717
artifacts/sniper/loot/credentials/brutex-10.0.0.132.txt	2,336
artifacts/sniper/loot/credentials/brutex-ec2-44-228-249-3.us-west-2.compute.amazonaws.com.txt	1,717
artifacts/sniper/loot/credentials/brutex-ec2-44-238-29-244.us-west-2.compute.amazonaws.com.txt	1,717

Artifact Path	Size (bytes)
artifacts/sniper/loot/credentials/brutex-www.adsl.vf.txt	2,046
artifacts/sniper/loot/domains/domains-all-sorted-00	156
artifacts/sniper/loot/domains/domains-all-sorted.txt	156
artifacts/sniper/loot/domains/targets-all-sorted.txt	156
artifacts/sniper/loot/domains/targets-all-unscanned.txt	0
artifacts/sniper/loot/domains/targets.txt	555
artifacts/sniper/loot/ips/ips-all-sorted.txt	38
artifacts/sniper/loot/ips/ips-all-unsorted.txt	38
artifacts/sniper/loot/VAPTORDISCOVERY/dns-10.0.0.103.txt	11
artifacts/sniper/loot/VAPTORDISCOVERY/dns-10.0.0.108.txt	11
artifacts/sniper/loot/VAPTORDISCOVERY/dns-10.0.0.128.txt	11
artifacts/sniper/loot/VAPTORDISCOVERY/dns-10.0.0.132.txt	11
artifacts/sniper/loot/VAPTORDISCOVERY/dns-ec2-44-228-249-3.us-west-2.compute.amazonaws.com.txt	13

Artifact Path	Size (bytes)
artifacts/sniper/loot/VAPTORDISCOVERY/dns-ec2-44-238-29-244.us-west-2.compute.amazonaws.com.txt	14
artifacts/sniper/loot/VAPTORDISCOVERY/dns-www.adsl.vf.txt	11
artifacts/sniper/loot/VAPTORDISCOVERY/livehosts-all-sorted-00	95
artifacts/sniper/loot/VAPTORDISCOVERY/livehosts-sorted.txt	95
artifacts/sniper/loot/VAPTORDISCOVERY/livehosts-unsorted.txt	179
artifacts/sniper/loot/VAPTORDISCOVERY/macaddress-10.0.0.103.txt	44
artifacts/sniper/loot/VAPTORDISCOVERY/macaddress-10.0.0.128.txt	30
artifacts/sniper/loot/VAPTORDISCOVERY/macaddress-www.adsl.vf.txt	48
artifacts/sniper/loot/VAPTORDISCOVERY/VAPTORDISCOVERY-10.0.0.103.txt	853
artifacts/sniper/loot/VAPTORDISCOVERY/VAPTORDISCOVERY-10.0.0.103.xml	4,398
artifacts/sniper/loot/VAPTORDISCOVERY/VAPTORDISCOVERY-10.0.0.108.txt	208
artifacts/sniper/loot/VAPTORDISCOVERY/VAPTORDISCOVERY-10.0.0.108.xml	1,468
artifacts/sniper/loot/VAPTORDISCOVERY/VAPTORDISCOVERY-10.0.0.128.txt	673

Artifact Path	Size (bytes)
artifacts/sniper/loot/VAPTORDISCOVERY/VAPTORDISCOVERY-10.0.0.128.xml	9,684
artifacts/sniper/loot/VAPTORDISCOVERY/VAPTORDISCOVERY-10.0.0.132.txt	208
artifacts/sniper/loot/VAPTORDISCOVERY/VAPTORDISCOVERY-10.0.0.132.xml	1,468
artifacts/sniper/loot/VAPTORDISCOVERY/VAPTORDISCOVERY-ec2-44-228-249-3.us-west-2.compute.amazonaws.com.txt	208
artifacts/sniper/loot/VAPTORDISCOVERY/VAPTORDISCOVERY-ec2-44-228-249-3.us-west-2.compute.amazonaws.com.xml	1,620
artifacts/sniper/loot/VAPTORDISCOVERY/VAPTORDISCOVERY-ec2-44-238-29-244.us-west-2.compute.amazonaws.com.txt	859
artifacts/sniper/loot/VAPTORDISCOVERY/VAPTORDISCOVERY-ec2-44-238-29-244.us-west-2.compute.amazonaws.com.xml	4,749
artifacts/sniper/loot/VAPTORDISCOVERY/VAPTORDISCOVERY-www.adsl.vf.txt	840
artifacts/sniper/loot/VAPTORDISCOVERY/VAPTORDISCOVERY-www.adsl.vf.xml	4,443
artifacts/sniper/loot/VAPTORDISCOVERY/nmapreport-10.0.0.103-2026-04-12-08-40.html	7,098
artifacts/sniper/loot/VAPTORDISCOVERY/nmapreport-10.0.0.103.html	7,098

Artifact Path	Size (bytes)
artifacts/sniper/loot/VAPTORDISCOVERY/nmapreport-10.0.0.108-2026-04-12-08-40.html	4,687
artifacts/sniper/loot/VAPTORDISCOVERY/nmapreport-10.0.0.108.html	4,687
artifacts/sniper/loot/VAPTORDISCOVERY/nmapreport-10.0.0.128-2026-04-12-08-41.html	6,163
artifacts/sniper/loot/VAPTORDISCOVERY/nmapreport-10.0.0.128.html	6,163
artifacts/sniper/loot/VAPTORDISCOVERY/nmapreport-10.0.0.132-2026-04-12-08-43.html	4,687
artifacts/sniper/loot/VAPTORDISCOVERY/nmapreport-10.0.0.132.html	4,687
artifacts/sniper/loot/VAPTORDISCOVERY/nmapreport-ec2-44-228-249-3.us-west-2.compute.amazonaws.com-2026-04-12-09-43.html	4,763
artifacts/sniper/loot/VAPTORDISCOVERY/nmapreport-ec2-44-228-249-3.us-west-2.compute.amazonaws.com.html	4,763
artifacts/sniper/loot/VAPTORDISCOVERY/nmapreport-ec2-44-238-29-244.us-west-2.compute.amazonaws.com-2026-04-12-10-17.html	8,401
artifacts/sniper/loot/VAPTORDISCOVERY/nmapreport-ec2-44-238-29-244.us-west-2.compute.amazonaws.com.html	8,401
artifacts/sniper/loot/VAPTORDISCOVERY/nmapreport-www.adsl.vf-2026-04-12-09-42.html	8,784

Artifact Path	Size (bytes)
artifacts/sniper/loot/VAPTORDISCOVERY/nmapreport-www.adsl.vf.html	8,784
artifacts/sniper/loot/VAPTORDISCOVERY/osfingerprint-10.0.0.132.txt	50
artifacts/sniper/loot/VAPTORDISCOVERY/osfingerprint-www.adsl.vf.txt	41
artifacts/sniper/loot/VAPTORDISCOVERY/ports-10.0.0.132.old	4
artifacts/sniper/loot/VAPTORDISCOVERY/ports-ec2-44-238-29-244.us-west-2.compute.amazonaws.com.diff	10
artifacts/sniper/loot/VAPTORDISCOVERY/ports-ec2-44-238-29-244.us-west-2.compute.amazonaws.com.old	4
artifacts/sniper/loot/VAPTORDISCOVERY/ports-ec2-44-238-29-244.us-west-2.compute.amazonaws.com.txt	8
artifacts/sniper/loot/VAPTORDISCOVERY/ports-www.adsl.vf.diff	12
artifacts/sniper/loot/VAPTORDISCOVERY/ports-www.adsl.vf.old	13
artifacts/sniper/loot/VAPTORDISCOVERY/ports-www.adsl.vf.txt	19
artifacts/sniper/loot/output/VAPTORMSF-10.0.0.132-port22-libssh_auth_bypass.txt	293

Artifact Path	Size (bytes)
artifacts/sniper/loot/output/VAPTORMSF-10.0.0.132-port22-ssh_enumusers.txt	430
artifacts/sniper/loot/output/VAPTORMSF-10.0.0.132-port22-ssh_version.txt	2,195
artifacts/sniper/loot/output/VAPTORDISCOVERY-10.0.0.132-port22.txt	4,490
artifacts/sniper/loot/output/VAPTORDISCOVERY-ec2-44-238-29-244.us-west-2.compute.amazonaws.com-port80.txt	1,964
artifacts/sniper/loot/output/VAPTORDISCOVERY-www.adsl.vf-port443.txt	1,797
artifacts/sniper/loot/output/VAPTORDISCOVERY-www.adsl.vf-port53.txt	3,890
artifacts/sniper/loot/output/VAPTORDISCOVERY-www.adsl.vf-port80.txt	7,248
artifacts/sniper/loot/output/sniper-10.0.0.103-nuke-202604120817.txt	10,313
artifacts/sniper/loot/output/sniper-10.0.0.108-nuke-202604120840.txt	9,826
artifacts/sniper/loot/output/sniper-10.0.0.128-nuke-202604120840.txt	10,248
artifacts/sniper/loot/output/sniper-10.0.0.132-nuke-202604120841.txt	25,514
artifacts/sniper/loot/output/sniper-ec2-44-228-249-3.us-west-2.compute.amazonaws.com-nuke-202604120942.txt	9,874

Artifact Path	Size (bytes)
artifacts/sniper/loot/output/sniper-ec2-44-238-29-244.us-west-2.compute.amazonaws.com-nuke-202604120943.txt	125,430
artifacts/sniper/loot/output/sniper-ec2-44-238-29-244.us-west-2.compute.amazonaws.com-webporthttp-80-202604120943.txt	110,084
artifacts/sniper/loot/output/sniper-www.adsl.vf-nuke-202604120843.txt	200,366
artifacts/sniper/loot/output/sniper-www.adsl.vf-webporthttp-80-202604120845.txt	90,449
artifacts/sniper/loot/output/sniper-www.adsl.vf-webporthttps-443-202604120858.txt	88,932
artifacts/sniper/loot/output/sshaudit-10.0.0.132-port22.txt	4,098
artifacts/sniper/loot/reports/sniper-10.0.0.103-nuke-202604120817.txt.html	21,639
artifacts/sniper/loot/reports/sniper-10.0.0.108-nuke-202604120840.txt.html	21,405
artifacts/sniper/loot/reports/sniper-10.0.0.128-nuke-202604120840.txt.html	21,827
artifacts/sniper/loot/reports/sniper-10.0.0.132-nuke-202604120841.txt.html	41,018
artifacts/sniper/loot/reports/sniper-ec2-44-228-249-3.us-west-2.compute.amazonaws.com-nuke-202604120942.txt.html	21,491

Artifact Path	Size (bytes)
artifacts/sniper/loot/reports/sniper-ec2-44-238-29-244.us-west-2.compute.amazonaws.com-nuke-202604120943.txt.html	194,817
artifacts/sniper/loot/reports/sniper-ec2-44-238-29-244.us-west-2.compute.amazonaws.com-webporthttp-80-202604120943.txt.html	167,624
artifacts/sniper/loot/reports/sniper-www.adsl.vf-nuke-202604120843.txt.html	260,938
artifacts/sniper/loot/reports/sniper-www.adsl.vf-webporthttp-80-202604120845.txt.html	112,590
artifacts/sniper/loot/reports/sniper-www.adsl.vf-webporthttps-443-202604120858.txt.html	114,678
artifacts/sniper/loot/scans/-AUTO_BRUTE.txt	0
artifacts/sniper/loot/scans/-osint.txt	0
artifacts/sniper/loot/scans/-recon.txt	0
artifacts/sniper/loot/scans/10.0.0.103-AUTO_BRUTE.txt	0
artifacts/sniper/loot/scans/10.0.0.103-normal.txt	43
artifacts/sniper/loot/scans/10.0.0.103-nuke.txt	113
artifacts/sniper/loot/scans/10.0.0.103-osint.txt	0

Artifact Path	Size (bytes)
artifacts/sniper/loot/scans/10.0.0.103-recon.txt	0
artifacts/sniper/loot/scans/10.0.0.103-webscan.txt	0
artifacts/sniper/loot/scans/10.0.0.108-AUTO_BRUTE.txt	0
artifacts/sniper/loot/scans/10.0.0.108-normal.txt	43
artifacts/sniper/loot/scans/10.0.0.108-nuke.txt	113
artifacts/sniper/loot/scans/10.0.0.128-AUTO_BRUTE.txt	0
artifacts/sniper/loot/scans/10.0.0.128-normal.txt	43
artifacts/sniper/loot/scans/10.0.0.128-nuke.txt	113
artifacts/sniper/loot/scans/10.0.0.132-AUTO_BRUTE.txt	0
artifacts/sniper/loot/scans/10.0.0.132-normal.txt	43
artifacts/sniper/loot/scans/10.0.0.132-nuke.txt	113
artifacts/sniper/loot/scans/ec2-44-228-249-3.us-west-2.compute.amazonaws.com-AUTO_BRUTE.txt	0
artifacts/sniper/loot/scans/ec2-44-228-249-3.us-west-2.compute.amazonaws.com-normal.txt	81

Artifact Path	Size (bytes)
artifacts/sniper/loot/scans/ec2-44-228-249-3.us-west-2.compute.amazonaws.com-nuke.txt	189
artifacts/sniper/loot/scans/ec2-44-238-29-244.us-west-2.compute.amazonaws.com-AUTO_BRUTE.txt	0
artifacts/sniper/loot/scans/ec2-44-238-29-244.us-west-2.compute.amazonaws.com-normal.txt	82
artifacts/sniper/loot/scans/ec2-44-238-29-244.us-west-2.compute.amazonaws.com-nuke.txt	191
artifacts/sniper/loot/scans/ec2-44-238-29-244.us-west-2.compute.amazonaws.com-webporthttp.txt	128
artifacts/sniper/loot/scans/notifications.txt	24,346
artifacts/sniper/loot/scans/notifications_new.txt	8,409
artifacts/sniper/loot/scans/scheduled/daily.sh	0
artifacts/sniper/loot/scans/scheduled/monthly.sh	0
artifacts/sniper/loot/scans/scheduled/weekly.sh	0
artifacts/sniper/loot/scans/tasks-running.txt	2
artifacts/sniper/loot/scans/tasks.txt	1,056
artifacts/sniper/loot/scans/updated.txt	0

Artifact Path	Size (bytes)
artifacts/sniper/loot/scans/www.adsl.vf-AUTO_BRUTE.txt	0
artifacts/sniper/loot/scans/www.adsl.vf-normal.txt	44
artifacts/sniper/loot/scans/www.adsl.vf-nuke.txt	115
artifacts/sniper/loot/scans/www.adsl.vf-webporthttp.txt	90
artifacts/sniper/loot/scans/www.adsl.vf-webporthttps.txt	92
artifacts/sniper/loot/screenshots/ec2-44-238-29-244.us-west-2.compute.amazonaws.com-port80.jpg	50,982
artifacts/sniper/loot/screenshots/www.adsl.vf-port443.jpg	24,248
artifacts/sniper/loot/screenshots/www.adsl.vf-port80.jpg	24,248
artifacts/sniper/loot/vulnerabilities/critical_vulns_total.txt	2
artifacts/sniper/loot/vulnerabilities/high_vulns_total.txt	2
artifacts/sniper/loot/vulnerabilities/info_vulns_total.txt	3
artifacts/sniper/loot/vulnerabilities/low_vulns_total.txt	2
artifacts/sniper/loot/vulnerabilities/medium_vulns_total.txt	3

Artifact Path	Size (bytes)
artifacts/sniper/loot/vulnerabilities/sc0pe-10.0.0.103-https-Strict_Tranposrt_Security_Not_Enforced.txt	77
artifacts/sniper/loot/vulnerabilities/sc0pe-10.0.0.132-Component_With_Known_Vulnerabilities_NMap.txt	645
artifacts/sniper/loot/vulnerabilities/sc0pe-10.0.0.132-Interesting_Ports_Found.txt	52
artifacts/sniper/loot/vulnerabilities/sc0pe-all-vulnerabilities-sorted.txt	6,971
artifacts/sniper/loot/vulnerabilities/sc0pe-ec2-44-238-29-244.us-west-2.compute.amazonaws.com-Component_With_Known_Vulnerabilities_NMap.txt	166
artifacts/sniper/loot/vulnerabilities/sc0pe-ec2-44-238-29-244.us-west-2.compute.amazonaws.com-Nuclei_Vulnerability_Scan_HTTP.txt	3,320
artifacts/sniper/loot/vulnerabilities/sc0pe-ec2-44-238-29-244.us-west-2.compute.amazonaws.com-http-Clear_Text_Protocol_HTTP.txt	118
artifacts/sniper/loot/vulnerabilities/sc0pe-ec2-44-238-29-244.us-west-2.compute.amazonaws.com-http-Server_Header_Disclosure_HTTP.txt	134
artifacts/sniper/loot/vulnerabilities/sc0pe-www.adsl.vf-Component_With_Known_Vulnerabilities_NMap.txt	2,046

Artifact Path	Size (bytes)
artifacts/sniper/loot/vulnerabilities/sc0pe-www.adsl.vf-Interesting_Ports_Found.txt	53
artifacts/sniper/loot/vulnerabilities/sc0pe-www.adsl.vf-Nuclei_Vulnerability_Scan_HTTP.txt	185
artifacts/sniper/loot/vulnerabilities/sc0pe-www.adsl.vf-Nuclei_Vulnerability_Scan_HTTPS.txt	97
artifacts/sniper/loot/vulnerabilities/sc0pe-www.adsl.vf-https-Strict_Tranposrt_Security_Not_Enforced.txt	78
artifacts/sniper/loot/vulnerabilities/vuln_score_total.txt	3
artifacts/sniper/loot/vulnerabilities/vulnerability-report-10.0.0.103.txt	550
artifacts/sniper/loot/vulnerabilities/vulnerability-report-10.0.0.108.txt	473
artifacts/sniper/loot/vulnerabilities/vulnerability-report-10.0.0.128.txt	473
artifacts/sniper/loot/vulnerabilities/vulnerability-report-10.0.0.132.txt	1,171
artifacts/sniper/loot/vulnerabilities/vulnerability-report-ec2-44-228-249-3.us-west-2.compute.amazonaws.com.txt	473
artifacts/sniper/loot/vulnerabilities/vulnerability-report-ec2-44-238-29-244.us-west-2.compute.amazonaws.com.txt	4,213

Artifact Path	Size (bytes)
artifacts/sniper/loot/vulnerabilities/vulnerability-report-www.adsl.vf.txt	2,934
artifacts/sniper/loot/vulnerabilities/vulnerability-risk-10.0.0.103.txt	2
artifacts/sniper/loot/vulnerabilities/vulnerability-risk-10.0.0.108.txt	2
artifacts/sniper/loot/vulnerabilities/vulnerability-risk-10.0.0.128.txt	2
artifacts/sniper/loot/vulnerabilities/vulnerability-risk-10.0.0.132.txt	3
artifacts/sniper/loot/vulnerabilities/vulnerability-risk-ec2-44-228-249-3.us-west-2.compute.amazonaws.com.txt	2
artifacts/sniper/loot/vulnerabilities/vulnerability-risk-ec2-44-238-29-244.us-west-2.compute.amazonaws.com.txt	3
artifacts/sniper/loot/vulnerabilities/vulnerability-risk-www.adsl.vf.txt	3
artifacts/sniper/loot/web/curldebug-www.adsl.vf-443.txt	598
artifacts/sniper/loot/web/hackertarget-http-ec2-44-238-29-244.us-west-2.compute.amazonaws.com.txt	57
artifacts/sniper/loot/web/headers-http-ec2-44-238-29-244.us-west-2.compute.amazonaws.com-80.txt	247

Artifact Path	Size (bytes)
artifacts/sniper/loot/web/http_options-ec2-44-238-29-244.us-west-2.compute.amazonaws.com-port80.txt	40
artifacts/sniper/loot/web/injectx-ec2-44-238-29-244.us-west-2.compute.amazonaws.com-http-80.raw	13,018
artifacts/sniper/loot/web/injectx-ec2-44-238-29-244.us-west-2.compute.amazonaws.com-http-80.txt	10,243
artifacts/sniper/loot/web/VAPTORRECON-http-ec2-44-238-29-244.us-west-2.compute.amazonaws.com-port80.txt	2,405
artifacts/sniper/loot/web/VAPTORRECON-http-www.adsl.vf-port80.txt	208
artifacts/sniper/loot/web/VAPTORRECON-https-www.adsl.vf-port443.txt	113
artifacts/sniper/loot/web/robots-www.adsl.vf:80-http.txt	610
artifacts/sniper/loot/web/smuggler-ec2-44-238-29-244.us-west-2.compute.amazonaws.com-port80.txt	58,229
artifacts/sniper/loot/web/smuggler-www.adsl.vf-port443.txt	58,193
artifacts/sniper/loot/web/smuggler-www.adsl.vf-port80.txt	58,191

Artifact Path	Size (bytes)
artifacts/sniper/loot/web/spider-ec2-44-238-29-244.us-west-2.compute.amazonaws.com.txt	57
artifacts/sniper/loot/web/spider-new-ec2-44-238-29-244.us-west-2.compute.amazonaws.com.txt	57
artifacts/sniper/loot/web/sslscan-www.adsl.vf-443.txt	1,865
artifacts/sniper/loot/web/static-idor-ec2-44-238-29-244.us-west-2.compute.amazonaws.com.txt	57
artifacts/sniper/loot/web/static-parameters-ec2-44-238-29-244.us-west-2.compute.amazonaws.com.txt	57
artifacts/sniper/loot/web/static-sql-ec2-44-238-29-244.us-west-2.compute.amazonaws.com.txt	57
artifacts/sniper/loot/web/static-ssti-ec2-44-238-29-244.us-west-2.compute.amazonaws.com.txt	57
artifacts/sniper/loot/web/static-xss-ec2-44-238-29-244.us-west-2.compute.amazonaws.com.txt	57
artifacts/sniper/loot/web/title-http-ec2-44-238-29-244.us-west-2.compute.amazonaws.com-80.txt	19
artifacts/sniper/loot/web/title-http-www.adsl.vf-80.txt	16
artifacts/sniper/loot/web/waf-ec2-44-238-29-244.us-west-2.compute.amazonaws.com-http-port80.txt	1,136
artifacts/sniper/loot/web/waf-www.adsl.vf-http-port80.txt	623

Artifact Path	Size (bytes)
artifacts/sniper/loot/web/waf-www.adsl.vf-https-port443.txt	912
artifacts/sniper/loot/web/webhosts-all-sorted-00	4
artifacts/sniper/loot/web/webhosts-sorted.txt	4
artifacts/sniper/loot/web/webhosts-unsorted.txt	74
artifacts/sniper/loot/web/websource-http-ec2-44-238-29-244.us-west-2.compute.amazonaws.com-80.txt	247
artifacts/sniper/loot/web/webtech-ec2-44-238-29-244.us-west-2.compute.amazonaws.com-http-port80.txt	81
artifacts/sniper/loot/web/VAPTORWEBPROBE-ec2-44-238-29-244.us-west-2.compute.amazonaws.com-http-port80.txt	234
artifacts/sniper/sniper_output.txt	400,124
artifacts/sniper/sniper_summary.json	25,926
artifacts/sniper/sniper_targets.txt	155
artifacts/sqlmap_http___testasp.vulnweb.com/testasp.vulnweb.com/log	0

Artifact Path	Size (bytes)
artifacts/sqlmap_http___testasp.vulnweb.com/testasp.vulnweb.com/session.sqlite	8,192
artifacts/sqlmap_http___testasp.vulnweb.com/testasp.vulnweb.com/target.txt	249
artifacts/sqlmap_http___testaspnet.vulnweb.com/testaspnet.vulnweb.com/log	0
artifacts/sqlmap_http___testaspnet.vulnweb.com/testaspnet.vulnweb.com/session.sqlite	8,192
artifacts/sqlmap_http___testaspnet.vulnweb.com/testaspnet.vulnweb.com/target.txt	258
artifacts/sqlmap_results.json	339
artifacts/vaptorgpt.json	37,943
artifacts/vaptorset/campaign_results.json	750
artifacts/vaptorset/set_summary.json	1,819
artifacts/vaptorset/templates/gmail.html	1,671
artifacts/vaptorset/templates/office365.html	1,447
artifacts/vaptorset/templates/router_login.html	1,250
artifacts/waf_vhost.json	2,778

Artifact Path	Size (bytes)
artifacts/web_recon.json	4,042
artifacts/web_target_gating.json	904
artifacts/websites.json	1,933
artifacts/zap_http_testasp.vulnweb.com.json	67,261
artifacts/zap_http_testaspnet.vulnweb.com.json	102,944
artifacts/zap_results.json	66,313
audit/audit_analysis.json	80,727
audit/include_in_report.flag	8