

Introduction

mStock Trading API is a set of REST-like HTTP APIs that expose many capabilities required to build a complete stock market investment and trading platform. It lets you execute orders in real time (equities, derivatives), stream live market data over WebSockets, get order status through websockets & much more.

All inputs are form-encoded parameters and responses are JSON (apart from a couple exceptions). The responses may be Gzipped. Standard HTTP codes are used to indicate success and error states with accompanying JSON data. The API endpoints are not cross site request enabled, hence cannot be called directly from browser.

Note

If you don't have a mStock account, read more about it and sign up [here](#). If you already have the mStock account you can generate the api key [here](#).

Libraries and SDKs

- [Python](#)
- [NodeJS](#) NEW
- [Postman Collection](#) NEW

Version

The mstock trading API current version is 1.0 and All requests go by default to this version. Look for this space for any version related changes in future

Note

This version is a mstock trading API version and should not be confused with the specific library release version going forward

Root End point

- Interactive URL : <https://api.mstock.trade>
- Broadcasting URL : <wss://ws.mstock.trade>

Rate Limits

Rate Limit	Order APIs	Data APIs	Quote APIs	Non Trading APIs
per second	30	1	20	Another order
per minute	250	1000	Unlimited	Unlimited
per hour	1000	5000	Unlimited	Unlimited
per day	Unlimited	Unlimited	Unlimited	Unlimited

Api Key & Access token Validity

Token Type	Validity	Note
API Key	1 year, 1 month, 1 day	Used for initial authentication. Store securely.
Access Token	Within 12 hours or on the same day, whichever occurs first	Required for all API requests. Renew daily.



BOD and EOD Timings

Please note that BOD (Beginning of Day) operations occur between 07:00 AM and 08:30 AM, while EOD (End of Day) processes run from 07:00 PM to 09:00 PM. During these times, system performance may be affected. Plan accordingly.

Request Headers to be passed in every API call

X-Mirae-Version : Specifies the version of the API being used. In this case, it is set to 1.

Authorization : A token-based authentication header. The format is token api_key:jwtToken.

Content-Type : A token-based authentication header. The format is token api_key:jwtToken.

Content-Type : For this request, it is set to application/json, which is used for submitting form data through body

X-PrivateKey : ay3xxxxxxxxxxYzkB/MAK@@@