

Orders

Glossary

Param	Value	Description
Variety	NORMAL	Normal Order (Regular)
	AMO	After Market Order
	STOPLOSS	Stop Loss Order
Order Type	MARKET	Market Order
	LIMIT	Limit Order
	STOPLOSS_LIMIT	Stop Loss Order
	STOPLOSS_MARKET	Stop Loss Market Order
Product Type	DELIVERY	Cash & Carry for equity
	INTRADAY	Margin Intraday Squareoff
	MARGIN	Margin Delivery
	CARRYFORWARD	Normal for futures and options
Duration	DAY	Regular order
	IOC	Immediate or Cancel

Orders APIs

The order APIs let you place orders of different varieties, modify and cancel pending orders, retrieve the daily order and more.

Method	Path	Description
GET	https://api.mstock.trade/openapi/typeb/orders/regular	Place a new order
PUT	https://api.mstock.trade/openapi/typeb/orders/regular/{OrderID}	Modify a pending order
DELETE	https://api.mstock.trade/openapi/typeb/orders/regular/{OrderID}	Cancel a pending order
POST	https://api.mstock.trade/openapi/typeb/orders/cancelall	Cancel all pending order
GET	https://api.mstock.trade/openapi/typeb/orders	View all the existing orders.
GET	https://api.mstock.trade/openapi/typeb/trades	This endpoint returns a list of all trades generated upon the
GET	https://api.mstock.trade/openapi/typeb/order/details	View the status of individual order

Order Placement

This endpoint allows users to place a regular trading order in the specified market. Users must provide relevant order details such as the trading symbol, exchange, transaction type, and other order specifics.

Request Headers -

- **X-Mirae-Version** : Specifies the version of the API being used. In this case, it is set to 1.
- **Authorization** : A token-based authentication header. The format is token jwtToken.

- **Content-Type** : A token-based authentication header. The format is token jwtToken. Content-Type: For this request, it is set to application/json, which is used for submitting form data through body.
- **X-PrivateKey** : api_key

cURL

```
curl --location 'https://api.mstock.trade/openapi/typeb/orders/regular' \
--header 'X-Mirae-Version: 1' \
--header 'X-PrivateKey: api_key' \
--header 'Authorization: Bearer jwtToken' \
--header 'Content-Type: application/json' \
--data '{
  "variety": "NORMAL",
  "tradingsymbol": "ACC-EQ",
  "symboltoken": "22",
  "exchange": "NSE",
  "transactiontype": "BUY",
  "ordertype": "MARKET",
  "quantity": "20",
  "producttype": "DELIVERY",
  "price": "194.50",
  "triggerprice": "0",
  "squareoff": "0",
  "stoploss": "0",
  "trailingStopLoss": "",
  "disclosedquantity": "",
  "duration": "DAY",
  "ordertag": ""
}'
```

Node.js

```
import axios from 'axios';

const response = await axios.get(
  'https://api.mstock.trade/openapi/typeb/orders/regular',
  // '{
  //   "variety": "NORMAL",
  //   "tradingsymbol": "ACC-EQ",
  //   "symboltoken": "22",
  //   "exchange": "NSE",
  //   "transactiontype": "BUY",
  //   "ordertype": "MARKET",
  //   "quantity": "20",
  //   "producttype": "DELIVERY",
  //   "price": "194.50",
  //   "triggerprice": "0",
  //   "squareoff": "0",
  //   "stoploss": "0",
  //   "trailingStopLoss": "",
  //   "disclosedquantity": "",
  //   "duration": "DAY",
  //   "ordertag": ""
  // }',
  {
    'variety': 'NORMAL',
    'tradingsymbol': 'ACC-EQ',
    'symboltoken': '22',
    'exchange': 'NSE',
    'transactiontype': 'BUY',
    'ordertype': 'MARKET',
    'quantity': '20',
    'producttype': 'DELIVERY',
    'price': '194.50',
    'triggerprice': '0',
    'squareoff': '0',
    'stoploss': '0',
    'trailingStopLoss': '',
    'disclosedquantity': '',
    'duration': 'DAY',
    'ordertag': ''
  }
);
```

```

    },
    {
        headers: {
            'X-Mirae-Version': '1',
            'X-PrivateKey': 'api_key',
            'Authorization': 'Bearer jwtToken',
            'Content-Type': 'application/json'
        }
    }
);

```

Python

```

import http.client
import json

conn = http.client.HTTPConnection('api.mstock.trade')
headers = {
    'X-Mirae-Version': '1',
    'X-PrivateKey': 'api_key',
    'Authorization': 'Bearer jwtToken',
    'Content-Type': 'application/json',
}
json_data = {
    'variety': 'NORMAL',
    'tradingsymbol': 'ACC-EQ',
    'symboltoken': '22',
    'exchange': 'NSE',
    'transactiontype': 'BUY',
    'ordertype': 'MARKET',
    'quantity': '20',
    'producttype': 'DELIVERY',
    'price': '194.50',
    'triggerprice': '0',
    'squareoff': '0',
    'stoploss': '0',
    'trailingStopLoss': '',
    'disclosedquantity': '',
    'duration': 'DAY',
    'ordertag': '',
}
conn.request(
    'GET',
    'openapi/typeb/orders/regular',
    json.dumps(json_data),
    # '{\n    "variety": "NORMAL",\n    "tradingsymbol": "ACC-EQ",\n
"symboltoken": "22",\n    "exchange": "NSE",\n    "transactiontype": "BUY",\n
"ordertype": "MARKET",\n    "quantity": "20",\n    "producttype": "DELIVERY",\n
"price": "194.50",\n    "triggerprice": "0",\n    "squareoff": "0",\n    "stoploss":
"0",\n    "trailingStopLoss": "",\n    "disclosedquantity": "",\n    "duration":
"DAY",\n    "ordertag": ""\n    }',
    headers
)
response = conn.getresponse()

```

Java

```

import java.io.IOException;
import java.net.URI;
import java.net.http.HttpClient;

```

```
import java.net.http.HttpRequest;
import java.net.http.HttpRequest.BodyPublishers;
import java.net.http.HttpResponse;

HttpClient client = HttpClient.newBuilder()
    .followRedirects(HttpClient.Redirect.NORMAL)
    .build();

HttpRequest request = HttpRequest.newBuilder()
    .uri(URI.create("https://api.mstock.trade/openapi/typeb/orders/regular"))
    .GET(BodyPublishers.ofString("{\n    \"variety\": \"NORMAL\",\n    \"tradingsymbol\": \"ACC-EQ\",\n    \"symboltoken\": \"22\",\n    \"exchange\": \"NSE\",\n    \"transactiontype\": \"BUY\",\n    \"ordertype\": \"MARKET\",\n    \"quantity\": \"20\",\n    \"producttype\": \"DELIVERY\",\n    \"price\": \"194.50\",\n    \"triggerprice\": \"0\",\n    \"squareoff\": \"0\",\n    \"stoploss\": \"0\",\n    \"trailingStopLoss\": \"\",\n    \"disclosedquantity\": \"\",\n    \"duration\": \"DAY\",\n    \"ordertag\": \"\"\n    }"))
    .setHeader("X-Mirae-Version", "1")
    .setHeader("X-PrivateKey", "api_key")
    .setHeader("Authorization", "Bearer jwtToken")
    .setHeader("Content-Type", "application/json")
    .build();

HttpResponse<String> response = client.send(request,
    HttpResponse.BodyHandlers.ofString());
```

Request Body - The body of the request must be URL-encoded and include the following parameters:

Field	Type	Description
variety	string	Variety of the order (<code>NORMAL</code> <code>AMO</code> <code>STOPLOSS</code>)
tradingsymbol	string	Refer Trading Symbol in Tables
symboltoken	string	Token of the contract for which modify is being sent
exchange	string	Exchange name : <code>NSE</code> <code>BSE</code> <code>NFO</code> <code>BFO</code>
transaction_type	string	The trading side of transaction : <code>BUY</code> <code>SELL</code>
order_type	string	Order Type : <code>LIMIT</code> <code>MARKET</code> <code>STOP_LOSS</code> <code>STOP_LOSS_MARKET</code>
quantity	string	Number of shares for the order
producttype	string	Product Type <code>DELIVERY</code> <code>INTRADAY</code> <code>MARGIN</code> <code>CARRYFORWARD</code>
price	string	Price at which order is placed

Field	Type	Description
trigger_price	string	Price at which the order is triggered, in case of <code>STOP_LOSS</code> <code>STOP_LOSS_MARKET</code>
squareoff	string	Auto Square off
stoploss	string	Stop Loss order
trailingStopLoss	string	Trailing Stop Loss order
disclosedquantity	string	Number of shares visible (Keep more than 30% of quantity)
duration	string	Regular Order Immediate or Cancel
ordertag	string	It is optional to apply to an order to identify. The length of the tag should be less than 20 (alphanumeric) characters.

Response Structure -

The response of the request will be based on authentication outcome.

- **Success (HTTP Status 200):** On successful order placement, the server returns a JSON object containing the order ID and status

```
{
  "status": "true",
  "message": "SUCCESS",
  "errorcode": "",
  "data": {
    "script": "ACC-EQ",
    "orderid": "1191241106101",
    "uniqueorderid": ""
  }
}
```

- **Failure (HTTP Status 400):** If the order fails due to invalid parameters, authentication issues, or other errors, the server will return an error message with below json format.

```
{
  "status": "false",
  "message": "Invalid request. Please try again.",
  "errorcode": "IA401",
  "data": null
}
```

- **Failure (HTTP Status 200):** If market is closed or not connected to NSE then api will return an error message with below json format.

```
{
  "status": "false",
  "message":
    "RMS:1141241105101:NSE,EQUITY,22,ACC,INTRADAY,,EQ,XXXXX,B,1,I,22,ACC,INTRADAY,89.449
    95,FUND LIMIT INSUFFICIENT,AVAILABLE FUND=0,ADDITIONAL REQUIRED
    FUND=572.36,CALCULATED MARGIN FOR ORDER=572.36",
  "errorcode": "RS-0111",
  "data": null
}
```

- **Failure (HTTP Status 400):** If the API Key is Invalid or expired.

```
{
  "status": "false",
  "message": "API is suspended/expired for use. Please check your API subscription
  and try again.",
  "errorcode": "IA403",
  "data": null
}
```

Order Modification

This endpoint allows users to update/modify an existing order by specifying the order ID and providing the updated order details.

Request Headers -

- **X-Mirae-Version** : Specifies the version of the API being used. In this case, it is set to 1.
- **Authorization** : A token-based authentication header. The format is token jwtToken.
- **Content-Type** : Indicated the media type of the resource. For this request, it is set to application/json, which is used for submitting form data through body
- **X-PrivateKey** : api_key

cURL

```
curl --location --request PUT
'https://api.mstock.trade/openapi/typeb/orders/regular/1191241106101' \
  --header 'X-Mirae-Version: 1' \
  --header 'X-PrivateKey: api_key' \
  --header 'Authorization: Bearer jwtToken' \
  --header 'Content-Type: application/json' \
  --data '{
    "variety": "NORMAL",
    "tradingsymbol": "ACC-EQ",
    "symboltoken": "22",
    "exchange": "NSE",
    "transactiontype": "BUY",
    "orderid": "1191241106101",
    "ordertype": "MARKET",
    "quantity": "15",
    "producttype": "DELIVERY",
    "duration": "DAY",
    "price": "2240",
  }
```

```
"triggerprice": "0",
"disclosedquantity": "",
"modqty_remng": "0"
}'
```

Node.js

```
import axios from 'axios';

const response = await axios.put(
  'https://api.mstock.trade/openapi/typeb/orders/regular/1191241106101',
  // '{\n  "variety": "NORMAL",\n  "tradingsymbol": "ACC-EQ",\n  "symboltoken":
  "22",\n  "exchange": "NSE",\n  "transactiontype": "BUY",\n  "orderid":
  "1191241106101",\n  "ordertype": "MARKET",\n  "quantity": "15",\n  "producttype":
  "DELIVERY",\n  "duration": "DAY",\n  "price": "2240",\n  "triggerprice": "0",\n
  "disclosedquantity": "",\n  "modqty_remng": "0"\n  }',
  {
    'variety': 'NORMAL',
    'tradingsymbol': 'ACC-EQ',
    'symboltoken': '22',
    'exchange': 'NSE',
    'transactiontype': 'BUY',
    'orderid': '1191241106101',
    'ordertype': 'MARKET',
    'quantity': '15',
    'producttype': 'DELIVERY',
    'duration': 'DAY',
    'price': '2240',
    'triggerprice': '0',
    'disclosedquantity': '',
    'modqty_remng': '0'
  },
  {
    headers: {
      'X-Mirae-Version': '1',
      'X-PrivateKey': 'api_key',
      'Authorization': 'Bearer jwtToken',
      'Content-Type': 'application/json'
    }
  }
);
```

Python

```
import http.client
import json

conn = http.client.HTTPConnection('api.mstock.trade')
headers = {
    'X-Mirae-Version': '1',
    'X-PrivateKey': 'api_key',
    'Authorization': 'Bearer jwtToken',
    'Content-Type': 'application/json',
}
json_data = {
    'variety': 'NORMAL',
    'tradingsymbol': 'ACC-EQ',
    'symboltoken': '22',
    'exchange': 'NSE',
    'transactiontype': 'BUY',
```

```

        'orderid': '1191241106101',
        'ordertype': 'MARKET',
        'quantity': '15',
        'producttype': 'DELIVERY',
        'duration': 'DAY',
        'price': '2240',
        'triggerprice': '0',
        'disclosedquantity': '',
        'modqty_remng': '0',
    }
    conn.request(
        'PUT',
        'openapi/typeb/orders/regular/1191241106101',
        json.dumps(json_data),
        # '{\n    "variety": "NORMAL",\n    "tradingsymbol": "ACC-EQ",\n    "symboltoken":
"22",\n    "exchange": "NSE",\n    "transactiontype": "BUY",\n    "orderid":
"1191241106101",\n    "ordertype": "MARKET",\n    "quantity": "15",\n    "producttype":
"DELIVERY",\n    "duration": "DAY",\n    "price": "2240",\n    "triggerprice": "0",\n
"disclosedquantity": "",\n    "modqty_remng": "0"\n    }',
        headers
    )
    response = conn.getresponse()

```

Java

```

import java.io.IOException;
import java.net.URI;
import java.net.http.HttpClient;
import java.net.http.HttpRequest;
import java.net.http.HttpRequest.BodyPublishers;
import java.net.http.HttpResponse;

HttpClient client = HttpClient.newBuilder()
    .followRedirects(HttpClient.Redirect.NORMAL)
    .build();

HttpRequest request = HttpRequest.newBuilder()

    .uri(URI.create("https://api.mstock.trade/openapi/typeb/orders/regular/1191241106101"))
    .PUT(BodyPublishers.ofString("{\n    \"variety\": \"NORMAL\", \n
    \"tradingsymbol\": \"ACC-EQ\", \n    \"symboltoken\": \"22\", \n    \"exchange\":
    \"NSE\", \n    \"transactiontype\": \"BUY\", \n    \"orderid\": \"1191241106101\", \n
    \"ordertype\": \"MARKET\", \n    \"quantity\": \"15\", \n    \"producttype\":
    \"DELIVERY\", \n    \"duration\": \"DAY\", \n    \"price\": \"2240\", \n
    \"triggerprice\": \"0\", \n    \"disclosedquantity\": \"\", \n    \"modqty_remng\":
    \"0\" \n    }"))
    .setHeader("X-Mirae-Version", "1")
    .setHeader("X-PrivateKey", "api_key")
    .setHeader("Authorization", "Bearer jwtToken")
    .setHeader("Content-Type", "application/json")
    .build();

HttpResponse<String> response = client.send(request,
    HttpResponse.BodyHandlers.ofString());

```

Path Parameter -

Field	Description
order_id	The unique identifier of the order to be updated or modified

Request Body - The body of the request must be URL-encoded and include the following parameters:

Field	Type	Description
variety	string	Variety of the order (<code>NORMAL</code> <code>AMO</code> <code>STOPLOSS</code>)
tradingsymbol	string	Refer Trading Symbol in Tables
symboltoken	string	Token of the contract for which modify is being sent
exchange	string	Exchange name : <code>NSE</code> <code>BSE</code>
transaction_type	string	The trading side of transaction : <code>BUY</code> <code>SELL</code>
orderid	string	Order Id Number
order_type	string	Order Type : <code>LIMIT</code> <code>MARKET</code> <code>STOP_LOSS</code> <code>STOP_LOSS_MARKET</code>
quantity	string	Number of shares for the order
producttype	string	Product Type <code>DELIVERY</code> <code>INTRADAY</code> <code>MARGIN</code> <code>CARRYFORWARD</code> <code>CNC</code> <code>INTRADAY</code> <code>MARGIN</code> <code>MTF</code> <code>CO</code> <code>BO</code>
duration	string	Regular Order Immediate or Cancel
price	string	Price at which order is placed
trigger_price	string	Price at which the order is triggered, in case of <code>STOP_LOSS</code> <code>STOP_LOSS_MARKET</code>
squareoff	string	Auto Sqaure off
disclosedquantity	string	Number of shares visible (Keep more than 30% of quantity)
modqty_remng	string	Remaining quantity

Request Response -

The response of the request will be based on authentication outcome.

- **Success (HTTP Status 200):** On successful order update, the server returns a JSON object containing the order ID and status.

```
{
  "status": "true",
  "message": "SUCCESS",
  "errorcode": "",
  "data": {
    "orderid": " 1191241106101",
    "uniqueorderid": ""
  }
}
```

- **Failure (HTTP Status 401):** If the order fails due to invalid parameters, authentication issues, or other errors, the server will return an error message with below json format.

```
{
  "status": "false",
  "message": "Enter valid trigger price.",
  "errorcode": "400",
  "data": null
}
```

- **Failure (HTTP Status 200):** If orderid does not exist then server will return below json response.

```
{
  "status": "false",
  "message": "Order is Cancelled.Kindly refresh your OrderBook",
  "errorcode": "RS-0034",
  "data": null
}
```

- **Failure (HTTP Status 400):** If the API Key is Invalid or expired.

```
{
  "status": "false",
  "message": "API is suspended/expired for use. Please check your API subscription and try again.",
  "errorcode": "IA403",
  "data": null
}
```

Order Cancellation

This endpoint allows users to delete an existing order specified by the order ID. Deleting an order will cancel the specified order.

Request Headers -

- **X-Mirae-Version :** Specifies the version of the API being used. In this case, it is set to 1.
- **Authorization :** A token-based authentication header. The format is token jwtToken.

- **Content-Type** : Indicated the media type of the resource. For this request, it is set to application/json, which is used for submitting form data through body
- **X-PrivateKey** : api_key

cURL

```
curl --location --request DELETE
'https://api.mstock.trade/openapi/typeb/orders/regular/1112241106105' \
  --header 'X-Mirae-Version: 1' \
  --header 'X-PrivateKey: api_key' \
  --header 'Authorization: Bearer jwtToken' \
  --header 'Content-Type: application/json' \
  --data '{
    "variety": "NORMAL",
    "orderid": "1181250130106"
  }'
```

Node.js

```
import axios from 'axios';

const response = await
axios.delete('https://api.mstock.trade/openapi/typeb/orders/regular/1112241106105', {
  headers: {
    'X-Mirae-Version': '1',
    'X-PrivateKey': 'api_key',
    'Authorization': 'Bearer jwtToken',
    'Content-Type': 'application/json'
  },
  // data: '{\n    "variety": "NORMAL",\n    "orderid": "1181250130106"\n  }',
  data: {
    'variety': 'NORMAL',
    'orderid': '1181250130106'
  }
});
```

Python

```
import http.client
import json

conn = http.client.HTTPConnection('api.mstock.trade')
headers = {
    'X-Mirae-Version': '1',
    'X-PrivateKey': 'api_key',
    'Authorization': 'Bearer jwtToken',
    'Content-Type': 'application/json',
}
json_data = {
    'variety': 'NORMAL',
    'orderid': '1181250130106',
}
conn.request(
    'DELETE',
    'openapi/typeb/orders/regular/1112241106105',
    json.dumps(json_data),
    # '{\n    "variety": "NORMAL",\n    "orderid": "1181250130106"\n  }',
```

```

        headers
    )
    response = conn.getResponse()

```

Java

```

import java.io.IOException;
import java.net.URI;
import java.net.http.HttpClient;
import java.net.http.HttpRequest;
import java.net.http.HttpRequest.BodyPublishers;
import java.net.http.HttpResponse;

HttpClient client = HttpClient.newBuilder()
    .followRedirects(HttpClient.Redirect.NORMAL)
    .build();

HttpRequest request = HttpRequest.newBuilder()

    .uri(URI.create("https://api.mstock.trade/openapi/typeb/orders/regular/1112241106105"))
    .method("DELETE", BodyPublishers.ofString("{\n    \"variety\": \"NORMAL\", \n
    \"orderid\": \"1181250130106\" \n    }"))
    .setHeader("X-Mirae-Version", "1")
    .setHeader("X-PrivateKey", "api_key")
    .setHeader("Authorization", "Bearer jwtToken")
    .setHeader("Content-Type", "application/json")
    .build();

HttpResponse<String> response = client.send(request,
    HttpResponse.BodyHandlers.ofString());

```

Path Parameter -

Field	Description
order_id	The unique identifier of the order to be updated or modified

Response Structure -

The response of the request will be based on authentication outcome.

- **Success (HTTP Status 200):** On successful order deletion, the server returns a JSON object containing the order ID and status.

```

{
  "status": "true",
  "message": "SUCCESS",
  "errorcode": "",
  "data": {
    "orderid": "201020000000080",
    "uniqueorderid": ""
  }
}

```

- **Failure (HTTP Status 200):** If orderid does not exist then server will return below json response.

```
{
  "status": "false",
  "message": "Order is Cancelled.Kindly refresh your OrderBook",
  "errorcode": "RS-00093",
  "data": null
}
```

- **Failure (HTTP Status 400):** Invalid product error

```
{
  "status": "false",
  "message": "Invalid product. valid product types allowed are DELIVERY, INTRADAY and CARRYFORWARD.",
  "errorcode": "400",
  "data": null
}
```

Cancel All

This endpoint allows users to cancel all the orders at once.

Request Headers -

- **X-Mirae-Version:** Specifies the version of the API being used. In this case, it is set to 1.
- **Authorization:** A token-based authentication header. The format is token jwtToken.
- **X-PrivateKey:** api_key

cURL

```
curl --location --request POST
'https://api.mstock.trade/openapi/typeb/orders/cancelall' \
--header 'X-Mirae-Version: 1' \
--header 'Authorization: Bearer jwtToken' \
--header 'X-PrivateKey: api_key' \
```

Node.js

```
import axios from 'axios';

const response = await axios.post(
  'https://api.mstock.trade/openapi/typeb/orders/cancelall',
  '',
  {
    headers: {
      'X-Mirae-Version': '1',
      'Authorization': 'Bearer jwtToken',
      'X-PrivateKey': 'api_key'
    }
  }
);
```

Python

```
import http.client

conn = http.client.HTTPConnection('api.mstock.trade')
headers = {
    'X-Mirae-Version': '1',
    'Authorization': 'Bearer jwtToken',
    'X-PrivateKey': 'api_key',
}
conn.request('POST', 'openapi/typeb/orders/cancelall', headers=headers)
response = conn.getresponse()
```

Java

```
import java.io.IOException;
import java.net.URI;
import java.net.http.HttpClient;
import java.net.http.HttpRequest;
import java.net.http.HttpResponse;

HttpClient client = HttpClient.newBuilder()
    .followRedirects(HttpClient.Redirect.NORMAL)
    .build();

HttpRequest request = HttpRequest.newBuilder()
    .uri(URI.create("https://api.mstock.trade/openapi/typeb/orders/cancelall"))
    .POST(HttpRequest.BodyPublishers.noBody())
    .setHeader("X-Mirae-Version", "1")
    .setHeader("Authorization", "Bearer jwtToken")
    .setHeader("X-PrivateKey", "api_key")
    .build();

HttpResponse<String> response = client.send(request,
    HttpResponse.BodyHandlers.ofString());
```

Response Structure -

The response of the request will be based on authentication outcome.

- **Success (HTTP Status 200):** On successful order deletion, the server returns a JSON object containing the order ID and status.

```
{
  "status": "success",
  "data": {
    "order_id": "1161241001100"
  }
}
```

- **Failure (HTTP Status 200):** If orderid does not exist then server will return below json response.

```
{
  "status": "error",
  "message": "Order Does not Exist.Need to refresh orderbook / relogin in application ",
  "error_type": "InputException",
  "data": null
}
```

- **Failure (HTTP Status 400):** If the API Key is Invalid or expired.

```
{
  "status": "false",
  "message": "API is suspended/expired for use. Please check your API subscription and try again.",
  "errorcode": "IA403",
  "data": null
}
```

Order Book

This endpoint allows users to retrieve a list of their trading orders. Users can view all their existing orders.

Request Headers -

- **X-Mirae-Version** : Specifies the version of the API being used. In this case, it is set to 1.
- **Authorization** : A token-based authentication header. The format is token jwtToken.
- **X-PrivateKey** : api_key

cURL

```
curl --location 'https://api.mstock.trade/openapi/typeb/orders' \
  --header 'X-Mirae-Version: 1' \
  --header 'X-PrivateKey: api_key' \
  --header 'Authorization: Bearer jwtToken' \
```

Node.js

```
import axios from 'axios';

const response = await axios.get('https://api.mstock.trade/openapi/typeb/orders', {
  headers: {
    'X-Mirae-Version': '1',
    'X-PrivateKey': 'api_key',
    'Authorization': 'Bearer jwtToken'
  }
});
```

Python

```
import http.client

conn = http.client.HTTPConnection('api.mstock.trade')
headers = {
    'X-Mirae-Version': '1',
    'X-PrivateKey': 'api_key',
    'Authorization': 'Bearer jwtToken',
}
conn.request('GET', 'openapi/typeb/orders', headers=headers)
response = conn.getresponse()
```

Java

```
import java.io.IOException;
import java.net.URI;
import java.net.http.HttpClient;
import java.net.http.HttpRequest;
import java.net.http.HttpResponse;

HttpClient client = HttpClient.newBuilder()
    .followRedirects(HttpClient.Redirect.NORMAL)
    .build();

HttpRequest request = HttpRequest.newBuilder()
    .uri(URI.create("https://api.mstock.trade/openapi/typeb/orders"))
    .GET()
    .setHeader("X-Mirae-Version", "1")
    .setHeader("X-PrivateKey", "api_key")
    .setHeader("Authorization", "Bearer jwtToken")
    .build();

HttpResponse<String> response = client.send(request,
    HttpResponse.BodyHandlers.ofString());
```

Request Body - This endpoint does not require a request body or additional parameters in the query string for the retrieval of orders.

Response Structure -

The response of the request will be based on authentication outcome.

- **Success (HTTP Status 200):** On successful order deletion, the server returns a JSON object containing the order ID and status.

```
{
  "status": "true",
  "message": "SUCCESS",
  "errorcode": "",
  "data": [
    {
      "variety": null,
      "ordertype": "SL",
      "producttype": "MARGIN",
      "duration": "DAY",
      "price": "2400.00",
      "triggerprice": "2390",
      "quantity": "900",
      "disclosedquantity": "0",
      "squareoff": "0",
      "stoploss": "0",
      "trailingstoploss": "0",
      "tradingsymbol": "ACC-28Nov2024-2400-CE",
      "transactiontype": "BUY",
      "exchange": "NSE",
      "symboltoken": "75307",
      "instrumenttype": "OPTSTK",
      "strikeprice": "2400",
      "optiontype": "CE",
      "expirydate": "2024-Nov-28",
      "lotsize": "",
      "cancelsize": "0",
      "averageprice": "0",
```

```

        "filledshares": "0",
        "unfilledshares": "0",
        "orderid": "1142241106106",
        "text": "EXCH:16284:The order price is out of the days price range.",
        "status": "Rejected",
        "orderstatus": "Rejected",
        "updatetime": "2024-Nov-06 12:42:18",
        "exchtime": "",
        "exchorderupdatetime": "2024-Nov-06 12:42:18",
        "fillid": "",
        "filltime": "",
        "parentorderid": "",
        "uniqueorderid": "",
        "exchangeorderid": "100000000017285"
    },
    {
        "variety": null,
        "ordertype": "SL",
        "producttype": "MARGIN",
        "duration": "DAY",
        "price": "2400.00",
        "triggerprice": "2390",
        "quantity": "900",
        "disclosedquantity": "0",
        "squareoff": "0",
        "stoploss": "0",
        "trailingstoploss": "0",
        "tradingsymbol": "ACC-28Nov2024-FUT",
        "transactiontype": "BUY",
        "exchange": "NSE",
        "symboltoken": "35593",
        "instrumenttype": "FUTSTK",
        "strikeprice": "-0.01",
        "optiontype": "XX",
        "expirydate": "2024-Nov-28",
        "lotsize": "",
        "cancelsize": "0",
        "averageprice": "0",
        "filledshares": "0",
        "unfilledshares": "0",
        "orderid": "1132241106107",
        "text": "CONFIRMED",
        "status": "Pending",
        "orderstatus": "Pending",
        "updatetime": "2024-Nov-06 12:41:00",
        "exchtime": "",
        "exchorderupdatetime": "2024-Nov-06 12:41:00",
        "fillid": "",
        "filltime": "",
        "parentorderid": "",
        "uniqueorderid": "",
        "exchangeorderid": "100000000017276"
    }
]
}

```

- **Failure (HTTP Status 400):** If authentication fails, the server will return an error message

```

{
    "status": "false",

```



```

    "message": "Invalid request. Please try again.",
    "errorcode": "IA401",
    "data": null
  }

```

- **Failure (HTTP Status 400):** If the API Key is Invalid or expired.

```

{
  "status": "false",
  "message": "API is suspended/expired for use. Please check your API subscription and try again.",
  "errorcode": "IA403",
  "data": null
}

```

Trade Book

This endpoint returns the trade book with all executed trades.

Request Headers -

- **X-Mirae-Version:** Specifies the version of the API being used. In this case, it is set to 1.
- **Authorization:** A token-based authentication header. The format is token jwtToken.
- **X-PrivateKey:** api_key

cURL

```

curl --location 'https://api.mstock.trade/openapi/typeb/tradebook' \
--header 'X-Mirae-Version: 1' \
--header 'Authorization: Bearer jwtToken' \
--header 'X-PrivateKey: api_key'

```

Node.js

```

import axios from 'axios';

const response = await axios.get('https://api.mstock.trade/openapi/typeb/tradebook',
{
  headers: {
    'X-Mirae-Version': '1',
    'Authorization': 'Bearer jwtToken',
    'X-PrivateKey': 'api_key'
  }
});

```

Python

```

import http.client

conn = http.client.HTTPConnection('api.mstock.trade')
headers = {
    'X-Mirae-Version': '1',
    'Authorization': 'Bearer jwtToken',
    'X-PrivateKey': 'api_key',

```

```

}
conn.request('GET', 'openapi/typeb/tradebook', headers=headers)
response = conn.getResponse()

```

Java

```

import java.io.IOException;
import java.net.URI;
import java.net.http.HttpClient;
import java.net.http.HttpRequest;
import java.net.http.HttpResponse;

HttpClient client = HttpClient.newBuilder()
    .followRedirects(HttpClient.Redirect.NORMAL)
    .build();

HttpRequest request = HttpRequest.newBuilder()
    .uri(URI.create("https://api.mstock.trade/openapi/typeb/tradebook"))
    .GET()
    .setHeader("X-Mirae-Version", "1")
    .setHeader("Authorization", "Bearer jwtToken")
    .setHeader("X-PrivateKey", "api_key")
    .build();

HttpResponse<String> response = client.send(request,
    HttpResponse.BodyHandlers.ofString());

```

Request Body - This endpoint does not require a request body or additional parameters in the query string.

Response Structure -

The response of the request will be based on authentication outcome.

- **Success (HTTP Status 200):** On successful request, the server returns a JSON object containing the trade book data.

```

{
  "status": "true",
  "message": "SUCCESS",
  "errorcode": "",
  "data": [
    {
      "ALGO_ID": "0",
      "BUY_SELL": "Sell",
      "CLIENT_ID": "MA68XXXX",
      "ENCASH_FLG": "N",
      "EXCHANGE": "NSE",
      "EXCH_ORDER_NUMBER": "110000048872942",
      "EXPIRY_DATE": "0",
      "FULL_SYMBOL": "VODAFONE IDEA LIMITED",
      "GTC_FLG": "N",
      "INSTRUMENT_NAME": "EQUITY",
      "MKT_PROTECT_FLG": "N",
      "MKT_PROTECT_VAL": 0,
      "MKT_TYPE": "NL",
      "OPT_TYPE": "XX",
      "ORDER_DATE_TIME": "10-06-2025 13:08:42",
      "ORDER_NUMBER": "21612506101476",
      "ORDER_TYPE": "MARKET",

```

```

    "PAN_NO": "BYPCXXXX",
    "PARTICIPANT_TYPE": "B",
    "PRICE": 6.98,
    "PRODUCT": "CNC",
    "QUANTITY": 4,
    "R": 1,
    "REMARKS1": "NA",
    "REMARKS2": "NA",
    "SEC_ID": "14366",
    "SEGMENT": "E",
    "SETTLOR": "90144",
    "SOURCE_FLG": "WEB",
    "STRIKE_PRICE": 0,
    "SYMBOL": "IDEA",
    "TRADE_NUMBER": "206465040",
    "TRADE_VALUE": 27.92
  },
  {
    "ALGO_ID": "0",
    "BUY_SELL": "Buy",
    "CLIENT_ID": "MA68XXXX",
    "ENCASH_FLG": "N",
    "EXCHANGE": "NSE",
    "EXCH_ORDER_NUMBER": "1100000045177810",
    "EXPIRY_DATE": "0",
    "FULL_SYMBOL": "VODAFONE IDEA LIMITED",
    "GTC_FLG": "N",
    "INSTRUMENT_NAME": "EQUITY",
    "MKT_PROTECT_FLG": "N",
    "MKT_PROTECT_VAL": 0,
    "MKT_TYPE": "NL",
    "OPT_TYPE": "XX",
    "ORDER_DATE_TIME": "10-06-2025 12:43:56",
    "ORDER_NUMBER": "21612506101398",
    "ORDER_TYPE": "MARKET",
    "PAN_NO": "BYPCXXXX",
    "PARTICIPANT_TYPE": "B",
    "PRICE": 6.99,
    "PRODUCT": "CNC",
    "QUANTITY": 1,
    "R": 2,
    "REMARKS1": "NA",
    "REMARKS2": "NA",
    "SEC_ID": "14366",
    "SEGMENT": "E",
    "SETTLOR": "90144",
    "SOURCE_FLG": "WEB",
    "STRIKE_PRICE": 0,
    "SYMBOL": "IDEA",
    "TRADE_NUMBER": "205988815",
    "TRADE_VALUE": 6.99
  }
]
0488",
"filltime": "12:39:05"
}
]
}

```

- **Failure (HTTP Status 400):** If the API Key is Invalid or expired.

```
{
  "status": "false",
  "message": "API is suspended/expired for use. Please check your API subscription and try again.",
  "errorcode": "IA403",
  "data": null
}
```

Trade History

While an orders is sent as single entry but, it may get executed in arbitrary chunks at the exchange level. This endpoint returns a list of all trades generated upon the execution of orders for that day.

Request Headers -

- **X-Mirae-Version:** Specifies the version of the API being used. In this case, it is set to 1.
- **Authorization:** A token-based authentication header. The format is token jwtToken.
- **X-PrivateKey:** api_key

cURL

```
curl --location --request GET 'https://api.mstock.trade/openapi/typeb/trades' \
--header 'X-Mirae-Version: 1' \
--header 'Authorization: Bearer jwtToken' \
--header 'X-PrivateKey: api_key' \
--header 'Content-Type: application/json' \
--data '{
  "fromdate": "2024-01-06",
  "todate" : "2025-01-07"
}'
```

Node.js

```
import axios from 'axios';

const response = await axios.get('https://api.mstock.trade/openapi/typeb/trades', {
  headers: {
    'X-Mirae-Version': '1',
    'Authorization': 'Bearer jwtToken',
    'X-PrivateKey': 'api_key',
    'Content-Type': 'application/json'
  },
  // data: '{\n  "fromdate": "2024-01-06",\n  "todate" : "2025-01-07"\n}',
  data: {
    'fromdate': '2024-01-06',
    'todate': '2025-01-07'
  }
});
```

Python

```
import http.client
import json
```

```
conn = http.client.HTTPConnection('api.mstock.trade')
headers = {
    'X-Mirae-Version': '1',
    'Authorization': 'Bearer jwtToken',
    'X-PrivateKey': 'api_key',
    'Content-Type': 'application/json',
}
json_data = {
    'fromdate': '2024-01-06',
    'todate': '2025-01-07',
}
conn.request(
    'GET',
    'openapi/typeb/trades',
    json.dumps(json_data),
    # '{\n    "fromdate": "2024-01-06",\n    "todate" : "2025-01-07"\n}',
    headers
)
response = conn.getresponse()
```

Java

```
import java.io.IOException;
import java.net.URI;
import java.net.http.HttpClient;
import java.net.http.HttpRequest;
import java.net.http.HttpRequest.BodyPublishers;
import java.net.http.HttpResponse;

HttpClient client = HttpClient.newBuilder()
    .followRedirects(HttpClient.Redirect.NORMAL)
    .build();

HttpRequest request = HttpRequest.newBuilder()
    .uri(URI.create("https://api.mstock.trade/openapi/typeb/trades"))
    .method("GET", BodyPublishers.ofString("{\n    \"fromdate\": \"2024-01-06\", \n\n\n    \"todate\" : \"2025-01-07\"\n}"))
    .setHeader("X-Mirae-Version", "1")
    .setHeader("Authorization", "Bearer jwtToken")
    .setHeader("X-PrivateKey", "api_key")
    .setHeader("Content-Type", "application/json")
    .build();

HttpResponse<String> response = client.send(request,
    HttpResponse.BodyHandlers.ofString());
```

Request Body - The body of the request must be URL-encoded and include the following parameters:

Field	Type	Description
fromdate	string	2024-01-06
todate	string	2025-01-07

Request Response -

The response of the request will be based on authentication outcome.

- **Success (HTTP Status 200):** On successful order update, the server returns a JSON object containing the order ID and status.

```
{
  "status": "true",
  "message": "SUCCESS",
  "errorcode": "",
  "data": [
    {
      "exchange": "NSE",
      "producttype": "DELIVERY",
      "tradingsymbol": "RASHTRIYA CHEMICALS & FER",
      "instrumenttype": "",
      "symbolgroup": "",
      "strikeprice": "",
      "optiontype": "",
      "expirydate": "",
      "marketlot": "",
      "precision": "",
      "multiplier": "",
      "tradevalue": "",
      "transactiontype": "SELL",
      "fillprice": "145.45",
      "fillsize": "1",
      "orderid": "1300000040250500",
      "fillid": "68346395",
      "filltime": "14:48:23"
    },
    {
      "exchange": "NSE",
      "producttype": "DELIVERY",
      "tradingsymbol": "RASHTRIYA CHEMICALS & FER",
      "instrumenttype": "",
      "symbolgroup": "",
      "strikeprice": "",
      "optiontype": "",
      "expirydate": "",
      "marketlot": "",
      "precision": "",
      "multiplier": "",
      "tradevalue": "",
      "transactiontype": "BUY",
      "fillprice": "145.60",
      "fillsize": "1",
      "orderid": "1300000040194885",
      "fillid": "68334426",
      "filltime": "14:47:53"
    }
  ]
}
```

- **Failure (HTTP Status 400):** If the API Key is Invalid or expired.

```
{
  "status": "false",
  "message": "API is suspended/expired for use. Please check your API subscription and try again.",
}
```

```
"errorcode": "IA403",  
"data": null  
}
```

Individual Order Details

This endpoint allows users to retrieve the status of individual order using the order id.

Request Headers -

- **X-Mirae-Version:** Specifies the version of the API being used. In this case, it is set to 1.
- **Authorization:** A token-based authentication header. The format is token jwtToken.
- **X-PrivateKey:** api_key

cURL

```
curl --location --request GET 'https://api.mstock.trade/openapi/typeb/order/details'  
\br/>--header 'X-Mirae-Version: 1' \  
--header 'Authorization: Bearer jwtToken' \  
--header 'X-PrivateKey: api_key' \  
--header 'Content-Type: application/json' \  
--data '{  
  "order_no": "1181250130105",  
  "segment": "E"  
}'
```

Node.js

```
import axios from 'axios';  
  
const response = await  
axios.get('https://api.mstock.trade/openapi/typeb/order/details', {  
  headers: {  
    'X-Mirae-Version': '1',  
    'Authorization': 'Bearer jwtToken',  
    'X-PrivateKey': 'api_key',  
    'Content-Type': 'application/json'  
  },  
  // data: '{\n    "order_no": "1181250130105",\n    "segment": "E"\n}',  
  data: {  
    'order_no': '1181250130105',  
    'segment': 'E'  
  }  
});
```

Python

```
import http.client  
import json  
  
conn = http.client.HTTPConnection('api.mstock.trade')  
headers = {  
  'X-Mirae-Version': '1',  
}
```

```

        'Authorization': 'Bearer jwtToken',
        'X-PrivateKey': 'api_key',
        'Content-Type': 'application/json',
    }
    json_data = {
        'order_no': '1181250130105',
        'segment': 'E',
    }
    conn.request(
        'GET',
        'openapi/typeb/order/details',
        json.dumps(json_data),
        # '{\n    "order_no": "1181250130105",\n    "segment": "E"\n}',
        headers
    )
    response = conn.getresponse()

```

Java

```

import java.io.IOException;
import java.net.URI;
import java.net.http.HttpClient;
import java.net.http.HttpRequest;
import java.net.http.HttpRequest.BodyPublishers;
import java.net.http.HttpResponse;

HttpClient client = HttpClient.newBuilder()
    .followRedirects(HttpClient.Redirect.NORMAL)
    .build();

HttpRequest request = HttpRequest.newBuilder()
    .uri(URI.create("https://api.mstock.trade/openapi/typeb/order/details"))
    .method("GET", BodyPublishers.ofString("{\n    \"order_no\": \"1181250130105\", \n    \"segment\": \"E\"\n}"))
    .setHeader("X-Mirae-Version", "1")
    .setHeader("Authorization", "Bearer jwtToken")
    .setHeader("X-PrivateKey", "api_key")
    .setHeader("Content-Type", "application/json")
    .build();

HttpResponse<String> response = client.send(request,
    HttpResponse.BodyHandlers.ofString());

```

Request Body - This endpoint does not require a request body or additional parameters in the query string for the retrieval of orders.

Field	Type	Description
order_id	string	The unique identifier of the order for which details need to be retrieved.
segment	string	E (Equity) / D (Derivative) -- Optional

Response Structure -

The response of the request will be based on authentication outcome.

- **Success (HTTP Status 200):** On successful order deletion, the server returns a JSON object containing the order ID and status.

```
{
  "status": "true",
  "message": "SUCCESS",
  "errorcode": "",
  "data": [
    {
      "variety": null,
      "ordertype": "MARKET",
      "producttype": "DELIVERY",
      "duration": "DAY",
      "price": 0,
      "triggerprice": 0,
      "quantity": "20",
      "disclosedquantity": "0",
      "squareoff": 0,
      "stoploss": 0,
      "trailingstoploss": 0,
      "tradingsymbol": "ACC",
      "transactiontype": "SELL",
      "exchange": "NSE",
      "symboltoken": "22",
      "instrumenttype": "EQUITY",
      "strikeprice": 0,
      "optiontype": "",
      "expirydate": "2025-Jan-23",
      "lotsize": "",
      "cancelsize": "0",
      "averageprice": "0",
      "filledshares": "20",
      "unfilledshares": "0",
      "orderid": "100000000016254",
      "text": "CONFIRMED",
      "status": "Pending",
      "orderstatus": "Pending",
      "updatetime": "23-01-2025 03:14:25 PM",
      "exchtime": "",
      "exchorderupdatetime": "",
      "fillid": "",
      "filltime": "",
      "parentorderid": "",
      "ordertag": "",
      "uniqueorderid": ""
    }
  ]
}
```

- **Failure (HTTP Status 200):** If authentication fails, the server will return an error message

```
{
  "status": "error",
  "message": "Please provide valid api version.",
  "error_type": "VersionException",
  "data": null
}
```

- **Failure (HTTP Status 400):** If the API Key is Invalid or expired.

```
{
  "status": "false",
  "message": "API is suspended/expired for use. Please check your API subscription
and try again.",
  "errorcode": "IA403",
  "data": null
}
```