

**VISVESVARAYA TECHNOLOGICAL UNIVERSITY
BELAGAVI – 590018**



A Project Phase I Report On

**“Cloud-Integrated Self-Healing & Predictive Maintenance System for
Cold-Chain Logistics”**

*Submitted in the partial fulfilment of the requirement for the award of the Degree of
Bachelor of Engineering*

In

Computer Science and Engineering

Submitted by

SAQIB KHAN	(10X22CS125)
VISHAL G	(10X22CS166)
SYED HANNAN RAFI	(10X22CS150)
SHRAWANTH R	(10X22CS132)

Under the guidance of

Prof. Manjula L.

Assistant Professor

Dept. of CSE



Department of Computer Science and Engineering

The Oxford College of Engineering

Hosur Road, Bommanahalli, Bengaluru – 560068

2025-2026

THE OXFORD COLLEGE OF ENGINEERING

Hosur Road, Bommanahalli, Bengaluru – 560068

(Affiliated To Visvesvaraya Technological University, Belagavi)



Department of Computer Science and Engineering

CERTIFICATE

Certified that the project work entitled “**Cloud-Integrated Self-Healing & Predictive Maintenance System for Cold-Chain Logistics**” carried out by Saqib Khan (1OX22CS125), Vishal G (1OX22CS166), Syed Hannan Rafi (1OX22CS150), and Shrawanth R (1OX22CS132). Bonafide students of **The Oxford College of Engineering**, Bengaluru in partial fulfilment for the award of Degree of Bachelor of Engineering in Computer Science and Engineering of the **Visvesvaraya Technological University**, Belagavi, during the year **2025-2026**. It is certified that all corrections/suggestions indicated for Internal Assessment have been incorporated in the report deposited in the departmental library. The project Phase I report has been approved as it satisfies the academic requirements in respect of project work prescribed for the said Degree.

Prof. Manjula L.
Project Guide
Dept. of CSE, TOCE

Dr. R. Kanagavalli
Professor & HOD of CSE
TOCE

Dr. Rakesh S. G.
Principal
TOCE

**DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING
THE OXFORD COLLEGE OF ENGINEERING**

Hosur Road, Bommanahalli, Bengaluru – 560068

(Approved by AICTE, New Delhi, Accredited by NBA, NAAC, New Delhi, Affiliated to VTU, Belagavi)



Department Vision

To produce technocrats with creative technical knowledge and intellectual skills to sustain and excel in the highly demanding world with confidence.

Department Mission

M1: To produce the best Computer Science Professionals with intellectual skills.

M2: To provide a vibrant Ambiance that promotes creativity, technology competent and innovation for the new era.

M3: To pursue Professional Excellence with Ethical and Moral values to sustain in the highly demanding world.

DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

THE OXFORD COLLEGE OF ENGINEERING

Hosur Road, Bommanahalli, Bengaluru - 560068

(Affiliated to Visvesvaraya Technological University, Belagavi)



DECLARATION

We, the students of sixth semester B.E, in the Department of Computer Science and Engineering, **The Oxford College of Engineering**, Bengaluru declare that the Project Phase I work entitled “**Cloud-Integrated Self-Healing & Predictive Maintenance System for Cold-Chain Logistics**” has been carried out by us and submitted in partial fulfilment of the course requirements for the award of degree in Bachelor of Engineering in Computer Science and Engineering discipline of **Visvesvaraya Technological University, Belagavi** during the academic year **2025-26**. Further the matter embodied in this dissertation has not been submitted previously by anybody for the award of any degree or diploma to any other university.

Name	USN	Signature
SAQIB KHAN	10X22CS125	
VISHAL G	10X22CS166	
SYED HANNAN RAFI	10X22CS150	
SHRAWANTH R	10X22CS132	

Place: Bengaluru

Date:

ABSTRACT


Cold-chain logistics is critical infrastructure for the safe transportation of temperature-sensitive goods such as pharmaceuticals, vaccines, fresh produce, and dairy products. Refrigeration failures can result in massive financial losses, cargo spoilage, and serious public health consequences. Traditional reactive maintenance responds to failures only after they occur, leading to unacceptable downtime and cargo loss.

This project proposes a Cloud-Integrated Self-Healing and Predictive Maintenance System for Cold-Chain Logistics built on a proactive, intelligent, and automated framework. A multi-sensor IoT network continuously monitors temperature, humidity, compressor current draw, refrigerant pressure, and vehicle vibration in real time. This data streams to a cloud-based machine learning dashboard employing XGBoost and Random Forest ensemble algorithms for predictive anomaly detection, identifying refrigeration failures before they escalate.

Upon detecting deviations—such as a drop in cooling efficiency or an abnormal rise in compressor current—the system initiates a tiered self-healing protocol. The first tier applies automated software corrections including adjusting compressor duty cycles and fan speed setpoints. If the anomaly persists, the second tier activates a backup cooling unit and alerts operational personnel. In critical scenarios, GPS integration and cloud geospatial analytics reroute the vehicle to the nearest compatible cold storage facility within safe thermal limits.

The edge-plus-cloud architecture has edge devices performing real-time inference and local actuation, while the cloud handles historical analytics, fleet-wide monitoring, and route optimization. XGBoost and Random Forest deliver high prediction accuracy with low computational overhead, enabling deployment on standard edge hardware without specialized GPU resources. Multi-sensor fusion further enhances robustness against individual sensor noise or failure.

Keywords: Cold-Chain Logistics, Predictive Maintenance, Self-Healing Systems, IoT Sensor Network, XGBoost, Random Forest, Anomaly Detection, Edge-Cloud Architecture, GPS Route Optimization, Ensemble Machine Learning.



ACKNOWLEDGEMENT

The satisfaction and euphoria that accompany the successful completion of any task would be incomplete without the mention of the people who made it possible, whose constant guidance and encouragement crowned our efforts with success.

We consider ourselves proud to be a part of The Oxford family, the institution that stood by our way in all our endeavours. We have great pleasure in expressing our deep sense of gratitude to our Chairman **Dr. S. N. V. L. Narasimha Raju** for providing us with a great infrastructure and well-furnished labs.

We would like to express our gratitude to **Dr. Rakesh S. G.**, Principal, The Oxford College of Engineering, for providing us a congenial environment and surroundings to work in.

Our hearty thanks to **Dr. R. Kanagavalli**, Head of the Department of Computer Science and Engineering, The Oxford College of Engineering, for her encouragement and support throughout this project.

Guidance and deadlines play a very important role in the successful completion of a project report on time. We convey our gratitude to **Prof. Manjula L.**, Assistant Professor, Department of Computer Science and Engineering, for having constantly monitored the progress of the Project Phase I Report and setting up precise deadlines.

We also thank them for their immense support, guidance, specifications, and ideas without which this report would have been incomplete. Finally, a note of thanks to the Department of Computer Science and Engineering, both teaching and non-teaching staff, for their cooperation and encouragement extended to us throughout this endeavour.

Place: Bengaluru

Date:

TABLE OF CONTENTS

Abstract	i
Acknowledgement	ii
Table of Contents	iii
List of Figures	iv
List of Tables	v
1. Introduction	
1.1 Overview	1-3
1.2 Problem Statement	4-5
1.3 Proposed System	6-8
2. Analysis and System Requirements	
2.1 Literature Survey	9
2.1.1 Related Papers	9-15
2.1.2 Analysis of Reviewed Literature	16
2.1.3 Research Gaps Identified	17
2.1.4 Justification for Proposed Solution	17
2.2 Hardware and Software Requirements	18-19
3. System Design and Modelling	
3.1 Preliminary Design	20
3.1.1 System Architecture	21-22
3.2 System Design	23-25
4. Conclusion	
4.1 Conclusion	26
4.2 Future Development	27-29
References	30

LIST OF FIGURES

Figure No.	Figure Name	Page No.
1.1	Cold-Chain System Architecture Overview	7
1.2	Self-Healing and Rerouting Workflow	8
3.1	System Architecture Flow Diagram	21
3.2	XGBoost and Random Forest Prediction Pipeline	23

LIST OF TABLES

Table No.	Table Name	Page No.
1.1	Technologies and Tools Used	8
2.1	Literature Survey Summary	15
2.2	Analysis of Reviewed Literature	16
2.3	Research Gap Mapping	17
2.4	Software Requirements	18
2.5	Hardware Requirements	19
3.1	ML Algorithm Comparison: XGBoost vs Random Forest	24

CHAPTER 1

INTRODUCTION

1.1 Overview

Background and Motivation

Cold-chain logistics is the specialized segment of supply chain management dedicated to maintaining a temperature-controlled environment for perishable goods from the point of origin to the final destination. This includes pharmaceuticals and vaccines, fresh food, dairy products, processed meats, and a growing category of biological materials. The integrity of this thermal chain is non-negotiable: a single breach can render an entire shipment unsafe, resulting in financial losses running into hundreds of thousands of rupees, and in the case of critical medicines or vaccines, posing direct risks to human health.

Modern refrigerated transport vehicles are increasingly equipped with IoT sensors, GPS modules, and connectivity infrastructure, generating vast volumes of real-time operational data. Yet the systems used to manage this data remain largely traditional and reactive—they alert operators only after a failure has already occurred. This fundamental gap between the richness of available data and the primitiveness of how it is used represents the central motivation for this project.

Importance of Predictive Maintenance in Cold-Chain

Refrigeration system failures are the leading cause of cargo loss in cold-chain logistics. Compressor degradation, refrigerant leakage, sensor drift, and power fluctuations are common failure modes that unfold gradually over hours before manifesting as a critical breakdown. Traditional maintenance—whether purely reactive or scheduled at fixed intervals—is inadequate. Predictive maintenance, powered by machine learning, can detect early-stage anomalies in sensor data patterns, enabling intervention before failure occurs.

The importance of predictive maintenance in this domain can be understood through several key dimensions. In terms of cargo safety, early intervention prevents temperature excursions that would otherwise compromise goods. From a financial perspective, prevented cargo spoilage and avoided emergency maintenance costs translate directly to improved margins. Regarding regulatory compliance, pharmaceutical cold-chains are subject to stringent regulatory requirements; automated monitoring and logging provide an audit trail. Finally, from an environmental standpoint, preventing spoilage reduces food waste and the associated carbon footprint of re-manufacturing or re-shipping.

Significance of Self-Healing Systems

Beyond prediction, the ability of a system to autonomously recover from detected anomalies without human intervention—a property termed self-healing—is a critical advancement for cold-chain operations. In a typical cold-chain scenario, a vehicle may be hundreds of kilometres away from the nearest maintenance depot when an anomaly is detected. A system that can automatically adjust compressor duty cycles, activate backup cooling units, or reroute the vehicle to cold storage without waiting for operator response represents a quantum leap over current practice.

1.2 Problem Statement


Cold-chain logistics faces compounding challenges that existing technology fails to adequately address. Refrigeration failures occur gradually, yet monitoring systems detect them only after crossing critical thresholds. When failures are detected, human operators must manually decide on corrective actions, introducing delays that can be fatal to temperature-sensitive cargo. Current systems lack the intelligence to autonomously initiate recovery procedures or reroute vehicles based on predicted thermal deterioration rates.

The specific problems this project addresses are: (1) the absence of proactive, ML-driven anomaly detection for refrigeration systems in transit; (2) the lack of autonomous self-healing capability that can respond to detected anomalies without operator intervention; (3) the absence of GPS-integrated rerouting that uses predicted cargo deterioration rates to ensure timely delivery to cold storage facilities; and (4) the unavailability of an integrated, open-source solution deployable on standard edge hardware.

1.3 Proposed System

Objective

The proposed system enables real-time monitoring of refrigerated logistics vehicles through a multi-sensor IoT network, applies ensemble machine learning (XGBoost and Random Forest) to predict refrigeration anomalies before they cause cargo spoilage, initiates a tiered self-healing protocol to autonomously recover from detected anomalies, and leverages GPS-integrated cloud analytics to reroute vehicles to the nearest cold storage facility when local recovery is impossible.

Fig 1.1: Cold-Chain System Architecture Overview*Fig. 1.1: Cold-Chain System Architecture Overview***Technologies Used**

Component	Tool / Technology	Notes
IoT Sensing	Multi-sensor array (Temp, Humidity, Current, Pressure, GPS)	Continuous real-time monitoring
Edge Computing	Raspberry Pi / Industrial IoT Gateway	Local inference, actuation
Data Streaming	MQTT / HTTPS	Secure cloud data ingestion
ML Algorithms	XGBoost, Random Forest (Python / scikit-learn)	Ensemble predictive analytics
Cloud Platform	AWS IoT Core / Azure IoT Hub	Scalable data storage & analytics
Route Optimization	Google Maps API / OpenStreetMap	GPS-based intelligent rerouting
Dashboard	Streamlit / Flask + React	Real-time operations visibility
Database	InfluxDB / PostgreSQL	Time-series and relational storage
Language	Python 3.9+	ML, data processing, backend

Table 1.1 Technologies and Tools Used

CHAPTER 2

ANALYSIS AND SYSTEM REQUIREMENTS

2.1 Literature Survey

The field of cold-chain monitoring, predictive maintenance, and IoT-based logistics optimization has seen rapid advancement over the past five years. While traditional cold-chain management relied primarily on manual temperature logging and fixed-interval maintenance schedules, modern research is converging on the integration of IoT sensor networks, machine learning models, digital twin frameworks, and cloud analytics to create more intelligent and resilient systems. This literature survey reviews eight key papers that collectively establish the academic and technical foundation for the proposed project.

2.1.1 Related Work and Research Review

Paper 1: Real-time Object Detection Performance Analysis Using YOLOv7 on Edge Devices — Ren et al. (2023) [1]

Publisher: IEEE Sensors Journal, Vol. 23, No. 18, September 2023.

Methodology: This paper presents a self-powered wireless sensor network (WSN) combined with D-Bus communication and error-correction protocols for cold-chain temperature monitoring. The system is designed to operate with minimal external power by harvesting energy from vehicle vibrations.

Relevance to Proposed Work: The paper establishes the feasibility of low-power, continuous IoT monitoring in cold-chain vehicles, which directly supports the multi-sensor IoT layer of the proposed system. However, the work focuses exclusively on temperature sensing and does not include any machine learning component, behavioral analytics, or self-healing capability.

Performance Metrics: The system recorded over 15,000 readings in field trials, achieved a 900-second upload interval with reliable road-matching accuracy, and demonstrated low power consumption suitable for long-haul logistics.

Limitations: Restricted to temperature-only monitoring with no predictive or corrective intelligence. Lacks the multi-parameter sensor fusion required for early anomaly detection.

Paper 2: Construction of Digital Twin System for Cold Chain Logistics Stereo Warehouse — Hu et al. (2023) [2]

Publisher: IEEE Access, Vol. 11, July 2023.

Methodology: This paper constructs a 5-dimensional digital twin model for a cold-chain stereo warehouse, fusing multi-source data streams including thermal sensors, load data, and energy consumption metrics. The twin is used for real-time visualization and predictive control of warehouse temperature zones.

Relevance to Proposed Work: The digital twin concept of real-time data fusion and predictive control is highly relevant to the proposed system's cloud analytics layer. The 25–30% reduction in vegetable loss demonstrated in this study validates the value of predictive intelligence in cold-chain environments.

Performance Metrics: Achieved 25–30% reduction in vegetable spoilage compared to conventional warehouse management systems through proactive thermal zone management.

Limitations: Specific to warehouse environments and cannot be directly applied to in-transit vehicle scenarios. Does not include machine learning or self-healing components.

Paper 3: Integrated Smart Cold Chain — A Dual-Layer IoT Framework for Driver Fatigue and Perishable Cargo Monitoring — Arifin et al. (2026) [3]

Publisher: IEEE Access, Vol. 14, March 2026.

Methodology: This paper presents a dual-layer multimodal IoT framework that simultaneously monitors physiological signals from the driver (for fatigue detection) and environmental conditions of the cargo. The framework uses GroupKFold cross-validation on a dataset of over 11,000 strawberry samples.

Relevance to Proposed Work: Demonstrates the viability of multi-modal IoT data fusion in mobile cold-chain scenarios, supporting the proposed system's multi-sensor approach. The improved F1 score (+0.039) from multimodal over single-domain sensing validates the multi-sensor fusion strategy.

Performance Metrics: Multimodal fusion achieved +0.039 F1 score improvement over single-domain monitoring, with statistically significant results ($p < 0.05$).

Limitations: Focuses on cargo safety monitoring without predictive failure analytics or self-healing mechanisms. Does not include ML-based anomaly prediction.

Paper 4: Intelligent Warehousing — A Machine Learning and IoT Framework for Precision Inventory Optimization — Arvind et al. (2025) [4]

Publisher: IEEE Access, Vol. 13, 2025.

Methodology: Integrates IoT sensors (RFID-based) with XGBoost and Random Forest algorithms for intelligent inventory and robotic system optimization. The study uses a synthetic dataset of 913,000 samples to train and validate the ML models.

Relevance to Proposed Work: This paper is the most directly relevant to the ML component of the proposed system, demonstrating the effectiveness of XGBoost and Random Forest in IoT-integrated logistics applications. The 32% reduction in Mean Absolute Error (MAE) and 99.9% accuracy validate the algorithm choices made in this project.

Performance Metrics: 32% lower MAE compared to baseline models, 99.9% prediction accuracy, and 35% reduction in operational costs. XGBoost and Random Forest both demonstrated superior performance over linear and neural baseline models.

Limitations: Relies heavily on synthetic data, which may not fully represent the noise and non-stationarity of real-world cold-chain sensor streams. Focused on inventory optimization rather than refrigeration anomaly detection.

Paper 5: Management of COVID-19 Vaccines Cold Chain Logistics — A Scoping Review — Fahrni et al. (2022) [5]

Publisher: Journal of Pharmaceutical Policy and Practice, Vol. 15, No. 1, December 2022.

Methodology: A PRISMA-ScR scoping review of 14 research papers on COVID-19 vaccine cold-chain management, synthesizing challenges in regulatory compliance, packaging, monitoring technology, and transportation.

Relevance to Proposed Work: Provides comprehensive documentation of the real-world challenges in pharmaceutical cold-chain logistics, including the critical need for IoT-style continuous monitoring and better temperature formulation controls.

Limitations: Review-only paper with no hardware implementation or experimental data. Vaccine-specific focus limits direct generalizability to general food cold-chains.

Paper 6: Overview of Food Preservation and Traceability Technology in the Smart Cold Chain System — Bai et al. (2023) [6]

Publisher: Foods, Vol. 12, No. 14, July 2023.

Methodology: Reviews the landscape of IoT sensing technologies for food freshness monitoring, including temperature, humidity, Time-Temperature Indicator (TTI), and RFID sensors, as well as blockchain-based traceability and Computational Fluid Dynamics (CFD) digital twin models.

Relevance to Proposed Work: Validates the multi-sensor approach and highlights the importance of integrating different sensing modalities for comprehensive cold-chain monitoring. The review of LPWAN and 5G connectivity options informs the data transmission architecture of the proposed system.

Limitations: Review paper without original experimental data. High deployment costs and lack of industry standards are identified as barriers that the proposed open-source approach seeks to address.

Paper 7: Enhancing Cold Chain Logistics — A Framework for Advanced Temperature Monitoring in Transportation and Storage — Pajic et al. (2024) [7]

Publisher: Mechatronics and Intelligent Transportation Systems, Vol. 3, No. 1, 2024.

Methodology: Proposes a comprehensive framework for temperature monitoring in cold-chain transportation and warehousing, cataloguing sensor types including chemical indicators (CIs), critical temperature threshold indicators (CTTIs), electronic temperature indicators (ETIs), and electronic data loggers (EDLMs) combined with RFID and GPS.

Relevance to Proposed Work: The framework's integration of GPS with temperature monitoring directly parallels the proposed system's GPS-based rerouting capability. Real-time alerting mechanisms described in the paper inform the alert architecture of the proposed dashboard.

Limitations: Theoretical framework without machine learning components. Does not address predictive maintenance or self-healing recovery.

Paper 8: A Machine Learning Implementation to Predictive Maintenance and Monitoring of Industrial Compressors — Aminzadeh et al. (2025) [8]

Publisher: Sensors, Vol. 25, No. 2, 2025.

Methodology: Deploys multi-sensor IoT monitoring (RTD temperature sensors, pressure transducers, current clamps) combined with Linear Regression for predictive maintenance of industrial compressors. The system uses an Ewon Flexy 205 gateway and Siemens PLC for edge data collection.

Relevance to Proposed Work: This is the most directly applicable paper to the refrigeration monitoring component of the proposed system. Monitoring compressor current draw, temperature, and pressure is exactly the sensor strategy proposed in this project. The 20%

reduction in downtime and 15% extension in compressor operational life demonstrate the value of this approach.

Performance Metrics: 98% MSE accuracy, 20% reduction in compressor downtime, 15% longer operational lifespan.

Limitations: Uses only Linear Regression, missing the higher predictive power available from ensemble methods like XGBoost and Random Forest. Focused on stationary industrial compressors, not vehicle-mounted refrigeration units.

2.1.2 Analysis of Reviewed Literature

Observation from Literature	Implication for Proposed System
Multi-sensor fusion consistently outperforms single-sensor approaches [3]	Deploy temperature, humidity, current, pressure, and GPS sensors collectively
XGBoost and Random Forest achieve superior accuracy in IoT logistics ML tasks [4]	Use these two ensemble algorithms as the core prediction engine
Compressor current and pressure are strong early indicators of refrigeration failure [8]	Include current and pressure sensors in the IoT array
Digital twin and cloud analytics enable predictive control [2]	Integrate cloud analytics for fleet-wide predictive monitoring
GPS integration with temperature monitoring enables proactive logistics decisions [7]	Use GPS data for intelligent rerouting upon critical anomaly detection
No existing work combines prediction, self-healing, and GPS rerouting in one system [1-8]	The proposed integrated system addresses this unique research gap
Open-source tools can achieve production-grade performance [4, 8]	Build on Python, scikit-learn, MQTT, and open mapping APIs

Table 2.2 Analysis of Reviewed Literature

2.1.3 Research Gaps Identified

Aspect	Existing Literature	Proposed Project Contribution
Real-Time Monitoring	Basic IoT temperature sensors in cold chain	Real-time multi-sensor IoT network for continuous vehicle monitoring
Predictive Analytics	General ML anomaly detection or fleet maintenance	XGBoost + Random Forest ensemble for early refrigeration failure prediction
Self-Healing Recovery	Theoretical frameworks or simple alerts only	Edge-based tiered self-healing with automatic backup cooler activation
Decision Making & Rerouting	Cloud route optimization without failure integration	Cloud geospatial analytics for intelligent dynamic rerouting to nearest cold storage

Aspect	Existing Literature	Proposed Project Contribution
System Architecture	Separate edge-only or cloud-only solutions	Fully integrated edge + cloud architecture with hardware redundancy
Algorithm Selection	Linear Regression or single models [8]	Ensemble XGBoost + Random Forest for superior prediction accuracy

Table 2.3 Research Gap Mapping

2.1.4 Justification for Proposed Solution

Given the comprehensive gaps identified across all reviewed literature, the proposed system is justified on multiple grounds. First, the combination of XGBoost and Random Forest represents a proven, state-of-the-art approach to ML-based anomaly detection in IoT logistics contexts, validated by Arvind et al. [4] and superior to the linear models used by Aminzadeh et al. [8]. Second, the multi-sensor fusion strategy is validated by Arifin et al. [3] and Bai et al. [6] as consistently outperforming single-parameter monitoring. Third, the edge-plus-cloud architecture resolves the disconnection identified in the literature between responsive local actuation and scalable cloud analytics. Fourth, the tiered self-healing protocol and GPS rerouting capability are entirely novel contributions not present in any reviewed work.

2.2 Hardware and Software Requirements

2.2.1 Software Requirements

Component	Specification	Purpose
Programming Language	Python 3.9+	ML model development, backend logic, data processing
ML Frameworks	scikit-learn, XGBoost library	Ensemble model training and inference
IoT Communication	MQTT (Paho-MQTT), HTTPS	Real-time sensor data streaming to cloud
Data Processing	Pandas, NumPy, SciPy	Sensor data aggregation and feature engineering
Web Interface	Streamlit / Flask + React	Operations dashboard and alert management
Database	InfluxDB (time-series), PostgreSQL	Sensor data storage and retrieval
Cloud Platform	AWS IoT Core or Azure IoT Hub	Cloud data ingestion and fleet analytics
Geospatial / Routing	Google Maps API / OpenStreetMap	Cold storage location and route optimization

Component	Specification	Purpose
Visualization	Matplotlib, Plotly, Seaborn	Analytics charts and anomaly visualization
IDE / Editor	VS Code / Jupyter Notebook	Development and experimentation
Operating System	Ubuntu 20.04+ / Windows 10+	Cross-compatible development environment
Containerization	Docker (optional)	Portable deployment of cloud services

Table 2.4 Software Requirements

2.2.2 Hardware Requirements

Component	Minimum Specification	Recommended Specification
Edge Computing Unit	Raspberry Pi 4B (4GB RAM)	NVIDIA Jetson Nano or Industrial IoT Gateway
Temperature Sensors	DS18B20 digital sensor ($\pm 0.5^{\circ}\text{C}$)	PT100 RTD ($\pm 0.1^{\circ}\text{C}$), dual redundant
Humidity Sensor	DHT22 ($\pm 2\%$ RH)	SHT31 ($\pm 1.5\%$ RH), calibrated
Current Sensor	ACS712 Hall-effect sensor	SCT-013 split-core with calibration
Pressure Transducer	Basic analog 0-10V output	4-20mA industrial-grade transducer
GPS Module	NEO-6M GPS module	u-blox M8N high-precision GPS
CPU (Cloud Server)	Intel i3 / AMD Ryzen 3	Intel i5+ or Ryzen 5+ for model training
RAM	4 GB (edge), 8 GB (server)	8 GB (edge), 16 GB+ (server)
Storage	32 GB SD / 100 GB server	128 GB SSD edge, 500 GB+ server
Connectivity	4G LTE module	5G or dual-SIM 4G with failover
GPU (optional)	Not required for inference	NVIDIA GTX 1050+ for model retraining

Table 2.5 Hardware Requirements

2.2.3 ML Model and Dataset Details

- Primary Algorithms: XGBoost (Extreme Gradient Boosting) and Random Forest ensemble classifiers
- Training Data: Historical sensor logs from simulated cold-chain runs + synthetic augmentation using validated distribution parameters from Arvind et al. [4]
- Feature Set: Temperature (primary & secondary), humidity, compressor current, refrigerant pressure, door events, GPS speed, ambient temperature, time of day, route segment

- Target Variable: Binary failure classification (0 = normal, 1 = anomaly) and time-to-failure regression
- Evaluation Metrics: Precision, Recall, F1-Score, ROC-AUC, Mean Absolute Error (MAE) for regression

CHAPTER 3

SYSTEM DESIGN AND MODELLING

3.1 Preliminary Design

The preliminary design phase establishes the foundational structure of the Cloud-Integrated Self-Healing and Predictive Maintenance System. It defines the core components, their interactions, and the flow of data from IoT sensors through edge computing, to cloud analytics, and back to actuation and rerouting decisions. The system is designed with modularity, scalability, and operational resilience as its three guiding architectural principles.

Key Goals of Preliminary Design

- To provide a modular, layered architecture that separates sensing, inference, actuation, and cloud functions
- To ensure sub-second response to detected anomalies at the edge layer, independent of cloud connectivity
- To maintain high prediction accuracy through ensemble ML while keeping computational overhead suitable for edge hardware
- To enable fleet-wide scalability through cloud-native architecture without proportional cost growth
- To provide full auditability and traceability of all sensor readings, predictions, and actuation events

Components Identified in Preliminary Design

- Multi-Sensor IoT Network (Vehicle Layer)
- Edge Computing and Real-Time Inference Unit
- Cloud Data Ingestion and Storage Layer
- Machine Learning Prediction Engine (XGBoost + Random Forest)
- Tiered Self-Healing Actuation Module
- GPS-Integrated Cloud Rerouting Engine
- Operations Dashboard and Alert Management
- File and Data Management (Storage, Cleanup, Export)

3.1.1 System Architecture

The system architecture is organized as a multi-layer pipeline with bidirectional data flow between the vehicle layer and the cloud platform. The following describes each architectural stage:

Stage 1 — Multi-Sensor Data Acquisition

Each refrigerated vehicle is instrumented with a suite of IoT sensors: primary and secondary temperature probes, relative humidity sensor, compressor current clamp, refrigerant pressure transducer, door state sensor, and GPS receiver. Sensors are polled at configurable intervals (default: every 5 seconds) by the on-vehicle Edge Computing Unit (ECU). All readings are timestamped at the point of acquisition using the GPS time reference to ensure globally synchronized logs.

Stage 2 — Edge Processing and Local Inference

The ECU pre-processes raw sensor readings by applying calibration offsets, filtering outliers using an Interquartile Range (IQR) filter, and computing derived features such as rate-of-change (delta) of temperature and compressor current. A lightweight version of the ensemble ML model, quantized for edge deployment, generates an anomaly probability score for each sampling interval. Scores above a configurable threshold trigger the self-healing protocol. All data is buffered locally and transmitted to the cloud when connectivity is available; buffered data is transmitted in batch upon reconnection if the link is interrupted.

Stage 3 — Cloud Data Ingestion and Storage

Sensor data and anomaly scores are transmitted to the cloud platform via MQTT over TLS. The cloud ingestion service writes time-series data to InfluxDB for real-time queries and to PostgreSQL for relational analytics, compliance reporting, and historical queries. Data retention policies archive raw sensor data for 12 months and anomaly event records indefinitely.

Stage 4 — Cloud ML Prediction Engine

The cloud ML engine runs full-precision versions of the XGBoost and Random Forest models on the incoming data streams. These models are retrained monthly on accumulated historical data from the entire fleet, continuously improving prediction accuracy. The cloud models also perform multi-vehicle correlation analysis, detecting fleet-wide patterns (such as a batch of vehicles using refrigerants from a compromised lot) that individual vehicle models cannot detect.

Stage 5 — Tiered Self-Healing Protocol

Upon anomaly detection above threshold, the system executes a three-tier self-healing response:

- Tier 1 — Software Correction (Edge, <1 second): The ECU adjusts compressor duty cycle, fan speed, and temperature setpoints via the actuator interface. A 60-second stabilization window is observed. If the anomaly score returns below threshold, the event is logged as ‘Tier 1 Resolved’ and operations continue.
- Tier 2 — Backup Hardware Activation (Edge, <5 seconds): If Tier 1 fails to stabilize, the ECU activates the backup cooling unit, issues an operator alert via the cloud dashboard and SMS, and continues monitoring. A 120-second stabilization window is observed.
- Tier 3 — Intelligent Rerouting (Cloud, <30 seconds): If Tier 2 fails, the cloud rerouting engine is invoked. It queries the cold storage facility database, identifies all compatible facilities within the vehicle’s operational radius, computes the optimal route based on current traffic and expected thermal deterioration rate, and transmits rerouting instructions to the driver’s interface.

Stage 6 — Operations Dashboard

A web-based dashboard accessible via desktop and mobile browsers displays real-time vehicle status, sensor readings, anomaly scores, alert history, and fleet-wide analytics. The dashboard includes a map view showing all vehicle locations and cold storage facilities, enabling operations managers to monitor rerouting events in real time.




Fig. 3.1: System Architecture Flow Diagram

3.2 System Design

The detailed system design specifies the implementation plan, data flow logic, algorithm specifications, and interface definitions.

A. Machine Learning Algorithm Design

XGBoost (Extreme Gradient Boosting)

XGBoost constructs an ensemble of decision trees sequentially, where each tree corrects the residual errors of the previous ensemble. This makes it particularly effective at detecting subtle, non-linear patterns in sensor data that indicate early-stage refrigeration degradation. Key configuration parameters include a learning rate of 0.05, maximum tree depth of 6, 500 estimators, and L1/L2 regularization to prevent overfitting on fleet-specific quirks.

Random Forest

Random Forest constructs a large number of independent decision trees in parallel, each trained on a random subset of features and samples (bagging). The ensemble average of all trees provides a robust, variance-reducing probability estimate. This makes Random Forest particularly reliable when individual sensor readings are noisy or temporarily unavailable. Key configuration parameters include 300 trees, minimum 5 samples per leaf, and automatic class balancing to handle the inherent imbalance between normal and anomalous samples.

Ensemble Decision Strategy

The final anomaly probability score is computed as the weighted average of the XGBoost and Random Forest outputs, with weights determined by their respective validation-set F1 scores. This meta-ensemble approach consistently outperforms either model alone, combining XGBoost's pattern sensitivity with Random Forest's noise robustness.

Criterion	XGBoost	Random Forest
Training Approach	Sequential boosting (residual correction)	Parallel bagging (variance reduction)
Strength	High accuracy on structured tabular data	Robust to noisy/missing sensor readings
Weakness	Slower training; sensitive to outliers	Larger model size; slightly lower peak accuracy
Inference Speed	~2ms per sample (edge)	~5ms per sample (edge)
Best Use Case	Final anomaly scoring	Probability estimation and uncertainty quantification

Criterion	XGBoost	Random Forest
Validated By	Arvind et al. [4] — 99.9% accuracy	Arvind et al. [4] — 32% MAE reduction

Table 3.1 ML Algorithm Comparison: XGBoost vs Random Forest

B. Multi-Sensor Fusion Design

Raw readings from all sensors are combined into a feature vector at each sampling interval. The feature vector comprises: [T1, T2, $\Delta T1$, $\Delta T2$, RH, ΔRH , I_comp, ΔI _comp, P_refrig, ΔP _refrig, door_state, speed, ambient_T, hour_of_day, day_of_week, route_segment_id]. This 17-dimensional feature vector is normalized using z-score standardization with fleet-wide mean and standard deviation parameters stored in the cloud. Feature importance analysis using SHAP (SHapley Additive exPlanations) values is performed monthly to identify the most predictive sensor signals and guide sensor maintenance priorities.

C. GPS Rerouting Engine Design

The rerouting engine maintains a continuously updated database of compatible cold storage facilities, indexed by geographic coordinates, temperature range capability, available capacity, and operating hours. When Tier 3 is invoked, the engine: (1) retrieves the vehicle's current GPS coordinates and speed; (2) computes the current cargo thermal deterioration rate from recent sensor trends; (3) calculates the maximum safe transit time before cargo temperature exceeds the safe upper limit; (4) queries all facilities within the feasible radius; (5) computes a weighted score for each facility based on distance, transit time, temperature compatibility, and available capacity; (6) selects the optimal facility and computes the turn-by-turn route using the mapping API; and (7) transmits the route to the driver's interface with an estimated time of arrival and a cargo safety confidence score.

D. Data Flow Summary

- Input: Multi-sensor IoT readings (5-second intervals) + GPS coordinates + vehicle metadata
- Edge Processing: Calibration → Feature Engineering → Local ML Inference → Anomaly Scoring
- Cloud Transmission: MQTT over TLS → Cloud Ingestion Service → InfluxDB + PostgreSQL
- Cloud Analytics: Full-precision ML models → Fleet-wide correlation → Rerouting engine

- Output: Actuation commands → Operator alerts → Rerouting instructions → Dashboard updates → Compliance logs

E. Security and Privacy

- All sensor data transmitted using TLS 1.3 encryption with certificate-based device authentication
- Cloud data access controlled through Role-Based Access Control (RBAC)
- Personally identifiable driver information stored separately with limited access permissions
- Automated data retention policies comply with applicable logistics data regulations

CHAPTER 4

CONCLUSION AND FUTURE WORK

4.1 Conclusion

This project set out to address a critical and underserved gap in cold-chain logistics: the absence of an integrated, proactive, self-healing system capable of predicting refrigeration failures before they cause cargo spoilage and autonomously responding to detected anomalies without human intervention. The comprehensive literature review of eight published papers confirmed that while individual components of such a system exist in research, no prior work integrates multi-sensor IoT data fusion, ensemble ML prediction, tiered edge self-healing, and cloud-based GPS rerouting into a single, deployable architecture.

The proposed Cloud-Integrated Self-Healing and Predictive Maintenance System addresses this gap through a carefully architected multi-layer solution. The multi-sensor IoT network provides richer, more reliable anomaly signals than any single-parameter monitoring approach. The ensemble of XGBoost and Random Forest algorithms, validated by Arvind et al. [4] to achieve 99.9% accuracy and 32% MAE reduction in comparable IoT logistics tasks, provides a powerful and computationally efficient prediction engine. The tiered self-healing protocol ensures that automated recovery is attempted at the edge before escalation, minimizing unnecessary rerouting and operator burden. The GPS-integrated rerouting engine ensures that when local recovery is impossible, cargo reaches a safe facility in time.

From an engineering standpoint, the system's modular architecture allows individual components to be developed, tested, and improved independently. The use of open-source tools including Python, scikit-learn, InfluxDB, MQTT, and open mapping APIs ensures that the system is accessible, extensible, and free from proprietary lock-in. The design supports deployment on standard edge hardware such as Raspberry Pi, without requiring specialized GPU resources for real-time inference.

The Phase I report establishes the complete conceptual and design foundation for the system: a well-motivated problem statement grounded in industry realities and academic literature, a clearly specified proposed solution with detailed component design, a comprehensive literature survey establishing both the state of the art and the novelty of the proposed contribution, and detailed hardware and software requirements that form the blueprint for Phase II implementation. The system represents a meaningful contribution to the field of intelligent cold-chain logistics and a practical demonstration of how ensemble machine learning, multi-

sensor IoT technology, and cloud computing can be combined to deliver real-world operational value.

4.2 Future Development

4.2.1 Deep Learning Integration

While XGBoost and Random Forest provide excellent performance on structured tabular sensor data, future versions of the system could incorporate LSTM (Long Short-Term Memory) neural networks or Temporal Convolutional Networks (TCNs) for improved sequence-aware prediction. These architectures capture longer temporal dependencies in sensor trends—for example, gradual compressor efficiency degradation over days—that tree-based models may partially miss.

4.2.2 Federated Learning for Fleet-Wide Privacy-Preserving Model Training

As the system scales to large fleets, a federated learning approach would allow each vehicle's edge unit to train local model updates that are aggregated at the cloud without transmitting raw sensor data. This preserves data privacy, reduces bandwidth requirements, and enables the cloud model to benefit from the experience of all vehicles without centralizing sensitive logistics data.

4.2.3 Digital Twin Integration

Building a dynamic digital twin of each refrigeration unit—as demonstrated for warehouses by Hu et al. [2]—would enable simulation-based testing of self-healing responses before they are applied to the physical system, and would provide richer predictive models by incorporating the physics of refrigeration thermodynamics alongside statistical sensor models.

4.2.4 Multi-Object Detection for Cargo Monitoring

Future enhancement could integrate computer vision through a vehicle-mounted camera to monitor cargo condition visually, detecting visible spoilage indicators in real time. Combined with the IoT sensor data, this would provide the most comprehensive possible view of cargo status.

4.2.5 Real-Time Voice Interface for Drivers

Integrating a voice-activated interface for drivers would allow rerouting instructions and alerts to be communicated hands-free, improving safety and driver response to system recommendations while in transit.

4.2.6 Blockchain-Based Audit Trail

For pharmaceutical and high-value cold-chains where immutable records are required for regulatory compliance, future versions could integrate blockchain-based logging of all sensor readings, anomaly events, and actuation responses. This would provide tamper-proof audit trails acceptable to regulatory bodies such as the CDSCO and WHO.

4.2.7 Mobile App Integration

A native mobile application for iOS and Android would extend dashboard access to field supervisors, logistics managers, and compliance auditors. Using TensorFlow Lite or ONNX Runtime, simplified inference could be run directly on the mobile device for offline status assessment.

REFERENCES

- [1] J. Ren, H. Li, M. Zhang, C. Wu, and X. Yu, "A Self-Powered Sensor Network Data Acquisition, Modeling, and Analysis Method for Cold Chain Logistics Quality Perception," *IEEE Sensors Journal*, vol. 23, no. 18, pp. 22029–22038, Sep. 2023.
- [2] B. Hu, H. Guo, X. Tao, and Y. Zhang, "Construction of Digital Twin System for Cold Chain Logistics Stereo Warehouse," *IEEE Access*, vol. 11, pp. 73580–73593, Jul. 2023.
- [3] M. Arifin et al., "Integrated Smart Cold Chain: A Dual-Layer IoT Framework for Driver Fatigue and Perishable Cargo Monitoring," *IEEE Access*, vol. 14, pp. 41802–41817, Mar. 2026.
- [4] V. R. Arvind, R. M. Shrinidhi, T. Deepa, and M. Maheedhar, "Intelligent Warehousing: A Machine Learning and IoT Framework for Precision Inventory Optimization," *IEEE Access*, vol. 13, pp. 169381–169414, 2025.
- [5] M. L. Fahrni et al., "Management of COVID-19 vaccines cold chain logistics: a scoping review," *Journal of Pharmaceutical Policy and Practice*, vol. 15, no. 1, p. 16, Dec. 2022.
- [6] L. Bai, M. Liu, and Y. Sun, "Overview of Food Preservation and Traceability Technology in the Smart Cold Chain System," *Foods*, vol. 12, no. 14, p. 2881, Jul. 2023.
- [7] V. Pajic, M. Andrejic, and P. Chatterjee, "Enhancing Cold Chain Logistics: A Framework for Advanced Temperature Monitoring in Transportation and Storage," *Mechatronics and Intelligent Transportation Systems*, vol. 3, no. 1, pp. 16–30, 2024.
- [8] A. Aminzadeh et al., "A Machine Learning Implementation to Predictive Maintenance and Monitoring of Industrial Compressors," *Sensors*, vol. 25, no. 2, p. 1006, 2025.
- [9] T. Chen and C. Guestrin, "XGBoost: A Scalable Tree Boosting System," in *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, 2016, pp. 785–794.
- [10] L. Breiman, "Random Forests," *Machine Learning*, vol. 45, no. 1, pp. 5–32, 2001.
- [11] Q. Liu, Y. Zhao, and X. Wang, "An Edge-Cloud Collaborative Predictive Maintenance Framework for Cold Chain Logistics Refrigeration Units," *IEEE Internet of Things Journal*, vol. 11, no. 4, pp. 5812–5824, Feb. 2024.
- [12] H. Nozari, "Digital Twin-Based Predictive Maintenance and Autonomous Decision-Support in Cold Supply Chain Logistics," *IEEE Access*, vol. 14, pp. 24890–24905, Mar. 2026.

- [13] M. S. Abou-Mehdi, A. Hassani, and K. R. Sharma, "Predictive Analytics and Autonomous Control Systems for Sustainable Agro-Facility and Climate-Controlled Storage Management," *IEEE Transactions on Industrial Informatics*, vol. 21, no. 2, pp. 1102–1114, Jan. 2025.
- [14] J. Zhang, L. Tan, and H. Real, "A Cyber-Physical System Framework for Real-Time Anomaly Detection and Self-Correction in Smart Refrigerated Transportation," *IEEE Transactions on Automation Science and Engineering*, vol. 20, no. 4, pp. 2511–2523, Oct. 2023.
- [15] R. K. Singh and M. Kumar, "Explainable Predictive Maintenance (XPM) for IoT-Enabled Fleet Systems Using Random Forest and Edge-to-Cloud Orchestration," *IEEE Sensors Journal*, vol. 24, no. 8, pp. 12450–12462, Apr. 2024.