

CS3001-1_Computer Network and Communication Unit 1 MCQ

- In a _____ communication, the media is dedicated.

a) point-to-point
b) multipoint
c) mesh
d) None of the choices are correct

___ Ans: a

- In a fully connected mesh topology with six computers, we need _____ links.

a) 6
b) 36
c) 15
d) 30
Ans: c

- Frequency and period are _____.

a) inverse of each other
b) proportional to each other
c) the same
d) are not related
Ans: a

- _____ is a type of transmission impairment in which the signal loses strength due to the different propagation speeds of each frequency that makes up the signal.

a) Attenuation
b) Distortion
c) Noise
d) Decibel
Ans: b

- _____ conversion involves three techniques: line coding, block coding, and scrambling.

a) Analog-to-digital
b) Digital-to-analog
c) Analog-to-analog
d) Digital-to-digital
Ans: d

- Which error detection method involves polynomials?

a) CRC
b) Simple parity check
c) Two-dimensional parity check
d) Checksum
Ans: a

- The _____ sublayer is responsible for the operation of the CSMA/CD access method and framing.

a) LLC
b) MII
c) MAC
d) IP
Ans: c

- Which of the following best describes a single-bit error?

- a) A single bit is inverted.
- b) A single bit per transmission is inverted.
- c) A single bit per data unit is inverted.
- d) All of the choices are correct

Ans: c

- A packet at the data-link layer is normally called a _____.

- a) datagram
- b) message
- c) packet
- d) frame

Ans: d

- In _____, the change or lack of change in the level of the voltage determines the value of the bit.

- a) NRZ-I
- b) NRZ-L
- c) NRZ-I or NRZ-L
- d) None of the choices are correct.

Ans: a

- What is the full form of OSI?
- a) optical service implementation
- b) open service Internet
- c) open system interconnection
- d) operating system interface

Answer: c

- When a collection of various computers appears as a single coherent system to its clients, what is this called?
- a) mail system
- b) networking system
- c) computer network
- d) distributed system

Answer: d

- Which one of the following is not a function of network layer?
- a) congestion control
- b) error control
- c) routing
- d) inter-networking

Answer: b

- Which topology requires a multipoint connection?
- a) Ring
- b) Bus
- c) Star
- d) Mesh

Answer: b

- Which layer is responsible for process to process delivery in a general network model?
- a) session layer
- b) data link layer
- c) transport layer
- d) network layer

Answer: c

- What is the term for the data communication system within a building or campus?
 - a) MAN
 - b) LAN
 - c) PAN
 - d) WAN

Answer: b

- Which layer provides the services to user?
 - a) physical layer
 - b) presentation layer
 - c) session layer
 - d) application layer

Answer: d

- Which connection is necessary for a computer to join the internet?
 - a) internet society
 - b) internet service provider
 - c) different computer
 - d) internet architecture board

Answer: b

- Which transmission media provides the highest transmission speed in a network?
 - a) coaxial cable
 - b) twisted pair cable
 - c) optical fiber
 - d) electrical cable

Answer: c

- A single channel is shared by multiple signals by _____
 - a) analog modulation
 - b) digital modulation
 - c) multiplexing
 - d) phase modulation

Answer: c

- Identify the layer which is responsible for data translating.
- Network Layer
- Data Link Layer
- Presentation Layer
- Application Layer

Ans: c Presentation Layer

- Identify the layer which provides service to the user.
- Session Layer
- Application Layer
- Network Layer
- Physical Layer

Ans : b Application Layer

- What is the length of the MAC address?
- 8 bits

- 16 bits
- 32 bits
- 48 bits

Ans: d 48 bits

- _____ is a type of transmission impairment in which the signal loses strength due to the resistance of the transmission medium.

- Attenuation
- Distortion
- Noise
- Decibel

Ans: a. Attenuation

- _____ is a type of transmission impairment in which the signal loses strength due to the different propagation speeds of each frequency that makes up the signal.

- Attenuation
- Distortion
- Noise
- Decibel

Ans: b. Distortion

- The _____ of a composite signal is the difference between the highest and the lowest frequencies contained in that signal

- frequency
- period
- bandwidth
- amplitude

Ans: c. bandwidth

- Baseband transmission of a digital signal is possible only if we have a _____ channel

- low-pass
- bandpass
- low rate
- high rate

Ans: a. low-pass

- The most common technique to change an analog signal to digital data is called _____.

- PAL
- PCM
- sampling
- none of the above

Ans: b PCM

- In _____ transmission, the channel capacity is shared by both communicating devices at all times.

- a. simplex
- b. half-duplex
- c. full-duplex
- d. half-simplex

Ans: c full-duplex

- **To deliver a message to the correct application program running on a host, the -----address must be consulted.**
- **port**
- **IP**
- **physical**
- **none of the above**

Ans: a. port