



## Neural Network Basics

Quiz, 10 questions

**Congratulations! You passed!**

Next Item

1 / 1  
point

1.

What does a neuron compute?

A neuron computes a linear function ( $z = Wx + b$ ) followed by an activation function**Correct**Correct, we generally say that the output of a neuron is  $a = g(Wx + b)$  where  $g$  is the activation function (sigmoid, tanh, ReLU, ...).

A neuron computes the mean of all features before applying the output to an activation function

A neuron computes a function  $g$  that scales the input  $x$  linearly ( $Wx + b$ )A neuron computes an activation function followed by a linear function ( $z = Wx + b$ )1 / 1  
point

2.

Which of these is the "Logistic Loss"?

 $\mathcal{L}^{(i)}(\hat{y}^{(i)}, y^{(i)}) = -(y^{(i)} \log(\hat{y}^{(i)}) + (1 - y^{(i)}) \log(1 - \hat{y}^{(i)}))$ **Correct**

Correct, this is the logistic loss you've seen in lecture!

 $\mathcal{L}^{(i)}(\hat{y}^{(i)}, y^{(i)}) = |y^{(i)} - \hat{y}^{(i)}|^2$  $\mathcal{L}^{(i)}(\hat{y}^{(i)}, y^{(i)}) = \max(0, y^{(i)} - \hat{y}^{(i)})$  $\mathcal{L}^{(i)}(\hat{y}^{(i)}, y^{(i)}) = |y^{(i)} - \hat{y}^{(i)}|$ 1 / 1  
point

3.



Suppose `img` is a `(32,32,3)` array, representing a 32x32 image with 3 color channels red, green and blue. How do you reshape

## Neural Network Basics

Quiz, 10 questions

- ☐ `x = img.reshape((32*32,3))`
- ☐ `x = img.reshape((3,32*32))`
- ☐ `x = img.reshape((1,32*32,*3))`
- ☒ `x = img.reshape((32*32*3,1))`

Correct



1 / 1  
point

4.  
Consider the two following random arrays "a" and "b":

```
1 a = np.random.randn(2, 3) # a.shape = (2, 3)
2 b = np.random.randn(2, 1) # b.shape = (2, 1)
3 c = a + b
```

What will be the shape of "c"?

- ☐ The computation cannot happen because the sizes don't match. It's going to be "Error"!
- ☐ `c.shape = (2, 1)`
- ☐ `c.shape = (3, 2)`
- ☒ `c.shape = (2, 3)`

Correct

Yes! This is broadcasting. `b` (column vector) is copied 3 times so that it can be summed to each column of `a`.



1 / 1  
point

5.

Consider the two following random arrays "a" and "b":



## Neural Network Basics

```
1 a = np.random.randn(4, 3) # a.shape = (4, 3)
2 b = np.random.randn(3, 2) # b.shape = (3, 2)
3 c = a*b
```

What will be the shape of "c"?

- ☐ c.shape = (4,2)
- ☐ c.shape = (3, 3)
- ☐ c.shape = (4, 3)
- ☒ The computation cannot happen because the sizes don't match. It's going to be "Error"!

### Correct

Indeed! In numpy the "\*" operator indicates element-wise multiplication. It is different from "np.dot()". If you would try "c = np.dot(a,b)" you would get c.shape = (4, 2).



1 / 1  
point

6.

Suppose you have  $n_x$  input features per example. Recall that  $X = [x^{(1)} x^{(2)} \dots x^{(m)}]$ . What is the dimension of X?

- ☐  $(1, m)$
- ☐  $(m, 1)$
- ☐  $(m, n_x)$
- ☒  $(n_x, m)$

### Correct



1 / 1  
point

7.

Recall that "np.dot(a,b)" performs a matrix multiplication on a and b, whereas "a\*b" performs an element-wise multiplication.



## Neural Network Basics

Consider the two following random arrays "a" and "b":

```
1 a = np.random.randn(12288, 150) # a.shape = (12288, 150)
2 b = np.random.randn(150, 45) # b.shape = (150, 45)
3 c = np.dot(a,b)
```

What is the shape of c?

- ☐ c.shape = (12288, 150)
- ☒ c.shape = (12288, 45)

**Correct**

Correct, remember that a np.dot(a, b) has shape (number of rows of a, number of columns of b). The sizes match because :

"number of columns of a = 150 = number of rows of b"

- ☐ The computation cannot happen because the sizes don't match. It's going to be "Error"!
- ☐ c.shape = (150,150)



0 / 1  
point

8.

Consider the following code snippet:

```
1 # a.shape = (3,4)
2 # b.shape = (4,1)
3
4 for i in range(3):
5     for j in range(4):
6         c[i][j] = a[i][j] + b[j]
```

How do you vectorize this?

- ☐ c = a + b.T
- ☒ c = a + b

**This should not be selected**

- ☐ c = a.T + b.T
- ☐ c = a.T + b



1 / 1  
point

## 9. Neural Network Basics

Consider the following code:

Quiz, 10 questions

```
1 a = np.random.randn(3, 3)
2 b = np.random.randn(3, 1)
3 c = a*b
```

What will be c? (If you're not sure, feel free to run this in python to find out).

☒ This will invoke broadcasting, so b is copied three times to become (3,3), and \* is an element-wise product so c.shape will be (3, 3)



Correct

☐ This will invoke broadcasting, so b is copied three times to become (3, 3), and \* invokes a matrix multiplication operation of two 3x3 matrices so c.shape will be (3, 3)


☐ This will multiply a 3x3 matrix a with a 3x1 vector, thus resulting in a 3x1 vector. That is, c.shape = (3,1).

☐ It will lead to an error since you cannot use "\*" to operate on these two matrices. You need to instead use np.dot(a,b)



1 / 1  
point

10.  
Consider the following computation graph.



What is the output J?

☐  $J = (c - 1) * (b + a)$

☒  $J = (a - 1) * (b + c)$



Correct

Yes.  $J = u + v - w = a*b + a*c - (b + c) = a * (b + c) - (b + c) = (a - 1) * (b + c)$ .



## Neural Network Basics

Quiz, 10 questions

☐

$J = a*b + b*c + a*c$

☐

$J = (b - 1) * (c + a)$

---

