

Report for: Wifi Capacity Test

Tue Jul 08 09:12:59 EDT 2025



Objective


The Candela WiFi Capacity test is designed to measure performance of an Access Point when handling different amounts of WiFi Stations. The test allows the user to increase the number of stations in user defined steps for each test iteration and measure the per station and the overall throughput for each trial. Along with throughput other measurements made are client connection times, Fairness, % packet loss, DHCP times and more. The expected behavior is for the AP to be able to handle several stations (within the limitations of the AP specs) and make sure all stations get a fair amount of airtime both in the upstream and downstream. An AP that scales well will not show a significant over-all throughput decrease as more stations are added.

Realtime Graph shows summary download and upload RX Goodput rate of connections created by this test. Goodput does not include Ethernet, IP, UDP/TCP header overhead.

[CSV Data for Realtime Throughput](#)

Realtime Throughput


Start Time: 2025-07-08 08:50:20
End Time: 2025-07-08 09:11:02



Total Megabits-per-second transferred. This only counts the protocol payload, so it will not count the Ethernet, IP, UDP, TCP or other header overhead. A well behaving system will show about the same rate as stations increase. If the rate decreases significantly as stations increase, then it is not scaling we

[CSV Data for Total Mbps Received vs Number of Stations Active](#)


Total Mbps Received vs Number of Stations Active



Protocol-Data-Units received. For TCP, this does not mean much, but for UDP connections, this correlates to packet size. If the PDU size is larger than what fits into a single frame, then the network stack will


segment it accordingly. A well behaving system will show about the same rate as stations increase. If the rate decreases significantly as stations increase, then it is not scaling well.

[CSV Data for Total PDU/s Received vs Number of Stations Active](#)




Histogram for WiFi MCS for packets sent and received by the wifi radios in the test.

[CSV Data for WiFi Packet MCS Percentages](#)




Block-Ack allows a series of frames to be sent in one transmit opportunity. This series of packets is known as a series of AMPDU frames. Having more frames in each AMPDU series normally improves throughput, but may increase latency or decrease airtime fairness. This histogram provides some visibility into the AMPDU chain length used in this test.

[CSV Data for WiFi Packet AMPDU Length Percentages](#)




Histogram for WiFi bandwidths for packets sent and received by the wifi radios in the test.

[CSV Data for WiFi Bandwidth Percentages](#)




Station disconnect stats. These will be only for the last iteration. If the 'Clear Reset Counters' option is selected, the stats are cleared after the initial association. Any re-connects reported indicate a potential stability issue. Can be used for long-term stability testing in cases where you bring up all stations in one iteration and then run the test for a longer duration. Note: Port Resets shown in the graph happened after the initial association.

[CSV Data for Port Reset Totals](#)



Station connect time is calculated from the initial Authenticate message through the completion of Open or RSN association/authentication.

[CSV Data for Station Connect Times](#)



Wifi-Capacity Test requested values

| | |
|--------------------|---------------|
| Station Increment: | 1 |
| Loop Iterations: | Single (1) |
| Duration: | 20 min (20 m) |

| | |
|-----------------------------|--|
| Estimated Run Duration: | 20.5 m |
| Layer 4-7 Endpoint: | NONE |
| IP Version | IPv4 |
| MSS | AUTO |
| Total Download Rate: | 100M (100 Mbps) |
| Total Upload Rate: | Zero (0 bps) |
| Protocol: | UDP |
| Payload Size: | AUTO |
| Socket buffer size: | OS Default |
| IP ToS: | Best Effort (0) |
| Multi-Conn: | AUTO |
| UDP-GRO | false |
| UDP-Burst | false |
| Use existing URL rate | false |
| Set Bursty Minimum Speed: | Burst Mode Disabled (-1) |
| Percentage TCP Rate: | 10% (10%) |
| Randomize Rates | true |
| Leave Ports Up | false |
| Advanced Latency Reporting | false |
| Settle Time: | 5 sec (5 s) |
| Rpt Timer: | fast (1 s) |
| Graph Max Samples: | Suggested (1,080) |
| Graph Compression Interval: | Suggested (5 min) (5 m) |
| Show-Per-Iteration-Charts | true |
| Show-Per-Loop-Totals | true |
| Hunt-Lower-Rates | false |
| Show Events | true |
| Clear Reset Counters | false |
| CSV Reporting Dir | - not selected - |
| Build Date | Wed Apr 2 12:45:22 PM PDT 2025 |
| Build Version | 5.4.9.1 |
| Git Version | ec15252a800cc9a93c3faea0ace84fa0c7082949 |
| Ports | 1.1.sta0002 1.1.eth1 |
| Firmware | 0. 6-5 |
| Machines | ct521b-da59 |

Requested Parameters:

| | | | | |
|----------------|--------------|-----------------------|-----------------------|-----------------------|
| Download Rate: | Per station: | 100000000 (100 Mbps) | All: | 100000000 (100 Mbps) |
| Upload Rate: | Per station: | 0 (0 bps) | All: | 0 (0 bps) |
| Total: | | | 100000000 (100 Mbps) | |
| Station count: | | | 1 | |

| | |
|--------------------------|-------------|
| Connections per station: | 1 |
| Payload (PDU) sizes: | AUTO (AUTO) |


Observed Rate:

This table shows stats for all connections this iteration based on their reporting interval average.

| | | | | | | | | |
|------------------|---------|-------------|---------|-------------|---------|-------------|---------|-------------|
| Download Rate: | Cx Min: | 99.973 Mbps | Cx Ave: | 99.973 Mbps | Cx Max: | 99.973 Mbps | All Cx: | 99.973 Mbps |
| Upload Rate: | Cx Min: | 0 bps | Cx Ave: | 0 bps | Cx Max: | 0 bps | All Cx: | 0 bps |
| Total: | | | | | | | | 99.973 Mbps |
| Aggregated Rate: | Min: | 99.973 Mbps | Avg: | 99.973 Mbps | Max: | 99.973 Mbps | | |

This graph shows fairness. On a fair system, each station should get about the same throughput. In the download direction, it is mostly the device-under-test that is responsible for this behavior, but in the upload direction, LANforge itself would be the source of most fairness issues unless the device-under-test takes specific actions to ensure fairness.

[CSV Data for Combined Mbps, 60 second running average](#)



Requested Parameters:

| | | | | |
|--------------------------|--------------|-----------------------|------|-----------------------|
| Download Rate: | Per station: | 100000000 (100 Mbps) | All: | 100000000 (100 Mbps) |
| Upload Rate: | Per station: | 0 (0 bps) | All: | 0 (0 bps) |
| Total: | | | | 100000000 (100 Mbps) |
| Station count: | | | | 1 |
| Connections per station: | | | | 1 |
| Payload (PDU) sizes: | | | | AUTO (AUTO) |

Observed Amount:

This table shows stats for all connections this iteration based on their reporting interval average.


| | | | | | | | | |
|------------------|---------|----------|---------|----------|---------|----------|---------|----------|
| Download Amount: | Cx Min: | 3.173 GB | Cx Ave: | 3.173 GB | Cx Max: | 3.173 GB | All Cx: | 3.173 GB |
| Upload Amount: | Cx Min: | 0 B | Cx Ave: | 0 B | Cx Max: | 0 B | All Cx: | 0 B |

Total:

3.173 GB


This graph shows fairness. On a fair system, each station should get about the same throughput. In the download direction, it is mostly the device-under-test that is responsible for this behavior, but in the upload direction, LANforge itself would be the source of most fairness issues unless the device-under-test takes specific actions to ensure fairness.

[CSV Data for Combined Received Megabytes, for entire 20 m run](#)



Maximum Stations Connected: 1
Stations NOT connected at this time: 0
Maximum Stations with IP Address: 1
Stations without IP at this time: 0


[CSV Data for Station Maximums](#)



RF stats give an indication of how well how congested is the RF environment. Channel activity is what the wifi radio reports as the busy-time for the RF environment. It is expected that this be near 100% when LANforge is running at max speed, but at lower speeds, this should be a lower percentage unless the RF environment is busy with other systems.

RF stats are collected at the end of the iteration.


[CSV Data for RF Stats for Stations](#)



Link rate stats give an indication of how well the rate-control is working. For rate-control, the 'RX' link rate corresponds to what the device-under-test is transmitting. If all of the stations are on the same radio, then the TX and RX encoding rates should be similar for all stations. If there is a definite pattern where some stations do not get good RX rate, then probably the device-under-test has rate-control problems. The TX rate is what LANforge is transmitting at.

Link Rate is recorded at the end of each iteration. Please see individual station statistics CSV files for link rate over time.

CSV Data for Link Rate for Stations



Key Performance Indicators CSV

Scan Results for SSIDs used in this test.

```
BSS 6c:cd:d6:27:fc:e6(on sta0002) -- associated
  last seen: 12433.822s [boottime]
  TSF: 2621455750 usec (0d, 00:43:41)
  freq: 2437.0
  beacon interval: 100 TUs
  capability: ESS Privacy SpectrumMgmt ShortSlotTime RadioMeasure (0x1511)
  signal: -46.00 dBm
  last seen: 11 ms ago
  Information elements from Probe Response frame:
  SSID: NETGEAR_2G
  Supported rates: 1.0* 2.0* 5.5* 11.0* 18.0 24.0 36.0 54.0
  DS Parameter set: channel 6
  Country: US      Environment: bogus
    Channels [1 - 11] @ 30 dBm
  Power constraint: 0 dB
  TPC report: TX power: 24 dBm
  ERP: Barker_Preamble_Mode
  Extended supported rates: 6.0 9.0 12.0 48.0
  RSN:
    * Version: 1
    * Group cipher: CCMP
    * Pairwise ciphers: CCMP
    * Authentication suites: PSK
    * Capabilities: 16-PTKSA-RC 1-GTKSA-RC MFP-capable (0x008c)
  BSS Load:
    * station count: 2
    * channel utilisation: 189/255
    * available admission capacity: 0 [*32us]
  RM enabled capabilities:
    Capabilities: 0x02 0x00 0x00 0x00 0x00
    Neighbor Report
    Nonoperating Channel Max Measurement Duration: 0
    Measurement Pilot Capability: 0
  AP Channel Report:
```

```

* operating class: 134
* channel(s): 69
Supported operating classes:
* current operating class: 83
* operating class: 12
* operating class: 32
* operating class: 33
* operating class: 81
* operating class: 83
* operating class: 84
HT capabilities:
Capabilities: 0x11ef
    RX LDPC
    HT20/HT40
    SM Power Save disabled
    RX HT20 SGI
    RX HT40 SGI
    TX STBC
    RX STBC 1-stream
    Max AMSDU length: 3839 bytes
    DSSS/CCK HT40
    Maximum RX AMPDU length 65535 bytes (exponent: 0x003)
    Minimum RX AMPDU time spacing: 4 usec (0x05)
    HT RX MCS rate indexes supported: 0-32
    HT TX MCS rate indexes are undefined
HT operation:
* primary channel: 6
* secondary channel offset: above
* STA channel width: any
* RIFS: 1
* HT protection: 20 MHz
* non-GF present: 1
* OBSS non-GF present: 1
* dual beacon: 0
* dual CTS protection: 0
* STBC beacon: 0
* L-SIG TXOP Prot: 0
* PCO active: 0
* PCO phase: 0
Extended capabilities:
* Extended Channel Switching
* Event
* BSS Transition
* Interworking
* QoS Map
* Operating Mode Notification
* Reserved Reserved Channel Schedule Management
* Reserved Channel Schedule Management
* TWT Responder Support
802.11u Interworking:
Network Options: 0x0
Network Type: 0 (Private)
802.11u Advertisement:
Query Response Info: 0x7f
Query Response Length Limit: 127
ANQP
HE capabilities:
HE MAC Capabilities (0x000512181000):
+HTC HE Supported
TWT Responder
BSR
Broadcast TWT
OM Control
Maximum A-MPDU Length Exponent: 2
OM Control UL MU Data Disable RX
HE PHY Capabilities: (0x222002c00d43811800cc00):
HE40/2.4GHz
242 tone RUs/2.4GHz
LDPC Coding in Payload
NDP with 4x HE-LTF and 3.2us GI
Rx HE MU PPDU from Non-AP STA
SU Beamformer
SU Beamformee
Beamformee STS <= 80Mhz: 3
Sounding Dimensions <= 80Mhz: 3
Ng = 16 SU Feedback
Codebook Size SU Feedback
PPE Threshold Present
Max NC: 3
TX 1024-QAM
RX 1024-QAM
HE RX MCS and NSS set <= 80 MHz
1 streams: MCS 0-11
2 streams: MCS 0-11
3 streams: MCS 0-11
4 streams: MCS 0-11
5 streams: not supported
6 streams: not supported
7 streams: not supported
8 streams: not supported
HE TX MCS and NSS set <= 80 MHz
1 streams: MCS 0-11
2 streams: MCS 0-11
3 streams: MCS 0-11
4 streams: MCS 0-11
5 streams: not supported
6 streams: not supported
7 streams: not supported
8 streams: not supported
PPE Threshold 0x1b 0x1c 0xc7 0x71 0x1c 0xc7 0x71
WPS:
* Version: 1.0
* Wi-Fi Protected Setup State: 2 (Configured)

```



```
* AP setup locked: 0x01
* Response Type: 3 (AP)
* UUID: c47c75fa-8316-68d8-2e95-d22b03063432
* Manufacturer: Broadcom
* Model: RAXE500
* Model Number: 123456
* Serial Number: 267
* Primary Device Type: 6-0050f204-1
* Device name: RAXE500
* Config methods: Display
* RF Bands: 0x3
* Version2: 2.0
WMM: * Parameter version 1
      * u-APSD
      * BE: CW 15-1023, AIFSN 3
      * BK: CW 15-1023, AIFSN 7
      * VI: CW 7-15, AIFSN 2, TXOP 3008 usec
      * VO: CW 3-7, AIFSN 2, TXOP 1504 usec
```

[META Information for Report for: Wifi Capacity Test](#)

Generated by Candela Technologies LANforge network testing tool.
www.candelatech.com

