


Inset Runway Touchdown Zone Light(LED)



High intensity Uni-directional inset light

VAS-IRTDZL-8-W-L-X

Compliance with standards

- ICAO Annex 14 - Volume 1
- FAA AC 150/5345-46
- FAA Engineering Brief 67D
- IEC 61827

Application

- Runway Touchdown Zone lights extend 900 m, from the runway threshold, or up to the midpoint for runways shorter than 1800 m.
- High-Intensity, Uni-directional, Runway touchdown zone light suitable for ICAO category II & III runways (use for low visibility landings).

Specifications

- | | |
|----------------------|-------------------------|
| • Power Supply | 2.8A~6.6A |
| • Rated Power | 17W |
| • Power Factor | >95% at nominal current |
| • Temperature | -40° C to +55° C |
| • Life Time of LED | 50,000 hrs |
| • Protection Class | IP 68 |
| • Protrusion Height | 6.3mm |
| • Color | White |
| • Direction | Uni-directional |
| • Light fitting Size | Ø8" |

Features

- The light fitting is designed in strict accordance with the technical requirements and specifications of ICAO, IEC and FAA for Runway and Taxiway as Navigational aid light for Airports.
- A surge protection device is provided in the electronics as required by FAA "Engineering Brief 67D.
- The long life, energy saving and maintenance-free characteristics of LEDs bring economic benefits.
- High-efficiency power factor correction circuit ensures effective reduction of interference to the power supply network.
- Efficient design of LED heat dissipation effectively reduces the working temperature of light fitting, LED and drivers to ensure long service life.
- Fully dimmable lights, simulates the dimming curve as per Standard's requirement.
- Electrolytic capacitors of high temperature and long life are used in circuitry to improve the stability of the LED driver.
- The optical prism adopts special tempered glass to prevent the prism from bursting due to drastic changes in temperature.
- Fail-open option is available to achieve compatibility with advance control and monitoring systems. The LED light automatically disconnects from the secondary side of the isolation transformer, resulting in an open circuit condition.



1st & 2nd Floor, Plot No. 13/C & 13/3, Rama Road Side, Industrial Area, Najafgarh Road , Delhi-110015, India



+91-9818295444

IT: +91-11-45710588



contact@vardhmanairports.com




www.vardhmanairports.com

CIN U62100DL2014PTC263759

Features

- The overall protection level of the light fitting reaches IP68, preventing dust and rain from eroding the interior of the light.
- Fully compatible with existing airfield lighting series circuits.
- Color emitted directly by LEDs in absence of colored filters ensures no energy losses and no color shifts.
- The main body of the light fitting is made of aluminium alloy which is strong and has good anti corrosion performance.
- The height of light fitting protruding from the ground is only 6.3mm. This helps in strongly reducing vibrations to aircrafts and to light itself, increasing its lifespan.
- The upper cover of the light fitting adopts high strength design and drop forging process, with good mechanical properties, strong bearing capacity and impact resistance
- Fasteners are made of stainless steel which are durable.
- The parts are modularly designed and universal, which are easy to replace.
- Style L-823 connectors are used.

Photometric Data



Runway Touchdown Zone Light ICAO Fig. A2-5	
Colour	White
Max./Min. Intensity Ratio	<3.0
Main Ellipse Average Intensity	5,000cd
Main Ellipse Minimum Intensity	2,500cd
Second Ellipse Minimum Intensity	500cd
Third Ellipse Minimum Intensity	250cd
Chromaticity	ICAO Annex. 14 Fig A1-1b

Ordering information

VAS-IRTDZL-8-W-L-X

X = O/M

O = Without Monitoring

M = With Monitoring

L = Led Light


W= White

8 = 8" Diameter


IRTDZL= Inset Runway Touchdown
Zone Light

VAS = VARDHMAN

Dimensions



Installation



ISO 9001:2015 Certified Company



1st & 2nd Floor, Plot No. 13/C & 13/3, Rama Road Side, Industrial Area, Najafgarh Road , Delhi-110015, India

+91-9818295444

IT: +91-11-45710588



contact@vardhmanairports.com

www.vardhmanairports.com

CIN U62100DL2014PTC263759