



Constant Current Regulator

VAS-CCR

Compliance with standards

- ICAO: Aerodrome Design Manual 9157 Part 5, para 3.2.
- FAA: AC 150/5345-10H
- IS : 12291 - 1987

Features

- Remote Control Operation.
- Nominal RMS output current (2.8A, 3.4A, 4.1A, 5.2A, 6.6A).
- Failure Indications for SCR Fail, Over Current, Open Circuit with alarm and failure indication for insulation resistance.
- Stable Output Current.

Product Range

S No.	Product Range	Order Code
1	2.5KW	VAS-CCR-2.5
2	4KW	VAS-CCR-04
3	7.5KW	VAS-CCR-7.5
4	10KW	VAS-CCR-10
5	15KW	VAS-CCR-15
6	20KW	VAS-CCR-20
7	30KW	VAS-CCR-30
8	50KW	VAS-CCR-50

Application

Designed specifically for the supply of airport lighting series circuits of varying intensities.

Environmental Properties

- Relative Humidity: $\leq 95\%$.
- Working Temperature between -40° to 55° degree.
- Altitude Range of 0 to 10000 feet above Mean Sea Level.
- Can withstand Salt laden atmosphere.

Performance

- Efficiency: $>90\%$
- Current Output: 5 Steps (2.8A, 3.4A, 4.1A, 5.2A, 6.6A) and 7 steps is optional as per requirement.
- Temperature Rise: $\leq 60^{\circ}\text{C}$.
- Power Factor: $>90\%$.
- Output Current Stability: $\pm 0.05\%$ of Nominal Current.

Electrical supply

- 220 - 240V for below 7.5KW CCRs, 50/60 Hz.
- 415V for above 10KW CCRs, 50/60 Hz.

Dimensions

- 1400mmx600mmx600mm

