

API: gettotalplayerlist

data category	member	update logic
PlayerBaseInfo	Location	Server collects data each 2 seconds, and send the new data to PCOB client if any new data updated (usually there will be updated in each 2 sec since player locations change frequently)
	Health	
	HealthMax	
	LiveState	
	KillNum	
PlayerRealTimeAPI	KillNumBeforeDie	Server collects data each 2 seconds, and send the new data to PCOB client if any new data updated (This set of data does not always change in each 2 seconds)
	GoAirDropNum	
	MaxKillDistance	
	Damage	
	KillNumInVehicle	
PlayerAfterMatchAPI	KillNumByGrenade	Server collects data each 2 seconds, only after whole game ends, this set of data will be sent to PCOB client, the value will keep 0 before game ends
	Rank	
	IsOutsideBlueCircle	
	InDamage	
	Heal	
	HeadShotNum	
	SurvivalTime	
	DriveDistance	
	MarchDistance	
	Assists	
	OutsideBlueCircleTime	
	Knockouts	
	RescueTimes	
	UseSmokeGrenadeNum	
	UseFragGrenadeNum	
	UseBurnGrenadeNum	
	UseFlashGrenadeNum	

Remark:

Server collects the 3 set of data in each 2 seconds, and send to PCOB client in different route

After PCOB client receives any update of category of data mentioned above, it will update the 'gettotalplayerlist' data and send to local http server via post request

PlayerBaseInfo' is sent via route A, 'PlayerRealTimeAPI' and 'PlayerAfterMatchAPI' is sent via route B.

The 2 routes dont affect each other, even the 3 sets of data are changed while server collecting, PCOB client may receive each set of data in different timing. And it will use multiple times of post request though PCOB client receives multiple sets of data

服务器上每隔2秒在同一帧会先后收集3个组别的数据, 并且通过不同的通道向PCOB客户端同步

PCOB客户端收到任意一个组别的数据后, 都会更新本地的 gettotalplayerlist的数据并且通过post请求发送到本地httpserver上

PlayerBaseInfo是通道A传输, PlayerRealTimeAPI和PlayerAfterMatchAPI都是通道B传输, 两个通道没有关系, 即使在服务器上某次收集数据这3个数据组别都变化了, PCOB客户端也有可能是不问帧收到不同的数据组别, 即使是同一帧收到多个不同的数据组别, 也会调用多次post请求

