

1-

PROBLEMA:

Write a function that accepts an array of 10 integers (between 0 and 9), that returns a string of those numbers in the form of a phone number.

Example

```
Kata.createPhoneNumber(new int[] {1, 2, 3, 4, 5, 6, 7, 8, 9, 0}) // =>
```

The returned format must be correct in order to complete this challenge.

Don't forget the space after the closing parentheses!



ARRAYS

STRINGS

REGULAR EXPRESSIONS

ALGORITHMS

SOLUCION:

Solution

```
1 public class Kata {  
2     public static String createPhoneNumber(int[] numbers) {  
3         return "(" + numbers[0] + numbers[1] + numbers[2] + ") "  
4             + numbers[3] + numbers[4] + numbers[5] + "-"  
5             + numbers[6] + numbers[7] + numbers[8] + numbers[9];  
6     }  
7 }  
8  
9
```

✓ Outstanding! You may take your time to refactor/comment your solution. Submit when ready.

PANTALLASO

Create Phone Number

399177485% of 29,49542,316 of 380,343xDranik

InstructionsOutput

Time: 2046ms Passed: 2 Failed: 0

Test Results:

- PhoneTests
 - basicTests
 - randomTests

Completed in 39ms

You have passed all of the tests! :)

Java17VIMEMACS

Solution

```
1 public class Kata {
2     public static String createPhoneNumber(int[] numbers) {
3         return "(" + numbers[0] + numbers[1] + numbers[2] + ") "
4             + numbers[3] + numbers[4] + numbers[5] + "-"
5             + numbers[6] + numbers[7] + numbers[8] + numbers[9];
6     }
7 }
8
9
```

Outstanding! You may take your time to refactor/comment your solution. Submit when ready.

Sample Tests

```
1 import org.junit.Test;
2 import static org.junit.Assert.assertEquals;
3
4 public class PhoneExampleTests {
5     @Test
6     public void tests() {
7         assertEquals("(123) 456-7890", Kata.createPhoneNumber(new int[] {1, 2, 3, 4, 5, 6, 7, 8, 9, 0}));
8     }
9 }
```

SKIPDISCUSS (246)RESETTESTSUBMIT

2-

PROBLEMA

You probably know the "like" system from Facebook and other pages. People can "like" blog posts, pictures or other items. We want to create the text that should be displayed next to such an item.

Implement the function which takes an array containing the names of people that like an item. It must return the display text as shown in the examples:

<code>[]</code>	--> "no one likes this"
<code>["Peter"]</code>	--> "Peter likes this"
<code>["Jacob", "Alex"]</code>	--> "Jacob and Alex like this"
<code>["Max", "John", "Mark"]</code>	--> "Max, John and Mark like this"
<code>["Alex", "Jacob", "Mark", "Max"]</code>	--> "Alex, Jacob and 2 others like t

Note: For 4 or more names, the number in "and 2 others" simply increases.

STRINGS FUNDAMENTALS

SOLUCION

```
1 class Solution {
2     public static String whoLikesIt(String... name) {
3
4         switch(name.length){
5
6             case 0 : return "no one likes this";
7
8             case 1: return name[0] + " likes this";
9
10            case 2: return name[0] + " and " + name[1] + " like this";
11
12            case 3: return name[0] + ", " + name[1] + " and " + name[2] + " like this";
13
14            default: return name[0] + ", " + name[1] + " and " + (name.length - 2) + " others like this";
15        }
16
17    }
18
19 }
```

PANTALLASO

The screenshot shows a coding challenge interface for the problem "Who likes it?". The interface includes a top bar with the problem name, a difficulty level of 17, and a language selector set to Java. Below the top bar, there are tabs for "Instructions" and "Output". The "Output" tab is active, showing the test results. The test results indicate that the solution passed all tests, with a completion time of 30ms. The solution code is displayed in a code editor, showing a Java class named Solution with a static method whoLikesIt. The method uses a switch statement to handle different lengths of the name array. The sample tests are also shown, including assertions for various input cases.

Who likes it?

5664 1082 86% of 29,688 34,075 of 396,493 BattleRattle

Java 17 VIM EMACS

Instructions Output

Time: 2194ms Passed: 3 Failed: 0

Test Results:

✓ SolutionTest

staticTests

Completed in 30ms

You have passed all of the tests! :)

Solution

```
1 class Solution {
2     public static String whoLikesIt(String... name) {
3
4         switch(name.length){
5
6             case 0 : return "no one likes this";
7
8             case 1: return name[0] + " likes this";
9
10            case 2: return name[0] + " and " + name[1] + " like this";
11
12            case 3: return name[0] + ", " + name[1] + " and " + name[2] + " like this";
13
14            default: return name[0] + ", " + name[1] + " and " + (name.length - 2) + " others like this";
15        }
16
17    }
18
19 }
```

Sample Tests

```
4
5 public class SolutionTest {
6     @test
7     public void staticTests() {
8         assertEquals("no one likes this", Solution.whoLikesIt());
9         assertEquals("Peter likes this", Solution.whoLikesIt("Peter"));
10        assertEquals("Jacob and Alex like this", Solution.whoLikesIt("Jacob", "Alex"));
11        assertEquals("Max, John and Mark like this", Solution.whoLikesIt("Max", "John", "Mark"));
12        assertEquals("Alex, Jacob and 2 others like this", Solution.whoLikesIt("Alex", "Jacob", "Ma
13    }
14 }
```

3-

PROBLEMA

Instructions

Output

Introduction

It's the early morning at a world famous, 5 star restaurant. People wait in line ages to get a seat here. Your task is, given a list of groups waiting, and a list of the available tables in the restaurant, what time will the restaurant close?

Input

Group[] queue:

An array of groups waiting at the door.

Group is a preloaded record as below. You can access the object's `size()`, `timeTaken()`, `hashCode()`, `equals()`, and `toString()`

```
public record Group(int size, int timeTaken) {}
```

Ex: {new Group(2,30), new Group(4,60)} means that there are two groups in line. The first group needs to have 2 people seated, and they will take 30

SOLUCION

```
1 import java.util.ArrayList;
2
3 public class Restaurant {
4
5     public static String timeClosing(Group[] queue, int[] tables) {
6         if (queue == null || queue.length == 0) {
7             return "06:00";
8         }
9
10        int mesaMasGrande = 0;
11        for (int i = 0; i < tables.length; i++) {
12            if (tables[i] > mesaMasGrande) {
13                mesaMasGrande = tables[i];
14            }
15        }
16
17        ArrayList<Group> cola = new ArrayList<>();
18        for (int i = 0; i < queue.length; i++) {
19            if (queue[i].size() <= mesaMasGrande) {
20                cola.add(queue[i]);
21            }
22        }
23
24        if (cola.size() == 0) {
25            return "06:00";
26        }
27
28        int tiempoActual = 0;
29        int[] tiempoMesaLibre = new int[tables.length];
30
31        while (cola.size() > 0) {
32            boolean sePudoSentarAlguien = false;
33
34            for (int i = 0; i < cola.size(); i++) {
35                Group grupo = cola.get(i);
36                int mejorMesa = -1;
37                int tamanoMejorMesa = 999999;
38
39                for (int j = 0; j < tables.length; j++) {
40                    if (tables[j] >= grupo.size() && tiempoMesaLibre[j] <= tiempoActual) {
```

PANTALLASO

Restaurant Closing Time

☆ 12 ● 2 100% of 12 ● 36 👤 zkinvig

Instructions Output

Time: 7315ms Passed: 4 Failed: 0

Test Results:

- RestaurantTests
 - simpleTests()
 - smallRandomTest()
 - mediumRandomTest()
 - largeRandomTest()

Completed in 4862ms

You have passed all of the tests!)

Solution

```
1 import java.util.ArrayList;
2
3 public class Restaurant {
4
5     public static String timeClosing(Group[] queue, int[] tables) {
6         if (queue == null || queue.length == 0) {
7             return "06:00";
8         }
9
10
11         int mesaMasGrande = 0;
12         for (int i = 0; i < tables.length; i++) {
13             if (tables[i] > mesaMasGrande) {
14                 mesaMasGrande = tables[i];
15             }
16         }
17     }
18 }
```

Sample Tests

```
1 import org.junit.jupiter.api.*;
2 import java.util.*;
3
4 public class RestaurantTests {
5
6     private String queueToString(Group[] queue) {
7         StringBuilder result = new StringBuilder();
8         for (Group g : queue) {
9             result.append(g.toString()).append(" ");
10        }
```

4-

PROBLEMA

Given a string, output the encoded version of that string.

Example:

Input:

'When nobody is around, the trees gossip about the people who have wa

First, the input is normalized; Any character other than alphabetic characters should be removed from the text and the message is converted into lowercase. No digits will be passed as input. Only ASCII English letters (upper and lower case) and ASCII symbols will be in the string:

!"#\$%&'()*+,-./:;<=>?@[\\]^_`{|}~

The input is normalized into:

SOLUCION

```
1 import java.util.ArrayList;
2
3 public class Solution {
4
5     public static String cipherText(String text) {
6         if (text == null || text.length() == 0) {
7             return "";
8         }
9
10        String textoLimpio = "";
11        for (int i = 0; i < text.length(); i++) {
12            char c = text.charAt(i);
13            if ((c >= 'a' && c <= 'z') || (c >= 'A' && c <= 'Z')) {
14                textoLimpio = textoLimpio + Character.toLowerCase(c);
15            }
16        }
17
18        int n = textoLimpio.length();
19        if (n == 0) {
20            return "";
21        }
22
23        int a = (int) Math.sqrt(n);
24        int b = a;
25
26        if (a * b < n) {
27            b = a + 1;
28        }
29        if (a * b < n) {
30            a = b;
31        }
32
33        char[][] matriz = new char[a][b];
34        int indice = 0;
35
36        for (int i = 0; i < a; i++) {
37            for (int j = 0; j < b; j++) {
38                if (indice < n) {
39                    matriz[i][j] = textoLimpio.charAt(indice);
40                    indice++;
41                } else {
42                    matriz[i][j] = ' ';
43                }
44            }
45        }
46    }
47}
```

```
20         return "";
21     }
22
23     int a = (int) Math.sqrt(n);
24     int b = a;
25
26     if (a * b < n) {
27         b = a + 1;
28     }
29     if (a * b < n) {
30         a = b;
31     }
32
33     char[][] matriz = new char[a][b];
34     int indice = 0;
35
36     for (int i = 0; i < a; i++) {
37         for (int j = 0; j < b; j++) {
38             if (indice < n) {
39                 matriz[i][j] = textoLimpio.charAt(indice);
40                 indice++;
41             } else {
42                 matriz[i][j] = ' ';
43             }
44         }
45     }
46
47     String resultado = "";
48     for (int j = 0; j < b; j++) {
49         String bloque = "";
50         for (int i = 0; i < a; i++) {
51             bloque = bloque + matriz[i][j];
52         }
53         if (j == 0) {
54             resultado = bloque;
55         } else {
56             resultado = resultado + " " + bloque;
57         }
58     }
59
60     return resultado;
61 }
62 }
```

PANTALLASO

6kpsu

Rectangle letter juggling

☆ 18 ● 1 ↗ 88% of 106 ● 37 of 295 👤 sid114

Instructions

Output

Given a string, output the encoded version of that string.

Example:

Input:

'When nobody is around, the trees gossip about the people who have wa

First, the input is normalized; Any character other than alphabetic characters should be removed from the text and the message is converted into lowercase. No digits will be passed as input. Only ASCII English letters (upper and lower case) and ASCII symbols will be in the string:

!"#\$%&'()*+,-./:;<=>?@[\\]^_`{|}~

The input is normalized into:

8 Reasons Why Codewarriors Practice Coding with Codewars

Java

17

VIM EMACS

Solution

```
1 import java.util.ArrayList;
2
3 public class Solution {
4
5     public static String cipherText(String text) {
6         if (text == null || text.length() == 0) {
7             return "";
8         }
9
10        String textolimpio = "";
11        for (int i = 0; i < text.length(); i++) {
12            char c = text.charAt(i);
13            if ((c >= 'a' && c <= 'z') || (c >= 'A' && c <= 'Z')) {
14                textolimpio = textolimpio + Character.toLowerCase(c);
15            }
16        }
17    }
18 }
```

Sample Tests

```
1 import org.junit.Test;
2 import static org.junit.Assert.assertEquals;
3 import org.junit.runners.JUnit4;
4
5 // TODO: Replace examples and use TDD by writing your own tests
6
7 public class SolutionTest {
8     @Test
9     public void basicTests() {
10         assertEquals("wytotear hihstwit eseshkhk natieoe nripphdm ooeaeau buebovm onsped ddgul",
11             Solution.cipherText("When nobody is around, the trees gossip about the people who have wa")
12         );
13     }
14 }
```

5-

PROBLEMA



Alex & snooker: scores.

☆ 23 🏆 7 🔄 91% of 123 © 101 of 546 👤 nekokat

Instructions

Output

Alex is a devoted fan of the Snooker Masters and, in particular, recorded the results of all the matches. Help Alex determine the score of the matches.

Hint:

A string with a score is presented as follows: **"24-79(72); 16-101(53); ..."**

"24" - points scored by the first player;

"79" - the number of points scored by the second player.

"(72)" - the maximum score for one approach.

Also, a player's score may be expressed as 105(53,52):

"105" - points in the frame, "53" and "52" - two separate numbers (not floats) giving the maximum points in the frame.

Frames are separated by ";" and the players' scores by "-".

It should count the number of frames won by each player and output the data as a "[10,7]".



STATISTICS

ARRAYS

STRINGS

ALGORITHMS



Educator, struggling to assess your students?

Assess your classroom or bootcamp with the world leading assessment platform, Qualified. [Request your demo today!](#)



SOLUCION

```

1 public class Frame {
2
3     public static int[] frame(String score) {
4         if (score == null || score.length() == 0) {
5             return new int[]{0, 0};
6         }
7
8         int junsP1 = 0;
9         int junsP2 = 0;
10
11         String[] frames = score.split(";");
12
13         for (int i = 0; i < frames.length; i++) {
14             String f = frames[i].trim();
15             if (f.length() == 0) {
16                 continue;
17             }
18
19             String[] partes = f.split("-");
20             String p1Texto = partes[0].trim();
21             String p2Texto = partes[1].trim();
22
23             int puntosP1 = extraerPuntos(p1Texto);
24             int puntosP2 = extraerPuntos(p2Texto);
25
26             if (puntosP1 > puntosP2) {
27                 junsP1++;
28             } else if (puntosP2 > puntosP1) {
29                 junsP2++;
30             }
31         }
32
33         return new int[]{junsP1, junsP2};
34     }
35
36     private static int extraerPuntos(String texto) {
37         int posPar = texto.indexOf("(");
38         if (posPar != -1) {
39             texto = texto.substring(0, posPar).trim();
40         }
41         return Integer.parseInt(texto);
42     }
43 }

```

PANTALLASO

Instructions

Output

Restore

Alex is a devoted fan of the Snooker Masters and, in particular, recorded the results of all the matches. Help Alex determine the score of the matches.

Hint:
A string with a score is presented as follows: "24-79(72); 16-101(53); ..."
"24" - points scored by the first player;
"79" - the number of points scored by the second player.
"(72)" - the maximum score for one approach.
Also, a player's score may be expressed as 105(53,52):
"105" - points in the frame, "53" and "52" - two separate numbers (not floats) giving the maximum points in the frame.
Frames are separated by ";" and the players' scores by "-".
It should count the number of frames won by each player and output the data as a "[10,7]".

STATISTICS ARRAYS STRINGS ALGORITHMS

Educator, struggling to assess your students?
Assess your classroom or bootcamp with the world leading assessment platform, Qualified. Request your demo today!

Solution

```
1 public class Frame {  
2  
3     public static int[] frame(String score) {  
4         if (score == null || score.length() == 0) {  
5             return new int[]{0, 0};  
6         }  
7  
8         int junsP1 = 0;  
9         int junsP2 = 0;  
10  
11         String[] frames = score.split(";");  
12  
13         for (int i = 0; i < frames.length; i++) {  
14             String f = frames[i].trim();  
15             if (f.length() == 0) {  
16                 continue;  
17             }  
18         }  
19     }  
20 }
```

Sample Tests

```
4  
5 public class FrameTest {  
6     @test  
7     public void ExampleTests() {  
8         System.out.println("Ronnie O'Sullivan - Joe Perry");  
9         String score = "24-79(72); 16-101(53); 86(58)-27; 31-90(74); 0-115(115); 67-40; 61-21; 81(55)-23;  
10         assertEquals("Ronnie O'Sullivan won Masters 2017!", new int[] {10, 7}, Frame.frame(score));  
11     }  
12 }  
13
```

SKIP UNLOCK SOLUTIONS DISCUSS (11) RESET

TEST ATTEMPT

6-

PROBLEMA

Instructions

Output

In the drawing below we have a part of the Pascal's triangle, lines are numbered from **zero** (top). The left diagonal in pale blue with only numbers equal to 1 is diagonal **zero**, then in dark green (1, 2, 3, 4, 5, 6, 7) is diagonal 1, then in pale green (1, 3, 6, 10, 15, 21) is diagonal 2 and so on.

We want to calculate the sum of the binomial coefficients on a given diagonal. The sum on diagonal 0 is 8 (we'll write it $S(7, 0)$, 7 is the number of the line where we start, 0 is the number of the diagonal). In the same way $S(7, 1)$ is 28, $S(7, 2)$ is 56.

Can you write a program which calculates $S(n, n)$ where n is the line where we

GOT FEEDBACK FOR US ?

SOLUCION

```
1 import java.math.BigInteger;
2
3 public class Diagonal {
4
5     public static BigInteger diagonal(int n, int p) {
6         BigInteger resultado = BigInteger.ONE;
7
8         int num = n + 1;
9         int den = p + 1;
10
11         for (int i = 0; i < den; i++) {
12             resultado = resultado.multiply(BigInteger.valueOf(num - i));
13             resultado = resultado.divide(BigInteger.valueOf(i + 1));
14         }
15
16         return resultado;
17     }
18 }
```

PANTALLASO

The screenshot shows a coding challenge interface for 'Easy Diagonal'. The top bar includes the problem title, a star rating of 279, a difficulty level of 55, a completion rate of 88% of 483 users, a time limit of 246 of 2,647, a user count of 964, and a note that 1 issue has been reported. The interface is divided into three main sections: 'Instructions', 'Output', and 'Solution'. The 'Instructions' section shows the test results for 'DiagonalTest', indicating that all tests passed (3 passed, 0 failed) in 2115ms. The 'Output' section shows a message: 'You have passed all of the tests! :)'. The 'Solution' section displays the Java code for the 'Diagonal' class, which calculates the diagonal of a matrix. The 'Sample Tests' section shows the test code for 'DiagonalTest', which uses JUnit to verify the output of the 'diagonal' method. The bottom bar includes buttons for 'SKIP', 'UNLOCK SOLUTIONS', 'DISCUSS (52)', 'RESET', 'TEST', and 'ATTEMPT'.

Easy Diagonal

☆ 279 ● 55 ↗ 88% of 483 ⌚ 246 of 2,647 👤 964 ⚠ 1 Issue Reported

Instructions Output

Time: 2115ms Passed: 3 Failed: 0

Test Results:

▼ DiagonalTest

- > test1
- > test2
- > test3

Completed in 15ms

You have passed all of the tests! :)

Solution

```
1 import java.math.BigInteger;
2
3 public class Diagonal {
4
5     public static BigInteger diagonal(int n, int p) {
6         BigInteger resultado = BigInteger.ONE;
7
8         int num = n + 1;
9         int den = p + 1;
10
11         for (int i = 0; i < den; i++) {
12             resultado = resultado.multiply(BigInteger.valueOf(num - i));
13             resultado = resultado.divide(BigInteger.valueOf(i + 1));
14         }
15
16         return resultado;
17     }
18 }
```

Sample Tests

```
1 import static org.junit.Assert.*;
2 import org.junit.Test;
3 import java.math.BigInteger;
4
5 public class DiagonalTest {
6
7     @Test
8     public void test1() {
9         assertEquals(BigInteger.valueOf(5985), Diagonal.diagonal(20, 3));
10     }
11 }
```

⏪ SKIP 🔒 UNLOCK SOLUTIONS 💬 DISCUSS (52) 🔄 RESET TEST ATTEMPT

7-

PROBLEMA

Instructions

Output

An orderly trail of ants is marching across the park picnic area.

It looks something like this:

```
..ant..ant.ant...ant.ant..ant.ant....ant..ant.ant.ant...ant..
```

But suddenly there is a rumour that a dropped chicken sandwich has been spotted on the ground ahead. The ants surge forward! *Oh No, it's an ant stampede!!*

Some of the slower ants are trampled, and their poor little ant bodies are broken up into scattered bits.

The resulting carnage looks like this:

```
...ant...ant..nat.ant.t..ant...ant..ant..ant..anant..t
```

Can you find how many ants have died?

SOLUCION

```
1 public class Dinglemouse {
2
3     public static int deadAntCount(final String ants) {
4         if (ants == null || ants.length() == 0) {
5             return 0;
6         }
7
8         String sinAnts = ants.replace("ant", "");
9
10        int a = 0;
11        int n = 0;
12        int t = 0;
13
14        for (int i = 0; i < sinAnts.length(); i++) {
15            char c = sinAnts.charAt(i);
16            if (c == 'a') {
17                a++;
18            } else if (c == 'n') {
19                n++;
20            } else if (c == 't') {
21                t++;
22            }
23        }
24
25        int max = a;
26        if (n > max) {
27            max = n;
28        }
29        if (t > max) {
30            max = t;
31        }
32
33        return max;
34    }
35 }
```

PANTALLASO

6 kyu

Dead Ants

☆ 141 ● 32 ↗ 90% of 557 ● 402 of 2,961 👤 dinglemouse 🚩 1 Issue Reported

Instructions

Output

An orderly trail of ants is marching across the park picnic area.

It looks something like this:

```
...ant..ant..ant...ant..ant...ant...ant..ant..ant...ant..
```

But suddenly there is a rumour that a dropped chicken sandwich has been spotted on the ground ahead. The ants surge forward! *Oh No, it's an ant stampede!!*

Some of the slower ants are trampled, and their poor little ant bodies are broken up into scattered bits.

The resulting carnage looks like this:

```
...ant...ant...ant..ant..t...ant...ant...ant...ant..ant...t
```

Can you find how many ants have died?

8 Reasons Why Codewarriors Practice Coding with Codewars

Not everyone trains the same. Discover new ways to leverage Codewars in your education and career.

Java

17

VIM EMACS

Solution

```
1 public class Dinglemouse {
2
3     public static int deadAntCount(final String ants) {
4         if (ants == null || ants.length() == 0) {
5             return 0;
6         }
7
8         String sinAnts = ants.replace("ant", "");
9
10        int a = 0;
11        int n = 0;
12        int t = 0;
13
14        for (int i = 0; i < sinAnts.length(); i++) {
15            char c = sinAnts.charAt(i);
16            if (c == 'a') {
17                a++;
18            }
19        }
20        return a;
21    }
22}
```

Sample Tests

```
1 import org.junit.Test;
2 import static org.junit.Assert.assertEquals;
3 import org.junit.runners.JUnit4;
4
5 public class Tests {
6
7     @Test
8     public void example() {
9         assertEquals(0, Dinglemouse.deadAntCount("ant ant ant ant"));
10        assertEquals(0, Dinglemouse.deadAntCount(null));
11    }
12}
```

SKIP

UNLOCK SOLUTIONS

DISCUSS (36)

RESET

TEST

ATTEMPT

8-

PROBLEMA

Instructions

Output

An isogram is a word that has no repeating letters, consecutive or non-consecutive. Implement a function that determines whether a string that contains only letters is an isogram. Assume the empty string is an isogram. Ignore letter case.

Example: (Input --> Output)

```
"Dermatoglyphics" --> true  
"aba" --> false  
"mo0se" --> false (ignore letter case)
```



STRINGS

FUNDAMENTALS

GOT FEEDBACK FOR US?



Our Annual Census is Ongoing!

Help shape what's next for Codewars in under 7 minutes, and you can opt in for a chance to win a

 **codewars**

SOLUCION

```

1 public class isogram {
2
3     public static boolean isIsogram(String str) {
4         if (str == null || str.length() == 0) {
5             return true;
6         }
7
8         String texto = str.toLowerCase();
9
10        for (int i = 0; i < texto.length(); i++) {
11            char letraActual = texto.charAt(i);
12
13            for (int j = i + 1; j < texto.length(); j++) {
14                if (letraActual == texto.charAt(j)) {
15                    return false;
16                }
17            }
18        }
19
20        return true;
21    }
22 }

```

PANTALLASO

7kyu

Isograms

3193

736

90% of 21,664

25,836 of 292,994

chunjef

2 Issues Reported

Instructions

Output

Time: 2075ms Passed: 1 Failed: 0

Test Results:

Tests

FixedTests

Completed in 13ms

You have passed all of the tests! :)

Java

17

VIM EMACS

Solution

```

1 public class isogram {
2
3     public static boolean isIsogram(String str) {
4         if (str == null || str.length() == 0) {
5             return true;
6         }
7
8         String texto = str.toLowerCase();
9
10        for (int i = 0; i < texto.length(); i++) {
11            char letraActual = texto.charAt(i);
12
13            for (int j = i + 1; j < texto.length(); j++) {
14                if (letraActual == texto.charAt(j)) {
15                    return false;
16                }
17            }
18        }
19
20        return true;
21    }
22 }

```

Sample Tests

```

1 import org.junit.Test;
2 import static org.junit.Assert.assertEquals;
3 import org.junit.runners.JUnit4;
4 public class Tests {
5     @Test
6     public void FixedTests() {
7         assertEquals(true, isogram.isIsogram("Dermatoglyphics"));
8         assertEquals(true, isogram.isIsogram("isogram"));
9         assertEquals(false, isogram.isIsogram("moose"));
10        assertEquals(false, isogram.isIsogram("isIsogram"));
11    }
12 }

```

SKIP

UNLOCK SOLUTIONS

DISCUSS (272)

RESET

TEST

ATTEMPT

9-

PROBLEMA

Write a function which receives 4 digits and returns the latest time of day that can be built with those digits.

The time should be in `HH:MM` format.

Examples:

```
digits: 1, 9, 8, 3 => result: "19:38"
```

```
digits: 9, 1, 2, 5 => result: "21:59" (19:25 is also a valid time, but
```

Notes

- Result should be a valid 24-hour time, between `00:00` and `23:59`.
- Only inputs which have valid answers are tested.



DATE TIME

FUNDAMENTALS

ALGORITHMS

SOLUCION

```

1 public class Kata {
2
3     public static String latestClock(int a, int b, int c, int d) {
4         int[] digitos = {a, b, c, d};
5         int maxMinutos = -1;
6
7         for (int i = 0; i < 4; i++) {
8             for (int j = 0; j < 4; j++) {
9                 if (i == j) {
10                     continue;
11                 }
12                 for (int k = 0; k < 4; k++) {
13                     if (k == i || k == j) {
14                         continue;
15                     }
16                     for (int l = 0; l < 4; l++) {
17                         if (l == i || l == j || l == k) {
18                             continue;
19                         }
20
21                         int horas = digitos[i] * 10 + digitos[j];
22                         int minutos = digitos[k] * 10 + digitos[l];
23
24                         if (horas < 24 && minutos < 60) {
25                             int total = horas * 60 + minutos;
26                             if (total > maxMinutos) {
27                                 maxMinutos = total;
28                             }
29                         }
30                     }
31                 }
32             }
33         }
34
35         if (maxMinutos == -1) {
36             return "";
37         }
38
39         int h = maxMinutos / 60;
40         int m = maxMinutos % 60;
41
42         String horaTexto = "";
43         if (h < 10) {
44             horaTexto = "0" + h;
45         } else {
46             horaTexto = "" + h;
47         }
48
49         String minutoTexto = "";
50         if (m < 10) {
51             minutoTexto = "0" + m;
52         } else {
53             minutoTexto = "" + m;
54         }

```

```

1 public class Kata {
2
3     public static String latestClock(int a, int b, int c, int d) {
4         int[] digitos = {a, b, c, d};
5         int maxMinutos = -1;
6
7         for (int i = 0; i < 4; i++) {
8             for (int j = 0; j < 4; j++) {
9                 if (i == j) {
10                     continue;
11                 }
12                 for (int k = 0; k < 4; k++) {
13                     if (k == i || k == j) {
14                         continue;
15                     }
16                     for (int l = 0; l < 4; l++) {
17                         if (l == i || l == j || l == k) {
18                             continue;
19                         }
20
21                         int horas = digitos[i] * 10 + digitos[j];
22                         int minutos = digitos[k] * 10 + digitos[l];
23
24                         if (horas < 24 && minutos < 60) {
25                             int total = horas * 60 + minutos;
26                             if (total > maxMinutos) {
27                                 maxMinutos = total;
28                             }
29                         }
30                     }
31                 }
32             }
33         }
34
35         if (maxMinutos == -1) {
36             return "";
37         }
38
39         int h = maxMinutos / 60;
40         int m = maxMinutos % 60;
41
42         String horaTexto = "";
43         if (h < 10) {
44             horaTexto = "0" + h;
45         } else {
46             horaTexto = "" + h;
47         }
48
49         String minutoTexto = "";
50         if (m < 10) {
51             minutoTexto = "0" + m;
52         } else {
53             minutoTexto = "" + m;
54         }

```

```

5      int maxMinutos = -1;
6
7      for (int i = 0; i < 4; i++) {
8          for (int j = 0; j < 4; j++) {
9              if (i == j) {
10                 continue;
11             }
12             for (int k = 0; k < 4; k++) {
13                 if (k == i || k == j) {
14                     continue;
15                 }
16                 for (int l = 0; l < 4; l++) {
17                     if (l == i || l == j || l == k) {
18                         continue;
19                     }
20
21                     int horas = digitos[i] * 10 + digitos[j];
22                     int minutos = digitos[k] * 10 + digitos[l];
23
24                     if (horas < 24 && minutos < 60) {
25                         int total = horas * 60 + minutos;
26                         if (total > maxMinutos) {
27                             maxMinutos = total;
28                         }
29                     }
30                 }
31             }
32         }
33     }
34
35     if (maxMinutos == -1) {
36         return "";
37     }
38
39     int h = maxMinutos / 60;
40     int m = maxMinutos % 60;
41
42     String horaTexto = "";
43     if (h < 10) {
44         horaTexto = "0" + h;
45     } else {
46         horaTexto = "" + h;
47     }
48
49     String minutoTexto = "";
50     if (m < 10) {
51         minutoTexto = "0" + m;
52     } else {
53         minutoTexto = "" + m;
54     }
55
56     return horaTexto + ":" + minutoTexto;
57 }
58 }

```

PANTALLASO

The screenshot shows a coding challenge interface. On the left, the 'Instructions' tab is active, displaying test results for the 'LatestClockTest' class. The tests passed, and a message states 'You have passed all of the tests! :)'.

On the right, the 'Solution' tab is active, showing a Java implementation of the 'latestClock' method. The code iterates through all possible combinations of hours (0-23) and minutes (0-59) to find the latest valid time that can be formed using the provided digits.

```
1 public class Kata {
2     public static String latestClock(int a, int b, int c, int d) {
3         int[] digits = {a, b, c, d};
4         int maxMinutes = -1;
5
6         for (int i = 0; i < 4; i++) {
7             for (int j = 0; j < 4; j++) {
8                 if (i == j) {
9                     continue;
10                }
11                for (int k = 0; k < 4; k++) {
12                    if (k == i || k == j) {
13                        continue;
14                    }
15                    for (int l = 0; l < 4; l++) {
16                        if (l == i || l == j || l == k) {
17                            continue;
18                        }
19                        int hours = digits[i] * 10 + digits[j];
20                        int minutes = digits[k] * 10 + digits[l];
21
22                        // ... (rest of the logic to find the latest time)
23                    }
24                }
25            }
26        }
27    }
28 }
```

Below the solution, the 'Sample Tests' tab is active, showing the test cases used to verify the solution:

```
1 import org.junit.jupiter.api.*;
2 import static org.junit.jupiter.api.Assertions.assertEquals;
3
4 public class LatestClockTest {
5     @Test @DisplayName("latestClock(1, 9, 8, 3) should return \"19:38\"")
6     public void test_1_9_8_3() {
7         assertEquals("19:38", Kata.latestClock(1, 9, 8, 3));
8     }
9
10    @Test @DisplayName("latestClock(9, 1, 2, 5) should return \"21:59\"")
11    public void test_9_1_2_5() {
12        assertEquals("21:59", Kata.latestClock(9, 1, 2, 5));
13    }
14 }
```

10-

PROBLEMA

Write a function which receives 4 digits and returns the latest time of day that can be built with those digits.

The time should be in `HH:MM` format.

Examples:

```
digits: 1, 9, 8, 3 => result: "19:38"
digits: 9, 1, 2, 5 => result: "21:59" (19:25 is also a valid time, but 21:59 is later)
```

Notes

- Result should be a valid 24-hour time, between `00:00` and `23:59`.
- Only inputs which have valid answers are tested.

DATE TIME FUNDAMENTALS ALGORITHMS

SOLUCION

```

1 public class Kata {
2
3     public static String latestClock(int a, int b, int c, int d) {
4         int[] digitos = {a, b, c, d};
5         int maxMinutos = -1;
6
7         for (int i = 0; i < 4; i++) {
8             for (int j = 0; j < 4; j++) {
9                 if (i == j) {
10                     continue;
11                 }
12                 for (int k = 0; k < 4; k++) {
13                     if (k == i || k == j) {
14                         continue;
15                     }
16                     for (int l = 0; l < 4; l++) {
17                         if (l == i || l == j || l == k) {
18                             continue;
19                         }
20
21                         int horas = digitos[i] * 10 + digitos[j];
22                         int minutos = digitos[k] * 10 + digitos[l];
23
24                         if (horas < 24 && minutos < 60) {
25                             int total = horas * 60 + minutos;
26                             if (total > maxMinutos) {
27                                 maxMinutos = total;
28                             }
29                         }
30                     }
31                 }
32             }
33         }
34
35         if (maxMinutos == -1) {
36             return "";
37         }
38
39         int h = maxMinutos / 60;
40         int m = maxMinutos % 60;
41
42         String horaTexto = "";
43         if (h < 10) {
44             horaTexto = "0" + h;
45         } else {
46             horaTexto = "" + h;
47         }
48
49         String minutoTexto = "";
50         if (m < 10) {
51             minutoTexto = "0" + m;
52         } else {
53             minutoTexto = "" + m;
54         }

```

PANTALLASO

Instructions

Output

Time: 2074ms Passed: 2 Failed: 0

Test Results:

LatestClockTest

- latestClock(9, 1, 2, 5) should return "21:59"
- latestClock(1, 9, 8, 3) should return "19:38"

Completed in 48ms

You have passed all of the tests! :)

Solution

```
21 * for (int k = 0; k < d; k++) {
22 *     if (k == i || k == j) {
23 *         continue;
24 *     }
25 *     for (int l = 0; l < 4; l++) {
26 *         if (l == i || l == j || l == k) {
27 *             continue;
28 *         }
29 *         int horas = digitos[i] * 10 + digitos[j];
30 *         int minutos = digitos[k] * 10 + digitos[l];
31 *
32 *         if (horas < 24 && minutos < 60) {
33 *             int total = horas * 60 + minutos;
34 *             if (total > maxMinutos) {
35 *                 maxMinutos = total;
36 *             }
37 *         }
38 *     }
39 * }
40 *
41 * if (maxMinutos == -1) {
```

Sample Tests

```
1 * import org.junit.jupiter.api.*;
2 * import static org.junit.jupiter.api.Assertions.assertEquals;
3 *
4 * public class LatestClockTest {
5 *
6 *     @Test @DisplayName("latestClock(1, 9, 8, 3) should return \"19:38\"")
7 *     public void test_1_9_8_3() {
8 *         assertEquals("19:38", Kata.latestClock(1, 9, 8, 3));
9 *     }
10 *
11 *     @Test @DisplayName("latestClock(9, 1, 2, 5) should return \"21:59\"")
12 *     public void test_9_1_2_5() {
13 *         assertEquals("21:59", Kata.latestClock(9, 1, 2, 5));
14 *     }
15 * }
```