

L12a: Synthetic Markets with Jump Hidden Markov Models

CHEME 5660 Cornell University

Copyright Jeffrey Varner 2026. All Rights Reserved

Disclaimer and Risks

Training only. This content is for training and informational purposes only. The teaching team does not make, give, or endorse any offer or solicitation to buy or sell securities or derivative products, or provide investment or trading advice or strategy.

Risk. Trading involves risk and is generally not recommended for those with limited resources, experience, or a low risk tolerance. Past performance does not guarantee future success.

Responsibility. You are responsible for your investment decisions based on your financial circumstances, objectives, risk tolerance, and liquidity needs.

Objectives for Today

Today, we build synthetic markets: simulated price histories with the features of real ones. How would a trading method do on thousands of plausible paths?

Today's concepts

- Markov chains and hidden Markov models: states, transition matrices, stationary distributions, emissions.
- A jump hidden Markov model of one asset: binned states, counted transitions, Student-t emissions, jump episodes.
- A synthetic market of many stocks: shared market and sector draws plus each stock's own draw.

What You Need to Know

Core concepts

- A Markov chain is a set of states $\mathcal{S}$ and a transition matrix $\mathbf{P}$ whose rows sum to one; its stationary distribution satisfies $\bar{\pi} = \bar{\pi}\mathbf{P}$.
- The jump hidden Markov model bins the daily growth rate into states, estimates $\mathbf{P}$ by counting, and draws each day from a Student-t of the day's state. Jump episodes (probability ϵ, mean length λ) keep volatility clustering.
- A synthetic stock is $g_i = \alpha_i + \beta_i\, g_m + \delta_i\, f_s + \psi_i\, \tilde{\varepsilon}_i$: shared market and sector draws make stocks move together.

For understanding (you won't reproduce these)

- Power iteration, the tuning objective for ϵ and λ, and how the sector loadings and own-draw scale are chosen.

Lectures and Examples

Lecture:

CHEME-5660-L12a-Lecture-JumpHMM-SyntheticMarkets-Fall-2026.ipynb

Examples:

CHEME-5660-L12a-Example-JumpHMM-SPY-Fall-2026.ipynb

CHEME-5660-L12a-Example-JumpHMM-SectorFactor-Fall-2026.ipynb

Why Synthetic Markets?

A backtest runs a method on one historical path, and a method that did well may have been lucky. A synthetic market generates many plausible paths. For stress tests, its paths need:

- Fat tails: large daily moves are far more common than a normal distribution predicts.
- Volatility clustering: large moves follow large moves, so the size of the daily move stays correlated for weeks.
- Co-movement: stocks move together, through the market and their sectors.

Geometric Brownian motion can have co-movement through correlated shocks, but neither fat tails nor volatility clustering.

Markov Chains

A discrete Markov model $\mathcal{M} = (\mathcal{S}, \mathbf{P})$ has a state space $\mathcal{S}$, the set of values the system can take, and a transition matrix $\mathbf{P}$. It has the Markov property: given the present state, the past does not matter:

$$P(X_{n+1} = s_{n+1} \mid X_0 = s_0, \ldots, X_n = s_n) = P(X_{n+1} = s_{n+1} \mid X_n = s_n)$$

The one-step transition probability from s_i to s_j is $p_{ij} = P(X_{n+1} = s_j \mid X_n = s_i)$, the same for every n (time-homogeneous).

The Transition Matrix

The p_{ij} fill the transition matrix $\mathbf{P} \in \mathbb{R}^{|\mathcal{S}|\times|\mathcal{S}|}$: rows are current states, columns next states, $p_{ij} \geq 0$, and each row sums to one. For weather with $\mathcal{S} = \{\text{Sunny}, \text{Rainy}\}$:

$$\mathbf{P} = \begin{bmatrix} 0.8 & 0.2 \\ 0.4 & 0.6 \end{bmatrix} \qquad \pi_1 = \pi_0 \mathbf{P} = [1,\, 0] \begin{bmatrix} 0.8 & 0.2 \\ 0.4 & 0.6 \end{bmatrix} = [0.8,\, 0.2]$$

If today is Sunny, tomorrow is Sunny with probability 0.8. The distribution π is a row vector: $\pi'_j = \sum_i \pi_i p_{ij}$.

Estimating the Transition Matrix

We do not know $\mathbf{P}$; we estimate it from observed states $X_1, \dots, X_T$. With n_{ij} the number of days in s_i followed by a day in s_j:

$$\hat{p}_{ij} = \frac{n_{ij}}{\sum_{k=1}^{|\mathcal{S}|} n_{ik}}$$

the share of days in s_i that moved to s_j. Each row sums to one by construction; this is the maximum likelihood estimate, and how a market generator estimates its transition matrix.

The Stationary Distribution

The stationary distribution $\bar{\pi}$ is unchanged by a step, $\bar{\pi} = \bar{\pi}\mathbf{P}$: the long-run share of time in each state, and where a generator starts its paths. Power iteration applies $\mathbf{P}$ until nothing changes:

- Start from the uniform $\pi = [1/N, \ldots, 1/N]$ over the N states.
- Repeat $\pi' \leftarrow \pi\mathbf{P}$ until $\|\pi' - \pi\|_1 \leq$ tol or T iterations; return $\bar{\pi} \leftarrow \pi'$.

This needs an ergodic $\mathbf{P}$; software often solves $\bar{\pi} = \bar{\pi}\mathbf{P}$ directly instead.

Hidden Markov Models

In a hidden Markov model $\mathcal{M} = (\mathcal{S}, \mathcal{O}, \mathbf{P}, \mathbf{E})$ we do not see the states, only what they emit: observations $\mathcal{O}$ with emission probabilities $e_{ij} = P(O_n = o_j \mid X_n = s_i)$, rows summing to one. To sample: draw $X_0 \sim \bar{\pi}$; then each step draws X_n from row X_{n-1} of $\mathbf{P}$ and O_n from row X_n of $\mathbf{E}$.

Continuous emissions: a growth rate is a number, so each state has an emission *distribution* instead of a row of $\mathbf{E}$: $g_n \mid X_n = s_k \sim$ emission distribution of s_k.

The Jump Hidden Markov Model

For the daily growth rate $g_t = \frac{1}{\Delta t}\ln(S_t/S_{t-1})$ (1/yr) of one asset:

- States: fit a Laplace distribution to the growth rates and cut it into N bins of equal probability; state 1 holds the most negative growth rates.
- Transitions: assign each day to its bin and count, $\hat{p}_{ij}$.
- Emissions: in state s_k, $g_t \mid X_t = s_k \sim \mu_k + \sigma_k T_\nu$: μ_k, σ_k the mean and standard deviation of the days in that state, T_ν a Student-t with ν fixed.

In the data the states are observed bins; in simulation they are hidden, and only the growth rates are reported.

Why Add Jumps?

The counted chain forgets quickly: after a volatile day, a few transitions usually return it to the middle states, so $|g_t|$ is correlated for only a few days. Jump episodes keep volatile periods going:

- With no episode under way, an episode starts with probability ϵ.
- It lasts a Poisson number of days with mean λ.
- Each episode day is drawn from the few most extreme states, negative or positive: a run of large moves of both signs.

Tuning and Checking the Model

A grid search picks (ϵ, λ). On the M simulated paths with an episode, it scores each path's autocorrelation $\hat{\rho}_{m,k}$ of $|g_t|$ and kurtosis $\hat{\kappa}_m$ against the data's ρ_k, κ:

$$J(\epsilon, \lambda) = \frac{1}{M} \sum_{m=1}^{M} \Big[\sum_{k=1}^{25} \left(\rho_k - \hat{\rho}_{m,k}\right)^2 + 0.2 \left(\kappa - \hat{\kappa}_m\right)^2 \Big]$$

The score is noisy, so the chosen pair can change with the seed.

Example: CHEME-5660-L12a-Example-JumpHMM-SPY-Fall-2026.ipynb

Many Assets: The Sector Factor Model

Each synthetic stock i in sector s is built from draws it shares with other stocks and a draw of its own:

$$g_i(t) = \alpha_i + \beta_i \underbrace{g_m(t)}_{\text{market}} + \delta_i \underbrace{f_s(t)}_{\text{sector}} + \psi_i \underbrace{\tilde{\varepsilon}_i(t)}_{\text{own}}$$

α_i, β_i: single index estimates, held fixed. f_s: a model of the sector's average residual, with loading δ_i. $\tilde{\varepsilon}_i$: a model of the stock, centered and scaled by ψ_i so its variance matches the real one on average. Each piece is a jump hidden Markov model.

What the Model Keeps and Gives Up

Composing stocks from shared draws on the same day has consequences:

- Keeps: fat tails and clustered volatility in every draw; stocks in a sector move together through their shared sector draw, all stocks through the market draw.
- Gives up: sector draws are independent, so stocks in different sectors are linked only through the market.
- No copula: a copula reorders each stock's draws across days and would scramble the timing of the volatile periods and jump episodes in them.

An Option: A Drifting β

Holding β_i fixed is a simplification: real β wanders. The model can let $\beta_i(t)$ drift around $\hat{\beta}_i$ as an exponential moving average of random shocks, sized by how much the online estimate of β wanders in the real data.

A trading method that re-estimates β as it trades then faces the same problem in the synthetic market as in the real one.

Example: CHEME-5660-L12a-Example-JumpHMM-SectorFactor-Fall-2026.ipynb

Summary

We built synthetic markets for stress tests, from Markov chains to a jump hidden Markov model of one asset and a sector factor model of many stocks.

Key takeaways

- Markov chains: states, a transition matrix estimated by counting, and a stationary distribution; hidden states emit what we observe.
- Jump hidden Markov model: fat tails from binned Student-t states, and part of the volatility clustering from tuned jump episodes.
- Sector factor model: shared market and sector draws make synthetic stocks move together.

Synthetic markets let us test a method on many paths, not one.