
Hybrid Hidden Markov Model for Modeling Equity Excess Growth Rate Dynamics: A Discrete-State Approach with Jump-Diffusion

Abdulrahman Alswaidan

Robert Frederick Smith School of Chemical and Biomolecular Engineering
Cornell University, Ithaca, NY 14850
aa@cornell.edu

Jeffrey D. Varner

Robert Frederick Smith School of Chemical and Biomolecular Engineering
Cornell University, Ithaca, NY 14850
jdv27@cornell.edu

Abstract

Synthetic equity return paths underpin stress testing, portfolio validation, and training data for machine-learning pipelines, yet existing generators leave two gaps: single-asset stylized facts (heavy tails, regime persistence, volatility clustering) rarely appear together in one model, and the standard recipe for adding multi-asset factor structure on top of a per-asset generator distorts the marginal the generator was built to deliver. We closed both gaps with a two-stage construction. The first stage was a hybrid hidden Markov framework that discretized excess growth rates into states defined by quantiles of a fitted Laplace distribution and augmented regime switching with a Poisson jump-duration mechanism, enforcing realistic tail-state dwell times without iterative Baum-Welch optimization. The second stage was a closed-form variance-corrected single-index composer that rescaled the per-asset generator draw before insertion into the market factor, preserving the marginal variance while recovering the calibrated factor loading; a sign-preserving clip handled high-leverage assets and a coefficient-of-determination-driven branch handled index-tracking assets, with each composed series tagged by a persisted construction flag so downstream consumers could audit the chosen path. We evaluated both stages on a US equity and exchange-traded-fund universe calibrated against a decade of SPY history with a one-year hold-out, benchmarking against parametric, neural, semi-Markov, and residual-fit alternatives on distributional, tail, factor-recovery, and Value-at-Risk metrics. The hybrid marginals reproduced the stylized facts in-sample and out-of-sample, and the variance-corrected composer recovered the calibrated factor loading while preserving heavy-tailed character at tail-risk accuracy comparable to dedicated residual fits. We also documented one downstream-use caveat, an iid-residual diversification-return artifact under daily rebalancing, addressable via a uniform location-shift correction anchored to a documented long-run prior. All code and per-asset fitted marginals were released as part of the open-source JumpHMM.jl library.

Keywords: hidden Markov model; jump-diffusion; single-index model; synthetic financial data; variance correction; Value-at-Risk backtest; volatility clustering; heavy-tailed marginals.

1 Introduction

Synthetic equity return paths are an input to many quantitative-finance workflows. Stress-testing a portfolio against plausible but unobserved market scenarios, validating a portfolio optimization algorithm under conditions the historical record does not contain, augmenting limited training sets for machine-learning pipelines, and backtesting an allocator across many independent draws all require synthetic data that behave statistically like real markets in the dimensions the downstream task cares about [1, 2]. Empirical equity excess growth rates exhibit three statistical regularities a faithful generative framework must reproduce together: a heavy-tailed (leptokurtic) marginal distribution, negligible linear autocorrelation of raw returns, and persistent volatility clustering, in which large changes are followed by large changes of either sign and small changes by small changes [3–5]. These regularities, called *stylized facts*, are the benchmark for synthetic financial data.

Two gaps in the literature leave practitioners without a drop-in solution. The first is the single-asset stylized-facts gap. Existing generative approaches each excel at one of the three regularities and miss others. Generalized autoregressive conditional heteroscedasticity (GARCH) models [6, 7] capture conditional variance dynamics but do not represent discrete regimes; stochastic-volatility and jump-diffusion models [8, 9] enrich tail behavior but lack volatility persistence after jumps; deep generative models [10–14] can learn complex distributions but struggle to reproduce volatility clustering [5]. Hidden Markov models (HMMs) offer a probabilistic regime-switching structure [15], yet standard HMMs revert too quickly to central regimes after extreme events and fail to dwell in high-volatility tail states long enough to reproduce the empirical volatility-clustering profile [16, 17]. The second gap is the multi-asset factor-structure gap. A per-asset generator that reproduces single-asset stylized facts on a given equity says nothing about how that equity should co-move with the market index or with other equities on the same day. The standard recipe for adding such cross-sectional structure is a linear factor model, either Sharpe’s one-factor single-index model (SIM) [18] or a multi-factor variant such as Ross’s arbitrage pricing theory [19] or the Fama-French construction [20]. Applied naively to a per-asset full-return generator, however, the SIM recipe inflates the marginal variance of the composed series quadratically in the factor loading, defeating the purpose of fitting a heavy-tailed generator in the first place. The opposite failure mode, drawing the residual from a Gaussian with variance taken from the real ordinary least squares fit, recovers the SIM coefficients exactly but erases the marginal structure entirely. Neither naive option satisfies both the stylized-facts requirement and the factor-structure requirement at once.

This paper closes both gaps with a two-stage construction. We first introduce a hybrid hidden Markov framework (Section 3.1) that discretizes continuous excess growth rates into Laplace quantile-defined states and augments regime switching with a two-parameter Poisson jump-duration mechanism. The Laplace partition lets us bypass the iterative Baum-Welch algorithm [21, 22] via direct frequentist counting of regime transitions, scaling the framework to a 424-asset pipeline. The Poisson override forces the chain to dwell in high-volatility tail states for empirically realistic durations, closing the volatility-clustering gap that standard HMMs leave open. We then introduce a variance-corrected single-index composition (Section 3.2) that takes the per-asset hybrid HMM marginal as input and rescales it by a closed-form scalar so the composed series inherits the generator’s marginal variance while recovering the calibrated factor loading. A sign-preserving clip handles high-leverage assets where the market loading would otherwise exceed the generator variance, and a separate R^2 -driven branch handles index-tracking assets where the calibrated coefficient of determination, rather than the generator marginal, is the quantity worth preserving. Branch selection is driven entirely by the calibrated R^2 , and each asset carries a persisted construction flag (hybrid, hybrid-clipped, r2-preserve) so downstream consumers can audit which path each asset took. The same construction generalizes to multi-factor variants without changes to its structure.

We validated both stages on a 424-ticker US equity and ETF universe calibrated against the 2014–2024 SPY history, with 2025 held out for out-of-sample evaluation. The single-asset stage was assessed against six baselines (Bootstrap, Gaussian, Laplace, GARCH, HMM without jumps, and a Gated Recurrent Unit [23] neural baseline) on Kolmogorov-Smirnov, Anderson-Darling, Wasserstein-1, and Hellinger pass rates (Section 4). The multi-asset stage was assessed against five composers (the naive composition, a Gaussian single-index residual, a JumpHMM fit directly to OLS residuals, a Politis-Romano stationary bootstrap of the real residual history [24], and a per-ticker GARCH(1,1)- t fit [7]) on factor-loading recovery, marginal fidelity, and a per-ticker one-day Value-at-Risk backtest assessed by the Kupiec unconditional-coverage test. Section 5 closes with a documented downstream-

use caveat, an iid-residual diversification-return artifact under daily rebalancing, and a calibrated location-shift bias correction that addresses it without restructuring the generator.

2 Related Work

Synthesizing equity returns that match real markets has been an active problem since the recognition that the Black-Scholes-Merton geometric Brownian motion baseline [25] fails on every empirical regularity that matters for risk and pricing. Mandelbrot [3] demonstrated that speculative price changes exhibit heavy tails (*leptokurtosis*) far beyond Gaussian predictions; Fama [26] reviewed evidence that raw returns display negligible linear autocorrelation; Schwert [27] and others later documented persistent *volatility clustering*, in which the autocorrelation of absolute returns decays slowly. Engle [6] and Bollerslev [7] introduced ARCH and GARCH conditional-variance models that addressed volatility clustering but produced light-tailed marginals unless paired with a fat-tailed innovation distribution, and represented neither discrete regimes nor sudden jumps [28]. Stochastic-volatility extensions [29, 8] treat volatility as a latent continuous process at the cost of computationally intensive estimation. Jump-diffusion models [9, 30] inject Poisson-driven discrete events directly into the price process, producing heavy tails by construction; they fit equity markets, where macroeconomic announcements, earnings surprises, and geopolitical events generate large discrete moves [31], but in standard form do not provide a mechanism for post-jump volatility persistence.

Hidden Markov models offer a different solution by embedding regime and jump dynamics in a latent discrete-state process. Hamilton [32] introduced the regime-switching HMM to economics in a two-state expansion-recession formulation, and subsequent work applied the framework to volatility forecasting [33] and equity trading [34, 35]. Rydén, Teräsvirta, and Åsbrink [16] evaluated HMMs against the stylized facts of daily returns and found that Gaussian-emission HMMs with few states reproduced heavy tails and the absence of return autocorrelation but failed to capture volatility clustering, with the absolute-return autocorrelation decaying far too quickly relative to empirical data. Bulla and Bulla [17] showed that hidden semi-Markov models substantially improved volatility-clustering reproduction by allowing realistic persistence in high-volatility states. These approaches typically rely on the Baum-Welch expectation-maximization algorithm [21] for parameter estimation, which requires iterative forward-backward passes and is sensitive to initialization. The hybrid HMM of the present paper sidesteps both limitations: it discretizes returns into quantile-defined regimes via a Laplace cumulative distribution function, which enables direct frequentist counting of transitions without EM, and augments regime switching with a Poisson jump-duration mechanism that forces the chain to dwell in high-volatility tail states for empirically realistic durations.

Deep generative models have been explored as an alternative to parametric and latent-state approaches. Generative adversarial networks and their financial variants [12, 14, 13] can learn complex distributions directly from data, but systematic evaluations have found that naive architectures fail to reproduce volatility clustering even when they match the marginal distribution [12]. Foundation inference models for Markov jump processes [36] offer a pretrained alternative not yet evaluated on financial data. Surveys of synthetic data quality more broadly [1, 2, 5] agree on the same concern: stylized-facts reproduction is the primary quality criterion, and naive generators tend to fail on at least one core stylized fact. The present paper follows the latent-state tradition rather than the deep-generative one, trading architectural complexity for a direct-counting fit augmented by a parameter-light jump override.

The single-index model (SIM) of Sharpe [18] is the standard recipe for adding multi-asset factor structure to an otherwise univariate generator: each asset’s growth rate decomposes into a market-loaded term plus an idiosyncratic residual, reducing the parameter count relative to a full multivariate specification. The construction generalizes to multi-factor variants [19, 20] without changing its essential form. Practitioners typically choose between two SIM-residual specifications: the *full-return* specification fits a per-asset generator to the asset’s full growth-rate history and plugs the draw into the SIM as the residual, while the *residual-fit* specification fits the per-asset generator to the ordinary least squares residual series and composes with no further correction. The full-return path is operationally attractive because it lets a per-asset generator calibrated for distributional interpretability, cached for other purposes, or chosen to retain regime-switching or jump structure enter the factor pipeline unchanged; however, it is well known to inflate the marginal variance of the composed series quadratically in the factor loading, while the residual-fit specification gives up the per-asset generator’s distributional richness. Mixture hidden Markov models [37] address some of

this by sharing latent state across assets, but joint estimation in high dimensions is computationally demanding. Copula-based dependence models [38–40] separate marginal distributions from the dependence structure but introduce model-selection complexity in the copula family. The variance-corrected SIM composition we develop in Section 3.2 threads these constraints: the closed-form scalar correction lets a full-return generator enter the factor pipeline while preserving the marginal variance, and the auditable R^2 -driven branch handles index-tracking edge cases without external metadata.

Validation of synthetic financial data has historically relied on goodness-of-fit tests for distributional fidelity [41–43] and on autocorrelation-based diagnostics for temporal structure [4]. Recent work has emphasized downstream-task validation as a complement: a synthetic dataset that passes distributional tests can still fail when used for the task it was generated to support. Booth and Fama [44] formalized one important downstream concern: a daily-rebalanced allocator on iid-residual paths extracts a structural *diversification return* that is not present under empirical positive residual autocorrelation [45]. We adopt both the classical distributional metrics and a downstream Value-at-Risk backtest assessed by Kupiec coverage, and we explicitly address the diversification-return artifact via a documented bias correction (Section 5).

3 Method

3.1 Hybrid hidden Markov marginal generator

The dataset was 424 United States-listed equities and exchange-traded funds spanning ten years (2014–2024). To validate the hybrid hidden Markov framework on a single representative asset, we focused the headline analysis on the SPDR S&P 500 ETF (SPY), reserving the 2,766 observations from January 3, 2014 to December 31, 2024 for in-sample fitting and the subsequent 249 trading days of 2025 for out-of-sample testing. The data consisted of daily open, high, low, and close prices and volume-weighted average price values. We computed the excess growth rate $G_{i,j}$ for ticker i between time period $j - 1 \rightarrow j$ from the equity price series $P_{i,j}$ as

$$G_{i,j} \equiv \left(\frac{1}{\Delta t} \right) \cdot \ln \left(\frac{P_{i,j}}{P_{i,j-1}} \right) - r_f, \quad (1)$$

with $\Delta t = 1/252$ (one trading day in years) and r_f a constant continuously compounded risk-free rate derived from STRIPS bond yields. The excess growth rate has units of year^{-1} and is time-additive under continuous compounding.

We defined the hybrid hidden Markov model on this dataset as the tuple $\mathcal{M} = (\mathcal{S}, \mathcal{O}, \mathbf{T}, \mathbf{E}, \bar{\pi})$ [15], where the hidden state $S_t \in \mathcal{S} = \{1, \dots, N\}$ represented market regimes, the observation space $\mathcal{O} \subset \mathbb{R}$ consisted of continuous excess growth rate values, $\mathbf{T}$ governed regime-to-regime transitions, $\mathbf{E}$ specified the state-conditional emission model, and $\bar{\pi}$ denoted the stationary distribution. States were defined by quantile boundaries $Q_k = F_L^{-1}(k/N; \mu_L, b_L)$ of a fitted Laplace distribution, with $Q_0 = -\infty$ and $Q_N = +\infty$. The Laplace was chosen for its sharper peak (better matching the concentration of small price movements [3, 4, 46]) and its closed-form quantile function, which scaled to the 424-ticker pipeline without iterative optimization [22]. An observation was assigned to state k when $Q_{k-1} < G_t \leq Q_k$. The within-state emission followed a location-scale Student- t distribution

$$G_t \mid S_t = k \sim \mu_k + \sigma_k \cdot t_\nu, \quad \nu = 5, \quad (2)$$

where $\nu = 5$ was selected from a sensitivity analysis over $\nu \in \{3, 4, 5, 6, 7, 8, 10, 15, 30, \infty\}$ as the value that minimized the kurtosis gap without degrading distributional fidelity ($\nu = \infty$ recovers the Normal baseline).

With the state space and emission family fixed, we estimated the transition matrix $\mathbf{T}$ through direct frequentist counting: the discrete state assignments allowed straightforward counting of observed transitions between regimes, which avoided the initialization sensitivity of expectation-maximization [22]. A consequence of direct counting was that empirical transition matrices often had low probabilities for exiting central states into tail states, which caused models to lose the effect of volatility clustering too quickly [17]. We corrected this by adding two jump parameters, ϵ representing the probability of a jump event and λ representing the mean jump-event duration, along with a tail-state selection rule. Tail states were defined as $\mathcal{S}_- = \{1, \dots, N_{\text{tail}}\}$ and $\mathcal{S}_+ = \{N - N_{\text{tail}} + 1, \dots, N\}$,




Figure 1: **Architecture of the hybrid hidden Markov model with jump-diffusion (HMM-WJ).** At each step the chain transitions according to the empirical transition matrix $\mathbf{T}$ (probability $1 - \epsilon$, thin bidirectional arrows) or enters a Poisson jump episode (probability ϵ , dashed upward arrow to the Poisson clock). During a jump episode the active state is forced to the bottom tail set $\mathcal{S}_-$ (red, lowest-valued states) or the top tail set $\mathcal{S}_+$ (blue, highest-valued states) for $K \sim \text{Poisson}(\lambda)$ consecutive steps before normal Markovian evolution resumes. Small bell curves above each state depict the state-conditional location-scale Student- t ($\nu = 5$) emission distribution. Tail sets are defined as the N_{tail} lowest- and highest-quantile states under the Laplace quantile partition.

where N_{tail} was user-configurable. When a jump was triggered, the jump duration K was sampled from a Poisson distribution $K \sim \text{Poisson}(\lambda)$, which is standard for modeling independent events in fixed intervals [47]. During these K steps, the standard Markovian transitions were overridden to target tail states, with a user-configurable bias p_{neg} (default 0.52) that favored negative-tail states to reproduce gain/loss asymmetry (Figure 1). Given the state assignments and transition matrix, the remaining model components were estimated directly from the data: the emission parameters μ_k and σ_k were the sample mean and standard deviation of observations assigned to state k , and the empirical transition matrix exhibited a dominant near-diagonal band reflecting short-range regime persistence (Online Appendix E). The stationary distribution $\bar{\pi}$ satisfied $\bar{\pi} = \bar{\pi}\mathbf{T}$ and was estimated by matrix powering ($\mathbf{T}^{50}$) [48, 49]. An initial state was drawn from $X_0 \sim \bar{\pi}$; at each subsequent step the chain either transitioned according to the empirical row $\mathbf{T}_{X_{n-1}, \cdot}$ (probability $1 - \epsilon$) or entered a Poisson jump episode (probability ϵ) that forced the state into $\mathcal{S}_-$ or $\mathcal{S}_+$ for K consecutive steps before normal transitions resumed. In both cases an observation was sampled from the emission distribution $O_n \sim \mathbf{E}_{X_n}$. The full simulation pseudocode is given in Online Appendix D.

With the simulator specified, we calibrated the two jump parameters, the jump probability ϵ and mean jump duration λ [9, 30], via a multi-objective grid search that minimized the discrepancy between historical and simulated market signatures. The objective targeted two stylized facts [4, 16]: volatility clustering, measured as the squared error between the observed and simulated autocorrelation function (ACF) of absolute excess growth rates [27] up to a lag of $L = 252$ trading days (approximately one trading year), and leptokurtosis, captured by a penalty term on the global kurtosis [3]:

$$J(\epsilon, \lambda) = \sum_{\tau=1}^L (\text{ACF}_{\text{obs}}(\tau) - \overline{\text{ACF}}_{\text{sim}}(\tau))^2 + w_K (K_{\text{obs}} - \bar{K}_{\text{sim}})^2, \quad (3)$$

where $\text{ACF}_{\text{obs}}(\tau)$ and K_{obs} are the empirical absolute-growth autocorrelation at lag τ and the global kurtosis, respectively, and the simulated counterparts $\overline{\text{ACF}}_{\text{sim}}(\tau)$ and $\bar{K}_{\text{sim}}$ were averaged across 200 independent synthetic paths of 2,766 trading days per grid point [47]. We set the kurtosis-penalty weight to $w_K = 0.20$ to balance tail behavior against the temporal ACF term. The grid explored ϵ from 10^{-4} to 2.5×10^{-2} and λ from 10 to 160. The full pseudocode is given in Online Appendix D.

The hybrid hidden Markov framework above produces a synthetic excess growth-rate path for one asset at a time, with a marginal that reproduces the asset's heavy tails, regime persistence, and volatility-clustering profile (validated empirically below). Multi-asset workflows that consume

these paths (portfolio construction, factor risk attribution, multi-name stress testing) need a second ingredient on top of the per-asset marginals: a cross-sectional structure that ties the synthetic series together so they co-move the way real markets do. The next subsection develops a closed-form composition rule that takes the per-asset hybrid HMM marginal as a black-box input and inserts it into a single-index market factor in a way that preserves the marginal the generator was built to deliver.

3.2 Variance-corrected single-index composition

We work throughout in continuously compounded annualized growth rates, $g(t) = [\log p(t) - \log p(t-1)]/\Delta t$, where $p(t)$ is the closing price on trading day t and Δt is the fraction of a trading year spanned by a single trading day (we use $\Delta t = 1/252$ in the experiments below, so the per-day log return is $g(t) \Delta t$). Working in annualized growth rates rather than raw log returns keeps variances and covariances in the units customary in risk reporting. Growth rates compose linearly under aggregation in time and are the natural unit for variance and covariance arithmetic, which the construction below relies on heavily. All variances and covariances refer to sample moments computed over the relevant time window unless stated otherwise. The method composes a synthetic asset growth-rate path of the form:

$$g_i(t) = \alpha_i + \beta_i g_m(t) + \varepsilon_i(t), \quad t = 1, \dots, T, \quad (4)$$

from an independent generator draw $\tilde{\varepsilon}_i \in \mathbb{R}^T$ and a shared market growth-rate path $g_m \in \mathbb{R}^T$ over T trading days (formally introduced below, with $\tilde{\varepsilon}_i$ assumed independent of g_m and $\mathbb{E}[\tilde{\varepsilon}_i] = 0$) by rescaling the generator draw as $\varepsilon_i = s_i \tilde{\varepsilon}_i$ with a scalar $s_i \in (0, 1]$ chosen to preserve one of two per-asset marginal targets while recovering the calibrated single-index model (SIM) coefficients (α_i, β_i) in the large- T limit.

Formally, we are given a single market growth-rate path $g_m \in \mathbb{R}^T$ over T trading days, with sample mean μ_m and sample variance $\sigma_m^2 = \text{Var}[g_m]$. In our experiments the market path is the SPY total-return growth-rate series; the construction is agnostic to whether g_m is a single-name proxy, a synthetic index, or a model-generated path.

For each of N assets indexed by $i = 1, \dots, N$, we are given a draw $\tilde{\varepsilon}_i \in \mathbb{R}^T$ from a generator that produces growth rates with the target marginal distribution: heavy tails, regime structure, jumps, or whatever the application requires. Write $\sigma_{\text{gen},i}^2 = \text{Var}[\tilde{\varepsilon}_i]$ for the sample variance of the draw. The construction is agnostic to how the generator is fit; in our experiments we use the per-asset hidden Markov model with Student- t emissions and explicit jump components from `JumpHMM.jl` v0.1.0 (commit 9be8099)¹, fit to the asset's own full growth-rate history (not to residuals after market detrending) using the package-default EM tolerance and maximum-iteration cap. Because the generator's variance reflects the full return rather than the idiosyncratic part, the rescaling $\varepsilon_i = s_i \tilde{\varepsilon}_i$ with $s_i^2 = 1 - \beta_i^2 \sigma_m^2 / \sigma_{\text{gen},i}^2$ is exactly what prevents the market term in the SIM composition from double-counting variance that is already carried by $\tilde{\varepsilon}_i$. The generator draws are demeaned, $\mathbb{E}[\tilde{\varepsilon}_i] = 0$, so that the constant term in the SIM is carried entirely by α_i . We assume $\text{Cov}[\tilde{\varepsilon}_i, g_m] \approx 0$ for each i , which holds when the generator and market path are independent draws (the typical use case), and holds after a copula rank reorder when the copula is sampled independently of g_m (verified empirically across the 423-ticker universe in Fig. S1). If the generator already carries non-trivial market correlation, the residual covariance can be subtracted from β_i before applying the correction; we return to this point in the discussion.

For each asset we are given a calibrated triple $(\alpha_i, \beta_i, R_{i,\text{real}}^2)$, estimated by ordinary least squares on the real return history of asset i against the real market path. These are the targets we want the synthetic construction to recover. The intercept α_i and slope β_i are the standard SIM coefficients; $R_{i,\text{real}}^2$ is the real-data coefficient of determination, used by the branch-selection step defined below.

Given these inputs, we want the synthetic composition $g_i = \alpha_i + \beta_i^{\text{eff}} g_m + \varepsilon_i$, with effective slope β_i^{eff} (equal to β_i on the unclipped branch and the attenuated value of Eq. (9) otherwise), to satisfy three properties in the large- T limit. The first is *SIM recovery*: ordinary least squares of g_i on g_m returns the calibrated intercept and slope, $\hat{\alpha}_i = \alpha_i$ and $\hat{\beta}_i = \beta_i^{\text{eff}}$. On the unclipped branch, $\beta_i^{\text{eff}} = \beta_i$ and the OLS output reproduces the calibration exactly; on the clipped branch, β_i^{eff} is the attenuated value defined by Eq. (9), and the attenuation is persisted alongside the output so it

¹<https://github.com/varnerlab/JumpHMM.jl>

is auditable. The second is *marginal fidelity*: each asset is assigned one of two per-asset targets based on its calibrated R^2 , not both at once. Assets whose generator marginal (heavy tails, regime structure, jumps) is the quantity of interest receive the variance-preserving target $\text{Var}[g_i] = \sigma_{\text{gen},i}^2$; assets that track the market closely receive the R^2 -preserving target $R^2 = R_{i,\text{real}}^2$, measured by the same OLS regression as above. The branch chosen for each asset is recorded as a construction flag so downstream consumers can audit which target was pursued. The third is *cross-sectional dependence*: any joint dependence structure applied to the residuals $\{\varepsilon_i\}_{i=1}^N$ passes through unchanged to the composed series $\{g_i\}_{i=1}^N$, automatic given the linearity of Eq. (4) in ε_i . The joint structure itself (empirical copula, factor copula, t-copula) is supplied as a separate design choice, and we report cross-sectional fidelity for the empirical-copula choice in the results below.

The naive composition $g_i = \alpha_i + \beta_i g_m + \tilde{\varepsilon}_i$ satisfies SIM recovery and cross-sectional dependence but violates marginal fidelity: its marginal variance is $\sigma_{\text{gen},i}^2 + \beta_i^2 \sigma_m^2$, an inflation that grows quadratically in β_i . The rest of this section fixes this inflation with a closed-form scalar correction, handles the degenerate high- β case with a sign-preserving clip, treats index-tracking assets through an R^2 -preserving branch, and ties the pieces together in an algorithm that also states the resulting properties of the composed series.

To fix the inflation, form the candidate residual $\varepsilon_i = s_i \tilde{\varepsilon}_i$ for some scalar $s_i \in (0, 1]$, and require that the composed series have the same variance as the generator,

$$\text{Var}[\beta_i g_m + \varepsilon_i] = \sigma_{\text{gen},i}^2. \quad (5)$$

Under the independence assumption $\text{Cov}[\tilde{\varepsilon}_i, g_m] \approx 0$, the cross term in (5) vanishes and

$$\beta_i^2 \sigma_m^2 + s_i^2 \sigma_{\text{gen},i}^2 = \sigma_{\text{gen},i}^2, \quad (6)$$

giving

$$s_i^2 = 1 - \frac{\beta_i^2 \sigma_m^2}{\sigma_{\text{gen},i}^2} \quad (7)$$

Define the *market loading ratio*

$$\rho_i \equiv \frac{\beta_i^2 \sigma_m^2}{\sigma_{\text{gen},i}^2}, \quad (8)$$

the share of the generator variance consumed by the market component. Then $s_i^2 = 1 - \rho_i$, valid whenever $\rho_i < 1$. The naive composition $g_i = \alpha_i + \beta_i g_m + \tilde{\varepsilon}_i$ corresponds to $s_i = 1$ and inflates $\text{Var}[g_i]$ by exactly $\beta_i^2 \sigma_m^2$.

Equation (7) breaks down when $\rho_i \geq 1$: the market loading alone would account for more than the entire generator variance, leaving no room for idiosyncratic noise. This case arises for high- β_i assets paired with low-volatility generators, or whenever the synthetic market g_m is more volatile than the market on which β_i was calibrated.

To handle it, impose a floor $f \in (0, 1)$ on the idiosyncratic share by requiring $s_i^2 \geq f$, and clip β_i downward whenever the floor would be violated. Writing the clip threshold as $\rho_i^{\max} = 1 - f$,

$$\beta_i^{\text{eff}} = \begin{cases} \beta_i & \text{if } \rho_i \leq \rho_i^{\max} \\ \text{sign}(\beta_i) \sqrt{(1-f) \frac{\sigma_{\text{gen},i}^2}{\sigma_m^2}} & \text{if } \rho_i > \rho_i^{\max} \end{cases} \quad s_i^2 = \begin{cases} 1 - \rho_i & \text{if } \rho_i \leq \rho_i^{\max} \\ f & \text{if } \rho_i > \rho_i^{\max} \end{cases} \quad (9)$$

Sign preservation in (9) keeps defensive (negative- β) assets defensive even when clipped. The floor f is a tunable knob; in the experiments below we use $f = 0.10$, which guarantees that at least 10% of each asset's variance comes from idiosyncratic noise. When β_i is clipped we log a warning and persist both β_i and β_i^{eff} so downstream consumers can audit the attenuation.

The variance-preserving construction above targets $\text{Var}[g_i] = \sigma_{\text{gen},i}^2$. That is the right target when the generator marginal carries information one wants to keep. For some assets the generator marginal is not really the quantity of interest; the SIM relationship to the market is. Index ETFs are the standard example. SPY against itself has $\beta = 1$, $R^2 = 1$, $\sigma_\varepsilon = 0$ exactly. QQQ against SPY has $R^2 \approx 0.84$, SPYG against SPY has $R^2 \approx 0.86$. For these tickers we require $\hat{\beta}$ and R^2 to recover their calibrated values, neither inflated to one by dropping ε nor implied by unrelated marginal-variance bookkeeping.

We branch on the real-data calibration $R_{i,\text{real}}^2$. Pick a threshold R_{preserve}^2 that separates index-tracking assets from genuine single stocks; in our universe the cumulative distribution sorts itself cleanly, with index ETFs above 0.80 and the most market-like single names below 0.65 (Fig. 11), so $R_{\text{preserve}}^2 = 0.80$ captures the trackers without sweeping in any genuinely idiosyncratic name. For any asset with $R_{i,\text{real}}^2 \geq R_{\text{preserve}}^2$, the population R^2 identity for (4),

$$R^2 = \frac{\beta_i^2 \sigma_m^2}{\beta_i^2 \sigma_m^2 + \sigma_{\varepsilon,i}^2}, \quad (10)$$

inverts to give the residual variance that hits the calibrated R^2 :

$$\sigma_{\varepsilon,\text{target}}^2 = \beta_i^2 \sigma_m^2 \cdot \frac{1 - R_{i,\text{real}}^2}{R_{i,\text{real}}^2} \quad (11)$$

Draw $\tilde{\varepsilon}_i$ from the ticker's generator and rescale,

$$\varepsilon_i = \sqrt{\frac{\sigma_{\varepsilon,\text{target}}^2}{\sigma_{\text{gen},i}^2}} \tilde{\varepsilon}_i, \quad (12)$$

then copula-reorder and compose as in (4). The construction recovers both calibrated quantities by design: $\hat{\beta} \rightarrow \beta_i$ in the large- T limit because ε_i is uncorrelated with g_m after the rank reorder, and $R^2 \rightarrow R_{i,\text{real}}^2$ by construction.

When $R_{i,\text{real}}^2 = 1$ exactly (SPY against itself), (11) gives $\sigma_{\varepsilon,\text{target}}^2 = 0$, so $\varepsilon_i \equiv 0$ and $g_i = \alpha_i + \beta_i g_m$ deterministically. No special-casing is needed: the SPY identity falls out of the same expression with $\beta = 1$, $\alpha = 0$, $R^2 = 1$. If the rescale factor in (12) exceeds one, the generator's tails are being stretched to fit a target larger than the original draw; this happens when the synthetic market g_m has lower variance than the calibration market. We detect and flag this case so the loss of marginal fidelity is auditable.

The pieces combine into a single procedure (Algorithm 1). For each asset the calibrated $R_{i,\text{real}}^2$ selects a branch: assets with $R_{i,\text{real}}^2 \geq R_{\text{preserve}}^2$ go through the R^2 -preserving construction of Eq. (11), and the rest go through the variance-preserving construction of Eq. (7) with the clip of Eq. (9) engaged when the market loading ratio ρ_i would otherwise exceed $1 - f$. Each asset is tagged with a construction flag `r2-preserve`, `hybrid`, or `hybrid-clipped` that is persisted alongside the output, so downstream consumers can audit which path each asset took. The optional rank reorder in line 14 accepts any joint dependence structure (empirical copula, t-copula, factor copula); reordering preserves the marginal variance of ε_i , so the variance algebra of Eq. (7) is unaffected and whatever cross-sectional structure is applied to ε_i passes through to g_i unchanged.

By construction the composed series g_i satisfies the three preservation criteria above (SIM recovery, marginal fidelity, cross-sectional dependence) in the large- T limit. OLS of g_i on g_m recovers $\hat{\alpha}_i \rightarrow \alpha_i$ and $\hat{\beta}_i \rightarrow \beta_i^{\text{eff}}$, with $\beta_i^{\text{eff}} = \beta_i$ unclipped and β_i^{eff} persisted alongside β_i when the clip triggers. Marginal variance matches $\sigma_{\text{gen},i}^2$ on the variance-preserving branch, either exactly, $\text{Var}[g_i] = \beta_i^2 \sigma_m^2 + s_i^2 \sigma_{\text{gen},i}^2 = \sigma_{\text{gen},i}^2$, or by the choice of β_i^{eff} in (9) under clipping; on the R^2 -preserving branch the marginal variance instead matches $\beta_i^2 \sigma_m^2 / R_{i,\text{real}}^2$, the value implied by the calibrated $(\beta_i, R_{i,\text{real}}^2)$ rather than by the generator marginal. Tail behavior on the variance-preserving branch follows from the floor: because at least $f \sigma_{\text{gen},i}^2$ of the variance is reserved for ε_i , the tails inherited from $\tilde{\varepsilon}_i$ dominate whenever $(\beta_i^{\text{eff}})^2 \sigma_m^2$ is small relative to those tails, while as β_i grows the marginal of g_i tightens toward Gaussian along the market-driven axis, mildly for low- β assets and noticeably at high β . The construction injects *contemporaneous* market dependence only; lagged dependence (lead-lag effects, market-driven volatility clustering) requires a richer construction, which we return to in the discussion. The pipeline (Pipeline.jl, in the released code) is modest in compute: fitting the 423 per-asset JumpHMM marginals runs once offline against the 2014–2024 price histories and is cached, while GARCH(1,1)- t residual paths are simulated per (ticker, replication) at scoring time rather than cached, so each run consumes a fresh draw. The scoring loop across $423 \times 100 = 42,300$ per-ticker replications per composer runs in minutes on a 2023 MacBook Pro (Apple M2 Pro, 16 GB RAM), and the full six-composer sweep reported below completes within an hour on the same hardware.

Algorithm 1 Hybrid SIM composition with variance correction.

Require: Market path $g_m \in \mathbb{R}^T$ with sample variance σ_m^2 ; per-asset generator draws $\tilde{\varepsilon}_i \in \mathbb{R}^T$ for $i = 1, \dots, N$; calibrated SIM parameters $(\alpha_i, \beta_i, R_{i,\text{real}}^2)$; floor $f \in (0, 1)$; threshold $R_{\text{preserve}}^2 \in (0, 1)$.

Ensure: Composed paths $g_i \in \mathbb{R}^T$ and per-asset construction flags.

```
1: for each asset  $i = 1, \dots, N$  do
2:   Compute generator variance  $\sigma_{\text{gen},i}^2 \leftarrow \text{Var}[\tilde{\varepsilon}_i]$ .
3:   if  $R_{i,\text{real}}^2 \geq R_{\text{preserve}}^2$  then
4:      $\sigma_{\varepsilon,\text{target}}^2 \leftarrow \beta_i^2 \sigma_m^2 (1 - R_{i,\text{real}}^2) / R_{i,\text{real}}^2$  {Eq. (11)}
5:      $\varepsilon_i \leftarrow \sqrt{\sigma_{\varepsilon,\text{target}}^2 / \sigma_{\text{gen},i}^2} \tilde{\varepsilon}_i$ 
6:      $\beta_i^{\text{eff}} \leftarrow \beta_i$ ; flag  $\leftarrow$  r2-preserve
7:   else
8:      $\rho_i \leftarrow \beta_i^2 \sigma_m^2 / \sigma_{\text{gen},i}^2$  {Eq. (8)}
9:     if  $\rho_i \leq 1 - f$  then
10:       $s_i^2 \leftarrow 1 - \rho_i$ ;  $\beta_i^{\text{eff}} \leftarrow \beta_i$ ; flag  $\leftarrow$  hybrid
11:    else
12:       $s_i^2 \leftarrow f$ ;  $\beta_i^{\text{eff}} \leftarrow \text{sign}(\beta_i) \sqrt{(1 - f) \sigma_{\text{gen},i}^2 / \sigma_m^2}$ ; flag  $\leftarrow$  hybrid-clipped
13:    end if
14:     $\varepsilon_i \leftarrow s_i \tilde{\varepsilon}_i$ 
15:  end if
16:  (Optional) apply cross-sectional rank reorder to  $\varepsilon_i$ .
17:   $g_i \leftarrow \alpha_i + \beta_i^{\text{eff}} g_m + \varepsilon_i$  {Eq. (4)}
18: end for
```

4 Results

We validated the two-stage construction in two passes. The first pass asked whether the hybrid hidden Markov framework reproduced single-asset stylized facts on real SPY data, in-sample and out-of-sample, against six baseline generators. The second pass asked whether the variance-corrected single-index composer preserved those validated marginals when combined with a market factor across a 424-ticker universe, against five alternative composers, and whether the resulting paths supported a downstream Value-at-Risk backtest at industry-standard coverage levels. Descriptive statistics confirmed that all three stylized facts were present in both the in-sample (2014–2024, $T = 2,766$) and out-of-sample (2025, $T = 249$) windows (Table 4): excess kurtosis of 7.7 (IS) and 6.9 (OoS) with Jarque-Bera rejection ($p < 0.001$), persistent volatility clustering (Ljung-Box on $|G_t|$ rejected, $p < 0.001$), and near-zero linear autocorrelation in raw returns [26].

With the stylized facts confirmed in both evaluation windows, we calibrated the jump mechanism. A multi-objective grid search over $\epsilon \in [10^{-4}, 2.5 \times 10^{-2}]$ and $\lambda \in [10, 160]$, with 200 simulated paths per grid point, identified the optimal values $\epsilon^* = 10^{-4}$ and $\lambda^* = 100$ (Online Appendix D). The optimal $\lambda^* = 100$ was an interior point of the grid, confirming that the mean jump duration was identifiable from data; $\epsilon^* = 10^{-4}$ fell at the lower boundary of the ϵ grid, indicating that the data consistently preferred rarer tail-entry events over the range explored. At these optimal values, the ACF of $|G_t|$ closely tracked the observed SPY ACF across lags 1–252, confirming that the jump mechanism partially reproduced the empirical ARCH effect. The primary analysis used $N = 100$ states, but a sensitivity study over $N \in \{30, 60, 90, 100, 150, 200\}$ confirmed robustness: KS and AD pass rates remained stable for both HMM-NJ (without jumps) and HMM-WJ (with jumps) across this range, with every state receiving adequate statistical support (Online Appendix F). At $N = 350$, certain states were never visited in the historical record, establishing a practical upper bound on state resolution.

With the model calibrated, we benchmarked HMM-WJ against seven alternative generators on 1,000 synthetic paths of 2,766 trading days each (Table 1, Figure 2). Bootstrap resampling set the non-parametric ceiling (100% KS, 100% coverage), while the Gaussian i.i.d. baseline (0% KS) confirmed that thin-tailed models were inadequate. Between these anchors, every model excelled on one quality dimension but failed on another. The GARCH(1,1) baseline achieved the best temporal

fidelity (ACF-MAE 0.031) but a poor distributional fit (5.5% KS), indicating a systematic shape mismatch despite its volatility clustering properties. The Gated Recurrent Unit (GRU) [23] closed 83% of the ACF-MAE gap but produced a 0.6% KS pass rate. The hidden semi-Markov model (HSMM) [17] occupied a middle ground (82% KS) but its coarse 8-state partition could not capture the full growth-rate distribution, as reflected by a 38% kurtosis gap and only 68.7% quantile coverage. No single model captured both quality dimensions. Both HMM variants achieved the highest distributional fidelity among all parametric models, with HMM-WJ’s pass rates 2–8 percentage points below HMM-NJ’s, a cost of the jump mechanism occasionally overweighting tail states. The Student- t ($\nu = 5$) emissions closely matched the observed kurtosis (within 1.3% for HMM-WJ), a substantial improvement over Normal emissions which underestimated kurtosis by approximately 29%. Negative skewness (-0.75 observed) was also well reproduced by both HMM variants, arising from the asymmetric state-occupancy distribution inherited from the Laplace partition rather than any explicit skewness parameter; symmetric-innovation models (GARCH, Gaussian, Laplace) all produced near-zero skewness by construction. On the temporal dimension, HMM-NJ scored 0.059 on ACF-MAE, closing only 3% of the gap between the i.i.d. floor (0.060) and the GARCH ceiling (0.031); HMM-WJ scored 0.052, closing 28% of the gap and the only non-GARCH non-neural model to reduce ACF-MAE meaningfully below the i.i.d. floor, because approximately 24% of HMM-WJ paths contained at least one Poisson jump event that sustained $\text{ACF}(|G_t|)$ decay across all lags while the remaining 76% behaved identically to HMM-NJ. Out-of-sample on the held-out 249 trading days of 2025 the same ranking held (Table 1, Figure 6): HMM-NJ achieved 96.7% KS and HMM-WJ achieved 94.4% KS, with simulated kurtosis of 6.4 and 6.1 against an observed 6.9, and HMM-WJ remained the only model to improve meaningfully on both dimensions simultaneously. GARCH’s W_1 deteriorated by 67% from in-sample to out-of-sample, exposing a tail misspecification that binary pass rates obscured. Cross-asset generalization to NVDA, JNJ, and JPM confirmed that the jump mechanism automatically adapted its duration λ^* to each asset’s clustering intensity (Online Appendix G).

Having validated the per-asset marginals on single-asset stylized facts in both windows, we turned to the multi-asset composition pipeline and asked whether those validated marginals plugged into a multi-asset construction without breaking either target. We evaluated six composers on a fixed set of per-asset JumpHMM marginals calibrated against the real SPY growth-rate path. This isolated the effect of the composition rule from the effect of market-path randomness: all composers consumed the same real SPY history and the same per-ticker innovation draw, so metric differences across composers reflected the composition rule alone. The ticker universe was a 424-asset US equity/ETF set drawn from Polygon.io daily-close histories, filtered to tickers with a complete in-sample trading history matching the reference length of AAPL ($T = 2,767$ daily closes covering January 2014 through December 2024); filtering on the common length preserved 424 tickers, of which the SPY total-return growth-rate series was taken as the market path g_m and the remaining 423 tickers as non-market assets. For each non-market ticker i we fitted a JumpHMM marginal to the asset’s own growth-rate history, using the default configuration ($N = 100$ Laplace-partition states, Student- t emissions with $\nu = 5$, annualized growth rates via `excess_growth_rates`, risk-free rate $r_f = 0$, $\Delta t = 1/252$); jump parameters (ϵ, λ) were left at the package defaults rather than tuned per ticker, which would improve per-ticker marginal fit but was not required for a comparison that tests the effect of the composition rule on top of whatever marginal the generator produces. For each non-market ticker we then ran ordinary least squares of the asset’s growth-rate history on g_m , yielding the calibrated quadruple $(\alpha_i, \beta_i, R_{i,\text{real}}^2, \sigma_{\epsilon,\text{real},i})$. The universe spanned $\beta \in [0.01, 1.79]$ with median $\beta = 1.00$ and quartiles $(0.81, 1.00, 1.18)$, with $R_{i,\text{real}}^2$ ranging from 0.001 to 0.933 (Fig. 11).

The composition rules used a *paired innovation* protocol where applicable: for each non-market ticker and each replication $r \in \{1, \dots, R\}$ we drew a single innovation path $\tilde{\epsilon}_i^{(r)}$ of length T from the ticker’s JumpHMM marginal, and the same $\tilde{\epsilon}_i^{(r)}$ was passed to the naive, Gaussian-residual-SIM, and hybrid composers, so that differences among those three reflected the composition rule and not generator stochasticity. The *Naive* composer set $g_i^{(r)} = \alpha_i + \beta_i g_m + \tilde{\epsilon}_i^{(r)}$ with no variance correction. The *Gaussian SIM* baseline replaced the JumpHMM draw with $g_i^{(r)} = \alpha_i + \beta_i g_m + \sigma_{\epsilon,\text{real},i} \xi_i^{(r)}$, $\xi_i^{(r)} \sim \mathcal{N}(0, I_T)$ drawn fresh per replication, recovering the calibrated R^2 exactly but discarding any marginal structure carried by $\tilde{\epsilon}$. The *Hybrid* composer applied Algorithm 1 with floor $f = 0.10$ and threshold $R_{\text{preserve}}^2 = 0.80$. Three further composers drew their innovations from dedicated residual generators, each fit to the real OLS residual series $e_i(t) = G_i(t) - \alpha_i - \beta_i G_m(t)$: the *JumpHMM*-

on-residuals composer fitted a fresh JumpHMM marginal to e_i via a pseudo-price inversion and composed $g_i^{(r)} = \alpha_i + \beta_i g_m + \tilde{\varepsilon}_{\text{resid},i}^{(r)}$ with no variance correction; the *Block bootstrap* composer drew a Politis–Romano stationary bootstrap replicate [24] of the empirical residual series with mean block length $\sqrt{T} \approx 50$ and composed analogously; the *GARCH(1,1)-t* composer fitted a conditional-variance model per ticker [7] and substituted a simulated residual path, with 30 of the 423 tickers yielding a non-stationary fit ($\alpha + \beta \geq 1$ at the optimizer’s termination) and excluded from that composer only. Across all composers, we skipped the optional cross-sectional rank reorder in Algorithm 1 so that per-ticker metrics reflected the marginal construction in isolation; cross-sectional dependence under copula-based reorder is treated separately and is outside the scope of the per-ticker evaluation reported here. For every composed series we computed three metric families against the ticker’s real growth-rate history and the real SPY path: SIM recovery reported $(\hat{\alpha}_i, \hat{\beta}_i, \hat{R}_i^2)$ from OLS of $g_i^{(r)}$ on g_m along with the absolute deviations $|\hat{\beta} - \beta|$ and $|\hat{R}^2 - R_{\text{real}}^2|$; marginal fidelity was assessed by Kolmogorov–Smirnov (KS) and Anderson–Darling (AD) two-sample p -values against the real marginal, Wasserstein-1 distance W_1 , excess kurtosis κ , and the classical Hill tail-index estimator $\hat{\xi} = (k-1)^{-1} \sum_{i=1}^{k-1} \log(X_{(i)}/X_{(k)})$ on the upper 5% order statistics of $|g_i^{(r)}|$, so reported Hill values are tail indices with $\hat{\xi} \approx 1/\alpha$ for a Pareto-tailed distribution with shape α ; variance preservation was the ratio $\text{Var}(g_i^{(r)})/\sigma_{\text{gen},i}^2$, using the real-data variance as a proxy for the generator’s targeted variance. Pass rates were reported at $\alpha = 0.05$, and we reported $\bar{R} = 100$ replications per ticker so that aggregate metrics were averages over $423 \times 100 = 42,300$ per-ticker observations per composer; the simulation seed was fixed at 1234.

With the protocol established, we computed per-asset medians of each metric and aggregated across the universe (Table 2). All composers recovered β to within a median absolute error of 0.018 to 0.022, consistent with the identity $\text{Cov}(g, g_m)/\sigma_m^2 \rightarrow \beta_i^{\text{eff}}$ holding at all residual scales. The differences between composers appeared everywhere else. The Gaussian SIM baseline recovered R^2 most tightly (median error 0.008) because it targeted R^2 by construction, but it failed marginal fidelity badly: KS pass rate 0.6%, AD pass rate 0.5%, excess kurtosis 1.4 (real data, ~ 13), Hill tail index 0.22 (versus ~ 0.37 on the generator; Fig. 7). The naive composition retained the generator marginal but inflated its variance by $\beta_i^2 \sigma_m^2$, so its KS and AD pass rates sat at 4.5% and 2.7%. The hybrid composer held both properties at once: KS pass rate 50.4%, AD pass rate 47.6%, kurtosis 7.2, Hill 0.36; the R^2 recovery (0.021) came in tighter than the naive baseline but looser than the Gaussian baseline, reflecting that the variance-preserving branch targeted $\sigma_{\text{gen},i}^2$ rather than $R_{i,\text{real}}^2$. The three residual-fit composers sidestepped the variance-inflation problem entirely by fitting a generator directly to e_i , which by construction has variance $\sigma_{\varepsilon,\text{real},i}^2$ and no double-counted market component; their aggregate KS pass rates were 75.8% (JumpHMM-on-residuals), 73.3% (block bootstrap), and 66.9% (GARCH(1,1)-t), each higher than hybrid’s 50.4% (Fig. 4). The advantage sat in the body of the distribution rather than the tails: hybrid’s median excess kurtosis (7.17) and Hill upper-tail index (0.365) matched JumpHMM-on-residuals (7.26 and 0.365) to within sampling variability, confirming that the variance correction of Eq. (7) preserves the heavy-tailed character of the full-return generator even when the rescaling is applied; block bootstrap and GARCH, by fitting their own residual generators, reproduced the empirical residual series but with slightly lighter tails ($\kappa = 6.68$ and 6.04; Hill 0.330 and 0.318) than either JumpHMM-based recipe. The downstream consequence of the body-fidelity gap was the question a per-ticker one-day Value-at-Risk backtest was designed to answer (Table 3, Fig. 5): at $\alpha = 0.99$ the nominal exceedance rate is 1%; the naive composer under-breached at 0.67% and the Gaussian baseline over-breached at 1.40%, both failing Kupiec unconditional coverage on the majority of the universe (45 and 47% pass rates), while the hybrid, JumpHMM-on-residuals, block bootstrap, and GARCH(1,1)-t composers all hit coverage within one-tenth of a percentage point of nominal (0.95, 0.99, 1.09, and 1.09% respectively), and their Kupiec pass rates clustered between 72 and 86%. Hybrid and JumpHMM-on-residuals were statistically indistinguishable on this test: the 25 percentage-point body-fidelity gap between them did not translate to a Value-at-Risk accuracy difference. Hybrid’s standalone advantage is therefore scoped: it is the right rule when a full-return per-asset generator is the given input, and it delivers tail accuracy on par with a dedicated residual generator without requiring a separate fitting stage.

Having established that body-fidelity did not translate into VaR accuracy, we traced where the KS advantage over the naive baseline came from. We plotted per-ticker KS pass rate and per-ticker marginal variance ratio $\text{Var}(g)/\sigma_{\text{gen}}^2$ as functions of the calibrated β (Fig. 3). The variance-ratio panel made the mechanism explicit: the naive scatter traced the theoretical curve $1 + \rho_i$ with

$\rho_i = \beta_i^2 \sigma_m^2 / \sigma_{\text{gen},i}^2$, overshooting the generator variance by 50% to 75% at high β , while hybrid and Gaussian SIM sat on the unit line by design. The KS-pass-rate panel showed the consequence: naive fell from a pass rate of ~ 0.25 at $\beta \approx 0.3$ to below 0.01 past $\beta \approx 0.7$, while hybrid sat between 0.3 and 0.9 across the full β range, and Gaussian SIM was pinned to zero throughout because with its Gaussian residual it did not match the heavy-tailed real marginal at any β . The two baselines' failure modes separated on tail metrics as well (Fig. 7): naive and hybrid clustered together near the real-data kurtosis reference line ($\kappa_{\text{real}} \approx 13$), with the difference between them reflecting the variance inflation under naive rather than any difference in tail shape, while Gaussian SIM collapsed to $\kappa \approx 1$ and Hill ≈ 0.22 , pinned below the generator regardless of β . Applying the branch-selection rule of Algorithm 1 to the 423-ticker universe produced 421 assignments to the hybrid branch, 2 to the r2-preserve branch, and no assignments to the hybrid-clipped branch (Fig. 8, Table 5); the two R^2 -preserving tickers were QQQ ($R^2 = 0.861$) and SPYG ($R^2 = 0.933$), both ETFs that track market-capitalization indices closely, and the highest- R^2 individual stock (BLK at $R^2 = 0.645$) sat ~ 0.22 below the $R_{\text{preserve}}^2 = 0.80$ threshold, so the branch assignment was empirically tracker-specific on this universe rather than a threshold artifact. The two trackers' KS pass rate under hybrid composition was 99%, consistent with the R^2 -preserving branch recovering both the calibrated β and the calibrated R^2 by construction. Clipping did not trigger anywhere in the universe: the market loading ratio ρ_i stayed below $1 - f = 0.90$ for every ticker, because the JumpHMM marginals carried enough variance that the market component never crowded out the $f = 0.10$ idiosyncratic floor. Because the R^2 -preserve branch had only two empirical assignments, we validated it on synthetic trackers where the target (β, R^2) was known by construction (Fig. 12): across 15 cells of $(\beta_{\text{true}}, R_{\text{true}}^2) \in \{0.8, 1.0, 1.2\} \times \{0.80, 0.85, 0.90, 0.95, 0.99\}$, the branch selector assigned r2-preserve as intended, recovered median $\hat{\beta}$ to within 0.001 of β_{true} and median $\hat{R}^2$ to within 0.001 of R_{true}^2 , and cleared the $\alpha = 0.05$ KS test on at least 99% of replications per cell. To check whether the preservation advantage held across the β distribution, we bucketed the universe by β quartile and recomputed the aggregate metrics within each bucket (Table 6): the hybrid KS pass rate declined gently from 67% in the low- β quartile to 44% in the high- β quartile, reflecting the caveat noted alongside Algorithm 1 that as $\beta^{\text{eff}^2} \sigma_m^2$ grows toward $(1 - f) \sigma_{\text{gen}}^2$ the market-driven component of g tightens the marginal toward Gaussian along its own axis; the effect was small enough that hybrid still beat both baselines by more than an order of magnitude in every bucket. To probe the clipping branch, which did not trigger anywhere in the main run, we re-ran the hybrid composer on the same universe with the market growth-rate path rescaled by a factor $\gamma \in \{1, 2, 3\}$, holding the calibrated marginals fixed and drawing $R = 100$ replications per (ticker, γ) pair (Fig. 9); at $\gamma = 1$ no ticker crossed the clipping threshold and the hybrid KS pass rate matched the headline value (50.3%), while at $\gamma = 2$ and $\gamma = 3$ the clipping branch activated on 76.4% and 95.2% of tickers respectively, and the hybrid KS pass rate rose to 71.8% and 77.3% above the unclipped baseline because the clipping branch rescales β^{eff} to hold the idiosyncratic floor and prevents the market component from crowding out the marginal. The clipping branch is therefore not a degradation under stress but a mechanism that keeps the composed marginal near the generator target as $\beta^{\text{eff}^2} \sigma_m^2$ inflates.

Finally, we asked whether the headline results were robust to the two hyperparameter choices of Algorithm 1 and to the simulation seed. We re-ran the hybrid composer on the full 423-ticker universe at every point of a 5×5 grid, $R_{\text{preserve}}^2 \in \{0.70, 0.75, 0.80, 0.85, 0.90\}$ and $f \in \{0.05, 0.10, 0.15, 0.20, 0.30\}$ (Fig. 10); hybrid KS pass rate ranged from 50.24% to 50.38% across the 25 cells, a spread of 0.14 percentage points, with the R^2 -preserve assignment stable at QQQ and SPYG for every threshold at or below $R^2 = 0.85$ and the floor f not changing any branch assignment in the grid. The headline number was therefore invariant to the hyperparameter values within wide tolerances, and the operating point ($R_{\text{preserve}}^2 = 0.80$, $f = 0.10$) reflects a principled choice of the R^2 -branch threshold and a standard floor value rather than a data-peaked local optimum. We also quantified the contribution of generator stochasticity to the headline numbers by re-running the full six-composer protocol under 8 random seeds (Table 7). The per-composer KS pass rates held to within fractions of a percentage point: hybrid sat at $50.40 \pm 0.18\%$ across seeds, JumpHMM-on-residuals at $75.61 \pm 0.11\%$, block bootstrap at $73.24 \pm 0.09\%$, GARCH(1,1)- t at $66.96 \pm 0.30\%$, naive at $4.41 \pm 0.07\%$, and Gaussian SIM at $0.60 \pm 0.04\%$. The across-composer differences therefore exceeded the seed-induced spread by roughly two orders of magnitude, and the seed sweep reproduced the relative ordering of the composers without inversions across seeds, confirming that the hybrid-vs-baseline gap and the residual-fit-vs-hybrid body-fidelity gap were not artifacts of the simulation seed.

5 Discussion

In this study, we composed synthetic per-asset growth-rate paths under a single-index model (SIM) by drawing each asset’s innovation from an independent JumpHMM generator fit to the asset’s own full growth-rate history, then rescaling the draw by a closed-form scalar before inserting it into the SIM composition. We evaluated six composers on a calibrated universe of 424 US equities and exchange-traded funds against the real SPY market path: the naive composition, a Gaussian-residual SIM baseline, the hybrid construction proposed here, and three residual-fit alternatives (JumpHMM-on-residuals, Politis–Romano block bootstrap [24], and a per-ticker GARCH(1,1)- t fit [7]). The one-line variance correction, together with the sign-preserving clip rule and the R^2 -preserving branch, closes a gap between two previously incomplete options for building synthetic asset paths with both marginal structure and factor structure: naive composition gives both but distorts the marginal by $\beta^2 \sigma_m^2$, while Gaussian-residual SIM gives the factor exactly but strips the marginal. The hybrid construction sat between the Gaussian-residual and naive baselines: it recovered β to the same precision as either, held the generator marginal to its target variance in every ticker, and preserved the generator’s tails at a level indistinguishable from the naive composition (Fig. 3, Table 2). The three residual-fit composers produced higher Kolmogorov–Smirnov pass rates than hybrid on marginal body fidelity (67 to 76% versus 50%, Table 2), but matched hybrid on the 99% Value-at-Risk coverage test to within statistical tolerance (Table 3); the body-fidelity gap did not translate to a tail-accuracy gap. The contribution of hybrid was therefore scoped to the case where the per-asset generator was specified in full-return units (a common setting, since per-asset generators are often calibrated for distributional interpretability, cached for other pipelines, or chosen to retain regime-switching or jump structure); in that case hybrid delivered 99% VaR accuracy on par with a dedicated residual generator without requiring a separate fitting stage. The variance-inflation gap was large enough to matter in practice: at the high- β end of the universe, naive composition inflated the marginal variance by over 70% relative to the generator target (Fig. 3). Because branch selection was driven entirely by the calibrated R^2 and each asset carried a persisted construction flag, the procedure ran uniformly across the ticker universe without external metadata and left an audit trail that downstream consumers could inspect. No part of the construction is new; the contribution is a minimal, practitioner-ready recipe with an auditable branch flag and an explicit treatment of the tracker limit, usable as a drop-in replacement for naive composition in workflows where both tail shape and market dependence matter.

The evaluation isolated the composition rule by fixing the market path at the real SPY history and using the same per-ticker innovation draw across all three composers. This design yielded a paired comparison of composition rules at the per-ticker level but set aside two questions that production users will need to address separately. The first concerns cross-sectional dependence: we skipped the optional rank-reorder step in Algorithm 1 so that per-ticker metrics reflected the composition rule alone. When the reorder is applied, the variance algebra is unchanged (rank-reordering preserves the marginal variance of ε_i), so the marginal results here carry over; cross-sectional fidelity under different copula specifications is a separate evaluation that we defer to follow-up work. The second concerns market-path uncertainty: the metrics reported here used the real SPY path, and under a simulated market path the composed marginal picks up additional variance from the sampling of $g_m^{(r)}$, which for high- R^2 tickers becomes a noticeable effect. In production, the two deferred questions compose: a reorder-plus-simulated-market pipeline would layer cross-sectional structure on top of per-ticker draws built against sampled market paths, with the variance correction of Eq. (7) still providing the per-asset variance target on each realized $g_m^{(r)}$. A separate scope boundary concerns the downstream use case: the main metrics reported here characterize marginal and factor fidelity of the composition rule on per-ticker targets. To test whether that fidelity translates to a consequential downstream number, we also report a per-ticker one-day 95% and 99% Value-at-Risk backtest of the composed paths against the real 2014–2024 growth-rate histories, with exceedance counts assessed by Kupiec’s unconditional coverage test; the per-ticker framing keeps this validation inside the paper’s scope, while portfolio-level VaR requires the cross-sectional copula reorder deferred above. High-turnover portfolio strategies remain a distinct scope boundary: the temporal structure of the residual draw matters in a way that contemporaneous composition does not capture.

A related boundary on the recipe was the clipping rule. Clipping did not trigger anywhere in the US-equity universe used here, because the JumpHMM marginals carried enough variance that $\rho_i = \beta_i^2 \sigma_m^2 / \sigma_{\text{gen},i}^2$ stayed below 0.90 even for the highest- β ticker. Clipping becomes relevant in two settings we did not evaluate: scenario-driven markets, where the synthetic g_m is constructed to be

much more volatile than the calibration market (e.g., stress tests), and universes that mix low-volatility single stocks with extreme betas (e.g., leveraged ETFs). In both settings we recommend reporting the original and effective β_i alongside the output, as in Algorithm 1, so that downstream consumers can audit the attenuation. A related attenuation appeared at the other end of the β spectrum, even when clipping did not trigger: the hybrid KS pass rate fell from 67% at low β to 44% at high β (Table 6), a mild attenuation that followed directly from the composition algebra. As $\beta_i^2 \sigma_m^2$ grows toward the idiosyncratic floor $(1 - f) \sigma_{\text{gen},i}^2$, the market-driven component carries an increasing share of the marginal, and that component is only as heavy-tailed as g_m . The market’s own heavy tails slow the attenuation (SPY growth rates are themselves heavy-tailed after JumpHMM fitting), but the effect is visible. Users who need exact marginal fidelity at high β can recover it by lowering the floor f (at the cost of less conservative clipping behavior) or by pre-scaling the generator variance so that ρ_i stays small.

The variance correction $s_i^2 = 1 - \rho_i$ relies on $\text{Cov}(\tilde{\varepsilon}_i, g_m) \approx 0$. The JumpHMM marginals are fit in isolation and sampled independently of the market path, so this holds by construction; if the generator is already correlated with the market (for example, a bootstrap from joint history), the empirical covariance should be subtracted from β_i before applying the correction, or s_i^2 should be estimated directly from the empirical variance of the composed series. The same warning applies to the R^2 -preserving branch, whose variance identity assumes ε is uncorrelated with g_m after any reorder. The construction also injects a contemporaneous market factor only: $g_i(t)$ depends on $g_m(t)$ and on $\tilde{\varepsilon}_i(t)$ but not on $g_m(t-1), g_m(t-2), \dots$, so lagged market dependence (lead-lag effects, market-driven volatility clustering, asymmetric responses to drawdowns) is not reproduced by this recipe. The natural extension is a lagged-factor SIM, $g_i(t) = \alpha_i + \sum_{k=0}^K \beta_{i,k} g_m(t-k) + \varepsilon_i(t)$; the variance correction generalizes to that form by replacing $\beta_i^2 \sigma_m^2$ with the variance of the full market-factor component, though the empirical value of the extra parameters is beyond the scope here. Lagged idiosyncratic dependence is likewise absent: the JumpHMM residuals $\tilde{\varepsilon}_i$ are drawn independently across time, so any residual autocorrelation present in the real data is discarded by the composition. This matters most for workflows that evaluate portfolios rebalancing at high frequency. With iid residuals, a rebalancing rule collects the full diversification return of [44], a compounding premium that scales with residual variance and rebalancing frequency and is largely absent in real markets, where daily residual autocorrelation is small but positive [50]. Two generator alternatives in Table 2 preserve temporal structure directly: the block-bootstrap composer resamples blocks of the empirical OLS residual series [24], inheriting whatever autocorrelation is present in the data, and the GARCH(1,1)- t composer fits a conditional-variance model per ticker [7]. Both recover marginal fidelity at the cost of committing the pipeline to a specific residual generator, whereas the variance correction of Eq. (7) is generator-agnostic and accepts a full-return JumpHMM marginal (with its jump and regime structure) as input. Users evaluating high-turnover strategies on JumpHMM-corrected paths should benchmark absolute return levels against a static-allocation baseline on the same paths, or adopt the bootstrap or GARCH alternatives when residual autocorrelation is the relevant structure for the downstream task.

The diversification-return artifact is quantitatively large enough on standard rebalancing rules that absolute-return claims drawn from JumpHMM-corrected paths require an explicit correction or an explicit caveat. As a concrete demonstration, a 20-asset target-weight allocator deployed against a hybrid-composed 2025 universe (calibration window 2014–2024) produced a median synthetic continuously-compounded growth rate (CCGR) of $\sim 30\%/yr$, while the same allocator deployed against the real 2025 growth-rate history produced $11.5\%/yr$. The decomposition isolated the artifact: equal-weight buy-and-hold on the synthetic ensemble produced $\sim 7.7\%/yr$, the same target-weight allocation held statically (no rebalance) produced $\sim 2.0\%/yr$, and switching the same allocation rule to daily rebalancing produced $\sim 29.7\%/yr$, a $+27.7$ percentage-point jump from the static-to-daily switch on the same allocation rule and the same paths (Online Appendix S2, Table ??). The ~ 22 pp gap between the synthetic and real engine CCGR was therefore a structural feature of the iid-residual generator family rather than a calibration error, consistent with [44, 50, 51].

Two practical responses follow. Where the workflow can tolerate being explicit about the issue, we recommend reporting the static-versus-rebalanced decomposition on the same allocation rule and the same synthetic paths, and framing absolute Sharpe levels under daily rebalancing as “this generator with this strategy” rather than as a forward prediction. Where the workflow requires an absolute-return level for downstream consumption (e.g., percentile diagnostics overlaying real outcomes against a synthetic distribution), we recommend a uniform location-shift bias correction (Eq. S2, Online

Appendix S2) that scales each synthetic wealth path by an exponential drag whose rate is set so the corrected median annualized growth rate matches a documented long-run prior, typically near eight percent per year, decomposable into the prevailing risk-free rate plus an active premium net of frictions [52, 53]. The correction is a per-path monotone transform: it preserves the rank order of paths by terminal wealth, the drawdown shape, and the volatility envelope; only the level shifts. Anchoring to a documented prior rather than to the realized test-year outcome keeps the correction independent of the sample to which the synthetic ensemble is being compared and avoids circular calibration. The realized year then lands inside the corrected ensemble at an honest percentile (in our deployment, real-2025 landed at the 63rd percentile of the corrected ensemble, consistent with 2025 being an above-typical equity year). Online Appendix S2 details the methodology, contrasts the location-shift correction with a multiplicative haircut alternative (which we do not recommend because it scrambles per-path rank order and distorts the drawdown distribution), and discusses why several intuitive alternatives (parameter drift between calibration and deployment, transaction-cost inflation, AR(1) on residuals without restructuring the copula sampling, residual block-bootstrap) do not address the underlying mechanism within the iid-residual SIM framework. The synthetic data remained reliable, both before and after correction, for the ensemble-shape questions the paper validates: percentile structure, drawdown distribution, and relative ranking of strategies on the same paths. The location-shift correction extends that reliability to absolute Sharpe and CCGR levels under daily rebalancing, at the cost of an external prior.

Two further extensions follow naturally. Multi-factor SIM replaces the single market factor with K factors, requiring ρ_i to become the sum of factor contributions and the loading vector to be clipped rather than a scalar, though the branch logic is unchanged. Per-ticker tuning of the jump parameters (ϵ, λ) tightens each marginal’s fit; the multi-asset evaluation used package defaults to keep fitting tractable across the universe, but the per-ticker grid search used for the single-asset evaluation, applied across the universe, would push the hybrid KS pass rates upward at the cost of a calibration step per asset. A stress-test harness ties these together: using the clipping rule to enforce a minimum idiosyncratic share in constructed market scenarios guarantees that per-asset marginals remain heavy-tailed even under synthetic markets much more volatile than history, which is precisely the regime where naive SIM composition breaks down most severely.

6 Conclusion

We presented a two-stage construction for synthetic equity path generation that closes two gaps in the literature: a hybrid hidden Markov framework that reproduces single-asset stylized facts via a Laplace quantile partition and a Poisson jump-duration override, and a closed-form variance-corrected single-index composer that places those validated marginals in a multi-asset factor structure without inflating the marginal variance. The construction is generator-agnostic on the composition side, in the sense that any per-asset full-return generator can plug into the variance correction and inherit the marginal it was built to deliver. Each composed asset carries an audit trail (hybrid, hybrid-clipped, r2-preserve) so downstream consumers can inspect the path selected per ticker without external metadata.

On the empirical side, the hybrid HMM marginals passed the Kolmogorov-Smirnov test against the real SPY univariate distribution at 97.6% in-sample and 94.4% out-of-sample, outperforming Bootstrap, Gaussian, Laplace, GARCH, hidden semi-Markov, and Gated Recurrent Unit baselines on combined distributional and tail metrics. The variance-corrected single-index composer recovered the factor loading to a median absolute error of 0.018 and matched the leading residual-fit alternatives on a per-ticker one-day 99% Value-at-Risk backtest, validating the composed paths against the real 2014–2024 growth-rate histories. We documented one downstream caveat: an iid-residual diversification-return artifact under daily rebalancing that inflates absolute return levels by roughly 22 percentage points on a deployed 20-asset target-weight allocator. A uniform location-shift bias correction anchored to a documented long-run prior addresses the artifact as a per-path monotone transform that preserves rank order, drawdown shape, and volatility envelope while shifting only the level.

Several extensions follow naturally from the present work. The variance correction generalizes to multi-factor and lagged-factor single-index models without changing its essential algebra; we leave the empirical evaluation of these extensions to follow-up work. Per-ticker tuning of the jump parameters (ϵ, λ) would push the hybrid composer’s marginal-fidelity pass rates upward at the cost of

a calibration step per asset. The diversification-return artifact admits a structural fix via autoregressive or block-bootstrap residuals composed with the single-index factor; that fix requires restructuring the copula sampling step and is the most consequential follow-up for high-turnover downstream workflows.

Acknowledgments

The authors thank the eCornell AI in Finance program participants for discussions that motivated the downstream-use bias-correction analysis, and Polygon.io for access to the 2014 to 2024 US equity and ETF daily price histories used in the experiments. Computations were run on a single laptop; no shared-resource allocation was required.

Author contributions. A.A. designed the hybrid hidden Markov marginal generator, performed the single-asset experiments and validation framework, and contributed to the manuscript. J.D.V. designed the variance-corrected single-index composition, performed the multi-asset experiments and downstream Value-at-Risk validation, developed the bias-correction methodology, released the code, and contributed to the manuscript.

Competing interests. The authors declare no competing interests.

Code and data availability. All source code, experiment scripts, and fitted per-asset marginals are released as part of JumpHMM.jl (<https://github.com/varnerlab/JumpHMM.jl>); the paper-specific evaluation harness (six-composer benchmark, Value-at-Risk backtest, bias-correction utility) lives in the `paper/` subdirectory of that repository.

References

- [1] Samuel A. Assefa, Danial Dervovic, Mahmoud Mahfouz, Robert E. Tillman, Prashant Reddy, and Manuela Veloso. Generating synthetic data in finance: Opportunities, challenges and pitfalls. In *Proceedings of the First ACM International Conference on AI in Finance*, pages 1–8, 2020. doi: 10.1145/3383455.3422554.
- [2] James Jordon, Lukasz Szpruch, Florimond Houssiau, Mirko Bottarelli, Giovanni Cherubin, Carsten Maple, Samuel N. Cohen, and Adrian Weller. Synthetic data: What, why and how? *arXiv preprint arXiv:2205.03257*, 2022.
- [3] Benoit Mandelbrot. The variation of certain speculative prices. *The Journal of Business*, 36(4): 394–419, 1963.
- [4] R. Cont. Empirical properties of asset returns: Stylized facts and statistical issues. *Quantitative Finance*, 1(2):223–236, 2001. doi: 10.1080/713665670.
- [5] Michael Stenger, André Bauer, Thomas Prantl, Robert Leppich, Nathaniel Hudson, Kyle Chard, Ian Foster, and Samuel Kounev. Thinking in categories: A survey on assessing the quality for time series synthesis. *Journal of Data and Information Quality*, 16(2):1–32, 2024. doi: 10.1145/3666006.
- [6] Robert F. Engle. Autoregressive conditional heteroscedasticity with estimates of the variance of United Kingdom inflation. *Econometrica*, 50(4):987–1007, 1982.
- [7] Tim Bollerslev. Generalized autoregressive conditional heteroskedasticity. *Journal of Econometrics*, 31(3):307–327, 1986. doi: 10.1016/0304-4076(86)90063-1.
- [8] Steven L. Heston. A closed-form solution for options with stochastic volatility with applications to bond and currency options. *The Review of Financial Studies*, 6(2):327–343, 1993. doi: 10.1093/rfs/6.2.327.
- [9] Robert C. Merton. Option pricing when underlying stock returns are discontinuous. *Journal of Financial Economics*, 3(1-2):125–144, 1976. doi: 10.1016/0304-405X(76)90022-2.

- [10] Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural Computation*, 9(8):1735–1780, 1997. doi: 10.1162/neco.1997.9.8.1735.
- [11] Thomas Fischer and Christopher Krauss. Deep learning with long short-term memory networks for financial market predictions. *European Journal of Operational Research*, 270(2):654–669, 2018. doi: 10.1016/j.ejor.2017.11.054.
- [12] Shuntaro Takahashi, Yu Chen, and Kumiko Tanaka-Ishii. Modeling financial time-series with generative adversarial networks. *Physica A: Statistical Mechanics and Its Applications*, 527:121261, 2019. doi: 10.1016/j.physa.2019.121261.
- [13] Sohyeon Kwon and Yongjae Lee. Can GANs learn the stylized facts of financial time series? In *Proceedings of the 5th ACM International Conference on AI in Finance*, pages 126–133, 2024. doi: 10.1145/3677052.3698661.
- [14] Jinsung Yoon, Daniel Jarrett, and Mihaela van der Schaar. Time-series generative adversarial networks. In *Advances in Neural Information Processing Systems*, volume 32, 2019.
- [15] L. Rabiner and B. Juang. An introduction to hidden Markov models. *IEEE ASSP Magazine*, 3(1):4–16, 1986. doi: 10.1109/MASSP.1986.1165342.
- [16] Tobias Rydén, Timo Teräsvirta, and Stefan Åsbrink. Stylized facts of daily return series and the hidden Markov model. *Journal of Applied Econometrics*, 13(3):217–244, 1998. doi: 10.1002/(SICI)1099-1255(199805/06)13:3<217::AID-JAE476>3.0.CO;2-V.
- [17] Jan Bulla and Ingo Bulla. Stylized facts of financial time series and hidden semi-Markov models. *Computational Statistics & Data Analysis*, 51(4):2192–2209, 2006. doi: 10.1016/j.csda.2006.07.021.
- [18] William F. Sharpe. A simplified model for portfolio analysis. *Management Science*, 9(2):277–293, 1963. doi: 10.1287/mnsc.9.2.277.
- [19] Stephen A. Ross. The arbitrage theory of capital asset pricing. *Journal of Economic Theory*, 13(3):341–360, 1976. doi: 10.1016/0022-0531(76)90046-6.
- [20] Eugene F. Fama and Kenneth R. French. Common risk factors in the returns on stocks and bonds. *Journal of Financial Economics*, 33(1):3–56, 1993. doi: 10.1016/0304-405X(93)90023-5.
- [21] Leonard E. Baum, Ted Petrie, George Soules, and Norman Weiss. A maximization technique occurring in the statistical analysis of probabilistic functions of Markov chains. *The Annals of Mathematical Statistics*, 41(1):164–171, 1970. doi: 10.1214/aoms/1177697196.
- [22] Jeff A. Bilmes. A gentle tutorial of the EM algorithm and its application to parameter estimation for Gaussian mixture and hidden Markov models. Technical Report TR-97-021, International Computer Science Institute, 1998.
- [23] Kyunghyun Cho, Bart van Merriënboer, Caglar Gulcehre, Dzmitry Bahdanau, Fethi Bougares, Holger Schwenk, and Yoshua Bengio. Learning phrase representations using RNN encoder-decoder for statistical machine translation. *arXiv preprint arXiv:1406.1078*, 2014.
- [24] Dimitris N. Politis and Joseph P. Romano. The stationary bootstrap. *Journal of the American Statistical Association*, 89(428):1303–1313, 1994. doi: 10.1080/01621459.1994.10476870.
- [25] Fischer Black and Myron Scholes. The pricing of options and corporate liabilities. *Journal of Political Economy*, 81(3):637–654, 1973. doi: 10.1086/260062.
- [26] Eugene F. Fama. Efficient capital markets: A review of theory and empirical work. *The Journal of Finance*, 25(2):383–417, 1970. doi: 10.2307/2325486.
- [27] G. William Schwert. Why does stock market volatility change over time? *The Journal of Finance*, 44(5):1115–1153, 1989. doi: 10.1111/j.1540-6261.1989.tb02647.x.
- [28] Francis X. Diebold and Atsushi Inoue. Long memory and regime switching. *Journal of Econometrics*, 105(1–2):131–159, 2001. doi: 10.1016/S0304-4076(01)00073-2.

- [29] Elias M. Stein and Jeremy C. Stein. Stock price distributions with stochastic volatility: An analytic approach. *The Review of Financial Studies*, 4(4):727–752, 1991.
- [30] S. G. Kou. A jump-diffusion model for option pricing. *Management Science*, 48(8):1086–1101, 2002. doi: 10.1287/mnsc.48.8.1086.166.
- [31] Jay F. K. Au Yeung, Zi-kai Wei, Kit Yan Chan, Henry Y. K. Lau, and Ka-Fai Cedric Yiu. Jump detection in financial time series using machine learning algorithms. *Soft Computing*, 24(3): 1789–1801, 2020. doi: 10.1007/s00500-019-04006-2.
- [32] James D. Hamilton. A new approach to the economic analysis of nonstationary time series and the business cycle. *Econometrica*, 57(2):357–384, 1989. doi: 10.2307/1912559.
- [33] Alessandro Rossi and Giampiero M. Gallo. Volatility estimation via hidden Markov models. *Journal of Empirical Finance*, 13(2):203–230, 2006. doi: 10.1016/j.jempfin.2005.09.003.
- [34] Nguyet Nguyen. Hidden Markov model for stock trading. *International Journal of Financial Studies*, 6(2):36, 2018. doi: 10.3390/ijfs6020036.
- [35] Chang-Jin Kim and Charles R. Nelson. Has the U.S. economy become more stable? A Bayesian approach based on a Markov-switching model of the business cycle. *The Review of Economics and Statistics*, 81(4):608–616, 1999. doi: 10.1162/003465399558472.
- [36] David Berghaus, Kostadin Cvejovski, Patrick Seifner, César Ojeda, and Ramsés J. Sanchez. Foundation inference models for Markov jump processes. In *Proceedings of the 38th International Conference on Neural Information Processing Systems*, pages 129407–129442, 2024.
- [37] José G. Dias, Jeroen K. Vermunt, and Sofia Ramos. Mixture hidden Markov models in finance research. In *Advances in Data Analysis, Data Handling and Business Intelligence*, pages 451–459. Springer, 2009. doi: 10.1007/978-3-642-01044-6_41.
- [38] Paul Embrechts, Alexander J. McNeil, and Daniel Straumann. Correlation and dependence in risk management: Properties and pitfalls. In *Risk Management: Value at Risk and Beyond*, pages 176–223. Cambridge University Press, 2002. doi: 10.1017/CBO9780511615337.008.
- [39] Umberto Cherubini, Elisa Luciano, and Walter Vecchiato. *Copula Methods in Finance*. John Wiley & Sons, 2004. ISBN 9780470863459.
- [40] Kjersti Aas, Claudia Czado, Arnoldo Frigessi, and Henrik Bakken. Pair-copula constructions of multiple dependence. *Insurance: Mathematics and Economics*, 44(2):182–198, 2009.
- [41] A. N. Kolmogorov. Sulla determinazione empirica di una legge di distribuzione. *Giornale dell’Istituto Italiano degli Attuari*, 4:83–91, 1933.
- [42] N. Smirnov. Table for estimating the goodness of fit of empirical distributions. *The Annals of Mathematical Statistics*, 19(2):279–281, 1948.
- [43] Theodore W. Anderson and Donald A. Darling. Asymptotic theory of certain “goodness of fit” criteria based on stochastic processes. *The Annals of Mathematical Statistics*, 23(2):193–212, 1952.
- [44] David G. Booth and Eugene F. Fama. Diversification returns and asset contributions. *Financial Analysts Journal*, 48(3):26–32, 1992. doi: 10.2469/faj.v48.n3.26.
- [45] Andrew W. Lo and A. Craig MacKinlay. When are contrarian profits due to stock market overreaction? *Review of Financial Studies*, 3(2):175–205, 1990. doi: 10.1093/rfs/3.2.175.
- [46] Samuel Kotz, Tomasz J. Kozubowski, and Krzysztof Podgórski. *The Laplace Distribution and Generalizations: A Revisit with Applications to Communications, Economics, Engineering, and Finance*. Birkhauser, 2001. ISBN 9780817641665.
- [47] Paul Glasserman. *Monte Carlo Methods in Financial Engineering*. Springer, 2003. doi: 10.1007/978-0-387-21617-1.

- [48] James D. Hamilton. Regime switching models. *The New Palgrave Dictionary of Economics*, pages 11421–11426, 2018. doi: 10.1057/978-1-349-95189-5_2459.
- [49] Charles M. Grinstead and J. Laurie Snell. *Introduction to Probability*. American Mathematical Society, 1997.
- [50] Paul Bouchev, Duncan Gunthorp, and Matt Sutherland. Volatility harvesting in theory and practice. *Journal of Wealth Management*, 15(2):89–100, 2012.
- [51] Harry M. Markowitz. Investment for the long run: New evidence for an old rule. *Journal of Finance*, 31(5):1273–1286, 1976. doi: 10.1111/j.1540-6261.1976.tb03213.x.
- [52] Aswath Damodaran. Equity risk premiums: Determinants, estimation and implications. NYU Stern School of Business working paper, updated annually, 2025. <https://pages.stern.nyu.edu/~adamodar/>.
- [53] Roger G. Ibbotson and Duff and Phelps. *SBBI Yearbook: Stocks, Bonds, Bills, and Inflation*. Duff and Phelps / Kroll, annual edition, 2024.

Table 1: **In-sample and out-of-sample model comparison for SPY** (1,000 simulated paths, significance level $\alpha = 0.05$). Bootstrap: i.i.d. resample of training data. Gaussian/Laplace: i.i.d. draws from MLE-fitted distributions. GARCH: GARCH(1,1) estimated by quasi-maximum likelihood. GRU: 2-layer gated recurrent unit [23] with Gaussian output head. HSMM: hidden semi-Markov model with $K = 8$ Laplace quantile states, negative-binomial dwell times, and Student- t ($\nu = 5$) emissions [17]. HMM-NJ: hidden Markov model ($N = 100$ states) without jumps. HMM-WJ: hybrid model with Poisson jump-duration extension. ACF-MAE: mean absolute error of the ACF of $|G_t|$ over lags 1–252. Wasserstein-1 and Hellinger distance defined in Online Appendix C. Coverage: fraction of 99 empirical quantiles (1st–99th) falling within the [5th, 95th] percentile envelope of the corresponding synthetic quantiles. Standard errors in parentheses: binomial SE for pass rates, $\text{std}/\sqrt{n}$ for kurtosis, Wasserstein-1, and Hellinger; bootstrap SE ($B = 500$) for ACF-MAE and coverage. Best value per row in bold.

Metric	Bootstrap	Gaussian	Laplace	GARCH(1,1)	GRU	HSMM	HMM-NJ	HMM-WJ
<i>In-sample: 2,766 trading days (2014–2024)</i>								
KS pass rate (%) $\uparrow$	100.0 (<0.1)	0.0 (<0.1)	44.0 (1.6)	5.5 (0.7)	0.6 (0.2)	82.0 (1.2)	99.7 (0.2)	97.6 (0.5)
AD pass rate (%) $\uparrow$	99.7 (0.2)	0.0 (<0.1)	43.3 (1.6)	1.9 (0.4)	0.2 (0.1)	42.5 (1.6)	99.1 (0.3)	91.3 (0.9)
Excess kurtosis (observed)				7.715				
Excess kurtosis (simulated) $\approx$	7.6 (0.08)	−0.0 (<0.01)	3.0 (0.02)	8.2 (0.37)	5.7 (0.16)	4.8 (0.08)	8.1 (0.14)	7.6 (0.14)
ACF-MAE $\downarrow$	0.060 (<0.001)	0.060 (<0.001)	0.060 (<0.001)	0.031 (0.001)	0.036 (<0.001)	0.059 (<0.001)	0.059 (<0.001)	0.052 (<0.001)
Coverage (%) $\uparrow$	100.0 (<0.1)	13.1 (0.1)	37.4 (1.5)	29.3 (1.4)	17.2 (0.5)	68.7 (1.1)	100.0 (<0.1)	100.0 (<0.1)
Wasserstein-1 $\downarrow$	0.062 (0.001)	0.399 (0.001)	0.138 (0.001)	0.304 (0.006)	0.421 (0.003)	0.176 (0.001)	0.081 (0.001)	0.101 (0.001)
Hellinger dist $\downarrow$	0.042 (<0.001)	0.148 (<0.001)	0.072 (<0.001)	0.100 (0.001)	0.134 (0.001)	0.113 (<0.001)	0.073 (<0.001)	0.075 (<0.001)
<i>Out-of-sample: 249 trading days (2025)</i>								
KS pass rate (%) $\uparrow$	97.4 (0.5)	62.2 (1.5)	88.0 (1.0)	80.3 (1.3)	71.8 (1.4)	96.2 (0.6)	96.7 (0.6)	94.4 (0.7)
AD pass rate (%) $\uparrow$	98.5 (0.4)	46.3 (1.6)	92.9 (0.8)	72.0 (1.4)	44.8 (1.6)	96.7 (0.6)	96.7 (0.6)	95.1 (0.7)
Excess kurtosis (observed)				6.867				
Excess kurtosis (simulated) $\approx$	6.0 (0.18)	−0.0 (<0.01)	2.7 (0.05)	1.6 (0.07)	2.9 (0.10)	4.1 (0.13)	6.4 (0.22)	6.1 (0.13)
ACF-MAE $\downarrow$	0.043 (<0.001)	0.043 (<0.001)	0.043 (<0.001)	0.026 (<0.001)	0.033 (<0.001)	0.042 (<0.001)	0.041 (<0.001)	0.039 (<0.001)
Coverage (%) $\uparrow$	100.0 (<0.1)	36.4 (1.9)	74.7 (1.0)	96.0 (1.3)	77.8 (2.9)	100.0 (0.2)	100.0 (<0.1)	100.0 (<0.1)
Wasserstein-1 $\downarrow$	0.232 (0.002)	0.452 (0.002)	0.263 (0.002)	0.507 (0.018)	0.488 (0.005)	0.287 (0.002)	0.258 (0.002)	0.282 (0.006)
Hellinger dist $\downarrow$	0.205 (0.001)	0.235 (0.001)	0.211 (0.001)	0.232 (0.001)	0.240 (0.001)	0.239 (0.001)	0.207 (0.001)	0.210 (0.001)
Parameters estimated	0	2	2	3	37,954	18	2	4




Figure 2: **Head-to-head in-sample model comparison for SPY** ($N = 100$, 1,000 simulated paths). *Panel (a)*: marginal density of excess growth rates with in-sample KS pass rates annotated. GARCH(1,1) fails the two-sample KS test on 95% of paths, indicating a systematic shape mismatch with the empirical distribution; both HMM variants pass at rates $\geq 97\%$. *Panel (b)*: autocorrelation function of $|G_t|$ at lags 1–252 (shaded bands: 10th–90th percentile across paths). HMM-NJ is structurally incapable of producing persistent volatility clustering; HMM-WJ generates a mixture of two path families, approximately 76% behaving like HMM-NJ and the remaining $\sim 24\%$ containing at least one Poisson jump that sustains ACF($|G_t|$) decay across all lags. *Panel (c)*: tail Q-Q plot at the 0.1st–99.9th percentile region; HMM-WJ provides the closest mean quantile match in the extreme tails.

Table 2: **Aggregate scorecard across 423 non-market tickers and 100 replications per ticker.**

Median values per composer. $|\hat{\beta} - \beta|$ and $|\hat{R}^2 - R_{\text{real}}^2|$: absolute deviation between OLS recovery and calibration. KS pass and AD pass: fraction of replications whose two-sample test against the real marginal exceeds $p = 0.05$. W_1 : Wasserstein-1 distance to the real marginal. κ : sample excess kurtosis. Hill: tail-index estimate on the upper 5% of $|g|$. All three composers recover β to the same precision; only the hybrid composer preserves the marginal distribution (KS pass 50.4%) while holding the variance close to the generator target.

Composer	$ \hat{\beta} - \beta $	$ \hat{R}^2 - R_{\text{real}}^2 $	KS pass (%)	AD pass (%)	W_1	κ	Hill
Naive	0.022	0.087	4.5	2.7	0.710	7.767	0.369
Gaussian SIM	0.017	0.008	0.6	0.5	0.682	1.427	0.217
Hybrid	0.018	0.021	50.4	47.6	0.272	7.165	0.365
JumpHMM-on-residuals	0.018	0.015	75.8	70.7	0.232	7.262	0.365
Block bootstrap	0.017	0.020	73.3	66.8	0.232	6.675	0.330
GARCH(1,1)- t	0.017	0.036	67.4	61.4	0.267	6.069	0.317




Figure 3: **Marginal-distribution preservation and variance preservation vs calibrated β .** Each point is a per-ticker median over 100 replications. *Left*: Kolmogorov–Smirnov pass rate against the real marginal at $\alpha = 0.05$. The hybrid composer (orange) maintains a pass rate between ~ 0.3 and ~ 0.9 across the full β range; the naive composer (blue) collapses past $\beta \approx 0.7$ as the market loading inflates the marginal variance; the Gaussian SIM baseline (purple) is pinned at zero throughout. *Right*: variance ratio $\text{Var}(g)/\sigma_{\text{gen}}^2$. The dotted curve is the theoretical naive inflation $1 + \rho$ evaluated at the universe-median σ_{gen}^2 ; the naive scatter follows it. Hybrid and Gaussian SIM sit on the unit line by design.

Table 3: **Per-ticker one-day Value-at-Risk backtest across the six composers.** For each (ticker, replication) pair we estimate the VaR threshold at coverage level α from the composed path and count exceedances against the real 2014–2024 growth-rate history. *rate*: mean exceedance rate across tickers (nominal: $1 - \alpha$). *Kupiec pass*: fraction of tickers on which the Kupiec unconditional-coverage test p -value exceeds 0.05. Hybrid and JumpHMM-on-residuals are statistically indistinguishable at both coverage levels; both strawman composers (naive, Gaussian SIM) fail coverage on a majority of the universe.

Composer	$\alpha = 0.95$		$\alpha = 0.99$	
	rate (%)	Kupiec pass (%)	rate (%)	Kupiec pass (%)
Naive	3.55	10.4	0.67	45.2
Gaussian SIM	4.06	42.6	1.40	47.0
Hybrid	4.75	80.4	0.95	79.7
JumpHMM-on-residuals	4.87	84.0	0.99	82.9
Block bootstrap	4.78	76.7	1.09	86.0
GARCH(1,1)- t	4.64	69.0	1.09	72.1




Figure 4: **Six-composer comparison on aggregate marginal fidelity and tail index.** *Left:* per-ticker Kolmogorov–Smirnov pass rate at $\alpha = 0.05$, aggregated across 423 tickers and 100 replications per ticker. The three residual-fit composers (JumpHMM-on-residuals, block bootstrap, GARCH(1,1)- t) dominate the hybrid on marginal body fidelity; both strawman composers collapse. *Right:* median Hill tail index on the upper 5% of $|g|$. Hybrid, JumpHMM-on-residuals, and naive cluster at ~ 0.37 , reflecting the shared full-return JumpHMM generator’s tail character; block bootstrap and GARCH sit slightly lower at 0.33–0.32; Gaussian SIM collapses to 0.22.




Figure 5: **99% Value-at-Risk exceedance rates and Kupiec coverage across the six composers.** *Left:* mean exceedance rate across tickers (nominal 1%, dashed line); error bars are one SD across tickers. Hybrid, JumpHMM-on-residuals, block bootstrap, and GARCH(1,1)- t all hit coverage within 0.1pp of nominal; naive under-breaches (inflated variance in the composed marginal) and Gaussian over-breaches (thin tails). *Right:* fraction of tickers on which the Kupiec unconditional-coverage test p -value exceeds 0.05. Hybrid and JumpHMM-on-residuals are statistically indistinguishable (80 and 83%); the strawman composers fail on the majority of the universe.

A Empirical cross-term diagnostic

The variance correction of Eq. (7) rests on the assumption $\text{Cov}[\tilde{\varepsilon}_i, g_m] \approx 0$, which is what allows the derivation to drop the cross-term in the expansion of $\text{Var}[g_i]$. Because the per-asset JumpHMM marginals are fit to each asset’s full growth-rate history, including its market-correlated component, the assumption is not automatic: a generator that picked up a residual market loading would invalidate the closed-form scaling. We tested the assumption empirically by sampling $R = 100$ innovation paths $\tilde{\varepsilon}_i^{(r)}$ per ticker from each generator and computing the normalized cross-covariance against the real SPY path:

$$\text{cov}_i^{\text{norm}} = \frac{1}{R} \sum_{r=1}^R \frac{\text{Cov}[\tilde{\varepsilon}_i^{(r)}, g_m]}{\sigma_{\tilde{\varepsilon},i} \sigma_m}. \quad (\text{S1})$$

Per-ticker values were plotted as histograms in Fig. S1. Across the 423 tickers, the full-return JumpHMM generator (`jumpmhm_full`, used by hybrid and naive) sat within ± 0.006 of zero with a per-ticker mean bias of 1.5×10^{-4} (Fig. S1); the residual-fit JumpHMM generator (`jumpmhm_residual`, used by JumpHMM-on-residuals) and the Gaussian baseline were also centered at zero (mean 7×10^{-5} and 2.3×10^{-4} respectively, Fig. S1). The independence assumption was therefore satisfied to within sampling tolerance for all three generators, and the derivation of Eq. (7) held in practice.

B Bias correction for daily-rebalanced backtests

S2.1 The diversification-return artifact under iid SIM residuals

S2.2 Empirical demonstration on a 20-asset deployed allocator

S2.3 Location-shift bias correction

The location-shift correction multiplies each path- p wealth trajectory $W_{p,t}$ at integer step t by a uniform exponential drag whose rate b closes the gap between the engine’s median annualized growth rate and an external long-run prior $\text{CCGR}^{\text{prior}}$:

$$W_{p,t}^{\text{corr}} = W_{p,t} \cdot \exp\left(-\frac{b}{100} \cdot t \Delta t\right), \quad b = \text{median}_p \text{CCGR}_p - \text{CCGR}^{\text{prior}}, \quad (\text{S2})$$

with Δt the integration step in years. The transform is monotone in $W_{p,t}$ for every path and every step, so per-path rank order on terminal wealth, drawdown geometry, and the volatility envelope are all preserved; only the level shifts.

S2.4 Why alternatives don’t work (or have worse trade-offs)

S2.5 Validation and downstream-use guidance

S2.6 Reproducibility

C Validation metric definitions

The four distributional metrics reported in the single-asset evaluation were defined as follows. The two-sample Kolmogorov-Smirnov statistic between the empirical CDFs of the observed and simulated growth-rate samples (G_{obs} of length n and G_{sim} of length m) is $D = \sup_x |F_n(x) - F_m(x)|$ [41, 42]; the test rejects when D exceeds the critical value at level $\alpha = 0.05$. The Anderson-Darling statistic places greater weight on the tails via the integral $A^2 = nm/(n+m) \int [F_n(x) - F_m(x)]^2 / [F(x)(1 - F(x))] dF(x)$, where F is the pooled empirical CDF [43]. The Wasserstein-1 distance between two empirical distributions of equal length is the average of sorted-quantile differences:

$$W_1 = \frac{1}{n} \sum_{i=1}^n |G_{\text{obs}}^{(i)} - G_{\text{sim}}^{(i)}|, \quad (\text{S3})$$

Table 4: **Descriptive statistics and stylized-facts tests for SPY daily excess growth rates.** In-sample: 2014–2024 ($T = 2,766$); out-of-sample: 2025 ($T = 249$). Gaussian and Laplace columns show maximum likelihood estimation (MLE) fits to the in-sample data. JB: Jarque-Bera normality test. LB: Ljung-Box autocorrelation test at lag 20. * denotes rejection at $\alpha = 0.05$.

Statistic	IS Observed	OoS Observed	Gaussian	Laplace
Mean (annualized, %)	6.31	11.60	6.31	14.19
Std Dev (annualized, %)	214.50	220.62	214.46	205.93
Skewness	−0.753	−1.093	0	0
Excess Kurtosis	7.715	6.867	0	3
JB normality test	reject* ($p < 0.001$)	reject* ($p < 0.001$)	n/a	n/a
LB test on G_t (lag 20)	reject* ($p < 0.001$)	reject* ($p = 0.019$)	n/a	n/a
LB test on $ G_t $ (lag 20)	reject* ($p < 0.001$)	reject* ($p < 0.001$)	n/a	n/a




Figure 6: **Statistical validation of HMM-WJ** ($N = 100$, $\alpha = 0.05$). Panels (a) and (d) condition on the $\sim 24\%$ of in-sample paths containing jump events. (a) In-sample KS p -values for 239 jump paths (pass rate 93.7%). (b) Out-of-sample KS p -values for all 1,000 paths (pass rate 95.4%). (c) Out-of-sample density fan chart; the observed density falls within the simulation envelope. (d) In-sample ACF of $|G_t|$ for jump paths; the mean closely tracks the observed ACF.

Table 5: **Hybrid composer broken out by construction flag.** N_{tickers} : number of tickers assigned to each branch by the $R^2_{\text{preserve}} = 0.80$ threshold. The hybrid-clipped branch does not trigger anywhere in the universe ($\rho_i < 0.90$ for all tickers) and is omitted. The two trackers in the r2-preserve branch (QQQ and SPYG) attain a KS pass rate of 99%, consistent with the branch recovering both β and R^2 by construction.

Branch	N_{tickers}	$ \hat{\beta} - \beta $	$ \hat{R}^2 - R^2_{\text{real}} $	KS pass (%)	W_1	κ
hybrid	421	0.018	0.021	50.1	0.273	7.142
r2-preserve	2	0.005	0.001	99.0	0.109	11.525

Table 6: **Aggregate metrics by β quartile, across composers.** Quartile cutoffs are computed from the calibrated β distribution across the 423-ticker universe. The hybrid KS pass rate declines gently from 67% in Q1 to 44% in Q4 as the market loading ratio ρ_i grows, consistent with the tail-attenuation caveat noted alongside Algorithm 1; naive collapses from 16% to under 1% over the same range.

β bucket	Composer	$ \hat{\beta} - \beta $	KS pass (%)	W_1	κ	$\text{Var}(g)$
Q1 (low β)	Naive	0.018	15.7	0.414	8.971	18.1
	Gaussian SIM	0.015	0.0	0.620	0.622	14.0
	Hybrid	0.016	67.3	0.200	8.369	14.6
	JumpHMM-on-residuals	0.015	73.2	0.204	7.059	14.3
	Block bootstrap	0.015	71.3	0.208	6.286	13.9
	GARCH(1,1)- t	0.015	57.8	0.253	5.255	13.4
Q2	Naive	0.021	0.9	0.632	7.510	25.1
	Gaussian SIM	0.016	0.2	0.653	1.509	18.0
	Hybrid	0.017	45.9	0.254	6.889	19.0
	JumpHMM-on-residuals	0.017	82.7	0.200	7.799	18.7
	Block bootstrap	0.016	79.8	0.197	7.213	18.0
	GARCH(1,1)- t	0.015	76.4	0.227	6.470	17.8
Q3	Naive	0.023	0.4	0.802	7.390	33.3
	Gaussian SIM	0.017	1.4	0.688	1.947	23.4
	Hybrid	0.018	44.6	0.297	6.904	24.4
	JumpHMM-on-residuals	0.018	78.3	0.242	7.454	24.0
	Block bootstrap	0.017	75.0	0.236	6.888	22.8
	GARCH(1,1)- t	0.016	71.0	0.263	6.265	21.9
Q4 (high β)	Naive	0.029	0.8	0.976	7.233	51.2
	Gaussian SIM	0.022	0.6	0.825	2.054	36.3
	Hybrid	0.022	43.7	0.363	6.739	37.1
	JumpHMM-on-residuals	0.022	69.1	0.313	6.842	37.0
	Block bootstrap	0.021	67.2	0.311	6.334	35.3
	GARCH(1,1)- t	0.021	64.5	0.361	6.064	34.7

Table 7: **Seed-uncertainty summary across 8 random seeds.** Each cell reports mean $\pm$ SD across the 8 seeds in $\{1234, 2345, 3456, 4567, 5678, 6789, 7890, 8910\}$, with each seed running the full 423-ticker $\times$ 100-replication protocol. Conditional-variance paths for GARCH(1,1)- t are re-simulated at scoring time so its seed SD is informative. The between-composer differences in KS pass rate exceed the seed-induced SD by roughly two orders of magnitude (hybrid SD 0.18 pp vs 25 pp gap to JumpHMM-on-residuals).

Composer	$ \hat{\beta} - \beta $	$ \hat{R}^2 - R_{\text{real}}^2 $	KS pass (%)	AD pass (%)	κ	Hill
Naive	0.022 $\pm$ 0.000	0.088 $\pm$ 0.000	4.41 $\pm$ 0.07	2.71 $\pm$ 0.02	7.746 $\pm$ 0.015	0.369 $\pm$ 0.000
Gaussian SIM	0.017 $\pm$ 0.000	0.008 $\pm$ 0.000	0.60 $\pm$ 0.04	0.50 $\pm$ 0.01	1.428 $\pm$ 0.005	0.217 $\pm$ 0.000
Hybrid	0.018 $\pm$ 0.000	0.021 $\pm$ 0.000	50.40 $\pm$ 0.18	47.50 $\pm$ 0.19	7.150 $\pm$ 0.011	0.364 $\pm$ 0.000
JumpHMM-on-residuals	0.018 $\pm$ 0.000	0.015 $\pm$ 0.000	75.61 $\pm$ 0.11	70.51 $\pm$ 0.12	7.250 $\pm$ 0.013	0.365 $\pm$ 0.000
Block bootstrap	0.017 $\pm$ 0.000	0.020 $\pm$ 0.000	73.24 $\pm$ 0.09	66.79 $\pm$ 0.11	6.676 $\pm$ 0.011	0.330 $\pm$ 0.000
GARCH(1,1)- t	0.017 $\pm$ 0.000	0.036 $\pm$ 0.000	66.96 $\pm$ 0.30	61.00 $\pm$ 0.26	6.072 $\pm$ 0.022	0.318 $\pm$ 0.000




Figure 7: **Heavy-tail preservation: excess kurtosis and Hill tail index vs calibrated β .** Each point is a per-ticker median over 100 replications. *Left:* excess kurtosis, y -axis clipped to $[-2, 20]$ for readability. The dashed line marks the median real-data excess kurtosis across the universe ($\kappa_{\text{real}} \approx 13$); the hybrid and naive composers (orange and blue) track the generator's kurtosis, while Gaussian SIM collapses to $\kappa \approx 1$. *Right:* Hill tail-index estimator on the upper 5% of $|g|$. The hybrid and naive medians sit near 0.37 throughout the β range; Gaussian SIM drops to ~ 0.22 , indicating the shift toward a thinner-tailed distribution. The hybrid's median sitting below κ_{real} reflects the JumpHMM marginal's own kurtosis rather than a composition-rule distortion; the panel's point is that hybrid tracks naive (inheriting generator tails) while Gaussian SIM does not.




Figure 8: **Construction-flag assignment in calibrated $(\beta, R^2_{\text{real}})$ space.** The $R^2_{\text{preserve}} = 0.80$ threshold (dashed line) separates tracker assets from genuine single stocks. In this universe, only QQQ and SPYG exceed the threshold, and both are assigned to the r^2 -preserve branch. The remaining 421 tickers populate the hybrid (variance-preserving) branch; the hybrid-clipped branch is unused because the market loading ratio $\rho_i = \beta_i^2 \sigma_m^2 / \sigma_{\text{gen},i}^2$ stays below 0.90 for every ticker.




Figure 9: **Clipping-branch behavior under market-variance stress.** Hybrid composer re-run with the SPY growth-rate path rescaled by $\gamma \in \{1, 2, 3\}$, holding the calibrated marginals fixed. *Left:* hybrid KS pass rate at $\alpha = 0.05$ rises from the baseline 50.3% at $\gamma = 1$ to 71.8% and 77.3% at $\gamma = 2$ and $\gamma = 3$, because the clipping branch rescales β^{eff} to hold the idiosyncratic floor and prevents the market component from crowding out the generator’s marginal. *Right:* fraction of tickers for which the clipping branch activated ($\rho_i > 1 - f = 0.90$). No ticker triggered clipping in the main run; doubling σ_m pushed 76% of the universe past the threshold, and $3\times$ pushed 95%. The branch is a robustness mechanism, not a degradation mode.




Figure 10: **Hybrid KS pass rate across a 5×5 hyperparameter grid.** Columns index the R^2 -preserve threshold $R^2_{\text{preserve}} \in \{0.70, 0.75, 0.80, 0.85, 0.90\}$; rows index the idiosyncratic floor $f \in \{0.05, 0.10, 0.15, 0.20, 0.30\}$. Hybrid KS pass rate varies from 50.24% to 50.38% across the 25 cells, a spread of 0.14 percentage points. The operating point (0.80, 0.10) used throughout the paper is indistinguishable from every other grid point within sampling noise, indicating that the headline result is not a data-peaked local optimum.




Figure 11: **Calibrated R^2 distribution across the 423 non-SPY tickers.** Histogram of OLS R^2 against SPY over the 2014–2024 window. The two tickers crossing the $R^2_{\text{preserve}} = 0.80$ threshold (dashed line) are index ETFs (QQQ, SPYG); the highest- R^2 individual stock (BLK, 0.645) sits a structural ~ 0.22 below the threshold. The r^2 -preserve branch’s $n = 2$ occupancy is therefore a property of the single-factor SIM on S&P 500 names against SPY, not a sample-size artifact or a data-peaked threshold.




Figure 12: **R^2 -preserve branch validated on synthetic trackers.** For each $(\beta_{\text{true}}, R^2_{\text{true}})$ with $\beta_{\text{true}} \in \{0.8, 1.0, 1.2\}$ and $R^2_{\text{true}} \in \{0.80, 0.85, 0.90, 0.95, 0.99\}$, a synthetic tracker was constructed from $\sigma_{\varepsilon, \text{true}}^2 = \beta_{\text{true}}^2 \sigma_m^2 (1 - R^2_{\text{true}}) / R^2_{\text{true}}$ and composed via Algorithm 1 at 100 replications. *Left:* recovered $\hat{R}^2$ against target R^2 , grouped by β_{true} ; the identity line is dashed. *Right:* recovered $\hat{\beta}$ against target R^2 . Across all 15 cells the branch recovered median $\hat{\beta}$ to within 0.001 of β_{true} , median $\hat{R}^2$ to within 0.001 of R^2_{true} , and cleared the $\alpha = 0.05$ KS test on at least 99% of replications per cell.




Figure S1: **Empirical normalized cross-covariance** $\text{Cov}[\tilde{\varepsilon}_i, g_m]/(\sigma_{\tilde{\varepsilon},i} \sigma_m)$ **across the 423-ticker universe.** Histograms were stacked per generator, with each per-ticker value averaged over $R = 100$ innovation draws. The full-return JumpHMM, residual-fit JumpHMM, and Gaussian generators all clustered at zero, validating the independence assumption used to derive Eq. (7).

with $G^{(i)}$ the i th order statistic. The Hellinger distance between two density estimates p and q on a common bin grid is

$$H(p, q) = \frac{1}{\sqrt{2}} \left\| \sqrt{p} - \sqrt{q} \right\|_2 \in [0, 1], \quad (\text{S4})$$

with $H = 0$ for identical densities and $H = 1$ for disjoint supports.

D HMM-WJ simulator and grid-search pseudocode

The hybrid hidden Markov simulator described in the main text proceeded as follows. Given fitted parameters $(\mathbf{T}, \mathbf{E}, \bar{\pi}, \epsilon, \lambda, p_{\text{neg}}, N_{\text{tail}})$ and a horizon T :

1. Draw $X_0 \sim \bar{\pi}$.
2. For $n = 1, \dots, T$: with probability $1 - \epsilon$, draw $X_n \sim \mathbf{T}_{X_{n-1}, :}$; with probability ϵ , sample $K \sim \text{Poisson}(\lambda)$, and for the next $\min(K, T - n)$ steps force $X_n \sim \text{Uniform}(\mathcal{S}_-)$ with probability p_{neg} or $X_n \sim \text{Uniform}(\mathcal{S}_+)$ with probability $1 - p_{\text{neg}}$.
3. For each X_n , sample $O_n \sim \mu_{X_n} + \sigma_{X_n} \cdot t_5$.

The grid-search procedure for (ϵ, λ) minimized Eq. (3) via brute-force evaluation over $\{\epsilon_1, \dots, \epsilon_K\} \times \{\lambda_1, \dots, \lambda_L\}$, with 200 independent simulated paths per grid point and the objective averaged over the path ensemble. The implementation lives in the released JumpHMM.jl library at <https://github.com/varnerlab/JumpHMM.jl>.

E Transition matrix internals and partition diagnostics

The fitted SPY transition matrix exhibited a dominant near-diagonal band reflecting short-range regime persistence: row-sum entropy peaked at the central states, and most off-diagonal mass was concentrated within ± 5 states of the diagonal. Tail-state exit probabilities were systematically lower than central-state exit probabilities by roughly an order of magnitude, which is what caused the volatility clustering loss flagged by Bulla and Bulla [17] and which the Poisson jump override addressed by re-injecting tail-state mass independently of the empirical transition kernel. Quantile-bin occupancy was approximately uniform over the in-sample window ($N = 100$), consistent with the Laplace fit's calibration to the empirical CDF; the residual sample-size variation across bins was smaller than the within-bin emission variance, so all 100 states received adequate statistical

support. The full transition matrix and partition-occupancy histograms are available in the released `JumpHMM.jl/paper/` subdirectory.

F State-resolution sensitivity

We swept the partition resolution over $N \in \{30, 60, 90, 100, 150, 200, 350\}$ and re-evaluated the in-sample KS and AD pass rates for HMM-NJ and HMM-WJ. Pass rates were flat across $N \in \{60, \dots, 200\}$ with sub-percent variation, indicating that the model was insensitive to partition resolution in this range. At $N = 30$ both models lost approximately 5 percentage points on the AD test, reflecting the coarser quantile bins’ reduced ability to track tail behavior. At $N = 350$ several quantile bins were never visited in the historical record, leaving the corresponding emission parameters undefined; this set the practical upper bound on N for the SPY in-sample window. We adopted $N = 100$ as the operating point for all subsequent experiments.

G Cross-asset generalization

To verify that the hybrid HMM framework generalized beyond SPY, we re-ran the full fit-and-validate pipeline on three single-stock tickers chosen to span sector and volatility regimes: NVDA (semiconductors, high volatility), JNJ (consumer staples, low volatility), and JPM (financials, moderate volatility). Per-ticker grid-search optimal (ϵ^*, λ^*) adapted to each asset’s empirical clustering intensity, with λ^* ranging from 80 (NVDA) to 130 (JNJ); the ϵ^* stayed at the lower boundary 10^{-4} for all three, consistent with the SPY result. In-sample KS pass rates for HMM-WJ were 96.0% (NVDA), 98.2% (JNJ), and 97.4% (JPM), and out-of-sample pass rates were 92.8%, 94.1%, and 93.5%, respectively. The Pareto-frontier property of HMM-WJ on combined distributional and temporal fidelity held on all three tickers.