# GAMING BASED AI STUDY PLANNER

**Varnika V**
Department of Computer Science and Engineering
Rajalakshmi Engineering College
Chennai, India
varnika.v.2024.cse@rajalakshmi.edu.in

**Thendral V**
Department of Computer Science and Engineering
Rajalakshmi Engineering College
Chennai, India
thendral.v.2024.cse@rajalakshmi.edu.in

***Abstract*—During electrical power grid outages, residential households encounter critical operational bottlenecks bounded by finite battery reserves and inverter peak wattage thresholds. Operating multiple appliances concurrently triggers inverter overload trips or prematurely drains battery reserves. This paper presents an intelligent household backup energy scheduling system based on Simulated Annealing (SA), a foundational local search optimization algorithm. The scheduling problem is formulated as a discrete 2D binary matrix search across discrete time intervals. A multi-objective fitness function integrates priority-weighted utility rewards, essential appliance runtimes, and strict quadratic barrier penalties for inverter and battery violations. Five stochastic neighborhood operators explore the combinatorial state space of 2^48 candidate configurations without relying on external mathematical programming solvers. The proposed system is validated through end-to-end simulations on a representative household testbench, demonstrating 100% satisfaction of essential appliances, zero inverter trips (maintaining peak demand at 985 W beneath a 1000 W inverter ceiling), and 1817.5 Wh energy consumption within a 2100 Wh available budget. We benchmark the algorithm against naive unconstrained and greedy baseline schedulers, conduct sensitivity analysis across cooling decay parameters, and document defect remediation through 36 automated regression tests. The system is deployed with a high-performance FastAPI REST backend and an interactive web dashboard.**

***Index Terms*—Simulated Annealing, local search, home energy management, smart inverter, battery storage, combinatorial optimization.**

## I. INTRODUCTION

Residential electricity supply is vulnerable to frequent power outages triggered by grid equipment failures, transmission overloads, and extreme climate events. Modern homes increasingly rely on localized emergency backup architectures, such as battery energy storage systems (BESS), solar-battery inverters, and uninterruptible power supplies (UPS) [1]. However, these backup systems possess rigid physical limitations: the instantaneous power capability of the inverter (Watts) and the finite cumulative energy capacity of the battery bank (Watt-hours) [2].

A critical engineering conflict emerges during prolonged blackouts: simultaneous activation of standard domestic loads frequently exceeds the inverter's peak rating, instantly tripping safety circuit breakers and plunging the residence into blackout (Fig. 1). Conversely, operating appliances in an uncoordinated, ad-hoc sequence drains the battery reserves within the initial hours, leaving life-support equipment, refrigeration, and communication devices without power during the latter stages of the emergency [3].





**Fig. 1.** Rational agent model for household backup energy optimization: the agent coordinates appliance schedules under physical inverter and battery constraints.

Manual scheduling by residents is inherently unviable. Calculating combinatorial switching combinations across several appliances and time intervals requires solving an NP-hard discrete scheduling problem. Moreover, residents cannot dynamically track continuous battery state-of-charge (SoC) decay or anticipate future power demands [4]. An autonomous, intelligent problem-solving agent is therefore imperative.

This paper describes a compact, reproducible, and mathematically rigorous power optimizer that formulates backup energy scheduling as a local search optimization problem solved via Simulated Annealing (SA) [5]. The core contributions of this work are:

(i) A discrete 2D binary matrix formulation modeling appliance operating schedules across discretized outage time slots;
(ii) A 100% hand-crafted Simulated Annealing search engine employing five domain-tailored stochastic neighborhood mutation operators;
(iii) A multi-objective fitness function incorporating quadratic barrier penalties that enforce hard inverter and battery constraints without requiring commercial solvers;
(iv) Rigorous comparative benchmarking against unconstrained and greedy baseline schedulers alongside parametric sensitivity analyses across cooling rates; and

(v) A full-stack software deployment featuring a FastAPI REST API, a responsive web dashboard with Gantt schedule visualization, and 36 automated pytest regression tests.

The remainder of this paper is organized as follows: Section II reviews related literature; Section III presents the mathematical problem formulation; Section IV describes the proposed Simulated Annealing optimization method; Section V outlines the system implementation and defect remediation; Section VI reports experimental results and sensitivity analyses; and Section VII concludes.

## II. RELATED WORK

### *A. Home Energy Management Systems (HEMS)*

Extensive research has focused on Home Energy Management Systems for grid-connected scenarios to minimize electricity tariffs, perform peak shaving, and maximize renewable photovoltaic self-consumption [6], [7]. In grid-tied paradigms, unmet power demands can simply be imported from the utility at monetary expense. Under islanded blackout conditions, however, the grid is entirely unavailable. Constraint violations result in physical inverter tripping and premature energy exhaustion rather than marginal financial penalties, demanding strict constraint satisfaction [8].

### *B. Exact Solvers and Combinatorial Explosion*

Classical exact search algorithms, such as Breadth-First Search (BFS), Depth-First Search (DFS), and Branch-and-Bound, suffer from severe combinatorial explosion when applied to appliance scheduling. For a standard household with N = 6 appliances and M = 8 discrete time intervals, the state space encompasses $2^{(6 \times 8)} = 2^{48} \approx 2.81 \times 10^{14}$ possible binary states [9]. Exhaustive search is mathematically intractable on microcontrollers or embedded edge gateways.

### *C. Local Search and Metaheuristics*

Pure greedy hill-climbing approaches iteratively accept states that improve objective fitness. Nevertheless, the fitness landscape of constrained scheduling is heavily non-convex, characterized by rugged local optima and infeasibility barriers imposed by inverter ceilings [10]. Greedy algorithms routinely become trapped in inferior local peaks. Simulated Annealing overcomes this vulnerability by probabilistically accepting deteriorating candidate moves under the Metropolis criterion, enabling the search to escape local traps before cooling into high-quality solutions [5], [11].

## III. PROBLEM FORMULATION

### *A. System Model and Appliance Profiles*

Let A = {a1, a2, ..., aN} denote the set of N household appliances. Each appliance ai is characterized by its nominal power consumption Pi (Watts), priority tier wi, required operating duration Di (hours), minimum operational bound Dmin,i, maximum bound Dmax,i, preferred time window [tstart,i, tend,i], and binary essential designation Ei ∈ {0, 1}.

The total blackout duration H is discretized into M uniform intervals of duration Δt (hours), such that M = H / Δt. A candidate schedule is represented as a 2D binary matrix $S \in \{0, 1\}^{(N \times M)}$, where:

$$s(i, t) \in \{0, 1\}, \quad \forall i \in \{1, \ldots, N\}, \; t \in \{1, \ldots, M\} \tag{1}$$

where s(i, t) = 1 indicates that appliance ai is operating (ON) in slot t, and s(i, t) = 0 indicates that ai is OFF.

### *B. Physical and Operational Constraints*

The optimizer enforces five essential physical and operational constraints:

1) Peak Inverter Limit: Total active load per slot must not exceed the maximum continuous inverter capacity Pmax:

$$\sum_{i=1}^{N} s(i, t) \cdot P_i \leq P_{max}, \quad \forall t \in \{1, \ldots, M\} \tag{2}$$

2) Battery Storage Capacity: Total energy consumed across all slots cannot exceed available battery energy E_avail:

$$\sum_{t=1}^{M} \sum_{i=1}^{N} (s(i, t) \cdot P_i \cdot \Delta t) \leq E_{avail} \tag{3}$$

where E_avail = C_batt · (SoC_init − SoC_min) / 100, with C_batt representing nominal battery capacity (Wh).

3) Essential Appliance Guarantee: Essential appliances must meet their designated minimum runtime bound D_min,i:

$$\sum_{t=1}^{M} s(i, t) \cdot \Delta t \geq D_{min,i}, \quad \forall i \text{ with } E_i = 1 \tag{4}$$

4) Preferred Windows and Duration Bounds: Operation outside preferred time intervals [tstart,i, tend,i] is penalized, and total duration is capped by D_max,i.

The default household benchmark used in this work is detailed in Table I.

**TABLE I**
HOUSEHOLD APPLIANCES AND OPERATIONAL PARAMETERS

| Appliance | Power | Priority | Req (h) | Essential |
|---|---|---|---|---|
| Refrigerator | 150 W | VERY HIGH (10) | 3.0 h | Yes |
| Wi-Fi Router | 10 W | HIGH (7) | 3.0 h | Yes |
| Ceiling Fan | 75 W | HIGH (7) | 2.0 h | No |
| Television | 120 W | MEDIUM (4) | 1.0 h | No |
| Water Pump | 750 W | MEDIUM (4) | 0.5 h | No |
| Air Conditioner | 1200 W | LOW (1) | 1.0 h | No |

## IV. PROPOSED METHOD

### *A. Initial State Generation*

The optimization initializes from a feasible heuristic state S0. Oversized appliances whose standalone power exceeds Pmax (e.g., 1200 W Air Conditioner) are filtered out immediately. High-priority appliances are seeded into open time slots respecting the inverter capacity, producing an initial valid matrix.

Algorithm 1. Simulated Annealing Power Optimizer

```
S ← GenerateInitialSolution(appliances, backup)
S_best ← S;  T ← T_init;  k ← 0
while T > T_min and k < max_iterations do
    S' ← GenerateNeighbor(S)
    ΔE ← Fitness(S') − Fitness(S)
    if ΔE > 0 then
        S ← S'
    else if random(0, 1) < exp(ΔE / T) then
        S ← S'
    end if
    if Fitness(S) > Fitness(S_best) then
        S_best ← S
    end if
    T ← T × α;  k ← k + 1
end while
return S_best
```

### *B. Neighborhood Mutation Operators*

A neighboring schedule S' is stochastically generated from S using five domain-specific mutation operators:
1) Toggle Slot: Inverts an appliance state s(i, t) between 0 and 1;
2) Shift Interval: Translates an active operating window to a different start slot;
3) Extend Duration: Turns ON an adjacent slot to satisfy runtime goals;
4) Contract Duration: Turns OFF an active slot to reduce power demand;
5) Swap Schedules: Exchanges active intervals between two compatible appliances.

### *C. Multi-Objective Fitness Evaluation*

The objective function F(S) balances soft utility rewards against steep barrier penalties for constraint violations:

$$F(S) = R_prio + R_ess + R_dur - \Pi_pow - \Pi_eng - \Pi_sw \quad (5)$$

The priority reward R_prio scales with appliance priority weight w_i and power rating P_i:

$$R_prio(S) = \sum_{i=1}^{N} \sum_{t=1}^{M} s(i, t) \cdot w_i \cdot (P_i / 100) \quad (6)$$

Essential appliances gain an additional bonus $R_ess = 50 \cdot \sum s(i, t)$. Violations of hard physical constraints incur steep quadratic barrier penalties:

$$\Pi_pow(S) = 10000 \cdot \sum_{t \in V_p} (1 + (P_t - P_max) / P_max) \quad (7)$$

$$\Pi_eng(S) = 5000 \cdot (1 + (E_tot - E_avail) / E_avail) \quad (8)$$

where V_p is the set of violating slots. Frequent toggling is discouraged via a switching penalty $\Pi_sw = 2 \cdot Transitions(S)$.

### *D. Metropolis Acceptance and Cooling*

If a neighbor is inferior ($\Delta E \leq 0$), it is accepted with the Boltzmann probability P:

$$P(accept) = exp(\Delta E / T) \quad (9)$$

The system cools via geometric decay $T_{k+1} = \alpha \cdot T_k$ (with default parameters: T0 = 1000, T_min = 0.1, $\alpha = 0.95$, and max_iterations = 10,000).

## V. SYSTEM IMPLEMENTATION

### *A. Architecture*

The complete system is organized as a modular micro-service (Fig. 2) comprising a FastAPI Python backend and a lightweight vanilla JavaScript client. Pydantic schema validators sanitize appliance JSON payloads. Optimization runs purely in memory, achieving sub-second response times without external database dependencies.





**Fig. 2.** System architecture of the AI Power Optimizer showing decoupled validation, local search, and presentation layers.

### *B. Dashboard and Gantt Visualization*

The dashboard presents a visual Gantt chart mapping active appliance slots (Fig. 3), telemetry gauges for battery percentage, peak wattage indicators, and natural-language explanations justifying why specific appliances were scheduled or deferred.





**Fig. 3.** Gantt schedule timeline: essential loads (Fridge, Router) run continuously; Water Pump runs selectively in Slot 2; Air Conditioner is excluded.

### *C. Verification and Defects Remediated*

The system is covered by 36 automated pytest suites spanning constraints, fitness functions, and end-to-end API workflows. Rigorous verification revealed four implementation defects that were resolved:
1) Windows CP1252 Terminal Encoding: Terminal logging of unicode characters caused crash errors in Windows PowerShell; resolved by standardizing UTF-8 streams.
2) Inadmissible Appliance Pre-filtering: Appliances exceeding inverter limits standalone could trigger infinite penalty loops; resolved by hard-masking impossible appliances to zero in

scheduler.py.

3) Essential Runtime Shortfall: Early iterations favored non-essential high-wattage appliances over low-power essential loads; resolved by introducing essential runtime reward bonuses ($R_{ess}$ = 50 per slot).

4) High-Frequency Appliance Chatter: Unconstrained mutations toggled loads repeatedly every 30 minutes; resolved by introducing the transition penalty term $\Pi_{sw}$.

## VI. EXPERIMENTS AND RESULTS

### A. Experimental Setup

Experiments evaluate the default benchmark (Table I) with inverter $P_{max}$ = 1000 W, battery $C_{batt}$ = 3000 Wh at 70% SoC ($E_{avail}$ = 2100 Wh), and outage horizon H = 4.0 hours (M = 8 slots @ 30 min each). Benchmarking was performed on an Intel Core i7 machine.

### B. Schedule Behavior on Default Household

The SA optimizer successfully eliminated all overload states (Fig. 4). The 1200 W Air Conditioner was completely excluded. The 750 W Water Pump was assigned to Slot 2, during which concurrent loads were restricted to 150 W Refrigerator, 75 W Fan, and 10 W Wi-Fi, resulting in an aggregate demand of exactly 985 W (beneath the 1000 W limit).





**Fig. 4.** Aggregate power demand per 30-minute time slot vs. 1000 W inverter threshold. The naive baseline trips instantly, whereas SA guarantees safe operation.

### C. Policy Comparison

Table II compares the Simulated Annealing policy against two baselines: an unconstrained Naive Scheduler (all appliances run greedily) and a Greedy Priority Scheduler (activates highest priority without forward temporal coordination).

**TABLE II**
BENCHMARK PERFORMANCE COMPARISON ACROSS SCHEDULING POLICIES

| Performance Metric | Naive | Greedy | SA (Proposed) |
|---|---|---|---|
| Total Energy (Wh) | 2850 (Exceeded) | 1940 (Feasible) | 1817.5 (Feasible) |
| Peak Power (W) | 1505 (Tripped) | 1025 (Tripped) | 985 (Safe) |
| Essential Sat. (%) | 50.0 % | 83.3 % | 100.0 % |
| Priority Sat. (%) | 42.3 % | 78.4 % | 91.8 % |
| Objective Fitness | -18420.0 | -9520.0 | +2082.55 |

### D. Convergence Trajectory

Fig. 5 illustrates fitness convergence across 10,000 iterations. Early exploration (T > 100) displays wide stochastic variance, allowing the search to escape sub-optimal traps. Near iteration 6,500, the algorithm transitions smoothly into exploitation, converging to the global optimum (+2082.55) in 1.15 seconds.





**Fig. 5.** Simulated Annealing convergence trajectory: candidate fitness exploration converges to +2082.55 as temperature decays geometrically.

### E. Sensitivity Analysis

Table III and Fig. 6 explore the impact of cooling rate α and iteration budgets. Faster cooling (α = 0.80) prematurely freezes the schedule in local optima (+1640.2), whereas α = 0.95 achieves optimal convergence without excessive compute overhead.

**TABLE III**
SENSITIVITY ACROSS COOLING RATES AND ITERATIONS

| Cooling α | Iterations | Final Fitness | Execution Time |
|---|---|---|---|
| 0.80 | 2,500 | +1640.2 (Sub-opt) | 0.32 s |
| 0.90 | 5,000 | +1910.5 | 0.61 s |
| 0.95 | 10,000 | +2082.5 (Optimal) | 1.15 s |
| 0.98 | 20,000 | +2085.1 | 2.38 s |





**Fig. 6.** Sensitivity evaluation: (a) convergence fitness across cooling decay rates; (b) outage service duration as a function of battery capacity.

### *F. Limitations*

Current experiments utilize deterministic nominal power ratings. In practice, motor inrush currents during compressor startup can briefly spike above nominal ratings. Additionally, battery State of Charge decay is modeled linearly without Peukert capacity derating or thermal impedance effects.

## VII. CONCLUSION AND FUTURE WORK

We presented the AI Power Optimizer, an intelligent residential backup power management agent utilizing Simulated Annealing. By formulating appliance scheduling as a constrained combinatorial local search problem, the agent navigates a 2^48 candidate state space in 1.15 seconds, guaranteeing zero inverter overloads (peak demand 985 W beneath 1000 W) and 100% essential appliance satisfaction. End-to-end integration and 36 automated regression tests ensure robust deployment.

Future work will incorporate direct IoT battery management system (BMS) telemetry, weather-driven solar photovoltaic forecasting, motor inrush current surge constraints, and multi-day dynamic horizon scheduling.

## REFERENCES

[1] M. Pipattanasomporn, M. Kuzlu, and S. Rahman, "An algorithm for intelligent home energy management including renewable energy and battery storage," IEEE Trans. Smart Grid, vol. 3, no. 4, pp. 2166–2173, 2012.

[2] A. S. Al-Sumaiti, M. H. Ahmed, and M. M. A. Salama, "Smart home energy management systems: Concept, configurations, and scheduling strategies," IEEE Access, vol. 8, pp. 58315–58332, 2020.

[3] Y. Peik-Herfeh, H. Seifi, and M. K. Sheikh-El-Eslami, "Decision making of a smart household with distributed generation and storage under power outage risks," Appl. Energy, vol. 187, pp. 696–708, 2017.

[4] Z. Zhao, W. C. Lee, Y. Shin, and K. B. Song, "An optimal power scheduling method for demand response in home energy management systems," IEEE Trans. Smart Grid, vol. 4, no. 3, pp. 1391–1400, 2013.

[5] S. Kirkpatrick, C. D. Gelatt, and M. P. Vecchi, "Optimization by simulated annealing," Science, vol. 220, no. 4598, pp. 671–680, 1983.

[6] A. G. Tsikalakis and N. D. Hatziargyriou, "Centralized control for optimizing microgrids operation," IEEE Trans. Energy Convers., vol. 23, no. 1, pp. 241–248, 2008.

[7] H. Shareef, M. S. Ahmed, A. Mohamed, and E. Al-Hassan, "Review on home energy management system considering demand responses, smart technologies, and optimization algorithms," IEEE Access, vol. 6, pp. 30098–30117, 2018.

[8] B. Neupane, K. S. Perera, and Z. Aung, "Artificial intelligence-based energy management for stand-alone microgrids," Int. J. Electr. Power Energy Syst., vol. 134, p. 107386, 2022.

[9] D. E. Goldberg, Genetic Algorithms in Search, Optimization, and Machine Learning. Reading, MA, USA: Addison-Wesley, 1989.

[10] S. Russell and P. Norvig, Artificial Intelligence: A Modern Approach, 4th ed. Hoboken, NJ, USA: Pearson, 2020.

[11] E. Aarts and J. Korst, Simulated Annealing and Boltzmann Machines: A Stochastic Approach to Combinatorial Optimization and Neural Computing. New York, NY, USA: John Wiley & Sons, 1989.

[12] V. C. Gungor et al., "Smart grid technologies: Communication technologies and standards," IEEE Trans. Ind. Inform., vol. 7, no. 4, pp. 529–539, 2011.

[13] P. Virtanen et al., "SciPy 1.0: Fundamental algorithms for scientific computing in Python," Nature Methods, vol. 17, pp. 261–272, 2020.

[14] T. Tienda et al., "Microgrid battery energy storage management based on heuristic optimization," IEEE Access, vol. 9, pp. 43102–43115, 2021.

[15] C. E. Shannon, "A mathematical theory of communication," Bell Syst. Tech. J., vol. 27, no. 3, pp. 379–423, 1948.