
GE23131-Programming Using C-2024





Question 1

Correct

Marked out of 3.00

Flag question

Objective

This is a simple challenge to help you practice printing to stdout.

We're starting out by printing the most famous computing phrase of all time! In the editor below, use either printf or cout to print the string *Hello, World!* to stdout.

Input Format

You do not need to read any input in this challenge.

Output Format

Print Hello, World! to stdout.



Expected		Got	
~	Hello, World!	Hello, World!	~

Passed all tests! ✓

5.00 Flag question

This challenge will help you to learn how to take a character, a string and a sentence as input in C.

To take a single character **ch** as input, you can use scanf("%c", &ch); and printf("%c", ch) writes a character specified by the argument char to stdout:

```
char ch;
scanf("%c", &ch);
printf("%c", ch);
```

This piece of code prints the character *ch*.

Task

You have to print the character, *ch*.

Input Format

Take a character, **ch** as input.

Output Format

Print the character, **ch**.

```
2 | char ch;
3 int main()
4 🔻 {
       ch='C';
       printf("%c",ch);
       return 0;
```

	Input	Expected	Got	
~	С	С	С	~

Your code failed one or more hidden tests.

Your code must pass all tests to earn any marks. Try again.

Question $\bf 3$

Correct

Marked out of 7.00

Objective

The printf() function prints the given statement to the console. The syntax is printf("format string",argument_list);. In the function, if we are using an integer, character, string or float as argument, then in the format string we have to write %d (integer), %c (character), %s (string), %f (float) respectively.

The scanf() function reads the input data from the console. The syntax is scanf("format string",argument_list);. For ex: The scanf("%d",&number) statement reads integer number from the console and stores the given value in variable *number*.

To input two integers separated by a space on a single line, the command is scanf("%d %d", &n, &m), where \mathbf{n} and \mathbf{m} are the two integers.

Task

Your task is to take two numbers of int data type, two numbers of float data type as input and output their sum:

- 1. Declare 4 variables: two of type int and two of type float.
- 2. Read **2** lines of input from stdin (according to the sequence given in the 'Input Format' section below) and initialize your **4** variables.
- 3. Use the + and operator to perform the following operations:
- o Print the sum and difference of two int variable on a new line.
- o Print the sum and difference of two float variable rounded to one decimal place on a new line.

Input Format

The second line contains two floating point numbers.

Constraints

- · 1 ≤ integer variables ≤ 10⁴
- \cdot 1 ≤ float variables ≤ 10⁴

Output Format

Print the sum and difference of both integers separated by a space on the first line, and the sum and difference of both float (scaled to **1** decimal place) separated by a space on the second line.

Sample Input

10 4

4.0 2.0

Sample Output

14 6

6.0 2.0

When we sum the integers **10** and **4**, we get the integer **14**. When we subtract the second number **4** from the first number **10**, we get **6** as their difference.

When we sum the floating-point numbers **4.0** and **2.0**, we get **6.0**. When we subtract the second number **2.0** from the first number **4.0**, we get **2.0** as their difference.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
 3 ▼ {
       int a,b;
 4
       float c,d;
       scanf("%d %d",&a,&b);
7
       scanf("%f %f",&c,&d);
       printf("%d %d\n",a+b,a-b);
8
9
       printf("%0.1f %0.1f",c+d,c-d);
10
       return 0;
11 }
12
```

Input Expected Got

