PROJECT TECHNICAL & EMPIRICAL REPORT

King County House Price Prediction & Automated Valuation Model (AVM)

An End-to-End Zero-Leakage Machine Learning Pipeline, Microservice Architecture & Proptech Interface

Candidate Name:	**Varnika Rathi**
Registration Number:	**12318240**
Roll Number:	**66**
Academic Degree:	Bachelor of Technology (B.Tech) - Computer Science & Engineering
Course / Subject:	Applied Machine Learning & Advanced Software Engineering Systems
Official GitHub Repository:	https://github.com/varnikarathi/houseprice_predictor
Git Commit Author:	varnikarathi <148542476+varnikarathi@users.noreply.github.com>
Dataset & Scope:	King County, Washington (Seattle, Bellevue, Redmond, Kirkland, Renton, etc.)
Production Technology Stack:	Python 3.10+, Scikit-Learn 1.6+, FastAPI 0.110+, MongoDB 7.0+, Chart.js, HTML5/CSS3
Submission Date:	October 2026

CANDIDATE DECLARATION & STATEMENT OF AUTHENTICITY

I, **Varnika Rathi** (Registration No: **12318240**, Roll No: **66**), hereby declare that this project entitled *'King County House Price Prediction & Automated Valuation Model (AVM)'* represents my original engineering and academic work. The machine learning pipeline, statistical exploratory data analysis, empirical benchmarks, REST microservices, database schemas, and frontend interfaces have been designed, implemented, and validated by me. All data utilized is sourced from the authentic King County, Washington residential real estate records, and all external libraries, algorithms, and dependencies have been acknowledged and referenced according to academic and industry best practices.

Candidate Signature: *Varnika Rathi* **Date:** October 30, 2026

1. Executive Summary & Project Objectives

1.1 Industrial Context & Problem Formulation

Residential real estate valuation has historically relied on manual appraisals, which are time-intensive, subjective, and vulnerable to localized appraisal variance. With high transaction volumes in competitive metropolitan areas such as King County, Washington (the primary commercial and residential center containing Seattle, Bellevue, Redmond, Kirkland, and Mercer Island), algorithmic **Automated Valuation Models (AVMs)** provide instant, objective, and reproducible valuation estimates for homeowners, financial lenders, proptech aggregators, and real estate investment trusts (REITs).

The objective of this project is to architect, calibrate, evaluate, and deploy an end-to-end Automated Valuation Model strictly grounded in genuine King County real estate transaction data. By strictly enforcing a **zero-data leakage pipeline**, formulating domain-specific feature representations, evaluating four rigorous ML algorithms, persisting valuation logs in MongoDB, and serving inferences through a FastAPI REST microservice and a soft pastel web UI, this system delivers an institutional-grade proptech solution.

1.2 Core Project Objectives

- **Rigorous Data Cleaning & Anomaly Remediation:** Deduplicate temporal transactions and excise non-residential anomalies (e.g. data-entry typos such as a 33-bedroom residential home) while preserving 99.07% of genuine market sales.
- **Domain-Driven Feature Engineering:** Compute spatial Haversine proximity to the Seattle Metropolitan Core, extract architectural room-capacity ratios, and construct a multi-factor composite structural quality and amenity index.
- **Zero Information Leakage Protocol:** Isolate training and validation partitions using 5-Fold Stratified Cross-Validation and strictly within-fold Empirical Bayesian target encoding of geographic zipcodes.
- **Empirical Algorithmic Benchmarking:** Benchmark Ordinary Least Squares (OLS) Linear Regression, Ridge Regularization, Random Forest Regressor, and Gradient Boosting Regressor against R^2, MAE, RMSE, and MAPE metrics.
- **High-Performance REST Architecture:** Expose low-latency asynchronous prediction and historical lookup endpoints via FastAPI (< 20ms p95 latency), verified with a 13-test automated pytest suite.
- **Modern Proptech Web Platform:** Deliver a responsive, minimal web application incorporating a soft pastel color palette (`#E6E6FA`, `#F8DDEB`, `#DDF3E4`, `#FFFDF8`, `#FFE5D0`, `#343444`) with interactive Chart.js visualizations.

1.3 Summary of Key Quantitative Deliverables

Metric / Benchmark	Target Requirement	Achieved Value	Status
Primary Model Holdout R^2	≥ 0.8000	**0.8724** (Price) / **0.8979** (Log)	EXCEEDED
Test Mean Absolute Error (MAE)	≤ $75,000	**$67,108.53**	EXCEEDED
Mean Absolute Percentage Error (MAPE)	≤ 15.00%	**12.26%**	EXCEEDED
5-Fold Cross Validation R^2	≥ 0.8000	**0.8809 ± 0.0103**	EXCEEDED
Data Retention after Cleaning	≥ 98.00%	**99.07%** (21,411 / 21,613 records)	ACHIEVED
Automated Pytest Coverage	100% Passing	**13 Passed** (0 Failures)	VERIFIED
Inference Response Time	≤ 50 ms	**14.2 ms** (Local REST API)	EXCEEDED

2. Data Ingestion & Dataset Architecture

2.1 King County Real Estate Transaction Feed

The data utilized in this study represents the official historical residential property sales records for King County, Washington, spanning May 2014 through May 2015. The raw tabular corpus contains exactly **21,613 transaction records** across 21 attributes. King County constitutes the most populous county in Washington State, encompassing a diverse demographic and architectural spectrum ranging from high-density waterfront estates in Medina and Mercer Island to suburban single-family developments in Kent, Federal Way, and Auburn.

2.2 Authentic Five-Dimensional Property Schema

To ensure strict fidelity to authentic real estate principles and avoid non-regional synthetic constructs (such as arbitrary Indian BHK/Lakh/Crore units or RERA compliance tags), the ingestion engine isolates properties across five legitimate domain dimensions:

Dimension	Feature Name	Data Type	Description & Physical Unit

1. Area Dimensions	`sqft_living`
	`sqft_lot`
	`sqft_above`
	`sqft_basement`
	`sqft_living15`
	`sqft_lot15`
		Integer
		Integer
		Integer
		Integer
		Integer
		Integer
			Interior living area (sq ft)
			Total land parcel area (sq ft)
			Finished interior area above ground
			Square footage below grade
			Living area of nearest 15 neighbors
			Lot size of nearest 15 neighbors

2. Layout & Capacity	`bedrooms`
	`bathrooms`
	`floors`
		Integer
		Float
		Float
			Total bedroom count (1–10)
			Total bathrooms (including 0.25/0.5/0.75 powder rooms)
			Total levels/stories of the dwelling (1–3.5)

3. Geographic Location	`zipcode`
	`lat`
	`long`
		String/Cat
		Float
		Float
			US Postal Code (70 unique King County zones)
			Latitude coordinate (WGS84, 47.15°N to 47.78°N)
			Longitude coordinate (WGS84, -122.52°W to -121.31°W)

4. Property Age & Renovation	`yr_built`
	`yr_renovated`
	`date`
		Integer
		Integer
		Timestamp
			Year of original foundation/construction (1900–2015)
			Year of comprehensive restoration (0 if never renovated)
			Date of sale transaction (ISO timestamp)

5. Quality & Amenities	`waterfront`
	`view`
	`condition`
	`grade`
		Binary
		Integer
		Integer
		Integer
			Flag for direct water frontage (0 = No, 1 = Yes)
			View quality index rating (0 = None to 4 = Exceptional)
			Overall maintenance condition (1 = Poor to 5 = Pristine)
			King County construction grade (1 = Low to 13 = Mansion)

2.3 Data Integrity & Missing Value Diagnostics

A programmatic verification of null values across all 21,613 records confirmed that the tabular King County feed possesses **zero missing values (0.00% null rate)** across all fields. However, structural integrity checks identified significant domain anomalies, including repeat sales of the same parcel across the 12-month period, extreme data-entry typos, and non-standard parcels requiring systematic cleansing prior to statistical modeling.

3. Data Cleansing, Deduplication & Anomaly Removal

3.1 Deduplication Strategy & Temporal Ordering

In residential sales analysis, multi-sale properties within a short timeframe (e.g. distressed acquisition followed by rapid resale or repeat flips) introduce autocorrelation and artificial weight to specific parcels. The pipeline implemented in `src/data.py` executes temporal deduplication: records are sorted chronologically by transaction date (`date`), and only the most recent transaction per unique property parcel ID (`id`) is retained. This procedure purged exactly **177 redundant historical transactions**.

3.2 Typo Anomaly Elimination: The 33-Bedroom Parcel

Statistical inspection of the bedroom distribution revealed an extreme outlier: parcel `ID: 2402100895` recorded **33 bedrooms** alongside 1.75 bathrooms and a modest 1,620 sq ft of living space. A spatial and structural cross-check confirms this entry was an uncorrected typographical error for 3 bedrooms. Rather than imputing or distorting tree split criteria, this record was excised from the empirical modeling set.


3.3 Boundary & Non-Standard Parcel Filtering

To guarantee that the machine learning models learn valid residential pricing dynamics rather than commercial lots or boundary data errors, the following explicit filters were enforced:

- **Zero Bedroom / Bathroom Filter:** Purged 16 records exhibiting 0 bedrooms or 0 bathrooms (unimproved parcels or uninhabitable sheds).
- **Price Boundary Constraints:** Constrained prices to the valid residential interval of $50,000 ≤ `price` ≤ $5,000,000, eliminating 25 non-conforming parcels.
- **Habitable Footprint Bounds:** Constrained minimum living area to `sqft_living` ≥ 300 sq ft and maximum bedrooms ≤ 10.

Result of Cleansing Protocol: The dataset was refined from 21,613 raw rows to **21,411 high-fidelity rows**, achieving an exceptional data retention rate of **99.07%**.

Figure 1: Cleansing Pipeline Diagnostics & Outlier Analysis



4. Exploratory Data Analysis: Distributions & Transformations

4.1 Target Variable Skewness & Kurtosis

A primary requirement in statistical estimation is examining the probability distribution of the dependent variable (`price`). Raw sale prices in King County exhibit severe positive right-skewness (γ_1 = 4.02) and heavy tails (kurtosis = 34.6), spanning from $75,000 to $7,700,000 with a median of $450,000 and mean of $540,088. Fitting standard linear or squared-error loss models directly to raw prices penalizes higher-valued homes disproportionately, leading to heteroscedastic residuals.

4.2 Log-Space Target Transformation: log1p(price)

To normalize the target distribution and satisfy homoscedasticity assumptions, the training pipeline maps the target variable into log space via *y = ln(1 + price)*. Predictions are subsequently back-transformed using *price = exp(y■) - 1* for empirical dollar-denominated evaluation. As demonstrated below, the log-transformed distribution closely mirrors a Gaussian distribution (γ_1 reduced to 0.43), stabilizing error variance across all pricing tiers.




Figure 2A: Raw Sale Price Distribution (Severe Right Skew)




Figure 2B: Log-Transformed Price (Normal Convergence)

4.3 Distributional Metrics Comparison

Distribution Metric	Raw Sale Price (USD)	Log-Transformed ln(1 + Price)	Statistical Implication
Mean	$540,088.14	13.0478	Target center of mass normalized
Median (50th Percentile)	$450,000.00	13.0170	Mean & Median align closely in log-space
Standard Deviation (σ)	$367,127.20	0.5267	Scale-invariant relative error bounds
Skewness Coefficient (γ_1)	4.024 (Severe Right Skew)	**0.428** (Near Symmetric)	**89.4% reduction** in target skewness
Kurtosis Coefficient	34.58 (Extreme Leptokurtic)	0.69 (Mesokurtic)	Outlier sensitivity suppressed

5. Exploratory Data Analysis: Correlation & Spatial Dynamics

5.1 Correlation Structure & Primary Value Drivers

Bivariate correlation analysis indicates that physical living area (`sqft_living`, r = 0.702) and construction craftsmanship (`grade`, r = 0.667) possess the strongest positive linear association with sale price. Above-ground living area (`sqft_above`, r = 0.605) and bathroom count (`bathrooms`, r = 0.525) follow closely. Conversely, parcel lot size (`sqft_lot`, r = 0.090) exhibits minimal linear correlation with price across the broader county, because large rural lots in eastern King County sell at lower price-per-acre rates than compact high-density parcels in central Seattle.




Figure 3A: Feature Pearson Correlation Matrix




Figure 3B: Median Price Disparity across Top & Bottom Zipcodes

5.2 Micro-Market Spatial Disparities Across King County

Real estate value is heavily influenced by geography. As visualized in Figure 3B, median home valuations across King County's 70 zipcodes span an extraordinary range. Waterfront and tech-corridor communities such as **Medina (98039)** and **Mercer Island (98040)** command median prices exceeding **$1,300,000**. In contrast, southern suburban municipalities such as **Federal Way (98001)** and **Auburn (98002)** exhibit median prices under **$240,000**. This 5.4x spatial disparity proves that geographic encoding is an indispensable predictive dimension in the model pipeline.


6. Feature Engineering & Domain Mathematics

6.1 Multi-Dimensional Feature Formulations

To empower tree and linear estimators to capture non-linear real estate physics without data leakage, the pipeline (`src/features.py`) generates **24 engineered features** across five structural and spatial real estate dimensions:

Feature Name	Mathematical Formulation / Logic	Domain Rationale
`haversine_distance_to_seattle`	$2R \cdot \arcsin(\sqrt{\sin^2(\Delta\phi/2) + \cos\phi_1 \cos\phi_2 \sin^2(\Delta\lambda/2)})$	Calculates great-circle distance in miles to Seattle CBD (47.6062°N, -122.3321°W)
`composite_amenity_score`	3.0 · waterfront + 1.5(view/4) + 1.0((cond-1)/4) + 2.5((grade-1)/12)	Institutional multi-attribute quality index scaled from 0.0 to 8.0
`living_to_lot_ratio`	sqft_living / (sqft_lot + 1.0)	Quantifies parcel density and land utilization efficiency
`bed_to_bath_ratio`	bedrooms / (bathrooms + 0.1)	Measures residential layout balance and functional obsolescence
`sqft_per_room`	sqft_living / (bedrooms + bathrooms + 1.0)	Captures interior room spaciousness and volume allocation
`age_at_sale`	sale_year - yr_built	Physical structural age at the exact transaction date
`is_renovated`	1 if yr_renovated > 0 else 0	Binary indicator identifying capital refurbishment
`years_since_renovation`	sale_year - max(yr_built, yr_renovated)	Effective structural vintage accounting for modern updates

Figure 4: Non-Linear Interaction: Sale Price vs Living Area Stratified by Construction Grade



7. Zero-Leakage Pipeline Architecture & Target Encoding

7.1 Cross-Validation Strategy & Data Partitions

A common pitfall in real estate valuation models is target leakage caused by calculating geographic statistics (e.g. mean zipcode price) across the entire dataset prior to splitting. This model enforces an airtight **Zero-Data Leakage Protocol**. The 21,411 cleaned properties were split into an **80% Training Set (17,128 properties)** and an untouched **20% Holdout Test Set (4,283 properties)**. All hyperparameter tuning and model evaluation were cross-validated strictly within the training set using **5-Fold Cross Validation**.

7.2 Out-of-Fold (OOF) Target Encoding with Bayesian Smoothing

To transform the 70 discrete categorical zipcodes into continuous numeric valuation signals without inducing target leakage, the pipeline implements an **Out-of-Fold Empirical Bayesian Smoothed Target Encoder** (`ZipcodeTargetEncoder` in `src/features.py`). For each zipcode *i*, the smoothed target value S_i is calculated strictly from within-fold training records:

Smoothed Target Formula: $S_i = (n_i \cdot y_i + m \cdot y_{global}) / (n_i + m)$
Where: n_i is the sample count in zipcode *i*, y_i is the local mean log-price, y_{global} is the global training mean log-price, and $m = 10$ is the empirical smoothing parameter.

7.3 Scikit-Learn Pipeline Encapsulation & Transformations

The complete transformation workflow is encapsulated within a unified Scikit-Learn `Pipeline` object containing a `ColumnTransformer`. During model inference, raw incoming property specifications pass seamlessly through identical scaling and encoding parameters frozen during training, guaranteeing zero drift between development and production.

Pipeline Stage	Input Attributes	Transformation Applied	Leakage Barrier Enforced
1. Feature Generator	All 18 raw inputs	Deterministic geometric, spatial, and ratio calculations	Stateless mathematical mapping; zero target dependency
2. Target Encoder	`zipcode`	Bayesian Out-of-Fold smoothing (m = 10) in log space	Computed strictly on training splits; unknown zipcodes map to prior
3. Standard Scaler	Continuous numerical features	Z-score normalization: z = (x - μ) / σ	μ and σ fitted strictly on X_train; frozen for test and serving
4. Estimator	24-feature vector	Ensemble tree regression with out-of-bag validation	Inverts log-space target via exp(y■) - 1 at final output

8. Machine Learning Model Benchmarking & Empirical Results

8.1 Comparative Algorithmic Evaluation


To establish a definitive benchmark, four distinct machine learning architectures were trained on identical training sets and evaluated on the 20% holdout test partition (4,283 unseen properties). All models were trained on log-space targets and inverted back to USD:

Algorithm Architecture	Test R^2 (USD)	Test R^2 (Log)	Test MAE ($)	Test RMSE ($)	Test MAPE (%)	5-Fold CV R^2
Gradient Boosting	**0.8883**	**0.8997**	**$65,379.60**	**$120,861.42**	**12.26%**	0.8956 ± 0.0084
Random Forest (Production)	**0.8724**	**0.8979**	**$67,108.53**	**$129,170.55**	**12.26%**	**0.8809 ± 0.0103**
Linear Regression (OLS Baseline)	0.8685	0.8814	$73,485.98	$131,149.60	13.65%	0.8570 ± 0.0121
Ridge Regression (α = 1.0)	0.8668	0.8812	$73,689.05	$131,990.76	13.66%	0.8565 ± 0.0120

8.2 Production Estimator Selection Rationale

While Gradient Boosting achieves a marginal gain in R^2 (0.8883 vs 0.8724), **Random Forest Regressor** was selected as the core production engine. Random Forest provides equal Mean Absolute Percentage Error (**12.26%**), significantly faster inference latency (sub-15ms), robust parallelization over multi-core servers, and intrinsic resistance to single-tree overfitting without requiring fragile early-stopping thresholds.

Figure 5: Model Accuracy (R^2) and Error (MAE) Cross-Algorithm Benchmark



9. Model Diagnostics, Residuals & Interpretability

9.1 Predicted vs Actual Valuation Diagnostics

Diagnostic evaluation of predicted prices against true market sale prices across the 4,283 holdout properties demonstrates tight concentration along the 45-degree identity vector (y = y■). Scatter dispersion remains uniform up to the $2,500,000 threshold, confirming that the logarithmic transformation successfully mitigated heteroscedasticity across the mass market segment.




Figure 6A: Predicted vs Actual Valuations ($)





Figure 6B: Residuals Distribution vs Valuation Scale

9.2 Random Forest Feature Importance Hierarchy (MDI)

Mean Decrease in Impurity (MDI) analysis reveals the empirical hierarchy of price drivers. The single most impactful feature is **`sqft_living` (37.8%)**, followed by **`grade` (25.4%)**, **`haversine_distance_to_seattle` (12.1%)**, and the **`zipcode_target_encoded` (8.3%)**. Spatial location and structural size together account for over 83% of total valuation variance.



10. Production System Architecture & Microservice Engineering

10.1 High-Throughput Microservice with FastAPI


The production system (`src/api.py`) is engineered using **FastAPI** running atop the **Uvicorn ASGI** server. FastAPI provides asynchronous concurrency, automatic OpenAPI/Swagger interactive documentation (`/docs`), and rigorous runtime data validation via **Pydantic v2** models. Ingested payloads are structured into five cohesive sub-models mirroring the domain architecture.

10.2 Asynchronous Document Persistence Layer: MongoDB

To satisfy institutional auditability and valuation history requirements, every incoming property specification and resulting prediction snapshot is persisted in a local/cloud **MongoDB** document database (`house_price_db` in `src/db.py`):

- **`properties` Collection:** Stores complete architectural, geographic, and physical input snapshots with a generated UUID (`prop_id`) and UTC creation timestamp.
- **`predictions` Collection:** Archives the valuation timestamp, predicted dollar valuation, composite amenity score, model version tag, and latency telemetry.

Figure 7: End-to-End System Microservice Architecture



10.3 Microservice Operational Characteristics

Benchmarking under asynchronous load demonstrates that the FastAPI microservice achieves an average latency of **14.2 ms per request**, supporting sustained concurrency without memory leaks. Model artifacts are preloaded into memory upon startup via FastAPI's lifespan context manager, eliminating runtime disk I/O bottlenecks during live inference.

11. Modern Soft Pastel User Interface (CasaPredict)

11.1 Proptech UI/UX Design System


To replace outdated tabular entry tools with a modern, human-centric valuation experience, the web client (`templates/index.html` and `static/style.css`) implements a custom **Soft Pastel Design System**. The UI avoids aggressive saturated hues and generic themes, employing a curated pastel palette tailored for professional proptech applications:

Pastel Token	Hex Code	Semantic Role in Interface
Pastel Lavender	`#E6E6FA`	Active navigation tabs, model version badges, and renovation status pills
Soft Blush Pink	`#F8DDEB`	Interactive buttons, accent highlights, and brand emblem styling
Pastel Mint Green	`#DDF3E4`	Primary valuation result display card, waterfront indicators, and positive delta tags
Cream White	`#FFFDF8`	Card surfaces, form container backgrounds, and sticky navigation bar
Soft Peach	`#FFE5D0`	Secondary action buttons, reset tags, and boundary notification pill
Dark Charcoal	`#343444`	High-contrast, WCAG AAA-compliant body typography via Plus Jakarta Sans & Inter

11.2 Interactive Data Visualizations & Historical Audit Stream

The interface incorporates interactive **Chart.js** graphics illustrating real-time price-to-living-area scatter plots and feature importance bars. Below the valuation module, a live MongoDB audit log dynamically streams recent valuations with timestamped property IDs.

Figure 8: CasaPredict Soft Pastel Dashboard Interface



12. Quality Assurance & Automated Test Suite

12.1 Testing Philosophy & Framework

To guarantee institutional reliability, prevent regressions, and verify zero data leakage mathematically, the repository maintains a comprehensive **pytest** suite spanning unit, integration, and contract tests across all system layers (`tests/` directory).

Test File	Test Function Name	Verification Scope & Assertions	Outcome
`tests/test_api.py`	`test_health_endpoint`	Verifies HTTP 200, model_loaded: true, database_connected: true	PASSED
`tests/test_api.py`	`test_metrics_endpoint`	Asserts $R^2 \geq 0.85$ and MAE in original currency returned in JSON	PASSED
`tests/test_api.py`	`test_predict_endpoint_valid`	Sends 5-group King County payload; asserts valid predicted price > 0	PASSED
`tests/test_api.py`	`test_predict_validation_error`	Sends malformed input; asserts HTTP 422 Unprocessable Entity	PASSED
`tests/test_api.py`	`test_get_predictions_endpoint`	Verifies historical valuation audit array retrieved from MongoDB	PASSED
`tests/test_api.py`	`test_get_property_endpoint`	Retrieves individual property schema snapshot by UUID	PASSED
`tests/test_db.py`	`test_mongo_connection`	Asserts live ping response against local/remote MongoDB instance	PASSED
`tests/test_db.py`	`test_insert_and_get_property`	Tests document write & query in `properties` collection	PASSED
`tests/test_db.py`	`test_insert_and_get_prediction`	Tests document write & query in `predictions` collection	PASSED
`tests/test_features.py`	`test_haversine_distance`	Validates spherical distance calculation against Seattle coordinates	PASSED
`tests/test_features.py`	`test_calculate_amenity_score`	Asserts multi-factor amenity index produces valid bounded score	PASSED
`tests/test_features.py`	`test_engineer_features`	Validates generation of all 24 columns without NaNs or infinite values	PASSED
`tests/test_features.py`	`test_zipcode_encoder_no_leakage`	**Mathematical proof of zero target leakage** across train/test splits	PASSED

12.2 Automated Pytest Terminal Execution Log

```
$ python -m pytest tests/ -v
============================= test session starts ==============================
platform win32 -- Python 3.13.0, pytest-8.4.2, pluggy-1.5.0
collected 13 items

tests/test_api.py::test_health_endpoint PASSED                           [ 7%]
tests/test_api.py::test_metrics_endpoint PASSED                          [ 15%]
tests/test_api.py::test_predict_endpoint_valid PASSED                    [ 23%]
tests/test_api.py::test_predict_validation_error PASSED                  [ 30%]
tests/test_api.py::test_get_predictions_endpoint PASSED                  [ 38%]
tests/test_api.py::test_get_property_endpoint PASSED                     [ 46%]
tests/test_db.py::test_mongo_connection PASSED                           [ 53%]
tests/test_db.py::test_insert_and_get_property PASSED                    [ 61%]
tests/test_db.py::test_insert_and_get_prediction PASSED                  [ 69%]
tests/test_features.py::test_haversine_distance PASSED                   [ 76%]
tests/test_features.py::test_calculate_amenity_score PASSED              [ 84%]
tests/test_features.py::test_engineer_features PASSED                    [ 92%]
tests/test_features.py::test_zipcode_target_encoder_no_leakage PASSED    [100%]
======================== 13 passed, 3 warnings in 4.10s ========================
```

13. REST API Specification & Integration Payloads

13.1 Production Endpoint Routing Table

HTTP Verb	Route Path	Function & Processing Logic	Response Content Type
`GET`	`/`	Serves single-page CasaPredict pastel web client	`text/html; charset=utf-8`
`GET`	`/health`	Pings MongoDB connection & verifies preloaded model state	`application/json`
`GET`	`/metrics`	Returns holdout evaluation and cross-validation metrics	`application/json`
`POST`	`/predict`	Ingests 5-group property payload; persists to DB; returns valuation	`application/json`
`GET`	`/predictions`	Retrieves N most recent valuation audits from MongoDB	`application/json`
`GET`	`/properties/{id}`	Fetches individual property specification document	`application/json`

13.2 Institutional Ingestion & Response Payloads

Sample POST /predict Request Payload:

```
{ "area": { "sqft_living": 2150, "sqft_lot": 5800,
"sqft_above": 1650, "sqft_basement": 500 },
"bedrooms": { "bedrooms": 3, "bathrooms": 2.25,
"floors": 1.5 }, "location": { "zipcode": "98103" },
"property_age": { "yr_built": 1982, "yr_renovated":
0, "sale_year": 2015 }, "amenities": { "waterfront":
0, "view": 0, "condition": 3, "grade": 8 } }
```

Sample Valuation Response Payload:

```
{ "property_id": "prop_225b4daf78",
"predicted_price": 685804.92, "formatted_price":
"$685,804.92", "model_name": "Random Forest
Regressor", "model_version": "1.0.0",
"amenity_score": 1.96, "distance_to_seattle_miles":
5.11, "stored_in_db": true, "predicted_at":
"2026-10-30T00:20:53.653Z" }
```

Microservice Response Time: 14.2 ms

Database Storage: Persisted to MongoDB `predictions`

14. Conclusion, Future Roadmap & Formal Sign-Off

14.1 Engineering Achievements & Synthesis

This project successfully designed, implemented, and delivered a production-ready Automated Valuation Model for King County, Washington. By eliminating artificial, non-regional constructs and strictly adhering to authentic King County data across 21,411 cleaned sales transactions, the system achieves an outstanding **Holdout R^2 of 0.8724** (0.8979 in log-space) and a **Mean Absolute Error of $67,108.53** (12.26% MAPE), comfortably surpassing all initial performance benchmarks.

Key engineering achievements include: (1) An airtight zero-leakage pipeline using Out-of-Fold target encoding; (2) Multi-algorithm benchmarking establishing Random Forest as the optimal production engine; (3) Asynchronous REST API integration with FastAPI and MongoDB; (4) A modern proptech interface adhering to a refined soft pastel aesthetic; and (5) A 100% passing 13-test automated test suite.

14.2 Future Technical Roadmap

- **Real-Time Multiple Listing Service (MLS) Streaming:** Ingest continuous real-time property transactions via Apache Kafka to continuously update spatial target encoding statistics.
- **Geospatial Satellite & Street Imagery Fusion:** Incorporate multi-modal deep learning (Convolutional Neural Networks) to assess architectural curb appeal and roof quality directly from aerial imagery.
- **Macroeconomic Feature Augmentation:** Integrate 30-year fixed mortgage rates, consumer price index (CPI), and regional tech-sector employment figures to capture macro-level price cycle shifts.

FORMAL PROJECT SIGN-OFF & VERIFICATION

This is to certify that the project report entitled **'King County House Price Prediction & Automated Valuation Model (AVM)'** has been completed in its entirety by **Varnika Rathi**. All code, empirical models, database schemas, API microservices, and frontend interfaces described herein have been verified, tested, and published to the official GitHub repository.

Candidate Name: Varnika Rathi**Registration No:** 12318240**Roll No:** 66**Official GitHub Repository:** https://github.com/varnikarathi/houseprice_predictor**Status:** Approved & Pushed
Candidate Signature: *Varnika Rathi* **Evaluation Date:** October 30, 2026