

Users > moshika > Desktop > c dns_server.c

```
1  #include <stdio.h>
2  #include <string.h>
3  #include <stdlib.h>
4  #include <unistd.h>
5  #include <arpa/inet.h>
6  #define DNS_PORT 53
7  #define BUF_SIZE 512
8
9  struct DNS_HEADER {
10     unsigned short id;
11     unsigned short flags;
12     unsigned short qcount;
13     unsigned short ans;
14     unsigned short auth;
15     unsigned short add;
16 };
17 struct QUESTION {
18     unsigned short qtype;
19     unsigned short qclass;
20 };
21 void to_dns_format(unsigned char *dns, unsigned char *host) {
22     int lock = 0, i;
23     strcat((char *)host, ".");
24     for (i = 0; i < strlen((char *)host); i++) {
25         if (host[i] == '.') {
26             *dns++ = i - lock;
27             for (; lock < i; lock++)
28                 *dns++ = host[lock];
29             lock++;
30         }
31     }
32     *dns++ = '\\0';
33 }
```

```

34 int main() {
35     unsigned char buffer[BUF_SIZE], *qname;
36     struct DNS_HEADER *dns = NULL;
37     struct QUESTION *qinfo = NULL;
38
39     char hostname[100];
40     printf("Enter hostname: ");
41     scanf("%s", hostname);
42
43     int sockfd = socket(AF_INET, SOCK_DGRAM, IPPROTO_UDP);
44     struct sockaddr_in dest;
45     dest.sin_family = AF_INET;
46     dest.sin_port = htons(DNS_PORT);
47     dest.sin_addr.s_addr = inet_addr("8.8.8.8");
48     dns = (struct DNS_HEADER *)&buffer;
49     dns->id = (unsigned short) htons(getpid());
50     dns->flags = htons(0x0100);
51     dns->qcount = htons(1);
52     dns->ans = 0;
53     dns->auth = 0;
54     dns->add = 0;
55
56     qname = (unsigned char *)&buffer[sizeof(struct DNS_HEADER)];
57     to_dns_format(qname, (unsigned char *)hostname);
58
59     qinfo = (struct QUESTION *)&buffer[sizeof(struct DNS_HEADER) + strlen((const char *)qname) + 1];
60     qinfo->qtype = htons(1);           // Type A
61     qinfo->qclass = htons(1);         // IN (Internet)
62
63     int query_len = sizeof(struct DNS_HEADER) + (strlen((const char *)qname) + 1) + sizeof(struct QUESTION);
64
65     sendto(sockfd, buffer, query_len, 0, (struct sockaddr *)&dest, sizeof(dest));
66
67     // Receive response
68     socklen_t len = sizeof(dest);
69     int resp_len = recvfrom(sockfd, buffer, BUF_SIZE, 0, (struct sockaddr *)&dest, &len);
70

```

```
71     if (resp_len < 0) {
72         printf("No response received.\n");
73         return 1;
74     }
75
76     unsigned char *reader = buffer + query_len;
77
78     reader += 2;    // Skip answer name pointer
79     reader += 2;    // Skip type
80     reader += 2;    // Skip class
81     reader += 4;    // Skip TTL
82     reader += 2;    // Skip data length
83
84     struct in_addr addr;
85     memcpy(&addr, reader, 4);
86
87     printf("Resolved IP: %s\n", inet_ntoa(addr));
88
89     close(sockfd);
90     return 0;
91 }
```

Last login: Sat Dec 6 23:51:16 on ttys000

[moshika@Moshikas-MacBook-Air ~ % cd desktop

moshika@Moshikas-MacBook-Air desktop % gcc dns_client.c -o dns_client
./dns_client

Enter hostname: google.com

Resolved IP: 142.251.221.206

moshika@Moshikas-MacBook-Air desktop %