Status	Finished
Started	Saturday, 10 October 2026, 10:59 AM
Completed	Saturday, 10 October 2026, 11:04 AM
Duration	5 mins 4 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Select which is true for Python tuple?

a. We can change the tuple once created

b. None of these

c. A tuple is unordered

d. A tuple maintains the order of items ✓

Question **2**

Correct

Mark 1.00 out of 1.00

What is the output of the following set operation

```
sampleSet = {"Yellow", "Orange", "Black"}
sampleSet.update(["Blue", "Green", "Red"])
print(sampleSet)
```

a. Name Error

b. {'Yellow', 'Orange', 'Black', ["Blue", "Green", "Red"]}

c. {'Yellow', 'Orange', 'Red', 'Black', 'Green', 'Blue'} ✓

d. TypeError: update() doesn't allow list as a argument.

Question **3**

Correct

Mark 1.00 out of 1.00

What will be the output of the below Python code?

t1=(55,12,78,64,25)

t1.pop(12)

print(tuple1)

- a. (55,78,64,25)
- b. (12)
- c. 12
- d. Error ✓

Question **4**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

t = (11, 3)

x = 3 * t

print(x)

- a. [11,11,11,3,3,3]
- b. (11,3)(11,3)(11,3)
- c. (11, 3, 11, 3, 11, 3) ✓
- d. (11,3,11,11,3,11,11,11,3)

Question **5**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

```
t1 = (1,2,3,(4,5))
t2 = (3,2,1,(4,5))
print(t1>t2)
```

- a. Error
- b. True
- c. False ✓
- d. Error

Question **6**

Correct

Mark 1.00 out of 1.00

Which of the following options will not result in an error when performed on tuples in Python where tupl=(5,2,7,0,3)?

- a. tupl[1]=2
- b. tupl.append(2)
- c. tupl1=tupl+tupl ✓
- d. tupl.sort()

Question **7**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
set1={2,5,3}

set2={3,1}

set3={}

set3=set1&set2

print(set3)
```

- a. {3} ✓
- b. {2,5,1}
- c. {}
- d. {2,5,3,1}

Question **8**

Correct

Mark 1.00 out of 1.00

What is the output of the following

```
set1 = {1, 2, 3, 4, 5}
set2 = {6, 7, 1, 3, 4, 8, 2, 5}

print(set1.issubset(set2))
print(set2.issuperset(set1))
```

a. False
True

b. True
False

c. True ✓
True

d. False
False

Question **9**

Correct

Mark 1.00 out of 1.00

If a=(15,16,17,18,19,25), then a[1:-1] will be

Note :

a=(15,16,17,18,19,25)

print((a[1:-1]))

a. (16,17,18)

b. (25,19,18,17)

c. Error

d. (16,17,18,19) ✓

Question **10**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
set1={0,0,9}

print(set1)
```

- a. {0,9} ✓
- b. {9}
- c. {0,0,9}
- d. It will throw an error as there are two 0 while creating the set.

Question **11**

Correct

Mark 1.00 out of 1.00

What is the output of the following

```
set1 = {10, 20, 30, 40, 50}
set2 = {60, 70, 10, 30, 40, 80, 20, 50}

print(set1.issubset(set2))
print(set2.issuperset(set1))
```

- a. False
  False
- b. True ✓
  True
- c. False
  True
- d. True
  False

Question **12**

Correct

Mark 1.00 out of 1.00

What will the below Python code do?

```
set1={2,3}

set2={3,2}

set3={2,1}

if(set1==set2):

    print("yes")

else:

    print("no")

if(set1==set3):

    print("yes")

else:

    print("no")
```

a. "==" is not supported for set in Python

b. Yes, Yes

c. No, No

d. Yes, No ✓

Question **13**

Correct

Mark 1.00 out of 1.00

Which of the following Python code will create a set?

(i) set1=set((0,9,0))
(ii) set1=set([0,2,9])
(iii) set1={}

a. All of the above

b. ii

c. i,ii ✓

d. iii

Question **14**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

```
t1 = (55, 44, 33, 22, 11)
x = [t1[i] for i in range(0, len(t1), 2)]
print(x)
```

a. ([55,33,11])

b. [(55,33,11)]

c. [55, 33, 11] ✓

d. (55,33,11)

Question **15**

Correct

Mark 1.00 out of 1.00

Write the Output of the following Code?

```
t = (15,83,83,52,60,45,52,85,100)
print(min(t)+max(t)+t.count(52))
```

a. 2

b. Error

c. 117 ✓

d. 100