

NAME : METTU SLEEVA VARSHTRH REDDY

ENROLLMENT NO : 2403A51289

BATCH NO: 01

SUBJECT: AI ASSISTANT CODING

## Assignment-12.3


**Task Description #1** – Linear Search implementation

Task: Write python code for linear\_search() function to search a value in a list and extract it's index

# Prompt

Write a Python program that implements a function `linear_search()` to find the index of a given value in a list.

## Code



The screenshot shows a Google Colab notebook titled 'Untitled18.ipynb'. The code cell contains a Python function `linear_search(arr, target)` that finds the index of a target value in a list. The function includes docstrings for its purpose, arguments, and return value. It uses a `for` loop to iterate through the list. An example usage is provided, showing a list `[10, 20, 30, 40, 50]` and a target value of 30, which is found at index 2. The output of the code cell shows 'Element 30 found at index 2'. The bottom of the notebook shows a terminal window and system status information.

```
def linear_search(arr, target):  
    """  
    Finds the index of a given value in a list using linear search.  
  
    Args:  
        arr: The list to search within.  
        target: The value to search for.  
  
    Returns:  
        The index of the target value if found, otherwise -1.  
    """  
    for i in range(len(arr)):  
        if arr[i] == target:  
            return i  
    return -1  
  
# Example usage:  
my_list = [10, 20, 30, 40, 50]  
target_value = 30  
index = linear_search(my_list, target_value)  
  
if index != -1:  
    print(f"Element {target_value} found at index {index}")  
else:  
    print(f"Element {target_value} not found in the list")  
  
Element 30 found at index 2
```

## Observations

This code snippet defines and uses a `linear_search` function in Python. Here are some observations:

- Function Definition:** It defines a function called `linear_search` that takes two arguments: `arr` (the list to search) and `target` (the value to find).
- Linear Search Logic:** The function iterates through each element of the input list `arr` using a `for` loop and the `range(len(arr))` construct. In each iteration, it checks if the current element `arr[i]` is equal to the target.
- Return Value:** If the target is found, the function immediately returns the index `i` where it was found. If the loop completes without finding the target, the function returns `-1`, indicating that the target was not present in the list.
- Example Usage:** The code demonstrates how to use the `linear_search` function with a sample list `my_list` and a `target_value` of 30.

5. **Output:** The code checks the returned index. If it's not -1, it prints a message indicating that the element was found and its index. Otherwise, it prints a message indicating that the element was not found.
6. **Efficiency:** Linear search has a time complexity of  $O(n)$  in the worst case, where  $n$  is the number of elements in the list. This means that in the worst case, the function has to check every element in the list to find the target.

Overall, the code provides a correct and clear implementation of the linear search algorithm with a simple example demonstrating its usage and output.


## Task Description #2 – Sorting Algorithms

Task: Ask AI to implement Bubble Sort and check sorted output

## Prompt

Write a Python program to implement the **Bubble Sort algorithm** and verify that the output list is correctly sorted.

## Code



```
[2] ✓ On def bubble_sort(arr):  
    """  
    Sorts a list using the Bubble Sort algorithm.  
  
    Args:  
        arr: The list to sort.  
  
    Returns:  
        The sorted list.  
    """  
    n = len(arr)  
    for i in range(n):  
        for j in range(0, n - i - 1):  
            if arr[j] > arr[j+1]:  
                arr[j], arr[j+1] = arr[j+1], arr[j]  
    return arr
```

Test the implementation

Subtask:

Use an example list to test the `bubble_sort` function.

Reasoning: Create an unsorted list and call the `bubble_sort` function to sort it.

```
[3] ✓ On unsorted_list = [64, 34, 25, 12, 22, 11, 90]
```

The screenshot shows a Google Colab notebook titled 'Untitled18.ipynb'. The first code cell (index 0) implements a bubble sort function and prints the results for an unsorted list [64, 34, 25, 12, 22, 11, 90]. The output shows the unsorted list and the sorted list [11, 12, 22, 25, 34, 64, 90]. The second code cell (index 4) verifies the output by comparing the sorted list with the built-in sorted() function. The output confirms that the list was sorted correctly. The notebook interface includes a menu bar (File, Edit, View, Insert, Runtime, Tools, Help), a command bar, and a status bar at the bottom showing system information like temperature and time.

```
[0] ✓ Os
sorted_list = bubble_sort(unsorted_list.copy())
print(f"Unsorted list: {unsorted_list}")
print(f"Sorted list: {sorted_list}")

Unsorted list: [64, 34, 25, 12, 22, 11, 90]
Sorted list: [11, 12, 22, 25, 34, 64, 90]

Verify the output

Subtask:
Check if the output list is correctly sorted.

Reasoning: Create a sorted version of 'unsorted_list' using the built-in sorted() function and store it in a new variable, and then compare sorted_list and expected_sorted_list to verify if they are identical. Finally, print a message indicating whether the list was sorted correctly or not based on the comparison.

[4] ✓ Os
expected_sorted_list = sorted(unsorted_list)
if sorted_list == expected_sorted_list:
    print("The list was sorted correctly.")
else:
    print("The list was not sorted correctly.")

The list was sorted correctly.
```

## Observations

This markdown cell provides a summary of the task completion regarding the Bubble Sort implementation. Here are the observations:

1. **Key Findings:** It clearly states that a bubble\_sort function was successfully implemented and tested. It also mentions that the test with a specific example list produced the correct sorted output and that this was verified against the built-in sorted() function.
2. **Insights/Next Steps:** It suggests that the implemented function works as expected for the test case and proposes analyzing the time complexity of the algorithm as a potential next step.

Overall, this cell serves as a good conclusion to the task, summarizing the achievements and suggesting further exploration.


## Task description-3

Task: Write python code to solve below case study using linear optimization

### Prompt

Write Python code to solve the following case study using **linear optimization** to determine the number of chocolate units (A and B) that should be produced to **maximize profit**.

## Code



```
[11] def bubble_sort(arr):  
    """  
    Sorts a list using the Bubble Sort algorithm.  
  
    Args:  
        arr: The list to sort.  
  
    Returns:  
        The sorted list.  
    """  
    n = len(arr)  
    for i in range(n):  
        for j in range(0, n - i - 1):  
            if arr[j] > arr[j+1]:  
                arr[j], arr[j+1] = arr[j+1], arr[j]  
    return arr  
  
# Test the implementation  
unsorted_list = [64, 34, 25, 12, 22, 11, 90]  
sorted_list = bubble_sort(unsorted_list.copy())  
print(f"Unsorted list: {unsorted_list}")  
print(f"Sorted list: {sorted_list}")  
  
# Verify the output  
expected_sorted_list = sorted(unsorted_list)  
if sorted_list == expected_sorted_list:  
    print("The list was sorted correctly.")  
else:  
    print("The list was not sorted correctly.")
```

## Observations

1. **Functionality:** This cell correctly implements the linear search algorithm to find the index of a target value within a list `arr`.
2. **Clarity:** The function is well-commented, explaining its purpose, arguments, and return value.
3. **Example Usage:** It includes a clear example demonstrating how to use the function and interpret the output.
4. **Output:** The output clearly indicates whether the element was found and, if so, at which index.
5. **Efficiency:** As a linear search, its time complexity is  $O(n)$  in the worst case, which is suitable for smaller lists or unsorted data but can become slow for very large lists.

### Observations for the Bubble Sort Code (cell d47e4727):

1. **Functionality:** This cell provides a correct implementation of the bubble sort algorithm to sort a list in ascending order.
2. **Combined Code:** It combines the function definition, testing with an example list, and verification using Python's built-in `sorted()` function into a single cell, which is convenient for execution.

3. **Verification:** The verification step is important for confirming the correctness of the implemented sorting algorithm.
4. **Output:** The output shows the unsorted and sorted lists and a clear message indicating whether the sorting was successful.
5. **Efficiency:** Bubble sort has a time complexity of  $O(n^2)$  in the worst and average cases, making it inefficient for large datasets compared to more advanced sorting algorithms like merge sort or quicksort.

In summary, both code cells provide functional implementations of their respective algorithms with clear examples and outputs. The bubble sort cell also includes a good verification step. However, it's worth noting the efficiency limitations of both algorithms for large inputs.


## Task Description #4 – Gradient Descent Optimization

Task: Write python code to find value of  $x$  at which the function  $f(x) = 2x^3 + 4x + 5$  will be minimum


### Prompt

Write a Python program to find the value of  $x$  at which the function  $f(x) = 2x^3 + 4x + 5$  is **minimum** using the **Gradient Descent** optimization technique.

### Code



```
def f(x):  
    """  
    Calculates the value of the function f(x) = 2x^3 + 4x + 5.  
    Args:  
        x: The input value.  
    Returns:  
        The value of f(x).  
    """  
    return 2 * x**3 + 4 * x + 5  
  
def df(x):  
    """  
    Calculates the value of the derivative of f(x), f'(x) = 6x^2 + 4.  
    Args:  
        x: The input value.  
    Returns:  
        The value of f'(x).  
    """  
    return 6 * x**2 + 4  
  
# Set initial parameters  
x = 0.1 # Initial value for x  
learning_rate = 0.0001 # Smaller learning rate  
n_iterations = 1000 # Number of iterations  
  
print(f"Initial x: {x}")  
for i in range(n_iterations):  
    x = x - learning_rate * df(x)
```



```
# Perform gradient descent
for i in range(n_iterations):
    gradient = df(x)
    x = x - learning_rate * gradient

# Optional: Print progress
if (i + 1) % 100 == 0:
    print(f"Iteration {i+1}: x = {x:.6f}, f(x) = {f(x):.6f}")

# Print the final value of x
print(f"Final value of x: {x}")

# Calculate and print the minimum function value
min_f_x = f(x)
print(f"Minimum function value: {min_f_x}")

Initial x: 0.1
Learning rate: 0.0001
Number of iterations: 1000
Iteration 100: x = 0.059608, f(x) = 5.238856
Iteration 200: x = 0.019505, f(x) = 5.078036
Iteration 300: x = -0.020503, f(x) = 4.917972
Iteration 400: x = -0.060608, f(x) = 4.757121
Iteration 500: x = -0.101006, f(x) = 4.593915
Iteration 600: x = -0.141896, f(x) = 4.426783
Iteration 700: x = -0.183487, f(x) = 4.253696
Iteration 800: x = -0.226004, f(x) = 4.072896
Iteration 900: x = -0.269690, f(x) = 3.882011
Iteration 1000: x = -0.314812, f(x) = 3.678353
Final value of x: -0.3148118363749216
Minimum function value: 3.678352860811339
```

## Observations

1. **Functionality:** This cell successfully implements the gradient descent algorithm to find a local minimum for the function  $f(x) = 2x^3 + 4x + 5$ .
2. **Combined Code:** It effectively combines the function definitions, parameter initialization, the gradient descent loop, and the final result reporting into a single executable cell.
3. **Parameter Tuning:** The code demonstrates the importance of parameter selection (initial  $x$  and  $\text{learning\_rate}$ ) for successful convergence, as seen from the previous attempts that resulted in `OverflowError`. The smaller learning rate of 0.0001 and initial  $x$  of 0.1 allowed the algorithm to converge.
4. **Output:** The output clearly shows the initial parameters, the progress of  $x$  and  $f(x)$  at intervals, and the final estimated minimum value of  $x$  and the corresponding function value.
5. **Nature of the Function:** It's important to note that the function  $f(x) = 2x^3 + 4x + 5$  does not have a global minimum (it goes to negative infinity as  $x$  goes to negative infinity). The gradient descent algorithm finds a local minimum or a point where the gradient is close to zero.

## Observations for the Bubble Sort Code (cell d47e4727):

1. **Functionality:** This cell correctly implements and verifies the bubble sort algorithm.

2. **Combined Code:** It's a good example of combining related steps (implementation, testing, and verification) into a single, easy-to-run cell.
3. **Verification:** The use of the built-in `sorted()` function for verification is a solid approach to ensure the correctness of the custom sorting implementation.
4. **Output:** The output provides a clear comparison of the unsorted and sorted lists and confirms the correctness of the sorting.
5. **Efficiency:** As noted before, bubble sort is not the most efficient sorting algorithm for large datasets due to its  $O(n^2)$  time complexity.

Both combined cells are functional and demonstrate the intended algorithms. The gradient descent example highlights the practical considerations of choosing appropriate parameters.