

APOLLO VALVE - 77C SERIES

Bronze Ball Valve, Full Port and Reduced Port

Rev D 2025-11

DESCRIPTION

The 77C is a two-piece bronze ball valve intended for general service in commercial plumbing and light industrial systems. The body is cast from lead-free bronze alloy C89833 and the valve carries a maximum working pressure of 400 PSI WOG at ambient temperature, falling to 125 PSI WSP in saturated steam service. Seats are reinforced PTFE. The stem is silicon bronze with a blowout-proof design. All sizes are supplied with a chrome-plated ball and a vinyl-covered lever handle unless noted otherwise below. Valves are certified to NSF/ANSI 61 and NSF/ANSI 372 for potable water and are marked accordingly. Operating temperature is rated from -20 degF to 365 degF continuous.

Torque to open at rated pressure falls between 14 and 19 ft-lb depending on size and seat wear; no single figure is published.

ORDERING INFORMATION

Catalog No	DN	Size	Port	Cv	Ctn Qty
77C-103	DN15	1/2"	Full	15.0	24
77C-104	DN20	3/4"	Full	28.0	20
77C-105	DN25	1"	Full	49.0	12
77C-105R	DN25	1"	Reduced	21.0	12
77C-106	DN32	1-1/4"	Full	88.0	6
77C-106R	DN32	1-1/4"	Reduced	37.0	6

NOTE 1: Sizes DN25 and larger are furnished with a tee handle in place of the lever handle described above.

NOTE 2: Catalog No 77C-102 (DN10) is discontinued and superseded by 77C-103. Do not order.

NOTE 3: Reduced port valves carry the same pressure rating but a lower Cv. Confirm flow requirements before substituting.

Country of origin: Taiwan.

Weights and packaging data available on request.