

Skill Week - 8

1.To Parse Combined Redirection, Duplicate File Descriptors, Merge Streams, Verify Ordering, Handle Edge Cases, Test Integrated Outputs

```
varshithcomple@MSI123: ~ × + ∨  
GNU nano 8.7.1 src/combined_redirect.c *  
  
#include <stdio.h>  
#include <fcntl.h>  
#include <unistd.h>  
  
int main() {  
    int fd;  
  
    fd = open("combined.txt",  
             O_WRONLY | O_CREAT | O_TRUNC, 0644);  
  
    if (fd < 0) {  
        perror("open");  
        return 1;  
    }  
  
    // Redirect stdout to file  
    dup2(fd, STDOUT_FILENO);  
  
    // Redirect stderr to same file  
    dup2(STDOUT_FILENO, STDERR_FILENO);  
  
    close(fd);  
  
    printf("This is standard output.\n");  
    fprintf(stderr, "This is standard error.\n");  
    printf("Output comes before the next error.\n");  
    fprintf(stderr, "This is another error message.\n");  
  
    fflush(stdout);  
    fflush(stderr);  
  
    return 0;  
}
```

Output:

```
varshithcomple@MSI123:~$ gcc src/combined_redirect.c -o bin/combined_redirect  
varshithcomple@MSI123:~$ ./bin/combined_redirect  
varshithcomple@MSI123:~$ cat combined.txt  
This is standard error.  
This is another error message.  
This is standard output.  
Output comes before the next error.
```

2.To Parse Complex Commands, Combine Pipes and Redirections, Resolve Execution Order, Validate Syntax, Generate Execution Plans, Test Scenarios

```
varshithcomple@MSI123: ~ × + ∨  
GNU nano 8.7.1 src/command_parser.c *  
  
#include <stdio.h>  
#include <string.h>  
  
int main() {  
    char input[200];  
    char copy[200];  
    char *cmd;  
    int count = 0;  
  
    printf("Enter command: ");  
    fgets(input, sizeof(input), stdin);  
  
    input[strcspn(input, "\n")] = '\0';  
  
    if (strlen(input) == 0) {  
        printf("Invalid command.\n");  
        return 1;  
    }  
  
    strcpy(copy, input);  
  
    printf("\nExecution Plan:\n");  
  
    cmd = strtok(copy, "|");  
  
    while (cmd != NULL) {  
        count++;  
        printf("Command %d: %s\n", count, cmd);  
        cmd = strtok(NULL, "|");  
    }  
  
    if (strstr(input, ">") != NULL)  
        printf("Output redirection detected.\n");  
  
    if (strstr(input, "<") != NULL)  
        printf("Input redirection detected.\n");  
  
    if (strstr(input, "2>") != NULL)  
        printf("Error redirection detected.\n");  
  
    if (strchr(input, '|') != NULL)  
        printf("Pipe detected.\n");  
  
    printf("Total commands: %d\n", count);  
    printf("Execution order: Left to Right.\n");  
  
    return 0;  
}
```

Output:

```
varshithcomple@MSI123:~$ gcc src/command_parser.c -o bin/command_parser
varshithcomple@MSI123:~$ ./bin/command_parser
Enter command: ls | grep .c > result.txt
```

```
Execution Plan:
Command 1: ls
Command 2: grep .c > result.txt
Output redirection detected.
Pipe detected.
Total commands: 2
Execution order: Left to Right.
varshithcomple@MSI123:~$ ./bin/command_parser
Enter command: ls | grep .c
```

```
Execution Plan:
Command 1: ls
Command 2: grep .c
Pipe detected.
Total commands: 2
Execution order: Left to Right.
varshithcomple@MSI123:~$ ./bin/command_parser
Enter command: cat < input.txt | grep Hello
```

```
Execution Plan:
Command 1: cat < input.txt
Command 2: grep Hello
Input redirection detected.
Pipe detected.
Total commands: 2
Execution order: Left to Right.
varshithcomple@MSI123:~$ ./bin/command_parser
Enter command: ls 2> errors.txt
```

```
Execution Plan:
Command 1: ls 2> errors.txt
Output redirection detected.
Error redirection detected.
Total commands: 1
Execution order: Left to Right.
```

3.To Detect Background Jobs, Launch Non-Blocking Processes, Return Prompt Immediately, Store Job Information, Monitor Execution, Test Background Tasks

```
varshithcomple@MSI123: ~ × + ∨
```

```
GNU nano 8.7.1 src/background_jobs.c *
```

```

#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <sys/wait.h>
#include <string.h>

int main() {
char command[100];
pid_t pid;

printf("myshell> ");
fgets(command, sizeof(command), stdin);
command[strcspn(command, "\n")] = '\0';

int len = strlen(command);

// Check for background operator &
if (len > 0 && command[len - 1] == '&') {
command[len - 1] = '\0';

pid = fork();

if (pid < 0) {
perror("fork");
return 1;
}

if (pid == 0) {
printf("Background job started. PID: %d\n", getpid());

sleep(5);

printf("Background job completed. PID: %d\n", getpid());
exit(0);
}

printf("[1] Background job PID: %d\n", pid);
printf("myshell> Prompt returned immediately.\n");

sleep(1);

if (waitpid(pid, NULL, WNOHANG) == 0)
printf("Job is still running.\n");

sleep(5);

waitpid(pid, NULL, 0);
printf("Job completed.\n");
} else {
printf("Foreground command detected.\n");
}

return 0;
}

```

Output:

```
varshithcomple@MSI123:~$ cd ~/OS_Skill/Skill-Week-8
nano src/background_jobs.c
varshithcomple@MSI123:~$ gcc src/background_jobs.c -o bin/background_jobs
varshithcomple@MSI123:~$ ./bin/background_jobs
myshell> sleep 10 &
[1] Background job PID: 1269
myshell> Prompt returned immediately.
Background job started. PID: 1269
Job is still running.
Background job completed. PID: 1269
Job completed.
```

4.To Create Job Table, Store Process Groups, Track States, Update Status, Remove Completed Jobs, Validate Job Records

varshithcomple@MSI123: ~ × + ∨

GNU nano 8.7.1 src/job_table.c *

```
#include <stdio.h>
#include <unistd.h>
#include <sys/wait.h>

#define MAX_JOBS 5

typedef struct {
    int job_id;
    pid_t pid;
    pid_t pgid;
    char state[20];
} Job;

Job jobs[MAX_JOBS];
int job_count = 0;

void add_job(pid_t pid) {
    jobs[job_count].job_id = job_count + 1;
    jobs[job_count].pid = pid;
    jobs[job_count].pgid = pid;
    snprintf(jobs[job_count].state, 20, "Running");
    job_count++;
}

void show_jobs() {
    printf("\nJob Table:\n");

    for (int i = 0; i < job_count; i++) {
        printf("[%d] PID=%d PGID=%d State=%s\n",
            jobs[i].job_id,
            jobs[i].pid,
            jobs[i].pgid,
            jobs[i].state);
    }
}

int main() {
    pid_t pid;

    pid = fork();

    if (pid == 0) {
        setpgid(0, 0);
        sleep(3);
    }
}
```

varshithcomple@MSI123: ~ × + ∨

GNU nano 8.7.1 src/job_table.c *

```

return 0;
}

add_job(pid);
show_jobs();

sleep(1);

if (waitpid(pid, NULL, WNOHANG) == 0)
printf("\nJob is still running.\n");

waitpid(pid, NULL, 0);

for (int i = 0; i < job_count; i++) {
if (jobs[i].pid == pid) {
snprintf(jobs[i].state, 20, "Completed");
}
}

show_jobs();

// Remove completed job
for (int i = 0; i < job_count; i++) {
if (jobs[i].pid == pid) {
for (int j = i; j < job_count - 1; j++)
jobs[j] = jobs[j + 1];

job_count--;
break;
}
}

printf("\nAfter removing completed job:\n");
show_jobs();

return 0;
}

```

Output:

```

varshithcomple@MSI123:~$ nano src/job_table.c

varshithcomple@MSI123:~$ gcc src/job_table.c -o bin/job_table
varshithcomple@MSI123:~$ ./bin/job_table

Job Table:
[1] PID=1423 PGID=1423 State=Running

Job is still running.

Job Table:
[1] PID=1423 PGID=1423 State=Completed

After removing completed job:

Job Table:

```