

1

```
#include <stdio.h>

int main()
{
    printf("Welcome to operating systems\n");
    return 0;
}
```

```
varshithreddy@Sai:~$ nano hello3.c
varshithreddy@Sai:~$ gcc hello3.c -o hello3
varshithreddy@Sai:~$ ./hello3
Welcome to operating systems
varshithreddy@Sai:~$
```

2

```
GNU nano 8.7.1 hello4.c *
#include <stdio.h>

int main()
{
    char name[30];

    printf("Enter your name: ");
    scanf("%s", name);

    printf("Welcome %s\n", name);

    return 0;
}
```

```
varshithreddy@Sai:~$ nano hello4.c
varshithreddy@Sai:~$ gcc hello4.c -o hello4
varshithreddy@Sai:~$ ./hello4
Enter your name: sai
Welcome sai
varshithreddy@Sai:~$
```

3

```

GNU nano 0.7.1
#include <stdio.h>
#include <unistd.h>

int main()
{
    printf("ProcessID=%d\n", getpid());

    return 0;
}|

```

```

varshithreddy@Sai:~$ nano hello5.c
varshithreddy@Sai:~$ gcc hello5.c -o hello5
varshithreddy@Sai:~$ ./hello5
ProcessID=714
varshithreddy@Sai:~$ |

```

4

```

#include <stdio.h>
#include <unistd.h>

int main() {
    fork();
    printf("Hello\n");

    printf("Hello\n");

    return 0;
}|

```

```

varshithreddy@Sai:~$ nano hello6.c
varshithreddy@Sai:~$ gcc hello6.c -o hello6
varshithreddy@Sai:~$ ./hello6
Hello
Hello
Hello
Hello
varshithreddy@Sai:~$ |

```