Name:Varssini.A Register No:250701811 Experiment Name:Handling Missing and Inappropriate Data in a Dataset

```
import numpy as np
import pandas as pd
df = pd.read_csv("Hotel_Dataset.csv")
print("--- Initial Duplicate Identification ---")
print(df.duplicated())
print("\n--- Dataframe Info Summary ---")
df.info()
df.drop_duplicates(inplace=True)
index = np.array(list(range(0, len(df))))
df.set_index(index, inplace=True)
df.drop(["Age_Group.1"], axis=1, inplace=True)
df.CustomerID.loc[df.CustomerID < 0] = np.nan
df.Bill.loc[df.Bill < 0] = np.nan
df.EstimatedSalary.loc[df.EstimatedSalary < 0] = np.nan
df["NoOfPax"].loc[(df["NoOfPax"] < 1) | (df["NoOfPax"] > 20)] = np.nan
print("\n--- Unique Categorical Value Sets ---")
print("Age Groups:", df.Age_Group.unique())
print("Hotels:", df.Hotel.unique())
df.Hotel.replace(["Ibys"], "Ibis", inplace=True)
df.FoodPreference.replace(["Vegetarian", "veg"], "Veg", inplace=True)
df.FoodPreference.replace(["non-Veg"], "Non-Veg", inplace=True)
df.EstimatedSalary.fillna(round(df.EstimatedSalary.mean()),
inplace=True)
df.NoOfPax.fillna(round(df.NoOfPax.median()), inplace=True)
df["Rating(1-5)"].fillna(round(df["Rating(1-5)"].median()),
inplace=True)
df.Bill.fillna(round(df.Bill.mean()), inplace=True)
print("\n--- Final Cleaned Dataset (df) ---")
print(df)
```

```
--- Initial Duplicate Identification ---
0     False
1     False
2     False
3     False
4     False
5     False
6     False
7     False
8     False
9      True
10    False
dtype: bool

--- Dataframe Info Summary ---
<class 'pandas.core.frame.DataFrame'>
```

```
RangeIndex: 11 entries, 0 to 10
Data columns (total 9 columns):
 #   Column           Non-Null Count  Dtype
---  ------           --------------  -----
 0   CustomerID       11 non-null     int64
 1   Age_Group        11 non-null     object
 2   Rating(1-5)      11 non-null     int64
 3   Hotel            11 non-null     object
 4   FoodPreference   11 non-null     object
 5   Bill             11 non-null     int64
 6   NoOfPax          11 non-null     int64
 7   EstimatedSalary  11 non-null     int64
 8   Age_Group.1      11 non-null     object
dtypes: int64(5), object(4)
memory usage: 924.0+ bytes

--- Unique Categorical Value Sets ---
Age Groups: ['20-25' '30-35' '25-30' '35+']
Hotels: ['Ibis' 'LemonTree' 'RedFox' 'Ibys']

--- Final Cleaned Dataset (df) ---
   CustomerID Age_Group  Rating(1-5)      Hotel FoodPreference    Bill
\
0         1.0     20-25            4       Ibis            Veg  1300.0

1         2.0     30-35            5  LemonTree        Non-Veg  2000.0

2         3.0     25-30            6     RedFox            Veg  1322.0

3         4.0     20-25           -1  LemonTree            Veg  1234.0

4         5.0       35+            3       Ibis            Veg   989.0

5         6.0       35+            3       Ibis        Non-Veg  1909.0

6         7.0       35+            4     RedFox            Veg  1000.0

7         8.0     20-25            7  LemonTree            Veg  2999.0

8         9.0     25-30            2       Ibis        Non-Veg  3456.0

9        10.0     30-35            5     RedFox        Non-Veg  1801.0


   NoOfPax  EstimatedSalary
0      2.0          40000.0
1      3.0          59000.0
2      2.0          30000.0
3      2.0         120000.0
4      2.0          45000.0
```

```
5      2.0         122220.0
6      2.0          21122.0
7      2.0         345673.0
8      3.0          96755.0
9      4.0          87777.0

C:\Users\swath\AppData\Local\Temp\ipykernel_28208\2624405208.py:12:
FutureWarning: ChainedAssignmentError: behaviour will change in pandas
3.0!
You are setting values through chained assignment. Currently this
works in certain cases, but when using Copy-on-Write (which will
become the default behaviour in pandas 3.0) this will never work to
update the original DataFrame or Series, because the intermediate
object on which we are setting values will behave as a copy.
A typical example is when you are setting values in a column of a
DataFrame, like:

df["col"][row_indexer] = value

Use `df.loc[row_indexer, "col"] = values` instead, to perform the
assignment in a single step and ensure this keeps updating the
original `df`.

See the caveats in the documentation:
https://pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html#
returning-a-view-versus-a-copy

  df.CustomerID.loc[df.CustomerID < 0] = np.nan
C:\Users\swath\AppData\Local\Temp\ipykernel_28208\2624405208.py:12:
SettingWithCopyWarning:
A value is trying to be set on a copy of a slice from a DataFrame

See the caveats in the documentation:
https://pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html#
returning-a-view-versus-a-copy
  df.CustomerID.loc[df.CustomerID < 0] = np.nan
C:\Users\swath\AppData\Local\Temp\ipykernel_28208\2624405208.py:13:
FutureWarning: ChainedAssignmentError: behaviour will change in pandas
3.0!
You are setting values through chained assignment. Currently this
works in certain cases, but when using Copy-on-Write (which will
become the default behaviour in pandas 3.0) this will never work to
update the original DataFrame or Series, because the intermediate
object on which we are setting values will behave as a copy.
A typical example is when you are setting values in a column of a
DataFrame, like:

df["col"][row_indexer] = value

Use `df.loc[row_indexer, "col"] = values` instead, to perform the
```

```
assignment in a single step and ensure this keeps updating the
original `df`.

See the caveats in the documentation:
https://pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html#
returning-a-view-versus-a-copy

  df.Bill.loc[df.Bill < 0] = np.nan
C:\Users\swath\AppData\Local\Temp\ipykernel_28208\2624405208.py:13:
SettingWithCopyWarning:
A value is trying to be set on a copy of a slice from a DataFrame

See the caveats in the documentation:
https://pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html#
returning-a-view-versus-a-copy
  df.Bill.loc[df.Bill < 0] = np.nan
C:\Users\swath\AppData\Local\Temp\ipykernel_28208\2624405208.py:14:
FutureWarning: ChainedAssignmentError: behaviour will change in pandas
3.0!
You are setting values through chained assignment. Currently this
works in certain cases, but when using Copy-on-Write (which will
become the default behaviour in pandas 3.0) this will never work to
update the original DataFrame or Series, because the intermediate
object on which we are setting values will behave as a copy.
A typical example is when you are setting values in a column of a
DataFrame, like:

df["col"][row_indexer] = value

Use `df.loc[row_indexer, "col"] = values` instead, to perform the
assignment in a single step and ensure this keeps updating the
original `df`.

See the caveats in the documentation:
https://pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html#
returning-a-view-versus-a-copy

  df.EstimatedSalary.loc[df.EstimatedSalary < 0] = np.nan
C:\Users\swath\AppData\Local\Temp\ipykernel_28208\2624405208.py:14:
SettingWithCopyWarning:
A value is trying to be set on a copy of a slice from a DataFrame

See the caveats in the documentation:
https://pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html#
returning-a-view-versus-a-copy
  df.EstimatedSalary.loc[df.EstimatedSalary < 0] = np.nan
C:\Users\swath\AppData\Local\Temp\ipykernel_28208\2624405208.py:15:
FutureWarning: ChainedAssignmentError: behaviour will change in pandas
3.0!
You are setting values through chained assignment. Currently this
```

```
works in certain cases, but when using Copy-on-Write (which will
become the default behaviour in pandas 3.0) this will never work to
update the original DataFrame or Series, because the intermediate
object on which we are setting values will behave as a copy.
A typical example is when you are setting values in a column of a
DataFrame, like:

df["col"][row_indexer] = value

Use `df.loc[row_indexer, "col"] = values` instead, to perform the
assignment in a single step and ensure this keeps updating the
original `df`.

See the caveats in the documentation:
https://pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html#
returning-a-view-versus-a-copy

  df["NoOfPax"].loc[(df["NoOfPax"] < 1) | (df["NoOfPax"] > 20)] =
np.nan
C:\Users\swath\AppData\Local\Temp\ipykernel_28208\2624405208.py:15:
SettingWithCopyWarning:
A value is trying to be set on a copy of a slice from a DataFrame

See the caveats in the documentation:
https://pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html#
returning-a-view-versus-a-copy
  df["NoOfPax"].loc[(df["NoOfPax"] < 1) | (df["NoOfPax"] > 20)] =
np.nan
C:\Users\swath\AppData\Local\Temp\ipykernel_28208\2624405208.py:19:
FutureWarning: A value is trying to be set on a copy of a DataFrame or
Series through chained assignment using an inplace method.
The behavior will change in pandas 3.0. This inplace method will never
work because the intermediate object on which we are setting values
always behaves as a copy.

For example, when doing 'df[col].method(value, inplace=True)', try
using 'df.method({col: value}, inplace=True)' or df[col] =
df[col].method(value) instead, to perform the operation inplace on the
original object.


  df.Hotel.replace(["Ibys"], "Ibis", inplace=True)
C:\Users\swath\AppData\Local\Temp\ipykernel_28208\2624405208.py:20:
FutureWarning: A value is trying to be set on a copy of a DataFrame or
Series through chained assignment using an inplace method.
The behavior will change in pandas 3.0. This inplace method will never
work because the intermediate object on which we are setting values
always behaves as a copy.

For example, when doing 'df[col].method(value, inplace=True)', try
```

```
using 'df.method({col: value}, inplace=True)' or df[col] =
df[col].method(value) instead, to perform the operation inplace on the
original object.


  df.FoodPreference.replace(["Vegetarian", "veg"], "Veg",
inplace=True)
C:\Users\swath\AppData\Local\Temp\ipykernel_28208\2624405208.py:24:
FutureWarning: A value is trying to be set on a copy of a DataFrame or
Series through chained assignment using an inplace method.
The behavior will change in pandas 3.0. This inplace method will never
work because the intermediate object on which we are setting values
always behaves as a copy.

For example, when doing 'df[col].method(value, inplace=True)', try
using 'df.method({col: value}, inplace=True)' or df[col] =
df[col].method(value) instead, to perform the operation inplace on the
original object.


  df["Rating(1-5)"].fillna(round(df["Rating(1-5)"].median()),
inplace=True)
```