

EXP 5

OBJ 1

```
clc; clear; close all;
```

```
% SNR range
```

```
SNR_dB = 0:2:20;
```

```
SNR = 10.^(SNR_dB/10);
```

```
% MIMO parameters
```

```
Nt = 2; Nr = 2;
```

```
BER = zeros(1,length(SNR));
```

```
for i = 1:length(SNR)
```

```
bits = randi([0 1],10000,1);
```

```
symbols = 2*bits-1; % BPSK
```

```
H = (randn(Nr,Nt) + 1j*randn(Nr,Nt))/sqrt(2);
```

```
noise = (randn(Nr,10000) + 1j*randn(Nr,10000))/sqrt(2*SNR(i));
```

```
tx = H(1,1)*symbols' + noise(1,:);
```

```
rx = real(tx) > 0;
```

```
BER(i) = sum(rx' ~= bits)/length(bits);
```

```
end
```

```
figure
```

```
% ----- Graph 1: BER vs SNR -----
```

```
subplot(2,1,1)
```

```
semilogy(SNR_dB,BER,'-o','LineWidth',2)
```

```
title('MIMO BER Performance vs SNR')
```

```
xlabel('SNR (dB)')
```

```
ylabel('Bit Error Rate (BER)')
```

```
grid on
```

```
% ----- Graph 2: SNR vs Quality Indicator -----
```

```
subplot(2,1,2)
```


```
plot(SNR_dB,1-BER,'-s','LineWidth',2)
```

```
title('MIMO System Reliability vs SNR')
```

```
xlabel('SNR (dB)')
```

```
ylabel('Reliability (1 - BER)')
```

```
grid on
```



Obj 2

```
clc; clear; close all;
```

```
% SNR range (dB)
```

```
SNR_dB = 0:2:20;
```

```
SNR = 10.^(SNR_dB/10);
```

```
% MIMO parameters
```

```
Nt = 2; Nr = 2;
```

```
% Simulated reliability metric (inverse BER model)
```

```
Reliability = zeros(1,length(SNR));
```

```
for i = 1:length(SNR)
```

```
% simple channel model effect
```

```
H = (randn(Nr,Nt) + 1j*randn(Nr,Nt))/sqrt(2);
```

```
noise_power = 1/SNR(i);
```

```
% reliability increases with SNR
```

```
Reliability(i) = 1 - exp(-SNR(i)/10);
```

```
end
```

```
figure
```

```
% ----- Graph 1: SNR vs Reliability -----
```

```
subplot(2,1,1)
```

```
plot(SNR_dB, Reliability, '-o', 'LineWidth', 2)
```

```
title('MIMO Reliability vs SNR')
```

```
xlabel('SNR (dB)')
```

```
ylabel('Reliability (0 to 1)')
```

```
grid on
```

```
% ----- Graph 2: SNR vs Noise Effect -----
```

```
subplot(2,1,2)
```


```
plot(SNR_dB, noise_power*ones(size(SNR_dB)), '-s', 'LineWidth', 2)
```

```
title('Noise Power Variation with SNR')
```

```
xlabel('SNR (dB)')
```

```
ylabel('Noise Power')
```

```
grid on
```



Obj 3

clc; clear; close all;

% Resource Block parameters

rb_bw = 180e3; % 180 kHz per RB

% Users

users = 1:5;

% Allocated Resource Blocks per user

alloc_RB = [10 12 8 15 5];

% Modulation efficiency (bits/symbol)

mod_eff = [2 4 6 4 2]; % QPSK, 16QAM, 64QAM etc.

% Throughput calculation (Mbps)

throughput = (alloc_RB .* rb_bw .* mod_eff) / 1e6;

% Display results

disp('User Throughput (Mbps):')

disp(throughput')

figure

% ----- Graph 1: Throughput per User -----

subplot(2,1,1)

plot(users, throughput, '-o','LineWidth',2)

title('OFDMA User Throughput')

xlabel('User Index')

ylabel('Throughput (Mbps)')

grid on

% ----- Graph 2: RB vs Throughput -----

subplot(2,1,2)

plot(alloc_RB, throughput, '-s','LineWidth',2)

title('Resource Blocks vs Throughput')

xlabel('Allocated Resource Blocks')

ylabel('Throughput (Mbps)')

grid on

