

TVASTRI · ENGINEERING

GARAGEST

Developer Handbook



Living Engineering Reference

Flutter + Spring Boot + PostgreSQL + Cloudflare R2

Version / date: 2026-09-30

Architecture baseline: Workflow + Trip/Navigation change (V61)

Source of truth: GARAGEST_DEVELOPER_HANDBOOK.md

Document status

Status: Living document — describes the system **as implemented** after the 2026-09-30 workflow + trip/navigation change.

Source of truth: `GARAGEST_DEVELOPER_HANDBOOK.md` (backend repo root). This PDF is a rendering of that file; if they differ, the Markdown file and the code win.

Secrets: none. Only environment variable *names* are documented.

System summary

GarageST runs a vehicle-service garage end to end: Booking → Pickup → Job Card → Inspection → Estimate → Customer approval → **Manager confirmation** → Repair → Quality check → Invoice → Payment → Delivery → Close. Flutter app (customers, staff, drivers) → REST `/api/v1` and STOMP `/ws` → Spring Boot 4.0.7 (Java 17) → PostgreSQL (Flyway). Media bytes go directly to a private Cloudflare R2 bucket via presigned URLs. Routing: Google Routes (when configured) with OSRM fallback. Hosting: Render (Docker).

How to read this document

Status labels used throughout: **Implemented** · **Legacy** (kept for compatibility) · **Declared-only** (enum/column exists, nothing writes it) · **Not implemented** · **Config-dependent** · **Manual-only** (needs a device). Sections marked `landscape` in the contents use landscape pages for wide tables.

Table of contents

1. Project Overview
2. Repository Structure
3. Technology Stack
4. System Architecture
5. Flutter Architecture
6. Backend Architecture
7. Security
8. Who Owns the State
9. State Machines `landscape`
10. JobCard vs RepairTask
11. Customer Approval vs Manager Confirmation
12. Guided Workflow Engine
13. Backend Service Ownership `landscape`
14. Workflow Coupling Rules `landscape`
15. Booking Architecture
16. Pickup Architecture (deep)
17. Delivery Architecture (deep)
18. Delivery Location
19. Navigation Architecture
20. OTP Architecture
21. Trip ↔ Booking ↔ JobCard Relationships
22. Customer Journey Logic
23. Media Architecture
24. Trip Media vs JobCard Media
25. Database Architecture
26. Flyway Migrations
27. API Reference (business-critical) `landscape`
28. WebSocket Architecture
29. Flutter Screen / Route Map `landscape`
30. Key Code Paths
31. Sequence Diagrams
32. Error Handling `landscape`
33. Transaction Boundaries
34. Legacy Compatibility Matrix `landscape`
35. Deployment Runbook
36. Render, Cloudflare R2 and Environment
37. Testing Strategy and Test Evidence
38. Manual Test Matrix `landscape`
39. Debugging Runbook
40. Architectural Rules — DO NOT BREAK THESE
41. Architecture Decision Records
42. Change Log
43. How to Maintain This Handbook

1. Project Overview

GarageST runs a vehicle-service garage end to end: a customer books a service (optionally with pickup), the garage inspects, estimates, repairs, invoices and delivers; drivers move the vehicle with live navigation, OTP handover and photo evidence.

- **Users (roles):** Owner, Manager, Service Advisor, Technician, Driver, Accountant, Cashier, Customer (`RoleCode` on the backend, `UserRole` in Flutter; Flutter intentionally omits `SUPER_ADMIN / USER`).
- **Capabilities:** booking, job-card workflow (inspection → estimate → approval → repair → QC → invoice → payment → delivery), pickup and delivery trips with live map, OTP-verified handover, evidence photos/videos, customer portal with live vehicle journey.
- **Runtime:** Flutter (Android is the tested target; iOS parked) → REST `/api/v1` + STOMP `/ws` → Spring Boot → PostgreSQL. Media bytes go straight to Cloudflare R2. Hosting: Render (Docker).

2. Repository Structure

Repo	Layout
Flutter	<code>lib/app</code> (composition root <code>app.dart</code> , <code>routes/</code> , <code>splash</code>) · <code>lib/core</code> (<code>ApiClient</code> , <code>EnvConfig</code> , secure storage, <code>location/geocoding</code> , <code>utils</code>) · <code>lib/features/<feature>/{models, services, screens, state, widgets}</code> · <code>lib/shared</code> · <code>android/app/src/main/kotlin/com/garagest/app</code> (<code>MainActivity</code> , <code>EvidenceVideoProcessor</code>) · <code>test/</code> mirrors <code>lib/</code>
Backend	<code>src/main/java/com/garageos/core</code> (<code>enums</code> , <code>exceptions</code> , <code>security</code> , <code>audit base</code>) · <code>modules/<module>/{controller, service(+impl), repository, entity, dto, mapper, validator}</code> · <code>src/main/resources/db/migration</code> (<code>Flyway</code>) · <code>Dockerfile</code>

Flutter features that matter here: `workflow`, `jobcard`, `estimate`, `repair`, `booking`, `navigation`, `handover`, `media`, `customer_portal`, `auth`. Backend modules: `serviceworkflow`, `jobcard`, `estimate`, `estimateitem`, `repairtask`, `jobassignment`, `qualitycheck`, `invoice`, `delivery`, `booking`, `navigation`, `handover`, `media`, `customer`, `audit`, `identity`.

3. Technology Stack

Only technologies present in the code: **Java 17**, **Spring Boot 4.0.7** (web, security, data-jpa, websocket, validation), **PostgreSQL** + **Flyway** (`spring.jpa.hibernate.ddl-auto=validate`), springdoc-openapi, AWS SDK S3 client (Cloudflare R2), Google Drive client (legacy media), **Docker** (`eclipse-temurin:17-jdk`, builds with `./mvnw clean package -DskipTests`), **Render**. **Flutter** (Dart `>=3.3.0 <4.0.0`), `provider`, `flutter_map` + `latlong2`, `google_maps_flutter`, `geolocator`, `geocoding`, `stomp_dart_client`, `video_player`, `image_picker`, `cached_network_image`, `flutter_cache_manager`. Native Android video: **Media3 Transformer 1.4.1** (declared in `android/app/build.gradle.kts`). Routing: Google Routes (when configured) with OSRM fallback. **No Kafka** anywhere.

4. System Architecture

```
Flutter —REST /api/v1 (Bearer JWT)→ Spring Boot —JPA→ PostgreSQL
|   └─ STOMP /ws (/app/location/update, /topic/trips/{id}/location) → location relay
|   └─ direct HTTPS PUT (presigned) → Cloudflare R2 (private bucket)
|   └─ Spring Boot → R2 (server-side evidence rendering)   Spring Boot → Google Routes / OSRM
```

Responsibility split: the backend owns business state, validation and authorization; Flutter renders that state and never invents it; R2 owns media bytes; PostgreSQL is the source of truth.

5. Flutter Architecture

- **Composition root:** `lib/app/app.dart` (`GarageSTApp`, one `MultiProvider`). Services take `ApiClient` in their constructor and are registered once; screens use `context.read/watch`. No screen constructs an `ApiClient`.
- **Routing:** `Routes.*` constants in `app/routes/app_routes_data.dart`; builders in `app/routes/app_router.dart`. Some screens are pushed directly (`TripEvidenceCaptureScreen`, `LocationPickerScreen`, `RegisterScreen`).
- **State:** `provider` only. `AuthState`, `WorkflowState` (deliberately a mutable bag — legacy JS port), `MediaUploadQueueService`, `LiveTripState`. Feature-local UI state stays in `StatefulWidget`s.
- **Personas:** splash redirect by role → `EmployeeHomeScreen` (Dashboard/Jobs/Customers/Vehicles tabs + "+ Workflow" FAB; technician/driver are role branches of the dashboard), `OwnerHome`, `CustomerHomeScreen`, `DriverHomeScreen`.
- **Session:** tokens in `SecureStorageService` only. Role gating in `Permissions` is presentation only (§7).

6. Backend Architecture

Controller → Service (interface + Impl) → Repository → Entity, DTOs + MapStruct mappers. Cross-module rules of thumb: a module writes its own aggregate's status; where several services write `JobCard.status` they all pass through `JobCardStatusValidator`. Orchestration lives in `ServiceWorkflowServiceImpl` (thin: it delegates to the owning services). Garage scoping is enforced in services, not only by URL.

7. Security

Authentication: JWT bearer (access token ~1 h, refresh ~7 d; configured under `security.jwt.*`). `/api/v1/auth/**`, `/api/v1/health/**` and static frontend paths are public (`SecurityConfig`); everything else needs authentication. Flutter never auto-refreshes (known gap, CLAUDE.md §5).

Authorization layers (all server-side):

Layer	Where	Examples
Role	<code>@PreAuthorize</code> on controllers	<code>WORKFLOW/JOB CARD/DELIVERY/ASSIGNMENT_OPERATIONAL_ROLES</code> = <code>MANAGER</code> , <code>SERVICE_ADVISOR</code> , <code>OWNER</code> ; <code>acceptInvoice</code> = <code>CUSTOMER</code>
Garage scoping	services	<code>JobCardServiceImpl.authorizeJobCardGarage</code> , <code>DeliveryServiceImpl.authorizeDeliveryAction</code> , <code>NavigationTripServiceImpl.requireOperationalStaffOfGarage</code> , <code>NavigationRequestServiceImpl</code>
Manager gate	<code>JobCardServiceImpl.authorizeProceedToRepair</code> (MANAGER only); <code>EstimateServiceImpl.authorizeEmployeeEstimateApproval</code> (MANAGER only, employee approval path)	repair start
Technician scope	<code>RepairTaskServiceImpl.authorizeRepairTaskAction</code>	technician may act only on their own non-cancelled assignment in their garage
Driver ownership	<code>NavigationTripServiceImpl.requireCallerIsDriver</code> / <code>getDriverTrip</code>	the <code>?driverId=</code> parameter must equal the authenticated user; driver must be an active DRIVER of the garage (<code>requireDriverOfGarage</code>)
Customer ownership	<code>HandoverServiceImpl</code> , <code>NavigationTripAccessGuard.authorizeViewer</code> , <code>EstimateServiceImpl.getOwnedCustomerEstimate</code> , portal services	not-found instead of forbidden, so existence is not leaked
OTP	<code>HandoverServiceImpl</code>	see §20
Media	<code>R2MediaStorageProvider</code>	private bucket, short-lived presigned URLs, server-generated keys

What Flutter UI gating does NOT protect: hiding a button (`Permissions.*`, `WorkflowStepDefinition.roles`, `allowedActions`) is cosmetic. Every rule that matters is re-checked by the backend; never rely on the UI to prevent an action. Several workflow endpoints have no `@PreAuthorize` and rely on service-level checks — do not assume a role check exists on a controller method without reading the service.

Secrets: environment variables only (§36). Known limitation: `application.properties` contains a default JWT secret value in source control, and `src/test/resources/application-test.properties` contains a local test DB password — move/rotate both (values are deliberately not reproduced here).

8. Who Owns the State

State	Owner (only writer of record)	Authorization of the transition
JobCard.status	JobCardServiceImpl for most; also EstimateServiceImpl (WAITING_FOR_APPROVAL, REPAIR_PENDING), RepairTaskServiceImpl / JobAssignmentServiceImpl.completeJob (REPAIR_COMPLETED), ServiceWorkflowServiceImpl.performQualityCheck (QUALITY_CHECK), QualityCheckServiceImpl, InvoiceServiceImpl, DeliveryServiceImpl (DELIVERED). All call JobCardStatusValidator.validate.	per operation (\$13)
Estimate.status	EstimateServiceImpl (DRAFT, APPROVED, REJECTED), EstimateItemServiceImpl (WAITING_FOR_APPROVAL when totals are recalculated)	customer owner for approve/reject
RepairTask.status	RepairTaskServiceImpl, JobAssignmentServiceImpl (start/complete of the linked task)	assigned technician or operational staff
JobAssignment.status	JobAssignmentServiceImpl (+ RepairTaskServiceImpl.syncLinkedJobAssignment)	assignee / assignment roles
Booking.status	BookingServiceImpl; JobCardServiceImpl.createJobCard sets COMPLETED	customer (cancel), staff (confirm/reject)
NavigationRequest.status	NavigationRequestServiceImpl (REQUESTED), NavigationTripServiceImpl (ASSIGNED, IN_PROGRESS, COMPLETED)	garage staff (assign), driver (start/complete)
NavigationTrip.status/currentLeg/arrivedAt	NavigationTripServiceImpl	the driver (requireCallerIsDriver)
VehicleHandover.status	HandoverServiceImpl	customer generates, driver verifies
Delivery.status	DeliveryServiceImpl (only DELIVERED is written)	operational roles (manual) or the driver's verified trip
workflow completedSteps / nextStep / progress	ServiceWorkflowServiceImpl.getWorkflowStatus (pure projection of JobCardStatus)	read-only
Flutter currentStep	WorkflowController (derives from backend completedSteps)	none — presentation

9. State Machines

9.1 JobCard (`JobCardStatusValidator` is the single rule set)

Current	Allowed next	Trigger / API	Actor	Owner method	Validation	Auto?
OPEN	INSPECTION_PENDING , CANCELLED	POST /workflow/{n}/inspection/start (Flutter chains it after create)	staff	<code>JobCardServiceImpl.startInspection</code> (via <code>ServiceWorkflowServiceImpl.startInspection</code>)	transition	manual (client chains)
INSPECTION_PENDING	INSPECTION_COMPLETED , CANCELLED	POST /workflow/{n}/inspection/complete (one request per complaint)	staff	<code>JobCardServiceImpl.completeInspection</code>	inspections count = complaints	manual
INSPECTION_COMPLETED	ESTIMATE_PENDING , CANCELLED	POST /workflow/{n}/estimate	staff	<code>JobCardServiceImpl.prepareEstimate</code>	transition	manual
ESTIMATE_PENDING	WAITING_FOR_APPROVAL , CANCELLED	PUT /estimates/{id} ("finish")	staff	<code>EstimateServiceImpl.updateEstimate</code> (only when job is <code>ESTIMATE_PENDING</code>)	transition	manual
WAITING_FOR_APPROVAL	REPAIR_PENDING , CANCELLED	PUT /estimates/{id}/approve	customer	<code>EstimateServiceImpl.approveEstimateCanonical</code>	ownership; estimate not already approved	manual (customer)
REPAIR_PENDING	REPAIR_IN_PROGRESS , CANCELLED	POST /workflow/{n}/repair/start (= /jobcards/{n}/repair/start)	manager	<code>JobCardServiceImpl.startRepair</code>	MANAGER role, estimate <code>APPROVED</code> , transition; idempotent	manual (manager gate)
REPAIR_IN_PROGRESS	REPAIR_COMPLETED , CANCELLED	last RepairTask completes	technician	<code>RepairTaskServiceImpl.completeRepair</code> / <code>JobAssignmentServiceImpl.completeJob</code>	all tasks <code>COMPLETED</code> ; job must be <code>REPAIR_IN_PROGRESS</code>	automatic
REPAIR_COMPLETED	QUALITY_CHECK , REPAIR_PENDING , CANCELLED	POST /workflow/{n}/quality-check	manager/ staff	<code>ServiceWorkflowServiceImpl.performQualityCheck</code>	transition	manual
QUALITY_CHECK	READY_FOR_INVOICE , REPAIR_PENDING (QC fail / rework)	POST /jobcards/{n}/quality-check/pass / /fail	staff	<code>QualityCheckServiceImpl</code>	QC body	manual
READY_FOR_INVOICE	INVOICE_GENERATED , CANCELLED	POST /workflow/{n}/invoice	staff	<code>InvoiceServiceImpl.generateInvoice</code>	transition	manual
INVOICE_GENERATED	READY_FOR_DELIVERY , CANCELLED	POST /workflow/{n}/payment	staff/customer	<code>InvoiceServiceImpl.receivePayment</code>	invoice accepted; customer ownership	manual

Current	Allowed next	Trigger / API	Actor	Owner method	Validation	Auto?
READY_FOR_DELIVERY	DELIVERED , CANCELLED	delivery trip completion (primary) or POST /deliveries (garage collection only)	driver / staff	DeliveryServiceImpl.completeDeliveryFrom Trip / createDelivery	invoice GENERATED + PAID ; see §17	automatic on trip complete
DELIVERED	CLOSED	PUT /jobcards/{n}/close (POST /workflow/{n}/close)	operational roles	JobCardServiceImpl.closeJobCard	transition	manual
CLOSED , CANCELLED	—	terminal				

Legacy source states (never written by canonical code; kept so old rows can move forward): ESTIMATE_APPROVED → REPAIR_PENDING , WORK_COMPLETED → READY_FOR_INVOICE , INVOICED/PAYMENT_PENDING/PAYMENT_COMPLETED → READY_FOR_DELIVERY . *Workflow projection* (resolveCompleted): see §12 — APPROVAL is completed only from REPAIR_IN_PROGRESS onward.

9.2 Estimate

State	How reached	Written by
DRAFT	created empty by EstimateServiceImpl.createEstimate(jobCardNumber)	EstimateServiceImpl
WAITING_FOR_APPROVAL	estimate totals recalculated after items are added	EstimateItemServiceImpl
APPROVED	customer PUT /estimates/{id}/approve (or manager path POST /workflow/{n}/estimate/approve , UI disconnected)	EstimateServiceImpl.approveEstimateCanonical
REJECTED	customer PUT /estimates/{id}/reject	EstimateServiceImpl.rejectEstimate
SENT_FOR_APPROVAL , EXPIRED	Declared-only	—

9.3 RepairTask

State	Trigger	Actor	Notes
PENDING	created on customer approval (RepairTaskServiceImpl.createRepairTasks)	system	one per authorised estimate scope
ASSIGNED	POST /job-assignments (JobAssignmentServiceImpl.assignJob)	manager/SA/owner	
IN_PROGRESS	PUT /job-assignments/{id}/start Or PUT /repair-tasks/{id}/start	assigned technician	refused unless the JobCard is REPAIR_IN_PROGRESS

State	Trigger	Actor	Notes
COMPLETED	PUT /job-assignments/{id}/complete or PUT /repair-tasks/{id}/complete	assigned technician	requires JobCard REPAIR_IN_PROGRESS; when all done the job moves to REPAIR_COMPLETED
ON_HOLD , CANCELLED	Declared-only		

9.4 JobAssignment

ASSIGNED → ACCEPTED (accept) → IN_PROGRESS (start) → COMPLETED (complete); CANCELLED via reassignment. ON_HOLD, QC_PENDING, QC_FAILED, REWORK are Declared-only. startJob requires ACCEPTED and (technician type) task ASSIGNED + job REPAIR_IN_PROGRESS, and **does not touch the JobCard**. JobAssignmentType.DRIVER is Legacy (\$34).

9.5 Booking

REQUESTED → CONFIRMED (confirmBooking, creates the PICKUP request when pickup was asked) · REQUESTED → REJECTED · REQUESTED/CONFIRMED → CANCELLED (customer) · CONFIRMED → COMPLETED **only** when a Job Card is created with that bookingId (JobCardServiceImpl.createJobCard). Trip completion does not change the booking.

9.6 NavigationRequest

State	Written when	By
REQUESTED	request created (booking confirm for PICKUP; POST /navigation/requests for DELIVERY)	NavigationRequestServiceImpl.createRequest
ASSIGNED	driver assigned	NavigationTripServiceImpl.assignDriver
IN_PROGRESS	startTrip	NavigationTripServiceImpl.setRequestStatus
COMPLETED	completeTrip	NavigationTripServiceImpl.setRequestStatus
CANCELLED	Declared-only (no cancel workflow)	—

9.7 NavigationTrip

ASSIGNED (assignDriver) → ACCEPTED (/accept) → IN_PROGRESS (/start) → COMPLETED (/complete). Sub-state: arrivedAt (/arrive), currentLeg GARAGE_TO_CUSTOMER → CUSTOMER_TO_GARAGE (pickup only, /continue, which also resets arrivedAt). CANCELLED is Declared-only.

9.8 VehicleHandover

PENDING (customer generates code) → VERIFIED (driver verifies) · PENDING → EXPIRED (10 min, 5 failed attempts, or superseded by a new code). CANCELLED is Declared-only.

9.9 Delivery

Entity states declared: `PENDING`, `READY_FOR_DELIVERY`, `DELIVERED`. **Only `DELIVERED` is ever written** (`DeliveryServiceImpl.createDelivery` / `completeDeliveryFromTrip`). One `Delivery` row per JobCard and per Invoice (unique).

10. JobCard vs RepairTask

JobCard = the overall vehicle/service lifecycle. RepairTask = one unit of repair work. RepairTask state must never be substituted for JobCard state.

- Creation: RepairTasks appear when the customer approves (`createRepairTasks`, inside the approval transaction).
- Assignment: `JobAssignment` links a technician to a task (`assignJob`); RepairTask `PENDING` → `ASSIGNED`.
- Technician start/complete: only after the manager has moved the JobCard to `REPAIR_IN_PROGRESS`; both `JobAssignmentServiceImpl.startJob` and `RepairTaskServiceImpl.startRepair` throw "A manager must proceed this Job Card to repair before a Repair Task can be started." otherwise. Completing a task requires the job to be `REPAIR_IN_PROGRESS`.
- The only task→job coupling: when **every** task of the job is `COMPLETED`, the job becomes `REPAIR_COMPLETED` (validated). Task start never changes the job.
- QC failure sends the job back to `REPAIR_PENDING`; the manager must confirm again.

11. Customer Approval vs Manager Confirmation

Customer approval does NOT equal manager confirmation.

```
Customer approves → Estimate APPROVED → RepairTasks created → JobCard REPAIR_PENDING
    (Approval step still PENDING in the workflow projection)
Manager taps "Proceed to Repair" → POST /workflow/{n}/repair/start → JobCardServiceImpl.startRepair
    → JobCard REPAIR_IN_PROGRESS → Approval step COMPLETED → Repair is the next step
```

- Authoritative gate: `JobCardServiceImpl.startRepair` — `authorizeProceedToRepair` (MANAGER), estimate must be `APPROVED`, `JobCardStatusValidator` (`REPAIR_PENDING` → `REPAIR_IN_PROGRESS`); already- `REPAIR_IN_PROGRESS` returns the current state (idempotent).
- Entry points that converge on it: `POST /workflow/{n}/repair/start`, `POST /jobcards/{n}/repair/start`, Job Card screen action `start_repair` (hidden from non-managers by `JobCardProjectionServiceImpl`).
- The pending state is *not* a new JobCard status: it is `REPAIR_PENDING` interpreted by the projection (ADR-004).

12. Guided Workflow Engine

Flutter: `WorkflowShellScreen` (`_steps()`): search, job, inspection, completed [SA only], estimate, estimateItems, estimateSummary, approval, repair, quality, invoice, payment, delivery — 12 visible for a manager), `WorkflowStepDefinition(id, roles, screenBuilder)`, `WorkflowController`, `WorkflowState`, `WorkflowService`.

Backend projection: `GET /workflow/{n}/status` → `WorkflowStatusResponse{jobCardNumber, status, nextStep, progress, completedSteps}` from `ServiceWorkflowServiceImpl.getWorkflowStatus` (`resolveCompleted`, `resolveStep`, `resolveProgress`). `completedSteps` per job status (each row also contains everything above it):

JobCard status	completedSteps adds
any	CUSTOMER, VEHICLE, JOB_CARD
INSPECTION_COMPLETED, ESTIMATE_PENDING	INSPECTION
WAITING_FOR_APPROVAL	ESTIMATE, ESTIMATE_ITEMS, ESTIMATE_SUMMARY
REPAIR_PENDING, ESTIMATE_APPROVED	(nothing more — APPROVAL still pending)
REPAIR_IN_PROGRESS	APPROVAL
REPAIR_COMPLETED	(same; REPAIR intentionally not complete — manager reviews then proceeds to QC)
QUALITY_CHECK	REPAIR
READY_FOR_INVOICE	QUALITY_CHECK
INVOICE_GENERATED ...	INVOICE
PAYMENT_COMPLETED, READY_FOR_DELIVERY	PAYMENT
DELIVERED, CLOSED	DELIVERY

`nextStep` uses the shell numbering (Approval 8, Repair 9, QC 10, Invoice 11, Payment 12, Delivery 13) and is informational; Flutter does **not** use it.

Position derivation: `WorkflowController._resolveCurrentStepFromCompletedSteps` picks the first *visible* step whose backend id (`_backendStepIdByLocalId`) is not in `completedSteps` (`search` is skipped once a job exists). It re-runs whenever `workflowStatus` changes (`_onWorkflowStateChanged`) or on `initializeFromWorkflowStatus()`. **Rules for screens:** after a mutation that calls `refreshWorkflowStatus()`, do not call `nextStep()` (it double-advances) — call `initializeFromWorkflowStatus()` (see `EstimateSummaryScreen`, `ApprovalScreen`). Prefer `resumeWorkflow` when other actors (customer) may have changed data. **Resume:** `WorkflowService.resumeWorkflow(n)` → `GET /workflow/{n}/resume` → `syncWorkflowState` (customer, vehicle, job, complaints, inspections, estimate + items, repair tasks, invoice). Entry points: "+ Workflow" FAB (`WorkflowState.reset()`, no API), Job Card "Resume Workflow"/navigate actions (argument = job number), **Booking** → **Create Job Card** (`WorkflowStartAtJobStep: customer/vehicle/bookingId` pre-loaded, starts on the Job Card step via `WorkflowController.goToStepById('job')`). **Job Card detail screen** uses server-driven actions (`JobCardProjectionServiceImpl.allowedActions` → `JobCardActionService`); its actions call the same backend operations as the shell. *Navigate*-kind actions open the shell. **Retained quirks (CLAUDE.md §11):** `WorkflowState.reset()` does not clear `workflowStatus/complaints/repairTasks/assignments`; `closeJob()` / `assignTechnician()` don't refresh status; the employee "Approve Estimate" button is disconnected. `WorkflowState.bookingId` (new) **is** cleared by `reset()`.

13. Backend Service Ownership

Business operation	Controller	Service	Authoritative method	Entity	State written
Job creation	<code>ServiceWorkflowController.createJob</code> (POST <code>/workflow/job</code>)	<code>ServiceWorkflowServiceImpl</code> → <code>JobCardServiceImpl</code>	<code>createJobCard</code>	<code>JobCard</code> , <code>Complaint</code>	<code>OPEN</code> ; Booking <code>COMPLETED</code> ; pickup request <code>jobCardId</code>
Inspection start	POST <code>/workflow/{n}/inspection/start</code>	<code>ServiceWorkflowServiceImpl.startInspection</code>	<code>InspectionService.startInspection</code> + <code>JobCardServiceImpl.startInspection</code>	<code>Inspection</code> , <code>JobCard</code>	<code>INSPECTION_PENDING</code>
Inspection completion	POST <code>/workflow/{n}/inspection/complete</code>	<code>ServiceWorkflowServiceImpl.completeInspection(list)</code> (@Transactional)	<code>InspectionService.completeInspection</code> + <code>JobCardServiceImpl.completeInspection</code>	<code>Inspection</code> , <code>JobCard</code>	<code>INSPECTION_COMPLETED</code>
Estimate creation	POST <code>/estimates</code> (+ POST <code>/workflow/{n}/estimate</code> for job state)	<code>EstimateServiceImpl.createEstimate</code> ; <code>JobCardServiceImpl.prepareEstimate</code>	same	<code>Estimate</code> (DRAFT)	<code>ESTIMATE_PENDING</code>
Estimate finish	PUT <code>/estimates/{id}</code>	<code>EstimateServiceImpl</code>	<code>updateEstimate</code>	<code>Estimate</code> , <code>JobCard</code>	<code>WAITING_FOR_APPROVAL</code>
Customer approval	PUT <code>/estimates/{id}/approve</code>	<code>EstimateServiceImpl</code>	<code>approveEstimate(Long)</code> → <code>approveEstimateCanonical</code>	<code>Estimate</code> , <code>RepairTask</code> , <code>JobCard</code>	<code>Estimate</code> <code>APPROVED</code> , tasks <code>PENDING</code> , job <code>REPAIR_PENDING</code>
Manager repair confirmation	POST <code>/workflow/{n}/repair/start</code> , POST <code>/jobcards/{n}/repair/start</code>	<code>JobCardServiceImpl</code>	<code>startRepair</code>	<code>JobCard</code>	<code>REPAIR_IN_PROGRESS</code>
Repair task start	PUT <code>/repair-tasks/{id}/start</code> , PUT <code>/job-assignments/{id}/start</code>	<code>RepairTaskServiceImpl</code> , <code>JobAssignmentServiceImpl</code>	<code>startRepair</code> , <code>startJob</code>	<code>RepairTask</code> , <code>JobAssignment</code>	task/assignment <code>IN_PROGRESS</code> (never the job)
Repair task completion	PUT <code>/repair-tasks/{id}/complete</code> , PUT <code>/job-assignments/{id}/complete</code>	same	<code>completeRepair</code> , <code>completeJob</code>	same + <code>JobCard</code>	task <code>COMPLETED</code> ; job <code>REPAIR_COMPLETED</code> when all done
QC	POST <code>/workflow/{n}/quality-check</code> ; <code>/jobcards/{n}/quality-check[/pass /fail]</code>	<code>ServiceWorkflowServiceImpl.performQualityCheck</code> ; <code>QualityCheckServiceImpl</code>	<code>passQualityCheck</code> , <code>failQualityCheck</code>	<code>QualityCheck</code> , <code>JobCard</code>	<code>QUALITY_CHECK</code> → <code>READY_FOR_INVOICE</code> / <code>REPAIR_PENDING</code>
Invoice generation	POST <code>/workflow/{n}/invoice</code>	<code>InvoiceServiceImpl</code>	<code>generateInvoice</code>	<code>Invoice</code> , <code>JobCard</code>	<code>INVOICE_GENERATED</code>

Business operation	Controller	Service	Authoritative method	Entity	State written
Payment	POST /workflow/{n}/payment	InvoiceServiceImpl	receivePayment	Invoice , JobCard	invoice PAID ; job READY_FOR_DELIVERY
Pickup request	POST /bookings/{id}/confirm	BookingServiceImpl → NavigationRequestService	confirmBooking	Booking , NavigationRequest	Booking CONFIRMED ; request REQUESTED
Pickup trip	POST /navigation/trips + /accept /start /arrive /continue /complete	NavigationTripServiceImpl	assignDriver ... completeTrip	NavigationTrip , NavigationRequest	\$9.6–9.7
Pickup handover	GET/POST /navigation/trips/{id}/handover/*	HandoverServiceImpl	getOrCreateActiveCode , verify	VehicleHandover	PENDING , VERIFIED
Pickup completion	POST /navigation/trips/{id}/complete	NavigationTripServiceImpl.completeTrip	same	trip, request	trip/request COMPLETED
Delivery request	POST /navigation/requests? customerId=	NavigationRequestServiceImpl	createRequest → validateDeliveryRequest	NavigationRequest	REQUESTED + jobCardId , address, coordinates
Delivery trip	POST /navigation/trips ...	NavigationTripServiceImpl	as pickup	trip	as pickup (no return leg)
Delivery handover	.../handover/*	HandoverServiceImpl	as pickup, direction=DELIVERY	VehicleHandover	
Delivery completion	POST /navigation/trips/{id}/complete	NavigationTripServiceImpl.completeTrip → DeliveryServiceImpl.completeDeliveryFromTrip	same	Delivery , JobCard , trip, request	Delivery DELIVERED , job DELIVERED
Job delivery (manual)	POST /deliveries	DeliveryServiceImpl	createDelivery	Delivery , JobCard	same, only when no delivery request exists
Job closure	PUT /jobcards/{n}/close , POST /workflow/{n}/close	JobCardServiceImpl	closeJobCard	JobCard	CLOSED

14. Workflow Coupling Rules

Connection	Who calls whom	Trigger	State change	Auto/explicit	Transactional	Reversible
Job create → inspection start	Flutter <code>WorkflowService.createJob</code> → two REST calls	job created	<code>OPEN</code> → <code>INSPECTION_PENDING</code>	client-chained	two transactions (the create, then the start)	no
Inspection → estimate	Flutter <code>createEstimate</code> → <code>/inspection/complete</code> then <code>/estimate</code>	user taps Create Estimate	→ <code>INSPECTION_COMPLETED</code> → <code>ESTIMATE_PENDING</code>	client-chained	inspection+job atomic (<code>completeInspection</code>); estimate prep separate	no
Estimate → customer	<code>EstimateServiceImpl.updateEstimate</code>	manager finish	→ <code>WAITING_FOR_APPROVAL</code>	explicit	yes	no
Customer approval → repair pending	<code>EstimateServiceImpl.approveEstimateCanonical</code> → <code>RepairTaskServiceImpl.createRepairTasks</code> , <code>JobCardRepository</code>	customer approve	Estimate <code>APPROVED</code> , tasks, job <code>REPAIR_PENDING</code>	explicit (customer)	one transaction	no (no un-approve)
Manager confirm → repair	<code>JobCardServiceImpl.startRepair</code>	manager	→ <code>REPAIR_IN_PROGRESS</code>	explicit manager	yes	no
Task start/complete → job	<code>JobAssignmentServiceImpl</code> / <code>RepairTaskServiceImpl</code>	technician	task state; job <code>REPAIR_COMPLETED</code> on last task	explicit (task) / automatic (aggregate)	yes	no
QC fail → rework	<code>QualityCheckServiceImpl</code>	QC fail	job <code>REPAIR_PENDING</code> (manager must confirm again)	explicit	yes	yes (loop)
Payment → deliverable	<code>InvoiceServiceImpl.receivePayment</code>	payment	job <code>READY_FOR_DELIVERY</code>	explicit	yes	no
Booking confirm → pickup request	<code>BookingServiceImpl.confirmBooking</code> → <code>NavigationRequestService</code>	staff confirm	request <code>REQUESTED</code>	automatic on confirm when pickup requested	yes	via cancel (no request cancel)
Booking → job	<code>JobCardServiceImpl.createJobCard</code> (<code>resolveBooking</code>)	job created with <code>bookingId</code>	Booking <code>COMPLETED</code> ; request <code>jobCardId</code>	explicit	yes	no
Driver assignment → trip	<code>NavigationTripServiceImpl.assignDriver</code>	staff	trip <code>ASSIGNED</code> ; request <code>ASSIGNED</code>	explicit	yes (+ DB unique index backstop)	no

Connection	Who calls whom	Trigger	State change	Auto/explicit	Transactional	Reversible
Trip start/complete → request	<code>NavigationTripServiceImpl.setRequestStatus</code>	driver	request <code>IN_PROGRESS</code> / <code>COMPLETED</code>	automatic	same transaction as the trip	no
Delivery trip complete → Delivery + job	<code>NavigationTripServiceImpl.completeTrip</code> → <code>DeliveryService.completeDeliveryFromTrip</code>	driver, after evidence + OTP	Delivery row, job <code>DELIVERED</code>	automatic	one transaction with the trip completion	no
Trip ↔ Workflow UI	none (Delivery screen buttons only)	—	—	—	—	—
Journey ← all	<code>CustomerVehicleJourneyServiceImpl</code> (read-only)	customer opens journey	none	derived	read-only	n/a

15. Booking Architecture

`BookingController (/api/v1/bookings)`: customer `POST`, staff `POST /phone` (operational roles), `GET /my`, `GET /garage`, `GET /{id}`, `POST /{id}/confirm|reject|cancel`. `BookingSource`: `CUSTOMER_APP`, `PHONE`. Confirm with `pickupRequested` builds a `PICKUP NavigationRequest` (address + coordinates copied) and stores `navigationRequestId`. **Booking** → **Job Card**: `BookingDetailScreen` shows **Create Job Card** for staff when `canCreateJobCardFromBooking` (status `CONFIRMED` and either no pickup or its trip is `COMPLETED`; UI gate only). It preloads customer (`CustomerService.getById`) and vehicle (`VehicleRepository.getById`) into `WorkflowState`, sets `bookingId`, and pushes `Routes.employeeWorkflow` with `WorkflowStartAtJobStep`. `JobStepScreen` sends `CreateJobCardRequest.bookingId`. Backend `JobCardServiceImpl.resolveBooking` requires: booking exists, same garage (else not-found), `CONFIRMED`, same vehicle, customer matches vehicle owner, no other job already uses it. Then it sets `JobCard.bookingId`, Booking `COMPLETED`, and `NavigationRequest.jobCardId` of the booking's pickup request. Walk-in jobs omit `bookingId` and are unchanged.

16. Pickup Architecture (deep)

```

Booking(REQUESTED) →confirm→ Booking(CONFIRMED) + NavigationRequest(PICKUP, REQUESTED)
- staff "Assign Driver" (AssignDriverSheet → POST /navigation/trips) → Trip ASSIGNED, request ASSIGNED
- driver Accept → Trip ACCEPTED → Start → Trip IN_PROGRESS (leg GARAGE_TO_CUSTOMER), request IN_PROGRESS
- GPS stream + route to customer → "I Have Arrived" → arrivedAt set
- 5 BEFORE_PICKUP photos (FRONT, REAR, LEFT, RIGHT, ODOMETER) → customer generates OTP → driver verifies →
handover VERIFIED
- "Start Return to Garage" → POST /continue: leg CUSTOMER_TO_GARAGE, arrivedAt=null,
destinationAddress="GARAGE"
- GPS + route to garage → "I Have Arrived" → arrivedAt set
- "Complete Pickup Trip" → POST /complete: Trip COMPLETED, request COMPLETED
- staff Create Job Card from the booking (job linked, booking COMPLETED, request.jobCardId set)

```

- **Completion preconditions** (`NavigationTripServiceImpl.completeTrip`, pickup): trip `IN_PROGRESS`; leg `CUSTOMER_TO_GARAGE` ("Pickup trip must return to garage before completion."); `arrivedAt != null` ("Mark arrival at the garage before completing the pickup trip."); all required `BEFORE_PICKUP` photos; verified PICKUP handover (re-checked defensively).
- **No garage-side OTP, by design:** custody transfer is confirmed once, at the customer (OTP + photos) before the return leg. At the garage there is no counter-party in the app to generate a code; the driver's arrival plus the earlier verified handover is the completion condition. `HandoverServiceImpl` therefore *refuses* code generation/verification for a pickup trip already on the return leg.
- **Return-leg destination detail:** the backend sets `destinationAddress` to the literal `"GARAGE"` and `NavigationTripResponse.destinationLatitude/Longitude` keep pointing at the customer's pickup coordinates. `ActiveTripScreen` resolves the real garage via `GET /garages/{id}` (`GarageService`, user's own `garageId`) and uses it for return-leg arrival/route. Anything else consuming a trip's destination on the return leg must do the same.
- **Driver UI:** `DriverDashboard._TripCard` renders `NavigationTrip.nextDriverAction` (`accept`, `start`, `arrive`, `evidenceAndHandover`, `completePickup`, `none`); `isPickupReturnLeg = tripType=='PICKUP' && currentLeg=='CUSTOMER_TO_GARAGE'`. `ActiveTripScreen` hides "View Confirmation Code" on the return leg.
- **Customer journey:** `DRIVER_ASSIGNED` → `DRIVER_EN_ROUTE` → `DRIVER_ARRIVED` → `EN_ROUTE_TO_GARAGE`; once the booking's job exists (request linked to job) the job-card stage takes over (§22).

17. Delivery Architecture (deep)

```

JobCard READY_FOR_DELIVERY
→ Delivery step (DeliveryScreen) restores state: GET /navigation/requests/job-card/{id}/delivery (404 = none)
→ "Request Delivery & Assign Driver": CreateDeliveryRequestSheet → LocationPickerScreen (map) → POST /navigation/requests?customerId=
    NavigationRequest(DELIVERY, jobCardId, deliveryAddress, deliveryLatitude, deliveryLongitude, REQUESTED)
→ AssignDriverSheet → POST /navigation/trips → Trip ASSIGNED, request ASSIGNED
→ driver Accept → Start → GPS/route to delivery coordinates → Arrive → 5 DELIVERY photos → customer OTP → driver verifies
→ POST /{trip}/complete:
    validateRequiredMedia(DELIVERY) + requireVerifiedHandover(DELIVERY)
    Trip COMPLETED; request COMPLETED
    DeliveryServiceImpl.completeDeliveryFromTrip(request.jobCardId, driverName, "Customer (OTP verified)")
        → Delivery(DELIVERED, deliveredBy, receivedBy) ; JobCard READY_FOR_DELIVERY → DELIVERED (same transaction)
→ manager Close Job → CLOSED

```

- **Request rules** (`NavigationRequestServiceImpl.validateDeliveryRequest`): `jobCardId` required; address **and** both coordinates required; job in caller's garage and the request's garage; job `READY_FOR_DELIVERY`; request vehicle/customer must match the job's; no other non-cancelled DELIVERY request for the job. DB backstop: partial unique index (V61).
- **completeDeliveryFromTrip rules**: garage match; no existing Delivery; invoice found via `InvoiceRepository.findByEstimateJobCardId`; invoice `GENERATED` and `PAID`; then create Delivery and `JobCardStatusValidator` + set `DELIVERED`. Any failure rolls back the trip completion (same `@Transactional` boundary).
- **Why manual POST /deliveries still exists**: a customer who collects the car at the garage has no delivery trip. It is now **rejected** when any DELIVERY request exists for the job ("A delivery trip exists for this Job Card...") and when the invoice belongs to another job. The Delivery screen hides "Mark Vehicle Delivered (collected at garage)" once a request exists.
- **Delivery step UI states**: loading → *no request* (button "Request Delivery & Assign Driver") → `REQUESTED` ("Assign Delivery Driver") → `ASSIGNED/IN_PROGRESS` ("Track Delivery") → `COMPLETED` ("View Delivery"; job is `DELIVERED`, "Close Job" enabled). Returning from `ActiveTripScreen` calls `_refreshDelivery` (reload request + `resumeWorkflow`).
- **Legacy**: delivery requests created before V61 have `job_card_id = NULL`; their trip completes but touches no job.
- **Not implemented**: automatic driver selection, workload balancing, driver rejection, reassignment, delivery/trip cancellation.

18. Delivery Location

`CreateDeliveryRequestSheet` (bottom sheet, `show(context, customerId, vehicleId, garageId, jobCardId)`) offers **Select location on map** (pushes the existing `LocationPickerScreen` with `LocationPickerMode.delivery` and a `LocationSearchService`) and the older **current device location** shortcut (`PickupLocationProvider`). The picker returns a `PickupLocation{latitude, longitude, address?}`; the sheet fills coordinates and an editable address field. `resolveDeliveryAddress` keeps the address if present, otherwise "`<lat>, <lng>`" (6 decimals). Submit requires coordinates. `NavigationTripService.createDeliveryRequest` sends `requestType=DELIVERY, jobCardId, deliveryAddress, deliveryLatitude, deliveryLongitude, scheduledAt(now+2 min)`. Persistence: `navigation_request.delivery_address/latitude/longitude`; consumed by `NavigationTripServiceImpl.toResponse` as the trip destination for DELIVERY trips → `NavigationTrip.destinationLatitude/Longitude` → `ActiveTripScreen/LiveTripState` route.

19. Navigation Architecture

- **Driver GPS:** `DriverLocationTracker.start` — `Geolocator.getPositionStream`, high accuracy, `distanceFilter: 10 m`, Android foreground-service notification. Started by `ActiveTripScreen._maybeStartDriverGps` for the driver; runs only while that screen is open.
- **Publish:** `LocationSocketService.publishLocation` → STOMP `/app/location/update` → `LocationWebSocketController` → `DriverLocationServiceImpl` (saves `DriverCurrentLocation`, appends `DriverLocationHistory` (`driver_location_history`), broadcasts via `SimpMessagingTemplate`).
- **Subscribe:** `/topic/trips/{tripId}/location` (customer, manager, driver), guarded by `TripLocationTopicInterceptor`. Socket: endpoint `/ws`, `reconnectDelay` 5 s, connection timeout 10 s, topics re-subscribed after reconnect.
- **REST fallback:** `LiveTripState` polls `GET /navigation/trips/{id}` every **10 s** (`_statusPollInterval`) and reads `GET /navigation/trips/{id}/location` when no recent socket fix.
- **Route:** `RouteService` → `POST /navigation/routes` (`RouteRequest{origin,destination}`) → `NavigationRouteServiceImpl`: Google Routes when configured (`GOOGLE_MAPS_ROUTES_API_KEY`), else OSRM. Recomputed only after the driver moved $\geq$ **150 m** since the last route (`_routeRecalculationDistanceMeters`).
- **Arrival:** the backend gate is the driver's `POST /arrive`; a 10 m GPS test (`kArrivalRadiusMeters`) drives only display labels.
- **Destination selection:** pickup outbound = request pickup coordinates; delivery = request delivery coordinates; pickup return leg = garage from `/garages/{id}` (§16). No coordinates → map shows the driver but no destination pin/route (`hasDestinationCoordinates`).
- **Screens:** `ActiveTripScreen` (driver/customer/manager), `ManagerFleetMapScreen` (`GET /navigation/trips/garage/{id}/fleet`), `DriverTripHistoryScreen`. Maps: `google_maps_flutter` on Android, `flutter_map` elsewhere.

20. OTP Architecture

`HandoverServiceImpl` (`VehicleHandover`, `V38`, `V39` = at most one pending per trip):

Aspect	Behaviour
Generation	customer <code>GET /navigation/trips/{tripId}/handover/code</code> (<code>getOrCreateActiveCode</code>); allowed only if the caller owns the request, <code>trip.arrivedAt != null</code> , trip <code>IN_PROGRESS</code> , and the trip is not a pickup already on its return leg
Code	6 digits, <code>SecureRandom</code> ; only a <code>PasswordEncoder</code> hash (<code>code_hash</code>) is stored; audit events never include the code
Delivery to the driver	shown in the customer app, read out to the driver — not sent by SMS/e-mail
Expiry	10 minutes (<code>EXPIRY_MINUTES</code>); requesting a new code marks the old pending one <code>EXPIRED</code>
Verification	driver <code>POST .../handover/verify {code}</code> (<code>VerifyHandoverRequest.code</code>); trip must be the driver's own and in the driver's garage; needs a <code>PENDING</code> , unexpired code
Attempts	<code>MAX_FAILED_ATTEMPTS = 5</code> ; wrong code increments; at 5 the code is <code>EXPIRED</code> and a new one is needed
Direction	<code>direction = trip.tripType</code> (<code>PICKUP</code> or <code>DELIVERY</code>) — identical flow
Effects	<code>VERIFIED</code> + <code>verifiedAt/verifiedByDriverId</code> ; audit <code>OTP_VERIFIED</code> and custody event. The trip does not move by itself: the driver presses "Start Return to Garage" (<code>continue</code> , pickup) or "Complete Delivery" (<code>complete</code> , delivery) in <code>HandoverVerifyScreen._advance</code>
Gate	<code>continueTrip</code> (pickup) and <code>completeTrip</code> (delivery; and pickup, re-checked) call <code>requireVerifiedHandover</code>
Status	<code>GET .../handover/status</code> (garage staff) returns latest handover

21. Trip ↔ Booking ↔ JobCard Relationships

```

Booking —navigationRequestId→ NavigationRequest(PICKUP) —unique→ NavigationTrip → VehicleHandover
|
| jobCardId (set when the job is created from the booking) ↳
NavigationTripMedia
└─ JobCard.bookingId → JobCard ←┐
    └─ Estimate — EstimateItem → RepairTask — JobAssignment
    └─ Invoice(estimate) → Delivery(jobCard 1:1, invoice 1:1)
    └─ NavigationRequest(DELIVERY).jobCardId —unique per live request→
NavigationTrip

```

The only reference added by the latest change is `navigation_request.job_card_id` (V61). Trips still have no direct FK to a JobCard; they reach it through their request. Vehicle-based heuristics remain only as a fallback in the customer journey.

22. Customer Journey Logic

`CustomerVehicleJourneyServiceImpl.getActiveJourneys()` (customer portal `GET /customer/vehicle-journeys/active`, screen `LiveVehicleJourneyScreen`). Per vehicle of the authenticated customer it batch-loads: latest **CONFIRMED booking**, latest **REQUESTED navigation request**, latest **ASSIGNED/ACCEPTED/IN_PROGRESS trip**, latest **non-CLOSED/CANCELLED job card** (note `DELIVERED` is still "active" and shows `COMPLETED`). Selection (`deriveStage`):

1. active trip → `deriveFromTrip` (`DRIVER_ASSIGNED`, `DRIVER_EN_ROUTE`, `DRIVER_ARRIVED`, `EN_ROUTE_TO_GARAGE` for pickup; `HANDOVER` for delivery);
2. else job card → `deriveFromJobCard` (`ARRIVED_AT_GARAGE`, `INSPECTION`, `ESTIMATE_PENDING`, `CUSTOMER_APPROVAL_REQUIRED`, `REPAIR_PENDING`, `REPAIR_IN_PROGRESS`, `QUALITY_CHECK`, `PAYMENT_PENDING`, `VEHICLE_READY`, `COMPLETED`);
3. else pending request → `BOOKING_CONFIRMED` ("arranging your pickup driver");
4. else confirmed booking → `BOOKING_CONFIRMED`.

Direct-link rule (new): if the active trip is a PICKUP whose `NavigationRequest.jobCardId` equals the vehicle's job card, the trip is ignored for stage selection (the vehicle is at the garage; the job card is the truth). A DELIVERY trip keeps priority (the customer must see the handover). Trips without the link (legacy, or before the job is created) keep the old "trip wins" behaviour. **Edge cases:** a pickup trip left uncompleted and not yet linked still shows `EN_ROUTE_TO_GARAGE`; the vehicle-based selection can mis-pair records when a vehicle has overlapping active records; a stuck trip never auto-expires (no cancellation workflow).

23. Media Architecture

Direct-to-R2, private bucket, presigned URLs. Spring never proxies media bytes; the old multipart limit was not raised.

New image

`MediaPickerSheet` (image_picker, optimized at pick) → capture metadata taken **at pick time** (`capturedAt`, one-shot GPS + reverse-geocoded address, sent with the offset via `isoWithLocalOffset`) → `MediaUploadQueueService.enqueue` (persistent queue) → `POST /job-cards/{id}/media/upload-intent` (`MediaServiceImpl.createUploadIntent`: row `evidence_only=true`, `captured_by` from the authenticated user, storage key `..._source.jpg`) → direct PUT → `POST /media/{id}/complete` → `MediaProcessingScheduler` (15 s poll) renders `..._evidence.jpg` (full resolution + footer: stage, captured time, captured-by, address, `Lat/Lng`, accuracy, GarageST) and `..._thumbnail.jpg` (320 px longest edge, from the evidence), sets `storage_key = evidence_key`, saves `COMPLETED`, **then** deletes the `_source` object. Retry: failures keep the row `UPLOADED`, `retry_count++`, `FAILED` after 5 (source kept); a lost save after rendering is detected and not re-rendered.

New video

Pick/record → `MediaOptimizationService.renderEvidenceVideo` → Android `EvidenceVideoProcessor` (Media3 Transformer, **single pass**): reads rotation and computes the target in the video's own orientation (long edge ≤ 1920, short edge ≤ 1080, even dimensions, never squeezed into a landscape frame), bitrate = 80 % of the source (`qualityPercent = 80`, H.264/AAC MP4), draws the footer as a full-frame bitmap overlay, then extracts a JPEG (≤ 480 px longest edge) from the **finished** file → upload intent (returns two presigned URLs: `..._evidence.mp4`, `..._thumbnail.jpg`) → PUT both → `/complete {thumbnailUploaded:true, durationSeconds}` (backend verifies the thumbnail object exists). Evidence text is built on-device from persisted queue-item metadata (`buildEvidenceLines`) and mirrors `MediaEvidenceText` on the backend (same literals asserted in both test suites). Local outputs live in `<temp>/media_optimized/{localId}.mp4|.jpg`, are re-used on retry (never re-rendered once the paths are persisted), deleted after completion, and orphans are swept at app start. A crashed render restarts from the untouched original.

Keys, access, cache, TTL

- Key convention: `GarageST/{garageCode}/{jobCardNumber}/{stage}/{jobCardNumber}_{stage}_{seq}_{source|evidence|thumbnail}.{ext}` (`MediaKeys.derive`); sequence from `getNextSequence`; no per-media folders.
- Access: `GET /media/{id}/access?variant=evidence|thumbnail` (employee) and `GET /customer/jobcards/{n}/media/{id}/access` (customer). `evidence_only` rows always resolve to the evidence (also for a stale `original`), and an image still being processed is `available=false` — the staging source is never signed.
- TTL: upload URL `R2_UPLOAD_URL_TTL_MINUTES` (default 15), playback `R2_PLAYBACK_URL_TTL_MINUTES` (default 10).
- Flutter cache keys: `media-video-{mediaId}` (stable, never the URL), `media-evidence-{id}`, `media-thumb-{id}`.
- Failure model: `MEDIA_STORAGE_NOT_CONFIGURED` is non-retryable; network/5xx retry with backoff (30 s, 2 m, 5 m, 15 m, 30 m); an upload URL that expired is re-requested (which creates a new row — known pre-existing behaviour).
- **Legacy compatibility:** Google Drive rows (proxied `/content`), and R2 rows with original + thumbnail/evidence keep working; the `evidence` variant falls back to the stored original when no evidence exists. Nothing was migrated or deleted. R2 delete removes a row's storage, evidence and thumbnail objects.
- **There is no separate original asset for NEW media.**

24. Trip Media vs JobCard Media

`JobCardMedia` $\neq$ `NavigationTripMedia`.

	JobCardMedia	NavigationTripMedia
Owner	a JobCard	a NavigationTrip
Storage	Cloudflare R2 (Drive for legacy)	server local disk (<code>LocalMediaStorageService</code> , <code>garageos.media.storage-path</code>) — <i>Config-dependent durability on Render</i>
Upload	presigned direct PUT + queue	multipart through Spring (<code>POST /navigation/trips/{id}/media</code>)
Processing	evidence footer + thumbnail	none
Metadata	captured-by/at, lat/lng, accuracy, address	shot type, stage, lat/lng, capturedBy/At
Purpose	inspection/repair evidence for the job	pickup/delivery condition evidence; required shot set gates trip continue/complete
Intentionally separate; connect only by ids if ever needed. The latest change did not touch either.		

25. Database Architecture

Key entities: `User` (garage, role) · `Garage` · `Customer` · `Vehicle` · `Booking` (customerId, vehicleId, garageId, navigationRequestId) · `JobCard` (garage, vehicle, customer, bookingId, status) · `Complaint` · `Inspection` · `Estimate` (jobCard) · `EstimateItem` (selected) · `RepairTask` (jobCard, jobAssignment) · `JobAssignment` (user, repairTask, type) · `QualityCheck` · `Invoice` (estimate 1:1) · `Delivery` (jobCard 1:1, invoice 1:1, deliveredBy, receivedBy) · `NavigationRequest` (customerId, vehicleId, garageId, requestType, pickup/delivery address + coordinates, `jobCardId`, status) · `NavigationTrip` (navigationRequestId unique, driverId, tripType, currentLeg, status, source/destinationAddress, accepted/started/arrived/completedAt) · `VehicleHandover` (tripId, direction, codeHash, status, expiresAt, failedAttempts) · `NavigationTripMedia` · `JobCardMedia` (evidence_only, storage/thumbnail/evidence keys, capture metadata) · `AuditEvent` · `spring.jpa.hibernate.ddl-auto=validate`: an entity field without a migrated column fails startup.

V61 — `V61__add_navigation_request_job_card_reference.sql`

- **Table:** `navigation_request`. **Column:** `job_card_id` `BIGINT`, **nullable**, no default. **No foreign-key constraint** (the entity stores a plain `Long`; V61 declares none); integrity is enforced in services.
- **Indexes:** `idx_navigation_request_job_card (job_card_id)`; and **partial unique** `idx_navigation_request_one_delivery_per_job` ON `navigation_request (job_card_id)` WHERE `request_type = 'DELIVERY'` AND `status <> 'CANCELLED'` AND `job_card_id IS NOT NULL`.
- **Why the partial index:** database backstop for "at most one live delivery request per job card", so two concurrent "request delivery" submissions cannot create two deliveries for one job. Cancelled requests and legacy rows (NULL) are excluded; PICKUP rows are excluded entirely.
- **Who requires `job_card_id`:** new DELIVERY requests (service-level, `validateDeliveryRequest`). PICKUP requests have it set later, when the job is created from their booking; otherwise NULL.
- **Legacy rows:** all NULL; they remain valid; their delivery trips complete without a job effect.
- **Rollback:** the column is additive and nullable, so an older backend build runs fine against the new schema (it ignores the column). The reverse is not true (new build on the old schema fails `validate`). To undo the schema, create **V62** that drops the index/column — never edit V61 once applied. Dropping the column loses the delivery↔job link.
- **Flyway:** applied automatically at application start (`spring.flyway.enabled=true`, `spring.flyway.locations=classpath:db/migration`) before JPA validation; recorded in `flyway_schema_history`.
- *Other schema changes in this line of work:* V60 `job_card_media.evidence_only` `BOOLEAN NOT NULL DEFAULT FALSE`. (V59, V58 are the earlier media migrations.)
- **Not verified here:** V61 was not executed against a PostgreSQL instance in this environment (*Environment required*).

26. Flyway Migrations

Location `src/main/resources/db/migration`, names `V{n}__snake_case_description.sql`, strictly increasing. **Never modify an applied migration.** New columns: nullable or with a default; prefer partial/unique indexes as backstops for service rules. Test on PostgreSQL (partial indexes are PostgreSQL syntax). Recent: V57 account deletion · V58 media provider fields · V59 media audit metadata · V60 media evidence flag · V61 navigation_request job reference.

27. API Reference (business-critical)

Base `/api/v1`. "Auth" lists the enforced restriction; svc = enforced in the service, not by annotation. Errors surface as `ApiException.message` in Flutter.

Workflow — `ServiceWorkflowController` `/workflow`

Method & path	Auth	Purpose / inputs	State change	Notable failures
POST <code>/job</code>	authenticated, garage user	create job (<code>CreateJobCardRequest</code> : vehicleId, odometer, complaints[], estimatedDeliveryDate, remarks, bookingId?)	<code>OPEN</code> ; Booking <code>COMPLETED</code> if bookingId	"User is not associated with a garage."; booking rules (§15)
POST <code>/{\$n}/inspection/start</code>	authenticated (svc garage scope)	creates inspection rows	<code>INSPECTION_PENDING</code>	invalid transition
POST <code>/{\$n}/inspection/complete</code>	authenticated	body: one <code>CreateInspectionRequest</code> per complaint	<code>INSPECTION_COMPLETE</code>	size mismatch
POST <code>/{\$n}/estimate</code>	authenticated	prepare estimate stage	<code>ESTIMATE_PENDING</code>	invalid transition
POST <code>/{\$n}/estimate/approve</code>	MANAGER (svc)	employee-side approval (UI disconnected)	as customer approval	"Only a Manager can approve this estimate."
POST <code>/{\$n}/repair/start</code>	MANAGER (svc)	manager confirmation	<code>REPAIR_IN_PROGRESS</code>	"Only a Manager can proceed a Job Card to repair."; "Estimate must be customer-approved before repair can start."; invalid transition
POST <code>/{\$n}/repair/complete</code>	authenticated	<i>Legacy</i> check-only wrapper	none	—
POST <code>/{\$n}/quality-check</code>	M/SA/OWNER	start QC	<code>QUALITY_CHECK</code>	invalid transition
POST <code>/{\$n}/invoice, /invoice/accept</code>	M/SA/OWNER ; CUSTOMER	generate / accept	<code>INVOICE_GENERATED</code>	
POST <code>/{\$n}/payment</code>	M/SA/OWNER/CUSTOMER (customer ownership svc)	receive payment	invoice <code>PAID</code> , <code>READY_FOR_DELIVERY</code>	"Invoice must be accepted before payment can be received."

Method & path	Auth	Purpose / inputs	State change	Notable failures
POST /{n}/delivery	authenticated	readyForDelivery (UI unused)	READY_FOR_DELIVERY	—
POST /{n}/close	M/SA/OWNER	close	CLOSED	invalid transition
GET /{n}/status	authenticated	WorkflowStatusResponse	none	
GET /{n}/resume	authenticated	full snapshot for WorkflowState	none	
GET /{n}/repair-tasks	authenticated	tasks	none	

JobCard — JobCardController /jobcards

GET /{id}/view (role-dependent projection: customer / technician / operational; allowedActions, visibleSections) · POST /{n}/inspection/start|complete, /estimate/prepare, /estimate/approve, /repair/start (same startRepair), /quality-check, /quality-check/pass|fail (M/SA/OWNER), PUT /{n}/ready-for-delivery, PUT /{n}/close (M/SA/OWNER).

Estimate — EstimateController /estimates

PUT /{id} finish (staff; ESTIMATE_PENDING → WAITING_FOR_APPROVAL) · PUT /{id}/approve and /reject (CUSTOMER owner only; not-found otherwise; "Estimate is already approved.").

Repair — /repair-tasks, /job-assignments

PUT /repair-tasks/{id}/assign (M/SA/OWNER) · PUT /repair-tasks/{id}/start|complete (assigned technician or operational staff) · POST /job-assignments (M/SA/OWNER) · PUT /job-assignments/{id}/accept|start|complete (the assignee) · PUT /job-assignments/{id}/reassign (M/SA/OWNER). Start/complete guards in §10.

Booking — /bookings

POST / (customer) · POST /phone (M/SA/OWNER) · GET /my, /garage, /{id} · POST /{id}/confirm|reject|cancel. Job linkage is via POST /workflow/job bookingId, not a booking endpoint.

Navigation — /navigation

Method & path	Caller	Purpose	Key validation / state
POST /requests?customerId=	garage staff	create request (CreateNavigationRequest)	DELIVERY: §17 rules; PICKUP created by booking confirm

Method & path	Caller	Purpose	Key validation / state
GET /requests/{id}, /customer/{id}, /garage/{id}, /{id}/trip	per svc	lookups	/trip restricted to customer/driver/garage staff
GET /requests/job-card/{jobCardId}/delivery	garage staff	rediscover a job's delivery request	404 if none / other garage
POST /trips	garage staff	assign driver ({navigationRequestId, driverId})	request REQUESTED ; driver active DRIVER of the garage; unique trip per request → trip ASSIGNED , request ASSIGNED
POST /trips/{id}/accept?driverId=	that driver		trip ASSIGNED → ACCEPTED
POST /trips/{id}/start?driverId=	that driver		ACCEPTED → IN_PROGRESS ; request IN_PROGRESS
POST /trips/{id}/arrive?driverId=	that driver	sets arrivedAt	trip IN_PROGRESS
POST /trips/{id}/continue?driverId=	that driver	pickup outbound → return leg	pickup only; outbound leg; required BEFORE_PICKUP photos; verified PICKUP handover
POST /trips/{id}/complete?driverId=	that driver	finish	pickup: return leg + arrival + photos + handover; delivery: photos + handover + completeDeliveryFromTrip ; request COMPLETED
GET /trips/{id}, /{id}/location	customer owner / driver / garage staff (NavigationTripAccessGuard)	trip / last location	not-found otherwise
GET /trips/driver/{id}, /driver/{id}/history, /garage/{id}/fleet	driver (self) / garage staff	lists	
POST /routes	authenticated	route between two points	Google → OSRM fallback
POST /trips/{id}/media, GET .../media, .../media/{stage}, .../media/{mediaId}/content	driver upload; viewers	trip evidence	upload only IN_PROGRESS and after arrival

Handover — /navigation/trips/{tripId}/handover

GET /code (customer owner) · POST /verify {code} (driver) · GET /status (garage staff) · POST /evidence-viewed (customer). Rules §20.

Delivery — /deliveries

POST / (M/SA/OWNER) CreateDeliveryRequest{jobCardId, invoiceId, deliveredBy?, receivedBy?, remarks?} — garage collection only; rejected if a delivery request exists, if the invoice isn't the job's, if invoice not GENERATED + PAID, or a Delivery already exists. Trip-driven completion has no endpoint of its own: it happens inside POST /navigation/trips/{id}/complete. GET /deliveries/{id}, GET /deliveries are lookups.

Media

POST /job-cards/{id}/media/upload-intent (UploadIntentRequest: stage, contentType, fileSize, repairTaskId?, capturedAt, latitude, longitude, locationAccuracyMeters, locationName) → UploadIntentResponse (mediald, uploadUrl, requiredHeaders, storageKey, uploadSessionId, **thumbnailUploadUrl/thumbnailRequiredHeaders for VIDEO**) · direct PUT to R2 · POST /media/{id}/complete (uploadSessionId, durationSeconds?, thumbnailUploaded?) idempotent · GET /media/{id}/access?variant= (employee) · GET /customer/jobcards/{n}/media/{id}/access (customer) · GET /job-cards/{id}/media · PUT /job-cards/{id}/media/{mediaId}/visibility · DELETE /media/{id} (privileged) · POST /job-cards/{id}/media (Legacy multipart). Failure: MEDIA_STORAGE_NOT_CONFIGURED.

28. WebSocket Architecture

`WebSocketConfig`: endpoint `/ws` (plain and SockJS, all origins), application prefix `/app`, simple broker `/topic`. Publish `/app/location/update` (`DriverLocationRequest`: `driverId`, `tripId`, `lat`/`lng`, `speed`, `heading`, `accuracy`). Subscribe `/topic/trips/{tripId}/location`. Authorization per subscription: `TripLocationTopicInterceptor` → `NavigationTripAccessGuard.authorizeViewer`. Client: `LocationSocketService` (singleton), 5 s reconnect, resubscribe on connect; if the socket is down `LiveTripState` keeps working through REST polling. The in-memory simple broker means a single backend instance (no external broker).

29. Flutter Screen / Route Map

Screen	Route	Entered by / how	State consumed	API calls	Changes	Next
EmployeeHomeScreen	/employee/home	splash redirect (employee roles)	Permissions, dashboards	dashboard + job list services	WorkflowState.reset() on FAB	workflow shell
WorkflowShellScreen	/employee/workflow (arg: job number WorkflowStartAtJobStep none)	FAB, Job Card actions, Booking "Create Job Card"	WorkflowController, WorkflowState	GET /workflow/{n}/resume when resuming	step position	its step screens
SearchScreen	(shell step)	first step	WorkflowState.customer/vehicle	customer by mobile, vehicle by registration	sets customer/vehicle	Job Card step
JobStepScreen	(shell)	manager/SA	customer, vehicle, bookingId	POST /workflow/job, /inspection/start, media queue	creates job, uploads media (queue)	Inspection
InspectionScreen	(shell)	manager	complaints, job	inspection create	inspections	Estimate
EstimateScreen	(shell)	manager	inspections	/inspection/complete, /estimate, POST /estimates	estimate DRAFT	Estimate Items
EstimateItemScreen	(shell)	manager	estimate	estimate-item CRUD	items, totals	Summary
EstimateSummaryScreen	(shell)	manager	estimate, items	PUT /estimates/{id}	job WAITING_FOR_APPROVAL	Approval (via initializeFromWorkflowStatus)
ApprovalScreen	(shell)	manager	estimate.status, workflowStatus.status	pull-to-refresh: GET /workflow/{n}/resume; button: POST /workflow/{n}/repair/start	REPAIR_IN_PROGRESS	Repair (re-derived)
RepairScreen	(shell)	manager, technician	tasks, assignments	/job-assignments/*, /repair-tasks, /workflow/{n}/quality-check	assignments/tasks; job REPAIR_COMPLETED (auto) then QC	Quality Check
QualityCheckScreen	(shell)	manager/technician	job	QC pass/fail	READY_FOR_INVOICE / REPAIR_PENDING	Invoice
InvoiceScreen	(shell)	manager/accountant	estimate, invoice	/workflow/{n}/invoice, /invoice/accept	INVOICE_GENERATED	Payment

Screen	Route	Entered by / how	State consumed	API calls	Changes	Next
PaymentScreen	(shell)	manager/accountant/cashier	invoice	/workflow/{n}/payment	READY_FOR_DELIVERY	Delivery
DeliveryScreen	(shell)	manager	workflowStatus , jobCardId , invoice	GET /navigation/requests/job-card/{id}/delivery , POST /deliveries (collection), PUT /jobcards/{n}/close via closeJob , resumeWorkflow	request/assignment, delivered, closed	Routes.activeTrip , sheets
JobCardDetailsScreen	/job-card (arg: id)	job lists	JobCardView	projection, JobCardActionService , media	transitions per action	workflow shell
BookingDetailsScreen	/booking/detail (arg: id)	queue, my bookings, journey	booking + pickup trip	bookings, getTripByRequest , CustomerService , VehicleRepository	confirm/reject/cancel; loads customer/vehicle into WorkflowState	AssignDriverSheet , Routes.activeTrip , workflow shell (WorkflowStartAtJobStep)
DriverDashboard (in DriverHomeScreen)	/driver/home	splash (driver role)	trips (nextDriverAction)	getMyTrips , accept/start/arrive/complete	trip state	TripEvidenceCaptureScreen , Routes.handoverVerify , Routes.activeTrip
ActiveTripScreen	/navigation/active-trip (arg: tripId)	driver, customer, manager, booking, delivery step	LiveTripState (trip, location, route), garage	trip GET/poll, location, routes, STOMP, /garages/{id}	publishes driver GPS (driver)	Routes.handoverCode
TripEvidenceCaptureScreen	pushed directly (tripId, stage)	driver "Capture Evidence"	captured shot types	trip media GET/POST	trip media	back
HandoverCodeScreen	/handover/code (arg: tripId)	customer/ ActiveTripScreen	trip	GET .../handover/code	pending handover	back
HandoverVerifyScreen	/handover/verify (arg: tripId)	driver "Confirm Handover"	trip	POST .../handover/verify , then continue (PICKUP outbound) or complete (DELIVERY)	handover VERIFIED , trip	back
LocationPickerScreen	pushed directly	PickupLocationSelector , CreateDeliveryRequestSheet	initial PickupLocation	place search, reverse geocode	none	pops PickupLocation
CreateDeliveryRequestSheet	bottom sheet	Delivery step	customer/vehicle/garage/job ids	POST /navigation/requests	delivery request	returns request id

Screen	Route	Entered by / how	State consumed	API calls	Changes	Next
AssignDriverSheet	bottom sheet	booking detail, delivery step	request id	GET /users/drivers , POST /navigation/trips	trip created	returns bool
CustomerEstimateDetailScreen	customer portal	customer estimate list	estimate	GET estimate, PUT /estimates/{id}/approve reject	estimate APPROVED , job REPAIR_PENDING	refresh
LiveVehicleJourneyScreen	/customer/vehicle-journey	customer home	journey summaries	GET /customer/vehicle-journeys/active	none	BookingDetailScreen , Routes.activeTrip
ManagerFleetMapScreen	/navigation/fleet-map	manager	fleet	fleet endpoint	none	Routes.activeTrip

30. Key Code Paths

Notation: *Flutter screen* → *service* → *endpoint* → *controller* → *service* → *entity/state*.

1. Customer approval → manager confirmation. BEFORE: `resolveCompleted` listed `APPROVAL` at `REPAIR_PENDING`, so the manager was moved to Repair. AFTER: `APPROVAL` only from `REPAIR_IN_PROGRESS`. Path:

`CustomerEstimateDetailScreen` → `CustomerPortalService.approveEstimate` → `PUT /estimates/{id}/approve` → `EstimateController` → `EstimateServiceImpl.approveEstimate(Long)` → `approveEstimateCanonical` → `Estimate.APPROVED`, `createRepairTasks`, `JobCard.REPAIR_PENDING`. Manager: `ApprovalScreen._refresh` → `WorkflowService.resumeWorkflow` → `GET /workflow/{n}/resume` → `ServiceWorkflowServiceImpl.resumeWorkflow` → `WorkflowController.initializeFromWorkflowStatus` stays on Approval; `_proceedToRepair` → `WorkflowService.proceedToRepair` → `POST /workflow/{n}/repair/start` → `ServiceWorkflowServiceImpl.startRepair` → `JobCardServiceImpl.startRepair` → `JobCard.REPAIR_IN_PROGRESS` → `refresh` → `step = Repair`.

2. Repair-start bypass prevention. BEFORE: `JobAssignmentServiceImpl.startJob` set `REPAIR_PENDING` → `REPAIR_IN_PROGRESS` itself (no manager/estimate/validator). AFTER: it throws "A manager must proceed..." unless the job is `REPAIR_IN_PROGRESS`, and never writes the job. Path: `RepairScreen._startRepair` → `JobAssignmentService.start` → `PUT /job-assignments/{id}/start` → `JobAssignmentController` → `JobAssignmentServiceImpl.startJob` → `task/assignment IN_PROGRESS`. `RepairTaskServiceImpl.startRepair` had the same guard already.

3. RepairTask completion. BEFORE: precondition in `RepairTaskServiceImpl.completeRepair` was commented out. AFTER: job must be `REPAIR_IN_PROGRESS`. Path: `RepairScreen._completeRepair` → `PUT /job-assignments/{id}/complete` (or `/repair-tasks/{id}/complete`) → `task COMPLETED`; last task → `statusValidator.validate` + job `REPAIR_COMPLETED`.

4. Booking → JobCard. BEFORE: Flutter never sent `bookingId`. AFTER: `BookingDetailScreen._startJobCard` → `WorkflowState.bookingId` → `JobStepScreen` → `CreateJobCardRequest.bookingId` → `POST /workflow/job` → `JobCardServiceImpl.createJobCard/resolveBooking` → `JobCard.bookingId`, `Booking COMPLETED`, `NavigationRequest.jobCardId` (pickup).

5. Pickup trip. `BookingDetailScreen` → `AssignDriverSheet` → `NavigationTripService.assignDriver` → `POST /navigation/trips` → `NavigationTripController` → `NavigationTripServiceImpl.assignDriver` → `NavigationTrip(ASSIGNED)`, request `ASSIGNED`. Driver: `DriverDashboard` → `acceptTrip/startTrip/arriveAtDestination` → `/accept/start/arrive`.

6. Pickup return completion. BEFORE: no UI called `completeTrip` for pickup (the handover screen re-called `continue`). AFTER: `DriverDashboard._DriverAction` (return leg + arrived) → `_complete` → `NavigationTripService.completeTrip` → `POST /trips/{id}/complete` → `completeTrip` → trip + request `COMPLETED`.

7. Pickup OTP. `ActiveTripScreen` → `HandoverCodeScreen` → `GET .../handover/code` → `HandoverServiceImpl.getOrCreateActiveCode` → `VehicleHandover(PENDING, codeHash)`; driver `HandoverVerifyScreen` → `POST .../handover/verify` → `verify` → `VERIFIED`; `_advance` → `continue`.

8. Trip ↔ JobCard linkage. `navigation_request.job_card_id` set by `JobCardServiceImpl.createJobCard` (pickup) and `NavigationRequestServiceImpl.createRequest` (delivery); exposed as `NavigationRequestResponse.jobCardId` and `NavigationTripResponse.jobCardId` (`NavigationTrip.jobCardId` in Flutter).

9. Delivery request. `DeliveryScreen._assignDeliveryDriver` → `CreateDeliveryRequestSheet.show` → `NavigationTripService.createDeliveryRequest` → `POST /navigation/requests` → `NavigationRequestController` → `NavigationRequestServiceImpl.createRequest` → `validateDeliveryRequest` → `NavigationRequest(DELIVERY, REQUESTED, jobCardId, address, lat, lng)`.

10. Delivery map selection. `CreateDeliveryRequestSheet._selectOnMap` → `LocationPickerScreen(mode: delivery)` → `PickupLocation` → `fields` → `resolveDeliveryAddress`.

11. Delivery driver assignment. `DeliveryScreen` → `AssignDriverSheet` → `POST /navigation/trips` (same as pickup; request must be `REQUESTED`). The screen re-loads the request afterwards.

12. Delivery navigation. Driver `ActiveTripScreen` → `DriverLocationTracker` → STOMP → `LiveTripState` on customer/manager; destination = `trip.destinationLatitude/Longitude` (delivery coordinates).

13. Delivery OTP. As #7 with `direction = DELIVERY`; `HandoverVerifyScreen._advance` → `completeTrip`.

14. Delivery evidence. `DriverDashboard` → `TripEvidenceCaptureScreen(stage: 'DELIVERY')` → `TripMediaService.upload` → `POST /trips/{id}/media` → `NavigationTripMediaServiceImpl.upload` (trip `IN_PROGRESS`, arrived) → `completeTrip` → `validateRequiredMedia(DELIVERY)`.

15. Delivery trip completion. `HandoverVerifyScreen._advance` → `POST /trips/{id}/complete` → `NavigationTripServiceImpl.completeTrip` → `setRequestStatus(COMPLETED)`.

16. Delivery → JobCard DELIVERED. `completeTrip` → `deliveryService.completeDeliveryFromTrip(jobCardId, driverName, "Customer (OTP verified)")` → `Delivery(DELIVERED)`, `JobCard.DELIVERED`.

17. Customer journey. `LiveVehicleJourneyScreen` → `GET /customer/vehicle-journeys/active` → `CustomerVehicleJourneyServiceImpl.getActiveJourneys` → linked-pickup rule (§22).

18. Workflow resume/state restoration. Job Card "Resume Workflow" / dashboard → `Routes.employeeWorkflow(jobNumber)` → `WorkflowShellScreen._resume` → `resumeWorkflow` → `syncWorkflowState` → `initializeFromWorkflowStatus`. The Delivery step additionally restores its request from the backend.

31. Sequence Diagrams

Diagram 1 — Normal job workflow

Syntax error in text
mermaid version 10.9.8

Diagram 2 — Pickup

Syntax error in text
mermaid version 10.9.8

Diagram 3 — Delivery

Syntax error in text
mermaid version 10.9.8



Diagram 4 — Media

Diagram 5 — Live navigation



32. Error Handling

Situation	Backend condition / message	Expected UI	Recovery
Manager confirmation rejected	non-manager: "Only a Manager can proceed a Job Card to repair."	snackbar with message	sign in as manager
Estimate not approved	"Estimate must be customer-approved before repair can start."	Approval button only shown when approved	wait for customer
JobCard in wrong state	<code>IllegalStateException</code> "Invalid Job Card status transition: A -> B"	message; screen reloads (<code>JobCardActionsSection</code> refreshes on rejection)	refresh; state is stale
Technician starts too early	"A manager must proceed this Job Card to repair before a Repair Task can be started."	snackbar	manager confirms first
Complete task in wrong state	"Job Card must be in REPAIR_IN_PROGRESS before a Repair Task can be completed."	snackbar	check job status
Delivery request invalid	"A delivery request must reference the Job Card...", "...requires a delivery address with coordinates.", "Delivery can only be requested once the Job Card is ready for delivery.", "...does not match the Job Card's vehicle and customer.", "...does not belong to your garage."	sheet shows message	fix input / wait for payment
Delivery already exists	"A delivery has already been requested for this Job Card." (or unique-index violation)	message; screen reloads request	open Track Delivery
Manual delivery blocked	"A delivery trip exists for this Job Card - delivery completes when the driver completes the trip."	message	complete the trip
Trip not arrived	"Driver must arrive at customer before capturing..." (media); <code>arrive</code> needs <code>IN_PROGRESS</code>	message	press "I Have Arrived"
Evidence missing	"Required {stage} photos are missing: [...]"	driver capture screen lists missing shots	capture them
OTP not generated	"No active confirmation code. Ask the customer to generate a new one."	verify screen error	customer opens code screen
OTP expired / exhausted / wrong	"This confirmation code has expired...", "Too many incorrect attempts...", "Incorrect confirmation code."	error text	customer generates a new code
Handover not verified	"Vehicle handover has not been verified yet - ask the customer for the confirmation code."	error on advance	verify first
Pickup completed too early	"Pickup trip must return to garage before completion.", "Mark arrival at the garage before completing the pickup trip."	snackbar	continue leg, arrive

Situation	Backend condition / message	Expected UI	Recovery
R2 not configured	<code>MEDIA_STORAGE_NOT_CONFIGURED</code> (503)	"Media upload is temporarily unavailable." (item <code>failed</code> , not retried)	set R2 variables
Signed URL expired	upload PUT/GET fails	queue requests a fresh intent; viewer re-requests access	retry
Mapping of exceptions to HTTP status is in <code>GlobalExceptionHandler</code> ; Flutter surfaces <code>ApiException.message</code> (<code>friendlyApiErrorMessage</code>).			

33. Transaction Boundaries

Read from the code (`@Transactional` present unless noted): - **Customer approval** —

`EstimateServiceImpl.approveEstimate(Long) / (String)` are `@Transactional`; estimate save, `createRepairTasks` and the job status write commit together. - **Inspection** → **estimate preparation** —

`ServiceWorkflowServiceImpl.completeInspection(jobCardNumber, list)` is `@Transactional` (inspections + job transition atomic). `createJob`, `prepareEstimate`, `approveEstimate`, `readyForDelivery` in that class are *not* annotated; they delegate to services that are (`JobCardServiceImpl.createJobCard`, `prepareEstimate`, ...). The Flutter chain job-create → inspection-start is **two** transactions. - **Manager confirmation** — `JobCardServiceImpl.startRepair`

`@Transactional`. - **Repair completion** — `RepairTaskServiceImpl.completeRepair`,

`JobAssignmentServiceImpl.completeJob` `@Transactional` (task, assignment sync, job aggregate). - **Delivery trip**

completion — `NavigationTripServiceImpl.completeTrip` `@Transactional`; it calls

`DeliveryServiceImpl.completeDeliveryFromTrip` (`@Transactional`, joins the outer transaction): trip, request, Delivery row and job status commit or roll back together. - **Booking** → **JobCard** — `JobCardServiceImpl.createJobCard`

`@Transactional`: job, booking `COMPLETED` and request `jobCardId` are atomic; a validation failure throws before any write. - **Driver assignment** — `assignDriver` `@Transactional` plus DB unique index (`v42`) for the concurrent-assign race. - **Media processing** — `MediaProcessingScheduler` is not one transaction: R2 writes are idempotent, the row save precedes the source delete (crash-safe).

34. Legacy Compatibility Matrix

Component	Current purpose	Why retained	New code should use?	Backward-compatible behaviour	Possible removal
Google Drive media (<code>GoogleDrive*</code> , <code>/content</code> , <code>POST /job-cards/{id}/media</code> multipart)	old media + retry scheduler	rows exist in production	No (R2 flow)	served through the proxied content path	after migration of old media
R2 rows with original + thumbnail/evidence	old R2 media	not migrated/deleted	No	<code>evidence</code> variant falls back to the original	after an approved migration
Legacy JobCard states <code>ESTIMATE_APPROVED</code> , <code>WORK_COMPLETED</code> , <code>INVOICED</code> , <code>PAYMENT_PENDING</code> , <code>PAYMENT_COMPLETED</code>	old rows	still readable/movable via validator	Do not write	projection/journey map them	when no rows remain
Delivery requests without <code>jobCardId</code>	pre-V61	history	not created anymore	trip completes, no job effect	after backfill or cleanup
Duplicate endpoints <code>/workflow/{n}/...</code> vs <code>/jobcards/{n}/...</code> (repair start, inspection, QC)	two client generations	Flutter uses both	either — they delegate to the same rule	identical behaviour	consolidate later
<code>JobAssignmentType.DRIVER</code> , <code>GET /job-assignments/my/driver</code>	earlier driver model	no writer/caller found	No (use trips)	returns empty	remove
Unused workflow endpoints (<code>POST /workflow/{n}/delivery</code> , <code>/repair/complete</code> , employee <code>/estimate/approve</code>)	compatibility	UI disconnected on purpose	No	<code>/repair/complete</code> is check-only	after client audit
Declared-only statuses (<code>Estimate SENT_FOR_APPROVAL/EXPIRED</code> , <code>RepairStatus ON_HOLD/CANCELLED</code> , <code>JobAssignment ON_HOLD/QC*/REWORK</code> , <code>NavigationRequest/Trip CANCELLED</code> , <code>HandoverStatus CANCELLED</code> , <code>DeliveryStatus PENDING/READY_FOR_DELIVERY</code>)	reserved	DB/enums	not without a feature	never written	prune or implement
<code>flutter_compress</code> dependency	no Dart code imports it; Media3 is declared directly	pubspec change needs approval	No	none	remove from <code>pubspec.yaml</code>
Old media rows without capture metadata	pre-V59	never fabricated	—	footer/metadata sheet omit missing fields	—
<code>ServiceWorkflowServiceImpl.completeInspection(String)</code> (returns null)	overload	unused	No (list overload)		remove

35. Deployment Runbook

1. Backend: run `mvn test` (expect only the known `InvoiceServiceImplTest` failures) and `mvn -DskipTests package` locally.
2. Commit backend (migrations `V60`, `V61` included). **Do not** edit any earlier migration.
3. Deploy the backend on Render (Docker build runs `./mvnw clean package -DskipTests`).
4. On startup Flyway applies pending migrations (V60/V61) before JPA `validate`. Check the Render logs for "Successfully applied" and that the app starts (a validate error means a migration/entity mismatch).
5. Verify in PostgreSQL: `select version, success from flyway_schema_history order by installed_rank desc limit 3;` and `\d navigation_request` shows `job_card_id` and the two indexes.
6. Verify R2 variables exist in Render (names in §36); an unset set yields `MEDIA_STORAGE_NOT_CONFIGURED` on upload.
7. Health: `GET /api/v1/health`.
8. API smoke: authenticated `GET /api/v1/workflow/{n}/status` on a job in `REPAIR_PENDING` returns `completedSteps` **without** `APPROVAL`.
9. Build Flutter: `flutter analyze`, `flutter test`, then the release build (`flutter build appbundle` — needs the local signing files; not part of this handbook's validation).
10. Publish the app **after** the backend (older apps keep working against the new backend; the new app needs V61 + the new delivery-request validation).
11. Manual smoke test: §38 (at least WF-004/005, PK-004/005, DL-001...006). **Rollback:** redeploy the previous backend build — safe against the V60/V61 schema (additive, nullable/defaulted). Old *apps* cannot create delivery requests against the new backend (no `jobCardId`/coordinates → rejected). Data rollback (dropping `job_card_id`) needs a new migration and loses the delivery↔job link; delivery trips completed by the new code have already written Delivery rows and `DELIVERED` job status, which a code rollback does not undo.

36. Render, Cloudflare R2 and Environment

- **Render:** Docker web service from the backend `Dockerfile`, PostgreSQL database; `server.port=${PORT:8080}`; production URL `https://garage-st-backend.onrender.com`.
- **R2:** private bucket; no public URLs; every access is a presigned URL from `R2MediaStorageProvider`. Object naming §23. Trip media is **not** in R2.
- **Environment variable names only:** `DB_HOST DB_PORT DB_NAME DB_USERNAME DB_PASSWORD PORT · R2_ACCOUNT_ID R2_ACCESS_KEY_ID R2_SECRET_ACCESS_KEY R2_BUCKET_NAME R2_UPLOAD_URL_TTL_MINUTES R2_PLAYBACK_URL_TTL_MINUTES · GOOGLE_MAPS_ROUTES_API_KEY GOOGLE_MAPS_PLACES_API_KEY · GOOGLE_DRIVE_APPLICATION_NAME GOOGLE_DRIVE_CLIENT_ID GOOGLE_DRIVE_CLIENT_SECRET GOOGLE_DRIVE_REDIRECT_URI GOOGLE_DRIVE_ROOT_FOLDER_ID` (legacy). JWT settings live under `security.jwt.*` (see §7 limitation). Flutter: `EnvConfig` via `--dart-define`; Android Maps key via local, gitignored Gradle properties.

37. Testing Strategy and Test Evidence

Strategy: backend Mockito service tests (`mvn test`); `ServiceWorkflowServiceImplCompleteInspectionRollbackIT` needs local PostgreSQL and is not in the default run. Flutter: `flutter analyze`, `flutter test` (unit + widget), `flutter build apk --debug`. GPS, maps, STOMP, native video, OTP UX, R2 need **manual** device tests (§38).

Key tests for the 2026-09-30 change: `ManagerConfirmationGateTest`, `NavigationTripLifecycleTest`, `NavigationRequestDeliveryTest`, `DeliveryCompletionTest`, `JobCardBookingLinkTest`, additions in `RepairTaskServiceImplJobAssignmentSyncTest` and `CustomerVehicleJourneyServiceImplTest`; Flutter `workflow_approval_gate_test.dart`, `assign_driver_test.dart`. Media: `EvidenceOnlyMediaModelTest`, `MediaKeysAndEvidenceTextTest`, `media_upload_queue_video_evidence_test.dart`, `video_viewport_test.dart`, `media_evidence_text_test.dart`.

Evidence (from the runs recorded below; commands executed from each repo root):

Check	Command	Result
Backend tests	<code>mvn -o test</code>	FAIL (known, unrelated) — 167 run, 2 failures + 1 error, all in <code>InvoiceServiceImplTest.receivePayment_*</code> (pre-existing); every other test passes
Backend package	<code>mvn -o -q package -DskipTests</code>	PASS (jar built; run earlier in this task)
Flutter analyze	<code>flutter analyze</code>	PASS — 0 errors, 0 warnings, 96 info-level lints
Flutter tests	<code>flutter test</code>	PASS — 306 tests
APK	<code>flutter build apk --debug</code>	PASS (run earlier in this task)
AAB / release build	—	NOT RUN
V61 on PostgreSQL	—	ENVIRONMENT REQUIRED (not executed)
Device flows (§38)	—	MANUAL REQUIRED
<code>start_repair</code> projection filter	—	no automated test (NOT COVERED)
<code>DeliveryScreen</code> restoration	—	no widget test (NOT COVERED); logic exercised via service tests only
Known unrelated failures: 3 in <code>InvoiceServiceImplTest</code> (<code>receivePayment_*</code>), present before this work.		

38. Manual Test Matrix

All rows are **manual/device required** unless stated. Roles: M manager, T technician, D driver, C customer.

ID	Scenario	Role	Precondition	Steps	Expected result	Backend state
WF-001	Job creation	M	customer + vehicle exist	+ Workflow → job step → complaints, odometer, date → save	Inspection step opens	JobCard <code>INSPECTION_PENDING</code>
WF-002	Inspection	M	WF-001	save all inspections	Estimate step	<code>INSPECTION_COMPLETED</code> → <code>ESTIMATE_PENDING</code>
WF-003	Estimate	M	WF-002	create, add items, summary → proceed	Approval step "waiting"	<code>WAITING_FOR_APPROVAL</code> , estimate <code>WAITING_FOR_APPROVAL</code>
WF-004	Customer approval	C→M	WF-003	customer approves; manager opens/refreshes	Approval shows "Customer Approved — Manager Confirmation Required"; Repair NOT started	Estimate <code>APPROVED</code> , tasks <code>PENDING</code> , job <code>REPAIR_PENDING</code> ; <code>completedSteps</code> lacks <code>APPROVAL</code>
WF-005	Manager confirmation	M	WF-004	tap Proceed to Repair	Repair step	<code>REPAIR_IN_PROGRESS</code>
WF-006	Technician repair	T	WF-005, task assigned	before WF-005: try start (must fail); after: accept, start, complete	start blocked then allowed; last task → QC next	tasks <code>IN_PROGRESS/COMPLETED</code> ; job <code>REPAIR_COMPLETED</code>
WF-007	QC	M	WF-006	proceed to QC → pass	Invoice step	<code>QUALITY_CHECK</code> → <code>READY_FOR_INVOICE</code>
WF-008	Invoice/payment	M	WF-007	generate invoice; customer accepts; pay	Delivery step	<code>INVOICE_GENERATED</code> → <code>READY_FOR_DELIVERY</code>
PK-001	Pickup creation	C,M	garage exists	book with pickup; manager confirms; assign driver	driver sees trip	request <code>ASSIGNED</code> , trip <code>ASSIGNED</code>
PK-002	Pickup navigation	D	PK-001	accept, start, open map	route to customer; customer sees driver	trip <code>IN_PROGRESS</code> , request <code>IN_PROGRESS</code>
PK-003	Pickup OTP	D,C	arrived + 5 photos	customer opens code; driver enters	"Pickup confirmed"	handover <code>VERIFIED</code>
PK-004	Pickup return	D	PK-003	Start Return to Garage; navigate; arrive	route to the garage ; no OTP/evidence asked	leg <code>CUSTOMER_TO_GARAGE</code> , <code>arrivedAt</code> set
PK-005	Pickup completion	D,M	PK-004	Complete Pickup Trip; then Create Job Card from booking	trip completed; job linked	trip/request <code>COMPLETED</code> ; <code>JobCard.bookingId</code> set, Booking <code>COMPLETED</code> , request <code>jobCardId</code> set

ID	Scenario	Role	Precondition	Steps	Expected result	Backend state
DL-001	Delivery request	M	job READY_FOR_DELIVERY	Delivery → Request Delivery	sheet opens; reopening step restores state	request REQUESTED (jobCardId set)
DL-002	Delivery map	M	DL-001	Select on map; confirm	address + lat/lng shown	request has address, lat, lng
DL-003	Driver assignment	M,D	DL-002	assign driver; driver accepts	driver sees delivery trip	trip ASSIGNED → ACCEPTED ; request ASSIGNED
DL-004	Delivery navigation	D,C	DL-003	start; navigate	marker at chosen delivery point; customer tracks	trip IN_PROGRESS
DL-005	Delivery OTP	D,C	arrived + 5 delivery photos	customer opens code; driver verifies	"Delivery confirmed"	handover VERIFIED (DELIVERY)
DL-006	Delivery completion	D,M	DL-005	Complete Delivery; manager reopens step; Close Job	job delivered then closed; manual delivered button absent	trip/request COMPLETED ; Delivery DELIVERED ; job DELIVERED → CLOSED
NAV-001	STOMP	D,C	active trip	move >10 m	customer marker moves smoothly	rows in driver_location_history
NAV-002	REST fallback	C	active trip	drop socket / airplane toggle	marker updates ≈ every 10 s	—
MED-001	Image	M/T	job open	capture image with GPS	evidence footer incl. address, lat/lng, accuracy; thumbnail in grid	R2: _evidence.jpg , _thumbnail.jpg only; evidence_only=true
MED-002	Video	M/T	job open	record portrait + landscape	evidence burned in; correct size; thumbnail	R2: _evidence.mp4 , _thumbnail.jpg
MED-003	Customer playback	C	MED-001/002	open media	evidence shown, video plays; repeat open uses cache	—
MED-004	Legacy media	M,C	old media exist	open old image/video	still displays	unchanged rows

39. Debugging Runbook

Approval screen skipped: `GET /workflow/{n}/status` → is `completedSteps` containing `APPROVAL` while `status = REPAIR_PENDING?` (should not). Check `JobCard.status`, `Estimate.status`. If backend is right, inspect `WorkflowController._onWorkflowStateChanged` (debug log "WORKFLOW RESOLVE") and any screen calling `nextStep()` after a refresh. **Technician cannot start repair:** `JobCard` status (must be `REPAIR_IN_PROGRESS`), `RepairTask` `ASSIGNED`, `JobAssignment` `ACCEPTED`, manager confirmation done? Error text says which. **Pickup stuck:** `TripStatus`, `TripLeg`, `arrivedAt` (reset by `continue`), `vehicle_handover` (status/expiry/`failed_attempts`), photos per stage (`navigation_trip_media` shot types), `NavigationRequest.status`. On the return leg the driver needs "I Have Arrived" then "Complete Pickup Trip". **Delivery doesn't appear / can't be requested:** `navigation_request` row (`request_type='DELIVERY'`, `job_card_id`, status), `GET /navigation/requests/job-card/{id}/delivery`, job status `READY_FOR_DELIVERY`, address+coordinates present, unique index violations, `DeliveryScreen` reload (`_loadDeliveryRequest`). **Delivery completed but job not DELIVERED:** request has `job_card_id`? (NULL = legacy); invoice `GENERATED` + `PAID`?; a `delivery` row already exists?; transaction rolled back (trip stays `IN_PROGRESS`). **Navigation not updating:** location permission + service enabled; driver has `ActiveTripScreen` open; STOMP connected and subscribed to `/topic/trips/{id}/location`; interceptor authorization; REST fallback (`GET .../location`); distance filter (10 m) — a stationary driver publishes nothing; route recalculation only after 150 m. **Media not loading:** R2 variables; upload intent response (`storageKey`); `/complete` called; row `upload_status/retry_count/last_error`; `evidence_key` set (images render asynchronously, `available=false` until then); presigned URL age (TTL 10 min); Flutter cache key (`media-video-{id}`); for video, `thumbnailUploaded` and thumbnail object existence. **Migration/startup failure:** `ddl-auto=validate` mismatch → check `flyway_schema_history` and entity columns.

40. Architectural Rules — DO NOT BREAK THESE

1. JobCard ≠ RepairTask; task work never writes job state except the all-tasks-complete aggregate.
2. Customer approval ≠ manager confirmation; only `JobCardServiceImpl.startRepair` moves `REPAIR_PENDING` → `REPAIR_IN_PROGRESS`.
3. Backend business state is authoritative; Flutter derives steps from `completedSteps` and never advances locally past a status-refreshing mutation.
4. Every writer of `JobCard.status` goes through `JobCardStatusValidator`.
5. A delivery completes through its delivery trip; the manual `/deliveries` record must not contradict it.
6. Trip/delivery state must not live only in Flutter screen state.
7. Direct-to-R2 media upload; no Spring media proxy; do not raise the multipart limit.
8. New media = evidence + thumbnail, no permanent original; legacy media stays compatible; no destructive migration without approval.
9. No secrets in source control; never document values.
10. Never modify an applied Flyway migration.
11. Keep `JobCardMedia` and `NavigationTripMedia` separate.
12. Do not reintroduce a garage-side OTP or a second `continueTrip` on the return leg.

41. Architecture Decision Records

ADR-001 — Direct-to-R2 media upload

Status: Accepted (implemented). **Context:** Drive-backed uploads buffered whole files in the JVM and had no range support. **Problem:** large photos/videos through Spring exhaust memory and hit the multipart limit. **Decision:** presigned PUT to a private R2 bucket + persistent Flutter queue; backend verifies at `/complete`. **Alternatives:** raise multipart limit (rejected); proxy streaming through Spring (rejected: cost/latency); keep Drive. **Why:** Spring never touches bytes; resumable client queue. **Consequences:** client owns retry; orphan rows on URL expiry; R2 config needed. **References:** `MediaServiceImpl.createUploadIntent/completeUpload`, `R2MediaStorageProvider`, `MediaUploadQueueService`.

ADR-002 — Evidence is the canonical new media

Status: Accepted. **Context:** original + evidence + thumbnail tripled storage and exposed unstamped originals. **Problem:** need tamper-evident, single asset. **Decision:** store only evidence + thumbnail; images rendered server-side from a temporary source, videos rendered on-device (Media3). **Alternatives:** keep originals; FFmpeg (APK size, license); server video processing (no decoder on Render). **Why:** Media3 already in the APK; one file to serve. **Consequences:** two renderers kept in sync by test literals; `evidence_only` flag; legacy fallback. **References:** `MediaProcessingScheduler`, `MediaEvidenceText`, `EvidenceVideoProcessor.kt`, `media_evidence_text.dart`.

ADR-003 — JobCard state vs RepairTask state

Status: Accepted. **Context:** technician actions were flipping the job. **Problem:** task state substituted for job state. **Decision:** separate machines; task start/complete require the job to be `REPAIR_IN_PROGRESS`; the only coupling is the automatic all-complete aggregate. **Alternatives:** derive job state from tasks (rejected). **Why:** manager gate must be unbypassable. **Consequences:** technicians blocked until confirmation. **References:** `JobAssignmentServiceImpl.startJob`, `RepairTaskServiceImpl.startRepair/completeRepair`.

ADR-004 — Customer approval vs manager confirmation

Status: Accepted. **Context:** approval landed the job at `REPAIR_PENDING` and the projection marked `APPROVAL` complete. **Problem:** manager skipped the Approval screen. **Decision:** keep `REPAIR_PENDING` as the "approved, awaiting manager" state; complete `APPROVAL` only at `REPAIR_IN_PROGRESS`; confirmation stays `POST /workflow/{n}/repair/start`. **Alternatives:** new `MANAGER_CONFIRMATION_PENDING` status (more migration/validator/legacy churn, rejected); client-side flag (violates backend authority). **Why:** smallest consistent change. **Consequences:** `resolveCompleted` is the single place encoding the distinction; screens must not `nextStep()` after refresh. **References:** `ServiceWorkflowServiceImpl.resolveCompleted`, `JobCardServiceImpl.startRepair`, `ApprovalScreen`.

ADR-005 — Trip ↔ JobCard linkage

Status: Accepted. **Context:** trips/requests referenced only vehicle/customer/garage; the journey guessed by vehicle. **Decision:** one nullable `navigation_request.job_card_id` (delivery = job delivered; pickup = job created from its booking). **Alternatives:** FKs on trips and bookings; new join table; backfill legacy rows (rejected as unnecessary). **Why:** minimal, no duplicate relationship. **Consequences:** legacy rows NULL; no FK constraint; partial unique index. **References:** V61, `NavigationRequestServiceImpl`, `JobCardServiceImpl.createJobCard`, `CustomerVehicleJourneyServiceImpl`.

ADR-006 — Delivery trip completion is the delivery completion

Status: Accepted. **Context:** `POST /deliveries` and trip completion were independent. **Problem:** contradictory completion paths. **Decision:** completing a verified delivery trip creates the Delivery row and moves the job to `DELIVERED` in one transaction; manual delivery only when no delivery request exists. **Alternatives:** trip completion informational only; remove `/deliveries`. **Why:** OTP + evidence should be what proves delivery. **Consequences:** requests need `jobCardId`; legacy requests don't affect jobs. **References:** `NavigationTripServiceImpl.completeTrip`, `DeliveryServiceImpl.completeDeliveryFromTrip/createDelivery`.

ADR-007 — Map-based delivery location

Status: Accepted. **Context:** delivery address was free text with optional coordinates. **Decision:** reuse `LocationPickerScreen`; require address + latitude + longitude (address falls back to the coordinates). **Alternatives:** second picker; keep text-only. **Why:** navigation needs coordinates; one picker to maintain. **Consequences:** old apps can no longer create delivery requests. **References:** `CreateDeliveryRequestSheet`, `NavigationRequestServiceImpl.validateDeliveryRequest`.

42. Change Log

2026-09-30 — Workflow + trip/navigation architecture - Approval: `APPROVAL` completes only at `REPAIR_IN_PROGRESS`; approval screen shows manager-confirmation state; `resolveStep` aligned to the shell numbering. - Repair: technician start no longer moves the job; task completion requires `REPAIR_IN_PROGRESS`; `start_repair` action manager-only. - Pickup: return-leg completion (arrive + complete), OTP refused on the return leg, request `IN_PROGRESS/COMPLETED` written. - Booking ↔ JobCard: `bookingId` sent from the workflow (Booking screen → Create Job Card); pickup request linked to the job. - Delivery: request tied to a job (V61) with address + coordinates, rediscovery endpoint, trip completion creates the Delivery and marks the job `DELIVERED`, manual delivery guarded; Delivery screen restores from the backend. - Map: delivery location selected with `LocationPickerScreen`. - Journey: linked pickup trips no longer hide the job-card stage. - Validation: see §37. **2026-09-30 (earlier) — Media:** evidence + thumbnail only, on-device video burn-in, orientation-correct output (`V60`).

43. How to Maintain This Handbook

1. Read the relevant section before changing architecture.
2. Inspect the actual code before changing documented behaviour — if they disagree, the code wins and the handbook must be fixed.
3. Update this handbook in the same task as any architectural change.
4. Add or amend an ADR for every significant decision (status, alternatives, consequences, references).
5. Update the state-machine tables (§9) whenever a transition, writer or guard changes.
6. Update the API reference (§27) when a business endpoint, role or validation changes.
7. Add recurring problems to the debugging runbook (§39) and error table (§32).
8. Never document secrets — names of variables only, no values (including defaults found in property files).
9. Never document unimplemented behaviour as current; mark *Declared-only* / *Not implemented* explicitly.
10. Keep legacy behaviour labelled in §34 and record removal criteria.

Source	D:\garageos-backend\GARAGEST_DEVELOPER_HANDBOOK.md
Generated	2026-09-30 (rendered from the Markdown source, headless Edge print pipeline)
Architecture version / date	Workflow + trip/navigation architecture, 2026-09-30 (migrations V60, V61)
Source of truth	The handbook Markdown file is the source of truth; regenerate this PDF after every handbook change.
Diagrams	5 Mermaid diagrams rendered as vector SVG; sources retained below.

Appendix — Mermaid diagram sources

Diagram 1 source

```
sequenceDiagram
    actor C as Customer
    actor M as Manager
    actor T as Technician
    participant F as Flutter
    participant B as Backend
    C->>B: Booking (POST /bookings)
    M->>B: confirm (POST /bookings/{id}/confirm)
    M->>F: Create Job Card (bookingId)
    F->>B: POST /workflow/job (bookingId) → JobCard OPEN, Booking COMPLETED
    F->>B: POST /workflow/{n}/inspection/start → INSPECTION_PENDING
    F->>B: POST /workflow/{n}/inspection/complete + /estimate → ESTIMATE_PENDING
    M->>B: PUT /estimates/{id} → WAITING_FOR_APPROVAL
    C->>B: PUT /estimates/{id}/approve → Estimate APPROVED, tasks PENDING, REPAIR_PENDING
    M->>B: POST /workflow/{n}/repair/start → REPAIR_IN_PROGRESS (manager gate)
    T->>B: job-assignments accept/start/complete → tasks COMPLETED → REPAIR_COMPLETED (auto)
    M->>B: POST /workflow/{n}/quality-check, QC pass → READY_FOR_INVOICE
    M->>B: POST /workflow/{n}/invoice → INVOICE_GENERATED
    M->>B: POST /workflow/{n}/payment → READY_FOR_DELIVERY
    Note over M,B: Delivery (Diagram 3) → DELIVERED
    M->>B: PUT /jobcards/{n}/close → CLOSED
```

Diagram 2 source

```
sequenceDiagram
    actor C as Customer
    actor D as Driver
    actor M as Manager
    participant B as Backend
    C->>B: Booking (pickupRequested)
    M->>B: confirm → NavigationRequest(PICKUP, REQUESTED)
    M->>B: POST /navigation/trips → Trip ASSIGNED, request ASSIGNED
    D->>B: accept, start → Trip IN_PROGRESS (GARAGE_TO_CUSTOMER), request IN_PROGRESS
    D->>B: arrive (arrivedAt)
    D->>B: 5 BEFORE_PICKUP photos
    C->>B: GET handover/code (OTP)
    D->>B: POST handover/verify {code} → VERIFIED
    D->>B: POST continue → CUSTOMER_TO_GARAGE (arrivedAt reset)
    D->>B: arrive at garage
    D->>B: POST complete → Trip COMPLETED, request COMPLETED
    M->>B: POST /workflow/job (bookingId) → JobCard; request.jobCardId set; Booking COMPLETED
```

Diagram 3 source

```
sequenceDiagram
    actor M as Manager
    actor D as Driver
    actor C as Customer
    participant F as Flutter
    participant B as Backend
    Note over B: JobCard READY_FOR_DELIVERY
    F->>B: GET /navigation/requests/job-card/{id}/delivery (404 = none)
    M->>F: Select location on map (LocationPickerScreen)
    F->>B: POST /navigation/requests (DELIVERY, jobCardId, address, lat, lng)
    M->>B: POST /navigation/trips (driver) → Trip ASSIGNED
    D->>B: accept, start; GPS → STOMP
    D->>B: arrive; 5 DELIVERY photos
    C->>B: GET handover/code
    D->>B: POST handover/verify → VERIFIED
    D->>B: POST /navigation/trips/{id}/complete
    B->>B: request COMPLETED; DeliveryService.completeDeliveryFromTrip
    B->>B: Delivery(DELIVERED); JobCard READY_FOR_DELIVERY → DELIVERED (one transaction)
    M->>B: PUT /jobcards/{n}/close → CLOSED
```

Diagram 4 source

```
sequenceDiagram
    participant F as Flutter queue
    participant B as Backend
    participant R as R2
    F->>B: POST upload-intent (stage, metadata)
    B-->>F: presigned PUT (+ thumbnail PUT for video), storageKey
    F->>R: PUT source (image) / evidence.mp4 + thumbnail.jpg (video)
    F->>B: POST /media/{id}/complete
    B->>R: (image) download source
    B->>R: upload _evidence.jpg + _thumbnail.jpg, delete _source
    B-->>B: status COMPLETED, storage_key = evidence
    F->>B: GET /media/{id}/access?variant=evidence|thumbnail
    B-->>F: short-lived presigned GET
    F->>R: GET (cached as media-evidence-{id} / media-video-{id})
```

Diagram 5 source

```
sequenceDiagram
    participant G as Geolocator (10 m filter)
    participant D as DriverLocationTracker
    participant S as STOMP /ws
    participant B as Backend
    participant V as Customer/Manager LiveTripState
    G->>D: position
    D->>S: SEND /app/location/update
    S->>B: LocationWebSocketController → DriverLocationServiceImpl
    B-->>V: /topic/trips/{id}/location
    loop every 10 s (fallback)
        V->>B: GET /navigation/trips/{id} and /location
    end
    V->>B: POST /navigation/routes (only after ≥150 m movement)
```

