SkillNavora GenAI Launchpad · Written by Varun Kumar · Part 5 of the automation series

Make.com: Scenarios, Routers and AI Agents

Make is a visual automation tool. You connect apps as boxes on a canvas and draw the flow between them. This guide takes you from your first scenario to the Resume Analysis Agent from the class. It uses fake data and a test account throughout.

1. Words you need first

Word	Meaning
Scenario	One automation: a chain of modules that runs in order.
Module	One step, such as "Watch responses" or "Add a row".
Trigger	The first module, which starts the scenario (a new form response, a schedule, a webhook).
Bundle	One item of data passing between modules.
Router	A split that sends each bundle down one or more paths based on filters.
Filter	A condition on a path, for example "score is above 70".
Connection	The saved login to an app (a credential). Use a test account.
Operation	Spend of the plan's credits per module run. Check the plan page for current credit rules.

2. The Make screen

The left menu has: **Org**, **Scenarios**, **AI Agents**, **Credentials**, **Webhooks**, **MCP Toolboxes**, **Templates**, **Data stores** and **More**. The canvas in the middle is where you build. The bottom toolbar has **Run once**, a schedule toggle (for example every 15 minutes) and the undo and settings icons.

3. Your first scenario: form to sheet

1. Click **Scenarios**, then **Create a new scenario**.
2. Add a **Google Forms** module, choose **Watch Responses**, and connect the test account. Pick a test form with two fields.

3. Add a **Google Sheets** module and choose **Add a Row**. Select a test sheet.
4. Map each form answer to a column using the mapping panel (click a field, choose the answer).
5. Click **Run once**, then submit one test response to the form.

You should see: the module bubbles turn green, the sheet gets a new row, and the output panel shows the values you mapped.

4. Scheduling and settings

- **Schedule:** the toggle sets how often the scenario checks for new items. The class example was every 15 minutes. Shorter intervals use more operations.
- **Sequential running:** keep it on when order matters, so two runs cannot write at the same time.
- **Error handling:** right-click a module to add an error route. Route failures to a sheet row or a message so they are visible.
- **Notifications:** decide when Make emails you about failed runs. Turn on notifications for failures, not for every success.

> **Before you enable a scenario,** check three things: its operations per month against your plan, its notification setting, and what happens on failure. A scenario left running on a schedule keeps spending operations.

5. Routers and filters

A router is a fork in the road. The class example, the Resume Analysis Agent, uses one.




Figure 1. A router splits bundles into paths. Each path has a filter.

1. Click the wrench icon between two modules and choose **Add router**.
2. Add a filter to each route (for example the AI score field equals "Strong Fit").

3. Test with one bundle that matches and one that does not. Confirm only the right route runs.

6. The Resume Analysis Agent (class example)

The class scenario was built to read a candidate's resume and sort the candidate. The full chain is:

1. **Google Forms (Watch Responses):** the candidate submits a form with a resume file link.
2. **Google Drive (Download a File):** the resume file is fetched from Drive.
3. **AI agent:** reads the resume, uses a knowledge source (the job criteria) and returns a fit rating.
4. **Router:** route 1 adds a row to Google Sheets for every candidate; route 2 sends a Slack message only for "Strong Fit" candidates.

The agent in the screenshot also had an **Add tool** option, an **Add MCP** option, a **Chat** option and a knowledge attachment. The AI model module was an OpenAI connection in the class.

> **Privacy.** A resume contains personal data. For practice, use a fake resume with a made-up name and email. Do not send real candidates' files to a test scenario, and do not post Slack messages to a shared channel during testing.

Build checklist

Step	You should see
Forms trigger runs on a test response	One bundle with the form fields
Drive download returns a file	A file name and size in the output
AI step returns a fixed-format rating	One word from your allowed list (for example Strong Fit, Possible, No Fit)
Router sends only matching bundles to Slack	Slack message only for Strong Fit
Failed AI step	Error route writes a row marked "needs attention"

7. Maia: building with a description

Maia is Make's AI assistant (labelled Beta in the class screenshots). You describe what you want in plain English, and Maia proposes modules. The panel offers "Continue where we left off", "Get inspiration" and "Ask a question about Make".

1. Open a scenario and click **Build with Maia**.

2. Describe the goal in one sentence: "When a form is submitted, download the attached file, ask an AI model to rate it, and add a row to a sheet."
3. Review every module Maia proposes. Check each connection, field mapping and filter yourself.
4. Never trust a generated scenario without running it on fake data first.

Maia is a drafting aid. The person who runs the scenario owns its results, so review every step.

8. MCP Toolboxes and AI Agents in Make

MCP (Model Context Protocol) is a standard way for an AI app to use outside tools. Make's MCP Toolboxes group tools that an agent can call. Give an agent only the tools it needs, and read-only tools where possible. The same least-permission rule from the skills and agents guide applies here.

9. Failure, retries and cost

Issue	What to do
Module fails on a bad file	Route the error to a "needs attention" row; fix the input; re-run that bundle.
Scenario runs too often	Lengthen the schedule or use a webhook trigger instead of polling.
Operations run out	Check the plan usage page and reduce the schedule or the number of modules per run.
Duplicate rows	Store the form response ID and skip responses already in the sheet.

Check Make's current plan and credit page before you estimate cost. Plans and credit rules change.

10. Quick check

1. What starts a scenario?
2. What does a filter do on a router path?
3. Why should you use a test connection?
4. What should you do before enabling a scenario that Maia built?

Answers: 1. The trigger module (for example a new form response). 2. Decides whether a bundle goes down that path. 3. So a mistake cannot touch real accounts or data. 4. Run it on fake data and check every module and filter.

11. Glossary and further reading

- Make help centre: help.make.com (scenarios, routers, Maia and MCP pages).
- Make pricing and credit page: check the live page before you estimate operations.

Part 2. Every Make option you need, explained

Make's labels can change between releases. The terms below are the concepts you will meet; if a menu name differs, look for the closest match.

2.1 Words on the canvas

Word	Meaning	Example
Scenario	The whole automation	Resume Analysis Agent
Module	One step (a bubble on the canvas)	Google Sheets: Add a Row
Bundle	One item of data passing between modules	One form response
Route (connection)	The line that carries bundles from one module to the next	Watch Responses → Download a File
Mapping	Choosing which earlier field fills a later field	Email field → Email column
Connection	Saved login for an app	Google account (test)
Data store	Make's built-in table for keeping records between runs	Processed response IDs
Operation	One module action; plans include a set number. Check the live plan page.	Each module run counts

2.2 Trigger modules: how a scenario starts

Trigger type	Starts when	Use it for	Watch out
Schedule	At the interval you set (the class used every 15 minutes)	Checking a sheet or inbox regularly	Each check uses operations even when nothing is new
Watch responses (Google Forms)	A new form response arrives	Intake forms	File uploads come as links; you need a Drive download step
Custom webhook	Another app posts to the Make URL	Real-time events from your own app	Use a test run while building; activate the scenario for live use

Watch new rows (Sheets)	A new row appears	Reacting to sheet data	Sheet changes can be batched; test with a few rows
Manual run	You press Run once	Building and debugging	Not automatic

2.3 Module types you will use

Module type	Examples	What to set
App action	Google Drive: Download a File; Google Sheets: Add a Row; Slack: Send a Message; Gmail: Send an Email	Connection, the action, and the field mapping
Flow control	Router, Filter, Repeater, Iterator, Aggregator, Sleep	Routes, filter conditions, the batch logic
Data tools	Set variable, Text parser, JSON parse, Tools	Use these to clean data before an AI step
Data store	Data store: Add record, Search records, Get record	Store, key field, record fields
AI module	An AI model call (OpenAI in the class example; check the apps list for other providers)	Connection, model, prompt, and output format
AI agent	The agent builder: tools, knowledge, chat	Goal, tools with least permission, stop rule
Error handler	Break, Resume, Commit, Rollback, Ignore directives on a module	Choose per module (section 4)

2.4 Filters and routers in detail

Concept	Plain meaning	Example
Router	Splits one route into several; each path has a filter	Path 1: all candidates to Sheets; Path 2: Strong Fit to Slack
Filter	A condition on a path; only matching bundles pass	AI rating equals "Strong Fit"
Fallback path	A path with no filter that catches everything else	Route anything unclassified to a review sheet
Text operators	Contains, equals, starts with	Rating text contains "Strong"
Number and date operators	Greater than, less than, after	Start date after today

> **Always add a fallback path** on a router. Without it, a bundle that matches no filter stops quietly and you will not know it happened.

Part 3. Build your own Make scenario: a 12-step recipe

1. **Write the goal in one sentence.** Example: "When a candidate submits a fake resume, rate it and log it."
   Check: you can state the output.
2. **List the inputs and fields**, with example values.
   Check: every field has a name and a sample.
3. **Choose the trigger**: manual to build, a form or webhook for real events, a schedule for polling.
   Check: Run once returns one bundle.
4. **Add the first action** and map a field. Run once.
   Check: the target row or message shows the mapped values.
5. **Add validation**: a filter that stops empty or malformed bundles, routed to a review path.
   Check: a bad input goes to review, not to the output.
6. **Add the AI step last among the data steps.** Ask for one fixed word from a list, not free text.
   Check: the output matches the list every time in five tests.
7. **Add the router** with a filter per path and a fallback.
   Check: each test bundle reaches exactly one path.
8. **Add the external action** (Slack, Gmail) only on the right path and only with a test channel or address.
   Check: the test channel receives one message per matching bundle.
9. **Set error handling** on each risky module (section 4).
   Check: force a failure; the error route writes "needs attention".
10. **Prevent duplicates** with a data store: search for the response ID before writing.
    Check: running the same bundle twice writes one row.
11. **Test five inputs**: normal, empty field, duplicate, unexpected AI output, and a tool failure.
    Check: each result matches the test plan (section 6).
12. **Activate and watch the first runs**, then review history daily while learning.
    Check: the run history shows green runs and any red runs are explained.

Part 4. Error handling, explained simply

Directive	What it does	Use it when
Resume	Continues the scenario using a substitute value	A non-critical field is missing

Ignore	Skips the failed bundle and continues the run	Losing this one item is acceptable and logged
Break	Stores the failed bundle to retry later	A temporary outage (for example an app is down)
Commit	Keeps the work done so far and stops the run	Partial results are still valid
Rollback	Undoes changes where the app supports it	An all-or-nothing change

For practice, use **Break** for external steps (so you can retry them) and **Resume** for optional fields. Write the choice in a note on the scenario, so the next person knows why it is set that way.

Part 5. The Resume Analysis Agent, built step by step (fake data only)

> **Fake data only.** Create a test Google Form with a made-up candidate (for example "Test Candidate", candidate.test@example.com) and a sample file. Do not upload real resumes. This tool must not make hiring decisions; a person reviews every result.




Figure 3. The Resume Analysis Agent layout, redrawn for SkillNavora.

1. **Create the scenario** "Resume analysis (test)" and add **Google Forms: Watch Responses**. Choose the test form and run once after one fake submission.
2. **Add Google Drive: Download a File**. Map the file ID from the form's upload field. Run once. *Check:* the bundle now includes the file name and content.
3. **Add the AI step.** Use one prompt with a fixed output: "Reply with exactly one of: Strong Fit, Possible, No Fit. Base the answer only on the job criteria provided." Provide the criteria as fixed text, not a real job list.
   Check: five fake resumes return only those three words.

4. **Add the router.** Path 1: Google Sheets Add a Row for every bundle (fallback-free). Path 2: a filter "rating equals Strong Fit", then Slack Send a Message to a test channel.
   Check: a Strong Fit test reaches both paths; a No Fit test reaches only Sheets.
5. **Add error handling.** On the Drive and AI modules, set Break; add an error route that writes "needs attention" and the error text to a sheet.
   Check: disconnect the Drive link for one run; the error row appears and no Slack message is sent.
6. **Add a duplicate check** with a data store keyed by form response ID.
   Check: the same response submitted twice writes one row.
7. **Review every output** before any real use. A person decides what happens next.

Part 6. Maia, the AI scenario builder

Maia (labelled Beta in the class screenshots) drafts a scenario from a plain-language description. The panel offers "Continue where we left off", "Get inspiration" and "Ask a question about Make".

Maia can help with	You must still check
Drafting the module order from a description	Each connection and which account it uses
Suggesting modules you have not used before	Every field mapping and filter
Explaining an existing scenario	Whether the scenario is safe to run with real data
Answering "how do I" questions about Make	That the answer matches the current product (check the help centre)

Rule: never run a Maia-built scenario on real data before you have run it on fake data and read each module's output.

Part 7. MCP and Make

MCP (Model Context Protocol) is a standard way for AI applications to use outside tools. Make's MCP toolboxes group tools an agent can call. A tool is a single action, such as reading a sheet or posting a message.

Concept	Plain meaning	Safe default
Input	What the agent sends to the tool	Only the fields the tool needs
Output	What the tool returns to the agent	Read-only results where possible

Scope	Which account data the tool can reach	A test account with fake data
Permission	Whether the tool can read, write or send	Read first; add write only when needed
Approval boundary	The point where a person must approve	Before any send, delete or access change
Audit log	A record of each tool call	Keep it, without personal data

Part 8. Full test plan

Test	Input	Pass when
Happy path	Fake strong candidate	Sheets row and Slack alert
Weak candidate	Fake no-fit candidate	Sheets row only
Unexpected AI output	Forced odd answer	Error route, no Slack message
Missing file	Form with no upload	Error route with a clear reason
Duplicate response	Same response twice	One row only
Slack down	Disconnect Slack	Break directive stores the bundle for retry

Part 9. Common errors

Error	Cause	Fix
Empty output field	Mapping points to the wrong module	Re-map from the latest module output
Connection expired	Login was revoked	Reconnect the test account
Scenario runs but nothing happens	Router has no matching path and no fallback	Add a fallback path
Operations used up quickly	Short schedule on a large scenario	Lengthen the schedule; reduce modules
Duplicate rows	No duplicate check	Add the data store check (Part 3, step 10)

Part 10. Final checklist before you go live

Item	Done

Test account and fake data only	[ ]
Every router has a fallback path	[ ]
Error routes on Break or Resume for every risky module	[ ]
Duplicate check tested	[ ]
Human review before any hiring-related action	[ ]
Operations and schedule checked against the live plan page	[ ]
Run history reviewed after the first ten runs	[ ]