SKILLNAVORA · AI PRODUCT MANAGEMENT & GENAI LAUNCHPAD · SKILL 7 OF 7

Agent Orchestration & Monitoring

Run longer AI workflows reliably: workflow patterns, routing and model selection, parallel work, state and checkpoints, human-in-the-loop approvals, error recovery, multi-agent systems, scheduling and triggers, cost control, and production monitoring.

Edition 2026 · skillnavora.in

How to use this guide

Each class has goals, concepts with Indian examples, key takeaways and a practice exercise, from basic to advanced. Finish with the final project to build something you can show in interviews.

	Class	Level
Class 1	**Workflows vs agents: start simple**	Basic
Class 2	**Core patterns: chaining, routing and parallelisation**	Basic
Class 3	**Designing a workflow: a worked example**	Basic
Class 4	**Orchestrator-workers and evaluator-optimizer**	Intermediate
Class 5	**Designing tools for agents**	Intermediate
Class 6	**State, checkpoints and long-running work**	Intermediate
Class 7	**Human-in-the-loop, approvals and error recovery**	Intermediate
Class 8	**Multi-agent systems**	Advanced
Class 9	**Triggers, scheduling and cost control**	Advanced
Class 10	**Testing workflows before and after launch**	Advanced
Class 11	**Monitoring, observability and the final project**	Advanced
	Toolkit: templates, patterns cheat sheet, glossary, 10 interview questions, further reading	

BASIC · CLASS 1

Workflows vs agents: start simple

Know when a fixed workflow is enough and when an agent is worth it.

	Workflow	Agent
Steps	Defined in advance by you	Chosen by the model as it goes
Predictability	High	Lower; needs guardrails
Cost / speed	Lower / faster	Higher / slower
Best for	Known, repeatable processes	Open-ended tasks with unknown steps

> Rule: start with one model and a few tools in a clear workflow. Add agent autonomy or multiple agents only when simpler options fail your evals.

Building blocks

An LLM call + retrieval + tools + memory, connected by an orchestrator (code, n8n, Make, Zapier or an agent framework).

Key takeaways

- Workflows are predictable; agents are flexible.
- Start simple; add autonomy only when needed.
- Measure with evals before adding complexity.

Practice exercise: For 3 processes in your work, decide workflow or agent and justify it.

BASIC · CLASS 2

Core patterns: chaining, routing and parallelisation

Use the three most common orchestration patterns.

Pattern	How it works	Example
Prompt chaining	Step 1 output → step 2 input, with checks between	Extract facts → draft PRD → review
Routing	Classify the request, send it to the right workflow or model	Support: refund → refund flow; bug → engineering; simple FAQ → cheap model
Parallelisation	Run independent parts at once, then combine; or run several attempts and vote	Analyse 5 competitors in parallel; 3 judges vote on a risky answer

Model selection inside routing

Use small, fast models for classification and simple answers; larger models for reasoning, writing and agents. Measure quality and cost per successful task, not per call.

Key takeaways

- Chain for sequences, route for variety, parallelise for speed.
- Routing also picks the right model for cost.
- Check outputs between steps.

Practice exercise: Design a router for a customer-support bot with 5 intents, the workflow and model size for each.

BASIC · CLASS 3

Designing a workflow: a worked example

Turn a messy task into clear steps with inputs, outputs and checks, before you touch any tool.

The best orchestration starts on paper. Take one real task and write each step down with what goes in, what comes out and how you know it worked.

Example: weekly customer-feedback report

#	Step	Input	Output	Who or what	Check
1	Collect	App reviews, support tickets, survey answers from the last 7 days	One table of feedback items	Automation (n8n, Zapier or Make)	Row count compared with last week
2	Clean	Feedback table	Items without duplicates, spam or personal data	Code + small model	No phone numbers or emails remain
3	Classify	Each item	Theme, sentiment, product area	Small model with fixed labels	Labels from the allowed list only
4	Summarise	Items per theme	Top 5 themes with counts and 2 quotes each	Strong model	Quotes exist in the source
5	Review	Draft report	Approved report	Product manager	Approve or edit
6	Publish	Approved report	Notion page and Slack post	Automation	Link posted

Questions to answer for every step

- Does this step need AI, or can a rule or code do it? (Code is cheaper and more predictable.)
- What happens if this step fails: retry, skip, or stop and alert?
- Which steps can run in parallel? (Here, step 3 runs on each item independently.)
- Where must a person look before the result leaves the team?

> If you cannot write the steps down, the task is not ready for automation, and an agent will not fix that.

Key takeaways

- Write every step with input, output, owner and check.
- Use code for rules, small models for simple labels, strong models for judgement.
- Decide failure handling and human review before building.

Practice exercise: Write the step table for one weekly task you do, with a check for every step, and mark which steps need AI.

INTERMEDIATE · CLASS 4

Orchestrator-workers and evaluator-optimizer

Use the two most powerful agentic patterns safely.

Orchestrator-workers

A lead model plans the work, sends sub-tasks to workers (other model calls or agents), then combines results. Good for research and analysis where sub-tasks aren't known in advance.

Evaluator-optimizer

One model drafts, another evaluates against a rubric and gives feedback, loop until the bar is met or a step limit is reached. Good for writing, code and PRDs with clear quality criteria.

```
loop max 3 times:
  draft = writer(brief, feedback)
  review = evaluator(draft, rubric)      # returns pass + issues
  if review.pass: break
  feedback = review.issues
return draft, review
```

Always set limits (steps, time, cost) so loops end.

Key takeaways

- Orchestrator plans; workers execute; orchestrator combines.
- Evaluator-optimizer loops on a rubric with a step cap.
- Limits on steps, time and cost are mandatory.

Practice exercise: Sketch an orchestrator-workers design for 'market research report on EV two-wheelers in India'.

INTERMEDIATE · CLASS 5

Designing tools for agents

Give agents tools they can choose and use correctly, with limits that keep them safe.

An agent decides what to do by reading the names and descriptions of its tools. Clear tools matter as much as a good prompt.

A good tool definition

```
name: search_orders
description: Find a customer's orders by phone number or order ID.
  Use before answering any question about an order's status, refund or
  delivery. Returns at most 5 orders, newest first.
parameters:
  order_id: string, optional, e.g. "OD-48213"
  phone_last4: string, optional, last 4 digits only
returns: [{order_id, status, placed_at, amount_inr, eta}]
errors: "NOT_FOUND: no order matches; ask the customer to check the ID"
```

Rules of thumb

Rule	Why
One clear job per tool, named with a verb	Agents confuse overlapping tools
Say when to use it in the description	That is how the agent decides
Return small, structured results	Raw dumps fill the context and hide the answer
Return helpful error messages	The agent can recover ("ask for the ID") instead of looping
Separate read tools from write tools	Writes can need approval; reads usually do not
Make writes idempotent	A retried "create refund" must not refund twice; pass a request ID
Limit scope and permissions	The tool, not the prompt, should enforce "max ₹2,000"

Through the Model Context Protocol (MCP), the same tool can be offered to Claude and other MCP-compatible assistants, so a well-designed tool is reusable across products.

Key takeaways

- Agents choose tools by their names and descriptions.
- One job per tool; small structured results; useful errors.
- Separate reads from writes; enforce limits in the tool; make writes idempotent.

Practice exercise: Write definitions for three tools an assistant for your product would need, including errors and which actions need approval.

INTERMEDIATE · CLASS 6

State, checkpoints and long-running work

Make workflows resumable and traceable.

- **State**: a record of what's done, what's pending, inputs, outputs and decisions (a table, JSON file or database row per run).
- **Checkpoints**: save after each major step so a failure resumes from there instead of starting over.
- **Idempotency**: re-running a step doesn't duplicate actions (e.g. doesn't create two Jira tickets).
- **Caching**: reuse valid results (search results, document summaries) to save time and money.

```
run_id | step | status (pending/running/done/failed) | input_ref | output_ref | started |
finished | cost
```

Key takeaways

- Track state per run.
- Checkpoint after major steps.
- Make actions idempotent; cache reusable results.

Practice exercise: Design a state table for a weekly competitor-report workflow with 5 steps.

INTERMEDIATE · CLASS 7

Human-in-the-loop, approvals and error recovery

Put people at the right points and recover from failures safely.

Where humans add value

- Before consequential actions: sending, publishing, paying, deleting.
- When confidence is low or rules conflict.
- Reviewing samples for quality.

Error recovery

Failure	Response
Timeout / rate limit	Retry with backoff; switch provider
Bad output (fails checks)	Retry with feedback; then escalate to human
Tool error	Log, retry once, fall back to manual path
Unexpected state	Stop, alert owner, keep checkpoint

Key takeaways

- Approvals before consequential actions.
- Retry with limits; fall back; escalate.
- Never fail silently: alert an owner.

Practice exercise: Write the approval points and error-recovery rules for an AI that drafts and sends customer emails.

ADVANCED · CLASS 8

Multi-agent systems

Know when splitting work across agents helps, and how to coordinate them.

Multiple specialised agents (researcher, analyst, writer, reviewer) can help when work is large, parallel and needs different tools or context. They also add cost, latency and coordination problems.

- Give each agent a clear role, tools and output format.
- Share state through a common store, not long chat histories.
- Use a lead agent or a fixed workflow to coordinate and to decide when work is done.
- Evaluate the final result and each agent's contribution.

> Many tasks work best with one capable agent and good tools; prove the multi-agent version is better on your evals before adopting it.

Key takeaways

- Multi-agent helps for large parallel work.
- Clear roles, shared state, a coordinator.
- Prove the benefit with evals.

Practice exercise: Design a 3-agent system for producing a weekly market newsletter and compare it with a single-agent design.

ADVANCED · CLASS 9

Triggers, scheduling and cost control

Run workflows automatically and within budget.

Triggers

- **Scheduled**: every morning, every Friday (cron, n8n schedule).
- **Event-driven**: new form submission, new support ticket, file uploaded, price change detected.
- **On demand**: a button, Slack command or chat request.

Cost management

- Budget per run and per month; alert at 80%.
- Route easy work to smaller models; cache; trim context.
- Cap steps, retries and tool calls.
- Track cost per successful task as a key metric.

Key takeaways

- Choose scheduled, event-driven or on-demand triggers.
- Set budgets and alerts.
- Measure cost per successful task.

Practice exercise: Define triggers and a monthly budget with alerts for 2 workflows you'd automate.

ADVANCED · CLASS 10

Testing workflows before and after launch

Catch broken steps, bad outputs and runaway costs before your users do.

A workflow can fail in a single step, in the hand-off between steps or only under real-world load. Test at each level.

Three levels of testing

Level	What you test	Example
Step tests	Each step alone, with fixed inputs	The classifier returns only allowed labels on 50 saved items
End-to-end evals	The whole workflow on realistic cases	20 weeks of past feedback produce reports a PM rates "usable"
Failure tests	What happens when things go wrong	An API times out, a file is empty, a model returns invalid JSON

Failure tests worth running

- A tool returns an error or nothing: does the workflow retry, skip or alert?
- The model returns malformed output: is it validated and retried with the error?
- A step is run twice: are emails, refunds or tickets duplicated?
- Input is ten times larger than usual: do cost and time limits stop it?
- Input contains an injection attempt: is any action taken without approval?

Replay real runs

Save the inputs and traces of real runs. After changing a prompt, model or step, replay them and compare outputs, cost and time with the previous version before you switch.

> Launch checklist: step tests pass, end-to-end score meets the target, every failure test has a known outcome, budgets and alerts are set, and one person owns the workflow.

Key takeaways

- Test each step, the whole flow and the failure paths.
- Validate model output and make side effects safe to repeat.
- Replay saved real runs before switching versions.

Practice exercise: Write five failure tests for a workflow you use or plan, with the expected outcome of each.

ADVANCED · CLASS 11

Monitoring, observability and the final project

Know when a workflow breaks or degrades, and fix it fast.

What to monitor

Signal	Example alert
Success rate	Runs succeeding fell below 95%
Quality	Sampled judge score dropped 5 points
Latency	p95 above 30 s
Cost	Daily spend above budget
Safety	Any unapproved action or injection flag
Drift	New topics or languages in inputs

Tools

Traces and dashboards in Langfuse, LangSmith, Arize Phoenix or Braintrust; n8n execution logs; simple Google Sheet logs and Slack alerts for no-code workflows.

Final project

Build one end-to-end workflow (e.g. "new customer feedback → classify → summarise weekly → Notion report → Slack"), with routing, a checkpointed state table, one approval step, retries, a budget, a monitoring sheet and a 10-case eval. Demo it in 5 minutes.

Key takeaways

- Monitor success, quality, latency, cost, safety, drift.
- Trace every run for debugging.
- Ship with alerts and an owner.

Practice exercise: Complete the final project.

TOOLKIT

Templates

A. Workflow design sheet

Field	Fill in
Goal and trigger	
Steps (pattern: chain / route / parallel / orchestrator)	
Models per step	
Tools	
State and checkpoints	
Approvals	
Error recovery	
Budget and limits	
Monitoring and owner	
Eval set	

B. Run log

```
run_id | trigger | steps done | status | cost | latency | quality score | approvals | errors
```

TOOLKIT

Patterns cheat sheet

Term / tool	Meaning / use
Prompt chaining	Sequential steps with checks
Routing	Classify then send to the right path or model
Parallelisation	Independent parts at once; or voting
Orchestrator-workers	Lead plans and delegates; combines results
Evaluator-optimizer	Draft → evaluate → improve loop with a cap
Checkpoint	Saved progress to resume after failure
Idempotency	Re-running doesn't duplicate actions
Human-in-the-loop	Approval or review by a person
Observability	Traces, logs and metrics to see what happened

Glossary

Orchestrator	Component that runs and connects steps
Trigger	Event or schedule that starts a workflow
Backoff	Waiting longer between retries
Trace	Record of every step in a run
Drift	Inputs or quality changing over time

INTERVIEW PREP

10 interview questions with answers

Q1. Workflow or agent?
Workflow when steps are known and repeatable; agent when steps can't be predicted. Start simple and prove the agent is better with evals.

Q2. Explain routing.
Classify each request and send it to the appropriate workflow or model, e.g. cheap model for FAQs, strong model for complex cases.

Q3. What is orchestrator-workers?
A lead model breaks a task into sub-tasks, delegates to workers and synthesises their results.

Q4. How do you make long workflows reliable?
State tracking, checkpoints, idempotent actions, retries with limits, approvals, alerts and monitoring.

Q5. When do you need multiple agents?
Large parallel work needing different tools or context, and only when evals show it beats a single agent.

Q6. How do you control AI workflow cost?
Budgets and alerts, routing to smaller models, caching, trimmed context, step and retry caps, and tracking cost per successful task.

Q7. What would you monitor in production?
Success rate, sampled quality scores, latency, cost, safety events and input drift, with owners and alerts.

Q8. Where do humans fit?
Before consequential actions, on low confidence or conflicts, and in sampled quality review.

Q9. How would you design a tool for an AI agent?
One clear job, a verb name, a description saying when to use it, typed parameters, small structured results, helpful errors, read/write separation, idempotent writes and limits enforced in the tool.

Q10. How do you test an AI workflow?
Step tests with fixed inputs, end-to-end evals on realistic cases, failure tests (timeouts, bad JSON, duplicates, oversized input, injection) and replays of saved real runs before switching versions.

LEARN MORE

Further reading and tools

- Anthropic: Building effective agents: https://www.anthropic.com/research/building-effective-agents
- Anthropic: Demystifying evals for AI agents: https://www.anthropic.com/research/demystifying-evals-for-ai-agents
- n8n docs: https://docs.n8n.io/
- LangGraph docs: https://langchain-ai.github.io/langgraph/
- Langfuse docs: https://langfuse.com/docs
- OpenAI Agents SDK: https://openai.github.io/openai-agents-python/

© SkillNavora · skillnavora.in · Part of the AI Product Management and GenAI Launchpad programs. Practise with the free AI Tutor, AI PM Toolkit and Practice Lab on skillnavora.in.