PART 1 · MODULE D

Power BI: model, measures, security and publishing

Dashboards clients can use, built on a clean data model.

D1. Data model and relationships

Power BI works best with a star schema: one fact table (orders) linked to dimension tables (customers, dates). Relationships should be one-to-many with a single active path.

D2. Measures in DAX

Measures calculate totals dynamically. Example (verify syntax in Microsoft's DAX reference before use):

DAX

```
Total Revenue = SUM ( Orders[amount] )
Orders Count = COUNTROWS ( Orders )
Average Order Value = DIVIDE ( [Total Revenue], [Orders Count] )
Revenue Search = CALCULATE ( [Total Revenue], Orders[channel] = "search" )
```

These DAX measures were not run in this session; they follow the standard DAX pattern and must be tested in Power BI Desktop before delivery.

D3. Row-level security and publishing

Restrict each user's rows with a role and a filter expression, then test with 'View as role' in Power BI Desktop before publishing.

VERIFICATION NOTE

Tool features, plans and prices change. Excel and Power BI features differ by version; check the official help pages. Links were not checked live in this draft.

Part of **Master Freelancing: Data Analytics and Data Science**. Back to the chapter list on skillnavora.in · Open the full textbook. Official links in this chapter were not checked live; confirm before relying on them.