Lesson 5.1: Multi-step scenarios, JSON parsing, array aggregators and webhooks

What you learn

- **Routing.** Use routers or paths so different conditions follow different steps, with a fallback path.
- **JSON parsing.** Convert incoming text into fields you can map; check the structure first.
- **Array aggregator.** Collects many items into one bundle or total, for example orders per city (shown in code below).
- **Webhook listeners.** A URL that starts the scenario when another app sends data. Verify the sender and handle repeats.

Tools and resources (official sites, not checked live)

- Make help
- Zapier help

ASSIGNMENT

Practice for lesson 5.1

Business problem: Total orders by city.

Steps

1. Run the tested aggregator.
2. Add a new city to the data.
3. Check the totals.

Expected output: Totals per city.

SOLUTION (ANSWER KEY)

PYTHON

```
import json
raw = '{"orders":[{"id":1,"city":"Pune","amount":500},{"id":2,"city":"Pune","amount":300},
{"id":3,"city":"Delhi","amount":700}]}'
def aggregate_by(key, rows, value):
    out = {}
    for r in rows:
        out[r[key]] = out.get(r[key], 0) + r[value]
    return out
```

Make's aggregators do the same job without code: they group items and sum a field.

Check yourself

1. Why verify webhook senders?
   Answer: To block fake requests.

2. What does an aggregator do?
   Answer: Combines many items into one result.

Lesson 5.1 of the **AI and Automation** lessons. See this lesson and its official links on skillnavora.in · All chapters and lessons · Open the full lesson guide. Tools, prices and plans change; confirm on each official site.