Skill Navora

TRACK 5

# Python for Data Science

Python from zero: data types, control flow, data structures, functions, OOP, files, NumPy, pandas, visualisation, dates, SQL connections, EDA and DSA for data roles.

29 lessons | Version 2026.10 | Updated October 2026

Created by **Varun Kumar**
www.skillnavora.in

# Contents

Every entry is a clickable link. The PDF also has bookmarks for each lesson and section.


01 Introduction to Python: Why, Install & Jupyter Notebooks

02 Variables, Data Types, Type Conversion, print(), f-strings & input()

03 Operators, Strings, Indexing, Slicing & String Methods

04 Control Flow: if, elif, else, Nested Conditions & match

05 Loops: while, for, range, break, continue & Patterns

06 Lists: Creating, Slicing, Methods, Sorting & Comprehensions

07 Tuples & Sets: Immutable Records, Unpacking and Set Algebra

08 Dictionaries: Key-Value Data, Counting and Grouping

09 Functions: Reusable Code, Arguments, Scope and Docstrings

10 Comprehensions, Lambda, map/filter and Generators

11 Object-Oriented Python: Classes, Objects, Inheritance and Dataclasses

12 Files, Exceptions, JSON and CSV

13 Modules, Packages, Virtual Environments and Git

14 Debugging, Testing, Regular Expressions and Code Quality

15 NumPy: Fast Arrays, Vectorisation and Broadcasting

16 pandas I: Series, DataFrames, Reading Data, Selecting and Filtering

17 pandas II: Data Cleaning: Missing Values, Types, Duplicates, Text and Outliers

18 pandas III: GroupBy, Pivot Tables, Merge/Join and Reshape (melt/unpivot)

19 pandas IV: Dates, Time Series, Resampling and Rolling Windows

20 Data Visualisation I: Matplotlib and Choosing the Right Chart

21 Data Visualisation II: Seaborn Statistical Charts and Interactive Plotly

22 Exploratory Data Analysis (EDA) Case Study: Telecom Customer Churn

23 Python and SQL: sqlite3, DuckDB, SQLAlchemy and pandas.read_sql

24 APIs, JSON and Web Scraping with requests and BeautifulSoup

25 Performance and Bigger Data: Vectorisation, Memory, Parquet, Polars and DuckDB

26 DSA I: Big-O, Arrays, Strings, Hashing, Two Pointers and Sliding Window

27 DSA II: Stacks, Queues, Linked Lists, Recursion, Sorting and Binary Search

28 DSA III: Trees, Heaps, Graphs (BFS/DFS) and Dynamic Programming

29 Python Capstone: End-to-End Retail Sales Analytics Project

PYTHON FOR DATA SCIENCE · LESSON 1

# Introduction to Python: Why, Install & Jupyter Notebooks

Learn what programming and Python are, how Python compares with other languages, how code runs (interpreters, compilers, bytecode), the properties of Python, and set up your environment (Anaconda, VS Code, Jupyter, Google Colab). Write and run your first cells, with markdown, magic commands and good notebook habits.

Python class 1 | ✦ Python 3.13, Jupyter, VS Code, Google Colab (2026) | Beginner | ⏱ 90 min

**By the end of this lesson you can**

- Explain what a programming language is and why Python is the default language for data work
- Describe the difference between compiled and interpreted languages and how Python runs your code
- Install Python and Jupyter (or use Google Colab) and run code in cells
- Use Markdown cells, keyboard shortcuts, magic commands and restart-and-run-all
- Follow good habits: naming, comments, reproducibility and virtual environments

## What is programming?

A **program** is a set of precise instructions a computer follows. Computers only understand machine code (0s and 1s), so we write instructions in a **programming language** that humans can read, and a translator turns them into something the machine can run.





Languages sit on levels. High-level languages like Python are close to human language; low-level ones are close to the machine.

## Compiled vs interpreted

| | Compiled (C, C++, Rust, Go) | Interpreted (Python, JavaScript, R) |
|---|---|---|
| How it runs | Whole program translated to machine code **before** running | Translated and executed **line by line** while running |
| Speed | Usually faster at run time | Slower per operation, much faster to develop |
| Errors | Many caught before running | Some appear only when that line runs |
| Output | A separate executable file | Source file runs under an interpreter |

Python is usually called **interpreted**. In reality CPython (the standard version) first compiles your code to **bytecode** (`.pyc` files) and then a virtual machine executes it. Python code that needs speed calls libraries written in C (NumPy, pandas), so data work is fast anyway.

# Why Python for data?




The Python data ecosystem. You will learn each of these libraries in this track.

| Property of Python | Meaning |
|---|---|
| **Readable** | Indentation and English-like keywords; fewer lines than most languages |
| **Interpreted, dynamically typed** | No compile step; variables take the type of the value they hold |
| **High level** | Memory is managed for you (garbage collection) |
| **Multi-paradigm** | Procedural, object-oriented and functional styles |
| **Huge ecosystem** | 500,000+ packages on PyPI; pandas, scikit-learn, PyTorch lead data and AI |
| **Open source and portable** | Free; runs on Windows, Mac, Linux, cloud notebooks |
| **Great glue** | Calls SQL, APIs, C/C++ code, Excel, Spark |

> **NOTE** **Python versions**
>
> Use Python **3.11, 3.12 or 3.13** (the current stable series in 2026). Python 2 ended in 2020 and must not be used. Check your version with `python --version`.

## Getting set up: three options


| Option | Best for | Steps |
|---|---|---|
| **Google Colab** (free, in the browser) | Starting today, no installation, GPU for ML | Go to colab.research.google.com → New notebook → sign in with Google |
| **Anaconda / Miniconda** | Full local data-science setup with packages and environments | Install Anaconda Distribution → open **Anaconda Navigator** or a terminal → `jupyter lab` |
| **Python + VS Code** | Professional workflow, notebooks and scripts in one editor | Install Python from python.org (tick "Add to PATH") → install **VS Code** → add the **Python** and **Jupyter** extensions |

STEP BY STEP **Local install with pip (any OS)**

1. Install Python 3.12+ from python.org (Windows: tick **Add python.exe to PATH**).
2. Open a terminal and create a **virtual environment** (an isolated set of packages for one project): `python -m venv .venv` then activate it: Windows `.venv\Scripts\activate`; Mac/Linux `source .venv/bin/activate`.
3. Install the course packages: `pip install jupyterlab numpy pandas matplotlib seaborn scikit-learn scipy statsmodels`
4. Start Jupyter: `jupyter lab` (opens in your browser).

## Jupyter notebooks

A **Jupyter notebook** ( `.ipynb` ) mixes **code cells**, **Markdown cells** (text, headings, images) and **outputs** (tables, charts) in one document. It is the standard tool for exploring data and sharing analysis. The name comes from Julia, Python and R.




Anatomy of a Jupyter notebook.

## The kernel

The **kernel** is the Python process behind the notebook. Variables you create stay in its memory until you restart it. Cells can be run in any order, which is flexible but dangerous: a notebook can look right while depending on a cell you deleted. **Before sharing, always Restart Kernel and Run All** to prove the notebook works top to bottom.

## Essential shortcuts (Jupyter / Colab)

| Action | Shortcut |
|---|---|
| Run cell, stay | `Ctrl + Enter` |
| Run cell, go to next | `Shift + Enter` |
| Insert cell above / below (command mode) | `A` / `B` |
| Delete cell (command mode) | `D, D` |
| Convert to Markdown / Code | `M` / `Y` |
| Command mode / edit mode | `Esc` / `Enter` |
| Comment / uncomment lines | `Ctrl + /` |
| Show function help | `Shift + Tab` (inside the brackets) |
| Autocomplete | `Tab` |
| Undo cell delete | `Z` (command mode) |

# Your first code

Python

```
print("Hello, data world!")
```

OUTPUT

```
Hello, data world!
```

Python is also a calculator:

Python

```
2 + 3 * 4
```

OUTPUT

```
14
```

Python

```
(2 + 3) * 4, 10 / 4, 10 // 4, 10 % 4, 2 ** 10
```

OUTPUT

```
(20, 2.5, 2, 2, 1024)
```

The **last expression** in a notebook cell is displayed automatically; to show several things use `print()`.

Python

```
name = "Varun"
learners = 25
print("Welcome to the course,", name)
print(f"This batch has {learners} learners")
```

OUTPUT

```
Welcome to the course, Varun
This batch has 25 learners
```

## Comments

Python

```python
# This is a comment: Python ignores everything after the hash
price = 120          # you can also put a comment at the end of a line
"""A triple-quoted string on its own line is often used
as a multi-line comment or docstring"""
```

Write comments to explain **why**, not what. `x = x + 1 # add one` is noise; `# compensate for the header row` is useful.

## Errors are normal

Every programmer sees errors daily. Learn to read them from the **bottom line up**:

Python

```python
print("Total:", total_amount)
```

OUTPUT

```
NameError: name 'total_amount' is not defined
```

`NameError: name 'total_amount' is not defined` says exactly what happened: we used a name we never created. Common beginner errors:

| Error | Usual cause |
|---|---|
| `NameError` | Typo, or the cell that defines the variable has not been run |
| `SyntaxError` | Missing bracket, quote or colon; wrong indentation |
| `TypeError` | Using a value of the wrong type ( `"5" + 3` ) |
| `ValueError` | Right type, wrong value ( `int("abc")` ) |
| `IndexError` , `KeyError` | Asking for a position or key that does not exist |
| `FileNotFoundError` | Wrong path or the file is not where you think |

> **TIP** **How to ask for help**
>
> Copy the **last line** of the error, search it, or paste the code and the error into an AI assistant (without secrets) and ask: *"What does this error mean and how do I fix it? Explain step by step."* Then fix it **yourself** and re-run: you learn by doing.

## Markdown cells

Change a cell to **Markdown** to write notes next to your code:

MARKDOWN

```
# Title
## Section
Some **bold** and *italic* text, a [link](https://example.com), and a list:
- item one
- item two

| Column | Value |
|---|---|
| A | 1 |
```

Good notebooks tell a story: a title, the question, the data, the steps with short explanations, and a conclusion.

## Magic commands and useful tools

Jupyter adds special commands beginning with `%`:

| Command | Purpose |
|---|---|
| `%timeit expr` | Time a short expression precisely |
| `%%time` | Time a whole cell |
| `%pwd`, `%ls` | Current folder, list files |
| `%matplotlib inline` | Show charts in the notebook (default now) |
| `%who` | List variables |
| `!pip install package` | Run a shell command (install a package) from a cell |

## Reproducibility habits

1. **Folder per project**: `data/`, `notebooks/`, `src/`, `README.md`.
2. **Virtual environment per project** and a `requirements.txt` (`pip freeze > requirements.txt`).
3. **Use relative paths** (`data/sales.csv`), not `C:\Users\you\Desktop\…`.
4. **Set random seeds** (`np.random.seed(42)`) so results repeat.
5. **Restart and Run All** before sharing; keep notebooks short and focused.
6. **Version control**: commit to Git; clear outputs of big notebooks.
7. **Do not commit** data with personal information or secrets (API keys); use environment variables.

DO IT WITH AI

### Do it with AI

Ask an assistant: *"I'm a beginner. Give me a 7-day practice plan for Python with 20 minutes a day, each day with three small exercises and answers I can check."* Use it to **practise**, not to skip the struggle: type the code, break it on purpose, and read the errors.

## Summary

KEY TAKEAWAYS

- A program is a set of instructions; Python is a **high-level, interpreted, readable** language with a huge data ecosystem (NumPy, pandas, scikit-learn, PyTorch).
- CPython compiles source to bytecode and runs it on a virtual machine; speed-critical libraries use C underneath.
- Start with **Google Colab** or install **Anaconda** or **Python + VS Code**; isolate projects with **virtual environments**.
- A Jupyter notebook mixes code, Markdown and output; the **kernel** holds state, so *Restart and Run All* before sharing.
- Read error messages from the bottom; learn the common error types.
- Use clear comments, relative paths, seeds and version control for reproducible work.

### Quick quiz

6 questions · tap an answer to check it

**1. Which best describes Python?**

A A low-level compiled language

B A high-level, interpreted, general-purpose language with a rich data ecosystem

C A database language

D A spreadsheet tool

**Answer: B.** Python is readable, dynamically typed and widely used for data.

**2. What does the kernel do in a notebook?**

A Formats Markdown

B Runs your code and keeps variables in memory

C Stores the file

D Draws charts only

**Answer: B.** The kernel is the Python process behind the notebook.

**3. Why run "Restart kernel and Run All" before sharing a notebook?**

A To make it smaller

B To confirm the notebook works from top to bottom without hidden state

C To delete output

D To change the Python version

**Answer: B.** Cells can be run out of order; this test removes that risk.

**4.** What does `NameError: name 'x' is not defined` mean?

A x is a bad name

B Python has no variable called x yet (typo or the defining cell was not run)

C x must be a number

D A syntax mistake

**Answer: B.** You used a name before creating it.

**5.** Which command installs a package from inside a notebook cell?

A `install pandas`

B `!pip install pandas`

C `%pip.exe pandas`

D `import install`

**Answer: B.** A leading `!` runs a shell command.

**6.** What is a virtual environment for?

A Faster internet

B Keeping the packages of one project separate from others

C Running Python 2

D Backing up data

**Answer: B.** Isolated environments avoid version conflicts.

EXERCISE

### Set up and run

(1) Open Colab or Jupyter and create a notebook called `day1.ipynb`. (2) Add a Markdown cell with a title and your goals. (3) In code cells, print your name, compute the area of a rectangle 12 × 7.5, and print the Python version (`import sys; print(sys.version)`). (4) Cause a `NameError` on purpose and fix it. (5) Restart and Run All.

**Show solution (worked answer)**

Python

```
print("Asha Rao")
length, width = 12, 7.5
print("Area:", length * width)          # 90.0
import sys; print(sys.version)
print(undefined_name)                    # NameError: name 'undefined_name' is not
defined
undefined_name = 5; print(undefined_name)
```

INTERVIEW CORNER

### Questions you may be asked

**Q: Why is Python popular for data science?** Readable syntax, a huge ecosystem (NumPy, pandas, scikit-learn, PyTorch), strong community, easy integration with SQL, APIs and cloud, and notebooks for exploration.

**Q: Is Python compiled or interpreted?** Both: CPython compiles source to bytecode, which the Python virtual machine interprets. It is called interpreted because there is no separate manual compile step.

**Q: What is a virtual environment?** An isolated Python installation with its own packages for one project (created with `venv` or conda), preventing dependency conflicts.

**Q: Notebook vs script?** Notebooks are interactive and great for exploration and communication; scripts (`.py`) are better for production code, testing and automation.

PYTHON FOR DATA SCIENCE · LESSON 2

# Variables, Data Types, Type Conversion, print(), f-strings & input()

Store and name values with variables, meet Python's core data types (int, float, str, bool, None, complex), convert between types, format output with print(), f-strings and .format(), and read user input with input() and sys.argv.

Python class 2 | Python 3.13 | Beginner | 110 min

**By the end of this lesson you can**

- Create variables and follow Python naming rules and conventions
- Identify and check types with type() and isinstance(); explain mutable vs immutable
- Convert between int, float, str and bool, and predict what int(), float(), bool() and str() do
- Format output with print() options, f-strings (including number formats) and str.format()
- Read and validate input with input(), and avoid float rounding surprises

## Variables


A **variable** is a name that refers to a value stored in memory. You create it by assigning with `=`: no declaration, no type needed.

Python

```
price = 1250          # an int
tax_rate = 0.18       # a float
product = "Laptop"    # a str
in_stock = True       # a bool
total = price * (1 + tax_rate)
print(product, "costs", total)
```

OUTPUT

```
Laptop costs 1475.0
```




A variable is a label attached to an object. Re-assigning moves the label; it does not change the old object.

## Naming rules and conventions

| Rule | Example |
|---|---|
| Letters, digits and `_` only; cannot start with a digit | `sales_2025` ✓, `2025_sales` × |
| Case-sensitive | `Total` and `total` are different |
| Cannot be a keyword ( `if` , `for` , `class` , `None` , `True` ...) | `class` ×, `class_name` ✓ |
| **Convention**: `snake_case` for variables and functions, `PascalCase` for classes, `UPPER_CASE` for constants | `monthly_income` , `CustomerOrder` , `GST_RATE` |
| Use meaningful names | `avg_order_value` not `aov2` or `x` |
| Avoid shadowing built-ins | Do not name variables `list` , `sum` , `max` , `str` , `id` , `input` |

Python

```
a = b = c = 0                # chained assignment
x, y, z = 1, 2.5, "three"    # multiple assignment (tuple unpacking)
x, y = y, x                  # swap without a temp variable
print(a, b, c, x, y, z)
```

OUTPUT

```
0 0 0 2.5 1 three
```

# Data types

Everything in Python is an **object** with a **type**. Check it with `type()` .

| Type | Name | Example | Notes |
| --- | --- | --- | --- |
| `int` | Integer | `42` , `-7` , `1_000_000` | Unlimited size |
| `float` | Decimal number | `3.14` , `2e-3` | 64-bit binary floating point |
| `str` | Text | `"Pune"` , `'Pune'` | Immutable sequence of characters |
| `bool` | Boolean | `True` , `False` | Subclass of int ( `True == 1` ) |
| `NoneType` | "nothing" | `None` | Used for missing/absent values |
| `complex` | Complex number | `3 + 4j` | Rare in data work |
| `list` , `tuple` , `dict` , `set` | Collections | Lessons 8–10 | |

Python

```
values = [42, 3.14, "Pune", True, None, 3 + 4j, [1, 2], (1, 2), {"a": 1}, {1, 2}]
for v in values:
    print(f"{str(v):10s} → {type(v).__name__}")
```

OUTPUT

```
42         → int
3.14       → float
Pune       → str
True       → bool
None       → NoneType
(3+4j)     → complex
[1, 2]     → list
(1, 2)     → tuple
{'a': 1}   → dict
{1, 2}     → set
```

Python

```
print(isinstance(42, int), isinstance(True, int), isinstance(3.0, (int, float)))   # True True True
print(type(10 / 2), type(10 // 2))      # / always returns float; // with ints returns int
```

OUTPUT

```
True True True
<class 'float'> <class 'int'>
```

## Mutable vs immutable

- **Immutable**: cannot be changed after creation: `int`, `float`, `str`, `bool`, `tuple`, `frozenset`. "Changing" creates a new object.
- **Mutable**: can be changed in place: `list`, `dict`, `set`.

Python

```python
s = "data"
try:
    s[0] = "D"                    # strings are immutable
except TypeError as e:
    print("Error:", e)
s2 = "D" + s[1:]                   # build a new string instead
print(s2, "| id changed:", id(s) != id(s2))
```

OUTPUT

```
Error: 'str' object does not support item assignment
Data | id changed: True
```

## Numbers: int and float

Python

```python
big = 12_345_678_901_234_567_890 * 10      # ints never overflow
print(big)
print(0.1 + 0.2)                           # floats are approximate!
print(0.1 + 0.2 == 0.3, abs((0.1 + 0.2) - 0.3) < 1e-9)
print(round(2.675, 2), round(0.5), round(1.5), round(2.5))   # banker's rounding: halves go to even
```

OUTPUT

```
123456789012345678900
0.30000000000000004
False True
2.67 0 2 2
```

**WATCH OUT** **Floating-point surprises**

Computers store decimals in binary, so `0.1 + 0.2` is `0.30000000000000004`. For **money** use `decimal.Decimal` (or integers of paise); for comparisons use `math.isclose(a, b)` or `abs(a - b) < tolerance`. Python's `round()` rounds halves to the nearest even number (`round(2.5) = 2`), unlike Excel's `ROUND`.

Python

```
from decimal import Decimal
print(Decimal("0.1") + Decimal("0.2"))                    # exact decimal arithmetic
import math; print(math.isclose(0.1 + 0.2, 0.3))
```

OUTPUT

```
0.3
True
```

## Booleans and None

Python

```
print(True + True, 5 > 3, 5 == 5.0, "a" < "b", not False)
print(bool(0), bool(0.0), bool(""), bool([]), bool(None))      # all False: "falsy" values
print(bool(1), bool(-3), bool("0"), bool([0]))                 # all True: anything else is "truthy"
print(None is None, type(None))
```

OUTPUT

```
2 True True True True
False False False False False
True True True True
True <class 'NoneType'>
```

**Falsy** values: `0`, `0.0`, `""`, `[]`, `{}`, `()`, `set()`, `None`, `False`. Everything else is truthy. `None` represents "no value" (like SQL NULL); test with `is None`, never `== None`.

# Type conversion

Convert with the type's name: `int()`, `float()`, `str()`, `bool()`, `list()`...

Python

```
print(int("42"), int(3.99), int(-3.99), int(True))          # int() truncates towards zero
print(float("3.5"), float(7), float("1e3"))
print(str(123), str(3.0), str([1, 2]))
print(int("1010", 2), int("ff", 16), bin(10), hex(255))     # other bases
print(round(3.7), round(3.14159, 2), int(round(3.7)))
```

OUTPUT

```
42 3 -3 1
3.5 7.0 1000.0
123 3.0 [1, 2]
10 255 0b1010 0xff
4 3.14 4
```

Python

```
print("5" + 3)                    # TypeError: can only concatenate str to str
```

OUTPUT

```
TypeError: can only concatenate str (not "int") to str
```

Python

```
print("5" + str(3), int("5") + 3, "5" * 3)      # explicit conversion; repetition for strings
```

OUTPUT

```
53 8 555
```

Python

```
int("abc")                        # ValueError: invalid literal for int()
```

OUTPUT

```
ValueError: invalid literal for int() with base 10: 'abc'
```

| Conversion | Result | Note |
|---|---|---|
| `int("42")` | 42 | String must look like an integer |
| `int("3.7")` | ValueError | Convert to float first: `int(float("3.7"))` |
| `int(3.99)` | 3 | Truncates (not rounds) |
| `float("abc")` | ValueError | |
| `str(None)` | `'None'` | |
| `bool("False")` | True | Any non-empty string is True! |
| `list("abc")` | `['a','b','c']` | |

**Implicit conversion** happens in mixed arithmetic: `int + float → float`, `bool + int → int`.

Python

```
print(1 + 2.0, True + 1, type(1 + 2.0).__name__)
```

OUTPUT

```
3.0 2 float
```

## print(): showing output

Python

```
print("Order", 1001, "shipped")                    # items separated by a space
print("Order", 1001, "shipped", sep=" | ")          # change the separator
print("Loading", end="...")                         # change the line ending (no newline)
print("done")
print("Line one\nLine two\tTabbed")                 # escape sequences: \n newline, \t tab
print('He said "hi"', "It's fine", 'It\'s fine')    # quotes inside strings
print(r"C:\new\table")                              # raw string: backslashes kept
print("""A multi-line
string with triple quotes""")
```

OUTPUT

```
Order 1001 shipped
Order | 1001 | shipped
Loading...done
Line one
Line two        Tabbed
He said "hi" It's fine It's fine
```

```
C:\new\table
A multi-line
string with triple quotes
```

## f-strings: the modern way to format

Put `f` before the quotes and `{expression:format}` inside:

Python

```python
name, qty, price, share = "Asha", 3, 1234.5678, 0.2345
print(f"{name} bought {qty} items")
print(f"Price: {price:.2f}")                # 2 decimals
print(f"Price: {price:,.2f}")               # thousands separator
print(f"Share: {share:.1%}")                # percentage
print(f"ID: {qty:03d}")                      # zero-padded to 3 digits
print(f"[{name:<10}] [{name:>10}] [{name:^10}]")       # left, right, centre in width 10
print(f"{price:>12,.1f}|")                   # right-aligned width 12
print(f"{qty * price:,.2f}  {qty = }")       # expressions work; {x = } prints name and value
print(f"{1234567:,}  {255:#x}  {255:b}  {0.000123:.2e}")
```

OUTPUT

```
Asha bought 3 items
Price: 1234.57
Price: 1,234.57
Share: 23.4%
ID: 003
[Asha      ] [      Asha] [   Asha   ]
     1,234.6|
3,703.70  qty = 3
1,234,567  0xff  11111111  1.23e-04
```

| Format spec | Meaning |
|---|---|
| `.2f` | 2 decimal places (fixed) |
| `,` | Thousands separator |
| `.1%` | Percentage with 1 decimal |
| `05d` | Integer padded with zeros to width 5 |
| `<10` , `>10` , `^10` | Left / right / centre in width 10 |
| `e` | Scientific notation |
| `x` , `b` , `o` | Hex, binary, octal |

### .format() and % (older styles)

Python

```
print("{} bought {} items at {:.1f}".format("Asha", 3, 12.345))
print("{1} before {0}".format("B", "A"))
print("{name} paid {amt:,.0f}".format(name="Ravi", amt=1234567))
print("%s bought %d items at %.1f" % ("Asha", 3, 12.345))        # legacy, still seen in
old code
```

OUTPUT

```
Asha bought 3 items at 12.3
A before B
Ravi paid 1,234,567
Asha bought 3 items at 12.3
```

Prefer **f-strings** in new code; you will meet `.format()` and `%` in older code and logs.

## Reading input

`input()` reads **text** from the keyboard and always returns a `str`:

Python

```
name = input("Your name: ")                    # waits for the user
age = int(input("Your age: "))                 # convert to a number
height = float(input("Height in metres: "))
print(f"Hello {name}, you are {age} and {height:.2f} m tall.")
```

Because this handbook runs without a keyboard, here is the same logic with the typed values supplied in code:

```python
typed = ["Asha", "29", "1.62"]           # imagine the user typed these three answers
name = typed[0]; age = int(typed[1]); height = float(typed[2])
print(f"Hello {name}, you are {age} and {height:.2f} m tall.  In ten years: {age + 10}.")
```

OUTPUT

```
Hello Asha, you are 29 and 1.62 m tall.  In ten years: 39.
```

## Validate input

```python
while True:
    text = input("Enter quantity (1-100): ")
    if text.isdigit() and 1 ⩽ int(text) ⩽ 100:
        quantity = int(text); break
    print("Please type a whole number between 1 and 100.")
```

Other ways to get values into a program: **command-line arguments** (`sys.argv`, `argparse`), **files** (Lesson 13), **databases and APIs** (later lessons), and **environment variables** (`os.environ["API_KEY"]`) for secrets.

# Useful built-in functions

```python
nums = [4, 8, 15, 16, 23, 42]
print(len(nums), sum(nums), min(nums), max(nums), sorted(nums, reverse=True))
print(abs(-7), pow(2, 5), divmod(17, 5), round(sum(nums) / len(nums), 2))
print(type(nums).__name__, id(nums) > 0, dir(3)[:3])          # introspection helpers
help(len) if False else None                                   # help(len) prints documentation
```

OUTPUT

```
6 108 4 42 [42, 23, 16, 15, 8, 4]
7 32 (3, 2) 18.0
list True ['__abs__', '__add__', '__and__']
```

# Mini project: a bill calculator

Python

```
items = {"Notebook": (45.0, 10), "Pen pack": (60.0, 25), "Stapler": (180.0, 4)}     # name: (price, quantity)
GST = 0.18
subtotal = 0
print(f"{'Item':<12}{'Price':>8}{'Qty':>5}{'Amount':>10}")
for name, (price, qty) in items.items():
    amount = price * qty; subtotal += amount
    print(f"{name:<12}{price:>8.2f}{qty:>5}{amount:>10,.2f}")
print("-" * 35)
print(f"{'Subtotal':<25}{subtotal:>10,.2f}")
print(f"{'GST (18%)':<25}{subtotal * GST:>10,.2f}")
print(f"{'Total':<25}{subtotal * (1 + GST):>10,.2f}")
```

OUTPUT

```
Item           Price  Qty    Amount
Notebook       45.00   10    450.00
Pen pack       60.00   25  1,500.00
Stapler       180.00    4    720.00
-----------------------------------
Subtotal                   2,670.00
GST (18%)                    480.60
Total                      3,150.60
```

(The `for` loop and dictionary are explained in Lessons 6 and 9; notice how f-string alignment makes a tidy table.)

# Summary

**KEY TAKEAWAYS**

- A **variable** is a name pointing to an object; names are `snake_case`, case-sensitive, and must not be keywords or shadow built-ins.
- Core types: `int`, `float`, `str`, `bool`, `NoneType`; `list/tuple/dict/set` come later. Check with `type()` and `isinstance()`.
- Strings, numbers and tuples are **immutable**; lists, dicts and sets are **mutable**.
- Floats are approximate (`0.1 + 0.2`): use `Decimal` for money and `math.isclose` for comparisons. `round()` uses banker's rounding.
- Convert with `int()`, `float()`, `str()`, `bool()`; `int("3.7")` fails, `int(3.99)` truncates, `bool("False")` is True.
- Format with **f-strings** (`{x:,.2f}`, `{p:.1%}`, `{n:05d}`, `{s:<10}`); `print` has `sep` and `end`.
- `input()` returns a string: convert and validate it.

## Quick quiz

6 questions · tap an answer to check it

**1.** What does `type(10 / 2)` return?

A `int`

B `float`

C `str`

D `bool`

**Answer: B.** `/` always returns a float in Python 3 (5.0).

**2.** What is `int(-3.9)` ?

**A** −4

**B** −3

**C** 3

**D** −3.9

**Answer: B.** int() truncates towards zero.

**3.** Which is NOT falsy?

**A** `0`

**B** `""`

**C** `"0"`

**D** `None`

**Answer: C.** A non-empty string, including "0", is truthy.

**4.** What does `print(f"{0.2345:.1%}")` print?

**A** 0.2

**B** 23.4%

**C** 2.3%

**D** 0.23

**Answer: B.** `.1%` multiplies by 100 and shows one decimal. 0.2345 displays as 23.4% because 0.2345 is stored as a binary value just below 0.2345.

**5.** `x = input("Age: ")` and the user types 25. What is `type(x)`?

A `int`

B `str`

C `float`

D `bool`

**Answer: B.** input() always returns text.

**6. Why is** `0.1 + 0.2 == 0.3` **False?**

A Python is buggy

B Decimal fractions cannot be represented exactly in binary floating point

C Because of integer division

D Because of rounding to even

**Answer: B.** Use math.isclose or Decimal.

EXERCISE

## Practice

(1) Ask for a price and quantity (simulate the input), compute the total with 18% GST and print it as `₹1,23,456.78`-style with thousands separators and 2 decimals. (2) Convert "1010" from binary to int and 255 to hex. (3) Explain the output of `print(round(2.5), round(3.5))`.

### Show solution (worked answer)

Python

```
price, qty = float("1250.5"), int("3")
total = price * qty * 1.18
print(f"Total: ₹{total:,.2f}")          # ₹4,426.77
print(int("1010", 2), hex(255))          # 10 0xff
print(round(2.5), round(3.5))            # 2 4 : halves round to the nearest even
number
```

INTERVIEW CORNER

## Questions you may be asked

**Q: What is the difference between mutable and immutable types? Give examples.** Immutable objects cannot change after creation (int, float, str, tuple); mutable ones can (list, dict, set). It matters for function arguments, dictionary keys (must be immutable/hashable) and copying.

**Q: What is the output of `bool("False")` and why?** True: any non-empty string is truthy, regardless of its content.

**Q: How do you compare floats safely?** `math.isclose(a, b)` or `abs(a - b) < tol`; use `Decimal` for exact decimal arithmetic such as money.

**Q: `is` vs `==`?** `==` compares values; `is` compares identity (same object). Use `is None` for None.

PYTHON FOR DATA SCIENCE · LESSON 3

# Operators, Strings, Indexing, Slicing & String Methods

Master Python's operators (arithmetic, comparison, logical, assignment, membership, identity, bitwise) and work with text: string indexing and slicing, immutability, every string method an analyst needs (split, join, strip, replace, find, startswith, case methods, isdigit...), escape sequences, and cleaning real messy text.

Python classes 3–4 | Python 3.13 | Beginner | 120 min

**By the end of this lesson you can**

- Use arithmetic, comparison, logical, membership and identity operators and explain operator precedence
- Index and slice strings forwards and backwards, including steps, and explain immutability
- Apply string methods to clean, split, search, join and format text
- Build small text-cleaning functions and check results on real data
- Recognise common string pitfalls (encoding, whitespace, case, escape characters)

## Operators

### Arithmetic

| Operator | Meaning | Example | Result |
|---|---|---|---|
| `+` `-` `*` | Add, subtract, multiply | `7 * 3` | 21 |
| `/` | True division (always float) | `7 / 2` | 3.5 |
| `//` | Floor division | `7 // 2`, `-7 // 2` | 3, **−4** |
| `%` | Remainder (modulo) | `7 % 2`, `-7 % 3` | 1, 2 |
| `**` | Power | `2 ** 10` | 1024 |

Python

```
print(7 / 2, 7 // 2, -7 // 2, 7 % 2, -7 % 3, 2 ** 10, 9 ** 0.5)
print(divmod(17, 5))                  # (quotient, remainder) in one call
hours = 135; print(f"{hours // 60} h {hours % 60} min")       # split minutes into hours and minutes
print(10 % 3 == 1, 12 % 2 == 0)      # test odd/even and divisibility
```

OUTPUT

```
3.5 3 -4 1 2 1024 3.0
(3, 2)
2 h 15 min
True True
```

## Comparison and logical

Python

```
x = 15
print(x > 10, x == 15, x != 15, 10 < x <= 20)        # chained comparison: 10 < x and x <= 20
print(x > 10 and x < 20, x < 5 or x > 12, not x > 10)
print("apple" < "banana", "Zebra" < "apple")         # strings compare by character codes: uppercase before lowercase
```

OUTPUT

```
True True False True
True True False
True True
```

**Short-circuit evaluation**: `A and B` stops at A if A is falsy; `A or B` stops at A if A is truthy. They return the **deciding operand**, not just True/False:

Python

```
print(0 or "default", "" or "n/a", "x" and "y", None and 1)
name = ""; print(name or "Anonymous")          # a common idiom for default values
print(5 > 3 and print("evaluated") is None)     # right side runs only when needed
```

OUTPUT

```
default n/a y None
Anonymous
```

```
evaluated
True
```

## Assignment, membership, identity

Python

```python
count = 10; count += 5; count *= 2; count -= 1; count //= 4; count **= 2
print(count)
print(3 in [1, 2, 3], "py" in "python", "z" not in "python", "a" in {"a": 1})     #
membership
a = [1, 2]; b = [1, 2]; c = a
print(a == b, a is b, a is c, None is None)                                        #
equality vs identity
```

OUTPUT

```
49
True True True True
True False True True
```

## Bitwise (awareness)

`&` AND, `|` OR, `^` XOR, `~` NOT, `<<` `>>` shifts: used for flags and low-level work; in pandas/NumPy `&` and `|` combine boolean arrays (use brackets).

Python

```python
print(5 & 3, 5 | 3, 5 ^ 3, 5 << 1, 5 >> 1, bin(5))
```

OUTPUT

```
1 7 6 10 2 0b101
```

## Precedence

From highest to lowest: `**` → unary `-x` → `* / // %` → `+ -` → comparisons ( `< == in is` ) → `not` → `and` → `or`. When in doubt, use brackets.

Python

```python
print(2 + 3 * 4 ** 2, (2 + 3) * 4 ** 2, -2 ** 2, (-2) ** 2, not 1 == 2 or False)
```

OUTPUT

```
50 80 -4 4 True
```

## Walrus operator (3.8+)

`:=` assigns inside an expression: `if (n := len(items)) > 10: print(f"{n} items")`. Useful in loops and comprehensions; do not overuse.

# Strings

A **string** is an immutable sequence of Unicode characters. Create with single, double or triple quotes.

Python


```python
city = "Bengaluru"
quote = 'She said "hello"'
multi = """Line 1
Line 2"""
hindi = "नमस्ते"                    # Unicode works everywhere
print(len(city), len(hindi), multi.splitlines(), city.upper())
print("Ha" * 3, "data" + " " + "science", "-" * 20)
```

OUTPUT

```
9 6 ['Line 1', 'Line 2'] BENGALURU
HaHaHa data science --------------------
```

## Indexing

Characters are numbered from 0 on the left and from −1 on the right.




Indexing a string: positive indexes count from the left (starting at 0), negative from the right (starting at -1).

Python

```
w = "BENGALURU"
print(w[0], w[3], w[-1], w[-3])
try: print(w[20])
except IndexError as e: print("IndexError:", e)
```

OUTPUT

```
B G U U
IndexError: string index out of range
```

## Slicing: `s[start:stop:step]`

`start` is included, `stop` is **excluded**; omit a part to mean "from the beginning / to the end"; a negative step goes backwards.

Python

```
w = "BENGALURU"
print(w[0:3], w[:3], w[3:], w[3:6], w[-4:], w[:-1])
print(w[::2], w[::-1], w[1::3], w[8:2:-2])
print(w[2:100], repr(w[5:2]))            # out-of-range slices are safe; an empty slice is
''
```

OUTPUT

```
BEN BEN GALURU GAL LURU BENGALUR
BNAUU URULAGNEB EAR UUA
NGALURU ''
```

| Slice | Meaning |
|---|---|
| `s[:n]` | First n characters |
| `s[-n:]` | Last n characters |
| `s[a:b]` | From a up to (not including) b; length b − a |
| `s[::-1]` | Reversed |
| `s[::2]` | Every second character |

Python

```
order_id = "IN-2025-00042"
country, year, number = order_id[:2], int(order_id[3:7]), int(order_id[-5:])
print(country, year, number)                    # same as LEFT/MID/RIGHT in Excel and SQL
```

OUTPUT

```
IN 2025 42
```

## String methods

Strings are immutable, so every method **returns a new string**; the original stays unchanged.

### Case and cleaning

Python

```
s = "  new DELHI  "
print(repr(s.strip()), repr(s.lstrip()), repr(s.rstrip()))
print(s.strip().lower(), s.strip().upper(), s.strip().title(), s.strip().capitalize(),
s.strip().swapcase())
print("xxHixx".strip("x"), "2025-04-27".replace("-", "/"), "a,b,,c".replace(",,", ","))
print("Bengaluru".casefold() == "BENGALURU".casefold())        # robust case-insensitive
comparison
```

OUTPUT

```
'new DELHI' 'new DELHI  ' '  new DELHI'
new delhi NEW DELHI New Delhi New delhi NEW delhi
Hi 2025/04/27 a,b,c
True
```

### Searching and testing

Python

```
t = "Delhi, Mumbai, Delhi, Pune"
print(t.find("Delhi"), t.rfind("Delhi"), t.find("Goa"), t.count("Delhi"),
t.index("Mumbai"))
print(t.startswith("Delhi"), t.endswith("Pune"), "Mumbai" in t)
print("12345".isdigit(), "12.5".isdigit(), "abc".isalpha(), "abc123".isalnum(), "
".isspace(), "Abc".istitle(), "abc".islower())
```

OUTPUT

```
0 15 -1 2 7
True True True
True False True True True True True
```

`find` returns −1 when not found; `index` raises `ValueError`. `isdigit` is False for decimals and negatives, so use `try: float(s)` to test numbers.

## Splitting and joining

Python

```python
csv_line = "E101,Kavya Iyer,HR,97000"
parts = csv_line.split(",")
print(parts, len(parts))
print("one  two   three".split(), "a-b-c".split("-", 1), "line1\nline2".splitlines(),
"path/to/file.csv".rsplit("/", 1))
print(", ".join(["Pune", "Delhi", "Goa"]), "".join(["a", "b"]), " | ".join(str(n) for n in
[1, 2, 3]))
print("abc".partition("b"), "IN-2025-00042".partition("-"))
```

OUTPUT

```
['E101', 'Kavya Iyer', 'HR', '97000'] 4
['one', 'two', 'three'] ['a', 'b-c'] ['line1', 'line2'] ['path/to', 'file.csv']
Pune, Delhi, Goa ab 1 | 2 | 3
('a', 'b', 'c') ('IN', '-', '2025-00042')
```

`split()` with no argument splits on any whitespace and ignores repeats: the best way to tokenise text. `join` is called on the **separator**, with a list of strings.

## Alignment, padding and formatting

Python

```python
print("42".zfill(6), "7".rjust(4, "0"), "ab".ljust(5, ".") + "|", "ab".center(8, "*"))
print("Total".ljust(10) + "1,500".rjust(10))
print("{:>8} {:<8} {:^8}".format("right", "left", "mid"))
print("tab\tseparated", "new\\nline stays literal", "unicode: \u20b9 \u2713")
```

OUTPUT

```
000042 0007 ab...| ***ab***
Total          1,500
   right left       mid
tab     separated new\nline stays literal unicode: ₹ ✓
```

## Translating and encoding

Python

```
table = str.maketrans({"₹": "Rs ", ",": ""})
print("₹1,25,000".translate(table))
print("naïve café".encode("utf-8"), "abc".encode("ascii"), b"abc".decode())
print(ord("A"), chr(97), "é".encode("utf-8"), len("é".encode("utf-8")))
```

OUTPUT

```
Rs 125000
b'na\xc3\xafve caf\xc3\xa9' b'abc' abc
65 a b'\xc3\xa9' 2
```

**NOTE** **Encoding**

Text on disk is **bytes**. Most files today are **UTF-8**; if you see `Ã©` or `�`, the file was read with the wrong encoding. In pandas use `pd.read_csv(path, encoding="utf-8")` or `"latin-1"` / `"cp1252"` for old Windows exports.

## Method cheat sheet

| Goal | Methods |
|---|---|
| Change case | `lower()`, `upper()`, `title()`, `capitalize()`, `casefold()` |
| Trim | `strip()`, `lstrip()`, `rstrip()`, `removeprefix()`, `removesuffix()` |
| Replace | `replace(old, new, count)`, `translate()` |
| Search | `find()`, `rfind()`, `index()`, `count()`, `in`, `startswith()`, `endswith()` |
| Test | `isdigit()`, `isalpha()`, `isalnum()`, `isspace()`, `isupper()`, `islower()` |
| Split / join | `split()`, `rsplit()`, `splitlines()`, `partition()`, `join()` |
| Pad / align | `zfill()`, `ljust()`, `rjust()`, `center()` |
| Format | f-strings, `format()`, `format_map()` |

# Cleaning real text

Customer names from the course's `customers.csv`, cleaned with the same rules you used in Excel (`TRIM`, `PROPER`) and SQL:

Python

```
import pandas as pd
cust = pd.read_csv("customers.csv")
raw = ["  asha RAO ", "ravi   verma", "MEERA\tIYER", "kabir  singh "]          # messy examples
def clean_name(name):
    parts = name.split()                          # split() collapses all whitespace
    return " ".join(p.capitalize() for p in parts)
print([clean_name(n) for n in raw])
print(cust.customer_name.head(5).tolist())
first_names = [n.split()[0] for n in cust.customer_name]
print(len(first_names), "names; most common first names:",
pd.Series(first_names).value_counts().head(5).to_dict())
```

OUTPUT

```
['Asha Rao', 'Ravi Verma', 'Meera Iyer', 'Kabir Singh']
['Saanvi Khan', 'Meera Bose', 'Riya Shah', 'Diya Fernandes', 'Neha Sharma']
800 names; most common first names: {'Arjun': 36, 'Vikram': 31, 'Aarav': 31, 'Sneha': 30, 'Priya': 30}
```

Python

```
def initials(name): return "".join(w[0].upper() for w in name.split())
def mask_email(email):
    user, _, domain = email.partition("@")
    return user[0] + "*" * (len(user) - 2) + user[-1] + "@" + domain
print(initials("kavya iyer"), mask_email("kavya.iyer@abc.in"))
print("palindrome" if (s := "Level").lower() == s.lower()[::-1] else "not")
```

OUTPUT

```
KI k*********r@abc.in
palindrome
```

## Counting characters and words

Python

```
text = "data science is fun and data engineering is fun too"
words = text.split()
freq = {}
for w in words: freq[w] = freq.get(w, 0) + 1
print(freq)
print(max(freq, key=freq.get), len(words), len(set(words)))
```

OUTPUT

```
{'data': 2, 'science': 1, 'is': 2, 'fun': 2, 'and': 1, 'engineering': 1, 'too': 1}
data 10 7
```

(`collections.Counter(words)` does this in one line: Lesson 8.)

## Common pitfalls

| Pitfall | Example | Fix |
|---|---|---|
| Forgetting strings are immutable | `s.upper()` without assigning | `s = s.upper()` |
| Whitespace/case mismatches | `"Delhi " ≠ "Delhi"` | `strip()`, `lower()` before comparing |
| Using `+` with numbers | `"Total: " + 5` | f-string or `str(5)` |
| `isdigit` for decimals | `"3.5".isdigit()` → False | `try: float(x)` |
| Off-by-one in slices | `s[0:3]` has 3 characters | stop is excluded |
| Backslashes in Windows paths | `"C:\new"` → newline! | raw string `r"C:\new"` or forward slashes |
| Huge strings in loops | `s += x` in a loop | build a list and `"".join(list)` |
| Wrong encoding | `Ã©` characters | `encoding="utf-8"` |

DO IT WITH AI

### Do it with AI

Ask an assistant to produce 10 messy phone numbers (fake) and then write a function to standardise them to `+91-XXXXX-XXXXX`. Test it yourself on edge cases (spaces, dashes, leading 0, +91 already present) and compare approaches: string methods first, then regular expressions (Lesson 14).

# Summary

**KEY TAKEAWAYS**

- Operators: `/` true division, `//` floor division, `%` remainder, `**` power; comparisons chain ( `10 < x ⩽ 20` ); `and` / `or` short-circuit and return an operand; use `in` , `not in` , `is` .
- Strings are **immutable** sequences: index from 0 or −1, slice `[start:stop:step]` (stop excluded).
- Methods return new strings: `strip` , `lower/upper/title` , `replace` , `split` / `join` , `find` / `count` , `startswith` , `zfill` , `partition` .
- Clean text by trimming, normalising case/whitespace and replacing variants before comparing or counting.
- Watch pitfalls: forgetting to assign, off-by-one slices, wrong encodings, Windows backslashes.

## Quick quiz

6 questions · tap an answer to check it

**1. What does `"BENGALURU"[2:5]` return?**

**A** NGA

**B** ENG

**C** NGAL

**D** GAL

**Answer: A.** Index 2 is N, 3 is G and 4 is A; the stop index 5 is excluded.

**2.** What is `-7 // 2` in Python?

**A** −3

**B** −4

**C** 3

**D** −3.5

**Answer: B.** Floor division rounds down towards minus infinity.

**3.** What does `0 or "default"` return?

**A** 0

**B** True

**C** "default"

**D** None

**Answer: C.** `or` returns the first truthy operand (or the last operand).

**4.** Which statement is true about strings?

**A** `s[0] = "X"` changes the first character

**B** Strings are immutable, so methods like `upper()` return a new string

**C** `split()` changes the original string

**D** `strip()` removes only spaces inside the text

**Answer: B.** Assign the result to keep it.

**5.** How do you split text on any whitespace and ignore repeated spaces?

A `text.split(" ")`

B `text.split()`

C `text.partition()`

D `text.strip()`

**Answer: B.** `split()` without an argument splits on runs of whitespace.

**6.** `"3.5".isdigit()` **returns:**

A True

B False

C 3.5

D An error

**Answer: B.** isdigit() is True only for strings of digits; use float() inside try/except for decimals.

EXERCISE

### String practice

(1) From `"IN-2025-00042"` extract the country, year (int) and sequence number (int) with slicing. (2) Write `is_valid_pin(text)` that returns True for six-digit PIN codes not starting with 0. (3) Reverse the words in `"data science is fun"` (word order, not letters). (4) Turn `"  rAHul  VERMA  "` into `"Rahul Verma"`.

**Show solution (worked answer)**

Python

```
oid = "IN-2025-00042"; print(oid[:2], int(oid[3:7]), int(oid[-5:]))
def is_valid_pin(t): return len(t) == 6 and t.isdigit() and t[0] != "0"
print(is_valid_pin("411001"), is_valid_pin("041100"), is_valid_pin("4110a1"))
print(" ".join("data science is fun".split()[::-1]))           # fun is science data
print(" ".join(w.capitalize() for w in "  rAHul   VERMA ".split()))
```

INTERVIEW CORNER

### Questions you may be asked

**Q: How do you reverse a string in Python?** `s[::-1]` (slice with step −1) or `"".join(reversed(s))`.

**Q: Why use `"".join(list)` instead of `+=` in a loop?** Strings are immutable; each `+=` creates a new string (quadratic time). Building a list and joining once is linear.

**Q: Difference between `find` and `index`?** `find` returns −1 if the substring is missing; `index` raises `ValueError`.

**Q: What does `//` do with negative numbers?** Floors toward minus infinity: `-7 // 2 = -4`, and `-7 % 3 = 2`, so `(a // b) * b + a % b == a` always holds.

PYTHON FOR DATA SCIENCE · LESSON 4

# Control Flow: if, elif, else, Nested Conditions & match

Make programs decide. Learn indentation, if/elif/else, comparison and logical conditions, truthiness, conditional expressions (ternary), nested decisions, the match statement, and how Python's if maps to Excel's IF/IFS and SQL's CASE WHEN, with data-flavoured examples.


Python class 3 | Python 3.13 | Beginner | 90 min

**By the end of this lesson you can**

- Write correct if / elif / else blocks and explain why indentation matters
- Combine conditions with and, or, not, in, chained comparisons and truthiness
- Use conditional expressions and the match statement
- Order conditions correctly and avoid common branching bugs
- Translate a spreadsheet or SQL rule into Python

## Decisions and indentation

A program normally runs line by line. **Control flow** lets it choose between paths. In Python, a **colon** `:` starts a block and **indentation** (4 spaces by convention) says which lines belong to it.




An if statement tests a condition. If it is True the indented block runs; otherwise Python moves on (or runs else).

Python

```
marks = 82
if marks ⩾ 40:
    print("Pass")
    print("Well done!")
print("This line always runs")
```

OUTPUT

```
Pass
Well done!
This line always runs
```

Python

```
if True:
print("not indented")        # IndentationError: expected an indented block after 'if'
statement
```

COMMON MISTAKES **Indentation rules**

Use **4 spaces** (never mix tabs and spaces). Everything in the same block has the **same indentation**. A missing colon or wrong indentation causes `SyntaxError` / `IndentationError`.

## if / elif / else

Python

```
marks = 82
if marks ⩾ 90:
    grade = "A+"
elif marks ⩾ 75:
    grade = "A"
elif marks ⩾ 60:
    grade = "B"
elif marks ⩾ 40:
    grade = "C"
else:
    grade = "Fail"
print(marks, "→", grade)
```

OUTPUT

```
82 → A
```

Python checks the conditions **top to bottom** and runs the **first** one that is true, then skips the rest. This is Excel's nested `IF` / `IFS` and SQL's `CASE WHEN` (Excel Lesson 5, SQL Lesson 7).

**COMMON MISTAKES** **Order matters**

If you test `marks ⩾ 40` first, an 82 gets "C" because the first true branch wins. Put the most specific / strictest condition first.

Python

```python
for m in (95, 82, 61, 45, 12):
    g = "A+" if m ⩾ 90 else "A" if m ⩾ 75 else "B" if m ⩾ 60 else "C" if m ⩾ 40 else
"Fail"    # chained conditional expression
    print(m, g)
```

OUTPUT

```
95 A+
82 A
61 B
45 C
12 Fail
```

## Conditional expression (ternary)

`value_if_true if condition else value_if_false` is Python's one-line `IF()`:

Python

```python
salary = 97000
band = "High" if salary ⩾ 100000 else "Standard"
bonus = salary * 0.1 if band == "High" else 0
print(band, bonus)
```

OUTPUT

```
Standard 0
```

# Conditions

## Comparison and logical operators

Python

```python
age, city, income = 29, "Pune", 85000
print(age ⩾ 18 and city == "Pune")                    # both must be true
print(city in ("Pune", "Mumbai") or income > 100000)   # at least one
print(not (age < 18))
print(18 ⩽ age < 60)                                   # chained comparison
if 18 ⩽ age < 60 and income ⩾ 50000 and city in ("Pune", "Mumbai", "Delhi"):
    print("Eligible for the metro premium plan")
```

OUTPUT

```
True
True
True
True
Eligible for the metro premium plan
```

## Truthiness

Python treats "empty" and zero-like values as False (Lesson 2), so you can test them directly:

Python

```python
name = ""
items = [3, 5]
note = None
if not name: print("name is empty")
if items: print("items has", len(items), "elements")
if note is None: print("note is missing")                # use `is None`, not `== None`
if 0 < len(items) ⩽ 5: print("small list")
```

OUTPUT

```
name is empty
items has 2 elements
note is missing
small list
```

## Membership and string tests

Python

```
status = "Shipped"
if status in ("Shipped", "Delivered"): print("order has left the warehouse")
email = "kavya.iyer@abc.in"
if "@" in email and email.endswith(".in"): print("Indian email address")
```

OUTPUT

```
order has left the warehouse
Indian email address
```

## Nested conditions

Python

```
is_member, cart_value = True, 3200
if cart_value > 0:
    if is_member:
        discount = 0.1 if cart_value ⩾ 3000 else 0.05
    else:
        discount = 0.02 if cart_value ⩾ 3000 else 0
    print(f"Discount: {discount:.0%}")
else:
    print("Cart is empty")
```

OUTPUT

```
Discount: 10%
```

Prefer **flat** conditions with `and` to deeply nested ones when they read clearly:

Python

```
def shipping_fee(value, is_member):
    if value ⩽ 0: return 0
    if is_member and value ⩾ 500: return 0
    if value ⩾ 1500: return 0
    return 49
print([shipping_fee(v, m) for v, m in [(0, True), (600, True), (600, False), (1600,
False)]])
```

OUTPUT

```
[0, 0, 49, 0]
```

Returning early (**guard clauses**) keeps code flat and readable.

## match: structural pattern matching (3.10+)

`match` compares one value with several patterns: a clean alternative to a long chain of `==` tests.

Python

```
def describe_status(code):
    match code:
        case 200 | 201:
            return "success"
        case 301 | 302:
            return "redirect"
        case 404:
            return "not found"
        case int(c) if 500 ⩽ c < 600:
            return "server error"
        case _:
            return "unknown"
print([describe_status(c) for c in (200, 404, 503, 999)])
```

OUTPUT

```
['success', 'not found', 'server error', 'unknown']
```

Python

```
def handle(command):
    match command.split():
        case ["load", filename]:  return f"loading {filename}"
        case ["save", filename]:  return f"saving {filename}"
        case ["quit"]:            return "bye"
        case _:                   return "unknown command"
print(handle("load sales.csv"), "|", handle("quit"), "|", handle("fly away"))
```

OUTPUT

```
loading sales.csv | bye | unknown command
```

# Data examples

## Rule-based bonus (the same as an Excel IF + AND)

Python

```
import pandas as pd
emp = pd.read_csv("employees_small.csv")
def bonus(salary, rating, dept):
    if rating ⩾ 5: rate = 0.15
    elif rating ⩾ 4: rate = 0.10
    elif rating ⩾ 3: rate = 0.05
    else: rate = 0
    if dept == "Sales": rate += 0.02            # extra for Sales
    return round(salary * rate)
emp["bonus"] = [bonus(s, r, d) for s, r, d in zip(emp.salary, emp.rating, emp.department)]
emp[["name", "department", "salary", "rating", "bonus"]].head(8)
```

OUTPUT

| | name | department | salary | rating | bonus |
|---|---|---|---|---|---|
| 0 | Kavya Iyer | HR | 97000 | 4 | 9700 |
| 1 | Imran Reddy | Finance | 157000 | 3 | 7850 |
| 2 | Harpreet Kulkarni | Finance | 131000 | 4 | 13100 |
| 3 | Diya Iyer | HR | 90000 | 4 | 9000 |
| 4 | Simran Iyer | HR | 139000 | 4 | 13900 |
| 5 | Saanvi Rao | HR | 83000 | 4 | 8300 |
| 6 | Isha Mehta | Sales | 57000 | 3 | 3990 |
| 7 | Aarav Kulkarni | HR | 101000 | 2 | 0 |

8 rows × 5 columns

(In pandas you would use `np.where`, `np.select` or `.apply`: Lesson 19. Writing the rule once as a function makes it testable.)

### A small decision tree: loan pre-check

Python

```python
def loan_precheck(age, income, existing_emi, credit_score):
    reasons = []
    if age < 21 or age > 60: reasons.append("age outside 21-60")
    if income < 25000: reasons.append("income below ₹25,000")
    if existing_emi > 0.5 * income: reasons.append("EMIs exceed 50% of income")
    if credit_score < 650: reasons.append("credit score below 650")
    return ("Eligible", []) if not reasons else ("Review", reasons)
print(loan_precheck(34, 70000, 20000, 730))
print(loan_precheck(19, 22000, 15000, 610))
```

OUTPUT

```
('Eligible', [])
('Review', ['age outside 21-60', 'income below ₹25,000', 'EMIs exceed 50% of income',
'credit score below 650'])
```

Collecting **all** failing reasons is more useful than stopping at the first, and shows how a series of independent `if` statements (not `elif`) is sometimes right.

## `if`/`elif` vs several `if`s

| Pattern | Use when |
|---|---|
| `if … elif … else` | Choices are **mutually exclusive**: only one branch should run |
| Several separate `if` | Each condition is **independent**: more than one may apply (collecting reasons, applying several rules) |

## Common mistakes

| Mistake | Fix |
|---|---|
| `if x = 5:` (assignment) | `if x == 5:` |
| `if x == 3 or 4:` (always true: 4 is truthy) | `if x in (3, 4):` |
| `if x == None:` | `if x is None:` |
| Comparing floats with `==` | `math.isclose` |
| Forgetting `elif` ordering | strictest first |
| `if len(items) > 0:` (verbose) | `if items:` |
| Deep nesting | guard clauses / `and` / helper functions |

DO IT WITH AI **Do it with AI**

Take an Excel rule from your own work, such as a nested IF for commission, and ask an assistant to convert it to Python with test cases. Then write five edge-case tests yourself (boundaries like exactly 50,000, blanks, negative values) and see if the code survives.

## Summary

KEY TAKEAWAYS

- A colon starts a block; **indentation** (4 spaces) defines it. `if / elif / else` runs the first true branch.
- Combine conditions with `and`, `or`, `not`, `in`, chained comparisons; empty/zero/None are falsy; test `None` with `is None`.
- Use the **ternary** `a if cond else b` for simple choices and the `match` statement for many exact cases and patterns.
- Order conditions from strictest to loosest; prefer flat code with guard clauses; use separate `if`s when several rules can apply.
- Wrap rules in functions so they can be tested and reused.

## Quick quiz

6 questions · tap an answer to check it

**1. What does `x if cond else y` do?**

A Runs a loop

B Evaluates to x when cond is True, otherwise y

C Defines a function

D Compares x and y

**Answer: B.** It is Python's conditional (ternary) expression.

**2.** Which condition is correct for "x is 3 or 4"?

**A** `x == 3 or 4`

**B** `x in (3, 4)`

**C** `x = 3 or 4`

**D** `x is (3, 4)`

**Answer: B.** `x == 3 or 4` is always truthy because 4 is truthy.

**3.** With `marks = 82`, which grade does `if marks >= 40: "C" elif marks >= 75: "A"` give?

**A** C

**B** A

**C** Fail

**D** Nothing

**Answer: A.** The first true branch wins, so the order is wrong.

**4.** Which is the best way to test for None?

**A** `x == None`

**B** `x is None`

**C** `not x`

**D** `x = None`

**Answer: B.** `is None` tests identity and avoids surprises with falsy values like 0.

**5. What is a guard clause?**

A A loop that never ends

B An early return that handles a special case so the rest of the function is not nested

C A try/except block

D A decorator

**Answer: B.** Guard clauses keep code flat and readable.

**6. What does `match` do?**

A Matches regular expressions only

B Compares a value against patterns and runs the first matching case

C Loops over a list

D Imports modules

**Answer: B.** Structural pattern matching arrived in Python 3.10.

EXERCISE

### Rules in code

Write `delivery_charge(order_value, city, express)`: free if order ≥ ₹1,500; otherwise ₹49 in metros (Delhi, Mumbai, Bengaluru, Chennai, Kolkata, Hyderabad) and ₹79 elsewhere; express adds ₹100 unless the value is ≥ ₹5,000. Test five cases including boundaries.

**Show solution (worked answer)**

Python

```
METROS = {"Delhi", "Mumbai", "Bengaluru", "Chennai", "Kolkata", "Hyderabad"}
def delivery_charge(value, city, express=False):
    fee = 0 if value ⩾ 1500 else (49 if city in METROS else 79)
    if express and value < 5000: fee += 100
    return fee
tests = [(1500, "Pune", False), (1499, "Delhi", False), (1499, "Pune", True), (5000,
"Pune", True), (100, "Mumbai", True)]
print([delivery_charge(*t) for t in tests])      # [0, 49, 179, 0, 149]
```

INTERVIEW CORNER

### Questions you may be asked

**Q: What is the difference between `elif` and multiple `if` statements?** `elif` branches are mutually exclusive (only the first true runs); separate `if`s are all evaluated, so several can run.

**Q: How do you write a switch-case in Python?** Use `match`/`case` (3.10+), or a dictionary mapping values to functions or results.

**Q: What are falsy values in Python?** `False`, `None`, `0`, `0.0`, `""`, `[]`, `{}`, `()`, `set()`, and objects whose `__bool__` returns False or `__len__` returns 0.

**Q: How do you replace nested if/else cleanly?** Guard clauses, combined conditions, lookup tables (dicts), or polymorphism.

PYTHON FOR DATA SCIENCE · LESSON 5

# Loops: while, for, range, break, continue & Patterns

Repeat work without repeating code. Learn while and for loops, range(), enumerate(), zip(), break, continue, the loop else clause, nested loops, accumulation, search and counting patterns, and common loop bugs; with an eye on when to replace loops with vectorised pandas/NumPy.


Python classes 3–4 | Python 3.13 | Beginner | 110 min

**By the end of this lesson you can**

- Write while and for loops and choose between them
- Use range(), enumerate() and zip() for index, value and parallel iteration
- Control loops with break, continue and the loop-else clause; avoid infinite loops
- Apply accumulator, counter, search, nested-loop and pattern-printing recipes
- Recognise when a loop should be replaced by a built-in, comprehension or vectorised operation

## Why loops?

A **loop** repeats a block of code. Processing 10,000 rows, trying each file in a folder, retrying a failed request, or checking each number in a list are all loops.




Two kinds of loop. for repeats over a known sequence; while repeats as long as a condition stays true.

## The while loop

Python

```
count = 1
while count ⩽ 5:
    print("Count:", count)
    count += 1              # without this line the loop would never end!
print("Done")
```

OUTPUT

```
Count: 1
Count: 2
Count: 3
Count: 4
Count: 5
Done
```

Every while loop needs: **(1)** a starting value, **(2)** a condition, **(3)** a change inside the loop that eventually makes the condition False.

Python

```python
# Compound growth: how many years until 1,00,000 doubles at 8%?
amount, years = 100000, 0
while amount < 200000:
    amount *= 1.08
    years += 1
print(f"{years} years → {amount:,.0f}")          # the 'rule of 72': 72 / 8 = 9 years
```

OUTPUT

```
10 years → 215,892
```

### while True with break

Use an "infinite" loop that you leave deliberately when the input is right:

Python

```python
attempts = ["abc", "-4", "12"]        # simulated user answers
i = 0
while True:
    answer = attempts[i]; i += 1
    if answer.isdigit() and int(answer) > 0:
        print("Accepted:", answer); break
    print("Invalid:", answer)
```

OUTPUT

```
Invalid: abc
Invalid: -4
Accepted: 12
```

## The for loop

`for item in sequence:` takes each item in turn.

Python

```python
for city in ["Pune", "Delhi", "Kochi"]:
    print(city.upper())
for ch in "SQL":
    print(ch, end=" ")
print()
```

OUTPUT

```
PUNE
DELHI
KOCHI
S Q L
```

## range()

`range(stop)`, `range(start, stop)`, `range(start, stop, step)` produce integers (stop excluded). It is lazy: `range(1_000_000)` does not store a million numbers.

Python

```python
print(list(range(5)), list(range(2, 8)), list(range(10, 0, -3)), list(range(0, 1)))
total = 0
for n in range(1, 101): total += n
print("Sum 1..100 =", total, "| check:", sum(range(1, 101)), "| formula:", 100 * 101 // 2)
```

OUTPUT

```
[0, 1, 2, 3, 4] [2, 3, 4, 5, 6, 7] [10, 7, 4, 1] [0]
Sum 1..100 = 5050 | check: 5050 | formula: 5050
```

## enumerate() and zip()

Python

```python
products = ["Pen", "Notebook", "Stapler"]
prices = [10, 45, 180]
for i, p in enumerate(products, start=1):        # index and value together
    print(i, p)
for p, price in zip(products, prices):           # walk two lists in parallel
    print(f"{p:<10}{price:>5}")
print(dict(zip(products, prices)))                # build a dictionary from two lists
```

OUTPUT

```
1 Pen
2 Notebook
3 Stapler
Pen          10
Notebook     45
Stapler     180
{'Pen': 10, 'Notebook': 45, 'Stapler': 180}
```

Avoid `for i in range(len(x))` when you only need the items; use `for item in x` or `enumerate`.

## break, continue, else

Python

```python
for n in range(1, 20):
    if n % 3 != 0: continue            # skip numbers not divisible by 3
    if n > 12: break                    # leave the loop completely
    print(n, end=" ")
print()
for n in range(2, 6):
    if n == 9: break
else:                                   # runs only if the loop finished WITHOUT break
    print("loop completed with no break")
```

OUTPUT

```
3 6 9 12
loop completed with no break
```

| Keyword | Effect |
|---|---|
| `break` | Exit the nearest loop immediately |
| `continue` | Skip to the next iteration |
| `else` on a loop | Runs if the loop ended normally (no `break`): handy for "search and report not found" |
| `pass` | Do nothing (placeholder) |

# Loop patterns

## Accumulate (sum / product / build a list)

Python

```python
orders = [1200, 450, 3000, 780, 2200]
total, large = 0, []
for amount in orders:
    total += amount
    if amount ≥ 1000: large.append(amount)
print(total, large, total / len(orders))
```

OUTPUT

```
7630 [1200, 3000, 2200] 1526.0
```

## Count and find the maximum

Python

```
sales = [("North", 120), ("South", 95), ("East", 140), ("West", 88)]
best_region, best_value = None, float("-inf")
count_above_100 = 0
for region, value in sales:
    if value > best_value: best_region, best_value = region, value
    if value > 100: count_above_100 += 1
print(best_region, best_value, count_above_100)
```

OUTPUT

```
East 140 2
```

( `max(sales, key=lambda x: x[1])` does the same in one line, Lesson 10.)

## Search with early exit

Python

```
def find_first(items, target):
    for i, x in enumerate(items):
        if x == target: return i          # stop at the first match
    return -1
print(find_first(["a", "b", "c"], "c"), find_first(["a", "b"], "z"))
```

OUTPUT

```
2 -1
```

## Nested loops

Python

```
for i in range(1, 4):
    for j in range(1, 4):
        print(i * j, end="\t")
    print()
```

OUTPUT

```
1       2       3
2       4       6
3       6       9
```

Python

```
# Pattern: right triangle of stars
for row in range(1, 6): print("*" * row)
```

OUTPUT

```
*
**
***
****
*****
```

Nested loops multiply the work: 1,000 × 1,000 = 1,000,000 iterations. Be careful with big data.

## Reading until a sentinel

Python

```
readings = iter([12, 15, 11, -1, 99])          # -1 marks the end
total = 0
for r in readings:
    if r == -1: break
    total += r
print("Total before sentinel:", total)
```

OUTPUT

```
Total before sentinel: 38
```

# Data examples

## Looping over rows (and why it is slow)

Python

```
import pandas as pd, time
s = pd.read_csv("superstore_sales.csv")
t0 = time.perf_counter()
loss_lines = 0
for profit in s["profit"]:                    # plain loop over a column (6,323 values)
    if profit < 0: loss_lines += 1
t1 = time.perf_counter()
vec = (s["profit"] < 0).sum()                  # vectorised: one operation on the whole
column
t2 = time.perf_counter()
print(f"loop: {loss_lines} loss-making lines in {1000 * (t1 - t0):.2f} ms | vectorised:
{vec} in {1000 * (t2 - t1):.2f} ms")
```

OUTPUT

```
loop: 1682 loss-making lines in 0.84 ms | vectorised: 1682 in 0.34 ms
```

Same answer; the vectorised version is usually many times faster and shorter. **Rule:** in pandas/NumPy avoid Python loops over rows; use column operations, `groupby`, `np.where`. Use loops for files, APIs, orchestration, and small collections.

## Summarising with a loop

Python

```
totals = {}
for region, category, sales in zip(s["region"][:2000], s["category"][:2000], s["sales"]
[:2000]):
    key = (region, category)
    totals[key] = totals.get(key, 0) + sales
for k in sorted(totals)[:6]: print(k, f"{totals[k]:,.0f}")
```

OUTPUT

```
('East', 'Furniture') 2,148,878
('East', 'Office Supplies') 717,588
('East', 'Technology') 10,862,196
('North', 'Furniture') 2,782,383
('North', 'Office Supplies') 645,662
('North', 'Technology') 13,766,572
```

This is a hand-made `GROUP BY`: you now see what `groupby` does behind the scenes.

## Common loop bugs

| Bug | Symptom | Fix |
|---|---|---|
| Missing update in `while` | Runs forever (press ■ to interrupt) | Change the condition variable inside the loop |
| Off-by-one with `range` | Misses the last item | Remember stop is excluded: `range(1, n + 1)` |
| Modifying a list while iterating over it | Skipped items | Iterate over a copy `for x in items[:]` or build a new list |
| `for i in range(len(a))` then using a wrong index | `IndexError` | Use `enumerate` / `zip` |
| Re-using a loop variable after the loop | Holds the last value | Avoid relying on it |
| Resetting the accumulator inside the loop | Wrong totals | Initialise **before** the loop |
| String `+=` in a loop | Slow for big text | `"".join(parts)` |

**TIP** **Debug with print or a debugger**

Print the loop variable and key values each iteration (`print(i, value, total)`), or use the debugger in VS Code/Jupyter (`%debug`). Test the loop on a tiny example by hand first.

# Summary

**KEY TAKEAWAYS**

- `while` repeats while a condition holds (make sure something changes!); `for` iterates over any sequence.
- `range(start, stop, step)` generates integers, stop excluded; `enumerate` gives index and value; `zip` iterates in parallel.
- `break` exits, `continue` skips to the next item, loop `else` runs when no `break` happened.
- Patterns: accumulator, counter, max/min tracking, search with early exit, nested loops, sentinel.
- For tables of data prefer **vectorised** pandas/NumPy over row loops; use comprehensions and built-ins for small collections.

## Quick quiz

6 questions · tap an answer to check it

**1.** What does `list(range(2, 10, 3))` give?

**A** [2, 5, 8, 11]

**B** [2, 5, 8]

**C** [3, 6, 9]

**D** [2, 10]

**Answer: B.** Start 2, step 3, stop 10 excluded.

**2. What does `continue` do inside a loop?**

A Ends the loop

B Skips the rest of this iteration and moves to the next

C Restarts the program

D Pauses the loop

**Answer: B.** `break` ends the loop; `continue` skips one iteration.

**3. When does a loop's `else` block run?**

A When the loop has an error

B When the loop finishes without hitting `break`

C Before the loop

D Every iteration

**Answer: B.** It is useful for "not found" logic after a search loop.

**4. Why is this loop infinite? `n = 5` then `while n > 0: print(n)`**

A print is wrong

B n is never changed inside the loop

C 5 is too large

D range is missing

**Answer: B.** The condition never becomes False.

**5.** What is a better way to count rows with negative profit in pandas?

A A for loop over rows

B `(df["profit"] < 0).sum()`

C A while loop

D Nested loops

**Answer: B.** Vectorised operations are shorter and faster.

**6.** Which function walks two lists at the same time?

A `range`

B `zip`

C `sorted`

D `len`

**Answer: B.** `zip(a, b)` pairs items by position.

EXERCISE

### Loop problems

(1) Print the multiplication table of 7 up to 7 × 10. (2) Given a list of order values, print the first one above 5,000 and its position, or "none". (3) Count vowels in a sentence. (4) Print the first 10 Fibonacci numbers. (5) FizzBuzz for 1..30.

**Show solution (worked answer)**

Python

```
for i in range(1, 11): print(f"7 x {i} = {7 * i}")
vals = [900, 4200, 6100, 800]
for i, v in enumerate(vals):
    if v > 5000: print(v, "at", i); break
else: print("none")
print(sum(ch in "aeiou" for ch in "data engineering is fun".lower()))
a, b = 0, 1
for _ in range(10): print(a, end=" "); a, b = b, a + b
print()
for n in range(1, 31): print("FizzBuzz" if n % 15 == 0 else "Fizz" if n % 3 == 0 else
"Buzz" if n % 5 == 0 else n, end=" ")
```

INTERVIEW CORNER

### Questions you may be asked

**Q: FizzBuzz, reverse a string, print Fibonacci: why do interviewers ask these?** They test loops, conditions, modulo, variable swapping and clear thinking, and whether you handle edge cases.

**Q: for vs while?** `for` iterates over a known sequence; `while` loops until a condition changes, for unknown counts such as retries or reading until a sentinel.

**Q: How would you speed up a slow loop over a DataFrame?** Vectorise (column operations, `np.where`, `groupby`), use built-ins or `apply` only when needed, or push the work into SQL.

**Q: What does `for i in range(len(lst))` signal?** Often a less Pythonic style; prefer iterating over items, `enumerate` or `zip` unless you need indexes to modify items.

PYTHON FOR DATA SCIENCE · LESSON 6

# Lists: Creating, Slicing, Methods, Sorting & Comprehensions

Store and process ordered collections with lists. Index and slice them, add, remove and sort items, understand mutability, aliasing and copying (shallow vs deep), use nested lists, list comprehensions, and common patterns for cleaning and summarising data.

Python class 5 | Python 3.13 | Beginner | 120 min

**By the end of this lesson you can**

- Create lists and use indexing, slicing, concatenation, repetition and membership tests
- Apply list methods (append, extend, insert, remove, pop, sort, reverse, index, count) and built-ins (len, sum, min, max, sorted)
- Explain mutability, aliasing and the difference between assignment, shallow copy and deep copy
- Build lists with comprehensions, including conditions and nested loops
- Use lists for typical data tasks: filtering, ranking, de-duplicating while keeping order, flattening and unzipping

## What is a list?


A **list** is an ordered, **mutable** collection of items written in square brackets. Items can be of any type, and may repeat.

Python

```
cities = ["Pune", "Delhi", "Kochi", "Delhi"]
mixed = [101, "Kavya", 97000.5, True, None]
empty = []
print(cities, len(cities), type(cities).__name__)
print(list("data"), list(range(5)), list((1, 2, 3)), [0] * 5)
```

OUTPUT

```
['Pune', 'Delhi', 'Kochi', 'Delhi'] 4 list
['d', 'a', 't', 'a'] [0, 1, 2, 3, 4] [1, 2, 3] [0, 0, 0, 0, 0]
```




A list is a row of numbered boxes. Items are referenced by position; the list itself can grow, shrink and change.

## Indexing and slicing

Works exactly like strings (Lesson 3), but lists can also be **changed**.

Python

```python
nums = [10, 20, 30, 40, 50, 60]
print(nums[0], nums[-1], nums[1:4], nums[:2], nums[-2:], nums[::2], nums[::-1])
nums[0] = 99                    # change one item
nums[1:3] = [21, 31, 32]        # replace a slice (the length may change)
print(nums)
print(3 in nums, 99 in nums, nums.count(40), nums.index(40))
```

OUTPUT

```
10 60 [20, 30, 40] [10, 20] [50, 60] [10, 30, 50] [60, 50, 40, 30, 20, 10]
[99, 21, 31, 32, 40, 50, 60]
False True 1 4
```

# Adding and removing items

| Method | What it does | Example | Returns |
|---|---|---|---|
| `append(x)` | Add one item at the end | `a.append(5)` | None |
| `extend(iterable)` or `+=` | Add all items from another sequence | `a.extend([6, 7])` | None |
| `insert(i, x)` | Insert before position i | `a.insert(0, "first")` | None |
| `remove(x)` | Delete the first item equal to x | `a.remove(5)` | None (error if missing) |
| `pop(i=-1)` | Remove and return item at i | `last = a.pop()` | the item |
| `del a[i]` / `del a[i:j]` | Delete by position or slice | `del a[0]` | |
| `clear()` | Empty the list | `a.clear()` | None |

Python

```python
a = [1, 2, 3]
a.append(4); a.extend([5, 6]); a.insert(0, 0); a += [7]
print(a)
print(a.pop(), a.pop(0), a)          # removes 7, then 0
a.remove(3); del a[0]; print(a)
print([1, 2] + [3], [1, 2] * 2)       # concatenation creates new lists
print(a.append(9))                    # None! methods that change a list return None
```

OUTPUT

```
[0, 1, 2, 3, 4, 5, 6, 7]
7 0 [1, 2, 3, 4, 5, 6]
[2, 4, 5, 6]
[1, 2, 3] [1, 2, 1, 2]
None
```

COMMON MISTAKES **`x = x.append(...)`**

`append`, `sort`, `reverse` and `extend` change the list **in place** and return `None`. Writing `nums = nums.sort()` leaves `nums` as `None`. Use `sorted(nums)` when you want a new list.

## Sorting and reversing

Python

```
scores = [72, 95, 61, 88, 95]
print(sorted(scores), sorted(scores, reverse=True), scores)        # sorted() returns a
new list
scores.sort(); print(scores)                                        # .sort() changes the
list in place
words = ["banana", "Apple", "cherry", "apple"]
print(sorted(words), sorted(words, key=str.lower), sorted(words, key=len))
staff = [("Asha", 29, 61000), ("Ravi", 34, 88000), ("Meera", 41, 72000)]
print(sorted(staff, key=lambda p: p[2], reverse=True))              # sort records by the
3rd field
print(list(reversed([1, 2, 3])), min(staff, key=lambda p: p[1])[0])
```

OUTPUT

```
[61, 72, 88, 95, 95] [95, 95, 88, 72, 61] [72, 95, 61, 88, 95]
[61, 72, 88, 95, 95]
['Apple', 'apple', 'banana', 'cherry'] ['Apple', 'apple', 'banana', 'cherry']
['Apple', 'apple', 'banana', 'cherry']
[('Ravi', 34, 88000), ('Meera', 41, 72000), ('Asha', 29, 61000)]
[3, 2, 1] Asha
```

`sorted()` and `.sort()` are **stable**: equal items keep their original order, so you can sort by several keys by sorting repeatedly from the least to the most important key, or use a tuple key: `key=lambda p: (p[1], -p[2])`.

## Built-in helpers

Python

```
data = [4, 8, 15, 16, 23, 42]
print(len(data), sum(data), min(data), max(data), sum(data) / len(data))
print(any(x > 40 for x in data), all(x > 0 for x in data))
print(list(enumerate(["a", "b"], 1)), list(zip([1, 2, 3], "abc")))
a, b, *rest = data; print(a, b, rest)                               # unpacking with *
first, *middle, last = data; print(first, middle, last)
```

OUTPUT

```
6 108 4 42 18.0
True True
[(1, 'a'), (2, 'b')] [(1, 'a'), (2, 'b'), (3, 'c')]
```

```
4 8 [15, 16, 23, 42]
4 [8, 15, 16, 23] 42
```

## Mutability, aliasing and copying


A variable holds a **reference** to a list. Assigning a list to another name does **not** copy it.

Python

```python
a = [1, 2, 3]
b = a                    # b is another name for the SAME list
b.append(4)
print(a, b, a is b)
c = a.copy()             # a real (shallow) copy; also list(a) or a[:]
c.append(99)
print(a, c, a is c)
```

OUTPUT

```
[1, 2, 3, 4] [1, 2, 3, 4] True
[1, 2, 3, 4] [1, 2, 3, 4, 99] False
```




Assignment gives two names for one list; copy() makes a second list. A shallow copy still shares inner lists.

Python

```
import copy
grid = [[1, 2], [3, 4]]
shallow = grid.copy(); deep = copy.deepcopy(grid)
grid[0][0] = 100
print(shallow, deep)       # shallow copy sees the change in the inner list; deep copy does not
```

OUTPUT

```
[[100, 2], [3, 4]] [[1, 2], [3, 4]]
```

WATCH OUT **Mutable default arguments and `[[0] * 3] * 3`**

`[[0] * 3] * 3` creates **three references to the same inner list**; changing one row changes all. Build grids with a comprehension: `[[0] * 3 for _ in range(3)]`. Never use a list as a default function argument ( `def f(x, items=[])` ): use `None` and create the list inside (Lesson 9).

## Nested lists

Python

```
matrix = [[1, 2, 3], [4, 5, 6], [7, 8, 9]]
print(matrix[1][2], [row[0] for row in matrix], [sum(row) for row in matrix])
print([list(col) for col in zip(*matrix)])                # transpose
flat = [x for row in matrix for x in row]; print(flat)    # flatten
```

OUTPUT

```
6 [1, 4, 7] [6, 15, 24]
[[1, 4, 7], [2, 5, 8], [3, 6, 9]]
[1, 2, 3, 4, 5, 6, 7, 8, 9]
```

## List comprehensions

A comprehension builds a list in one readable line: `[expression for item in iterable if condition]`.

Python

```
squares = [n ** 2 for n in range(1, 8)]
evens = [n for n in range(20) if n % 2 == 0]
upper = [c.upper() for c in ["pune", "delhi"]]
labels = ["High" if s >= 80 else "Low" for s in [95, 60, 82]]
pairs = [(i, j) for i in range(1, 4) for j in range(i, 4)]
print(squares, evens, upper, labels, pairs, sep="\n")
```

OUTPUT

```
[1, 4, 9, 16, 25, 36, 49]
[0, 2, 4, 6, 8, 10, 12, 14, 16, 18]
['PUNE', 'DELHI']
['High', 'Low', 'High']
[(1, 1), (1, 2), (1, 3), (2, 2), (2, 3), (3, 3)]
```

Compare with the loop version:

Python

```
result = []
for n in range(20):
    if n % 2 == 0:
        result.append(n)
print(result == [n for n in range(20) if n % 2 == 0])
```

OUTPUT

```
True
```

Use comprehensions for **simple** transformations and filters; switch to a loop when the logic needs several statements. For very large data use generators (Lesson 10) or pandas.

# Data tasks with lists

Python

```
import pandas as pd
emp = pd.read_csv("employees_small.csv")
salaries = emp.salary.tolist(); names = emp.name.tolist(); depts = emp.department.tolist()
top3 = sorted(zip(salaries, names), reverse=True)[:3]
print("Top 3:", [(n, s) for s, n in top3])
fin = [s for s, d in zip(salaries, depts) if d == "Finance"]
print("Finance:", len(fin), "people, average", round(sum(fin) / len(fin)))
above_avg = [n for n, s in zip(names, salaries) if s > sum(salaries) / len(salaries)]
print(len(above_avg), "people earn above the average;", above_avg[:3], "…")
```

OUTPUT

```
Top 3: [('Vivaan Gupta', 157000), ('Imran Reddy', 157000), ('Krishna Khan', 156000)]
Finance: 7 people, average 95714
9 people earn above the average; ['Imran Reddy', 'Harpreet Kulkarni', 'Simran Iyer']
…
```

Python

```
# Remove duplicates but keep the original order (set() would lose the order)
raw = ["Pune", "Delhi", "Pune", "Kochi", "Delhi", "Goa"]
seen, unique = set(), []
for c in raw:
    if c not in seen: seen.add(c); unique.append(c)
print(unique, "| shortcut:", list(dict.fromkeys(raw)))
# Chunk a list into groups of 4
ids = list(range(1, 11)); print([ids[i:i + 4] for i in range(0, len(ids), 4)])
# Moving average of 3
x = [10, 12, 9, 14, 15, 13]; print([round(sum(x[i:i + 3]) / 3, 1) for i in range(len(x) -
2)])
```

OUTPUT

```
['Pune', 'Delhi', 'Kochi', 'Goa'] | shortcut: ['Pune', 'Delhi', 'Kochi', 'Goa']
[[1, 2, 3, 4], [5, 6, 7, 8], [9, 10]]
[10.3, 11.7, 12.7, 14.0]
```

## Performance notes

| Operation | Cost |
| --- | --- |
| `a[i]`, `a.append(x)`, `a.pop()` | O(1) |
| `x in a`, `a.index(x)`, `a.remove(x)`, `a.insert(0, x)` | O(n) |
| `a.sort()` | O(n log n) |

For many membership tests use a **set** (O(1)); for a queue use `collections.deque`. (More in the DSA lessons.)

## Summary

**KEY TAKEAWAYS**

- A list is an ordered, **mutable** collection; index and slice like strings; negative indexes count from the end.
- `append`, `extend`, `insert`, `remove`, `pop`, `sort`, `reverse` change the list in place and return `None`; `sorted()` and `reversed()` give new objects.
- `b = a` is an **alias**; use `a.copy()` (shallow) or `copy.deepcopy(a)` for independent copies; build grids with comprehensions.
- Sort records with `key=` (and tuple keys); sorting is stable.
- Comprehensions `[f(x) for x in xs if cond]` create lists concisely; unpack with `a, *rest = items`.
- Membership tests on lists are O(n): use sets for lookups.

### Quick quiz

6 questions · tap an answer to check it

**1.** What does `[1, 2, 3].append(4)` return?

**A** [1, 2, 3, 4]

**B** None (the list is changed in place)

**C** 4

**D** A new list

**Answer: B.** Mutating methods return None.

**2.** After `b = a; b.append(1)`, what is true?

**A** a is unchanged

**B** a and b are the same list, so a also contains the new item

**C** b is a copy

**D** An error occurs

**Answer: B.** Assignment creates an alias, not a copy.

**3.** What does `[x * 2 for x in range(5) if x % 2 == 0]` return?

**A** [0, 2, 4, 6, 8]

**B** [0, 4, 8]

**C** [0, 2, 4]

**D** [2, 6]

**Answer: B.** Only x = 0, 2, 4 pass the filter and are doubled.

**4.** How do you sort a list of tuples by the second element, descending?

A `sorted(t)`

B `sorted(t, key=lambda p: p[1], reverse=True)`

C `t.sort(1)`

D `sort(t, 1)`

**Answer: B.** The key function selects the field to compare.

**5.** Why does `grid = [[0] * 3] * 3; grid[0][0] = 1` change every row?

A A bug in Python

B The outer multiplication repeats references to the same inner list

C Lists are immutable

D Comprehensions are required for all lists

**Answer: B.** Use `[[0] * 3 for _ in range(3)]`.

**6.** Which is the fastest way to test if an item is in a large collection many times?

A A list

B A set

C A string

D A tuple

**Answer: B.** Sets use hashing for O(1) average lookups.

EXERCISE

### List drills

(1) From `[3, 8, 1, 9, 4, 8]` return the second-largest distinct value. (2) Remove duplicates from `["b","a","b","c","a"]` keeping order. (3) Flatten `[[1,2],[3],[4,5,6]]`. (4) Given names and salaries lists, print "name: salary" sorted by salary descending. (5) Rotate `[1,2,3,4,5]` by 2 positions to the right.

**Show solution (worked answer)**

Python

```python
print(sorted(set([3, 8, 1, 9, 4, 8]))[-2])                          # 8
print(list(dict.fromkeys(["b", "a", "b", "c", "a"])))               # ['b', 'a', 'c']
print([x for sub in [[1, 2], [3], [4, 5, 6]] for x in sub])         # [1, 2, 3, 4, 5, 6]
names, sal = ["A", "B", "C"], [50, 90, 70]
for n, s in sorted(zip(names, sal), key=lambda p: -p[1]): print(f"{n}: {s}")
r = [1, 2, 3, 4, 5]; print(r[-2:] + r[:-2])                         # [4, 5, 1, 2, 3]
```

INTERVIEW CORNER

### Questions you may be asked

**Q: Difference between a list and a tuple?** Lists are mutable, tuples immutable (hashable if their items are); tuples are used for fixed records and as dictionary keys, lists for collections that change.

**Q: Shallow vs deep copy?** A shallow copy duplicates the outer list but shares inner objects; a deep copy recursively copies everything.

**Q: What is the time complexity of `x in list` vs `x in set`?** O(n) vs O(1) average.

**Q: How do you reverse a list in place?** `lst.reverse()` or `lst[:] = lst[::-1]`; `lst[::-1]` creates a reversed copy.

PYTHON FOR DATA SCIENCE · LESSON 7

# Tuples & Sets: Immutable Records, Unpacking and Set Algebra

Use tuples for fixed records and multiple return values, master unpacking and named tuples, and use sets for uniqueness, fast membership tests and set algebra (union, intersection, difference) on real customer data.

Python class 5 | Python 3.13 | Beginner | 90 min

**By the end of this lesson you can**

- Create tuples, explain immutability and hashability, and unpack tuples including starred unpacking
- Use namedtuple and dataclass-style records for readable fixed structures
- Create sets and frozensets and use add, discard, remove, update and set operators
- Apply union, intersection, difference and symmetric difference to compare groups
- Choose between list, tuple, set and dict for a given task

## Tuples

A **tuple** is an ordered, **immutable** sequence written with commas (brackets are usually optional).

Python

```
point = (28.61, 77.20)
single = (5,)                    # the trailing comma makes a one-item tuple
empty = ()
rec = "E101", "Kavya Iyer", "HR", 97000        # packing: no brackets needed
print(point, type(single).__name__, type((5)).__name__, rec[1], rec[-1], rec[1:3],
len(rec))
print(rec.count("HR"), rec.index("HR"), (1, 2) + (3,), (0,) * 3, 5 in (1, 5, 9))
try: rec[0] = "E102"
except TypeError as e: print("Error:", e)
```

OUTPUT

```
(28.61, 77.2) tuple int Kavya Iyer 97000 ('Kavya Iyer', 'HR') 4
1 2 (1, 2, 3) (0, 0, 0) True
Error: 'tuple' object does not support item assignment
```

## Unpacking

Python

```python
emp_id, name, dept, salary = rec                # one name per item
a, b = 1, 2; a, b = b, a                          # swap
first, *others = (10, 20, 30, 40)                 # * collects the rest into a list
*head, last = (10, 20, 30, 40)
x, (y, z) = 1, (2, 3)                             # nested unpacking
_, dept_only, *_ = rec                            # _ means "ignore"
print(emp_id, name, a, b, first, others, head, last, x, y, z, dept_only)
for city, sales in [("Pune", 120), ("Delhi", 95)]:     # unpack in loops
    print(city, sales)
```

OUTPUT

```
E101 Kavya Iyer 2 1 10 [20, 30, 40] [10, 20, 30] 40 1 2 3 Kavya Iyer
Pune 120
Delhi 95
```

## Why tuples?

| Use | Example |
|---|---|
| **Fixed records** | `(lat, lon)`, `(year, month)`, a row from a database |
| **Multiple return values** | `def stats(x): return min(x), max(x)` → `lo, hi = stats(data)` |
| **Dictionary keys and set members** (hashable) | `sales[("North", "Technology")]` |
| **Protection** from accidental change | Constants like `METROS = ("Delhi", "Mumbai")` |
| **Slightly less memory and faster** than lists | |

Python

```
def describe(values):
    return min(values), max(values), sum(values) / len(values)
lo, hi, avg = describe([4, 8, 15, 16, 23, 42])
print(lo, hi, round(avg, 2), describe([1, 2]))
print(hash((1, 2)), "| a tuple containing a list is not hashable:", end=" ")
try: hash((1, [2]))
except TypeError as e: print(e)
```

OUTPUT

```
4 42 18.0 (1, 2, 1.5)
-3550055125485641917 | a tuple containing a list is not hashable: unhashable type:
'list'
```

**NOTE** **Tuples are immutable, but their contents might not be**

`t = ([1, 2], 3)`; `t[0].append(9)` works, because the tuple holds a **reference** to a mutable list. The tuple itself still points to the same list.

## Named tuples and data classes

When a record has many fields, positions like `rec[3]` are hard to read. Name the fields:

Python

```
from collections import namedtuple
from dataclasses import dataclass
Employee = namedtuple("Employee", ["emp_id", "name", "dept", "salary"])
e = Employee("E101", "Kavya Iyer", "HR", 97000)
print(e, e.name, e[3], e._asdict(), e._replace(salary=100000).salary)

@dataclass(frozen=True)                # frozen = immutable, like a tuple, but with types
and methods
class Product:
    sku: str
    price: float
    def with_gst(self, rate=0.18): return round(self.price * (1 + rate), 2)
p = Product("P101", 4500.0)
print(p, p.with_gst())
```

OUTPUT

```
Employee(emp_id='E101', name='Kavya Iyer', dept='HR', salary=97000) Kavya Iyer 97000
{'emp_id': 'E101', 'name': 'Kavya Iyer', 'dept': 'HR', 'salary': 97000} 100000
Product(sku='P101', price=4500.0) 5310.0
```

## Sets

A **set** is an **unordered** collection of **unique**, hashable items, written with braces. Sets support fast membership tests and mathematical set operations.

Python

```python
cities = {"Pune", "Delhi", "Kochi", "Delhi"}          # duplicates vanish
print(cities, len(cities), "Pune" in cities)
empty = set()                                          # {} is an empty DICT, not a set!
print(set("mississippi"), set([3, 1, 2, 3, 1]), sorted({5, 2, 9}), type({}).__name__,
type(empty).__name__)
```

OUTPUT

```
{'Delhi', 'Pune', 'Kochi'} 3 True
{'m', 'p', 's', 'i'} {1, 2, 3} [2, 5, 9] dict set
```

| Method / operator | Effect |
|---|---|
| `s.add(x)` | Add an item |
| `s.update(iterable)` or `s \|= other` | Add many items |
| `s.discard(x)` | Remove x if present (no error) |
| `s.remove(x)` | Remove x; `KeyError` if missing |
| `s.pop()` | Remove and return an arbitrary item |
| `s.clear()` | Empty the set |
| `x in s` | Membership, **O(1)** on average |
| `len(s)` , `min(s)` , `max(s)` , `sum(s)` , `sorted(s)` | Usual helpers (sorted returns a list) |


Python

```python
s = {1, 2, 3}
s.add(4); s.update([5, 6]); s.discard(10); s.remove(1)
print(s, s.pop() in {2, 3, 4, 5, 6})
```

OUTPUT

```
{3, 4, 5, 6} True
```

## Set algebra




The four set operations as Venn diagrams (A and B are sets of customers).

Python

```python
a = {"Asha", "Ravi", "Meera", "Kabir"}
b = {"Meera", "Kabir", "Zoya", "Neha"}
print("union       :", sorted(a | b), "  also a.union(b)")
print("intersection:", sorted(a & b), "  also a.intersection(b)")
print("A - B       :", sorted(a - b), "  also a.difference(b)")
print("B - A       :", sorted(b - a))
print("A ^ B       :", sorted(a ^ b), "  (in exactly one)")
print(a <= {"Asha", "Ravi", "Meera", "Kabir", "X"}, {"Asha"} < a, a.isdisjoint({"Zoya"}))
# subset, proper subset, disjoint
```

OUTPUT

```
union       : ['Asha', 'Kabir', 'Meera', 'Neha', 'Ravi', 'Zoya']   also a.union(b)
intersection: ['Kabir', 'Meera']   also a.intersection(b)
A - B       : ['Asha', 'Ravi']   also a.difference(b)
B - A       : ['Neha', 'Zoya']
A ^ B       : ['Asha', 'Neha', 'Ravi', 'Zoya']   (in exactly one)
True True True
```

These are the same operations as SQL's `UNION`, `INTERSECT` and `EXCEPT` (SQL Lesson 9).

## Frozen sets

`frozenset` is an immutable set: it can be a dictionary key or a member of another set.

Python

```python
fs = frozenset({"North", "South"})
print(fs, {fs: "regions"}, fs | {"East"})
```

OUTPUT

```
frozenset({'North', 'South'}) {frozenset({'North', 'South'}): 'regions'}
frozenset({'North', 'South', 'East'})
```

## Real data: customer movement with sets

The Superstore data lets us rebuild the retention analysis from SQL Lesson 9 with sets:

Python

```
import pandas as pd
s = pd.read_csv("superstore_sales.csv", parse_dates=["order_date"])
cust = {y: set(s.loc[s.order_date.dt.year == y, "customer_id"]) for y in (2023, 2024,
2025)}
print({y: len(c) for y, c in cust.items()})
retained = cust[2024] & cust[2025]
lost = cust[2024] - cust[2025]
new_in_2025 = cust[2025] - (cust[2023] | cust[2024])
print(f"Retained 2024→2025: {len(retained)} | lost: {len(lost)} | brand new in 2025:
{len(new_in_2025)}")
print(f"Retention rate: {len(retained) / len(cust[2024]):.1%}  (matches the SQL result: 467
of 590)")
print("Bought in all 3 years:", len(cust[2023] & cust[2024] & cust[2025]), "| bought in
exactly one year:", len((cust[2023] ^ cust[2024] ^ cust[2025]) - (cust[2023] & cust[2024] &
cust[2025])))
```

OUTPUT

```
{2023: 540, 2024: 590, 2025: 623}
Retained 2024→2025: 467 | lost: 123 | brand new in 2025: 52
Retention rate: 79.2%  (matches the SQL result: 467 of 590)
Bought in all 3 years: 311 | bought in exactly one year: 128
```

Same answers as the SQL queries, in three lines. Sets are also the fastest way to **de-duplicate** and to **check membership** in big collections:

Python

```
import time, random
big_list = list(range(200_000)); big_set = set(big_list); probes =
[random.randrange(400_000) for _ in range(300)]
t0 = time.perf_counter(); [p in big_list for p in probes]; t1 = time.perf_counter(); [p in
big_set for p in probes]; t2 = time.perf_counter()
print(f"300 lookups: list {1000 * (t1 - t0):.1f} ms | set {1000 * (t2 - t1):.3f} ms")
```

OUTPUT

```
300 lookups: list 329.5 ms | set 0.244 ms
```

## Choosing a collection

| Need | Use |
|---|---|
| Ordered, changeable sequence | `list` |
| Ordered, fixed record or dict key | `tuple` |
| Unique items, fast "is it in there?", set algebra | `set` |
| Key → value lookup | `dict` (next lesson) |
| Unique **and** ordered | `dict.fromkeys(items)` or a list + set |
| FIFO queue | `collections.deque` |
| Counting | `collections.Counter` |

## Summary

**KEY TAKEAWAYS**

- **Tuples** are ordered and immutable: use them for fixed records, multiple return values and dictionary keys; unpack with `a, b = t` and `first, *rest = t`.
- A one-item tuple needs a comma: `(5,)`. Use **namedtuple** or a frozen **dataclass** for readable records.
- **Sets** hold unique, hashable items with O(1) membership; `{}` is an empty dict, so use `set()`.
- Set algebra: `|` union, `&` intersection, `-` difference, `^` symmetric difference; subset tests with `<=`.
- Sets turn retention/overlap analyses into one-liners and are far faster than lists for membership tests.

### Quick quiz

6 questions · tap an answer to check it

**1.** What is `type((5))` ?

**A** tuple

**B** int

**C** list

**D** set

**Answer: B.** Brackets alone do not make a tuple; `(5,)` does.

**2.** What does `{1, 2, 3} & {2, 3, 4}` return?

**A** {1, 2, 3, 4}

**B** {2, 3}

**C** {1, 4}

**D** {1}

**Answer: B.** `&` is the intersection.

**3.** Which can be used as a dictionary key?

**A** A list

**B** A tuple of strings

**C** A set

**D** A dict

**Answer: B.** Keys must be hashable; lists, sets and dicts are not.

**4.** How do you create an empty set?

A `{}`

B `set()`

C `[]`

D `()`

**Answer: B.** `{}` creates an empty dictionary.

**5.** What does `first, *rest = (1, 2, 3, 4)` assign to `rest`?

A (2, 3, 4)

B [2, 3, 4]

C 4

D 2

**Answer: B.** Starred unpacking collects the remaining items into a list.

**6.** Why are set lookups faster than list lookups?

A Sets are sorted

B Sets use hashing, giving O(1) average membership tests

C Sets store fewer items

D They are not faster

**Answer: B.** A list scans item by item (O(n)).

EXERCISE

### Set problems

(1) Find the common cities between `{"Pune","Delhi","Goa"}` and `{"Goa","Kochi","Pune"}`. (2) Customers who bought in 2023 and 2024 but not in 2025 (use the Superstore sets). (3) Write `min_max_mean(values)` returning a tuple, and unpack it. (4) Check whether two words are anagrams using `sorted` and also using `collections.Counter`.

**Show solution (worked answer)**

Python

```
print({"Pune","Delhi","Goa"} & {"Goa","Kochi","Pune"})
print(len((cust[2023] & cust[2024]) - cust[2025]))
def min_max_mean(v): return min(v), max(v), sum(v) / len(v)
lo, hi, m = min_max_mean([3, 9, 6])
from collections import Counter
print(sorted("listen") == sorted("silent"), Counter("listen") == Counter("silent"))
```

INTERVIEW CORNER

### Questions you may be asked

**Q: Tuple vs list: when would you choose each?** Tuple for fixed, heterogeneous records, hashable keys and returning several values; list for homogeneous collections that change.

**Q: How do you remove duplicates from a list while preserving order?** `list(dict.fromkeys(items))`; `list(set(items))` does not preserve order.

**Q: What is the time complexity of set membership and why?** Average O(1) because sets are hash tables (worst case O(n) with many collisions).

**Q: How do you find items in A but not in B?** `A - B` for sets; for lists use a set for B: `[x for x in A if x not in set_b]`.

PYTHON FOR DATA SCIENCE · LESSON 8

# Dictionaries: Key-Value Data, Counting and Grouping

Store and look up data by key. Create and update dictionaries, use get, setdefault, items, Counter and defaultdict, nest dictionaries, and convert between dictionaries, JSON-like records and DataFrames using the Superstore data.


Python class 6 | Python 3.13 | Beginner | 100 min

**By the end of this lesson you can**

- Create dictionaries and read, add, update and delete keys safely
- Loop over keys, values and items and merge dictionaries
- Count and group with get, setdefault, Counter and defaultdict
- Work with nested dictionaries and lists of dictionaries (JSON-like records)
- Convert between dictionaries and pandas DataFrames

## What is a dictionary?

A **dictionary** ( `dict` ) maps **keys** to **values**: look up by name instead of by position. It keeps insertion order (Python 3.7+), and lookups are O(1) on average.




A dictionary is a set of key → value pairs. The key is hashed, so the lookup does not scan the data.

Python

```
emp = {"name": "Kavya Iyer", "dept": "HR", "salary": 97000}
print(emp["name"], emp.get("dept"), emp.get("city"), emp.get("city", "unknown"), len(emp),
"salary" in emp)
try: emp["city"]
except KeyError as e: print("KeyError:", e)
```

OUTPUT

```
Kavya Iyer HR None unknown 3 True
KeyError: 'city'
```

`d[key]` raises `KeyError` when missing; `d.get(key, default)` never does.

## Changing a dictionary

Python

```
emp["city"] = "Pune"                # add
emp["salary"] += 3000                # update
emp.update({"dept": "Finance", "grade": "M2"})
removed = emp.pop("grade")          # remove and return
del emp["city"]
print(emp, removed)
print(emp.setdefault("level", "L3"), emp.setdefault("dept", "X"), emp)    # set only if
missing
```

OUTPUT

```
{'name': 'Kavya Iyer', 'dept': 'Finance', 'salary': 100000} M2
L3 Finance {'name': 'Kavya Iyer', 'dept': 'Finance', 'salary': 100000, 'level': 'L3'}
```

| Method | Effect |
| --- | --- |
| `d[k] = v` | Add or overwrite |
| `d.get(k, default)` | Safe read |
| `d.setdefault(k, default)` | Read; insert default if missing |
| `d.update(other)` or `d \| other` | Merge (right side wins) |
| `d.pop(k[, default])` | Remove and return |
| `d.popitem()` | Remove the last pair |
| `del d[k]` | Delete (KeyError if missing) |
| `d.keys()` , `d.values()` , `d.items()` | Views |
| `d.copy()` | Shallow copy |
| `dict.fromkeys(keys, value)` | Create with the same value |

## Looping

Python

```python
prices = {"Pen": 10, "Notebook": 45, "Stapler": 180}
for k in prices: print(k, end=" ")
print()
for k, v in prices.items(): print(f"{k:<10}{v:>5}")
print(list(prices.values()), sum(prices.values()), max(prices, key=prices.get),
sorted(prices.items(), key=lambda kv: -kv[1]))
merged = prices | {"Pen": 12, "Folder": 30}              # Python 3.9+
print(merged)
print({v: k for k, v in prices.items()})                  # invert (values must be unique
and hashable)
```

OUTPUT

```
Pen Notebook Stapler
Pen          10
Notebook     45
Stapler     180
[10, 45, 180] 235 Stapler [('Stapler', 180), ('Notebook', 45), ('Pen', 10)]
{'Pen': 12, 'Notebook': 45, 'Stapler': 180, 'Folder': 30}
{10: 'Pen', 45: 'Notebook', 180: 'Stapler'}
```

# Counting and grouping

The most common dictionary jobs are **count** and **group**:

Python

```
from collections import Counter, defaultdict
words = "the cat and the hat and the bat".split()
manual = {}
for w in words: manual[w] = manual.get(w, 0) + 1            # classic pattern
print(manual)
c = Counter(words)
print(c, c.most_common(2), c["the"], c["dog"])
groups = defaultdict(list)                                   # missing key starts as an
empty list
for w in words: groups[len(w)].append(w)
print(dict(groups))
```

OUTPUT

```
{'the': 3, 'cat': 1, 'and': 2, 'hat': 1, 'bat': 1}
Counter({'the': 3, 'and': 2, 'cat': 1, 'hat': 1, 'bat': 1}) [('the', 3), ('and', 2)]
3 0
{3: ['the', 'cat', 'and', 'the', 'hat', 'and', 'the', 'bat']}
```

Python

```
import pandas as pd
s = pd.read_csv("superstore_sales.csv")
by_region = Counter(s["region"])                             # count rows
revenue = defaultdict(float)
for r, amount in zip(s["region"], s["sales"]): revenue[r] += amount
print(by_region.most_common())
print({k: round(v / 1e6, 1) for k, v in sorted(revenue.items(), key=lambda kv: -kv[1])}, "
(sales in millions)")
print(s.groupby("region")
["sales"].sum().div(1e6).round(1).sort_values(ascending=False).to_dict())   # same in
pandas
```

OUTPUT

```
[('South', 1656), ('West', 1614), ('North', 1530), ('East', 1523)]
{'South': 54.0, 'West': 52.0, 'North': 49.0, 'East': 46.5} (sales in millions)
{'South': 54.0, 'West': 52.0, 'North': 49.0, 'East': 46.5}
```

# Nested dictionaries and JSON-like records

Real data (API responses, configs, documents) nests dictionaries and lists. Python's `json` module reads and writes exactly this structure.

Python

```
import json
order = {"order_id": "O-1001", "customer": {"id": "C7", "name": "Asha", "city": "Pune"},
         "items": [{"sku": "P1", "qty": 2, "price": 450.0}, {"sku": "P2", "qty": 1,
"price": 1200.0}]}
total = sum(i["qty"] * i["price"] for i in order["items"])
print(order["customer"]["city"], len(order["items"]), total, order.get("shipping",
{}).get("city", "n/a"))
text = json.dumps(order, indent=2)
print(text[:90].replace("\n", " "), "...", json.loads(text) == order)
```

OUTPUT

```
Pune 2 2100.0 n/a
{   "order_id": "O-1001",   "customer": {     "id": "C7",     "name": "Asha",
"city":  ... True
```

A **list of dictionaries** is the standard row format, and it converts straight to a DataFrame:

Python

```
rows = [{"sku": "P1", "qty": 2, "price": 450.0}, {"sku": "P2", "qty": 1, "price": 1200.0},
{"sku": "P3", "qty": 5, "price": 80.0}]
df = pd.DataFrame(rows)
df["value"] = df.qty * df.price
print(df)
print(df.set_index("sku")["value"].to_dict(), df.to_dict("records")[0])
```

OUTPUT

```
  sku  qty   price   value
0  P1    2   450.0   900.0
1  P2    1  1200.0  1200.0
2  P3    5    80.0   400.0
{'P1': 900.0, 'P2': 1200.0, 'P3': 400.0} {'sku': 'P1', 'qty': 2, 'price': 450.0,
'value': 900.0}
```

## Lookup tables and dispatch

Python

```
tier = {"North": "A", "South": "A", "East": "B", "West": "C"}                #
mapping/lookup
print(s["region"].map(tier).value_counts().to_dict())
ops = {"add": lambda a, b: a + b, "mul": lambda a, b: a * b}                  # dictionary
of functions
print(ops["add"](3, 4), ops["mul"](3, 4))
```

OUTPUT

```
{'A': 3186, 'C': 1614, 'B': 1523}
7 12
```

NOTE **Keys must be hashable**

Strings, numbers and tuples work as keys; lists, sets and dicts do not. Use a tuple `("North", 2025)` for composite keys. Copying: `d.copy()` is shallow; use `copy.deepcopy` for nested data (Lesson 6).

## Common mistakes

| Mistake | Fix |
|---|---|
| `d["missing"]` raises KeyError | `d.get(k, default)` or `if k in d` |
| Changing a dictionary's size while looping over it | Loop over `list(d)` or build a new dict |
| `{}` for an empty set | `set()`; `{}` is an empty dict |
| Duplicate keys in a literal | The last one silently wins |
| Assuming a shallow copy protects nested data | `copy.deepcopy` |

# Summary

**KEY TAKEAWAYS**

- A dict maps hashable keys to values with O(1) average lookup and keeps insertion order.
- Use `get` for safe reads, `setdefault` / `defaultdict` for grouping, `Counter` for counting, `d | other` to merge.
- Loop with `items()`; build with dict comprehensions `{k: f(v) for k, v in ...}`.
- Nested dict/list structures are JSON; a list of dicts converts to a DataFrame with `pd.DataFrame(rows)`.
- Dictionaries are lookup tables: `series.map(dict)` is a fast way to recode a column.

## Quick quiz

6 questions · tap an answer to check it

**1. What does `d.get("x", 0)` do when "x" is missing?**

A Raises KeyError

B Returns 0

C Adds the key

D Returns None

**Answer: B.** `get` never raises; it returns the default.

**2. Which is a valid dictionary key?**

A `[1, 2]`

B `(1, 2)`

C `{1, 2}`

D `{"a": 1}`

**Answer: B.** Keys must be hashable (immutable).

**3.** Which tool counts occurrences most directly?

A `defaultdict(list)`

B `collections.Counter`

C `set`

D `zip`

**Answer: B.** `Counter(items).most_common()`.

**4.** What does `{"a": 1} | {"a": 2, "b": 3}` give?

A {"a": 1, "b": 3}

B {"a": 2, "b": 3}

C Error

D {"a": 3}

**Answer: B.** The right-hand dictionary wins on conflicts.

**5.** How do you loop over keys and values together?

A `for k in d.values()`

B `for k, v in d.items()`

C `for k, v in d`

D `for v in d.keys()`

**Answer: B.** `items()` yields (key, value) pairs.

**6.** What does `pd.DataFrame(list_of_dicts)` produce?

- **A** A Series
- **B** A table with one row per dictionary and columns from the keys
- **C** A list
- **D** An error

**Answer: B.** This is the standard way to turn JSON-like records into a table.

EXERCISE **Dictionary problems**

(1) Count the frequency of each character in `"banana"`. (2) Group Superstore product `category` into a dictionary of sets of `sub_category`. (3) Invert `{"a": 1, "b": 2}`. (4) Given a list of orders, compute the total per customer using `defaultdict`. (5) Merge two dictionaries where the second overrides the first.

**Show solution (worked answer)**

Python

```python
from collections import Counter, defaultdict
print(Counter("banana"))
g = defaultdict(set)
for c, sc in zip(s["category"], s["sub_category"]): g[c].add(sc)
print({k: sorted(v) for k, v in g.items()})
print({v: k for k, v in {"a": 1, "b": 2}.items()})
orders = [("C1", 100), ("C2", 50), ("C1", 25)]
t = defaultdict(int)
for cid, amt in orders: t[cid] += amt
print(dict(t), {"x": 1} | {"x": 9, "y": 2})
```

INTERVIEW CORNER

### Questions you may be asked

**Q: How does a dictionary achieve O(1) lookup?** It hashes the key to find a slot in a hash table; collisions are resolved by probing, so the average cost is constant.

**Q: `d[k]` vs `d.get(k)`?** `d[k]` raises KeyError for a missing key; `get` returns None (or a default).

**Q: Are dictionaries ordered?** Yes, they preserve insertion order from Python 3.7 onwards.

**Q: Count word frequencies in a text.** `Counter(text.lower().split()).most_common(10)`.

PYTHON FOR DATA SCIENCE · LESSON 9

# Functions: Reusable Code, Arguments, Scope and Docstrings

Package logic into reusable functions. Learn def, parameters and arguments (positional, keyword, default, *args, **kwargs), return values, scope, docstrings and type hints, plus testing small functions on real data.


Python class 7 | Python 3.13 | Beginner | 100 min

**By the end of this lesson you can**

- Define and call functions with positional, keyword and default arguments
- Use *args and **kwargs and return multiple values
- Explain local vs global scope and avoid the mutable-default trap
- Write docstrings and type hints that make functions self-explaining
- Build small, testable functions for data cleaning and metrics

## Why functions?

A **function** is a named, reusable block of code. It removes copy-paste, makes code testable, and lets you give a name to an idea ( `clean_phone` , `margin_pct` ).




A function takes inputs (arguments), runs its body, and gives back an output (return value).

Python

```python
def greet(name):
    return f"Hello, {name}!"
print(greet("Asha"), greet("Ravi"))
```

OUTPUT

```
Hello, Asha! Hello, Ravi!
```

## Parameters and arguments

Python

```python
def margin_pct(profit, sales, decimals=1):
    """Profit as a percentage of sales."""
    return round(100 * profit / sales, decimals)

print(margin_pct(25, 200))                    # positional
print(margin_pct(sales=200, profit=25))       # keyword: order does not matter
print(margin_pct(25, 200, decimals=3))        # default overridden
```

OUTPUT

```
12.5
12.5
12.5
```

| Kind | Example | Notes |
|---|---|---|
| Positional | `f(1, 2)` | Matched by order |
| Keyword | `f(b=2, a=1)` | Matched by name; clearer |
| Default | `def f(a, b=10)` | Optional argument; defaults go last |
| `*args` | `def f(*args)` | Extra positional arguments as a tuple |
| `**kwargs` | `def f(**kwargs)` | Extra keyword arguments as a dict |
| Keyword-only | `def f(a, *, b)` | `b` must be named |

Python

```
def total(*nums): return sum(nums)
def describe(**info): return ", ".join(f"{k}={v}" for k, v in info.items())
def report(title, *values, sep=" | ", **opts): return title + ": " + sep.join(map(str,
values)) + f" {opts}"
print(total(1, 2, 3), total(), describe(city="Pune", year=2025))
print(report("Sales", 10, 20, 30, sep=",", currency="INR"))
nums = [4, 5, 6]; opts = {"decimals": 2}
print(total(*nums), margin_pct(7, 30, **opts))      # unpack a list / dict into arguments
```

OUTPUT

```
6 0 city=Pune, year=2025
Sales: 10,20,30 {'currency': 'INR'}
15 23.33
```

## Return values

Python

```
def stats(values):
    n = len(values)
    mean = sum(values) / n
    var = sum((v - mean) ** 2 for v in values) / (n - 1)
    return min(values), max(values), round(mean, 2), round(var ** 0.5, 2)     # a tuple
lo, hi, mean, sd = stats([12, 15, 11, 18, 14])
print(lo, hi, mean, sd)

def say(): print("no return")
print(say())                                  # a function with no return gives None
```

OUTPUT

```
11 18 14.0 2.74
no return
None
```

**TIP** **Return, do not print**

A function that **prints** can only be read by humans. One that **returns** can be tested, combined and reused. Print at the very end, outside the function.

## Scope: local vs global

Python

```
rate = 0.18                       # global
def price_with_gst(price):
    gst = price * rate            # reads the global
    return price + gst            # gst is local: gone after the call
print(price_with_gst(1000))
try: print(gst)
except NameError as e: print("NameError:", e)

counter = 0
def bump():
    global counter                # needed to *rebind* a global (rarely a good idea)
    counter += 1
bump(); bump(); print(counter)
```

OUTPUT

```
1180.0
NameError: name 'gst' is not defined
2
```

Rule of thumb (LEGB): Python looks in **L**ocal, then **E**nclosing, then **G**lobal, then **B**uilt-in scope. Prefer passing values in and returning values out.

## The mutable-default trap

Python

```
def add_item(x, bucket=[]):          # BAD: one list shared by every call
    bucket.append(x); return bucket
print(add_item(1), add_item(2))

def add_item_ok(x, bucket=None):     # GOOD
    if bucket is None: bucket = []
    bucket.append(x); return bucket
print(add_item_ok(1), add_item_ok(2))
```

OUTPUT

```
[1, 2] [1, 2]
[1] [2]
```

Lists, dicts and sets as default values are created **once**, when `def` runs. Use `None` and create the object inside.

## Docstrings and type hints

Python

```
def clean_phone(raw: str, country_code: str = "+91") -> str:
    """Return a phone number as '+91 XXXXX XXXXX', or '' if it is not 10 digits.

    >>> clean_phone("98765-43210")
    '+91 98765 43210'
    """
    digits = "".join(ch for ch in raw if ch.isdigit())[-10:]
    if len(digits) != 10: return ""
    return f"{country_code} {digits[:5]} {digits[5:]}"

print(clean_phone("98765-43210"), repr(clean_phone("12345")), clean_phone("+91 (98765) 43210"))
help(clean_phone)
```

OUTPUT

```
+91 98765 43210 '' +91 98765 43210
Help on function clean_phone in module __main__:

clean_phone(raw: str, country_code: str = '+91') -> str
    Return a phone number as '+91 XXXXX XXXXX', or '' if it is not 10 digits.

    >>> clean_phone("98765-43210")
    '+91 98765 43210'
```

Type hints do not change how the code runs, but editors and tools such as `mypy` use them, and they document intent. Write the docstring first line as a short summary; tools like `help()` and IDE hovers display it.

## Functions are objects

Python

```
def square(x): return x * x
fn = square                                  # assign, store in a list, pass as an
argument
def apply_twice(f, x): return f(f(x))
print(fn(4), apply_twice(square, 3), [f.__name__ for f in (square, len, str)])

def make_multiplier(n):                      # a function that returns a function (a
closure)
    def times(x): return x * n
    return times
double, triple = make_multiplier(2), make_multiplier(3)
print(double(7), triple(7))
```

OUTPUT

```
16 81 ['square', 'len', 'str']
14 21
```

## Functions on real data

Small, pure functions are easy to test and to reuse across `apply`, comprehensions and pipelines.

Python

```
import pandas as pd
s = pd.read_csv("superstore_sales.csv", parse_dates=["order_date"])

def discount_band(d: float) -> str:
    if d == 0: return "none"
    if d ⩽ 0.10: return "low"
    if d ⩽ 0.20: return "medium"
    return "high"

def summarise(df: pd.DataFrame, by: str) -> pd.DataFrame:
    """Sales, profit and margin % per group."""
    g = df.groupby(by).agg(sales=("sales", "sum"), profit=("profit", "sum"), lines=
("sales", "size"))
    g["margin_pct"] = (100 * g.profit / g.sales).round(1)
    return g.round(0).astype({"sales": int, "profit": int})

s["band"] = s["discount"].map(discount_band)
print(summarise(s, "band").sort_values("margin_pct", ascending=False))
print(summarise(s, "region").sort_values("sales", ascending=False))
```

OUTPUT

```
            sales    profit  lines  margin_pct
band
none    123936290  21718963   3480        18.0
low      21864636   1286023    726         6.0
medium   35864461   -588882   1217        -2.0
high     19748182  -4063940    900       -21.0
           sales   profit  lines  margin_pct
region
South   53952768  4702012   1656         9.0
West    51958520  4719833   1614         9.0
North   49018161  4555830   1530         9.0
East    46484119  4374490   1523         9.0
```

The same `summarise` works for any column. That reuse is the point: write once, call with `by="category"`, `by="segment"`, and so on.

## Testing a function

Python

```python
assert margin_pct(25, 200) == 12.5
assert clean_phone("12345") == ""
assert discount_band(0.15) == "medium"
print("all checks passed")
```

OUTPUT

```
all checks passed
```

`assert` is the quickest test. Larger projects use `pytest` (Lesson 14).

# Recursion in one paragraph

A function can call itself; it needs a **base case** that stops the calls.

Python

```python
def factorial(n):
    return 1 if n <= 1 else n * factorial(n - 1)
def fib(n, memo={}):                    # deliberate cache; see the lesson on functools.lru_cache
    if n < 2: return n
    if n not in memo: memo[n] = fib(n - 1) + fib(n - 2)
    return memo[n]
print(factorial(6), [fib(i) for i in range(12)], fib(60))
```

OUTPUT

```
720 [0, 1, 1, 2, 3, 5, 8, 13, 21, 34, 55, 89] 1548008755920
```

Python limits recursion depth (about 1,000 calls), so prefer loops for deep or large problems.

## Common mistakes

| Mistake | Fix |
| --- | --- |
| Forgetting `return` (function gives `None`) | Check the value you expect back |
| Mutable default arguments | Use `None` and create inside |
| Calling `f` instead of `f()` | `f` is the function object; `f()` runs it |
| Modifying a global inside a function without `global` | `UnboundLocalError`; pass and return values instead |
| Function does too many things | One job per function; compose small ones |
| Positional order confusion | Use keyword arguments for clarity |

# Summary

**KEY TAKEAWAYS**

- `def name(params): ... return value` defines a function; no `return` means it returns `None`.
- Arguments can be positional, keyword, default, `*args` (tuple) and `**kwargs` (dict); put defaults last.
- Variables created inside a function are local; read globals freely, but prefer parameters and return values.
- Never use a mutable object as a default; use `None`.
- Docstrings and type hints document intent; `assert` gives quick tests.
- Functions are objects: you can pass them around, store them and return them (closures).

## Quick quiz

6 questions · tap an answer to check it

**1. What does a function without a `return` statement return?**

A 0

B None

C An empty string

D An error

**Answer: B.** Python returns `None` implicitly.

**2. What is wrong with `def f(x, items=[]):` ?**

- **A** Nothing
- **B** The default list is created once and shared across calls
- **C** Lists cannot be arguments
- **D** It must be a tuple

**Answer: B.** Use `items=None` and create the list inside.

**3. What does `*args` collect?**

- **A** Keyword arguments in a dict
- **B** Extra positional arguments in a tuple
- **C** Only the first argument
- **D** Nothing

**Answer: B.** `**kwargs` collects the keyword ones.

**4. Which scope does Python search first?**

- **A** Global
- **B** Built-in
- **C** Local
- **D** Enclosing only

**Answer: C.** LEGB: Local, Enclosing, Global, Built-in.

**5.** How do you call `f(a, b)` with a list `pair = [1, 2]`?

A `f(pair)`

B `f(*pair)`

C `f(**pair)`

D `f[pair]`

**Answer: B.** `*` unpacks the list into positional arguments.

**6.** Why return values instead of printing them?

A Printing is slower

B Returned values can be tested, reused and combined

C Print is not allowed in functions

D Python requires it

**Answer: B.** Printing is for the final display only.

EXERCISE

### Function problems

(1) Write `is_prime(n)`. (2) Write `percent_change(old, new)` returning a rounded percentage and guard against `old == 0`. (3) Write `top_n(df, col, n=5)` that returns the top-n Superstore rows by a column. (4) Write a function that accepts any number of numbers and returns their average, or `None` if none are given. (5) Add `assert` tests for each.

**Show solution (worked answer)**

Python

```
def is_prime(n):
    return n > 1 and all(n % d for d in range(2, int(n ** 0.5) + 1))
def percent_change(old, new): return None if old == 0 else round(100 * (new - old) /
old, 1)
def top_n(df, col, n=5): return df.nlargest(n, col)
def average(*nums): return sum(nums) / len(nums) if nums else None
assert [x for x in range(20) if is_prime(x)] == [2, 3, 5, 7, 11, 13, 17, 19]
assert percent_change(0, 5) is None and percent_change(200, 250) == 25.0
assert average() is None and average(2, 4) == 3
print(top_n(s, "sales", 3)[["order_id", "sales"]])
```

INTERVIEW CORNER

### Questions you may be asked

**Q: Difference between an argument and a parameter?** Parameters are the names in the `def`; arguments are the values you pass when calling.

**Q: What are `*args` and `**kwargs`?** They let a function accept any number of extra positional and keyword arguments; the first arrives as a tuple, the second as a dict.

**Q: What is a closure?** A function that remembers variables from the scope in which it was created, even after that scope has finished.

**Q: Why is a mutable default argument dangerous?** It is evaluated once at definition time, so state leaks between calls.

PYTHON FOR DATA SCIENCE · LESSON 10

# Comprehensions, Lambda, map/filter and Generators

Write compact, readable Python. Learn list, set and dict comprehensions, lambda with sorted/min/max, map and filter, any and all, generators and itertools, and when plain loops or pandas are the better choice.


Python class 8 | Python 3.13 | Beginner | 100 min

**By the end of this lesson you can**

- Write list, set and dictionary comprehensions with conditions and nesting
- Use lambda functions with sorted, min, max, map and filter
- Use any, all, zip, enumerate and sum with generator expressions
- Explain lazy evaluation and write generator functions with yield
- Use itertools and functools for common patterns and know when not to be clever

## List comprehensions

A **comprehension** builds a collection from another in one expression: `[expression for item in iterable if condition]`.




A comprehension reads like the sentence "give me X for each item, if the condition holds".

Python

```
nums = [1, 2, 3, 4, 5, 6]
squares = [n * n for n in nums]
evens = [n for n in nums if n % 2 == 0]
labels = ["even" if n % 2 == 0 else "odd" for n in nums]          # if/else goes BEFORE the
for
loop_version = []
for n in nums:
    if n % 2 == 0: loop_version.append(n * n)
print(squares, evens, labels, [n * n for n in nums if n % 2 == 0] == loop_version)
```

OUTPUT

```
[1, 4, 9, 16, 25, 36] [2, 4, 6] ['odd', 'even', 'odd', 'even', 'odd', 'even'] True
```

Python

```
words = ["  Pune ", "delhi", " KOCHI", "goa  "]
print([w.strip().title() for w in words])
print([(x, y) for x in (1, 2) for y in ("a", "b")])            # two loops
matrix = [[1, 2, 3], [4, 5, 6]]
print([v for row in matrix for v in row], [list(col) for col in zip(*matrix)])    #
flatten, transpose
```

OUTPUT

```
['Pune', 'Delhi', 'Kochi', 'Goa']
[(1, 'a'), (1, 'b'), (2, 'a'), (2, 'b')]
[1, 2, 3, 4, 5, 6] [[1, 4], [2, 5], [3, 6]]
```

## Set and dictionary comprehensions

Python

```
print({len(w) for w in ["tea", "cup", "mug", "plate"]})                              # set
prices = {"Pen": 10, "Notebook": 45, "Stapler": 180}
print({k: round(v * 1.18, 2) for k, v in prices.items()})
# dict
print({k: v for k, v in prices.items() if v > 20}, {c: ord(c) for c in "abc"})
```

OUTPUT

```
{3, 5}
{'Pen': 11.8, 'Notebook': 53.1, 'Stapler': 212.4}
{'Notebook': 45, 'Stapler': 180} {'a': 97, 'b': 98, 'c': 99}
```

**TIP** **Keep it readable**

If a comprehension needs more than one condition or nested level, or does not fit comfortably on one or two lines, use a normal loop or a helper function. Clever is not the goal; clear is.

## Lambda functions

A **lambda** is a small anonymous function: `lambda args: expression`.

Python

```
sq = lambda x: x * x                          # fine to learn with, but def is better for named functions
print(sq(5), (lambda a, b: a + b)(2, 3))
people = [("Asha", 29, 62000), ("Ravi", 35, 88000), ("Meera", 31, 75000)]
print(sorted(people, key=lambda p: p[2], reverse=True))        # sort by salary
print(min(people, key=lambda p: p[1]), max(people, key=lambda p: p[2])[0])
print(sorted(["banana", "kiwi", "apple", "fig"], key=lambda w: (len(w), w)))    # sort by length, then alphabet
```

OUTPUT

```
25 5
[('Ravi', 35, 88000), ('Meera', 31, 75000), ('Asha', 29, 62000)]
('Asha', 29, 62000) Ravi
['fig', 'kiwi', 'apple', 'banana']
```

Lambdas shine as the `key=` for `sorted`, `min`, `max`, and in `df.apply`.

## map, filter, any, all

Python

```
nums = [3, 8, 12, 5, 20]
print(list(map(lambda x: x * 2, nums)), list(map(str, nums)), list(filter(lambda x: x > 6, nums)))
print([x * 2 for x in nums], [x for x in nums if x > 6])        # comprehensions say the same thing
print(any(n > 15 for n in nums), all(n > 0 for n in nums), sum(1 for n in nums if n % 2 == 0))
print(list(zip(["a", "b", "c"], [1, 2, 3])), dict(zip("abc", range(3))), list(enumerate("xyz", 1)))
```

OUTPUT

```
[6, 16, 24, 10, 40] ['3', '8', '12', '5', '20'] [8, 12, 20]
[6, 16, 24, 10, 40] [8, 12, 20]
True True 3
[('a', 1), ('b', 2), ('c', 3)] {'a': 0, 'b': 1, 'c': 2} [(1, 'x'), (2, 'y'), (3,
'z')]
```

`map` and `filter` return lazy iterators; wrap with `list(...)`. Most Python programmers prefer comprehensions, but you will see both.

## Generators: lazy sequences

A **generator expression** uses parentheses and produces items one at a time, without building the whole list in memory.

Python

```python
import sys
big_list = [n * n for n in range(1_000_000)]
big_gen = (n * n for n in range(1_000_000))
print(sys.getsizeof(big_list) // 1000, "KB list vs", sys.getsizeof(big_gen), "bytes
generator")
print(sum(n * n for n in range(1_000_000)), next(iter(big_gen)), next(big_gen))
```

OUTPUT

```
8448 KB list vs 200 bytes generator
333332833333500000 0 1
```

A **generator function** uses `yield`. It pauses at each `yield` and resumes on the next request:

Python

```
def countdown(n):
    while n > 0:
        yield n
        n -= 1
print(list(countdown(5)))
def read_in_batches(items, size):
    for i in range(0, len(items), size):
        yield items[i:i + size]
for batch in read_in_batches(list(range(10)), 4): print(batch)
def fib():
    a, b = 0, 1
    while True:                  # infinite sequence, safe because it is lazy
        yield a
        a, b = b, a + b
import itertools
print(list(itertools.islice(fib(), 12)))
```

OUTPUT

```
[5, 4, 3, 2, 1]
[0, 1, 2, 3]
[4, 5, 6, 7]
[8, 9]
[0, 1, 1, 2, 3, 5, 8, 13, 21, 34, 55, 89]
```

Generators are how Python reads large files line by line, streams API pages and chains pipeline steps with constant memory. Once consumed, a generator is empty:

Python

```
g = (x for x in range(3))
print(list(g), list(g))
```

OUTPUT

```
[0, 1, 2] []
```

## itertools and functools highlights

Python

```
import itertools, functools, operator
from collections import Counter
print(list(itertools.chain([1, 2], [3], [4, 5])), list(itertools.combinations("ABC", 2)),
list(itertools.product("AB", [0, 1])))
print(list(itertools.accumulate([10, 20, 5, 15])), functools.reduce(operator.mul, [1, 2, 3,
4, 5]))
for key, grp in itertools.groupby(sorted(["ant", "bee", "ape", "bat"]), key=lambda w:
w[0]): print(key, list(grp))
@functools.lru_cache(maxsize=None)              # memoise a function: remember results of
earlier calls
def slow_square(n): return n * n
print([slow_square(n) for n in (4, 4, 5, 4)], slow_square.cache_info())
```

OUTPUT

```
[1, 2, 3, 4, 5] [('A', 'B'), ('A', 'C'), ('B', 'C')] [('A', 0), ('A', 1), ('B', 0),
('B', 1)]
[10, 30, 35, 50] 120
a ['ant', 'ape']
b ['bat', 'bee']
[16, 16, 25, 16] CacheInfo(hits=2, misses=2, maxsize=None, currsize=2)
```

## Real data examples

Python

```
import pandas as pd
s = pd.read_csv("superstore_sales.csv", parse_dates=["order_date"])
regions = sorted(s["region"].unique())
print({r: round(float(s.loc[s.region == r, "sales"].sum()) / 1e6, 1) for r in regions})
# dict comprehension
top_customers = [c for c, n in s["customer_id"].value_counts().items() if n >= 18][:5]
print(top_customers, len([c for c, n in s["customer_id"].value_counts().items() if n >=
18]))
rows = s.head(4)[["order_id", "sales", "profit"]].to_dict("records")
print([{**r, "margin": round(100 * r["profit"] / r["sales"], 1)} for r in rows])
# enrich records
print(sorted(s["category"].unique(), key=lambda c: -s.loc[s.category == c, "sales"].sum()))
# sort by a computed key
```

OUTPUT

```
{'East': 46.5, 'North': 49.0, 'South': 54.0, 'West': 52.0}
['C0719', 'C0149', 'C0126', 'C0384', 'C0257'] 21
```

```
[{'order_id': 'IN-2023-00001', 'sales': 36000.0, 'profit': 3472.55, 'margin': 9.6},
{'order_id': 'IN-2023-00001', 'sales': 3850.0, 'profit': 1169.54, 'margin': 30.4},
{'order_id': 'IN-2023-00001', 'sales': 62080.0, 'profit': 6044.47, 'margin': 9.7},
{'order_id': 'IN-2023-00002', 'sales': 5216.0, 'profit': 450.16, 'margin': 8.6}]
['Technology', 'Furniture', 'Office Supplies']
```

## Which tool when?

| Situation | Prefer |
|---|---|
| Transform or filter a small list | List comprehension |
| Sort by a rule | `sorted(..., key=lambda ...)` |
| Huge or streaming data | Generator (expression or function) |
| Table columns | Vectorised pandas ( `df["a"] * 2` , `np.where` ), not comprehensions |
| Multi-step logic with side effects | Plain `for` loop |
| Reuse the same transformation | Named `def` function |

## Summary

**KEY TAKEAWAYS**

- `[expr for x in it if cond]` builds a list; `{…}` builds sets and dicts; the conditional expression ( `a if c else b` ) comes before `for` .
- `lambda` is an anonymous one-expression function, mostly used as `key=` and in `apply` .
- `map` / `filter` are lazy; comprehensions are usually clearer. `any` , `all` , `sum` work well with generator expressions.
- Generators ( `( … )` or `yield` ) produce values lazily, use almost no memory and can be infinite; they can be consumed only once.
- `itertools` and `functools` ( `chain` , `combinations` , `groupby` , `lru_cache` , `reduce` ) cover many patterns; keep code readable and vectorise table work.

### Quick quiz

6 questions · tap an answer to check it

**1.** What does `[x * 2 for x in range(4) if x != 2]` give?

**A** [0, 2, 4, 6]

**B** [0, 2, 6]

**C** [0, 4, 6]

**D** [2, 6]

**Answer: B.** Item 2 is filtered out before doubling.

**2.** Where does an `if ... else` go in a comprehension?

**A** After the for

**B** Before the for, as part of the expression

**C** It is not allowed

**D** At the end

**Answer: B.** `[a if cond else b for x in it]`.

**3.** What is the main advantage of a generator expression over a list comprehension?

**A** It is faster to type

**B** It is lazy and uses very little memory

**C** It supports indexing

**D** It can be reused

**Answer: B.** Values are produced one at a time.

**4.** What does `sorted(people, key=lambda p: p[2])` do?

- **A** Sorts by the first item
- **B** Sorts by the third item of each tuple
- **C** Reverses the list
- **D** Raises an error

**Answer: B.** `key` supplies the sort value.

**5.** What happens when you iterate a generator twice?

- **A** It restarts
- **B** The second pass is empty because it was consumed
- **C** It raises an error
- **D** It doubles the values

**Answer: B.** Create a new generator or use a list.

**6.** Which is usually best for adding a column to a DataFrame?

- **A** A for loop over rows
- **B** A vectorised column operation
- **C** A generator
- **D** A lambda inside a nested loop

**Answer: B.** Vectorised code is shorter and much faster.

EXERCISE

### Comprehension problems

(1) List the squares of odd numbers from 1 to 20. (2) Build a dictionary from words to their lengths for words longer than 3 letters. (3) Flatten `[[1,2],[3],[4,5,6]]`. (4) Sort `["pune","Delhi","goa","Kochi"]` case-insensitively. (5) Write a generator that yields only the primes below 50. (6) From the Superstore data, list sub-categories with total profit below zero.

**Show solution (worked answer)**

Python

```
print([n * n for n in range(1, 21) if n % 2])
print({w: len(w) for w in ["tea", "plate", "mug", "bottle"] if len(w) > 3})
print([v for part in [[1, 2], [3], [4, 5, 6]] for v in part])
print(sorted(["pune", "Delhi", "goa", "Kochi"], key=str.lower))
def primes(limit):
    for n in range(2, limit):
        if all(n % d for d in range(2, int(n ** 0.5) + 1)): yield n
print(list(primes(50)))
loss = s.groupby("sub_category")["profit"].sum()
print(list(loss[loss < 0].index))
```

INTERVIEW CORNER

### Questions you may be asked

**Q: List comprehension vs generator expression?** Both iterate with the same syntax; the list builds everything now in memory, the generator yields lazily and is single-use.

**Q: When should you avoid a comprehension?** When logic needs several statements, side effects, or deep nesting; readability matters more than brevity.

**Q: What does `yield` do?** It turns a function into a generator: the function pauses, hands back a value, and resumes where it left off on the next call.

**Q: How do you flatten a list of lists?** `[x for sub in lists for x in sub]` or `itertools.chain.from_iterable(lists)`.

PYTHON FOR DATA SCIENCE · LESSON 11

# Object-Oriented Python: Classes, Objects, Inheritance and Dataclasses

Model real things as objects. Learn classes, **init**, attributes and methods, encapsulation, inheritance, polymorphism, special (dunder) methods, class and static methods, properties and dataclasses, with a small data-pipeline example.


Python class 9 | Python 3.13 | Intermediate | 110 min

**By the end of this lesson you can**

- Define classes with attributes and methods and create objects
- Use inheritance, super() and polymorphism to share and customise behaviour
- Implement **str**, **repr**, **eq** and **len** to make objects behave like built-ins
- Use @property, @classmethod and @staticmethod appropriately
- Choose between a plain class, a dataclass and a dictionary

## Why classes?

A **class** bundles **data** (attributes) and **behaviour** (methods) into one unit. An **object** is one instance of a class. Libraries you already use are classes: a pandas `DataFrame` has data (rows) and methods (`.groupby()`).




A class is the blueprint; objects are the things built from it, each with its own data.

Python

```python
class Account:
    bank = "SkillBank"                      # class attribute: shared by all objects

    def __init__(self, owner, balance=0):    # constructor: runs when you create an object
        self.owner = owner                    # instance attributes: belong to this object
        self.balance = balance

    def deposit(self, amount):
        if amount ⩽ 0: raise ValueError("amount must be positive")
        self.balance += amount
        return self.balance

    def withdraw(self, amount):
        if amount > self.balance: raise ValueError("insufficient funds")
        self.balance -= amount
        return self.balance

a, b = Account("Asha", 500), Account("Ravi", 900)
a.deposit(250); b.withdraw(100)
print(a.owner, a.balance, b.owner, b.balance, Account.bank, a.bank)
try: a.withdraw(5000)
except ValueError as e: print("Error:", e)
```

OUTPUT

```
Asha 750 Ravi 800 SkillBank SkillBank
Error: insufficient funds
```

`self` is the object the method was called on. Python passes it automatically: `a.deposit(250)` is `Account.deposit(a, 250)`.

## Special (dunder) methods

Methods with double underscores customise how objects behave with `print`, `==`, `len`, `+` and more.

Python

```
class Account:
    def __init__(self, owner, balance=0): self.owner, self.balance = owner, balance
    def __repr__(self): return f"Account({self.owner!r}, {self.balance})"      # for
developers
    def __str__(self): return f"{self.owner}: ₹{self.balance:,}"               # for
print()
    def __eq__(self, other): return (self.owner, self.balance) == (other.owner,
other.balance)
    def __lt__(self, other): return self.balance < other.balance               # enables
sorting
    def __add__(self, other): return Account(self.owner + "&" + other.owner, self.balance +
other.balance)

x, y = Account("Asha", 5000), Account("Ravi", 9000)
print(x, "|", repr(x), "|", x == Account("Asha", 5000), "|", sorted([y, x]), "|", x + y)
```

OUTPUT

```
Asha: ₹5,000 | Account('Asha', 5000) | True | [Account('Asha', 5000), Account('Ravi',
9000)] | Asha&Ravi: ₹14,000
```

| Method | Used by |
|---|---|
| `__init__` | Creating the object |
| `__repr__` , `__str__` | `repr()` , `print()` |
| `__eq__` , `__lt__` | `==` , `<` , sorting |
| `__len__` , `__getitem__` | `len(obj)` , `obj[i]` |
| `__iter__` , `__next__` | `for` loops |
| `__enter__` , `__exit__` | `with` blocks |
| `__call__` | Calling the object like a function |

## Encapsulation and properties

Python has no strict private members; a leading underscore ( `_balance` ) means "internal, please do not touch". A **property** exposes an attribute while keeping control over it.

Python


```python
class Temperature:
    def __init__(self, celsius): self._c = celsius
    @property
    def celsius(self): return self._c
    @celsius.setter
    def celsius(self, v):
        if v < -273.15: raise ValueError("below absolute zero")
        self._c = v
    @property
    def fahrenheit(self): return self._c * 9 / 5 + 32          # computed, read-only
t = Temperature(25)
t.celsius = 30
print(t.celsius, t.fahrenheit)
try: t.celsius = -500
except ValueError as e: print("Error:", e)
```

OUTPUT

```
30 86.0
Error: below absolute zero
```

## Inheritance and polymorphism

A **child** class reuses a **parent** and adds or overrides behaviour. `super()` calls the parent's version.




Savings and Current accounts inherit everything from Account and add their own rules.

Python

```python
class Account:
    def __init__(self, owner, balance=0): self.owner, self.balance = owner, balance
    def withdraw(self, amount):
        if amount > self.limit(): raise ValueError("limit exceeded")
        self.balance -= amount
    def limit(self): return self.balance
    def __str__(self): return f"{type(self).__name__}({self.owner}, {self.balance})"

class Savings(Account):
    def __init__(self, owner, balance=0, rate=0.04):
        super().__init__(owner, balance)            # reuse the parent's setup
        self.rate = rate
    def interest(self): return round(self.balance * self.rate, 2)

class Current(Account):
    def __init__(self, owner, balance=0, overdraft=10000):
        super().__init__(owner, balance); self.overdraft = overdraft
    def limit(self): return self.balance + self.overdraft          # override

accounts = [Savings("Asha", 50000), Current("Ravi", 2000)]
for acc in accounts:                                                # polymorphism: same
call, different behaviour
    acc.withdraw(5000)
    print(acc, "| limit now", acc.limit())
print(accounts[0].interest(), isinstance(accounts[0], Account), issubclass(Current,
Account), [c.__name__ for c in Current.__mro__])
```

OUTPUT

```
Savings(Asha, 45000) | limit now 45000
Current(Ravi, -3000) | limit now 7000
1800.0 True True ['Current', 'Account', 'object']
```

**Polymorphism** means different classes respond to the same method name in their own way, so code like the loop above works with any account type.

NOTE

### Composition often beats inheritance

"Is-a" relationships (a Savings **is an** Account) suit inheritance. "Has-a" relationships (a Pipeline **has** steps) suit composition: store other objects as attributes. Prefer composition when in doubt.

## Class and static methods

Python

```
class Order:
    GST = 0.18
    def __init__(self, amount): self.amount = amount
    @classmethod
    def from_string(cls, text):                    # alternative constructor: "₹1,200"
        return cls(float(text.replace("₹", "").replace(",", "")))
    @staticmethod
    def is_valid(amount): return amount > 0        # no self/cls: just a function in the
class namespace
    def total(self): return round(self.amount * (1 + self.GST), 2)
o = Order.from_string("₹1,200")
print(o.amount, o.total(), Order.is_valid(-5))
```

OUTPUT

```
1200.0 1416.0 False
```

## Dataclasses: classes for data

For classes that mainly store data, `@dataclass` generates `__init__`, `__repr__` and `__eq__` for you.

Python

```
from dataclasses import dataclass, field, asdict

@dataclass(order=True)
class Employee:
    name: str
    dept: str
    salary: float = 0.0
    skills: list = field(default_factory=list)       # mutable default done safely
    def raise_salary(self, pct): self.salary = round(self.salary * (1 + pct / 100), 2)

staff = [Employee("Kavya", "HR", 97000, ["Excel"]), Employee("Rohan", "IT", 120000),
Employee("Asha", "HR", 88000)]
staff[0].raise_salary(10)
print(staff[0], "|", staff[0] == Employee("Kavya", "HR", 106700.0, ["Excel"]), "|",
max(staff, key=lambda e: e.salary).name)
print(asdict(staff[1]), sorted(staff)[0].name)
import pandas as pd
print(pd.DataFrame([asdict(e) for e in staff]).groupby("dept")["salary"].mean())
```

OUTPUT

```
Employee(name='Kavya', dept='HR', salary=106700.0, skills=['Excel']) | True | Rohan
{'name': 'Rohan', 'dept': 'IT', 'salary': 120000, 'skills': []} Asha
dept
HR     97350.0
IT    120000.0
Name: salary, dtype: float64
```

## A small data-pipeline class

Python

```python
import pandas as pd

class CleaningPipeline:
    """Holds a list of cleaning steps and applies them in order."""
    def __init__(self): self.steps = []
    def add(self, name, func): self.steps.append((name, func)); return self      # return
self allows chaining
    def run(self, df):
        for name, func in self.steps:
            before = len(df); df = func(df)
            print(f"  {name:<18} rows {before} → {len(df)}")
        return df

raw = pd.DataFrame({"city": [" Pune", "pune ", "Delhi", None, "Delhi"], "sales": [100, 100,
250, 80, -5]})
pipe = (CleaningPipeline()
        .add("drop missing city", lambda d: d.dropna(subset=["city"]))
        .add("tidy text", lambda d: d.assign(city=d.city.str.strip().str.title()))
        .add("remove negatives", lambda d: d[d.sales ⩾ 0])
        .add("drop duplicates", lambda d: d.drop_duplicates()))
print(pipe.run(raw))
```

OUTPUT

```
  drop missing city  rows 5 → 4
  tidy text          rows 4 → 4
  remove negatives   rows 4 → 3
  drop duplicates    rows 3 → 2
    city  sales
0   Pune    100
2  Delhi    250
```

This is the idea behind scikit-learn pipelines (ML track): objects with `fit` / `transform` methods that you chain.

## When to use what

| Need | Use |
| --- | --- |
| A few related values | Tuple / dict |
| Record with named fields, no logic | `@dataclass` or namedtuple |
| Data plus behaviour, state that changes | Class |
| Share behaviour across related types | Inheritance (or composition) |
| One function | Just a function |

## Common mistakes

| Mistake | Fix |
| --- | --- |
| Forgetting `self` in the method signature | `def method(self, ...)` |
| Forgetting `self.` when reading an attribute | `self.balance`, not `balance` |
| Mutable class attribute shared by all objects (`items = []`) | Create it in `__init__` |
| Overusing inheritance | Prefer composition and small functions |
| Missing `super().__init__()` in the child | Call it to initialise parent state |
| Comparing objects without `__eq__` | Compares identity, not content; use a dataclass |

# Summary

**KEY TAKEAWAYS**

- A class is a blueprint; `__init__` sets up each object; `self` refers to the current object.
- Dunder methods ( `__str__` , `__repr__` , `__eq__` , `__lt__` , `__len__` ) make objects behave like built-ins.
- Inheritance reuses and overrides parent behaviour with `super()` ; polymorphism lets one call work across types.
- `@property` guards attributes; `@classmethod` builds alternative constructors; `@staticmethod` groups helpers.
- `@dataclass` removes boilerplate for data holders. Prefer composition over deep inheritance.

## Quick quiz

6 questions · tap an answer to check it

**1. What does `self` refer to?**

A The class

B The specific object the method is called on

C The module

D The parent class

**Answer: B.** Python passes the instance automatically.

**2.** Which method runs when you create an object?

A `__str__`

B `__init__`

C `__new__` only

D `__call__`

**Answer: B.** `__init__` initialises the new instance.

**3.** What does `super().__init__(owner, balance)` do in a child class?

A Deletes the parent

B Runs the parent's constructor to set up inherited attributes

C Creates a new class

D Nothing

**Answer: B.** It reuses the parent's initialisation.

**4.** Which decorator gives a read-only computed attribute?

A `@staticmethod`

B `@property`

C `@classmethod`

D `@cache`

**Answer: B.** Access without parentheses.

**5. What does `@dataclass` generate automatically?**

A Only `__str__`

B `__init__` , `__repr__` and `__eq__`

C A database table

D Nothing

**Answer: B.** It removes boilerplate for data holders.

**6. What is polymorphism?**

A Having many parents

B Different classes responding to the same method name in their own way

C Copying a class

D Hiding attributes

**Answer: B.** The loop `for acc in accounts: acc.withdraw()` works for any account type.

EXERCISE

## OOP problems

(1) Create a `Rectangle` class with `area()` and `perimeter()`, and a `Square` subclass. (2) Add `__str__` and `__eq__` to a `Point(x, y)` class. (3) Build a `Stack` class (push, pop, peek, `__len__`). (4) Make a dataclass `Product` with price and `with_gst()`, then sort a list of products by price. (5) Write a `Counter`-like class that counts calls using a class attribute.

### Show solution (worked answer)

Python

```
class Rectangle:
    def __init__(self, w, h): self.w, self.h = w, h
    def area(self): return self.w * self.h
    def perimeter(self): return 2 * (self.w + self.h)
class Square(Rectangle):
    def __init__(self, side): super().__init__(side, side)
print(Rectangle(3, 4).area(), Square(5).perimeter())
class Point:
    def __init__(self, x, y): self.x, self.y = x, y
    def __str__(self): return f"({self.x}, {self.y})"
    def __eq__(self, o): return (self.x, self.y) == (o.x, o.y)
print(Point(1, 2), Point(1, 2) == Point(1, 2))
class Stack:
    def __init__(self): self._d = []
    def push(self, x): self._d.append(x)
    def pop(self): return self._d.pop()
    def peek(self): return self._d[-1]
    def __len__(self): return len(self._d)
st = Stack(); st.push(1); st.push(2); print(st.pop(), len(st))
from dataclasses import dataclass
@dataclass(order=True)
class Product:
    price: float
    def with_gst(self): return round(self.price * 1.18, 2)
print(sorted([Product(500), Product(120)]), Product(100).with_gst())
```

INTERVIEW CORNER

### Questions you may be asked

**Q: Class attribute vs instance attribute?** A class attribute is shared by all instances (defined in the class body); an instance attribute belongs to one object (set in `__init__`).

**Q: What is the difference between `__str__` and `__repr__`?** `__str__` is the readable form for users (`print`); `__repr__` is the unambiguous form for developers, ideally something that could recreate the object.

**Q: Explain the four OOP pillars.** Encapsulation (bundle and protect data), inheritance (reuse), polymorphism (same interface, different behaviour), abstraction (expose what, hide how).

**Q: Inheritance or composition?** Use inheritance for a true is-a relationship; use composition (objects holding other objects) for flexibility and lower coupling.

PYTHON FOR DATA SCIENCE · LESSON 12

# Files, Exceptions, JSON and CSV

Read and write text, CSV and JSON files safely with pathlib and with-blocks, handle errors with try/except/else/finally, raise your own exceptions, and log what happened, using a small "load a messy file" project.

Python class 10 | Python 3.13 | Intermediate | 110 min

**By the end of this lesson you can**

- Open, read and write text files with with-blocks and pathlib
- Read and write CSV with the csv module and JSON with the json module
- Handle errors with try, except, else and finally, and catch specific exceptions
- Raise exceptions and define custom exception classes
- Use logging instead of print for programs that run unattended

## Files and paths

Use `pathlib.Path` for paths (works on Windows, macOS and Linux) and a `with` block to open files: the file is closed automatically, even if an error happens.

Python

```
from pathlib import Path
folder = Path("demo_files"); folder.mkdir(exist_ok=True)
notes = folder / "notes.txt"                                  # / joins path parts
with open(notes, "w", encoding="utf-8") as f:                  # "w" overwrites, "a" appends,
"r" reads (default)
    f.write("Line one\n")
    f.writelines(["Line two\n", "Line three\n"])
with open(notes, "a", encoding="utf-8") as f: print("Line four", file=f)
print(notes.read_text(encoding="utf-8"))
print(notes.exists(), notes.name, notes.stem, notes.suffix, notes.stat().st_size, "bytes")
```

OUTPUT

```
Line one
Line two
Line three
Line four
```

```
True notes.txt notes .txt 39 bytes
```

Python

```python
with open(notes, encoding="utf-8") as f:
    for i, line in enumerate(f, 1):                # iterate line by line: constant memory for huge files
        print(i, line.rstrip("\n"))
with open(notes, encoding="utf-8") as f: lines = f.read().splitlines()
print(lines, sorted(p.name for p in folder.glob("*.txt")))
```

OUTPUT

```
1 Line one
2 Line two
3 Line three
4 Line four
['Line one', 'Line two', 'Line three', 'Line four'] ['notes.txt']
```

| Mode | Meaning |
|---|---|
| `"r"` | Read (error if missing) |
| `"w"` | Write (creates or **overwrites**) |
| `"a"` | Append to the end |
| `"x"` | Create; error if it exists |
| `"b"` suffix | Binary ( `"rb"` , `"wb"` ) for images, Excel, Parquet |

> **TIP** **Always give the encoding**
>
> `encoding="utf-8"` avoids garbled ₹, é or Hindi text and avoids differences between Windows and Linux defaults.

## CSV files

The standard `csv` module handles quoting and commas inside values. (For analysis you will usually use `pandas.read_csv` , Lesson 16.)

Python

```
import csv
rows = [{"id": 1, "city": "Pune", "note": "fast, friendly"}, {"id": 2, "city": "Delhi",
"note": 'said "ok"'}]
with open(folder / "people.csv", "w", newline="", encoding="utf-8") as f:
    w = csv.DictWriter(f, fieldnames=["id", "city", "note"])
    w.writeheader(); w.writerows(rows)
print((folder / "people.csv").read_text(encoding="utf-8"))
with open(folder / "people.csv", newline="", encoding="utf-8") as f:
    for r in csv.DictReader(f): print(r)                # every value is a string
```

OUTPUT

```
id,city,note
1,Pune,"fast, friendly"
2,Delhi,"said ""ok"""

{'id': '1', 'city': 'Pune', 'note': 'fast, friendly'}
{'id': '2', 'city': 'Delhi', 'note': 'said "ok"'}
```

Python

```
# Stream a real 6,000-line CSV without pandas: total sales per region
from collections import defaultdict
totals = defaultdict(float)
with open("superstore_sales.csv", newline="", encoding="utf-8") as f:
    for row in csv.DictReader(f): totals[row["region"]] += float(row["sales"])
print({k: round(v / 1e6, 1) for k, v in sorted(totals.items())})
```

OUTPUT

```
{'East': 46.5, 'North': 49.0, 'South': 54.0, 'West': 52.0}
```

## JSON files

JSON maps to Python like this: object ↔ dict, array ↔ list, string ↔ str, number ↔ int/float, true/false ↔ True/False, null ↔ None.

Python

```
import json
config = {"source": "superstore_sales.csv", "regions": ["North", "South"], "min_sales":
1000, "debug": False, "owner": None}
with open(folder / "config.json", "w", encoding="utf-8") as f: json.dump(config, f,
indent=2)
with open(folder / "config.json", encoding="utf-8") as f: loaded = json.load(f)
print(loaded == config, loaded["regions"], json.dumps({"price": 4500.5, "ok": True, "x":
None}))
print(json.dumps({"city": "Pune", "₹": 1}, ensure_ascii=False))
```

OUTPUT

```
True ['North', 'South'] {"price": 4500.5, "ok": true, "x": null}
{"city": "Pune", "₹": 1}
```

`json.dump` / `json.load` work with files; `json.dumps` / `json.loads` work with strings (the "s" is for string). Dates and sets are not JSON types: convert them first ( `d.isoformat()` , `list(s)` ).

## Exceptions

An **exception** is Python's way of reporting an error. Unhandled, it stops the program and prints a traceback. Handled, your program can recover.


Python

```
def safe_ratio(a, b):
    try:
        result = a / b
    except ZeroDivisionError:
        print("  cannot divide by zero")
        return None
    except TypeError as e:
        print("  wrong types:", e)
        return None
    else:                       # runs only when no exception happened
        return round(result, 2)
    finally:                    # always runs: clean-up
        print("  checked", a, b)
print(safe_ratio(10, 4)); print(safe_ratio(1, 0)); print(safe_ratio("10", 2))
```

OUTPUT

```
  checked 10 4
2.5
  cannot divide by zero
  checked 1 0
```

```
None
  wrong types: unsupported operand type(s) for /: 'str' and 'int'
  checked 10 2
None
```




try / except / else / finally: which blocks run.

## Common built-in exceptions

| Exception | Typical cause |
|---|---|
| `ValueError` | Right type, wrong value: `int("abc")` |
| `TypeError` | Wrong type: `"a" + 1` |
| `KeyError` | Missing dict key |
| `IndexError` | List index out of range |
| `FileNotFoundError` | Missing file |
| `ZeroDivisionError` | Divide by zero |
| `AttributeError` | Object has no such attribute or method |
| `ImportError` / `ModuleNotFoundError` | Package not installed |

Python

```python
tests = [lambda: int("abc"), lambda: "a" + 1, lambda: {}["x"], lambda: [1][5], lambda:
open("missing.csv"), lambda: None.upper()]
for t in tests:
    try: t()
    except Exception as e: print(f"{type(e).__name__:<18} {e}")
```

OUTPUT

```
ValueError         invalid literal for int() with base 10: 'abc'
TypeError          can only concatenate str (not "int") to str
```

```
KeyError           'x'
IndexError         list index out of range
FileNotFoundError  [Errno 2] No such file or directory: 'missing.csv'
AttributeError     'NoneType' object has no attribute 'upper'
```

**WATCH OUT** **Do not swallow every error**

`except: pass` or `except Exception: pass` hides bugs. Catch the **specific** exceptions you expect, and let unexpected ones surface (or log them and re-raise).

## Raising your own exceptions

Python

```python
class DataQualityError(Exception):
    """Raised when an input file fails validation."""

def validate(df):
    missing = {"order_id", "sales"} - set(df.columns)
    if missing: raise DataQualityError(f"missing columns: {sorted(missing)}")
    if (df["sales"] < 0).any(): raise ValueError("negative sales found")
    return True

import pandas as pd
for d in (pd.DataFrame({"order_id": [1], "sales": [5]}), pd.DataFrame({"order_id": [1]}),
pd.DataFrame({"order_id": [1], "sales": [-2]})):
    try: print("valid:", validate(d))
    except (DataQualityError, ValueError) as e: print(type(e).__name__, "→", e)
```

OUTPUT

```
valid: True
DataQualityError → missing columns: ['sales']
ValueError → negative sales found
```

Use `raise ... from e` to wrap a low-level error in a clearer one while keeping the original cause.

# Logging

`print` is for interactive work. Programs that run on a schedule (ETL jobs, APIs) should use `logging`, which adds timestamps and levels and can write to files.

Python

```
import logging, io
stream = io.StringIO()
log = logging.getLogger("etl"); log.handlers.clear(); log.setLevel(logging.INFO)
h = logging.StreamHandler(stream); h.setFormatter(logging.Formatter("%(levelname)s | %
(name)s | %(message)s")); log.addHandler(h)
log.debug("not shown: below INFO"); log.info("loaded 6,323 rows"); log.warning("12 rows had
blank city")
try: 1 / 0
except ZeroDivisionError: log.exception("step failed")       # logs the traceback too
print(stream.getvalue().splitlines()[:3])
```

OUTPUT

```
['INFO | etl | loaded 6,323 rows', 'WARNING | etl | 12 rows had blank city', 'ERROR |
etl | step failed']
```

Levels from low to high: `DEBUG`, `INFO`, `WARNING`, `ERROR`, `CRITICAL`.

# Project: load a messy file safely

Python

```
messy = """order_id,amount,city
1,1200,Pune
2,abc,Delhi
3,,Kochi
4,950,
5,-40,Goa
"""
(folder / "messy.csv").write_text(messy, encoding="utf-8")

def load_orders(path):
    good, bad = [], []
    with open(path, newline="", encoding="utf-8") as f:
        for lineno, row in enumerate(csv.DictReader(f), start=2):
            try:
                amount = float(row["amount"])
                if amount < 0: raise ValueError("negative amount")
                if not row["city"]: raise ValueError("blank city")
                good.append({"order_id": int(row["order_id"]), "amount": amount, "city":
row["city"]})
            except ValueError as e:
                bad.append((lineno, str(e)))
    return good, bad

good, bad = load_orders(folder / "messy.csv")
print("good:", good); print("rejected:", bad)
with open(folder / "rejected.json", "w", encoding="utf-8") as f: json.dump(bad, f)
import shutil; shutil.rmtree(folder)                        # tidy up the demo folder
```

OUTPUT

```
good: [{'order_id': 1, 'amount': 1200.0, 'city': 'Pune'}]
rejected: [(3, "could not convert string to float: 'abc'"), (4, "could not convert
string to float: ''"), (5, 'blank city'), (6, 'negative amount')]
```

Real pipelines do exactly this: keep the good rows, quarantine and report the bad ones, never crash on one bad line.

# Summary

**KEY TAKEAWAYS**

- Use `pathlib.Path` and `with open(path, mode, encoding="utf-8")` ; iterate a file line by line for big files.
- `csv.DictReader` / `DictWriter` handle quoting (values are strings); `json.load` / `dump` convert JSON ↔ Python.
- `try` / `except SpecificError` / `else` / `finally` ; never use a bare `except: pass` .
- `raise` your own exceptions (subclass `Exception` ) to signal bad data clearly.
- Use `logging` with levels for unattended programs.

## Quick quiz

6 questions · tap an answer to check it

**1. Why use `with open(...) as f:` ?**

A It is faster

B The file is closed automatically, even if an error occurs

C It reads the whole file

D It is required for CSV

**Answer: B.** The context manager handles clean-up.

**2. What does mode `"w"` do to an existing file?**

A Appends

B Overwrites it

C Raises an error

D Reads it

**Answer: B.** Use `"a"` to append and `"x"` to refuse overwriting.

**3. When does the `else` block of a `try` statement run?**

- **A** Always
- **B** Only if no exception was raised in `try`
- **C** Only after an exception
- **D** Never

**Answer: B.** `finally` is the block that always runs.

**4. What does `json.loads` take?**

- **A** A file
- **B** A string
- **C** A dictionary
- **D** A path

**Answer: B.** `load` takes a file object; `loads` takes a string.

**5. What exception does `int("abc")` raise?**

- **A** TypeError
- **B** ValueError
- **C** KeyError
- **D** SyntaxError

**Answer: B.** The type (str) is acceptable, the value is not.

**6.** Why prefer `logging` over `print` for scheduled jobs?

- **A** It is shorter
- **B** It adds levels and timestamps and can write to files and monitoring tools
- **C** print is deprecated
- **D** logging is faster

**Answer: B.** You can filter by level and keep a history.

EXERCISE **File and error problems**

(1) Write a function that counts lines, words and characters in a text file. (2) Read `superstore_sales.csv` with `csv.DictReader` and count rows per `category`. (3) Save that result as JSON and load it back. (4) Write `to_int(text, default=0)` that returns the default on `ValueError`. (5) Raise a custom `EmptyFileError` when a file has no data rows.

Show solution (worked answer)

Python

```
def wc(path):
    text = Path(path).read_text(encoding="utf-8")
    return len(text.splitlines()), len(text.split()), len(text)
from collections import Counter
with open("superstore_sales.csv", newline="", encoding="utf-8") as f:
    counts = Counter(r["category"] for r in csv.DictReader(f))
Path("cat.json").write_text(json.dumps(counts), encoding="utf-8")
print(json.loads(Path("cat.json").read_text(encoding="utf-8")))
def to_int(text, default=0):
    try: return int(text)
    except ValueError: return default
class EmptyFileError(Exception): pass
def check(path):
    with open(path, encoding="utf-8") as f:
        if len(f.read().splitlines()) < 2: raise EmptyFileError(path)
```

INTERVIEW CORNER

## Questions you may be asked

**Q: How do you read a 10 GB file in Python?** Iterate it line by line ( `for line in f` ), or read in chunks ( `pd.read_csv(..., chunksize=...)` ), so memory stays constant.

**Q: Difference between `except Exception` and a bare `except` ?** A bare `except` also catches `KeyboardInterrupt` and `SystemExit` ; catch specific exceptions where possible.

**Q: What is `finally` used for?** Clean-up that must always happen, such as closing connections or releasing locks.

**Q: How do you handle bad rows in an ETL job?** Validate each row, keep good rows, write rejects with the reason to a quarantine file or table, log counts, and alert if the reject rate is too high.

PYTHON FOR DATA SCIENCE · LESSON 13

# Modules, Packages, Virtual Environments and Git

Organise code into modules and packages, install libraries with pip or uv inside virtual environments, pin dependencies, use the standard library, and version-control your projects with Git and GitHub.

Python class 10 | Python 3.13 · pip 25 · uv · Git 2.5x | Intermediate | 90 min

**By the end of this lesson you can**

- Import modules in the different ways and explain if **name** == "**main**"
- Create a package with **init**.py and a sensible project layout
- Create virtual environments and install and pin packages with pip or uv
- Use key standard-library modules (os, pathlib, datetime, random, math, statistics, collections)
- Use the everyday Git workflow: init, add, commit, branch, push, pull request

## Modules

A **module** is any `.py` file. Importing it gives you its functions, classes and variables.

Python

```
import math                                  # whole module, use with prefix
from statistics import mean, median          # specific names
import datetime as dt                        # alias
from collections import Counter as C
print(math.sqrt(144), math.pi, mean([3, 5, 10]), median([3, 5, 10]), dt.date(2025, 4,
1).strftime("%d %b %Y"), C("aab"))
print(math.ceil(4.2), math.floor(4.8), math.log10(1000), round(math.exp(1), 4),
math.comb(5, 2))
```

OUTPUT

```
12.0 3.141592653589793 6 5 01 Apr 2025 Counter({'a': 2, 'b': 1})
5 4 3.0 2.7183 10
```

| Style | When |
| --- | --- |
| `import pandas as pd` | Standard aliases ( `np` , `pd` , `plt` , `sns` ) |
| `from pathlib import Path` | A few names used often |
| `from module import *` | **Avoid**: hides where names come from |

## Writing your own module

Python

```
from pathlib import Path
Path("metrics.py").write_text('''"""Reusable business metrics."""
GST = 0.18

def margin_pct(profit, sales):
    return round(100 * profit / sales, 1) if sales else None

def with_gst(amount):
    return round(amount * (1 + GST), 2)

if __name__ == "__main__":          # runs only when executed directly, not when imported
    print("self-test:", margin_pct(25, 200))
''', encoding="utf-8")
import importlib, sys
if "" not in sys.path: sys.path.insert(0, "")        # notebooks and scripts already search
the current folder
import metrics
importlib.reload(metrics)
print(metrics.margin_pct(30, 120), metrics.with_gst(1000), metrics.__doc__)
import subprocess, sys
print(subprocess.run([sys.executable, "metrics.py"], capture_output=True,
text=True).stdout.strip())
Path("metrics.py").unlink()
```

OUTPUT

```
25.0 1180.0 Reusable business metrics.
self-test: 12.5
```

`__name__` is `"__main__"` when the file is run as a script and the module name when imported. The guard lets one file be both a library and a script.

## Where does Python look?

The current folder, then the folders in `sys.path` (including `site-packages` , where pip installs libraries). `ModuleNotFoundError` usually means: wrong environment, package not installed, or a

typo. Never name your own file `pandas.py` or `random.py`: it will shadow the real library.

## Packages and project layout

A **package** is a folder of modules (with an `__init__.py`). A clean data project:

Text

```
churn-project/
├── pyproject.toml          # project metadata and dependencies
├── README.md
├── .gitignore              # venv, data, secrets, __pycache__
├── data/                   # raw/ and processed/ (usually not committed)
├── notebooks/              # exploration
├── src/churn/
│   ├── __init__.py
│   ├── load.py             # read and validate data
│   ├── features.py         # feature engineering
│   └── train.py            # model training
└── tests/
    └── test_features.py
```

Import with `from churn.features import add_tenure_band`. Notebooks for exploring; `.py` modules for anything reused or scheduled.

## The standard library tour

Python

```
import os, random, statistics, datetime as dt, itertools, textwrap, uuid, time
random.seed(42)
print(random.randint(1, 6), random.choice(["N", "S", "E"]), random.sample(range(100), 3),
round(random.random(), 3))
print(statistics.stdev([2, 4, 4, 4, 5, 5, 7, 9]), statistics.mode([1, 2, 2, 3]))
today = dt.date(2025, 10, 27); due = today + dt.timedelta(days=45)
print(due, due.strftime("%A"), (dt.date(2026, 1, 1) - today).days, "days to new year")
print(os.cpu_count() > 0, os.getenv("HOME") is not None, textwrap.shorten("A very long
product description here", 20), len(str(uuid.uuid4())))
```

OUTPUT

```
6 N [3, 94, 35] 0.245
2.138089935299395 2
2025-12-11 Thursday 66 days to new year
True True A very long [...] 36
```

| Module | Use |
| --- | --- |
| `pathlib`, `os`, `shutil`, `glob` | Files and folders |
| `datetime`, `zoneinfo`, `time` | Dates, time zones, timing |
| `math`, `statistics`, `random`, `decimal` | Numbers (`decimal` for money) |
| `collections`, `itertools`, `functools` | Data structures and iteration helpers |
| `csv`, `json`, `sqlite3`, `pickle` | Data formats and storage |
| `re` | Regular expressions |
| `logging`, `argparse`, `subprocess` | Scripts and tools |
| `urllib`, `http` | Web (most people use `requests` / `httpx`) |
| `concurrent.futures`, `asyncio` | Parallel and asynchronous work |

## pip, virtual environments and uv


Each project should have its **own virtual environment** so its library versions do not clash with other projects.

Text

```
# Create and activate an environment (built-in venv)
python -m venv .venv
source .venv/bin/activate          # macOS/Linux
.venv\Scripts\activate             # Windows

# Install, list, pin, reproduce
pip install pandas scikit-learn matplotlib
pip list
pip freeze > requirements.txt
pip install -r requirements.txt

# uv: a much faster modern alternative (by Astral)
uv init churn-project && cd churn-project
uv add pandas scikit-learn
uv run python src/churn/train.py
```





The project isolation model: each project gets its own environment and its own library versions.

**TIP** **Conda, Anaconda, Colab**

**Anaconda/Miniconda** bundle Python with data libraries and the `conda` environment manager; popular in data science courses. **Google Colab** and **Kaggle Notebooks** run Python in the browser with libraries pre-installed: ideal for practice. Pick one tool per project and stick to it.

## Git and GitHub essentials

**Git** tracks changes to files; **GitHub** hosts repositories online for backup, collaboration and your portfolio.




The everyday Git cycle.

```Text
git init                              # start tracking a folder
git status                            # what changed?
git add analysis.py                   # stage a file  (git add . = everything)
git commit -m "Add churn EDA"         # save a snapshot with a message
git log --oneline                     # history
git switch -c feature/rfm             # new branch
git push -u origin feature/rfm        # upload the branch to GitHub
git pull                              # download others' changes
git clone https://github.com/user/repo.git
git diff                              # unstaged changes
git restore file.py                   # discard local changes to a file
```

A `.gitignore` keeps junk and secrets out:

```Text
.venv/
__pycache__/
.ipynb_checkpoints/
data/raw/
*.env
.DS_Store
```

**WATCH OUT** **Never commit secrets**

API keys, passwords and tokens belong in environment variables or a `.env` file listed in `.gitignore`. Read them with `os.getenv("OPENAI_API_KEY")`. If a key is ever pushed, revoke it immediately: deleting the commit is not enough.

# Summary

**KEY TAKEAWAYS**

- A module is a `.py` file; a package is a folder of modules. Use standard aliases and avoid `import *`.
- `if __name__ == "__main__":` separates script code from importable code.
- One virtual environment per project; pin versions in `requirements.txt` or `pyproject.toml` (pip, uv or conda).
- The standard library covers files, dates, maths, data formats, logging and more.
- Git: add → commit → push → pull request → merge; use `.gitignore` and never commit secrets.

## Quick quiz

6 questions · tap an answer to check it

**1. What does `if __name__ == "__main__":` do?**

A Imports main

B Runs the block only when the file is executed directly

C Defines the main function

D Speeds up the program

**Answer: B.** When imported, `__name__` is the module name.

**2.** Why use a virtual environment?

A It makes Python faster

B It isolates each project's library versions

C It is required by Git

D It encrypts the code

**Answer: B.** Different projects may need different versions.

**3.** How do you record the exact installed versions for others?

A `pip list`

B `pip freeze > requirements.txt`

C `git add .`

D `pip update`

**Answer: B.** Others recreate with `pip install -r requirements.txt`.

**4.** Why should you not name your file `pandas.py`?

A It is too long

B It shadows the real pandas library on import

C Git rejects it

D It is reserved

**Answer: B.** Python finds your file first.

**5.** Which Git command uploads your commits to GitHub?

A `git commit`

B `git push`

C `git add`

D `git log`

**Answer: B.** Commit saves locally; push uploads.

**6.** Where should API keys go?

A In the code

B In environment variables or an ignored .env file

C In the README

D In a commit message

**Answer: B.** Never commit secrets.

EXERCISE **Setup checklist**

(1) Create a project folder with a virtual environment and install pandas and matplotlib. (2) Write a module `cleaning.py` with two functions and import it from a notebook. (3) Create a GitHub repository, add a `.gitignore` and a README, and push. (4) Create a branch, change the README and open a pull request to yourself.

**Show solution (worked answer)**

Follow the commands in this lesson. Check with `python -c "import pandas; print(pandas.__version__)"` and `git log --oneline`. A good README states the question, the data source, how to run the code and the key findings with one chart.

INTERVIEW CORNER

### Questions you may be asked

**Q: Difference between a module, a package and a library?** A module is one file, a package is a folder of modules, and a library is a collection of packages distributed together (e.g. on PyPI).

**Q: How do you make a Python project reproducible?** Virtual environment, pinned dependencies, a README with run instructions, fixed random seeds, version control, and data lineage.

**Q: git merge vs git rebase?** Merge combines histories with a merge commit; rebase replays your commits on top of another branch for a linear history. Never rebase shared branches.

PYTHON FOR DATA SCIENCE · LESSON 14

# Debugging, Testing, Regular Expressions and Code Quality

Find and fix bugs systematically, write automated tests with pytest, clean text with regular expressions, and keep code readable with PEP 8, type hints, linters and formatters.

Python class 10 | Python 3.13 · pytest 9 · ruff | Intermediate | 100 min

**By the end of this lesson you can**

- Read a traceback and debug with print, breakpoints and pdb
- Write and run unit tests with assert and pytest, including parametrised tests
- Use regular expressions to search, extract, validate and replace text
- Apply PEP 8 naming and layout, type hints, and automatic tools (ruff, black, mypy)
- Use AI assistants to debug and review code responsibly

## Reading a traceback

Read a traceback **from the bottom up**: the last line names the error, the lines above show where it happened.

Python

```
def average(values):
    return sum(values) / len(values)
def report(data):
    return f"Average: {average(data['scores']):.1f}"
print(report({"scores": []}))
```

OUTPUT

```
ZeroDivisionError: division by zero
```


The last line says `ZeroDivisionError`; the frame above points at `average`, called from `report`. The fix is a guard for empty input:

```python
def average(values):
    return sum(values) / len(values) if values else None
print(average([]), average([4, 6]))
```

OUTPUT

```
None 5.0
```

## A debugging routine




A systematic debugging loop beats random changes.

| Technique | How |
| --- | --- |
| Print / f-string debugging | `print(f"{i=} {total=}")` shows names and values |
| `breakpoint()` | Pauses and opens the `pdb` debugger at that line |
| IDE debugger | VS Code / PyCharm: breakpoints, step over/into, watch variables |
| Jupyter `%debug` | Post-mortem debugging after an error in a cell |
| Rubber-duck | Explain the code line by line to someone (or an AI) |
| Bisect | Comment out halves of the code to find the failing part |

Python

```python
total = 0
for i, v in enumerate([5, 10, 15]):
    total += v
    print(f"{i=} {v=} {total=}")          # the = specifier prints the name and the value
```

OUTPUT

```
i=0 v=5 total=5
i=1 v=10 total=15
i=2 v=15 total=30
```

pdb commands: `n` (next line), `s` (step into), `c` (continue), `p var` (print), `l` (list code), `q` (quit).

## Testing

A **test** is code that checks other code. Tests catch regressions when you change things later.

Python

```python
def clean_city(raw):
    return " ".join(raw.split()).title() if raw else None

assert clean_city("  new   delhi ") == "New Delhi"
assert clean_city("") is None
print("asserts passed")
```

OUTPUT

```
asserts passed
```

## pytest

`pytest` finds files named `test_*.py` and runs functions named `test_*`. Plain `assert` statements give detailed failure messages.

Python

```
from pathlib import Path
import subprocess, sys
Path("tests_demo").mkdir(exist_ok=True)
Path("tests_demo/cleaning.py").write_text('''
def clean_city(raw):
    return " ".join(raw.split()).title() if raw else None

def to_inr(value):
    return f"₹{value:,.0f}"
''', encoding="utf-8")
Path("tests_demo/test_cleaning.py").write_text('''
import pytest
from cleaning import clean_city, to_inr

@pytest.mark.parametrize("raw, expected", [("  pune", "Pune"), ("NEW  DELHI", "New Delhi"),
("", None), (None, None)])
def test_clean_city(raw, expected):
    assert clean_city(raw) == expected

def test_to_inr():
    assert to_inr(1234567) == "₹1,234,567"

def test_bad_input():
    with pytest.raises(ValueError):          # a str cannot take the ',' number format
        to_inr("abc")

def test_deliberately_failing():
    assert to_inr(1000) == "₹1000"          # wrong expectation, to show a failure report
''', encoding="utf-8")
r = subprocess.run([sys.executable, "-m", "pytest", "-q", "--no-header", "-p",
"no:cacheprovider", "tests_demo"], capture_output=True, text=True)
lines = r.stdout.strip().splitlines()
print("\n".join([l for l in lines if "assert" in l or "passed" in l or "failed" in l]
[-4:]))
import shutil; shutil.rmtree("tests_demo")
```

OUTPUT

```
>       assert to_inr(1000) == "₹1000"          # wrong expectation, to show a
failure report
E       AssertionError: assert '₹1,000' == '₹1000'
1 failed, 6 passed in 0.02s
```

The report says which test failed and shows both values: `'₹1,000' == '₹1000'`. The function is right, so the test expectation is fixed.

> **TIP** **What to test in data work**
>
> Cleaning functions, metric calculations, edge cases (empty, missing, negative, duplicates), schema checks on loaded data (columns, types, ranges), and that a pipeline's row counts reconcile. Tools such as **pandera** and **Great Expectations** validate DataFrames.

## Regular expressions

A **regular expression** (regex) is a pattern for text. Python's `re` module searches, extracts, validates and replaces.

| Pattern | Matches |
|---|---|
| `\d` / `\D` | A digit / a non-digit |
| `\w` / `\s` | Word character (letter, digit, _) / whitespace |
| `.` | Any character except newline |
| `[A-Z]`, `[^0-9]` | Character set / negated set |
| `*`, `+`, `?` | 0 or more, 1 or more, 0 or 1 |
| `{3}`, `{2,4}` | Exactly 3, between 2 and 4 |
| `^`, `$` | Start, end of string |
| `( )` | Capture group; `(?P<name> )` named group |
| `\|` | Or |

Python

```
import re
text = "Call 98765-43210 or +91 91234 56789; email asha.k@gmail.com, ravi@skillnavora.in.
Order #A-1029 on 2025-04-07."
print(re.findall(r"\d{5}[- ]?\d{5}", text))                                  # phone numbers
print(re.findall(r"[\w.+-]+@[\w-]+(?:\.[\w-]+)+", text))                      # emails (no
trailing full stop)
m = re.search(r"(?P<y>\d{4})-(?P<m>\d{2})-(?P<d>\d{2})", text)
print(m.group(), m["y"], m.groupdict())
print(re.sub(r"\d", "X", "PAN ABCDE1234F"), re.split(r"[;,]\s*", "a, b;c ,d"))
print(bool(re.fullmatch(r"[A-Z]{5}\d{4}[A-Z]", "ABCDE1234F")), bool(re.fullmatch(r"[A-Z]
{5}\d{4}[A-Z]", "ABCD1234F")))    # PAN format
```

OUTPUT

```
['98765-43210', '91234 56789']
['asha.k@gmail.com', 'ravi@skillnavora.in']
2025-04-07 2025 {'y': '2025', 'm': '04', 'd': '07'}
PAN ABCDEXXXXF ['a', 'b', 'c ', 'd']
True False
```

Always use **raw strings** `r"..."` for patterns, so `\d` is not treated as an escape. Test patterns at regex101.com.

## Regex on a DataFrame

Python

```python
import pandas as pd
c = pd.DataFrame({"name": ["Asha", "Ravi", "Meera", "Kabir", "Zoya"],
                  "email": ["asha@gmail.com", "ravi@company", "MEERA@Yahoo.co.in", "kabir
@gmail.com", None],
                  "phone": ["98765 43210", "+91-91234-56789", "12345", "9123456789",
"0987654321"]})
c["email_ok"] = c["email"].str.fullmatch(r"[\w.+-]+@[\w-]+(?:\.[\w-]+)+", na=False)
c["domain"] = c["email"].str.lower().str.extract(r"@([\w.-]+)$")[0]
digits = c["phone"].str.replace(r"\D", "", regex=True).str[-10:]
c["phone_ok"] = digits.str.fullmatch(r"[6-9]\d{9}")
print(c[["name", "email_ok", "domain", "phone_ok"]])
```

OUTPUT

```
    name  email_ok       domain  phone_ok
0   Asha      True    gmail.com      True
1   Ravi     False      company      True
2  Meera      True  yahoo.co.in     False
3  Kabir     False    gmail.com      True
4   Zoya     False          NaN     False
```

pandas string methods ( `.str.contains` , `.str.extract` , `.str.replace` , `.str.fullmatch` ) accept regex and run on the whole column.

# Code quality

**PEP 8** is Python's style guide. The essentials:

| Rule | Example |
| --- | --- |
| `snake_case` for variables and functions | `total_sales`, `clean_city()` |
| `PascalCase` for classes | `CleaningPipeline` |
| `UPPER_CASE` for constants | `GST_RATE = 0.18` |
| 4-space indentation, lines ≤ 79–100 chars | |
| Spaces around operators, after commas | `x = a + b`, `f(a, b)` |
| Imports at the top, grouped std / third-party / local | |
| Meaningful names over comments | `days_since_last_order`, not `d` |

Let tools do the work:

```text
pip install ruff mypy
ruff check .          # lint: unused imports, undefined names, bad patterns
ruff format .         # auto-format (black-compatible)
mypy src/             # check type hints
pre-commit install    # run them automatically before each commit
```

> **NOTE** **Using AI to debug**
>
> Paste the **full traceback and the smallest code that reproduces it** into an AI assistant (Claude, ChatGPT, Copilot, Gemini). Ask it to explain the cause before proposing a fix, then run the fix and add a test. Never paste secrets or confidential data, and check that suggested library functions really exist.

# Summary

**KEY TAKEAWAYS**

- Read tracebacks bottom-up; reproduce, isolate, hypothesise, fix, then add a test.
- Debug with `print(f"{x=}")`, `breakpoint()`, an IDE debugger or `%debug`.
- `pytest` runs `test_*` functions with plain `assert`; use `parametrize` for many cases and `pytest.raises` for errors.
- Regex: `re.search`, `findall`, `fullmatch`, `sub`, `split`; raw strings; pandas `.str` methods accept regex.
- Follow PEP 8 and automate it with ruff, a formatter and mypy.

## Quick quiz

6 questions · tap an answer to check it

**1. Where do you start reading a Python traceback?**

A The first line

B The last line, which names the error

C The middle

D The import lines

**Answer: B.** Then read upward to find where it happened.

**2. What does `print(f"{total=}")` print when total is 5?**

A 5

B total=5

C {total=5}

D An error

**Answer: B.** The `=` specifier is a debugging shortcut.

**3. Which file name will pytest discover by default?**

A cleaning_tests.py

B test_cleaning.py

C tests.txt

D cleaning.py

**Answer: B.** Files `test_*.py` or `*_test.py`, functions `test_*`.

**4. What does `\d{3}` match?**

A The letter d three times

B Exactly three digits

C Up to three digits

D Any three characters

**Answer: B.** `\d` is a digit; `{3}` repeats it exactly three times.

**5. Why use `r"..."` for regex patterns?**

A It runs faster

B Backslashes are kept literally instead of being treated as escapes

C It makes the pattern case-insensitive

D It is required by pandas

**Answer: B.** Raw strings avoid double escaping.

**6.** Which naming follows PEP 8 for a function?

A CalculateMargin

B calculate_margin

C CALCULATE_MARGIN

D calculateMargin

**Answer: B.** snake_case for functions and variables.

EXERCISE **Practice**

(1) Write a regex that extracts all hashtags from a tweet. (2) Validate Indian PIN codes (6 digits, not starting with 0). (3) Write three pytest tests for a `percent_change` function, including the zero case. (4) Run `ruff check` on one of your notebooks exported as `.py` and fix the warnings.

**Show solution (worked answer)**

Python

```python
import re
print(re.findall(r"#\w+", "Loving #Python and #DataScience!"))
pin = re.compile(r"[1-9]\d{5}")
print(bool(pin.fullmatch("411001")), bool(pin.fullmatch("011001")))
# test_metrics.py
# def test_up(): assert percent_change(100, 120) == 20
# def test_down(): assert percent_change(100, 80) == -20
# def test_zero(): assert percent_change(0, 5) is None
```

INTERVIEW CORNER

### Questions you may be asked

**Q: How do you debug a function that gives wrong output only for some inputs?** Reproduce with the smallest failing input, inspect intermediate values (prints or debugger), form a hypothesis, fix, and add the case as a regression test.

**Q: Unit test vs integration test?** A unit test checks one small function in isolation; an integration test checks that components work together (e.g. load → transform → write).

**Q: Write a regex for a 10-digit Indian mobile number.** `^[6-9]\d{9}$` (optionally allowing a `+91` prefix: `^(?:\+91[- ]?)?[6-9]\d{9}$`).

PYTHON FOR DATA SCIENCE · LESSON 15

# NumPy: Fast Arrays, Vectorisation and Broadcasting

Learn the array library under pandas, scikit-learn and PyTorch. Create arrays, understand shape and dtype, index and slice in 1-D and 2-D, filter with boolean masks, compute with vectorised operations, aggregations along axes and broadcasting, generate random data and do basic linear algebra.

Python class 11 | NumPy 2.x | Intermediate | 120 min

**By the end of this lesson you can**

- Create arrays and describe their shape, ndim, dtype and size
- Index, slice and filter 1-D and 2-D arrays with boolean masks and fancy indexing
- Use vectorised arithmetic, universal functions and aggregations along an axis
- Apply broadcasting rules, reshape, stack and split arrays
- Generate reproducible random data and perform matrix operations

## Why NumPy?

A Python list holds pointers to separate objects; a NumPy **array** stores numbers of one type in one contiguous block of memory and runs operations in compiled C. The result: code that is shorter **and** usually many times faster (the gap grows with heavier maths).

Python

```
import numpy as np, time
n = 1_000_000
py = list(range(n)); arr = np.arange(n)
t0 = time.perf_counter(); sq_list = [x * x for x in py]; t1 = time.perf_counter(); sq_arr =
arr * arr; t2 = time.perf_counter()
print(f"list comprehension {1000*(t1-t0):.1f} ms | numpy {1000*(t2-t1):.1f} ms | same
result: {sq_list[-1] == sq_arr[-1]}")
print(np.__version__)
```

OUTPUT

```
list comprehension 44.7 ms | numpy 34.8 ms | same result: True
2.5.3
```


## Creating arrays

Python

```python
a = np.array([3, 1, 4, 1, 5])
m = np.array([[1, 2, 3], [4, 5, 6]])
print(a, a.dtype, a.shape, a.ndim, a.size)
print(m, m.shape, m.ndim, m.dtype)
print(np.zeros(3), np.ones((2, 2)), np.full(3, 7), np.eye(2))
print(np.arange(0, 10, 2.5), np.linspace(0, 1, 5), np.array([1, 2.5]).dtype, np.array([1,
2], dtype=np.float32).dtype)
```

OUTPUT

```
[3 1 4 1 5] int64 (5,) 1 5
[[1 2 3]
 [4 5 6]] (2, 3) 2 int64
[0. 0. 0.] [[1. 1.]
 [1. 1.]] [7 7 7] [[1. 0.]
 [0. 1.]]
[0.  2.5 5.  7.5] [0.   0.25 0.5  0.75 1.  ] float64 float32
```




Shapes of 1-D, 2-D and 3-D arrays. axis 0 runs down the rows, axis 1 across the columns.

All items share one **dtype** ( `int64` , `float64` , `bool` , `<U5` strings...). Mixing ints and floats upcasts to float.

## Indexing and slicing

Python

```
a = np.array([10, 20, 30, 40, 50, 60])
print(a[0], a[-1], a[1:4], a[::2], a[::-1])
m = np.arange(1, 13).reshape(3, 4)
print(m)
print(m[0, 2], m[1], m[:, 1], m[1:, 2:], m[-1, -1])          # [row, column]
```

OUTPUT

```
10 60 [20 30 40] [10 30 50] [60 50 40 30 20 10]
[[ 1  2  3  4]
 [ 5  6  7  8]
 [ 9 10 11 12]]
3 [5 6 7 8] [ 2  6 10] [[ 7  8]
 [11 12]] 12
```

**WATCH OUT** **Slices are views**

`b = a[1:4]` does **not** copy; changing `b` changes `a`. Use `a[1:4].copy()` when you need an independent array. (Python lists behave the other way: slicing copies.)

## Boolean masks and fancy indexing

Python

```
sales = np.array([120, 45, 300, 80, 210, 15])
mask = sales > 100
print(mask, sales[mask], sales[(sales > 50) & (sales < 250)], sales[~mask])    # & | ~ with brackets
print(sales[[0, 2, 4]], np.where(sales > 100, "high", "low"), np.where(sales > 100)[0])
sales[sales < 50] = 0                                    # conditional assignment
print(sales, np.count_nonzero(sales), (sales > 100).mean())
```

OUTPUT

```
[ True False  True False  True False] [120 300 210] [120  80 210] [45 80 15]
[120 300 210] ['high' 'low' 'high' 'low' 'high' 'low'] [0 2 4]
[120   0 300  80 210   0] 4 0.5
```

## Vectorised maths and aggregations

Python

```
price = np.array([100.0, 250.0, 80.0]); qty = np.array([3, 1, 10])
print(price * qty, (price * qty).sum(), price * 1.18, np.round(np.sqrt(price), 2),
np.log(price).round(2))
m = np.array([[5, 2, 9], [1, 7, 3]])
print(m.sum(), m.sum(axis=0), m.sum(axis=1), m.max(axis=1), m.argmax(axis=1),
m.mean(axis=0))
x = np.array([2, 4, 4, 4, 5, 5, 7, 9])
print(x.mean(), np.median(x), x.std(), x.std(ddof=1).round(3), np.percentile(x, [25, 75]),
np.cumsum(x), np.diff(x))
```


OUTPUT

```
[300. 250. 800.] 1350.0 [118.  295.   94.4] [10.   15.81  8.94] [4.61 5.52 4.38]
27 [ 6  9 12] [16 11] [9 7] [2 1] [3.  4.5 6. ]
5.0 4.5 2.0 2.138 [4.  5.5] [ 2  6 10 14 19 24 31 40] [2 0 0 1 0 2 2]
```

`axis=0` collapses rows (one result per column); `axis=1` collapses columns (one result per row). `ddof=1` gives the **sample** standard deviation that pandas uses by default.

## Broadcasting

When shapes differ, NumPy **stretches** the smaller array along dimensions of size 1, without copying data.




Broadcasting: a (3, 3) matrix plus a (3,) row is applied to every row.

Python

```
m = np.arange(1, 10).reshape(3, 3)
print(m + np.array([10, 20, 30]))                       # add to each row
print(m * np.array([[1], [10], [100]]))                 # multiply each row by its own
factor (column vector)
scores = np.array([[70, 80, 90], [60, 75, 85], [88, 92, 79]], dtype=float)
z = (scores - scores.mean(axis=0)) / scores.std(axis=0)   # standardise each column in one
line
print(z.round(2))
```

OUTPUT

```
[[11 22 33]
 [14 25 36]
 [17 28 39]]
[[  1   2   3]
 [ 40  50  60]
 [700 800 900]]
[[-0.23 -0.33  1.19]
 [-1.09 -1.03  0.07]
 [ 1.32  1.36 -1.26]]
```

Rule: compare shapes from the right; dimensions are compatible if equal or one of them is 1.

## Reshaping, stacking, sorting

Python

```
a = np.arange(12)
print(a.reshape(3, 4).shape, a.reshape(2, -1).shape, a.reshape(3, 4).T.shape, a.reshape(3,
4).ravel()[:5])
x, y = np.array([1, 2]), np.array([3, 4])
print(np.vstack([x, y]), np.hstack([x, y]), np.column_stack([x, y]), np.concatenate([x,
y]))
v = np.array([30, 10, 20, 10])
print(np.sort(v), np.argsort(v), np.unique(v, return_counts=True), v[np.argsort(-v)][:2])
```

OUTPUT

```
(3, 4) (2, 6) (4, 3) [0 1 2 3 4]
[[1 2]
 [3 4]] [1 2 3 4] [[1 3]
 [2 4]] [1 2 3 4]
[10 10 20 30] [1 3 2 0] (array([10, 20, 30]), array([2, 1, 1])) [30 20]
```

## Random numbers

Use the modern generator API with a seed so results are reproducible.

Python

```
rng = np.random.default_rng(42)
print(rng.integers(1, 7, size=10))                      # dice
print(rng.normal(loc=50, scale=10, size=5).round(1))    # normal distribution
print(rng.choice(["A", "B"], size=8, p=[0.7, 0.3]), rng.uniform(0, 1, 3).round(3))
sample = rng.normal(50, 10, 100_000)
print(round(sample.mean(), 2), round(sample.std(), 2), round(((sample > 40) & (sample <
60)).mean(), 3))   # about 68% within 1 sd
```

OUTPUT

```
[1 5 4 3 3 6 1 5 2 1]
[37.  51.3 46.8 49.8 41.5]
['A' 'B' 'A' 'B' 'A' 'A' 'A' 'A'] [0.828 0.632 0.758]
49.96 10.04 0.682
```

## Linear algebra basics

Machine-learning models are built from these operations.

Python

```
A = np.array([[2, 1], [1, 3]]); b = np.array([5, 10])
print(A @ np.array([1, 2]), A.T, np.linalg.det(A).round(2), np.linalg.inv(A).round(3))
print(np.linalg.solve(A, b))                            # solves 2x + y = 5, x + 3y = 10
w = np.array([0.5, -0.2]); X = np.array([[1.0, 2.0], [3.0, 1.0], [2.0, 2.0]])
print(X @ w)                                             # predictions of a linear model y
= Xw
```

OUTPUT

```
[4 7] [[2 1]
 [1 3]] 5.0 [[ 0.6 -0.2]
 [-0.2  0.4]]
[1. 3.]
[0.1 1.3 0.6]
```

# Real data: house prices

Python

```
import pandas as pd
h = pd.read_csv("house_prices.csv")
area, price = h["area_sqft"].to_numpy(), h["price_lakh"].to_numpy()
print("missing values:", np.isnan(area).sum(), "area,", np.isnan(price).sum(), "price")
# real data has gaps
ok = ~np.isnan(area) & ~np.isnan(price)
area, price = area[ok], price[ok]
# keep complete rows
per_sqft = price * 1e5 / area
print(f"{len(price)} houses | median price ₹{np.median(price):.1f} lakh | median ₹
{np.median(per_sqft):,.0f}/sq ft")
print("price percentiles 10/50/90:", np.percentile(price, [10, 50, 90]).round(1))
big = area > 1500
print(f"{big.mean():.0%} are over 1,500 sq ft; their median price is ₹
{np.median(price[big]):.1f} lakh vs ₹{np.median(price[~big]):.1f} lakh")
r = np.corrcoef(area, price)[0, 1]
slope, intercept = np.polyfit(area, price, 1)
print(f"correlation area-price r = {r:.2f}; fitted line: price ≈ {intercept:.1f} +
{slope*100:.2f} lakh per 100 sq ft")
```

OUTPUT

```
missing values: 25 area, 0 price
1175 houses | median price ₹78.7 lakh | median ₹6,258/sq ft
price percentiles 10/50/90: [ 40.3  78.7 119.9]
27% are over 1,500 sq ft; their median price is ₹110.0 lakh vs ₹68.1 lakh
correlation area-price r = 0.79; fitted line: price ≈ -7.5 + 7.05 lakh per 100 sq ft
```

`np.polyfit` fits a straight line by least squares, which is the same idea as linear regression (ML track).

# Summary

**KEY TAKEAWAYS**

- Arrays hold one dtype in contiguous memory; operations are vectorised and much faster than Python loops.
- Know `shape`, `ndim`, `dtype`, `size`; index with `[row, col]`; slices are views (use `.copy()`).
- Boolean masks (`a[a > 0]`, `&`, `|`, `~`) and `np.where` filter and recode.
- Aggregate with `axis=0` (per column) or `axis=1` (per row); `ddof=1` for sample standard deviation.
- Broadcasting stretches size-1 dimensions; reshape with `-1` to infer a dimension.
- Use `np.random.default_rng(seed)` and `@` for matrix multiplication.

## Quick quiz

6 questions · tap an answer to check it

**1.** What is `np.arange(12).reshape(3, -1).shape`?

**A** (3, 3)

**B** (3, 4)

**C** (4, 3)

**D** Error

**Answer: B.** -1 lets NumPy infer the missing dimension: 12 / 3 = 4.

**2. What does `m.sum(axis=0)` return for a 2 × 3 matrix?**

A One number

B Three numbers: the sum of each column

C Two numbers: the sum of each row

D A 2 × 3 matrix

**Answer: B.** axis=0 collapses the rows.

**3. Which expression keeps values between 10 and 20?**

A `a[a > 10 and a < 20]`

B `a[(a > 10) & (a < 20)]`

C `a[10:20]`

D `a.between(10, 20)`

**Answer: B.** Use `&` with brackets for element-wise conditions.

**4. After `b = a[0:3]; b[0] = 99`, what happens to `a[0]`?**

A Unchanged

B It becomes 99 because a slice is a view

C Error

D It becomes 0

**Answer: B.** Use `.copy()` to avoid this.

**5.** Can a (3, 4) array be added to a (4,) array?

**A** Yes, the (4,) array is broadcast across the rows

**B** No, shapes must match exactly

**C** Only with a loop

**D** Only if both are float

**Answer: A.** Trailing dimensions match (4 and 4).

**6.** How do you make random results reproducible?

**A** Use `np.random.random()`

**B** Create a generator with a seed: `np.random.default_rng(42)`

**C** Run the cell twice

**D** Use floats

**Answer: B.** The same seed gives the same numbers.

EXERCISE

### NumPy practice

(1) Create a 5 × 5 array of 1..25 and select the diagonal and the last column. (2) Replace all negative values in an array with 0. (3) Standardise the `area_sqft` column (z-scores) and count values beyond ±2. (4) Simulate 10,000 rolls of two dice and estimate P(sum = 7). (5) Solve 3x + 2y = 12, x − y = 1.

**Show solution (worked answer)**

Python

```
g = np.arange(1, 26).reshape(5, 5); print(np.diag(g), g[:, -1])
v = np.array([3, -1, 4, -5]); v[v < 0] = 0; print(v)
z = (area - area.mean()) / area.std(); print((np.abs(z) > 2).sum())
rng = np.random.default_rng(0); rolls = rng.integers(1, 7, (10_000, 2)).sum(axis=1);
print((rolls == 7).mean())   # about 1/6
print(np.linalg.solve([[3, 2], [1, -1]], [12, 1]))   # x = 2.8, y = 1.8
```

INTERVIEW CORNER

### Questions you may be asked

**Q: Why is NumPy faster than Python lists?** Contiguous memory of one dtype, operations implemented in C over the whole array (vectorisation), and no per-element Python overhead.

**Q: What is broadcasting?** NumPy's rule for operating on arrays of different shapes by virtually repeating dimensions of size 1, aligning shapes from the right.

**Q: View vs copy?** Basic slices return views that share memory; fancy/boolean indexing and `.copy()` return copies.

**Q: Difference between `np.std(x)` and `pandas.Series.std()`?** NumPy defaults to population std ( `ddof=0` ); pandas defaults to sample std ( `ddof=1` ).

PYTHON FOR DATA SCIENCE · LESSON 16

# pandas I: Series, DataFrames, Reading Data, Selecting and Filtering

Meet the most-used data library. Create Series and DataFrames, read CSV and Excel files, inspect data with head, info and describe, select columns and rows with loc and iloc, filter with conditions and query, sort, add columns and save results, using the Superstore sales data.


Python class 12 | pandas 2.3 / 3.0 | Intermediate | 120 min

**By the end of this lesson you can**

- Create Series and DataFrames and explain the index
- Read CSV and Excel files with the right options and write results back out
- Inspect a dataset with shape, dtypes, head, info, describe and value_counts
- Select with [], loc and iloc and filter rows with boolean conditions, isin, between and query
- Sort, rank, add and rename columns, and avoid the SettingWithCopy pitfall

## Series and DataFrame

**pandas** gives Python spreadsheet-like tables. A **Series** is one labelled column; a **DataFrame** is a table of Series sharing one **index** (row labels).




A DataFrame is a set of Series (columns) that share an index (row labels).

Python

```
import pandas as pd, numpy as np
pd.set_option("display.max_columns", 20); pd.set_option("display.width", 160)   # show wide tables in full
s = pd.Series([120, 95, 140], index=["North", "South", "East"], name="sales")
print(s, s["South"], s.max(), s.idxmax(), sep="\n")
df = pd.DataFrame({"city": ["Pune", "Delhi", "Kochi"], "sales": [120, 95, 140], "target": [100, 110, 130]})
df["hit"] = df["sales"] ⩾ df["target"]
print(df)
print(df.shape, list(df.columns), df.index, df.dtypes.to_dict(), pd.__version__)
```

OUTPUT

```
North    120
South     95
East     140
Name: sales, dtype: int64
95
140
East
    city  sales  target    hit
0   Pune    120     100   True
1  Delhi     95     110  False
2  Kochi    140     130   True
(3, 4) ['city', 'sales', 'target', 'hit'] RangeIndex(start=0, stop=3, step=1)
{'city': dtype('O'), 'sales': dtype('int64'), 'target': dtype('int64'), 'hit': dtype('bool')} 2.3.3
```

## Reading data

Python

```
s = pd.read_csv("superstore_sales.csv", parse_dates=["order_date", "ship_date"])
print(s.shape)
print(s.head(3).T)
```

OUTPUT

```
(6323, 19)
                              0                    1                    2
row_id                        1                    2                    3
order_id             IN-2023-00001        IN-2023-00001        IN-2023-00001
order_date     2023-01-01 00:00:00  2023-01-01 00:00:00  2023-01-01 00:00:00
ship_date      2023-01-05 00:00:00  2023-01-05 00:00:00  2023-01-05 00:00:00
ship_mode            Second Class         Second Class         Second Class
```

| | | | |
|---|---|---|---|
| customer_id | C0765 | C0765 | C0765 |
| customer_name | Ishaan Gupta | Ishaan Gupta | Ishaan Gupta |
| segment | Consumer | Consumer | Consumer |
| city | Bengaluru | Bengaluru | Bengaluru |
| state | Karnataka | Karnataka | Karnataka |
| region | South | South | South |
| product_id | P0059 | P0050 | P0011 |
| category | Technology | Office Supplies | Furniture |
| sub_category | Phones | Appliances | Tables |
| product_name | Nova Phone 223 | Orbit Appliance 798 | Orbit Table 248 |
| sales | 36000.0 | 3850.0 | 62080.0 |
| quantity | 2 | 1 | 4 |
| discount | 0.0 | 0.0 | 0.0 |
| profit | 3472.55 | 1169.54 | 6044.47 |

| Option | Use |
|---|---|
| `sep=";"` | Other delimiters ( `"\t"` for TSV) |
| `usecols=[...]` | Read only some columns (faster, less memory) |
| `dtype={"pin": str}` | Keep leading zeros and IDs as text |
| `parse_dates=[...]` | Convert date columns |
| `na_values=["NA", "-"]` | Extra markers for missing |
| `nrows=1000` , `chunksize=100_000` | Sample or stream big files |
| `encoding="latin-1"` | Fix decode errors in older files |

Other readers: `pd.read_excel("file.xlsx", sheet_name="Sales")` (needs `openpyxl` ), `pd.read_json` , `pd.read_parquet` , `pd.read_sql` (Lesson 23), `pd.read_html` , `pd.read_clipboard` .

## Inspecting data

Run these five on every new dataset:

Python

```
print(s.info(memory_usage="deep"))
```

OUTPUT

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 6323 entries, 0 to 6322
```

```
Data columns (total 19 columns):
 #   Column         Non-Null Count  Dtype
---  ------         --------------  -----
 0   row_id         6323 non-null   int64
 1   order_id       6323 non-null   object
 2   order_date     6323 non-null   datetime64[ns]
 3   ship_date      6323 non-null   datetime64[ns]
 4   ship_mode      6323 non-null   object
 5   customer_id    6323 non-null   object
 6   customer_name  6323 non-null   object
 7   segment        6323 non-null   object
 8   city           6323 non-null   object
 9   state          6323 non-null   object
 10  region         6323 non-null   object
 11  product_id     6323 non-null   object
 12  category       6323 non-null   object
 13  sub_category   6323 non-null   object
 14  product_name   6323 non-null   object
 15  sales          6323 non-null   float64
 16  quantity       6323 non-null   int64
 17  discount       6323 non-null   float64
 18  profit         6323 non-null   float64
dtypes: datetime64[ns](2), float64(3), int64(2), object(12)
memory usage: 4.6 MB
None
```

Python

```python
print(s.describe(include="number").round(1).T)
print(s["region"].value_counts(), s["category"].value_counts(normalize=True).round(3),
sep="\n")
print(s["customer_id"].nunique(), "customers |", s["order_date"].min().date(), "to",
s["order_date"].max().date())
print(s.isna().sum().sum(), "missing cells |", s.duplicated().sum(), "duplicate rows")
```

OUTPUT

```
             count     mean      std      min     25%     50%      75%       max
row_id      6323.0   3162.0   1825.4      1.0  1581.5  3162.0   4742.5    6323.0
sales       6323.0  31854.1  60414.2     42.0  1564.0  8430.0  32592.0  619290.0
quantity    6323.0      2.6      1.6      1.0     1.0     2.0      3.0       7.0
discount    6323.0      0.1      0.1      0.0     0.0     0.0      0.2       0.4
profit      6323.0   2902.4  11002.0 -75873.8   -17.9   266.3   2270.1  149424.9
region
South     1656
West      1614
North     1530
```

```
East     1523
Name: count, dtype: int64
category
Office Supplies    0.398
Furniture          0.303
Technology         0.299
Name: proportion, dtype: float64
785 customers | 2023-01-01 to 2025-12-31
0 missing cells | 0 duplicate rows
```

## Selecting columns and rows

Python

```python
print(s["sales"].head(3).tolist())                    # one column → Series
print(s[["order_id", "region", "sales"]].head(3))     # list of columns → DataFrame
print(s.loc[0, "customer_name"], s.iloc[0, 6])        # loc = labels, iloc = positions
print(s.loc[0:2, "region":"product_id"])               # loc slices INCLUDE the end label
print(s.iloc[0:2, 10:12])                              # iloc slices EXCLUDE the end, like
Python
```

OUTPUT

```
[36000.0, 3850.0, 62080.0]
        order_id region    sales
0  IN-2023-00001  South  36000.0
1  IN-2023-00001  South   3850.0
2  IN-2023-00001  South  62080.0
Ishaan Gupta Ishaan Gupta
  region product_id
0  South      P0059
1  South      P0050
2  South      P0011
  region product_id
0  South      P0059
1  South      P0050
```

| Tool | Selects by | Example |
|---|---|---|
| `df["col"]` / `df[["a","b"]]` | Column names | `s["sales"]` |
| `df.loc[rows, cols]` | **Labels** and boolean masks | `s.loc[s.profit < 0, ["order_id", "profit"]]` |
| `df.iloc[rows, cols]` | **Integer positions** | `s.iloc[:5, :3]` |
| `df.at[r, c]` / `df.iat[i, j]` | One value, fast | `s.at[0, "sales"]` |

## Filtering rows

Python

```
loss = s[s["profit"] < 0]
print(len(loss), "loss-making lines")
tech_south = s[(s["category"] == "Technology") & (s["region"] == "South")]           # & |
~ need brackets
print(len(tech_south), round(tech_south["sales"].sum() / 1e6, 2), "M")
print(s[s["city"].isin(["Pune", "Kochi"])]["city"].value_counts().to_dict())
print(len(s[s["discount"].between(0.1, 0.2)]),
len(s[s["product_name"].str.contains("Chair")]))
print(s.query("region == 'West' and sales > 50000 and discount == 0")[["order_id",
"sales"]].head(3))
big = 50000
print(len(s.query("sales > @big")))                    # @ refers to a Python variable
```

OUTPUT

```
1682 loss-making lines
495 41.89 M
{'Pune': 529, 'Kochi': 417}
1943 493
         order_id    sales
7   IN-2023-00003  69280.0
22  IN-2023-00013  72000.0
98  IN-2023-00051  64450.0
1126
```

# Sorting and ranking

Python

```
top = s.sort_values("sales", ascending=False)[["order_id", "product_name",
"sales"]].head(5)
print(top)
print(s.sort_values(["region", "profit"], ascending=[True,
False]).groupby("region").head(1)[["region", "product_name", "profit"]])
print(s.nlargest(3, "profit")[["product_name", "profit"]], s.nsmallest(2, "profit")
[["product_name", "profit"]], sep="\n")
```

OUTPUT

```
          order_id       product_name     sales
3669  IN-2024-01857   Orbit Copier 746  619290.0
2087  IN-2024-01040  Vertex Copier 262  551530.0
1142  IN-2023-00564  Vertex Copier 262  551530.0
5696  IN-2025-02880   Orbit Copier 746  530820.0
1653  IN-2023-00809   Orbit Copier 746  526396.5
     region       product_name     profit
4219   East   Orbit Copier 746  135564.21
3669  North   Orbit Copier 746  149424.89
3893  South    Apex Copier 347  107757.96
481    West  Zenith Copier 719   95485.58
         product_name     profit
3669  Orbit Copier 746  149424.89
4219  Orbit Copier 746  135564.21
3893   Apex Copier 347  107757.96
            product_name    profit
5979    Orbit Copier 746 -75873.84
639   Pioneer Copier 366 -67392.75
```

# Adding, changing and removing columns

Python

```
e = pd.read_csv("employees_small.csv", parse_dates=["join_date"])
e["bonus"] = e["salary"] * 0.1                                    # vectorised
arithmetic
e["band"] = np.where(e["salary"] ⩾ 100000, "Senior", "Standard")      # IF
e["grade"] = pd.cut(e["salary"], bins=[0, 70000, 100000, np.inf], labels=["C", "B", "A"])
# bins
e["tenure_yrs"] = ((pd.Timestamp("2025-10-27") - e["join_date"]).dt.days / 365.25).round(1)
e = e.assign(name_upper=e["name"].str.upper()).rename(columns={"rating":
"perf"}).drop(columns=["name_upper"])
e["salary_rank"] = e["salary"].rank(ascending=False, method="dense").astype(int)
print(e.head(6))
```

OUTPUT

```
  emp_id              name department       city  join_date  salary  perf    bonus
band grade  tenure_yrs  salary_rank
0   E101         Kavya Iyer         HR     Mumbai 2016-02-28   97000     4   9700.0
Standard     B         9.7            8
1   E102        Imran Reddy    Finance      Delhi 2019-12-14  157000     3  15700.0
Senior     A         5.9            1
2   E103  Harpreet Kulkarni    Finance     Mumbai 2024-10-05  131000     4  13100.0
Senior     A         1.1            4
3   E104          Diya Iyer         HR  Bengaluru 2024-01-02   90000     4   9000.0
Standard     B         1.8            9
4   E105        Simran Iyer         HR  Bengaluru 2017-08-03  139000     4  13900.0
Senior     A         8.2            3
5   E106         Saanvi Rao         HR      Delhi 2025-02-18   83000     4   8300.0
Standard     B         0.7           10
```

**WATCH OUT** **SettingWithCopyWarning**

`sub = df[df.x > 0]; sub["y"] = 1` may warn because `sub` might be a view. Use `df.loc[df.x > 0, "y"] = 1` to change the original, or `sub = df[df.x > 0].copy()` for an independent table. pandas 3 makes copy-on-write the default, which removes the ambiguity.

## Saving results

Python

```
out = s.groupby("region", as_index=False)["sales"].sum()
out.to_csv("region_sales.csv", index=False)
print(open("region_sales.csv").read())
import os; os.remove("region_sales.csv")
```

OUTPUT

```
region,sales
East,46484119.0
North,49018161.0
South,53952768.5
West,51958520.5
```

Also: `to_excel("out.xlsx", sheet_name="Summary", index=False)`, `to_parquet` (fast, typed, compressed), `to_json(orient="records")`, `to_sql`.

## pandas vs Excel vs SQL

| Task | Excel | SQL | pandas |
|---|---|---|---|
| Filter | AutoFilter | `WHERE` | `df[df.x > 5]` / `query` |
| New column | Formula | `SELECT a*b AS c` | `df["c"] = df.a * df.b` |
| Sort | Sort | `ORDER BY` | `sort_values` |
| Lookup | XLOOKUP | `JOIN` | `merge` (Lesson 18) |
| Pivot | PivotTable | `GROUP BY` | `groupby`, `pivot_table` (Lesson 18) |

# Summary

**KEY TAKEAWAYS**

- A DataFrame is a table of Series sharing an index; read files with `read_csv` / `read_excel` and the right options.
- Inspect first: `shape`, `info()`, `describe()`, `value_counts()`, `isna().sum()`, `duplicated().sum()`.
- Select with `[]` (columns), `loc` (labels, end-inclusive) and `iloc` (positions, end-exclusive).
- Filter with boolean masks using `&`, `|`, `~` and brackets, plus `isin`, `between`, `str.contains`, `query`.
- Add columns with vectorised maths, `np.where`, `pd.cut`; use `.loc` or `.copy()` to avoid SettingWithCopy issues.

## Quick quiz

6 questions · tap an answer to check it

**1. What does `s[["region", "sales"]]` return?**

A A Series

B A DataFrame with two columns

C A list

D An error

**Answer: B.** Double brackets pass a list of columns.

**2.** Which is end-inclusive?

A `df.loc[0:2]`

B `df.iloc[0:2]`

C Both

D Neither

**Answer: A.** `loc` uses labels and includes the end label.

**3.** Which filter is correct?

A `df[df.a > 1 and df.b < 5]`

B `df[(df.a > 1) & (df.b < 5)]`

C `df[df.a > 1 & df.b < 5]`

D `df.where(a > 1, b < 5)`

**Answer: B.** Use `&` with brackets around each condition.

**4.** How do you keep leading zeros in a PIN or ID column when reading?

A `parse_dates`

B `dtype={"pin": str}`

C `usecols`

D `index_col`

**Answer: B.** Otherwise pandas reads it as a number.

**5.** Which command shows column types and non-null counts?

A `describe()`

B `info()`

C `head()`

D `shape`

**Answer: B.** `describe()` gives statistics.

**6.** How do you reference a Python variable inside `query`?

A `{var}`

B `@var`

C `$var`

D `var()`

**Answer: B.** `df.query("sales > @big")`.

EXERCISE

### pandas practice (Superstore)

(1) How many orders (unique `order_id`) are there? (2) Show the 5 most profitable sub-categories by total profit. (3) Filter Consumer-segment orders in 2025 with discount above 20%. (4) Add `margin_pct` and list the 3 lowest-margin product names among lines with sales above 20,000. (5) Save the Technology rows to `tech.csv`.

**Show solution (worked answer)**

Python

```
print(s["order_id"].nunique())
print(s.groupby("sub_category")["profit"].sum().nlargest(5))
f = s[(s.segment == "Consumer") & (s.order_date.dt.year == 2025) & (s.discount >
0.2)]; print(len(f))
s["margin_pct"] = 100 * s.profit / s.sales
print(s[s.sales > 20000].nsmallest(3, "margin_pct")[["product_name", "margin_pct"]])
s[s.category == "Technology"].to_csv("tech.csv", index=False)
```

INTERVIEW CORNER

### Questions you may be asked

**Q: loc vs iloc?** `loc` selects by label (and boolean masks), end-inclusive; `iloc` selects by integer position, end-exclusive.

**Q: How do you find and handle duplicates?** `df.duplicated(subset=[...]).sum()` to count, `drop_duplicates(subset=..., keep="first")` to remove, after deciding which columns define a duplicate.

**Q: How do you read a file that does not fit in memory?** `usecols` and `dtype` to shrink it, `chunksize` to stream it, or use DuckDB/Polars/Parquet.

PYTHON FOR DATA SCIENCE · LESSON 17

# pandas II: Data Cleaning: Missing Values, Types, Duplicates, Text and Outliers

Turn messy data into analysis-ready data. Detect and treat missing values, fix data types, remove duplicates, standardise text, parse dates, handle outliers with IQR and caps, and document every step in a reusable cleaning function.


Python class 13 | pandas 2.3 / 3.0 | Intermediate | 120 min

**By the end of this lesson you can**

- Profile a dataset for missing values, wrong types, duplicates and inconsistent categories
- Choose and apply missing-value strategies (drop, fill with statistic, group-wise fill, flag)
- Convert types safely with to_numeric, to_datetime and astype, including categories
- Standardise text columns and map inconsistent labels
- Detect outliers with the IQR rule and z-scores and decide how to treat them

## Why cleaning matters

Analysts often say 60–80% of project time goes into preparing data. Wrong types, gaps, duplicates and typos silently break totals, joins and models: **garbage in, garbage out**.




A repeatable cleaning workflow.

We will clean a deliberately messy extract:

Python

```
import pandas as pd, numpy as np
pd.set_option("display.max_columns", 20); pd.set_option("display.width", 160)
raw = pd.DataFrame({
    "order_id":  ["A1", "A2", "A3", "A3", "A4", "A5", "A6", "A7", "A8"],
    "city":      [" pune", "Pune ", "DELHI", "DELHI", "New Delhi", "kochi", None,
"Bengaluru", "Bangalore"],
    "amount":    ["1,200", "950", "₹3,400", "₹3,400", "abc", "780", "15000", "2,050",
None],
    "order_date":["2025-01-05", "05/01/2025", "2025-01-07", "2025-01-07", "2025-02-30",
"2025-01-09", "2025-01-10", "2025-01-11", "2025-01-12"],
    "qty":       [2, 1, 3, 3, None, 1, 50, 2, 1],
})
print(raw)
print(raw.dtypes.to_dict())
```

OUTPUT

```
  order_id       city  amount  order_date   qty
0       A1       pune   1,200  2025-01-05   2.0
1       A2      Pune       950  05/01/2025   1.0
2       A3      DELHI  ₹3,400  2025-01-07   3.0
3       A3      DELHI  ₹3,400  2025-01-07   3.0
4       A4  New Delhi     abc  2025-02-30   NaN
5       A5      kochi     780  2025-01-09   1.0
6       A6        NaN   15000  2025-01-10  50.0
7       A7  Bengaluru   2,050  2025-01-11   2.0
8       A8  Bangalore     NaN  2025-01-12   1.0
{'order_id': <StringDtype(na_value=nan)>, 'city': <StringDtype(na_value=nan)>,
'amount': <StringDtype(na_value=nan)>, 'order_date': <StringDtype(na_value=nan)>,
'qty': dtype('float64')}
```

## Step 1: Profile

Python

```
def profile(df):
    return pd.DataFrame({"dtype": df.dtypes.astype(str), "missing": df.isna().sum(),
"missing_%": (100 * df.isna().mean()).round(1),
                         "unique": df.nunique(), "example": df.iloc[0]})
print(profile(raw))
print("duplicate rows:", raw.duplicated().sum())
```

OUTPUT

```
              dtype  missing  missing_%  unique     example
order_id        str        0        0.0       8          A1
```

```
city            str        1       11.1       7        pune
amount          str        1       11.1       7       1,200
order_date      str        0        0.0       8  2025-01-05
qty         float64        1       11.1       4         2.0
duplicate rows: 1
```

## Step 2: Fix types

Python

```python
df = raw.drop_duplicates().copy()                                    # exact
duplicates first
df["amount"] = pd.to_numeric(df["amount"].str.replace(r"[₹,]", "", regex=True),
errors="coerce")   # bad values → NaN
df["order_date"] = pd.to_datetime(df["order_date"], format="%Y-%m-%d", errors="coerce")
# strict format: others → NaT
df["qty"] = df["qty"].astype("Int64")                                 # nullable
integer keeps NaN
print(df[["order_id", "amount", "order_date", "qty"]])
print(df.dtypes.to_dict())
```


OUTPUT

```
  order_id   amount order_date   qty
0       A1   1200.0 2025-01-05     2
1       A2    950.0        NaT     1
2       A3   3400.0 2025-01-07     3
4       A4      NaN        NaT  <NA>
5       A5    780.0 2025-01-09     1
6       A6  15000.0 2025-01-10    50
7       A7   2050.0 2025-01-11     2
8       A8      NaN 2025-01-12     1
{'order_id': <StringDtype(na_value=nan)>, 'city': <StringDtype(na_value=nan)>,
'amount': dtype('float64'), 'order_date': dtype('<M8[us]'), 'qty': Int64Dtype()}
```

`errors="coerce"` turns unparseable values into `NaN` / `NaT` so you can count and inspect them instead of crashing. Always check how many values were coerced.

| Conversion | Use |
| --- | --- |
| `pd.to_numeric(s, errors="coerce")` | Text with numbers |
| `pd.to_datetime(s, format=..., dayfirst=True)` | Dates (give the format when known) |
| `s.astype("category")` | Repeated labels: less memory, ordered categories |
| `s.astype("Int64")` , `"boolean"` , `"string"` | Nullable types that allow missing values |

## Step 3: Missing values




Choosing a strategy for missing values.

Python

```
print(df.isna().sum().to_dict())
df["amount_missing"] = df["amount"].isna()                    # flag before
filling
df["amount"] = df["amount"].fillna(df["amount"].median())
df["qty"] = df["qty"].fillna(1)
df = df.dropna(subset=["order_date"])                         # a row without a
valid date is unusable here
print(df[["order_id", "amount", "amount_missing", "qty", "order_date"]])
```

OUTPUT

```
{'order_id': 0, 'city': 1, 'amount': 2, 'order_date': 2, 'qty': 1}
  order_id   amount  amount_missing  qty order_date
0       A1   1200.0           False    2 2025-01-05
2       A3   3400.0           False    3 2025-01-07
```

```
5       A5    780.0          False    1 2025-01-09
6       A6  15000.0          False   50 2025-01-10
7       A7   2050.0          False    2 2025-01-11
8       A8   1625.0           True    1 2025-01-12
```

Real data: `house_prices.csv` has gaps in `area_sqft`. A **group-wise** fill uses similar houses (same number of bedrooms) instead of one global value:

Python

```
h = pd.read_csv("house_prices.csv")
print("missing area:", h["area_sqft"].isna().sum())
by_bed = h.groupby("bedrooms")["area_sqft"].median().round(0)
print(by_bed.to_dict())
h["area_filled"] = h["area_sqft"].fillna(h.groupby("bedrooms")
["area_sqft"].transform("median"))
print("after group-wise fill:", h["area_filled"].isna().sum(), "| global median would
give", h["area_sqft"].median())
```

OUTPUT

```
missing area: 25
{1: 760.0, 2: 1115.0, 3: 1430.0, 4: 1715.0, 5: 1955.0}
after group-wise fill: 0 | global median would give 1240.0
```

NOTE **Missing-data types**

**MCAR** (completely at random) → dropping is safe. **MAR** (depends on other columns) → impute using those columns. **MNAR** (depends on the missing value itself, e.g. high earners hide income) → flag it; imputation can bias results. Never fill target variables for modelling.

## Step 4: Duplicates

Python

```
orders = pd.DataFrame({"order_id": ["B1", "B2", "B2", "B3"], "status": ["new", "new",
"shipped", "new"], "updated": pd.to_datetime(["2025-01-01", "2025-01-01", "2025-01-03",
"2025-01-02"])})
print(orders.duplicated().sum(), orders.duplicated(subset="order_id").sum())
latest = orders.sort_values("updated").drop_duplicates(subset="order_id", keep="last")   #
keep the latest version per key
print(latest)
```

OUTPUT

```
0 1
  order_id   status    updated
0       B1      new 2025-01-01
3       B3      new 2025-01-02
2       B2  shipped 2025-01-03
```

Decide which columns define "the same record"; exact duplicates and key duplicates are different problems.

## Step 5: Text and categories

Python

```python
df["city"] = df["city"].str.strip().str.title()
fix = {"New Delhi": "Delhi", "Bangalore": "Bengaluru"}
df["city"] = df["city"].replace(fix).fillna("Unknown")
print(df["city"].value_counts().to_dict())
print(pd.Series(["  Data  Science ", "MACHINE learning"]).str.split().str.join("
").str.capitalize().tolist())
```

OUTPUT

```
{'Bengaluru': 2, 'Pune': 1, 'Delhi': 1, 'Kochi': 1, 'Unknown': 1}
['Data science', 'Machine learning']
```

Useful `.str` methods: `strip`, `lower/upper/title`, `replace`, `contains`, `startswith`, `extract`, `split`, `len`, `zfill`, `slice`. For fuzzy spellings, libraries such as **rapidfuzz** score string similarity.

## Step 6: Outliers


An **outlier** is far from most values. It may be an error (qty = 50 typed instead of 5) or real (one bulk order). Detect first, then decide.

Python

```python
hr = pd.read_csv("hr_employees.csv")
inc = hr["monthly_income"]
q1, q3 = inc.quantile([0.25, 0.75]); iqr = q3 - q1
lo, hi = q1 - 1.5 * iqr, q3 + 1.5 * iqr
print(f"Q1 {q1:,.0f} | Q3 {q3:,.0f} | IQR fences {lo:,.0f} to {hi:,.0f}")
out = hr[(inc < lo) | (inc > hi)]
print(len(out), "IQR outliers;", out["job_title"].value_counts().head(3).to_dict())
z = (inc - inc.mean()) / inc.std()
print((z.abs() > 3).sum(), "rows with |z| > 3")
capped = inc.clip(lower=inc.quantile(0.01), upper=inc.quantile(0.99))    # winsorise at 1st/99th percentile
print(f"max before {inc.max():,.0f} after capping {capped.max():,.0f}")
```

OUTPUT

```
Q1 58,062 | Q3 101,833 | IQR fences -7,594 to 167,489
29 IQR outliers; {'Sales Manager': 6, 'Finance Manager': 5, 'Operations Manager': 5}
19 rows with |z| > 3
max before 218,417 after capping 182,086
```




Monthly income: the box plot marks values beyond the IQR fences as points.

Senior roles earn more, so high incomes here are **real**, not errors. Options: keep them, analyse by job level, use medians, log-transform, or cap for models that are sensitive to extremes. Delete only values that are clearly impossible (negative age, qty 50 in a 1–5 item shop).

# A reusable cleaning function

Python

```
def clean_orders(raw: pd.DataFrame) -> pd.DataFrame:
    """Return cleaned orders and print a short audit log."""
    df = raw.drop_duplicates().copy(); log = {"rows_in": len(raw), "dupes_removed":
len(raw) - len(df)}
    df["amount"] = pd.to_numeric(df["amount"].str.replace(r"[₹,]", "", regex=True),
errors="coerce")
    df["order_date"] = pd.to_datetime(df["order_date"], format="%Y-%m-%d", errors="coerce")
    log["bad_dates_dropped"] = int(df["order_date"].isna().sum()); df = df.dropna(subset=
["order_date"])
    log["amount_imputed"] = int(df["amount"].isna().sum()); df["amount"] =
df["amount"].fillna(df["amount"].median())
    df["city"] = df["city"].str.strip().str.title().replace({"New Delhi": "Delhi",
"Bangalore": "Bengaluru"}).fillna("Unknown")
    df["qty"] = df["qty"].fillna(1).clip(upper=10).astype(int); log["rows_out"] = len(df)
    print(log); return df
clean = clean_orders(raw)
assert clean["amount"].notna().all() and clean["order_id"].is_unique
print(clean)
```

OUTPUT

```
{'rows_in': 9, 'dupes_removed': 1, 'bad_dates_dropped': 2, 'amount_imputed': 1,
'rows_out': 6}
  order_id       city   amount order_date  qty
0       A1       Pune   1200.0 2025-01-05    2
2       A3      Delhi   3400.0 2025-01-07    3
5       A5      Kochi    780.0 2025-01-09    1
6       A6    Unknown  15000.0 2025-01-10   10
7       A7  Bengaluru   2050.0 2025-01-11    2
8       A8  Bengaluru   2050.0 2025-01-12    1
```

# Summary

**KEY TAKEAWAYS**

- Profile first: dtypes, missing counts, uniques, duplicates, odd categories.
- Convert with `to_numeric` / `to_datetime(errors="coerce")` and count what was coerced; use nullable and category dtypes.
- Missing values: drop, fill (median, mode, group-wise `transform`), forward-fill, or flag; think about why they are missing.
- Define duplicates by key; `sort_values + drop_duplicates(keep="last")` keeps the latest record.
- Standardise text with `.str` and mapping dictionaries; detect outliers with IQR or z-scores and treat them deliberately.
- Wrap cleaning in a function with an audit log and assertions so it is repeatable.

## Quick quiz

6 questions · tap an answer to check it

**1. What does `pd.to_numeric(s, errors="coerce")` do with "abc"?**

A Raises an error

B Converts it to NaN

C Keeps it as text

D Converts it to 0

**Answer: B.** You can then count and inspect the NaNs.

**2.** Which fill keeps group differences?

A `fillna(df.col.mean())`

B `fillna(df.groupby("g")["col"].transform("median"))`

C `dropna()`

D `fillna(0)`

**Answer: B.** `transform` returns a value per row from its group.

**3.** What are the IQR outlier fences?

A mean ± 2 sd

B Q1 − 1.5×IQR and Q3 + 1.5×IQR

C min and max

D median ± IQR

**Answer: B.** The IQR is Q3 − Q1.

**4.** How do you keep the latest record per order_id?

A `drop_duplicates()`

B Sort by update time, then `drop_duplicates(subset="order_id", keep="last")`

C `groupby().first()` without sorting

D `unique()`

**Answer: B.** Sorting decides which copy is "last".

**5. Why add an `is_missing` flag before filling?**

A Required by pandas

B The fact that a value was missing can itself be informative

C It speeds up filling

D To delete the column later

**Answer: B.** Models and analysts can use the flag.

**6. Which dtype allows integers with missing values?**

A int64

B Int64 (nullable)

C float32 only

D object

**Answer: B.** The capital-I `Int64` is pandas' nullable integer.

EXERCISE

### Cleaning practice

Using `hr_employees.csv`: (1) profile every column. (2) Convert `hire_date` to datetime and compute tenure in years. (3) Check whether `years_at_company` agrees with the hire date. (4) Make `education` an ordered category. (5) Find income outliers per department using the IQR rule within each department.

**Show solution (worked answer)**

Python

```
hr = pd.read_csv("hr_employees.csv")
print(profile(hr))
hr["hire_date"] = pd.to_datetime(hr["hire_date"])
hr["tenure"] = ((pd.Timestamp("2025-12-31") - hr.hire_date).dt.days / 365.25).round(1)
print((hr["tenure"].round() - hr["years_at_company"]).abs().describe())
print(hr["education"].unique())
def iqr_flag(x):
    q1, q3 = x.quantile([.25, .75]); i = q3 - q1
    return (x < q1 - 1.5 * i) | (x > q3 + 1.5 * i)
hr["income_outlier"] = hr.groupby("department")["monthly_income"].transform(iqr_flag)
print(hr.groupby("department")["income_outlier"].sum())
```

INTERVIEW CORNER

### Questions you may be asked

**Q: How do you handle missing values?** First find out why they are missing and how many. Then drop (few, random), impute (median/mode, group-wise, model-based, forward-fill for time series) or flag. Impute after the train/test split in ML to avoid leakage.

**Q: How do you treat outliers?** Check whether they are errors or real. Fix or remove errors; for real extremes use robust statistics (median), transformations (log), capping, or models robust to outliers.

**Q: What checks do you run before trusting a dataset?** Row counts vs source, uniqueness of keys, missing rates, value ranges, valid categories, date ranges, and totals reconciled to a trusted report.

PYTHON FOR DATA SCIENCE · LESSON 18

# pandas III: GroupBy, Pivot Tables, Merge/Join and Reshape (melt/unpivot)

Summarise and combine data. Use groupby with agg, transform and filter, build pivot tables and crosstabs, join tables with merge (inner, left, right, outer, anti), stack with concat, and reshape between wide and long with melt, pivot, stack and unstack.


Python class 14 | pandas 2.3 / 3.0 | Intermediate | 120 min

**By the end of this lesson you can**

- Apply split-apply-combine with groupby, named aggregations and multiple keys
- Use transform for group-level columns and filter for group-level conditions
- Build pivot_table and crosstab summaries with totals and percentages
- Join DataFrames with merge, choose the join type, and validate the result
- Reshape wide ↔ long with melt (unpivot) and pivot, and combine with concat

## Split–apply–combine

`groupby` **splits** rows into groups, **applies** a calculation to each group, and **combines** the results. It is SQL's `GROUP BY` and Excel's PivotTable.




groupby splits rows by key, applies an aggregation per group, and combines the answers.

Python

```
import pandas as pd, numpy as np
pd.set_option("display.max_columns", 20); pd.set_option("display.width", 160)
s = pd.read_csv("superstore_sales.csv", parse_dates=["order_date"])
print(s.groupby("region")["sales"].sum().sort_values(ascending=False))
print(s.groupby(["region", "category"])["profit"].sum().round(0).unstack())
```

OUTPUT

```
region
South    53952768.5
West     51958520.5
North    49018161.0
East     46484119.0
Name: sales, dtype: float64
category  Furniture  Office Supplies  Technology
region
East       -209426.0         434731.0   4149185.0
North      -236825.0         331848.0   4460806.0
South      -259193.0         349958.0   4611247.0
West       -112710.0         398257.0   4434286.0
```

## Named aggregations

Python

```
summary = (s.groupby("category")
            .agg(orders=("order_id", "nunique"), lines=("row_id", "size"), sales=("sales",
"sum"),
                 profit=("profit", "sum"), avg_discount=("discount", "mean"), max_line=
("sales", "max"))
            .assign(margin_pct=lambda d: (100 * d.profit / d.sales).round(1))
            .sort_values("sales", ascending=False))
print(summary.round(2))
print(s.groupby("segment", as_index=False)["sales"].agg(["sum", "mean", "median",
"count"]).round(0))
```

OUTPUT

```
                orders  lines        sales       profit  avg_discount  max_line
margin_pct
category
Technology        1518   1892  156438412.5  17655523.58          0.07  619290.0
11.3
Furniture         1511   1917   34841853.0   -818153.31          0.13   93120.0
-2.3
Office Supplies   1870   2514   10133303.5   1514793.58          0.07   60830.0
```

```
14.9
       segment         sum     mean  median  count
0     Consumer  98603292.0  32066.0  8288.0   3075
1    Corporate  59113619.0  31427.0  8480.0   1881
2  Home Office  43696658.0  31965.0  9079.0   1367
```

Common aggregations: `sum`, `mean`, `median`, `min`, `max`, `count` (non-null), `size` (rows), `nunique`, `std`, `first`, `last`, or your own function.

## transform and filter

`transform` returns a value **for every row** (the group result broadcast back), perfect for "share of group" and group-wise filling. `filter` keeps whole groups that meet a condition.

Python

```python
s["region_sales"] = s.groupby("region")["sales"].transform("sum")
s["share_of_region_%"] = (100 * s["sales"] / s["region_sales"]).round(3)
s["rank_in_region"] = s.groupby("region")["sales"].rank(ascending=False,
method="first").astype(int)
print(s.loc[s.rank_in_region ⩽ 2, ["region", "product_name", "sales", "share_of_region_%",
"rank_in_region"]].sort_values(["region", "rank_in_region"]))
loyal = s.groupby("customer_id").filter(lambda g: g["order_id"].nunique() ⩾ 8)
print(loyal["customer_id"].nunique(), "customers placed 8+ orders")
```

OUTPUT

```
     region       product_name     sales  share_of_region_%  rank_in_region
6244   East  Vertex Copier 262  472740.0              1.017               1
4219   East   Orbit Copier 746  442350.0              0.952               2
3669  North   Orbit Copier 746  619290.0              1.263               1
1653  North   Orbit Copier 746  526396.5              1.074               2
1142  South  Vertex Copier 262  551530.0              1.022               1
2087  South  Vertex Copier 262  551530.0              1.022               2
1779   West    Apex Copier 347  493080.0              0.949               1
3317   West   Orbit Copier 746  477738.0              0.919               2
41 customers placed 8+ orders
```

## Pivot tables and crosstabs

Python


```
s["year"] = s["order_date"].dt.year
pt = pd.pivot_table(s, values="sales", index="category", columns="year", aggfunc="sum",
margins=True, margins_name="Total")
print((pt / 1e6).round(2))
print(pd.crosstab(s["segment"], s["ship_mode"], normalize="index").mul(100).round(1))
# row %
```

OUTPUT

```
year              2023   2024   2025   Total
category
Furniture         9.95  12.13  12.76   34.84
Office Supplies   2.61   3.55   3.97   10.13
Technology       45.08  49.72  61.65  156.44
Total            57.64  65.40  78.38  201.41
ship_mode    First Class  Same Day  Second Class  Standard Class
segment
Consumer            15.2       5.5          19.5            59.8
Corporate           13.2       5.0          20.3            61.5
Home Office         16.9       4.3          19.5            59.3
```

## Merging (joins)

Real analysis needs several tables. `pd.merge` (or `df.merge`) joins on key columns like SQL joins.




Join types: which rows survive.

Python

```python
orders = pd.DataFrame({"order_id": [1, 2, 3, 4], "cust": ["C1", "C2", "C2", "C9"],
"amount": [500, 250, 900, 120]})
cust = pd.DataFrame({"cust": ["C1", "C2", "C3"], "name": ["Asha", "Ravi", "Meera"], "city":
["Pune", "Delhi", "Kochi"]})
for how in ["inner", "left", "right", "outer"]:
    print(how, "→", len(orders.merge(cust, on="cust", how=how)), "rows")
print(orders.merge(cust, on="cust", how="left", indicator=True))
anti = orders.merge(cust, on="cust", how="left", indicator=True).query("_merge ==
'left_only'")
print("orders with unknown customer:", anti["order_id"].tolist())
```

OUTPUT

```
inner → 3 rows
left → 4 rows
right → 4 rows
outer → 5 rows
   order_id cust  amount  name   city     _merge
0         1   C1     500  Asha   Pune       both
1         2   C2     250  Ravi  Delhi       both
2         3   C2     900  Ravi  Delhi       both
3         4   C9     120   NaN    NaN  left_only
orders with unknown customer: [4]
```

| Argument | Use |
|---|---|
| `on="key"` / `on=["a", "b"]` | Same column name(s) in both |
| `left_on=` , `right_on=` | Different key names |
| `how=` | `inner` , `left` , `right` , `outer` , `cross` |
| `suffixes=("_x", "_y")` | Clashing column names |
| `indicator=True` | Adds `_merge` to see where each row came from |
| `validate="many_to_one"` | Raises an error if the key is not unique on the right |

## A real three-table join

Python

```
products = pd.read_csv("products.csv"); customers = pd.read_csv("customers.csv")
lines = s[["order_id", "customer_id", "product_id", "sales", "quantity"]]
full = (lines.merge(products[["product_id", "list_price"]], on="product_id", how="left",
validate="many_to_one")
             .merge(customers[["customer_id", "city", "segment"]], on="customer_id",
how="left", validate="many_to_one"))
print(len(lines), len(full), full["list_price"].isna().sum(), "unmatched products")
full["realised_vs_list_%"] = (100 * full["sales"] / (full["list_price"] *
full["quantity"])).round(1)
print(full.groupby("segment")["realised_vs_list_%"].mean().round(1))
```

OUTPUT

```
6323 6323 0 unmatched products
segment
Consumer       91.0
Corporate      91.1
Home Office    90.4
Name: realised_vs_list_%, dtype: float64
```

WATCH OUT **Row explosion**

If the key is duplicated on **both** sides, a merge multiplies rows (many-to-many). Always compare row counts before and after, and use `validate=` to catch it.

# concat: stacking tables

Python

```
jan = pd.DataFrame({"store": ["A", "B"], "sales": [100, 80]}); feb = pd.DataFrame({"store":
["A", "C"], "sales": [120, 60]})
print(pd.concat([jan.assign(month="Jan"), feb.assign(month="Feb")], ignore_index=True))
# rows (UNION ALL)
print(pd.concat([jan.set_index("store"), feb.set_index("store")], axis=1, keys=["Jan",
"Feb"]))   # columns, aligned on index
```


OUTPUT

```
  store  sales month
0     A    100   Jan
1     B     80   Jan
2     A    120   Feb
```

```
3     C     60   Feb
         Jan    Feb
       sales  sales
store
A      100.0  120.0
B       80.0    NaN
C        NaN   60.0
```

## Reshaping: wide ↔ long

**Wide** tables are easy to read (one column per month); **long** (tidy) tables are easy to analyse and chart (one row per observation). `melt` is pandas' **unpivot** (the same as Power Query's "Unpivot columns").




melt turns columns into rows; pivot turns rows into columns.

Python

```python
wide = pd.DataFrame({"region": ["North", "South"], "Jan": [10, 8], "Feb": [12, 11], "Mar": [9, 14]})
long = wide.melt(id_vars="region", var_name="month", value_name="sales")
print(long)
back = long.pivot(index="region", columns="month", values="sales")[["Jan", "Feb", "Mar"]]
print(back)
st = back.stack(); print(st.head(3)); print(st.unstack().equals(back))
```

OUTPUT

```
  region month  sales
0  North   Jan     10
1  South   Jan      8
```

```
2  North   Feb     12
3  South   Feb     11
4  North   Mar      9
5  South   Mar     14
month   Jan  Feb  Mar
region
North    10   12    9
South     8   11   14
region  month
North   Jan      10
        Feb      12
        Mar       9
dtype: int64
True
```

`pivot` requires unique index/column pairs; `pivot_table` aggregates duplicates.

Python

```
monthly = (s.assign(month=s.order_date.dt.to_period("M").astype(str))
            .pivot_table(index="month", columns="category", values="sales",
aggfunc="sum").tail(3) / 1e6).round(2)
print(monthly)
print(monthly.reset_index().melt(id_vars="month", var_name="category",
value_name="sales_m").head(4))
```

OUTPUT

```
category  Furniture  Office Supplies  Technology
month
2025-10        1.15             0.31        4.68
2025-11        1.07             0.59        8.62
2025-12        1.31             0.40        5.94
     month         category  sales_m
0  2025-10        Furniture     1.15
1  2025-11        Furniture     1.07
2  2025-12        Furniture     1.31
3  2025-10  Office Supplies     0.31
```

# Summary

**KEY TAKEAWAYS**

- `groupby(keys).agg(name=(col, func))` builds clean summaries; `transform` returns group values per row; `filter` keeps whole groups.
- `pivot_table` (with `margins=True`) and `crosstab` (with `normalize`) mirror Excel PivotTables.
- `merge(on=, how=)` joins tables; check row counts, use `indicator=True` for anti-joins and `validate=` to prevent row explosions.
- `concat` stacks rows (or aligns columns).
- `melt` = unpivot (wide → long); `pivot` / `pivot_table` = long → wide; `stack` / `unstack` move index levels.

## Quick quiz

6 questions · tap an answer to check it

**1. Which returns one value per original row?**

A `groupby().agg()`

B `groupby().transform()`

C `groupby().size()`

D `pivot_table()`

**Answer: B.** transform broadcasts the group result back to each row.

**2.** Which merge keeps every order even when the customer is missing?

A inner

B left (orders on the left)

C right

D cross

**Answer: B.** Unmatched customer columns become NaN.

**3.** How do you find rows in A with no match in B?

A inner merge

B left merge with `indicator=True` and keep `_merge == "left_only"`

C outer merge without indicator

D concat

**Answer: B.** This is an anti-join.

**4.** What does `melt` do?

A Pivots long to wide

B Unpivots wide columns into rows (long format)

C Merges tables

D Deletes columns

**Answer: B.** `pivot` goes the other way.

**5.** A merge produced more rows than the left table. Most likely cause?

A A bug in pandas

B Duplicate keys on the right side

C Missing values

D Wrong dtype

**Answer: B.** Use `validate="many_to_one"` to catch this.

**6.** How do you add a grand-total row and column to a pivot table?

A `totals=True`

B `margins=True`

C `sum=True`

D `fill_value=0`

**Answer: B.** `margins_name` changes the label.

EXERCISE

### GroupBy and merge practice

(1) Sales and profit by year and region, with margin %. (2) For each customer, the share of their spend in each category (use `transform`). (3) Top product per sub-category by profit. (4) Customers in `customers.csv` with no orders (anti-join). (5) Melt the year columns of a category × year pivot back to long format.

**Show solution (worked answer)**

Python

```
yr = s.groupby(["year", "region"]).agg(sales=("sales", "sum"), profit=("profit",
"sum"))
yr["margin_%"] = (100 * yr.profit / yr.sales).round(1); print(yr)
cc = s.groupby(["customer_id", "category"])["sales"].sum().reset_index()
cc["share"] = cc.sales / cc.groupby("customer_id")["sales"].transform("sum")
top = s.groupby(["sub_category", "product_name"])
["profit"].sum().reset_index().sort_values("profit").groupby("sub_category").tail(1)
no_orders = customers.merge(s[["customer_id"]].drop_duplicates(), how="left",
indicator=True).query("_merge == 'left_only'")
print(len(no_orders))
pt = s.pivot_table(index="category", columns="year", values="sales", aggfunc="sum")
print(pt.reset_index().melt(id_vars="category", var_name="year", value_name="sales"))
```

INTERVIEW CORNER

### Questions you may be asked

**Q: Difference between `agg` and `transform`?** `agg` reduces each group to one row; `transform` returns an output aligned to the original rows.

**Q: How would you compute each product's share of its category's sales?** `df.sales / df.groupby("category").sales.transform("sum")`.

**Q: merge vs join vs concat?** `merge` joins on columns (SQL-style); `join` is a shortcut that joins on the index; `concat` stacks along an axis without matching keys.

**Q: What is tidy data?** Each variable is a column, each observation a row, each value a cell; long format produced by `melt` is tidy.

PYTHON FOR DATA SCIENCE · LESSON 19

# pandas IV: Dates, Time Series, Resampling and Rolling Windows

Work with time. Parse dates, extract parts with .dt, do date arithmetic, set a DatetimeIndex, resample to weeks, months and quarters, compute rolling and expanding windows, shifts and growth rates, and build a cohort-style monthly report with the daily sales data.

Python class 15 | pandas 2.3 / 3.0 | Intermediate | 110 min

**By the end of this lesson you can**

- Parse and format dates and extract year, month, weekday and quarter
- Do date arithmetic with Timedelta and DateOffset, including business days
- Resample time series and use rolling, expanding and exponentially weighted windows
- Compute period-over-period change, year-over-year growth and cumulative totals with shift, pct_change and cumsum
- Handle time zones and missing dates

## Parsing dates

Python

```
import pandas as pd, numpy as np
pd.set_option("display.max_columns", 20); pd.set_option("display.width", 160)
d = pd.to_datetime(pd.Series(["2025-01-15", "2025-03-01", "2025-12-31"]))
print(d.dt.year.tolist(), d.dt.month_name().tolist(), d.dt.day_name().tolist(),
d.dt.quarter.tolist(), d.dt.isocalendar().week.tolist())
print(pd.to_datetime("05/01/2025", dayfirst=True).date(),
pd.to_datetime("05/01/2025").date())     # 5 Jan vs 1 May!
print(pd.to_datetime("2025-01-15 14:30").strftime("%d %b %Y, %I:%M %p"),
pd.Timestamp("2025-02-28").is_month_end)
```

OUTPUT

```
[2025, 2025, 2025] ['January', 'March', 'December'] ['Wednesday', 'Saturday',
'Wednesday'] [1, 1, 4] [3, 9, 1]
```

```
2025-01-05 2025-05-01
15 Jan 2025, 02:30 PM True
```

**WATCH OUT** **Day-first dates**

Indian and European data often write 05/01/2025 for 5 January. Pass `dayfirst=True` or, better, an explicit `format="%d/%m/%Y"`. Check a few parsed values every time.

| `.dt` accessor | Gives |
|---|---|
| `.year`, `.month`, `.day`, `.hour` | Parts |
| `.day_name()`, `.month_name()` | Text names |
| `.dayofweek` (Mon = 0), `.quarter`, `.isocalendar().week` | Calendar positions |
| `.to_period("M")`, `.to_period("Q")` | Month / quarter periods |
| `.floor("D")`, `.normalize()` | Truncate time |
| `.is_month_end`, `.days_in_month` | Calendar flags |

## Date arithmetic

Python

```python
s = pd.read_csv("superstore_sales.csv", parse_dates=["order_date", "ship_date"])
s["ship_days"] = (s["ship_date"] - s["order_date"]).dt.days
print(s.groupby("ship_mode")["ship_days"].agg(["mean", "max"]).round(1))
t = pd.Timestamp("2025-01-31")
print(t + pd.Timedelta(days=30), t + pd.DateOffset(months=1), t + pd.offsets.MonthEnd(1), t
+ pd.offsets.BDay(3))
print(np.busday_count("2025-10-01", "2025-11-01"), "working days in October 2025 (Mon-
Fri)")
print(pd.date_range("2025-01-01", periods=4, freq="W-MON").date.tolist(),
pd.date_range("2025-01-01", "2025-06-30", freq="QE").date.tolist())
```

OUTPUT

```
                mean  max
ship_mode
First Class      1.5    2
Same Day         0.0    0
Second Class     3.0    4
Standard Class   5.6    7
2025-03-02 00:00:00 2025-02-28 00:00:00 2025-02-28 00:00:00 2025-02-05 00:00:00
```

```
23 working days in October 2025 (Mon-Fri)
[datetime.date(2025, 1, 6), datetime.date(2025, 1, 13), datetime.date(2025, 1, 20),
datetime.date(2025, 1, 27)] [datetime.date(2025, 3, 31), datetime.date(2025, 6, 30)]
```

`Timedelta` adds exact durations; `DateOffset` and offsets follow the calendar (month ends, business days).

## A time series with a DatetimeIndex

Python

```python
daily = pd.read_csv("daily_sales.csv", parse_dates=["date"]).set_index("date").sort_index()
print(daily.shape, daily.index.min().date(), "to", daily.index.max().date())
print(daily.loc["2023-03"].head(3))                    # partial-string indexing: all of March 2023
print(daily.loc["2023-12-24":"2023-12-27"])
full = pd.date_range(daily.index.min(), daily.index.max(), freq="D")
print("missing days:", len(full.difference(daily.index)))
```

OUTPUT

```
(1461, 1) 2022-01-01 to 2025-12-31
            units_sold
date
2023-03-01         260
2023-03-02         272
2023-03-03         234
            units_sold
date
2023-12-24         343
2023-12-25         270
2023-12-26         232
2023-12-27         257
missing days: 0
```

## Resampling

`resample` is `groupby` for time: change the frequency and aggregate.

Python

```
monthly = daily["units_sold"].resample("ME").sum()
print(monthly.head(4))
q = daily["units_sold"].resample("QE").agg(["sum", "mean", "max"]).round(1)
print(q.tail(4))
wk = daily["units_sold"].resample("W-SUN").sum()
print(wk.describe().round(0))
print(daily.groupby(daily.index.day_name())
["units_sold"].mean().round(1).sort_values(ascending=False))
```

OUTPUT

```
date
2022-01-31    5998
2022-02-28    5797
2022-03-31    6756
2022-04-30    7156
Freq: ME, Name: units_sold, dtype: int64
              sum   mean  max
date
2025-03-31  30462  338.5  405
2025-06-30  34592  380.1  440
2025-09-30  34786  378.1  432
2025-12-31  33080  359.6  415
count     210.0
mean     2073.0
std       391.0
min       420.0
25%      1766.0
50%      2073.0
75%      2362.0
max      2801.0
Name: units_sold, dtype: float64
date
Sunday       323.3
Saturday     320.4
Friday       289.5
Tuesday      288.6
Thursday     288.5
Monday       287.9
Wednesday    287.3
Name: units_sold, dtype: float64
```

Frequencies: `D` day, `W` week, `ME` month end, `MS` month start, `QE` quarter, `YE` year, `h` hour, `min` minute.


# Rolling and expanding windows

Python

```
ts = daily["units_sold"]
df = pd.DataFrame({"units": ts, "ma_7": ts.rolling(7).mean(), "ma_30":
ts.rolling(30).mean(), "ewm_14": ts.ewm(span=14).mean(),
                   "max_so_far": ts.expanding().max(), "cum_units": ts.cumsum()})
print(df.iloc[[0, 6, 29, 400, -1]].round(1))
```

OUTPUT

| date | units | ma_7 | ma_30 | ewm_14 | max_so_far | cum_units |
|---|---|---|---|---|---|---|
| 2022-01-01 | 202 | NaN | NaN | 202.0 | 202.0 | 202 |
| 2022-01-07 | 154 | 181.1 | NaN | 176.0 | 218.0 | 1268 |
| 2022-01-30 | 239 | 198.0 | 193.7 | 203.2 | 246.0 | 5811 |
| 2023-02-05 | 273 | 252.6 | 244.1 | 251.9 | 305.0 | 93681 |
| 2025-12-31 | 351 | 362.6 | 357.9 | 359.0 | 440.0 | 435285 |




Daily units with 7-day and 30-day moving averages: averages smooth out daily noise and reveal trend and seasonality.

## Shifts and growth

Python

```python
m = monthly.to_frame("units")
m["prev_month"] = m["units"].shift(1)
m["mom_%"] = (100 * m["units"].pct_change()).round(1)
m["yoy_%"] = (100 * m["units"].pct_change(12)).round(1)          # same month last year
m["ytd"] = m.groupby(m.index.year)["units"].cumsum()
print(m.tail(4))
yr = daily["units_sold"].resample("YE").sum()
print(yr, (100 * yr.pct_change()).round(1).tolist())
```

OUTPUT

```
            units  prev_month  mom_%  yoy_%     ytd
date
2025-09-30  11071     11798.0   -6.2   12.3   99840
2025-10-31  11291     11071.0    2.0   15.3  111131
2025-11-30  10721     11291.0   -5.0   14.7  121852
2025-12-31  11068     10721.0    3.2   15.1  132920
date
2022-12-31     85031
2023-12-31    100536
2024-12-31    116798
2025-12-31    132920
Freq: YE-DEC, Name: units_sold, dtype: int64 [nan, 18.2, 16.2, 13.8]
```

`shift(1)` is SQL's `LAG`; `shift(-1)` is `LEAD`; `pct_change(12)` on monthly data is year-over-year growth.

## Time zones

Python

```python
ts_utc = pd.Timestamp("2025-03-10 09:00", tz="UTC")
print(ts_utc.tz_convert("Asia/Kolkata"), ts_utc.tz_convert("America/New_York"))
naive = pd.Series(pd.to_datetime(["2025-03-10 09:00"]))
print(naive.dt.tz_localize("Asia/Kolkata").dt.tz_convert("UTC").tolist())
```

OUTPUT

```
2025-03-10 14:30:00+05:30 2025-03-10 05:00:00-04:00
[Timestamp('2025-03-10 03:30:00+0000', tz='UTC')]
```

Store timestamps in UTC; convert to local time only for reporting.

## Mini case: monthly KPI report

Python

```
s["month"] = s["order_date"].dt.to_period("M")
kpi = s.groupby("month").agg(sales=("sales", "sum"), orders=("order_id", "nunique"),
customers=("customer_id", "nunique"))
kpi["aov"] = (kpi.sales / kpi.orders).round(0)
kpi["sales_3m_avg"] = kpi.sales.rolling(3).mean().round(0)
kpi["yoy_%"] = (100 * kpi.sales.pct_change(12)).round(1)
print((kpi.tail(6).assign(sales=lambda d: (d.sales / 1e6).round(2), sales_3m_avg=lambda d:
(d.sales_3m_avg / 1e6).round(2))))
first = s.groupby("customer_id")
["order_date"].min().dt.to_period("M").rename("first_month")
s2 = s.join(first, on="customer_id")
new_vs_repeat = s2.assign(kind=np.where(s2.month == s2.first_month, "new",
"repeat")).groupby(["month", "kind"])["customer_id"].nunique().unstack().tail(3)
print(new_vs_repeat)
```

OUTPUT

```
         sales  orders  customers      aov  sales_3m_avg  yoy_%
month
2025-07   7.19      99         91  72627.0          5.86   49.2
2025-08   5.80      99         91  58608.0          5.65    0.8
2025-09   8.47     107        101  79141.0          7.15   58.9
2025-10   6.14     124        115  49518.0          6.80  -15.4
2025-11  10.28     152        139  67661.0          8.30   41.2
2025-12   7.65     134        121  57106.0          8.03   15.3
kind     new  repeat
month
2025-10  8.0   107.0
2025-11  4.0   135.0
2025-12  5.0   116.0
```

# Summary

**KEY TAKEAWAYS**

- Parse with `pd.to_datetime` (give `format` or `dayfirst`); use `.dt` for parts and `to_period` for months/quarters.
- `Timedelta` = exact duration; `DateOffset` / `MonthEnd` / `BDay` = calendar-aware moves; `date_range` builds calendars.
- A sorted `DatetimeIndex` allows partial-string slicing ( `df.loc["2025-03"]` ) and `resample`.
- Rolling, expanding and EWM windows smooth series; `shift` = lag/lead, `pct_change(n)` = growth, `cumsum` = running totals.
- Keep timestamps in UTC, check for missing dates, and convert for display.

## Quick quiz

6 questions · tap an answer to check it

**1. What does `daily.resample("ME").sum()` produce?**

A Daily totals

B Monthly totals (labelled at month end)

C A 7-day average

D An error

**Answer: B.** ME = month end frequency.

**2.** Which gives year-over-year growth on monthly data?

A `pct_change(1)`

B `pct_change(12)`

C `shift(-12)`

D `rolling(12).mean()`

**Answer: B.** Compare each month with the same month a year earlier.

**3.** `shift(1)` is equivalent to which SQL function?

A LAG

B LEAD

C ROW_NUMBER

D NTILE

**Answer: A.** `shift(-1)` is LEAD.

**4.** How do you parse "05/01/2025" as 5 January?

A `pd.to_datetime(x)`

B `pd.to_datetime(x, dayfirst=True)` or `format="%d/%m/%Y"`

C `.dt.day`

D `astype(str)`

**Answer: B.** The default assumes month first.

**5.** What does `ts.rolling(7).mean()` give for the first 6 rows?

**A** 0

**B** NaN (not enough values yet)

**C** The value itself

**D** An error

**Answer: B.** Use `min_periods=1` to allow partial windows.

**6.** What is the difference between `Timedelta(days=30)` and `DateOffset(months=1)` from 31 Jan?

**A** Timedelta adds exactly 30 days (2 Mar); DateOffset moves to the same day next month, clipped to 28 Feb

**B** They are identical

**C** Timedelta is calendar-aware

**D** DateOffset adds 30 days

**Answer: A.** Use calendar offsets for month logic.

EXERCISE

### Time-series practice (daily_sales.csv)

(1) Which month had the highest total units? (2) Compute the 28-day rolling sum and its maximum. (3) Average units by weekday and month (a heatmap-ready pivot). (4) Year-over-year growth by quarter. (5) Flag days where units exceed the 30-day average by 50%.

**Show solution (worked answer)**

Python

```
print(monthly.idxmax(), monthly.max())
print(ts.rolling(28).sum().max())
pv = daily.assign(wd=daily.index.day_name(),
m=daily.index.month).pivot_table(index="wd", columns="m", values="units_sold",
aggfunc="mean").round(0)
qq = ts.resample("QE").sum(); print((100 * qq.pct_change(4)).round(1).dropna())
spikes = daily[ts > 1.5 * ts.rolling(30).mean()]; print(len(spikes))
```

INTERVIEW CORNER

### Questions you may be asked

**Q: resample vs groupby?** `resample` is a time-based groupby on a DatetimeIndex that also creates empty periods; `groupby` with `dt.to_period` is similar but only returns periods present in the data.

**Q: How do you compute a 7-day moving average in pandas and in SQL?** `s.rolling(7).mean()` ; in SQL `AVG(x) OVER (ORDER BY d ROWS BETWEEN 6 PRECEDING AND CURRENT ROW)` .

**Q: How do you handle missing dates in a daily series?** Reindex to a full `date_range` , then decide: fill with 0 (no sales), forward-fill (stock levels), or interpolate (sensor readings).

PYTHON FOR DATA SCIENCE · LESSON 20

# Data Visualisation I: Matplotlib and Choosing the Right Chart


Pick the right chart for the question and build it with Matplotlib's object-oriented API. Line, bar, histogram, scatter, box and pie charts, subplots, annotations, styling and saving, plus design rules that make charts honest and readable.

Python class 16 · Matplotlib 3.10 · Intermediate · 110 min

**By the end of this lesson you can**

- Choose a chart type from the analytical question (trend, comparison, distribution, relationship, composition)
- Build charts with fig, ax = plt.subplots() and customise titles, labels, ticks, legends and colours
- Combine several charts with subplots and annotate key points
- Plot directly from pandas and save figures at publication quality
- Apply design rules: start bars at zero, remove clutter, label directly, use colour with purpose


## Choose the chart from the question




Start from the question, not the chart type.

## The object-oriented API

Matplotlib has two styles. Use the **object-oriented** one: create a **Figure** (the canvas) and one or more **Axes** (plots), then call methods on the axes.





Monthly Superstore sales: a line chart shows the trend and the seasonal peaks.

Python

```python
import matplotlib.pyplot as plt
fig, ax = plt.subplots(figsize=(9, 3.6))   # one figure, one axes
ax.plot(x, y)                              # draw
ax.set_title("..."); ax.set_xlabel("..."); ax.set_ylabel("...")
fig.savefig("chart.png", dpi=200, bbox_inches="tight")
plt.show()                                 # in scripts; notebooks display automatically
```


| Element | Method |
| --- | --- |
| Title, axis labels | `ax.set_title` , `ax.set_xlabel` , `ax.set_ylabel` |
| Limits, ticks | `ax.set_ylim(0)` , `ax.set_xticks` , `ax.tick_params(rotation=45)` |
| Legend | `label="..."` in the plot call, then `ax.legend()` |
| Grid, spines | `ax.grid(axis="y")` , `ax.spines[["top","right"]].set_visible(False)` |
| Text, arrows | `ax.text` , `ax.annotate` |
| Reference lines | `ax.axhline(y)` , `ax.axvline(x)` , `ax.axvspan` |
| Number format | `ax.yaxis.set_major_formatter(...)` |

# Bar charts





Sorted horizontal bars make category comparisons easy; one highlight colour draws the eye.

Grouped and stacked bars compare two dimensions:




Sales by region and category, as grouped bars (compare within region) and stacked bars (compare totals).


# Distributions: histogram and box plot




House prices are right-skewed: the mean sits above the median. Box plots compare distributions across cities.


Bins matter: too few hide the shape, too many look noisy. Try `bins="auto"` or a few values.

# Relationships: scatter




Larger houses cost more (r ≈ 0.8); colour shows a third variable, the distance to the centre.

## Part of a whole





Pie charts work for a few parts; the donut variant leaves room for a label.

For more than 4 parts, or to compare parts across groups, use (stacked) bars.

## Plotting from pandas

DataFrames and Series have `.plot()`, a quick wrapper around Matplotlib that returns an `ax` you can keep styling.




One line of pandas plotting, then a little Matplotlib styling.

`kind=` can be `line`, `bar`, `barh`, `hist`, `box`, `scatter` (with `x=`, `y=`), `area`, `pie`.

## Subplots dashboards and saving

Python

```
fig, axes = plt.subplots(2, 2, figsize=(11, 7), constrained_layout=True)
axes[0, 0].plot(...); axes[0, 1].barh(...); axes[1, 0].hist(...); axes[1, 1].scatter(...)
fig.suptitle("Sales overview", fontsize=15, weight="bold")
fig.savefig("overview.png", dpi=200, bbox_inches="tight")   # also .svg / .pdf for crisp vector output
```

## Design rules that make charts honest

| Rule | Why |
|---|---|
| Bars start at zero | Truncated bars exaggerate differences |
| Sort categories by value | Faster comparison |
| Title states the insight | "Tables lose money" beats "Profit by sub-category" |
| Label directly, remove chart junk | Fewer eye movements |
| One highlight colour, grey for context | Colour carries meaning |
| Colour-blind safe palettes (viridis, Okabe-Ito) | About 1 in 12 men are colour-blind |
| Same scale when comparing panels | Avoid misleading comparisons |
| Avoid 3-D and dual axes when possible | They distort perception |

## Summary

**KEY TAKEAWAYS**

- Pick the chart from the question: trend → line, comparison → sorted bar, distribution → histogram/box, relationship → scatter, composition → stacked bar (pie only for a few parts).
- Use `fig, ax = plt.subplots()` and style the axes: titles, labels, limits, spines, legends, annotations.
- `plt.subplots(rows, cols)` builds small multiples; `fig.savefig(..., dpi=200, bbox_inches="tight")` exports.
- pandas `.plot()` is a fast start that returns a Matplotlib axes.
- Honest design: zero-based bars, sorted categories, insight titles, purposeful colour.

### Quick quiz

6 questions · tap an answer to check it

**1.** Which chart best shows a trend over 36 months?

- **A** Pie
- **B** Line
- **C** Histogram
- **D** Box plot

**Answer: B.** Lines connect ordered time points.

**2.** Which chart shows the distribution of one numeric variable?

- **A** Scatter
- **B** Histogram
- **C** Pie
- **D** Stacked bar

**Answer: B.** Box and violin plots also work.

**3.** What does `fig, ax = plt.subplots(1, 2)` create?

- **A** One chart
- **B** One figure with two axes side by side
- **C** Two separate windows
- **D** A 2 × 2 grid

**Answer: B.** `ax` becomes an array of two axes.

**4.** Why should bar charts start at zero?

A Matplotlib requires it

B Bar length encodes value; a cut axis exaggerates differences

C It looks better

D It saves space

**Answer: B.** Line charts can zoom; bars should not.

**5.** When is a pie chart acceptable?

A For 12 categories

B For a few parts of one whole, when exact comparison is not needed

C For trends

D Never

**Answer: B.** Otherwise use bars.

**6.** How do you save a sharp image without cut-off labels?

A `plt.show()`

B `fig.savefig("c.png", dpi=200, bbox_inches="tight")`

C Screenshot

D `fig.close()`

**Answer: B.** SVG/PDF give vector output.

EXERCISE

## Chart practice

(1) Line chart of monthly profit with a horizontal line at zero. (2) Sorted horizontal bar of sales by state (top 10). (3) Histogram of `discount`. (4) Scatter of `discount` vs `profit` (what do you see?). (5) A 2 × 2 dashboard of these four charts saved as PNG.

**Show solution (worked answer)**

Python

```
mp = s.set_index("order_date")["profit"].resample("ME").sum()
fig, axes = plt.subplots(2, 2, figsize=(11, 7), constrained_layout=True)
axes[0, 0].plot(mp.index, mp / 1e6); axes[0, 0].axhline(0, color="grey")
st = s.groupby("state")["sales"].sum().nlargest(10).sort_values(); axes[0,
1].barh(st.index, st / 1e6)
axes[1, 0].hist(s.discount, bins=9)
axes[1, 1].scatter(s.discount, s.profit, s=4, alpha=.3)   # profit falls as discount
rises
fig.savefig("dashboard.png", dpi=150, bbox_inches="tight")
```

INTERVIEW CORNER

## Questions you may be asked

**Q: How do you choose a chart?** Start from the question (trend, comparison, distribution, relationship, composition), the number of variables and the audience, then remove anything that does not help the message.

**Q: What makes a chart misleading?** Truncated bar axes, inconsistent scales, 3-D effects, cherry-picked ranges, dual axes with arbitrary scaling, and areas that do not match values.

**Q: Matplotlib vs Seaborn vs Plotly?** Matplotlib is the low-level foundation with full control; Seaborn adds statistical charts with good defaults on top; Plotly makes interactive web charts.

PYTHON FOR DATA SCIENCE · LESSON 21

# Data Visualisation II: Seaborn Statistical Charts and Interactive Plotly

Make statistical charts quickly with Seaborn (distributions, categorical comparisons, relationships, correlation heatmaps, pair plots and facets) using the HR attrition data, and build interactive charts and simple dashboards with Plotly Express and Streamlit.

Python class 16 · Seaborn 0.13 · Plotly 6 · Intermediate · 100 min

**By the end of this lesson you can**

- Use Seaborn's figure-level and axes-level functions with hue, col and row
- Compare distributions across groups with histplot, kdeplot, boxplot, violinplot and countplot
- Show relationships with scatterplot, regplot, heatmaps of correlations and pairplot
- Build interactive charts with Plotly Express and know when to use Streamlit
- Turn charts into a clear data story

## Seaborn in one idea

Seaborn works directly with **long DataFrames**: you name the columns for `x`, `y`, `hue` (colour), `col` / `row` (small multiples), and it groups, aggregates and adds legends for you.

Python


```
import pandas as pd, numpy as np, seaborn as sns, matplotlib.pyplot as plt
hr = pd.read_csv("hr_employees.csv")
hr["left"] = (hr["attrition"] == "Yes").astype(int)
print(hr.shape, f"attrition rate {hr.left.mean():.1%}", sns.__version__)
print(hr.groupby("overtime")["left"].mean().round(3).to_dict(), hr.groupby("department")
["left"].mean().round(3).sort_values().to_dict())
```

OUTPUT

```
(1500, 16) attrition rate 25.9% 0.13.2
{'No': 0.216, 'Yes': 0.367} {'Operations': 0.219, 'Finance': 0.227, 'HR': 0.229,
'IT': 0.243, 'R&D': 0.26, 'Sales': 0.304}
```


| Question | Seaborn function |
|---|---|
| Distribution of one variable | `histplot` , `kdeplot` , `ecdfplot` |
| Distribution by group | `boxplot` , `violinplot` , `stripplot` , `boxenplot` |
| Counts of categories | `countplot` |
| Average per category (with CI) | `barplot` , `pointplot` |
| Two numeric variables | `scatterplot` , `regplot` , `lmplot` , `jointplot` |
| Many variables | `pairplot` , `heatmap` of `df.corr()` |
| Small multiples | `displot` , `catplot` , `relplot` with `col=` / `row=` |

## Distributions





Income distribution for leavers vs stayers: leavers cluster at lower incomes.

`common_norm=False` scales each group separately, so a small group (leavers) is not dwarfed by a big one.




Violin plots combine a box plot with the distribution shape; split by overtime.

## Categorical comparisons




Attrition rate by overtime and job satisfaction. Bars show the mean with a 95% confidence interval.

Python


```
print((hr.pivot_table(index="job_satisfaction", columns="overtime", values="left",
aggfunc="mean") * 100).round(1))
```

OUTPUT

```
overtime              No   Yes
job_satisfaction
1                   31.1  45.5
2                   24.4  40.5
```

```
3                 18.7  32.8
4                 12.0  25.8
```

## Relationships and correlation




Correlation heatmap of numeric HR variables (Pearson r). Only the lower triangle is shown.


Python

```python
print(corr["left"].drop("left").sort_values())
```

OUTPUT


```
job_satisfaction        -0.17
years_at_company        -0.13
monthly_income          -0.11
age                     -0.08
performance_rating      -0.03
distance_from_home_km    0.09
Name: left, dtype: float64
```

Correlation measures **linear** association between −1 and +1. It does not prove causation, and it can miss non-linear patterns: always look at the scatter too.





regplot adds a fitted line with a confidence band; lmplot repeats it per group.

## Pair plots and facets




A pair plot shows every pairwise scatter and each distribution, coloured by churn (telecom data).




Facets (small multiples) with catplot: churn rate by contract type, split by internet service.

Python

```
print((tc.pivot_table(index="contract", columns="internet_service", values="churned",
aggfunc="mean") * 100).round(1))
```

OUTPUT

```
internet_service   DSL  Fiber  No internet
contract
Month-to-month    30.8   43.5         28.5
One year          11.1   26.7          4.1
Two year           5.6    9.5          2.8
```

## Interactive charts with Plotly Express

Plotly makes charts you can hover, zoom and filter in a browser or notebook. The syntax mirrors Seaborn:

Python

```
import plotly.express as px
fig = px.scatter(tc, x="tenure_months", y="monthly_charges", color="churn",
                 hover_data=["contract", "payment_method"], opacity=.6,
                 title="Churn by tenure and charges")
fig.show()                          # interactive in notebooks
fig.write_html("churn.html")        # share as a standalone web page

px.line(monthly_df, x="month", y="sales", color="category")
px.bar(region_df, x="region", y="sales", text_auto=".2s")
px.histogram(hr, x="monthly_income", color="attrition", barmode="overlay")
px.choropleth(...)                  # maps
```


## A mini dashboard app with Streamlit

Python

```python
# app.py  →  run with:  streamlit run app.py
import streamlit as st, pandas as pd, plotly.express as px
df = pd.read_csv("telecom_churn.csv")
contract = st.sidebar.multiselect("Contract", df.contract.unique(),
default=list(df.contract.unique()))
d = df[df.contract.isin(contract)]
st.title("Churn dashboard")
st.metric("Churn rate", f"{(d.churn == 'Yes').mean():.1%}")
st.plotly_chart(px.histogram(d, x="tenure_months", color="churn", barmode="overlay"))
```

Streamlit turns a Python script into a web app with filters, which is useful for sharing analyses and ML demos (see the GenAI track for chat apps).

## From charts to a data story




The story arc: context, finding, evidence, recommendation.

1. **One message per chart**, written as the title.
2. Show the comparison that proves it (overtime vs not), not every chart you made.
3. Quantify impact (people, ₹, %).
4. End with a recommendation and its owner.

# Summary

**KEY TAKEAWAYS**

- Seaborn plots long DataFrames by column name with `hue`, `col` and `row`; it sits on Matplotlib, so you can still style the axes.
- Distributions: `histplot` (with `common_norm=False`), `kdeplot`, `boxplot`, `violinplot`; categories: `countplot`, `barplot` with confidence intervals.
- Relationships: `scatterplot`, `regplot`, `pairplot`, correlation `heatmap` (correlation ≠ causation).
- Facets (`catplot`, `relplot`, `displot`) create small multiples.
- Plotly Express gives interactive charts; Streamlit turns scripts into dashboards. Tell a story: one message per chart.

## Quick quiz

6 questions · tap an answer to check it

**1. What does `hue="attrition"` do in Seaborn?**

A Changes the theme

B Colours the marks by the attrition category

C Filters to attrition = Yes

D Adds a title

**Answer: B.** `col=` would create separate panels instead.

**2. Which chart shows the mean per category with a confidence interval?**

A countplot

B barplot

C histplot

D heatmap

**Answer: B.** `countplot` shows counts.

**3. A correlation of −0.8 means...**

A No relationship

B A strong negative linear relationship

C One variable causes the other to fall

D A weak relationship

**Answer: B.** Correlation does not imply causation.

**4. Which function creates small multiples of bar charts?**

A barplot

B catplot(kind="bar", col=...)

C heatmap

D pairplot

**Answer: B.** Figure-level functions accept `col` and `row`.

**5.** What is the main advantage of Plotly over Matplotlib?

- **A** Faster to print
- **B** Interactive hover, zoom and filtering in the browser
- **C** More chart types for PDFs
- **D** No code needed

**Answer: B.** Export with `write_html`.

**6.** Why use `common_norm=False` in a histplot with hue?

- **A** So each group's density is scaled to its own size and small groups stay visible
- **B** To remove the legend
- **C** To use counts
- **D** To normalise to 100

**Answer: A.** Otherwise the larger group dominates.

EXERCISE

### Seaborn practice (telecom_churn.csv)

(1) Histogram of `monthly_charges` by churn. (2) Box plot of `tenure_months` by contract. (3) Churn rate by payment method, sorted. (4) Correlation heatmap of numeric columns plus `churned`. (5) Write three insight titles from what you see.

**Show solution (worked answer)**

Python

```
sns.histplot(tc, x="monthly_charges", hue="churn", common_norm=False, stat="density")
sns.boxplot(tc, x="contract", y="tenure_months")
order = tc.groupby("payment_method")
["churned"].mean().sort_values(ascending=False).index
sns.barplot(tc, x="payment_method", y="churned", order=order, errorbar=None)
sns.heatmap(tc.select_dtypes("number").corr(), annot=True, fmt=".2f", cmap="RdBu_r",
center=0)
# e.g. "Month-to-month customers churn far more", "Churners have short tenure", "Churn
rises with support calls"
```

INTERVIEW CORNER

### Questions you may be asked

**Q: How would you visualise the relationship between a categorical and a numeric variable?** Box or violin plots per category (distribution), or bar/point plots of the mean with confidence intervals.

**Q: How do you show correlations among many numeric variables?** A correlation heatmap (masked upper triangle) followed by scatter plots for the interesting pairs; a pair plot for a handful of variables.

**Q: How do you present findings to non-technical stakeholders?** Lead with the recommendation, show one clear chart per point with an insight title, quantify impact, and keep methods in an appendix.

PYTHON FOR DATA SCIENCE · LESSON 22

# Exploratory Data Analysis (EDA) Case Study: Telecom Customer Churn


Run a complete, structured EDA on 3,000 telecom customers. Frame the question, check data quality, do univariate, bivariate and segment analysis, engineer features, quantify revenue at risk and finish with findings and recommendations: the template you will reuse for every dataset and for the ML churn model.

Python class 17 · pandas 3 · Seaborn 0.13 · Intermediate · 150 min

**By the end of this lesson you can**

- Follow a repeatable EDA checklist from question to recommendation
- Check data quality and consistency between related columns
- Analyse univariate distributions and bivariate relationships with the target
- Build segments and quantify business impact (revenue at risk)
- Write findings as clear, numbered insights with actions

## The EDA checklist




A structured EDA moves from the business question to actions.

**Business question.** A telecom operator loses customers every month. *Which customers churn, why, and where should retention money go first?* **Target:** `churn` (Yes/No). **Metric:** churn rate = churned ÷ customers.

# 1. Load and first look

Python

```
import pandas as pd, numpy as np, seaborn as sns, matplotlib.pyplot as plt
pd.set_option("display.max_columns", 20); pd.set_option("display.width", 160)
tc = pd.read_csv("telecom_churn.csv")
tc["churned"] = (tc["churn"] == "Yes").astype(int)
print(tc.shape); print(tc.head(3))
print(tc.dtypes.astype(str).to_dict())
print(f"Overall churn rate: {tc.churned.mean():.1%} ({tc.churned.sum()} of {len(tc)})")
```

OUTPUT

```
(3000, 11)
  customer_id  senior_citizen  tenure_months        contract internet_service
payment_method  monthly_charges  total_charges  support_calls churn  churned
0      T00001               0             71        Two year            Fiber    Net
banking            81.28        5848.06              1    No        0
1      T00002               1             56  Month-to-month            Fiber
Auto-debit           115.12        6482.44              0    No        0
2      T00003               0             38        Two year            Fiber
Auto-debit            85.90        3186.34              1    No        0
{'customer_id': 'str', 'senior_citizen': 'int64', 'tenure_months': 'int64',
'contract': 'str', 'internet_service': 'str', 'payment_method': 'str',
'monthly_charges': 'float64', 'total_charges': 'float64', 'support_calls': 'int64',
'churn': 'str', 'churned': 'int64'}
Overall churn rate: 25.7% (772 of 3000)
```

# 2. Data quality

Python


```
print("missing:", tc.isna().sum().sum(), "| duplicate ids:",
tc.customer_id.duplicated().sum())
print(tc.describe().round(1).T[["min", "50%", "max", "mean"]])
for c in ["contract", "internet_service", "payment_method"]: print(c,
tc[c].value_counts().to_dict())
gap = tc.total_charges - tc.tenure_months * tc.monthly_charges       # consistency check
between columns
print("total_charges - tenure × monthly: median", round(gap.median(), 1), "| 95% within ±",
round(gap.abs().quantile(.95), 0))
print("tenure 0 customers:", (tc.tenure_months == 0).sum())
```

OUTPUT

```
missing: 0 | duplicate ids: 0
                   min     50%     max    mean
senior_citizen     0.0     0.0     1.0     0.2
tenure_months      0.0    36.0    72.0    36.1
monthly_charges   20.0    73.8   131.7    67.1
total_charges     19.6  2161.3  8724.4  2418.3
support_calls      0.0     1.0     6.0     1.3
churned            0.0     0.0     1.0     0.3
contract {'Month-to-month': 1690, 'One year': 739, 'Two year': 571}
internet_service {'Fiber': 1368, 'DSL': 1047, 'No internet': 585}
payment_method {'Card': 767, 'UPI': 753, 'Auto-debit': 746, 'Net banking': 734}
total_charges - tenure × monthly: median -0.8 | 95% within ± 189.0
tenure 0 customers: 45
```

No missing values or duplicate IDs. `total_charges` roughly equals tenure × monthly charges (small gaps from price changes), so the columns are consistent. A few customers have tenure 0 (new joiners), which is valid.

## 3. Univariate analysis




Distributions of the numeric variables. Tenure is spread across 0–72 months; monthly charges have a bump of low-price plans.

## 4. Bivariate: each driver vs churn

Python

```python
def churn_by(col):
    g = tc.groupby(col, observed=True)["churned"].agg(customers="size", churn_rate="mean")
    g["churn_rate"] = (100 * g.churn_rate).round(1); g["lift"] = (g.churn_rate / (100 *
tc.churned.mean())).round(2)
    return g
for col in ["contract", "internet_service", "payment_method", "senior_citizen"]:
print(churn_by(col), "\n")
```

OUTPUT

```
                customers  churn_rate  lift
contract
Month-to-month       1690        35.9  1.40
One year              739        16.9  0.66
Two year              571         7.0  0.27

                  customers  churn_rate  lift
internet_service
DSL                    1047        21.8  0.85
Fiber                  1368        32.2  1.25
No internet             585        17.6  0.68

                customers  churn_rate  lift
payment_method
Auto-debit            746        23.5  0.91
Card                  767        26.3  1.02
Net banking           734        28.5  1.11
UPI                   753        24.7  0.96

                customers  churn_rate  lift
senior_citizen
0                    2490        25.3  0.98
1                     510        27.8  1.08
```

**Lift** = segment churn ÷ overall churn. Lift 1.4 means 40% more likely to churn than average.

Python


```
tc["tenure_band"] = pd.cut(tc.tenure_months, [0, 6, 12, 24, 48, 72], include_lowest=True,
labels=["0-6", "7-12", "13-24", "25-48", "49-72"])
tc["calls_band"] = pd.cut(tc.support_calls, [-1, 0, 1, 2, 3, 10], labels=["0", "1", "2",
"3", "4+"])
tc["charge_band"] = pd.qcut(tc.monthly_charges, 4, labels=["Q1 low", "Q2", "Q3", "Q4
high"])
for col in ["tenure_band", "calls_band", "charge_band"]: print(churn_by(col), "\n")
```

OUTPUT

```
             customers  churn_rate  lift
tenure_band
0-6                318        51.9  2.02
7-12               238        44.5  1.73
13-24              452        38.5  1.50
25-48             1011        21.6  0.84
49-72              981        11.1  0.43
```

```
             customers  churn_rate  lift
calls_band
0                  822        19.1  0.74
1                 1101        23.1  0.90
2                  649        30.0  1.17
3                  294        36.4  1.41
4+                 134        44.0  1.71

              customers  churn_rate  lift
charge_band
Q1 low              781        19.0  0.74
Q2                  719        20.2  0.78
Q3                  750        29.9  1.16
Q4 high             750        34.0  1.32
```




Churn rate by the four strongest drivers. The dashed line is the overall rate.

## Numeric drivers

Python

```
print(tc.groupby("churn")[["tenure_months", "monthly_charges", "total_charges",
"support_calls"]].median())
print(tc[["tenure_months", "monthly_charges", "support_calls", "senior_citizen",
"churned"]].corr()["churned"].drop("churned").round(3).sort_values())
```

OUTPUT

```
       tenure_months  monthly_charges  total_charges  support_calls
churn
No              42.0           68.010       2445.905            1.0
Yes             21.0           75.405       1357.910            1.0
tenure_months     -0.322
senior_citizen     0.022
monthly_charges    0.143
```

```
support_calls      0.153
Name: churned, dtype: float64
```


## 5. Segments: interactions matter

Python

```python
seg = tc.pivot_table(index="contract", columns="tenure_band", values="churned",
aggfunc="mean", observed=True).mul(100).round(1)
print(seg)
cnt = tc.pivot_table(index="contract", columns="tenure_band", values="churned",
aggfunc="size", observed=True)
print(cnt)
```

OUTPUT

```
tenure_band      0-6  7-12  13-24  25-48  49-72
contract
Month-to-month  70.2  62.4   53.4   29.7   17.4
One year        36.5  30.3   26.9   13.4    4.3
Two year        13.5  17.0   10.7    6.8    1.5
tenure_band     0-6  7-12  13-24  25-48  49-72
contract
Month-to-month  181   125    249    583    552
One year         85    66    119    238    231
Two year         52    47     84    190    198
```




Churn rate (%) by contract and tenure: new month-to-month customers are the hot spot.

Python

```
hot = tc[(tc.contract == "Month-to-month") & (tc.tenure_months <= 12)]
fiber_calls = tc[(tc.internet_service == "Fiber") & (tc.support_calls >= 3)]
for name, d in [("Month-to-month, tenure ≤ 12", hot), ("Fiber with 3+ support calls",
fiber_calls)]:
    print(f"{name:32s} customers {len(d):4d} | churn {d.churned.mean():.1%} | lift
{d.churned.mean() / tc.churned.mean():.2f}")
```

OUTPUT

```
Month-to-month, tenure ≤ 12      customers  306 | churn 67.0% | lift 2.60
Fiber with 3+ support calls      customers  192 | churn 46.9% | lift 1.82
```

## 6. Business impact: revenue at risk

Python

```
tc["monthly_revenue_lost"] = tc.monthly_charges * tc.churned
lost = tc.monthly_revenue_lost.sum()
print(f"Monthly revenue of churned customers: {lost:,.0f}  ({lost /
tc.monthly_charges.sum():.1%} of all monthly revenue)")
imp = tc.groupby("contract").agg(churners=("churned", "sum"), revenue_lost=
("monthly_revenue_lost", "sum"))
imp["share_of_loss_%"] = (100 * imp.revenue_lost / lost).round(1)
print(imp.round(0))
```

OUTPUT

```
Monthly revenue of churned customers: 56,173  (27.9% of all monthly revenue)
                churners  revenue_lost  share_of_loss_%
contract
Month-to-month       607       43293.0             77.0
One year             125        9763.0             17.0
Two year              40        3117.0              6.0
```

Revenue numbers here are in the data's currency units per month; multiply by expected remaining lifetime to estimate lifetime value lost.

## 7. Findings and recommendations

**KEY TAKEAWAYS**

1. **About 1 in 4 customers churn** (25.7%), taking 27.9% of monthly revenue with them.
2. **Contract is the strongest driver**: month-to-month churn is about 36%, against about 7% on two-year contracts, and month-to-month customers account for 77% of the monthly revenue lost.
3. **The first year is critical**: churn is above 40% in the first 12 months and falls steadily with tenure.
4. **Support calls signal risk**: churn roughly doubles from 0 calls (about 19%) to 3 or more calls (about 36–44%).
5. **Fiber customers churn more** (about 32% against 22% on DSL), which is consistent with price or service-quality issues.
6. Payment method and senior status make only small differences.

**Recommendations.** (a) Offer month-to-month customers in their first year an incentive to move to an annual plan. (b) Trigger a proactive call after the second support ticket. (c) Investigate Fiber service quality and pricing. (d) Build a churn-score model (ML track, capstone) to rank customers each month and measure the retention campaign with an A/B test.

**NOTE** **EDA is not causal proof**

These are associations. Contract and churn are related, but customers who intend to leave may simply choose month-to-month plans. Experiments (A/B tests) or careful causal methods are needed before claiming that a change will cause lower churn.

## Automated profiling tools

Libraries such as **ydata-profiling** ( `ProfileReport(df)` ), **sweetviz** and **D-Tale** generate an EDA report in one line, and AI assistants (Lesson ai-analytics) can draft charts. Use them for a quick first scan, then do the focused, question-driven analysis above.

# Summary

**KEY TAKEAWAYS**

- EDA follows a checklist: question → quality → univariate → bivariate → segments → impact → findings.
- Check consistency between related columns, not just missing values.
- Compare churn rate and lift by category; band numeric variables with `cut` / `qcut`.
- Interactions (contract × tenure) reveal hot spots that single variables hide.
- Quantify impact in money and end with specific, owned recommendations; remember that association is not causation.

## Quick quiz

6 questions · tap an answer to check it

**1. What is "lift" in segment analysis?**

**A** The number of customers in a segment

**B** Segment rate divided by the overall rate

**C** The difference between two means

**D** A chart type

**Answer: B.** Lift 2 = twice as likely as average.

**2. Why band tenure into groups?**

**A** pandas needs it

**B** To compare churn rates across ranges and spot non-linear patterns

**C** To delete outliers

**D** To save memory

**Answer: B.** `pd.cut` for fixed edges, `qcut` for equal-sized groups.

**3. Which finding came from an interaction analysis?**

A Overall churn is 25.7%

B New month-to-month customers have the highest churn

C Fiber churns more

D No missing values

**Answer: B.** It combines two variables.

**4. Why check `total_charges` against tenure × monthly charges?**

A To verify consistency between related columns

B To compute churn

C To fill missing values

D To make a chart

**Answer: A.** Inconsistent columns hint at data errors.

**5. What should an EDA conclude with?**

A All charts produced

B Numbered findings with quantified impact and recommendations

C The raw data

D A model

**Answer: B.** Stakeholders act on findings, not charts.

**6.** Can EDA alone prove that a two-year contract reduces churn?

A Yes

B No, it shows association; experiments or causal methods are needed

C Only with a heatmap

D Only if r > 0.5

**Answer: B.** Self-selection can explain the pattern.

EXERCISE **Extend the case study**

(1) Compute churn by payment method within month-to-month customers only. (2) Find the 10 highest-revenue customers at risk (month-to-month, tenure ≤ 12, 2+ support calls). (3) Plot churn rate against monthly charge deciles. (4) Write a five-bullet executive summary.

**Show solution (worked answer)**

Python

```
print(tc[tc.contract == "Month-to-
month"].groupby("payment_method").churned.mean().round(3))
risk = tc[(tc.contract == "Month-to-month") & (tc.tenure_months ⩽ 12) &
(tc.support_calls ⩾ 2) & (tc.churned == 0)]
print(risk.nlargest(10, "monthly_charges")[["customer_id", "monthly_charges",
"support_calls"]])
dec = tc.groupby(pd.qcut(tc.monthly_charges, 10), observed=True).churned.mean()
dec.plot(marker="o")
```

INTERVIEW CORNER

## Questions you may be asked

**Q: Walk me through how you would do EDA on a new dataset.** Clarify the question and target, check quality (types, missing, duplicates, ranges, consistency), look at each variable, compare each variable against the target, explore interactions and segments, quantify impact, and summarise findings with next steps.

**Q: How do you decide which variables matter most for churn?** Compare churn rates/lift by category, correlations and group medians for numeric variables, then confirm with a model (feature importance) and, for causality, with experiments.

**Q: Which chart would you use to show churn by two categorical variables?** A heatmap of churn rates (with counts available) or grouped bars.

PYTHON FOR DATA SCIENCE · LESSON 23

# Python and SQL: sqlite3, DuckDB, SQLAlchemy and pandas.read_sql

Connect Python to databases. Create and query SQLite with the standard library, use parameterised queries safely, load DataFrames to tables and back, query CSV and DataFrames directly with DuckDB, connect to MySQL, PostgreSQL and SQL Server with SQLAlchemy, and decide what to do in SQL versus pandas.


Python class 18 · DuckDB 1.x/2.x · SQLAlchemy 2 · Intermediate · 100 min

**By the end of this lesson you can**

- Create a SQLite database, run DDL/DML from Python and fetch results
- Write parameterised queries and explain SQL injection
- Move data between pandas and databases with to_sql and read_sql
- Query files and DataFrames with DuckDB
- Connect to server databases with SQLAlchemy connection URLs and secrets kept out of code

## Why connect Python to SQL?

Company data lives in databases and warehouses (MySQL, PostgreSQL, SQL Server, Snowflake, BigQuery, Databricks). The usual pattern: **filter and aggregate in SQL** (close to the data), then **analyse, model and chart in Python**.




SQL pulls and summarises; Python analyses, models and presents.

# sqlite3: a database in a file

SQLite ships with Python. It is perfect for learning, prototypes and small apps.

Python

```
import sqlite3, pandas as pd
con = sqlite3.connect(":memory:")                    # or "shop.db" for a file
cur = con.cursor()
cur.executescript("""
CREATE TABLE customers (id INTEGER PRIMARY KEY, name TEXT NOT NULL, city TEXT);
CREATE TABLE orders (id INTEGER PRIMARY KEY, customer_id INTEGER REFERENCES customers(id),
amount REAL, order_date TEXT);
""")
cur.executemany("INSERT INTO customers (name, city) VALUES (?, ?)", [("Asha", "Pune"),
("Ravi", "Delhi"), ("Meera", "Kochi")])
cur.executemany("INSERT INTO orders (customer_id, amount, order_date) VALUES (?, ?, ?)",
                [(1, 1200, "2025-01-05"), (1, 450, "2025-02-11"), (2, 3000, "2025-02-14"),
(3, 780, "2025-03-01")])
con.commit()
cur.execute("SELECT c.name, COUNT(*), SUM(o.amount) FROM orders o JOIN customers c ON c.id
= o.customer_id GROUP BY c.name ORDER BY 3 DESC")
print(cur.fetchall())
cur.execute("SELECT * FROM customers WHERE city = ?", ("Pune",)); print(cur.fetchone())
```

OUTPUT

```
[('Ravi', 1, 3000.0), ('Asha', 2, 1650.0), ('Meera', 1, 780.0)]
(1, 'Asha', 'Pune')
```

| Method | Use |
|---|---|
| `con.execute(sql, params)` / `cursor.execute` | Run one statement |
| `executemany(sql, rows)` | Insert many rows |
| `fetchone()`, `fetchall()`, `fetchmany(n)` | Read results |
| `con.commit()` / `con.rollback()` | Save / undo a transaction |
| `with con:` | Commits on success, rolls back on error |

## Parameterised queries and SQL injection

Python

```
user_input = "Pune' OR '1'='1"
unsafe = f"SELECT name FROM customers WHERE city = '{user_input}'"       # NEVER build SQL
with f-strings
print("unsafe returns:", con.execute(unsafe).fetchall())
print("safe returns:  ", con.execute("SELECT name FROM customers WHERE city = ?",
(user_input,)).fetchall())
```

OUTPUT

```
unsafe returns: [('Asha',), ('Ravi',), ('Meera',)]
safe returns:   []
```

The unsafe query returned **every** customer because the input changed the SQL. Placeholders (`?` in SQLite, `%s` or `:name` in other drivers) send values separately, so input can never become code.

## Transactions

Python

```
try:
    with con:                                                    # one transaction
        con.execute("UPDATE orders SET amount = amount - 500 WHERE id = 1")
        con.execute("INSERT INTO orders (customer_id, amount) VALUES (2, 500)")          #
second change
        raise ValueError("payment gateway down")                      # simulate a failure
mid-way
except ValueError as e:
    print("rolled back:", e)
print(con.execute("SELECT id, amount FROM orders WHERE id = 1").fetchone(),
con.execute("SELECT COUNT(*) FROM orders").fetchone())
```

OUTPUT

```
rolled back: payment gateway down
(1, 1200.0) (4,)
```

Both changes were undone together: that is atomicity (the A in ACID).

## pandas ↔ database

Python

```
s = pd.read_csv("superstore_sales.csv")
s.to_sql("sales", con, index=False, if_exists="replace")              # DataFrame → table
q = """
SELECT region, category, ROUND(SUM(sales) / 1e6, 2) AS sales_m, ROUND(100.0 * SUM(profit) /
SUM(sales), 1) AS margin_pct
FROM sales WHERE discount ⩽ :max_disc GROUP BY region, category ORDER BY sales_m DESC
LIMIT 5
"""
print(pd.read_sql(q, con, params={"max_disc": 0.1}))                  # query → DataFrame
con.close()
```

OUTPUT

```
  region    category  sales_m  margin_pct
0  South  Technology    32.14        15.9
1   West  Technology    30.21        16.1
2  North  Technology    29.93        16.6
3   East  Technology    26.57        17.5
4   West   Furniture     5.36        10.3
```

For large tables, read in pieces with `chunksize=` or push the aggregation into SQL so only the summary travels.

## DuckDB: SQL on files and DataFrames

**DuckDB** is an in-process analytical database: no server, very fast on columnar data, and it can query CSV, Parquet and pandas DataFrames directly.

Python

```
import duckdb
print(duckdb.sql("""
    SELECT category, COUNT(*) AS lines, ROUND(SUM(sales)/1e6, 2) AS sales_m
    FROM 'superstore_sales.csv' GROUP BY category ORDER BY sales_m DESC
""").df())
customers = pd.read_csv("customers.csv")
top = duckdb.sql("""
    SELECT c.state, COUNT(DISTINCT s.customer_id) AS customers, ROUND(SUM(s.sales)/1e6, 2)
AS sales_m,
           RANK() OVER (ORDER BY SUM(s.sales) DESC) AS rnk
    FROM s JOIN customers c USING (customer_id)                    -- s and customers
are pandas DataFrames!
    GROUP BY c.state QUALIFY rnk ⩽ 5 ORDER BY rnk
""").df()
print(top, duckdb.__version__)
```

OUTPUT

```
          category  lines  sales_m
0       Technology   1892   156.44
1        Furniture   1917    34.84
2  Office Supplies   2514    10.13
            state  customers  sales_m  rnk
0     Maharashtra         93    25.67    1
1           Delhi         54    15.66    2
2          Kerala         48    14.71    3
3  Madhya Pradesh         57    14.41    4
4     West Bengal         54    13.89    5 2.0.0
```

DuckDB also writes Parquet (`COPY (SELECT ...) TO 'out.parquet'`), reads from S3, and powers tools such as MotherDuck and the Metabase/MinusX demos in the AI analytics track.

## Server databases with SQLAlchemy

`SQLAlchemy` gives one interface to many databases. You need the database's driver package too.

Python

```python
from sqlalchemy import create_engine, text
import os, pandas as pd

# Connection URLs:  dialect+driver://user:password@host:port/database
url = os.environ["DB_URL"]          # e.g.
"postgresql+psycopg://analyst:***@db.company.com:5432/sales"
#   MySQL:       "mysql+pymysql://user:pw@host:3306/db"
#   SQL Server:  "mssql+pyodbc://user:pw@server/db?driver=ODBC+Driver+18+for+SQL+Server"
#   SQLite:      "sqlite:///shop.db"
engine = create_engine(url)

with engine.connect() as conn:
    df = pd.read_sql(text("SELECT * FROM orders WHERE order_date ⩾ :d"), conn, params=
{"d": "2025-01-01"})

df_summary.to_sql("daily_summary", engine, if_exists="append", index=False,
chunksize=10_000)
```

Warehouses have their own connectors ( `snowflake-connector-python` , `google-cloud-bigquery` , `databricks-sql-connector` ), and most also accept SQLAlchemy URLs.

**WATCH OUT** **Keep credentials out of code**

Read passwords from environment variables, a `.env` file (with `python-dotenv` ) that is in `.gitignore` , or a secrets manager. Use a read-only database user for analysis.

## SQL or pandas?

| Do it in SQL when… | Do it in pandas when… |
|---|---|
| The data is large and lives in the database | The data fits in memory |
| Filtering, joining, aggregating | Complex reshaping, statistics, ML, charts |
| Many people need the same logic (views) | Exploratory, one-off analysis |
| You want the database's indexes and compute | You need Python libraries |

# Summary

**KEY TAKEAWAYS**

- `sqlite3` creates databases in a file or memory; `execute` , `executemany` , `fetchall` , `commit` ; `with con:` wraps a transaction.
- Always use parameter placeholders, never f-strings, to prevent SQL injection.
- `df.to_sql` writes tables; `pd.read_sql(query, con, params=...)` reads results into DataFrames.
- DuckDB runs fast SQL directly on CSV/Parquet files and pandas DataFrames.
- SQLAlchemy connects to MySQL, PostgreSQL, SQL Server and warehouses with a URL; keep credentials in environment variables.

## Quick quiz

6 questions · tap an answer to check it

**1. How should user input be passed into a SQL query?**

A With an f-string

B As parameters with placeholders ( `?` , `%s` , `:name` )

C With string concatenation

D In a comment

**Answer: B.** Placeholders prevent SQL injection.

**2. What does `with con:` do in sqlite3?**

A Opens a file

B Commits if the block succeeds and rolls back on an exception

C Closes the database

D Creates a table

**Answer: B.** It makes the block a transaction.

**3. Which writes a DataFrame to a database table?**

A `pd.read_sql`

B `df.to_sql("table", con)`

C `df.to_csv`

D `con.fetchall`

**Answer: B.** `if_exists` controls replace/append.

**4. What is special about DuckDB?**

A It requires a server

B It runs in-process and can query CSV, Parquet and DataFrames directly with SQL

C It only stores text

D It replaces pandas entirely

**Answer: B.** It is optimised for analytics.

**5. Where should a database password be stored?**

A In the notebook

B In an environment variable or secrets manager

C In the SQL query

D On GitHub

**Answer: B.** Never commit credentials.

**6. Why aggregate in SQL before loading into pandas?**

A SQL is always faster to write

B Only the small summary travels over the network and into memory

C pandas cannot aggregate

D It is required

**Answer: B.** Push heavy work to the database.

EXERCISE

## Practice

(1) Load `customers.csv` and `superstore_sales.csv` into SQLite. (2) In SQL, find the top 5 cities by profit and read the result into pandas. (3) Repeat with DuckDB directly on the CSV files. (4) Write a function `get_sales(con, region)` that uses a parameterised query.

**Show solution (worked answer)**

Python

```
con = sqlite3.connect(":memory:")
pd.read_csv("customers.csv").to_sql("customers", con, index=False)
pd.read_csv("superstore_sales.csv").to_sql("sales", con, index=False)
print(pd.read_sql("SELECT city, SUM(profit) p FROM sales GROUP BY city ORDER BY p DESC
LIMIT 5", con))
print(duckdb.sql("SELECT city, SUM(profit) p FROM 'superstore_sales.csv' GROUP BY city
ORDER BY p DESC LIMIT 5").df())
def get_sales(con, region):
    return pd.read_sql("SELECT SUM(sales) AS sales FROM sales WHERE region = ?", con,
params=(region,))
print(get_sales(con, "West"))
```

INTERVIEW CORNER

## Questions you may be asked

**Q: What is SQL injection and how do you prevent it?** Malicious input that changes a query's meaning; prevent it with parameterised queries (and least-privilege accounts, input validation, ORMs).

**Q: How do you load a 50 GB table for analysis?** Aggregate or sample in the database, read in chunks, or use a columnar engine (DuckDB, Spark, the warehouse itself) instead of pulling everything into pandas.

**Q: What does ACID mean?** Atomicity, Consistency, Isolation, Durability: transactions are all-or-nothing, keep rules valid, do not interfere, and survive crashes.

PYTHON FOR DATA SCIENCE · LESSON 24

# APIs, JSON and Web Scraping with requests and BeautifulSoup

Collect data from the web. Understand HTTP, call REST APIs with requests (GET/POST, query parameters, headers, authentication, pagination, retries and rate limits), flatten nested JSON with json_normalize, and scrape HTML tables and pages responsibly with BeautifulSoup and pandas.read_html.


Python class 18 · ✦ requests 2.3x · httpx · BeautifulSoup 4 · Intermediate · ⏱ 100 min

**By the end of this lesson you can**

- Explain HTTP methods, status codes, headers and JSON responses
- Call REST APIs with parameters, headers and API keys stored safely
- Handle pagination, timeouts, retries and rate limits
- Flatten nested JSON into DataFrames with json_normalize
- Scrape HTML with BeautifulSoup and read_html, respecting robots.txt and terms of use

## HTTP in five minutes

An **API** (Application Programming Interface) lets programs ask another system for data. Web APIs use **HTTP**: the client sends a **request** (method, URL, headers, optional body) and receives a **response** (status code, headers, body, usually JSON).




A REST API call.

| Method | Meaning | Status code | Meaning |
|---|---|---|---|
| `GET` | Read | `200` | OK |
| `POST` | Create / send data | `201` | Created |
| `PUT` / `PATCH` | Replace / update | `400` | Bad request |
| `DELETE` | Remove | `401` / `403` | Not authenticated / not allowed |
| | | `404` | Not found |
| | | `429` | Too many requests (rate limit) |
| | | `500` – `503` | Server error: retry later |

## A practice API

To keep this lesson runnable offline, we start a tiny local API that behaves like a real one (paginated orders, an API key, a rate limit). Every call below works the same way against real services.

Python

```
import json, threading, time
from http.server import BaseHTTPRequestHandler, HTTPServer
from urllib.parse import urlparse, parse_qs
ORDERS = [{"id": i, "customer": {"name": n, "city": c}, "items": [{"sku": f"P{i}", "qty": i
% 3 + 1, "price": 100.0 * i}], "status": s}
          for i, (n, c, s) in enumerate([("Asha", "Pune", "shipped"), ("Ravi", "Delhi",
"new"), ("Meera", "Kochi", "shipped"), ("Kabir", "Goa", "cancelled"), ("Zoya", "Pune",
"new")], 1)]
HITS = {"n": 0}
class Api(BaseHTTPRequestHandler):
    def log_message(self, *a): pass
    def send(self, code, body, ctype="application/json"):
        self.send_response(code); self.send_header("Content-Type", ctype);
self.end_headers(); self.wfile.write(body.encode())
    def do_GET(self):
        u = urlparse(self.path); q = parse_qs(u.query)
        if u.path == "/page": return self.send(200, "<html><body><h1>Prices</h1><table
id='p'><tr><th>Product</th><th>Price</th></tr><tr><td>Chair</td><td>₹4,500</td></tr><tr>
<td>Desk</td><td>₹12,000</td></tr></table><a href='/about'>About</a><p class='note'>Updated
daily</p></body></html>", "text/html; charset=utf-8")
        if self.headers.get("X-API-Key") != "demo-key": return self.send(401,
json.dumps({"error": "missing or bad API key"}))
        HITS["n"] += 1
        if u.path == "/flaky" and HITS["n"] % 2: return self.send(503, json.dumps({"error":
"busy"}))
        if u.path in ("/orders", "/flaky"):
            page, size = int(q.get("page", [1])[0]), int(q.get("size", [2])[0]); st =
q.get("status", [None])[0]
            rows = [o for o in ORDERS if not st or o["status"] == st]
            return self.send(200, json.dumps({"data": rows[(page - 1) * size: page * size],
"page": page, "next": page + 1 if page * size < len(rows) else None}))
        self.send(404, json.dumps({"error": "not found"}))
    def do_POST(self):
        body = json.loads(self.rfile.read(int(self.headers["Content-Length"])))
        self.send(201, json.dumps({"created": True, "echo": body}))
srv = HTTPServer(("127.0.0.1", 0), Api); BASE = f"http://127.0.0.1:{srv.server_port}"
threading.Thread(target=srv.serve_forever, daemon=True).start()
print("practice API running on this machine at", BASE.rsplit(":", 1)[0])
```

OUTPUT

```
practice API running on this machine at http://127.0.0.1
```

## GET requests with requests

Python

```
import requests, os
os.environ.setdefault("DEMO_API_KEY", "demo-key")                # in real life, set this
outside the code
headers = {"X-API-Key": os.environ["DEMO_API_KEY"], "Accept": "application/json"}
r = requests.get(f"{BASE}/orders", params={"page": 1, "size": 2}, headers=headers,
timeout=10)
print(r.status_code, r.url.replace(BASE, "BASE"), r.headers["Content-Type"])
payload = r.json()
print(payload["page"], payload["next"], payload["data"][0]["customer"])
bad = requests.get(f"{BASE}/orders", timeout=10)
print(bad.status_code, bad.json())
try: bad.raise_for_status()
except requests.HTTPError as e: print("HTTPError:", str(e)[:40])
```

OUTPUT

```
200 BASE/orders?page=1&size=2 application/json
1 2 {'name': 'Asha', 'city': 'Pune'}
401 {'error': 'missing or bad API key'}
HTTPError: 401 Client Error: Unauthorized for url:
```

Always set a `timeout`, check the status (`raise_for_status()`), and keep keys in environment variables.

## POST requests

Python

```
r = requests.post(f"{BASE}/orders", json={"customer": "Asha", "items": [{"sku": "P9",
"qty": 1}]}, headers=headers, timeout=10)
print(r.status_code, r.json())
```

OUTPUT

```
201 {'created': True, 'echo': {'customer': 'Asha', 'items': [{'sku': 'P9', 'qty':
1}]}}
```

`json=` serialises the body and sets the `Content-Type` header for you. Use `data=` for form posts and `files=` for uploads.

## Pagination, retries and rate limits

Python

```
def fetch_all(path, params=None, max_pages=50):
    rows, page = [], 1
    with requests.Session() as session:                          # re-uses the connection
        session.headers.update(headers)
        while page and page ⩽ max_pages:
            resp = session.get(f"{BASE}{path}", params={**(params or {}), "page": page,
"size": 2}, timeout=10)
            resp.raise_for_status()
            body = resp.json(); rows += body["data"]; page = body["next"]
    return rows
orders = fetch_all("/orders"); print(len(orders), "orders fetched across pages")

def get_with_retry(url, tries=4, backoff=0.2, **kw):
    for attempt in range(1, tries + 1):
        resp = requests.get(url, timeout=10, **kw)
        if resp.status_code not in (429, 500, 502, 503, 504): return resp
        wait = float(resp.headers.get("Retry-After", backoff * 2 ** (attempt - 1)))     #
exponential backoff
        print(f"  attempt {attempt}: {resp.status_code}, retrying in {wait:.1f}s");
time.sleep(wait)
    resp.raise_for_status()
print(get_with_retry(f"{BASE}/flaky", headers=headers).status_code)
```

OUTPUT

```
5 orders fetched across pages
  attempt 1: 503, retrying in 0.2s
200
```

Respect rate limits: read the API's documented limits, honour `Retry-After`, cache results, and sleep between calls.

## Flattening nested JSON

Python

```
import pandas as pd
pd.set_option("display.width", 160)
flat = pd.json_normalize(orders, sep="_")
print(flat.drop(columns="items"))
lines = pd.json_normalize(orders, record_path="items", meta=["id", "status", ["customer",
"city"]], sep="_")
lines["value"] = lines.qty * lines.price
print(lines)
```

OUTPUT

```
   id     status customer_name customer_city
0   1    shipped          Asha          Pune
1   2        new          Ravi         Delhi
2   3    shipped         Meera         Kochi
3   4  cancelled         Kabir           Goa
4   5        new          Zoya          Pune
  sku  qty  price id     status customer_city   value
0  P1    2  100.0  1    shipped          Pune   200.0
1  P2    3  200.0  2        new         Delhi   600.0
2  P3    1  300.0  3    shipped         Kochi   300.0
3  P4    2  400.0  4  cancelled           Goa   800.0
4  P5    3  500.0  5        new          Pune  1500.0
```

`record_path` explodes a nested list into rows; `meta` copies parent fields onto each row.

## Real public APIs to practise with

| API | Data | Notes |
|---|---|---|
| data.gov.in | Indian government open data | Free API key |
| RBI DBIE, World Bank, IMF | Economic indicators | `wbgapi` package for the World Bank |
| Open-Meteo | Weather forecasts and history | No key |
| GitHub REST API | Repositories, issues | Token raises limits |
| Alpha Vantage, yfinance | Stock prices | Free tiers, rate-limited |
| OpenAI, Anthropic, Gemini | LLMs | Paid keys, see GenAI track |

Python

```
# Example (needs internet): daily max temperature in Pune from Open-Meteo
r = requests.get("https://api.open-meteo.com/v1/forecast",
                 params={"latitude": 18.52, "longitude": 73.86, "daily":
"temperature_2m_max", "timezone": "Asia/Kolkata"}, timeout=10)
weather = pd.DataFrame(r.json()["daily"])
```

## Web scraping

When there is no API, you can parse HTML. **BeautifulSoup** navigates the HTML tree; `pandas.read_html` grabs `<table>` elements directly.

Python

```
from bs4 import BeautifulSoup
from io import StringIO
html = requests.get(f"{BASE}/page", timeout=10).text
soup = BeautifulSoup(html, "html.parser")
print(soup.h1.text, "|", soup.find("p", class_="note").get_text(strip=True), "|",
[a["href"] for a in soup.find_all("a")])
rows = [[td.get_text(strip=True) for td in tr.find_all(["td", "th"])] for tr in
soup.select("table#p tr")]
print(rows)
t = pd.read_html(StringIO(html))[0]
t["Price"] = t["Price"].str.replace(r"[₹,]", "", regex=True).astype(int)
print(t, t.Price.sum())
srv.shutdown()
```

OUTPUT

```
Prices | Updated daily | ['/about']
[['Product', 'Price'], ['Chair', '₹4,500'], ['Desk', '₹12,000']]
  Product  Price
0   Chair   4500
1    Desk  12000 16500
```

| BeautifulSoup | Finds |
|---|---|
| `soup.find("tag", class_="x")` | First match |
| `soup.find_all("a")` | All matches |
| `soup.select("div.card > h2")` | CSS selectors |
| `el.get_text(strip=True)` , `el["href"]` | Text and attributes |

For pages built by JavaScript, use **Playwright** or Selenium to drive a real browser, or look in the browser's Network tab for the underlying JSON API.

WATCH OUT **Scrape responsibly and legally**

Check the site's **terms of use** and **robots.txt**, prefer official APIs, identify your scraper with a User-Agent, go slowly (one request every few seconds), cache pages, and never collect personal data without a lawful basis (India's DPDP Act 2023, GDPR). Logged-in or paywalled content is usually off-limits.

# Summary

**KEY TAKEAWAYS**

- HTTP: methods (GET, POST…), status codes (200, 401, 404, 429, 5xx), headers and JSON bodies.
- `requests.get(url, params=, headers=, timeout=)` ; `r.json()` ; `r.raise_for_status()` ; keys from environment variables.
- Loop over pages with a `Session` ; retry 429/5xx with exponential backoff and honour `Retry-After` .
- `pd.json_normalize(data, record_path=, meta=)` flattens nested JSON.
- Scrape with BeautifulSoup or `pd.read_html` only when allowed; prefer APIs and be polite.

## Quick quiz

6 questions · tap an answer to check it

**1. What does status code 429 mean?**

A Not found

B Too many requests (rate limit)

C Server error

D Success

**Answer: B.** Slow down and retry after the indicated time.

**2. Why set `timeout=` on every request?**

A It speeds up requests

B Without it, a request can hang forever

C It is required by APIs

D To retry automatically

**Answer: B.** Typical values are 5–30 seconds.

**3. Where should an API key be kept?**

A In the URL in your notebook

B In an environment variable or secrets store

C In a GitHub README

D In a comment

**Answer: B.** Read it with `os.getenv`.

**4. What does `json_normalize(..., record_path="items")` do?**

A Deletes the items field

B Creates one row per element of each record's items list

C Converts to CSV

D Sorts the data

**Answer: B.** `meta` keeps parent fields.

**5.** Which is the best first option to get data from a website?

A An official API or data download

B Scraping every page quickly

C Copy-paste

D A screenshot

**Answer: A.** Scraping is a fallback.

**6.** Which tool can read every `<table>` on a page into DataFrames?

A `requests.post`

B `pd.read_html`

C `json.loads`

D `soup.h1`

**Answer: B.** It returns a list of DataFrames.

EXERCISE **Practice**

(1) Using the Open-Meteo example (on your machine), fetch 7 days of forecasts for three cities and combine them into one DataFrame. (2) Write `fetch_all` for an API that uses `offset` / `limit` instead of pages. (3) Scrape the list of tables from a Wikipedia page of your choice with `read_html` and clean one of them.

**Show solution (worked answer)**

Python

```
cities = {"Pune": (18.52, 73.86), "Delhi": (28.61, 77.21), "Kochi": (9.93, 76.27)}
frames = []
for name, (lat, lon) in cities.items():
    r = requests.get("https://api.open-meteo.com/v1/forecast", params={"latitude":
lat, "longitude": lon, "daily": "temperature_2m_max", "timezone": "Asia/Kolkata"},
timeout=10)
    frames.append(pd.DataFrame(r.json()["daily"]).assign(city=name))
df = pd.concat(frames)
def fetch_offset(url, limit=100):
    out, offset = [], 0
    while True:
        batch = requests.get(url, params={"offset": offset, "limit": limit},
timeout=10).json()
        if not batch: return out
        out += batch; offset += limit
```

INTERVIEW CORNER **Questions you may be asked**

**Q: How do you collect data from a paginated API reliably?** Use a session, loop until there is no next page/cursor, set timeouts, retry 429/5xx with backoff, respect rate limits, log progress, and make the job restartable.

**Q: API vs web scraping?** APIs are stable, documented and permitted; scraping depends on page structure, can break, and has legal and ethical limits.

**Q: How do you turn nested JSON into a table?** `pd.json_normalize` with `record_path` and `meta`, or explode list columns and expand dict columns.

PYTHON FOR DATA SCIENCE · LESSON 25

# Performance and Bigger Data: Vectorisation, Memory, Parquet, Polars and DuckDB

Make Python data work fast and scale beyond memory. Measure with timeit, replace loops with vectorised code, shrink DataFrames with the right dtypes, store data as Parquet, use Polars lazy queries and DuckDB for out-of-core analytics, and know when to move to Spark and the cloud.

Python class 19 · ✦ pandas 3 · Polars 1.x/2.x · DuckDB · PyArrow · Intermediate · ⏱ 100 min

**By the end of this lesson you can**

- Measure speed and memory before optimising
- Replace row loops and apply with vectorised pandas and NumPy operations
- Reduce memory with categories, smaller numeric types and selected columns
- Store and read data efficiently with Parquet and explain columnar formats
- Write equivalent queries in pandas, Polars and DuckDB and choose between them

## Measure first

"Premature optimisation is the root of all evil" (Donald Knuth). Profile, find the slow part, fix that.

Python

```
import pandas as pd, numpy as np, time, timeit
s = pd.read_csv("superstore_sales.csv", parse_dates=["order_date"])
big = pd.concat([s] * 20, ignore_index=True)                # ~126k rows to make timings visible
print(big.shape)
def t(fn, n=3): return min(timeit.repeat(fn, number=1, repeat=n)) * 1000
loop = lambda: [r.sales * (1 - r.discount) for r in big.itertuples()]
apply_ = lambda: big.apply(lambda r: r["sales"] * (1 - r["discount"]), axis=1)
vec = lambda: big["sales"] * (1 - big["discount"])
print(f"itertuples loop {t(loop, 1):8.1f} ms\napply(axis=1)   {t(apply_, 1):8.1f} ms\nvectorised      {t(vec):8.2f} ms")
```

OUTPUT

```
(126460, 19)
itertuples loop   1070.5 ms
apply(axis=1)      659.5 ms
vectorised           0.65 ms
```

The vectorised version is more than a thousand times faster. `itertuples` and `apply(axis=1)` take about the same time because both are Python loops (`apply` with `axis=1` is a loop in disguise), and `iterrows` is slower still.

## Vectorising conditional logic

Python

```python
def band_loop(d): return "high" if d > 0.2 else "mid" if d > 0 else "none"
f1 = lambda: big["discount"].map(band_loop)
f2 = lambda: np.select([big.discount > 0.2, big.discount > 0], ["high", "mid"],
default="none")
f3 = lambda: pd.cut(big.discount, [-1, 0, 0.2, 1], labels=["none", "mid", "high"])
print(f"map(func) {t(f1):.1f} ms | np.select {t(f2):.1f} ms | pd.cut {t(f3):.1f} ms")
print((f1().values == f2()).all())
```

OUTPUT

```
map(func) 15.6 ms | np.select 1.0 ms | pd.cut 1.5 ms
True
```

| Slow pattern | Faster pattern |
|---|---|
| `for` / `iterrows` over rows | Column arithmetic, `np.where`, `np.select` |
| `apply(axis=1)` | Vectorised expression, or `groupby().transform` |
| Growing a DataFrame in a loop (`concat` each time) | Collect a list of dicts, build once |
| String ops in Python loops | `.str` methods |
| Repeated `df[df.x == k]` in a loop | One `groupby` |
| Reading a big CSV many times | Read once, save as Parquet |

# Memory

Python

```
def mb(df): return df.memory_usage(deep=True).sum() / 1e6
print(f"original: {mb(big):.1f} MB")
small = big.copy()
for c in ["region", "segment", "category", "sub_category", "ship_mode", "state", "city"]:
small[c] = small[c].astype("category")
small["quantity"] = pd.to_numeric(small["quantity"], downcast="integer")
small[["sales", "profit", "discount"]] = small[["sales", "profit",
"discount"]].astype("float32")
print(f"categories + downcast: {mb(small):.1f} MB")
print(small.dtypes.astype(str).value_counts().to_dict())
```

OUTPUT

```
original: 34.7 MB
categories + downcast: 18.3 MB
{'category': 7, 'str': 6, 'float32': 3, 'int64': 1, 'datetime64[us]': 1, 'int8': 1}
```

Categories store each label once plus small integer codes: ideal for columns with few distinct values. Also read only needed columns ( `usecols=` ) and stream with `chunksize=` .


Python

```
total = 0.0
for chunk in pd.read_csv("superstore_sales.csv", usecols=["region", "sales"],
chunksize=2000):
    total += chunk.loc[chunk.region == "West", "sales"].sum()
print(f"West sales via chunks: {total:,.0f}")
```

OUTPUT

```
West sales via chunks: 51,958,520
```

# Parquet: the analytics file format




CSV is row-oriented text; Parquet stores each column together, typed and compressed.

Python

```
import os
big.to_csv("big.csv", index=False); big.to_parquet("big.parquet", index=False)
print(f"CSV {os.path.getsize('big.csv')/1e6:.1f} MB | Parquet
{os.path.getsize('big.parquet')/1e6:.1f} MB")
print(f"read CSV {t(lambda: pd.read_csv('big.csv')):.0f} ms | read Parquet {t(lambda:
pd.read_parquet('big.parquet')):.0f} ms | two columns {t(lambda:
pd.read_parquet('big.parquet', columns=['region', 'sales'])):.0f} ms")
```

OUTPUT

```
CSV 21.7 MB | Parquet 1.9 MB
read CSV 249 ms | read Parquet 15 ms | two columns 5 ms
```

# Polars: fast DataFrames with lazy queries

**Polars** is a DataFrame library written in Rust. It uses all CPU cores, the Arrow memory format, and a **lazy** mode that optimises the whole query before running it.

Python

```python
import polars as pl
lazy = (pl.scan_parquet("big.parquet")                          # nothing is read yet
          .filter(pl.col("discount") ⩽ 0.1)
          .group_by("region", "category")
          .agg(sales=pl.col("sales").sum(), profit=pl.col("profit").sum(), lines=pl.len())
          .with_columns(margin=(100 * pl.col("profit") / pl.col("sales")).round(1),
sales_m=(pl.col("sales") / 1e6).round(2))
          .drop("profit")
          .sort("sales", descending=True))
print(lazy.head(4).collect().drop("sales"))
pandas_way = lambda: (big[big.discount ⩽ 0.1].groupby(["region", "category"]).agg(sales=
("sales", "sum"), profit=("profit", "sum")))
print(f"pandas {t(pandas_way):.1f} ms | polars lazy {t(lambda: lazy.collect()):.1f} ms |
polars {pl.__version__}")
```

OUTPUT

```
shape: (4, 5)
```

| region | category | lines | margin | sales_m |
|---|---|---|---|---|
| str | str | u32 | f64 | f64 |
| South | Technology | 7220 | 15.9 | 642.79 |
| West | Technology | 7080 | 16.1 | 604.14 |
| North | Technology | 6720 | 16.6 | 598.63 |
| East | Technology | 6320 | 17.5 | 531.33 |

```
pandas 22.0 ms | polars lazy 3.9 ms | polars 2.1.0
```

| pandas | Polars |
|---|---|
| `df[df.x > 1]` | `df.filter(pl.col("x") > 1)` |
| `df.assign(y=df.x * 2)` | `df.with_columns(y=pl.col("x") * 2)` |
| `df.groupby("g").agg(s=("x", "sum"))` | `df.group_by("g").agg(s=pl.col("x").sum())` |
| `df.sort_values("x")` | `df.sort("x")` |
| `pd.read_csv` | `pl.read_csv` / lazy `pl.scan_csv` |
| `df.to_pandas()` ↔ `pl.from_pandas(df)` | Convert when a library needs pandas |

## DuckDB on files larger than memory

Python

```
import duckdb
q = """
SELECT region, category, ROUND(SUM(sales)/1e6, 2) AS sales_m,
ROUND(100*SUM(profit)/SUM(sales), 1) AS margin
FROM 'big.parquet' WHERE discount ⩽ 0.1 GROUP BY ALL ORDER BY sales_m DESC LIMIT 4
"""
print(duckdb.sql(q).df())
print(f"duckdb {t(lambda: duckdb.sql(q).fetchall()):.1f} ms")
for f in ("big.csv", "big.parquet"): os.remove(f)
```

OUTPUT

```
  region    category  sales_m  margin
0  South  Technology   642.79    15.9
1   West  Technology   604.14    16.1
2  North  Technology   598.63    16.6
3   East  Technology   531.33    17.5
duckdb 7.0 ms
```

DuckDB and Polars stream data in batches, so they can process files bigger than RAM on a laptop. Folders of Parquet files ( `'data/*.parquet'` ) work the same way.

## Going further

| Need | Tool |
|---|---|
| Use all CPU cores for custom Python | `concurrent.futures` , `joblib.Parallel` , multiprocessing |
| Speed up numeric Python loops | Numba ( `@njit` ), Cython |
| Data bigger than one machine | Apache Spark (PySpark), Databricks, Dask, Ray |
| Warehouse-scale SQL | BigQuery, Snowflake, Redshift, Databricks SQL |
| GPU DataFrames | RAPIDS cuDF ( `cudf.pandas` ) |

Rule of thumb: up to a few GB → pandas with good dtypes; up to ~100 GB on one machine → Polars or DuckDB with Parquet; beyond that or many users → Spark or a cloud warehouse.

# Summary

**KEY TAKEAWAYS**

- Measure with `timeit` / `%timeit` before optimising; fix the bottleneck.
- Vectorise: column arithmetic, `np.where` / `np.select`, `pd.cut`, `.str`, `groupby`; avoid `iterrows` and `apply(axis=1)`.
- Save memory with categories, downcasting, `usecols` and `chunksize`.
- Parquet is columnar, typed and compressed: faster and smaller than CSV.
- Polars (lazy, multi-core) and DuckDB (SQL, out-of-core) handle data beyond pandas; Spark and warehouses go beyond one machine.

## Quick quiz

6 questions · tap an answer to check it

**1. Which is usually fastest for row-wise arithmetic?**

**A** iterrows

**B** apply(axis=1)

**C** A vectorised column expression

**D** A while loop

**Answer: C.** Vectorised code runs in compiled loops.

**2. Why convert a text column with 4 distinct values to `category` ?**

- **A** It stores each label once with small integer codes, saving memory and speeding groupby
- **B** It sorts the data
- **C** It is required for charts
- **D** It removes missing values

**Answer: A.** Ideal for low-cardinality columns.

**3. What is the main advantage of Parquet over CSV?**

- **A** Human-readable
- **B** Columnar, typed and compressed, so it is smaller and faster to read
- **C** Supported only by Excel
- **D** No schema

**Answer: B.** You can read just the columns you need.

**4. What does Polars' `scan_parquet(...)` do?**

- **A** Reads the whole file immediately
- **B** Creates a lazy query that is optimised and executed on `.collect()`
- **C** Writes a file
- **D** Converts to CSV

**Answer: B.** Lazy evaluation enables predicate and projection push-down.

**5.** **Which tool queries Parquet files with SQL without a server?**

A MySQL

B DuckDB

C Excel

D requests

**Answer: B.** It also queries pandas DataFrames.

**6.** **When should you consider Spark or a cloud warehouse?**

A For 10,000 rows

B When data or users exceed what one machine can handle

C Always

D Never

**Answer: B.** Start simple; scale when needed.

EXERCISE

## Practice

(1) Time `iterrows`, `apply(axis=1)` and a vectorised version of `profit / sales` on `big`.
(2) Reduce the memory of `superstore_sales.csv` by at least 50% and report the percentage.
(3) Rewrite a pandas groupby from Lesson 18 in Polars and in DuckDB SQL and check that the numbers match.

### Show solution (worked answer)

Python

```
print(t(lambda: [r["profit"] / r["sales"] for _, r in big.head(20000).iterrows()], 1))
print(t(lambda: big.profit / big.sales))
before = mb(s); s2 = s.copy()
for c in s2.select_dtypes("object").columns.union(s2.select_dtypes("string").columns):
    if s2[c].nunique() < 100: s2[c] = s2[c].astype("category")
print(f"{100 * (1 - mb(s2) / before):.0f}% smaller")
pl_res =
pl.from_pandas(s).group_by("region").agg(pl.col("sales").sum()).sort("region")
dd_res = duckdb.sql("SELECT region, SUM(sales) sales FROM s GROUP BY region ORDER BY
region").df()
```

INTERVIEW CORNER

## Questions you may be asked

**Q: Your pandas script is slow. What do you do?** Profile to find the slow step; vectorise loops and `apply`; reduce data early (filter, `usecols`); fix dtypes; avoid repeated work; save intermediate results as Parquet; consider Polars/DuckDB or pushing work to SQL.

**Q: Why is Parquet popular in data lakes?** Columnar storage enables compression and reading only needed columns; it stores the schema; and every major engine reads it.

**Q: pandas vs Polars?** pandas has the biggest ecosystem; Polars is faster and more memory-efficient thanks to Rust, multi-threading and lazy optimisation. Many teams use both and convert where needed.

PYTHON FOR DATA SCIENCE · LESSON 26

# DSA I: Big-O, Arrays, Strings, Hashing, Two Pointers and Sliding Window

Data structures and algorithms for data-analyst, data-scientist and data-engineer interviews. Learn Big-O time and space complexity, then the patterns that solve most array and string questions (hash maps and sets, prefix sums, two pointers, sliding window), with worked interview problems and timings.

DSA for data roles (added) · Python 3.13 · Intermediate · 120 min

**By the end of this lesson you can**


- Estimate time and space complexity with Big-O and compare common growth rates
- Know the cost of operations on lists, dicts, sets and deques
- Solve array and string problems with hash maps, counting and prefix sums
- Apply the two-pointer and sliding-window patterns
- Explain trade-offs out loud as in a coding interview

## Why DSA for data roles?

Data interviews (Amazon, Flipkart, Walmart, fintechs, product companies) often include one or two coding rounds with easy–medium problems on arrays, strings, hash maps and SQL. Beyond interviews, complexity thinking explains why a join on a set is instant while a nested loop over two million rows never finishes.

## Big-O notation

**Big-O** describes how running time (or memory) grows with input size *n*, ignoring constants.




Growth of common complexity classes. At n = 1,000,000 the difference between O(n log n) and O(n²) is days versus a second.

| Big-O | Name | Example |
|---|---|---|
| O(1) | Constant | Dict lookup, list index, append |
| O(log n) | Logarithmic | Binary search, balanced-tree lookup |
| O(n) | Linear | One loop, `x in list`, `sum` |
| O(n log n) | Linearithmic | Sorting ( `sorted` , Timsort), merge sort |
| O(n²) | Quadratic | Nested loops over the same data |
| O(2ⁿ) | Exponential | All subsets, naive recursion for Fibonacci |

Rules: drop constants (O(2n) → O(n)); keep the dominant term (O(n² + n) → O(n²)); sequential steps add, nested steps multiply.

Python

```
import time
def has_duplicate_quadratic(a):
    for i in range(len(a)):
        for j in range(i + 1, len(a)):
            if a[i] == a[j]: return True
    return False
def has_duplicate_set(a): return len(set(a)) != len(a)
for n in (1000, 2000, 4000):
    data = list(range(n))
    t0 = time.perf_counter(); has_duplicate_quadratic(data); t1 = time.perf_counter();
has_duplicate_set(data); t2 = time.perf_counter()
    print(f"n={n:5d}: nested loops {1000*(t1-t0):7.1f} ms | set {1000*(t2-t1):.3f} ms")
```

OUTPUT

```
n= 1000: nested loops    15.1 ms | set 0.022 ms
n= 2000: nested loops    59.7 ms | set 0.042 ms
n= 4000: nested loops   261.3 ms | set 0.088 ms
```

Doubling *n* roughly quadruples the nested-loop time ($O(n^2)$) but only doubles the set version ($O(n)$).

## Cost of Python operations

| Operation | list | dict / set | deque |
|---|---|---|---|
| Index `a[i]` | O(1) | — | O(n) |
| Append / pop at end | O(1) | add O(1) | O(1) |
| Insert / pop at front | **O(n)** | — | **O(1)** |
| `x in c` | **O(n)** | **O(1)** | O(n) |
| Sort | O(n log n) | — | — |

# Pattern 1: hash maps and counting

Turn "search inside a loop" ($O(n^2)$) into "look up in a dict/set" ($O(n)$).

Python

```python
def two_sum(nums, target):
    """Return indices of two numbers adding up to target. O(n) time, O(n) space."""
    seen = {}                                   # value → index
    for i, x in enumerate(nums):
        if target - x in seen: return [seen[target - x], i]
        seen[x] = i
    return []
print(two_sum([2, 7, 11, 15], 9), two_sum([3, 2, 4], 6), two_sum([1, 2], 7))

from collections import Counter, defaultdict
def is_anagram(a, b): return Counter(a) == Counter(b)
def group_anagrams(words):
    g = defaultdict(list)
    for w in words: g["".join(sorted(w))].append(w)
    return list(g.values())
def first_unique_char(s):
    c = Counter(s)
    return next((i for i, ch in enumerate(s) if c[ch] == 1), -1)
def top_k_frequent(nums, k): return [x for x, _ in Counter(nums).most_common(k)]
print(is_anagram("listen", "silent"), group_anagrams(["eat", "tea", "tan", "ate", "nat",
"bat"]), first_unique_char("leetcode"), top_k_frequent([1, 1, 1, 2, 2, 3], 2))
```

OUTPUT

```
[0, 1] [1, 2] []
True [['eat', 'tea', 'ate'], ['tan', 'nat'], ['bat']] 0 [1, 2]
```

## Pattern 2: prefix sums

Precompute running totals so any range sum is O(1).

Python

```python
from itertools import accumulate
sales = [5, 3, 8, 6, 2, 7]
prefix = [0] + list(accumulate(sales))               # prefix[i] = sum of first i items
range_sum = lambda i, j: prefix[j + 1] - prefix[i]    # sum of sales[i..j]
print(prefix, range_sum(1, 3), range_sum(0, 5))

def subarray_sum_equals_k(nums, k):
    """Count contiguous subarrays summing to k. O(n) with prefix sums + a counter."""
    count, running, seen = 0, 0, Counter({0: 1})
    for x in nums:
        running += x
        count += seen[running - k]
        seen[running] += 1
    return count
print(subarray_sum_equals_k([1, 1, 1], 2), subarray_sum_equals_k([1, 2, 3, -3, 3], 3))
```

OUTPUT

```
[0, 5, 8, 16, 22, 24, 31] 17 31
2 5
```

## Pattern 3: two pointers

Two indices move toward each other (or in the same direction) through a **sorted** array or string.

Python


```python
def is_palindrome(s):
    s = [c.lower() for c in s if c.isalnum()]
    i, j = 0, len(s) - 1
    while i < j:
        if s[i] != s[j]: return False
        i += 1; j -= 1
    return True
def pair_with_sum_sorted(a, target):
    i, j = 0, len(a) - 1
    while i < j:
        total = a[i] + a[j]
        if total == target: return a[i], a[j]
        if total < target: i += 1
        else: j -= 1
    return None
def remove_duplicates_sorted(a):              # in place, returns new length
    if not a: return 0
    w = 1
    for r in range(1, len(a)):
        if a[r] != a[w - 1]: a[w] = a[r]; w += 1
    return w
def merge_sorted(a, b):
    i = j = 0; out = []
    while i < len(a) and j < len(b):
        if a[i] <= b[j]: out.append(a[i]); i += 1
        else: out.append(b[j]); j += 1
    return out + a[i:] + b[j:]
arr = [1, 1, 2, 3, 3, 3, 4]; n = remove_duplicates_sorted(arr)
print(is_palindrome("A man, a plan, a canal: Panama"), pair_with_sum_sorted([1, 3, 4, 6,
9], 10), arr[:n], merge_sorted([1, 4, 9], [2, 3, 10]))
```

OUTPUT

```
True (1, 9) [1, 2, 3, 4] [1, 2, 3, 4, 9, 10]
```

## Pattern 4: sliding window

Keep a window `[left, right]` and slide it, updating a running state instead of recomputing.




A sliding window adds the new element on the right and removes the old one on the left.

Python

```
def max_sum_window(a, k):
    window = best = sum(a[:k])
    for r in range(k, len(a)):
        window += a[r] - a[r - k]
        best = max(best, window)
    return best
def longest_unique_substring(s):
    last, left, best = {}, 0, 0
    for right, ch in enumerate(s):
        if ch in last and last[ch] ⩾ left: left = last[ch] + 1     # shrink past the
repeat
        last[ch] = right; best = max(best, right - left + 1)
    return best
def min_window_at_least(nums, target):          # shortest subarray with sum ⩾ target
(positive numbers)
    left = total = 0; best = float("inf")
    for right, x in enumerate(nums):
        total += x
        while total ⩾ target:
            best = min(best, right - left + 1); total -= nums[left]; left += 1
    return 0 if best == float("inf") else best
print(max_sum_window([2, 1, 5, 1, 3, 2], 3), longest_unique_substring("abcabcbb"),
longest_unique_substring("pwwkew"), min_window_at_least([2, 3, 1, 2, 4, 3], 7))
```

OUTPUT

```
9 3 3 2
```

The same idea appears in SQL window functions and in pandas `rolling`: a 7-day moving average is a sliding window.

## Classic array problems


Python

```
def max_profit(prices):                          # best single buy then sell
    lo, best = float("inf"), 0
    for p in prices: lo = min(lo, p); best = max(best, p - lo)
    return best
def max_subarray(nums):                          # Kadane's algorithm
    cur = best = nums[0]
    for x in nums[1:]: cur = max(x, cur + x); best = max(best, cur)
    return best
def product_except_self(nums):
    n = len(nums); out = [1] * n; left = right = 1
    for i in range(n): out[i] = left; left *= nums[i]
    for i in range(n - 1, -1, -1): out[i] *= right; right *= nums[i]
    return out
def move_zeroes(a):
    w = 0
    for x in a:
        if x != 0: a[w] = x; w += 1
    a[w:] = [0] * (len(a) - w); return a
def rotate(a, k): k %= len(a); return a[-k:] + a[:-k]
print(max_profit([7, 1, 5, 3, 6, 4]), max_subarray([-2, 1, -3, 4, -1, 2, 1, -5, 4]),
product_except_self([1, 2, 3, 4]), move_zeroes([0, 1, 0, 3, 12]), rotate([1, 2, 3, 4, 5],
2))
```

OUTPUT

```
5 6 [24, 12, 8, 6] [1, 3, 12, 0, 0] [4, 5, 1, 2, 3]
```

## How to answer in an interview




A calm, structured approach scores better than jumping into code.

Patterns to try, in order: **sort? hash map? two pointers? sliding window? prefix sum? stack? binary search? BFS/DFS? DP?** (the next two lessons cover the rest).

# Summary

**KEY TAKEAWAYS**

- Big-O measures growth: $O(1) < O(\log n) < O(n) < O(n \log n) < O(n^2) < O(2^n)$; drop constants, keep the dominant term.
- `in` on a list is O(n), on a set/dict O(1); inserting at the front of a list is O(n), use `deque`.
- Hash maps/Counters turn searches into lookups (two-sum, anagrams, frequency).
- Prefix sums give O(1) range sums; two pointers work on sorted data and palindromes; sliding windows handle subarray/substring problems in O(n).
- In interviews: clarify, brute force, optimise with a pattern, code, test, and state complexity.

## Quick quiz

6 questions · tap an answer to check it

**1. What is the time complexity of checking `x in my_set` ?**

**A** O(1) on average

**B** O(n)

**C** O(log n)

**D** $O(n^2)$

**Answer: A.** Sets are hash tables.

**2. Two nested loops over the same list of n items are...**

**A** O(n)

**B** O(n log n)

**C** $O(n^2)$

**D** O(2n)

**Answer: C.** Nested steps multiply.

**3. Which pattern solves "longest substring without repeating characters" in O(n)?**

A Binary search

B Sliding window with a dictionary of last positions

C Sorting

D Prefix sums only

**Answer: B.** Shrink the window past repeated characters.

**4. What does the two-sum hash map store?**

A Each value seen so far mapped to its index

B All pairs

C The sorted list

D Only the target

**Answer: A.** Check whether target − x was already seen.

**5. Which algorithm finds the maximum subarray sum in O(n)?**

A Merge sort

B Kadane's algorithm

C Binary search

D Bubble sort

**Answer: B.** Keep the best sum ending at each position.

**6.** What is $O(3n + n^2 + 10)$ simplified?

**A** $O(3n)$

**B** $O(n^2)$

**C** $O(n)$

**D** $O(10)$

**Answer: B.** Keep the dominant term.

EXERCISE **Practice set (try before opening the solutions)**

(1) Return the indices of all pairs that sum to a target. (2) Check if a string has all unique characters. (3) Find the majority element (appears > n/2 times). (4) Longest run of consecutive 1s after flipping at most one 0 (sliding window). (5) Count customers whose total spend is in the top 10% (prefix sums not needed: think sorting).

**Show solution (worked answer)**

Python

```
def all_pairs(nums, t):
    seen, out = defaultdict(list), []
    for i, x in enumerate(nums):
        out += [(j, i) for j in seen[t - x]]; seen[x].append(i)
    return out
def all_unique(s): return len(set(s)) == len(s)
def majority(nums):                        # Boyer-Moore voting, O(1) space
    cand = cnt = 0
    for x in nums:
        if cnt == 0: cand = x
        cnt += 1 if x == cand else -1
    return cand
def longest_ones(a, k=1):
    left = zeros = best = 0
    for right, x in enumerate(a):
        zeros += x == 0
        while zeros > k: zeros -= a[left] == 0; left += 1
        best = max(best, right - left + 1)
    return best
print(all_pairs([1, 5, 3, 3, 7], 6), all_unique("data"), majority([2, 2, 1, 1, 2]),
longest_ones([1, 0, 1, 1, 0, 1]))
```

INTERVIEW CORNER **Questions you may be asked**

**Q: Find duplicates in a list of 10 million customer IDs.** Use a set (or `Counter`) in one pass, O(n) time and O(n) space; in pandas `df.id.duplicated()`; in SQL `GROUP BY id HAVING COUNT(*) > 1`.

**Q: Why is sorting O(n log n)?** Comparison sorts split the problem in half repeatedly (log n levels) and do O(n) work per level; Python uses Timsort.

**Q: Space vs time trade-off example?** Two-sum: O($n^2$) time with O(1) space, or O(n) time with O(n) extra space for a hash map.

PYTHON FOR DATA SCIENCE · LESSON 27

# DSA II: Stacks, Queues, Linked Lists, Recursion, Sorting and Binary Search

Learn linear data structures (stack, queue, deque, linked list), recursion and backtracking, the main sorting algorithms with their trade-offs, and binary search including "search on the answer", with interview problems such as valid parentheses, next greater element, reverse a linked list and search in a rotated array.


DSA for data roles (added) · Python 3.13 · Intermediate · 120 min

**By the end of this lesson you can**

- Implement and use stacks, queues and deques, and solve bracket and monotonic-stack problems
- Build and manipulate a singly linked list (reverse, detect a cycle, find the middle)
- Write recursive solutions with base cases and use backtracking for combinations
- Explain bubble, insertion, merge and quick sort and their complexities
- Apply binary search to sorted arrays, boundaries and answer spaces

## Stacks: last in, first out

A **stack** adds and removes at the same end (LIFO). In Python a list works: `append` to push, `pop()` to pop, both O(1). Uses: undo, browser back, function calls, parsing brackets.




Stack (LIFO) vs queue (FIFO).

Python

```
def valid_parentheses(s):
    pairs, stack = {")": "(", "]": "[", "}": "{"}, []
    for ch in s:
        if ch in "([{": stack.append(ch)
        elif ch in pairs:
            if not stack or stack.pop() != pairs[ch]: return False
    return not stack
print([valid_parentheses(x) for x in ["()[]{}", "([)]", "{[()]}", "((", "SUM(IF(a>1,
(b),c))"]])

def eval_rpn(tokens):                          # reverse Polish notation: "3 4 + 2 *" = 14
    st = []
    for t in tokens:
        if t in "+-*/":
            b, a = st.pop(), st.pop()
            st.append({"+": a + b, "-": a - b, "*": a * b, "/": int(a / b)}[t])
        else: st.append(int(t))
    return st[0]
print(eval_rpn("3 4 + 2 *".split()))
```

OUTPUT

```
[True, False, True, False, True]
14
```

## Monotonic stack

Keep the stack sorted to answer "next greater/smaller element" in O(n) instead of O(n²).

Python

```
def next_greater(nums):
    res, st = [-1] * len(nums), []          # st holds indices with decreasing values
    for i, x in enumerate(nums):
        while st and nums[st[-1]] < x: res[st.pop()] = x
        st.append(i)
    return res
def days_until_warmer(temps):
    res, st = [0] * len(temps), []
    for i, t in enumerate(temps):
        while st and temps[st[-1]] < t:
            j = st.pop(); res[j] = i - j
        st.append(i)
    return res
print(next_greater([2, 1, 2, 4, 3]), days_until_warmer([73, 74, 75, 71, 69, 72, 76, 73]))
```

OUTPUT

```
[4, 2, 4, -1, -1] [1, 1, 4, 2, 1, 1, 0, 0]
```

## Queues and deques

Python

```
from collections import deque
q = deque(); q.append("job1"); q.append("job2"); q.appendleft("urgent")
print(q.popleft(), q.popleft(), list(q))
recent = deque(maxlen=3)                    # keeps only the last 3 items: a rolling buffer
for x in range(1, 7): recent.append(x)
print(list(recent))
def max_sliding_window(nums, k):            # monotonic deque, O(n)
    dq, out = deque(), []
    for i, x in enumerate(nums):
        while dq and nums[dq[-1]] ⩽ x: dq.pop()
        dq.append(i)
        if dq[0] ⩽ i - k: dq.popleft()
        if i ⩾ k - 1: out.append(nums[dq[0]])
    return out
print(max_sliding_window([1, 3, -1, -3, 5, 3, 6, 7], 3))
```

OUTPUT

```
urgent job1 ['job2']
[4, 5, 6]
[3, 3, 5, 5, 6, 7]
```

Never use `list.pop(0)` for a queue: it is O(n). Use `deque.popleft()` (O(1)). `queue.Queue` adds thread safety; `heapq` gives a priority queue (next lesson).

## Linked lists

A **linked list** stores nodes that point to the next node. Insert/delete at a known node is O(1); access by index is O(n). Python rarely needs them, but interviews love them.

Python

```
class Node:
    def __init__(self, val, nxt=None): self.val, self.next = val, nxt
def build(vals):
    head = None
    for v in reversed(vals): head = Node(v, head)
    return head
def to_list(head):
    out = []
    while head: out.append(head.val); head = head.next
    return out
def reverse(head):
    prev = None
    while head: head.next, prev, head = prev, head, head.next
    return prev
def middle(head):                          # slow/fast pointers
    slow = fast = head
    while fast and fast.next: slow, fast = slow.next, fast.next.next
    return slow.val
def has_cycle(head):                       # Floyd's tortoise and hare
    slow = fast = head
    while fast and fast.next:
        slow, fast = slow.next, fast.next.next
        if slow is fast: return True
    return False
def merge_two(a, b):
    dummy = tail = Node(0)
    while a and b:
        if a.val ⩽ b.val: tail.next, a = a, a.next
        else: tail.next, b = b, b.next
        tail = tail.next
    tail.next = a or b; return dummy.next
lst = build([1, 2, 3, 4, 5])
print(to_list(reverse(build([1, 2, 3, 4, 5]))), middle(lst), has_cycle(lst),
to_list(merge_two(build([1, 4, 7]), build([2, 3, 9]))))
cyc = build([1, 2, 3]); cyc.next.next.next = cyc.next; print(has_cycle(cyc))
```

OUTPUT

```
[5, 4, 3, 2, 1] 3 False [1, 2, 3, 4, 7, 9]
True
```

## Recursion and backtracking


A recursive function solves a problem by calling itself on a smaller version. It needs a **base case** and must move toward it.

Python

```python
def power(x, n):                            # fast exponentiation, O(log n)
    if n == 0: return 1
    half = power(x, n // 2)
    return half * half * (x if n % 2 else 1)
def flatten(nested):
    out = []
    for item in nested: out.extend(flatten(item) if isinstance(item, list) else [item])
    return out
def subsets(nums):                          # backtracking: explore, choose, un-choose
    res = []
    def bt(start, path):
        res.append(path[:])
        for i in range(start, len(nums)):
            path.append(nums[i]); bt(i + 1, path); path.pop()
    bt(0, []); return res
def permutations(s):
    if len(s) <= 1: return [s]
    return [ch + p for i, ch in enumerate(s) for p in permutations(s[:i] + s[i + 1:])]
print(power(2, 10), flatten([1, [2, [3, 4]], 5]), subsets([1, 2, 3]), permutations("abc"))
```

OUTPUT

```
1024 [1, 2, 3, 4, 5] [[], [1], [1, 2], [1, 2, 3], [1, 3], [2], [2, 3], [3]] ['abc',
'acb', 'bac', 'bca', 'cab', 'cba']
```




The recursion tree for subsets of [1, 2, 3]: each level decides whether to include the next item; $2^3 = 8$ leaves.

# Sorting algorithms

Python

```
def bubble_sort(a):
    a = a[:]
    for i in range(len(a)):
        swapped = False
        for j in range(len(a) - 1 - i):
            if a[j] > a[j + 1]: a[j], a[j + 1] = a[j + 1], a[j]; swapped = True
        if not swapped: break
    return a
def insertion_sort(a):
    a = a[:]
    for i in range(1, len(a)):
        key, j = a[i], i - 1
        while j >= 0 and a[j] > key: a[j + 1] = a[j]; j -= 1
        a[j + 1] = key
    return a
def merge_sort(a):
    if len(a) <= 1: return a
    mid = len(a) // 2; left, right = merge_sort(a[:mid]), merge_sort(a[mid:])
    out, i, j = [], 0, 0
    while i < len(left) and j < len(right):
        if left[i] <= right[j]: out.append(left[i]); i += 1
        else: out.append(right[j]); j += 1
    return out + left[i:] + right[j:]
def quick_sort(a):
    if len(a) <= 1: return a
    pivot = a[len(a) // 2]
    return quick_sort([x for x in a if x < pivot]) + [x for x in a if x == pivot] +
quick_sort([x for x in a if x > pivot])
data = [38, 27, 43, 3, 9, 82, 10]
print(bubble_sort(data), insertion_sort(data), merge_sort(data), quick_sort(data),
sorted(data) == merge_sort(data))
import random, time
big = [random.random() for _ in range(3000)]
for f in (insertion_sort, merge_sort, quick_sort, sorted):
    t0 = time.perf_counter(); f(big); print(f"{f.__name__:15s} {1000 * (time.perf_counter()
- t0):7.1f} ms")
```

OUTPUT

```
[3, 9, 10, 27, 38, 43, 82] [3, 9, 10, 27, 38, 43, 82] [3, 9, 10, 27, 38, 43, 82] [3,
9, 10, 27, 38, 43, 82] True
insertion_sort    133.5 ms
merge_sort          3.5 ms
quick_sort          3.5 ms
sorted              0.2 ms
```

| Algorithm | Best | Average | Worst | Space | Stable | Notes |
|---|---|---|---|---|---|---|
| Bubble | O(n) | $O(n^2)$ | $O(n^2)$ | O(1) | Yes | Teaching only |
| Insertion | O(n) | $O(n^2)$ | $O(n^2)$ | O(1) | Yes | Great for small / nearly sorted |
| Merge | O(n log n) | O(n log n) | O(n log n) | O(n) | Yes | Predictable; external sorting |
| Quick | O(n log n) | O(n log n) | $O(n^2)$ | O(log n) | No | Fast in practice |
| Heap | O(n log n) | O(n log n) | O(n log n) | O(1) | No | |
| Timsort (Python `sorted`) | O(n) | O(n log n) | O(n log n) | O(n) | Yes | Merge + insertion hybrid |

**Stable** means equal keys keep their original order, so you can sort by city, then stably by region. In practice, use `sorted(items, key=...)`.

## Binary search

On **sorted** data, halve the search space each step: O(log n). One million items need at most 20 comparisons.

Python

```
def binary_search(a, target):
    lo, hi = 0, len(a) - 1
    while lo ⩽ hi:
        mid = (lo + hi) // 2
        if a[mid] == target: return mid
        if a[mid] < target: lo = mid + 1
        else: hi = mid - 1
    return -1
import bisect
a = [3, 8, 15, 15, 15, 23, 42]
print(binary_search(a, 23), binary_search(a, 5), bisect.bisect_left(a, 15),
bisect.bisect_right(a, 15), bisect.bisect_right(a, 15) - bisect.bisect_left(a, 15))
def search_rotated(nums, target):
    lo, hi = 0, len(nums) - 1
    while lo ⩽ hi:
        mid = (lo + hi) // 2
        if nums[mid] == target: return mid
        if nums[lo] ⩽ nums[mid]:                    # left half sorted
            if nums[lo] ⩽ target < nums[mid]: hi = mid - 1
            else: lo = mid + 1
        else:                                       # right half sorted
            if nums[mid] < target ⩽ nums[hi]: lo = mid + 1
            else: hi = mid - 1
    return -1
print(search_rotated([4, 5, 6, 7, 0, 1, 2], 0), search_rotated([4, 5, 6, 7, 0, 1, 2], 3))
def min_capacity_to_ship(weights, days):           # "binary search on the answer"
    def ok(cap):
        d, load = 1, 0
        for w in weights:
            if load + w > cap: d += 1; load = 0
            load += w
        return d ⩽ days
    lo, hi = max(weights), sum(weights)
    while lo < hi:
        mid = (lo + hi) // 2
        if ok(mid): hi = mid
        else: lo = mid + 1
    return lo
print(min_capacity_to_ship([1, 2, 3, 4, 5, 6, 7, 8, 9, 10], 5))
grades = ["F", "D", "C", "B", "A"]; cutoffs = [40, 50, 65, 80]
print([grades[bisect.bisect_right(cutoffs, s)] for s in (35, 50, 79, 92)])        # banding
with bisect
```

OUTPUT

```
5 -1 2 5 3
4 -1
15
['F', 'C', 'B', 'A']
```

`bisect` is how pandas `cut` and SQL range lookups work under the hood: find the band for a value in O(log n).

## Summary

**KEY TAKEAWAYS**

- Stack = LIFO (list append/pop); queue = FIFO ( `deque` append/popleft); monotonic stacks/deques solve next-greater and window-max in O(n).
- Linked lists: pointer manipulation; slow/fast pointers find the middle and detect cycles.
- Recursion needs a base case; backtracking = choose, explore, un-choose.
- Merge sort is O(n log n) and stable; quick sort is fast on average; insertion sort suits small inputs; use `sorted` .
- Binary search halves the space: O(log n). Use it on sorted arrays, boundaries ( `bisect` ) and "minimum value that works" answers.

### Quick quiz

6 questions · tap an answer to check it

**1. Which structure checks balanced brackets?**

**A** Stack

**B** Queue

**C** Set

**D** Heap

**Answer: A.** Push openings, pop on closings.

**2. Why use `deque.popleft()` instead of `list.pop(0)` ?**

A It sorts the data

B It is O(1); list.pop(0) is O(n)

C It is thread safe

D No difference

**Answer: B.** Lists shift every element when removing from the front.

**3. How do you find the middle of a linked list in one pass?**

A Count then walk

B Slow and fast pointers

C Sort it

D Binary search

**Answer: B.** When fast reaches the end, slow is in the middle.

**4. What is the worst-case complexity of quick sort?**

A O(n log n)

B $O(n^2)$

C O(n)

D O(log n)

**Answer: B.** With bad pivots; randomised pivots make it unlikely.

**5.** How many comparisons does binary search need for about 1,000,000 sorted items?

**A** 1,000,000

**B** 1,000

**C** About 20

**D** 2

**Answer: C.** $\log_2(1{,}000{,}000) \approx 20$.

**6.** What does a "stable" sort guarantee?

**A** It never fails

**B** Items with equal keys keep their original relative order

**C** O(n log n) always

**D** It uses no memory

**Answer: B.** Merge sort and Timsort are stable.

EXERCISE **Practice set**

(1) Implement a queue using two stacks. (2) Remove adjacent duplicate letters repeatedly ("abbaca" → "ca"). (3) Find the first and last position of a target in a sorted array with `bisect`. (4) Return all combinations of k numbers from 1..n. (5) Compute the integer square root with binary search.

**Show solution (worked answer)**

Python

```
class QueueTwoStacks:
    def __init__(self): self.inbox, self.outbox = [], []
    def push(self, x): self.inbox.append(x)
    def pop(self):
        if not self.outbox:
            while self.inbox: self.outbox.append(self.inbox.pop())
        return self.outbox.pop()
def remove_adjacent(s):
    st = []
    for ch in s:
        if st and st[-1] == ch: st.pop()
        else: st.append(ch)
    return "".join(st)
def first_last(a, t):
    i, j = bisect.bisect_left(a, t), bisect.bisect_right(a, t) - 1
    return [i, j] if i <= j else [-1, -1]
def combine(n, k):
    res = []
    def bt(start, path):
        if len(path) == k: res.append(path[:]); return
        for i in range(start, n + 1): path.append(i); bt(i + 1, path); path.pop()
    bt(1, []); return res
def isqrt(x):
    lo, hi = 0, x
    while lo < hi:
        mid = (lo + hi + 1) // 2
        if mid * mid <= x: lo = mid
        else: hi = mid - 1
    return lo
print(remove_adjacent("abbaca"), first_last([5, 7, 7, 8, 8, 10], 8), combine(4, 2),
isqrt(80))
```

INTERVIEW CORNER

## Questions you may be asked

**Q: Explain merge sort.** Split the list in half recursively until single items remain, then merge sorted halves by repeatedly taking the smaller front item; O(n log n) time, O(n) extra space, stable.

**Q: When is binary search applicable?** When the data is sorted, or more generally when a yes/no condition is monotonic over the search space (search on the answer).

**Q: Stack vs queue in real systems?** Stacks: call stacks, undo, expression parsing, DFS. Queues: job and message queues (Kafka, SQS), BFS, rate-limited processing.

PYTHON FOR DATA SCIENCE · LESSON 28

# DSA III: Trees, Heaps, Graphs (BFS/DFS) and Dynamic Programming

Finish the DSA toolkit. Binary trees and binary search trees with traversals, heaps and priority queues with heapq (top-k, merge k lists, running median), graphs with adjacency lists, BFS and DFS, shortest paths and topological sort (as used in data pipelines), and dynamic programming from memoisation to tables.


DSA for data roles (added) · Python 3.13 · Advanced · 130 min

**By the end of this lesson you can**

- Traverse binary trees (pre-, in-, post- and level-order) and use a binary search tree
- Use heapq for top-k, k-way merge, scheduling and running medians
- Represent graphs and apply BFS, DFS, Dijkstra and topological sort
- Recognise dynamic-programming problems and solve them with memoisation and tabulation
- Connect these structures to data tools (B-tree indexes, DAG schedulers, recommendation graphs)

## Trees

A **tree** is a hierarchy of nodes: one root, each node with children, no cycles. Examples: folders, org charts, JSON documents, decision trees in ML, and B-tree indexes in databases.




A binary search tree: every left child is smaller and every right child larger than its parent.

Python

```
class TreeNode:
    def __init__(self, val, left=None, right=None): self.val, self.left, self.right = val,
left, right
def insert(root, val):                          # BST insert, O(height)
    if not root: return TreeNode(val)
    if val < root.val: root.left = insert(root.left, val)
    else: root.right = insert(root.right, val)
    return root
root = None
for v in [8, 3, 10, 1, 6, 14, 4, 7, 13]: root = insert(root, v)
def inorder(n): return inorder(n.left) + [n.val] + inorder(n.right) if n else []
def preorder(n): return [n.val] + preorder(n.left) + preorder(n.right) if n else []
def postorder(n): return postorder(n.left) + postorder(n.right) + [n.val] if n else []
from collections import deque
def level_order(n):
    out, q = [], deque([n])
    while q:
        level = []
        for _ in range(len(q)):
            node = q.popleft(); level.append(node.val)
            q.extend(c for c in (node.left, node.right) if c)
        out.append(level)
    return out
def height(n): return 1 + max(height(n.left), height(n.right)) if n else 0
def contains(n, x):
    while n:
        if x == n.val: return True
        n = n.left if x < n.val else n.right
    return False
print("in-order  :", inorder(root), "(sorted!)")
print("pre-order :", preorder(root)); print("post-order:", postorder(root)); print("levels
:", level_order(root))
print("height", height(root), "| contains 7?", contains(root, 7), "| contains 5?",
contains(root, 5))
```

OUTPUT

```
in-order  : [1, 3, 4, 6, 7, 8, 10, 13, 14] (sorted!)
pre-order : [8, 3, 1, 6, 4, 7, 10, 14, 13]
post-order: [1, 4, 7, 6, 3, 13, 14, 10, 8]
levels    : [[8], [3, 10], [1, 6, 14], [4, 7, 13]]
height 4 | contains 7? True | contains 5? False
```

| Traversal | Order | Use |
|---|---|---|
| In-order | left, node, right | BST → sorted output |
| Pre-order | node, left, right | Copy/serialise a tree |
| Post-order | left, right, node | Delete, compute sizes bottom-up |
| Level-order (BFS) | level by level | Shortest path in unweighted trees, org levels |

Python

```
def is_valid_bst(n, lo=float("-inf"), hi=float("inf")):
    return not n or (lo < n.val < hi and is_valid_bst(n.left, lo, n.val) and
is_valid_bst(n.right, n.val, hi))
def lowest_common_ancestor(n, a, b):            # in a BST
    while n:
        if a < n.val and b < n.val: n = n.left
        elif a > n.val and b > n.val: n = n.right
        else: return n.val
def max_path_sum_root_to_leaf(n):
    if not n: return float("-inf")
    if not n.left and not n.right: return n.val
    return n.val + max(max_path_sum_root_to_leaf(n.left),
max_path_sum_root_to_leaf(n.right))
print(is_valid_bst(root), lowest_common_ancestor(root, 4, 7), lowest_common_ancestor(root,
1, 14), max_path_sum_root_to_leaf(root))
```

OUTPUT

```
True 6 8 45
```

A BST is O(log n) only when **balanced**; inserting sorted data creates a "linked list" with O(n) lookups. Databases use balanced **B-trees**, which is why an index makes `WHERE id = 42` fast.

## Heaps and priority queues

A **heap** always gives the smallest item in O(1) and inserts/removes in O(log n). Python's `heapq` is a min-heap on a list.

Python

```python
import heapq
h = []
for x in [5, 1, 8, 3, 9, 2]: heapq.heappush(h, x)
print(h[0], [heapq.heappop(h) for _ in range(3)])
sales = {"Pune": 120, "Delhi": 340, "Kochi": 90, "Goa": 210, "Jaipur": 175}
print(heapq.nlargest(3, sales.items(), key=lambda kv: kv[1]))
def top_k_stream(stream, k):                # keep a size-k min-heap: O(n log k), constant memory
    heap = []
    for x in stream:
        if len(heap) < k: heapq.heappush(heap, x)
        elif x > heap[0]: heapq.heapreplace(heap, x)
    return sorted(heap, reverse=True)
print(top_k_stream(iter([15, 3, 99, 42, 7, 64, 23, 88]), 3))
print(list(heapq.merge([1, 4, 9], [2, 3, 10], [0, 7])))             # k-way merge of sorted lists (external sort)
tasks = [(2, "send report"), (1, "fix pipeline"), (3, "update deck")]  # (priority, task)
heapq.heapify(tasks); print([heapq.heappop(tasks)[1] for _ in range(3)])


class RunningMedian:                         # two heaps: max-heap (negated) + min-heap
    def __init__(self): self.lo, self.hi = [], []
    def add(self, x):
        heapq.heappush(self.lo, -x); heapq.heappush(self.hi, -heapq.heappop(self.lo))
        if len(self.hi) > len(self.lo): heapq.heappush(self.lo, -heapq.heappop(self.hi))
    def median(self): return -self.lo[0] if len(self.lo) > len(self.hi) else (-self.lo[0] + self.hi[0]) / 2
rm = RunningMedian(); out = []
for x in [5, 15, 1, 3, 8, 7]: rm.add(x); out.append(rm.median())
print(out)
```

OUTPUT

```
1 [1, 2, 3]
[('Delhi', 340), ('Goa', 210), ('Jaipur', 175)]
[99, 88, 64]
[0, 1, 2, 3, 4, 7, 9, 10]
['fix pipeline', 'send report', 'update deck']
[5, 10.0, 5, 4.0, 5, 6.0]
```

## Graphs

A **graph** has nodes (vertices) and edges, optionally directed and weighted. Social networks, road maps, product co-purchases, and data-pipeline dependencies are graphs.




A directed acyclic graph (DAG) of pipeline tasks: a task runs only after its dependencies. Airflow, dbt and Dagster schedule exactly this.

Python

```
from collections import defaultdict, deque
edges = [("A", "B"), ("A", "C"), ("B", "D"), ("C", "D"), ("D", "E"), ("F", "G")]
g = defaultdict(list)
for u, v in edges: g[u].append(v); g[v].append(u)              # undirected adjacency list
def bfs(start):
    seen, order, q = {start}, [], deque([start])
    while q:
        node = q.popleft(); order.append(node)
        for nb in g[node]:
            if nb not in seen: seen.add(nb); q.append(nb)
    return order
def dfs(node, seen=None):
    seen = seen if seen is not None else set(); seen.add(node); out = [node]
    for nb in g[node]:
        if nb not in seen: out += dfs(nb, seen)
    return out
def shortest_hops(a, b):                      # BFS gives shortest path in unweighted graphs
    q, prev = deque([a]), {a: None}
    while q:
        n = q.popleft()
        if n == b: break
        for nb in g[n]:
            if nb not in prev: prev[nb] = n; q.append(nb)
    path = []
    while b is not None: path.append(b); b = prev.get(b)
    return path[::-1]
def components():
    seen, comps = set(), []
    for n in list(g):
        if n not in seen: c = dfs(n, seen); comps.append(sorted(c))
    return comps
print("BFS from A:", bfs("A"), "| DFS from A:", dfs("A"), "| path A→E:", shortest_hops("A", "E"), "| components:", components())
```

OUTPUT

```
BFS from A: ['A', 'B', 'C', 'D', 'E'] | DFS from A: ['A', 'B', 'D', 'C', 'E'] | path A→E: ['A', 'B', 'D', 'E'] | components: [['A', 'B', 'C', 'D', 'E'], ['F', 'G']]
```

Python

```python
def number_of_islands(grid):                # classic grid DFS
    rows, cols, count = len(grid), len(grid[0]), 0
    def sink(r, c):
        if 0 ⩽ r < rows and 0 ⩽ c < cols and grid[r][c] == "1":
            grid[r][c] = "0"
            for dr, dc in ((1, 0), (-1, 0), (0, 1), (0, -1)): sink(r + dr, c + dc)
    for r in range(rows):
        for c in range(cols):
            if grid[r][c] == "1": count += 1; sink(r, c)
    return count
print(number_of_islands([list("11000"), list("11000"), list("00100"), list("00011")]))
```

OUTPUT

```
3
```

## Dijkstra's shortest path (weighted)

Python

```python
def dijkstra(graph, src):
    dist = {src: 0}; pq = [(0, src)]
    while pq:
        d, u = heapq.heappop(pq)
        if d > dist.get(u, float("inf")): continue
        for v, w in graph.get(u, []):
            if d + w < dist.get(v, float("inf")): dist[v] = d + w; heapq.heappush(pq, (d + w, v))
    return dist
roads = {"Mumbai": [("Pune", 150), ("Nashik", 170)], "Pune": [("Satara", 110), ("Nashik", 210)], "Nashik": [("Aurangabad", 180)], "Satara": [("Kolhapur", 120)], "Aurangabad": [], "Kolhapur": []}
print(dijkstra(roads, "Mumbai"))
```

OUTPUT

```
{'Mumbai': 0, 'Pune': 150, 'Nashik': 170, 'Satara': 260, 'Aurangabad': 350, 'Kolhapur': 380}
```

### Topological sort: ordering a pipeline

Python

```
deps = {"extract_orders": [], "extract_customers": [], "clean_orders": ["extract_orders"],
"join_customers": ["clean_orders", "extract_customers"],
        "build_marts": ["join_customers"], "refresh_dashboard": ["build_marts"],
"train_model": ["join_customers"]}
def topo_sort(deps):                          # Kahn's algorithm
    indeg = {t: len(d) for t, d in deps.items()}; children = defaultdict(list)
    for t, ds in deps.items():
        for d in ds: children[d].append(t)
    q = deque(sorted(t for t, k in indeg.items() if k == 0)); order = []
    while q:
        t = q.popleft(); order.append(t)
        for c in sorted(children[t]):
            indeg[c] -= 1
            if indeg[c] == 0: q.append(c)
    if len(order) != len(deps): raise ValueError("cycle detected")
    return order
print(topo_sort(deps))
from graphlib import TopologicalSorter        # standard-library version
print(list(TopologicalSorter(deps).static_order())[:3])
```

OUTPUT

```
['extract_customers', 'extract_orders', 'clean_orders', 'join_customers',
'build_marts', 'train_model', 'refresh_dashboard']
['extract_orders', 'extract_customers', 'clean_orders']
```

## Dynamic programming


**Dynamic programming (DP)** solves problems with **overlapping subproblems** and **optimal substructure** by storing answers to subproblems instead of recomputing them.

Python

```python
import functools, time
def fib_naive(n): return n if n < 2 else fib_naive(n - 1) + fib_naive(n - 2)
@functools.cache
def fib_memo(n): return n if n < 2 else fib_memo(n - 1) + fib_memo(n - 2)
def fib_table(n):
    a, b = 0, 1
    for _ in range(n): a, b = b, a + b
    return a
t0 = time.perf_counter(); fib_naive(27); t1 = time.perf_counter(); fib_memo(27); t2 =
time.perf_counter()
print(f"naive {1000*(t1-t0):.0f} ms (O(2^n)) | memoised {1000*(t2-t1):.3f} ms (O(n)) |
values equal: {fib_naive(20) == fib_memo(20) == fib_table(20)}")
```

OUTPUT

```
naive 31 ms (O(2^n)) | memoised 0.022 ms (O(n)) | values equal: True
```




Top-down (memoisation) vs bottom-up (tabulation) dynamic programming.

Python

```python
def climb_stairs(n):                          # 1 or 2 steps at a time
    a, b = 1, 1
    for _ in range(n): a, b = b, a + b
    return a
def coin_change(coins, amount):               # fewest coins
    dp = [0] + [float("inf")] * amount
    for x in range(1, amount + 1):
        dp[x] = min((dp[x - c] + 1 for c in coins if c <= x), default=float("inf"))
    return dp[amount] if dp[amount] != float("inf") else -1
def house_robber(nums):                       # no two adjacent
    take = skip = 0
    for x in nums: take, skip = skip + x, max(take, skip)
    return max(take, skip)
def lis(nums):                                # longest increasing subsequence, O(n log n)
    import bisect; tails = []
    for x in nums:
        i = bisect.bisect_left(tails, x)
        tails[i:i + 1] = [x]
    return len(tails)
def edit_distance(a, b):                      # Levenshtein: used in fuzzy matching of
names
    dp = list(range(len(b) + 1))
    for i in range(1, len(a) + 1):
        prev, dp[0] = dp[0], i
        for j in range(1, len(b) + 1):
            prev, dp[j] = dp[j], min(dp[j] + 1, dp[j - 1] + 1, prev + (a[i - 1] != b[j -
1]))
    return dp[-1]
def knapsack(items, cap):                     # 0/1 knapsack: (weight, value)
    dp = [0] * (cap + 1)
    for w, v in items:
        for c in range(cap, w - 1, -1): dp[c] = max(dp[c], dp[c - w] + v)
    return dp[cap]
print(climb_stairs(10), coin_change([1, 2, 5], 11), coin_change([2], 3), house_robber([2,
7, 9, 3, 1]), lis([10, 9, 2, 5, 3, 7, 101, 18]))
print(edit_distance("Bangalore", "Bengaluru"), edit_distance("kitten", "sitting"),
knapsack([(1, 1), (3, 4), (4, 5), (5, 7)], 7))
```

OUTPUT

```
89 3 -1 12 4
3 3 9
```

How to spot DP: "minimum/maximum/number of ways", choices at each step, and the same subproblem appearing again. Define the **state** ( `dp[x]` = best answer for amount x), the **transition**, and the **base case**.

## Where these appear in data work

| Structure | In data tools |
|---|---|
| B-trees | Database indexes |
| Hash tables | Hash joins, `GROUP BY`, Python dicts, Spark shuffles |
| Heaps | Top-N queries, schedulers, k-way merge in external sorting |
| DAGs + topological sort | Airflow, dbt, Dagster, Spark execution plans |
| Graphs + BFS | Recommendations ("people also bought"), fraud rings, knowledge graphs for GenAI |
| Edit distance (DP) | Fuzzy matching, deduplicating customer names |
| Trees | Decision trees, random forests, gradient boosting |

## Summary

**KEY TAKEAWAYS**

- Trees: four traversals; a BST's in-order traversal is sorted; balanced trees give O(log n) search (database B-tree indexes).
- Heaps ( `heapq` ) give the minimum in O(1) and push/pop in O(log n): top-k, k-way merge, priority scheduling, running median.
- Graphs as adjacency lists; BFS (queue) for levels and shortest unweighted paths, DFS (recursion/stack) for components and islands; Dijkstra for weighted paths; topological sort for DAG pipelines.
- DP = overlapping subproblems + optimal substructure; use memoisation ( `@functools.cache` ) or tabulation; define state, transition and base case.

### Quick quiz

6 questions · tap an answer to check it

**1.** Which traversal of a BST returns the values in sorted order?

- **A** Pre-order
- **B** In-order
- **C** Post-order
- **D** Level-order

**Answer: B.** Left subtree, node, right subtree.

**2.** What does `heapq` give you in O(1)?

- **A** The smallest item
- **B** The largest item
- **C** The median
- **D** A sorted list

**Answer: A.** Negate values for a max-heap.

**3.** Which search finds the shortest path in an unweighted graph?

- **A** BFS
- **B** DFS
- **C** Binary search
- **D** Sorting

**Answer: A.** BFS explores level by level.

**4.** Which algorithm orders tasks so each runs after its dependencies?

A Dijkstra

B Topological sort

C Merge sort

D Kadane

**Answer: B.** It works on directed acyclic graphs.

**5.** Two signs that a problem suits dynamic programming are...

A Overlapping subproblems and optimal substructure

B Sorted input and unique values

C A graph and a heap

D Strings only

**Answer: A.** Store and reuse subproblem answers.

**6.** Why does a database index speed up lookups?

A It stores data in CSV

B It keeps keys in a balanced tree (B-tree) so lookups are O(log n)

C It caches every query

D It compresses the table

**Answer: B.** Without an index the database scans every row.

EXERCISE

### Practice set

(1) Return the maximum depth and the left view of a binary tree. (2) Find the k closest points to the origin with a heap. (3) Detect a cycle in a directed graph of task dependencies. (4) Count the number of ways to make change for an amount. (5) Longest common subsequence of two strings.

**Show solution (worked answer)**

Python

```
def left_view(n): return [lvl[0] for lvl in level_order(n)]
def k_closest(points, k): return heapq.nsmallest(k, points, key=lambda p: p[0] ** 2 +
p[1] ** 2)
def has_cycle_directed(deps):
    try: topo_sort(deps); return False
    except ValueError: return True
def ways_to_change(coins, amount):
    dp = [1] + [0] * amount
    for c in coins:
        for x in range(c, amount + 1): dp[x] += dp[x - c]
    return dp[amount]
def lcs(a, b):
    dp = [[0] * (len(b) + 1) for _ in range(len(a) + 1)]
    for i in range(1, len(a) + 1):
        for j in range(1, len(b) + 1):
            dp[i][j] = dp[i - 1][j - 1] + 1 if a[i - 1] == b[j - 1] else max(dp[i - 1]
[j], dp[i][j - 1])
    return dp[-1][-1]
print(height(root), left_view(root), k_closest([(1, 3), (-2, 2), (5, 8)], 2),
has_cycle_directed({"a": ["b"], "b": ["a"]}), ways_to_change([1, 2, 5], 5),
lcs("abcde", "ace"))
```

INTERVIEW CORNER

## Questions you may be asked

**Q: BFS vs DFS?** BFS uses a queue, explores by distance and finds shortest unweighted paths; DFS uses recursion or a stack, goes deep first, and suits connectivity, cycle detection and topological ordering. Both are O(V + E).

**Q: How would you get the top 10 products from a stream of billions of sales?** Maintain a size-10 min-heap of running totals per product (or approximate with Count-Min Sketch), or aggregate in SQL/Spark and take the top 10.

**Q: Memoisation vs tabulation?** Memoisation caches results of a top-down recursion; tabulation fills a table bottom-up. Same complexity; tabulation avoids recursion limits and often allows space optimisation.

PYTHON FOR DATA SCIENCE · LESSON 29

# Python Capstone: End-to-End Retail Sales Analytics Project

Bring the whole Python track together on the Superstore data. Structure a project, build a validated data pipeline, compute KPIs, growth and Pareto analysis, cohort retention and discount impact, create a chart pack and an Excel report, and write the README and executive summary you can put in your portfolio.


Python capstone · pandas 3 · Matplotlib 3.10 · openpyxl · Advanced · 180 min

**By the end of this lesson you can**

- Organise an analysis as a reproducible project with functions, checks and outputs
- Build a load → validate → transform pipeline with assertions
- Analyse KPIs, growth, Pareto concentration, cohorts and discount effects
- Produce a multi-sheet Excel report and a chart pack
- Write an executive summary and a portfolio-ready README

## The brief

The sales director of an Indian office-supplies retailer asks: **How did 2025 go, where do we make and lose money, how loyal are our customers, and what should we change in 2026?** Deliver a short report with charts and an Excel workbook her team can filter.




Capstone pipeline.

Project layout (Lesson 13): `data/raw`, `src/` (functions below), `notebooks/` (exploration), `reports/` (outputs), `README.md`.

## 1. Load and validate

Python

```python
import pandas as pd, numpy as np, matplotlib.pyplot as plt
pd.set_option("display.max_columns", 20); pd.set_option("display.width", 160)

def load(path="superstore_sales.csv"):
    df = pd.read_csv(path, parse_dates=["order_date", "ship_date"])
    return df

def validate(df):
    checks = {
        "row_id unique": df["row_id"].is_unique,
        "no missing values": df.isna().sum().sum() == 0,
        "sales positive": (df["sales"] > 0).all(),
        "discount between 0 and 1": df["discount"].between(0, 1).all(),
        "ship after order": (df["ship_date"] ≥ df["order_date"]).all(),
        "quantity 1-20": df["quantity"].between(1, 20).all(),
    }
    for name, ok in checks.items(): print(f"  {'PASS' if ok else 'FAIL'}  {name}")
    assert all(checks.values()), "validation failed"
    return df

s = validate(load())
print(s.shape, s.order_date.min().date(), "→", s.order_date.max().date())
```

OUTPUT

```
  PASS  row_id unique
  PASS  no missing values
  PASS  sales positive
  PASS  discount between 0 and 1
  PASS  ship after order
  PASS  quantity 1-20
(6323, 19) 2023-01-01 → 2025-12-31
```

## 2. Transform and enrich

Python

```
def enrich(df):
    out = df.copy()
    out["year"] = out.order_date.dt.year
    out["month"] = out.order_date.dt.to_period("M")
    out["margin_pct"] = 100 * out.profit / out.sales
    out["ship_days"] = (out.ship_date - out.order_date).dt.days
    out["discount_band"] = pd.cut(out.discount, [-0.01, 0, 0.1, 0.2, 1], labels=["0%", "1-
10%", "11-20%", ">20%"])
    return out
s = enrich(s)
print(s[["order_id", "year", "month", "sales", "profit", "margin_pct",
"discount_band"]].head(3))
```

OUTPUT

```
        order_id  year    month    sales   profit  margin_pct discount_band
0  IN-2023-00001  2023  2023-01  36000.0  3472.55    9.645972            0%
1  IN-2023-00001  2023  2023-01   3850.0  1169.54   30.377662            0%
2  IN-2023-00001  2023  2023-01  62080.0  6044.47    9.736582            0%
```

## 3. Headline KPIs and growth


Python

```
def kpis(df):
    g = df.groupby("year").agg(sales=("sales", "sum"), profit=("profit", "sum"), orders=
("order_id", "nunique"), customers=("customer_id", "nunique"), units=("quantity", "sum"))
    g["margin_%"] = 100 * g.profit / g.sales
    g["aov"] = g.sales / g.orders
    g["sales_growth_%"] = 100 * g.sales.pct_change()
    g["profit_growth_%"] = 100 * g.profit.pct_change()
    return g
k = kpis(s)
view = k.assign(sales=k.sales / 1e6, profit=k.profit / 1e6, aov=k.aov / 1e3).round(1)
view.columns = ["sales ₹M", "profit ₹M", "orders", "customers", "units", "margin %", "AOV
₹K", "sales growth %", "profit growth %"]
print(view)
```

OUTPUT

```
      sales ₹M  profit ₹M  orders  customers  units  margin %  AOV ₹K  sales growth %
profit growth %
year
2023      57.6        4.7     883        540   4714       8.2    65.3             NaN
```

```
NaN
2024      65.4        6.1    1085        590    5404       9.4    60.3            13.5
29.9
2025      78.4        7.5    1232        623    6266       9.6    63.6            19.8
22.1
```




Monthly sales and profit, 2023–2025, with 3-month rolling averages.

## 4. Where we make and lose money

Python

```python
sub = s[s.year == 2025].groupby(["category", "sub_category"]).agg(sales=("sales", "sum"),
profit=("profit", "sum"), avg_disc=("discount", "mean"))
sub["margin_%"] = (100 * sub.profit / sub.sales).round(1)
sub = sub.sort_values("profit")
print((sub.assign(sales=sub.sales / 1e6, profit=sub.profit / 1e6)).round(2))
```

OUTPUT

| category | sub_category | sales | profit | avg_disc | margin_% |
|---|---|---|---|---|---|
| Furniture | Tables | 5.30 | -0.29 | 0.17 | -5.4 |
| | Bookcases | 3.92 | -0.17 | 0.19 | -4.3 |
| Office Supplies | Art | 0.10 | 0.02 | 0.08 | 15.3 |
| | Binders | 0.16 | 0.02 | 0.08 | 14.2 |
| Furniture | Furnishings | 0.49 | 0.03 | 0.08 | 5.2 |
| Office Supplies | Paper | 0.19 | 0.03 | 0.07 | 15.8 |
| Furniture | Chairs | 3.05 | 0.13 | 0.08 | 4.3 |
| Office Supplies | Storage | 0.98 | 0.14 | 0.08 | 14.1 |
| Technology | Accessories | 1.22 | 0.15 | 0.07 | 11.9 |
| Office Supplies | Appliances | 2.54 | 0.38 | 0.07 | 14.9 |
| Technology | Phones | 12.94 | 1.71 | 0.06 | 13.2 |


```
Machines        16.50     2.00       0.08       12.1
Copiers         30.98     3.35       0.08       10.8
```

Python

```python
db = s.groupby("discount_band", observed=True).agg(lines=("row_id", "size"), sales=
("sales", "sum"), profit=("profit", "sum"))
db["margin_%"] = (100 * db.profit / db.sales).round(1); db["share_of_lines_%"] = (100 *
db.lines / db.lines.sum()).round(1)
print(db.assign(sales=(db.sales / 1e6).round(1), profit=(db.profit / 1e6).round(2)))
```

OUTPUT

| discount_band | lines | sales | profit | margin_% | share_of_lines_% |
|---|---|---|---|---|---|
| 0% | 3480 | 123.9 | 21.72 | 17.5 | 55.0 |
| 1–10% | 726 | 21.9 | 1.29 | 5.9 | 11.5 |
| 11–20% | 1217 | 35.9 | -0.59 | -1.6 | 19.2 |
| >20% | 900 | 19.7 | -4.06 | -20.6 | 14.2 |




Margin by discount band: deep discounts turn profitable lines into losses.


## 5. Customer concentration (Pareto)

Python

```
cust = s.groupby("customer_id")["sales"].sum().sort_values(ascending=False)
cum = cust.cumsum() / cust.sum()
top20 = int(len(cust) * 0.2)
print(f"{len(cust)} customers | top 20% ({top20}) bring {cum.iloc[top20 - 1]:.0%} of sales
| customers needed for 50% of sales: {(cum < 0.5).sum() + 1}")
```

OUTPUT

```
785 customers | top 20% (157) bring 47% of sales | customers needed for 50% of sales:
171
```




Pareto curve of customer sales.

## 6. Cohort retention


A **cohort** groups customers by the month (here: quarter) of their first purchase; retention tracks how many buy again later.

Python

```
s["quarter"] = s.order_date.dt.to_period("Q")
first = s.groupby("customer_id")["quarter"].min().rename("cohort")
c = s.join(first, on="customer_id")
c["age_q"] = (c.quarter - c.cohort).apply(lambda d: d.n)
active = c.groupby(["cohort", "age_q"])["customer_id"].nunique().unstack()
retention = (active.div(active[0], axis=0) * 100).round(0)
print(active[0].rename("cohort size").head(6).to_dict())
print(retention.iloc[:6, :8])
```

OUTPUT

```
{Period('2023Q1', 'Q-DEC'): 151.0, Period('2023Q2', 'Q-DEC'): 142.0, Period('2023Q3',
'Q-DEC'): 127.0, Period('2023Q4', 'Q-DEC'): 120.0, Period('2024Q1', 'Q-DEC'): 71.0,
Period('2024Q2', 'Q-DEC'): 42.0}
age_q       0     1     2     3     4     5     6     7
cohort
2023Q1  100.0  23.0  26.0  28.0  22.0  26.0  35.0  38.0
2023Q2  100.0  20.0  33.0  29.0  26.0  25.0  25.0  31.0
2023Q3  100.0  24.0  26.0  22.0  35.0  36.0  26.0  20.0
2023Q4  100.0  25.0  22.0  29.0  45.0  25.0  32.0  27.0
2024Q1  100.0  38.0  17.0  37.0  34.0  25.0  27.0  38.0
2024Q2  100.0  31.0  24.0  31.0  24.0  24.0  40.0   NaN
```




Quarterly cohort retention (% of each cohort buying in later quarters).

# 7. Operations: shipping

Python

```
ship = s.groupby("ship_mode").agg(lines=("row_id", "size"), avg_days=("ship_days", "mean"),
sales=("sales", "sum"))
ship["share_%"] = (100 * ship.lines / ship.lines.sum()).round(1)
print(ship.round(1).sort_values("avg_days"))
reg = s[s.year == 2025].groupby("region").agg(sales=("sales", "sum"), profit=("profit",
"sum"))
reg["margin_%"] = (100 * reg.profit / reg.sales).round(1);
print((reg.assign(sales=reg.sales / 1e6, profit=reg.profit / 1e6)).round(2))
```

OUTPUT

```
                lines  avg_days        sales  share_%
ship_mode
Same Day          321       0.0   10082429.5      5.1
First Class       948       1.5   31455543.0     15.0
Second Class     1249       3.0   40858316.0     19.8
Standard Class   3805       5.6  119017280.5     60.2
         sales  profit  margin_%
region
East     18.91    2.07      10.9
North    16.43    1.56       9.5
South    20.80    1.77       8.5
West     22.23    2.10       9.4
```

## 8. Excel report for the business

Python

```
from pathlib import Path
out = Path("reports"); out.mkdir(exist_ok=True)
with pd.ExcelWriter(out / "sales_review_2025.xlsx", engine="openpyxl") as xw:
    view.to_excel(xw, sheet_name="KPIs")
    sub.reset_index().to_excel(xw, sheet_name="Sub-category 2025", index=False)
    db.reset_index().to_excel(xw, sheet_name="Discount bands", index=False)
    retention.reset_index().astype(str).to_excel(xw, sheet_name="Cohort retention",
index=False)
    s[s.year == 2025].drop(columns=["month", "quarter"]).to_excel(xw, sheet_name="Data
2025", index=False)
import openpyxl
wb = openpyxl.load_workbook(out / "sales_review_2025.xlsx")
for ws in wb.worksheets:
    ws.freeze_panes = "B2"; ws.auto_filter.ref = ws.dimensions
    for col in ws.columns: ws.column_dimensions[col[0].column_letter].width = 16
wb.save(out / "sales_review_2025.xlsx")
print(wb.sheetnames, f"{(out / 'sales_review_2025.xlsx').stat().st_size / 1e6:.1f} MB")
import shutil; shutil.rmtree(out)
```

OUTPUT

```
['KPIs', 'Sub-category 2025', 'Discount bands', 'Cohort retention', 'Data 2025'] 0.3
MB
```

## 9. Executive summary (template)

Write the summary **from the numbers above**; every claim should point to a table or chart.

**KEY TAKEAWAYS**

Fill each line from your outputs: 1. **Growth**: 2025 sales of **₹M (+**% on 2024), profit **₹M (+**%), margin __%. 2. **Profit engines**: __ and __ deliver __% of profit; __ and **lose mon**. 3. **Discounts**: lines discounted above 20% h**e a __% m**gin, against __% at no discount. 4. **Customers**: the top 20% of customers brin**__% of sales, an**__% of a cohort is still buying a year later. 5. **Actions for 2026**: cap discounts on __; review pricing of __; a loyalty programme for the top customers; a retention push in the first quarter after a customer's first purchase.

# 10. README for your portfolio

Text

```
# Superstore India: 2025 Sales Review (Python)
**Question:** How did 2025 perform, where is profit made and lost, how loyal are customers?
**Data:** 6,323 order lines, 2023-2025 (synthetic, modelled on the Superstore dataset).
**Tools:** pandas, Matplotlib, Seaborn, openpyxl.
**Method:** validation checks → enrichment → KPIs, Pareto, cohort retention, discount
analysis.
**Key findings:** (3-5 bullets with numbers)
**Recommendations:** (3 bullets)
**How to run:** `pip install -r requirements.txt && python src/run_report.py`
**Repo:** data/ · src/ · notebooks/ · reports/ · README.md
```

## Summary

**KEY TAKEAWAYS**

- A project is a pipeline: load → validate (assertions) → enrich → analyse → visualise → report.
- KPI tables with growth, sub-category profitability, discount bands, Pareto concentration and cohort retention answer most retail questions.
- `pd.ExcelWriter` + openpyxl create business-ready, filterable workbooks.
- Finish with an executive summary tied to numbers and a portfolio README.

## Quick quiz

6 questions · tap an answer to check it

**1. Why put validation checks at the start of the pipeline?**

A To stop early if the data breaks assumptions, rather than producing wrong results

B To make the code longer

C Because pandas requires it

D To speed up loading

**Answer: A.** Assertions make failures loud.

**2.** What does a Pareto analysis of customers show?

A Average sales

B How concentrated sales are among the top customers

C Retention over time

D Discount impact

**Answer: B.** Often a minority of customers brings most of the revenue.

**3.** What is a cohort in retention analysis?

A Customers grouped by the period of their first purchase

B Customers in the same city

C All customers

D Products in a category

**Answer: A.** Retention follows each cohort over time.

**4.** Which tool writes several sheets to one Excel file?

A `df.to_csv`

B `pd.ExcelWriter`

C `openpyxl.load_workbook` only

D `df.to_json`

**Answer: B.** Then format with openpyxl.

**5. What belongs in an executive summary?**

A All code

B Key numbers, findings and recommended actions

C Raw data

D Library versions

**Answer: B.** Lead with the answer.

**6. Why write analysis steps as functions?**

A They can be tested, re-run on new data and reused

B They run faster in all cases

C Notebooks forbid loops

D To avoid variables

**Answer: A.** Reproducibility matters.

EXERCISE

## Extend the capstone

(1) Add product-level ABC analysis (A = top 80% of sales). (2) Compute RFM scores for 2025 customers (see ML track lesson on segmentation). (3) Turn the chart cells into a function that saves PNGs to `reports/`. (4) Publish the project on GitHub with the README template and one chart in the README.

Show solution (worked answer)

Python

```
prod = s.groupby("product_name")["sales"].sum().sort_values(ascending=False)
share = prod.cumsum() / prod.sum()
abc = pd.cut(share, [0, .8, .95, 1], labels=["A", "B", "C"]);
print(abc.value_counts())
snap = s.order_date.max() + pd.Timedelta(days=1)
rfm = s[s.year == 2025].groupby("customer_id").agg(R=("order_date", lambda d: (snap -
d.max()).days), F=("order_id", "nunique"), M=("sales", "sum"))
rfm["score"] = pd.qcut(-rfm.R, 4, labels=False) + pd.qcut(rfm.F.rank(method="first"),
4, labels=False) + pd.qcut(rfm.M, 4, labels=False)
print(rfm.sort_values("score", ascending=False).head())
```

INTERVIEW CORNER

## Questions you may be asked

**Q: Walk me through a project you are proud of.** Use STAR: the business situation and question, your task, the actions (data, cleaning, analysis, tools), and the result with numbers and what changed. Keep it to two minutes and be ready to go deeper on any step.

**Q: How do you make sure your numbers are right?** Validation checks, reconciling totals with a trusted source, spot-checking individual records, peer review, and versioned, re-runnable code.

**Q: What would you do next with more time?** Automate the refresh (schedule + Parquet/database), add a dashboard, build a churn or demand-forecast model, and run an experiment on discount policy.