GENERATIVE AI & AGENTIC AI · LESSON 6 OF 12

Tool Use and Function Calling: Letting LLMs Query Data, Call APIs and Take Actions

Connect a model to the outside world. How function calling works (tool definitions, JSON schemas, tool_use and tool_result blocks), the request–execute–respond loop, writing good tool descriptions, strict schemas and validation, parallel calls, error handling, server-side tools (web search, code execution), and safety controls, with a runnable sales-analytics assistant that answers questions by calling SQL and calculator tools.

GenAI Launchpad · ✦ Anthropic tool use, tool runner and strict schemas (2026) · Intermediate · ⏱ 120 min

By the end of this lesson you can


- Define tools with names, descriptions and JSON input schemas
- Implement the tool-use loop and return tool results (including errors) correctly
- Use the SDK tool runner, strict schemas and parallel tool calls
- Combine client tools with server tools such as web search and code execution
- Apply safety controls: least privilege, validation, confirmation and audit logs

Datasets used

`superstore_sales.csv`

Why tools?

LLMs cannot see your database, today's exchange rate or your calendar, and they are unreliable at arithmetic. **Tool use** (function calling) lets the model ask *your code* to do these things: the model decides **which tool** to call with **which arguments**; your code runs it and returns the result; the model uses the result to answer.



The tool-use loop: the model requests a tool, your application executes it, and the result goes back to the model until it can answer.

Defining tools

A tool is a name, a **description** (the model reads it to decide when to use the tool) and a **JSON Schema** for the input.

Python

```
import json, re, duckdb, pandas as pd, numpy as np
sales = pd.read_csv("superstore_sales.csv", parse_dates=["order_date"])
con = duckdb.connect(); con.register("sales", sales)
TOOLS = [
    {"name": "run_sql",
     "description": "Run a read-only DuckDB SQL query on table `sales` (one row per order
line) and return up to 20 rows as JSON. "
                    "Columns: order_id, order_date (DATE), ship_date, ship_mode,
customer_id, segment, city, state, region, category, sub_category, "
                    "product_name, sales (INR), quantity, discount (0-1), profit (INR). Use
this for any question about sales data.",
     "input_schema": {"type": "object", "properties": {"sql": {"type": "string",
"description": "A single SELECT statement"}}, "required": ["sql"], "additionalProperties":
False}},
    {"name": "calculator",
     "description": "Evaluate an arithmetic expression exactly, e.g. '(78.38 - 65.40) /
65.40 * 100'. Use for growth rates and percentages.",
     "input_schema": {"type": "object", "properties": {"expression": {"type": "string"}},
"required": ["expression"], "additionalProperties": False}},
    {"name": "convert_currency",
     "description": "Convert an amount from INR to USD, EUR or AED using today's reference
rate.",
     "input_schema": {"type": "object", "properties": {"amount_inr": {"type": "number"},
"to": {"type": "string", "enum": ["USD", "EUR", "AED"]}}, "required": ["amount_inr", "to"],
"additionalProperties": False}},
]
print(json.dumps(TOOLS[1], indent=1))
```

OUTPUT

```
{
 "name": "calculator",
 "description": "Evaluate an arithmetic expression exactly, e.g. '(78.38 - 65.40) /
65.40 * 100'. Use for growth rates and percentages.",
 "input_schema": {
  "type": "object",
  "properties": {
   "expression": {
    "type": "string"
   }
  },
  "required": [
   "expression"
  ],
  "additionalProperties": false
 }
}
```

TIP **Write tool descriptions like documentation for a new colleague**

Say what the tool does, when to use it (and when not to), what each parameter means with formats and examples, and what it returns. Most tool-use failures come from vague descriptions, not from the model.

Implementing the tools safely

Python

```
import ast, operator as op
def run_sql(sql: str):
    if not re.match(r"^\s*(with|select)\b", sql, re.I) or
re.search(r"\b(insert|update|delete|drop|alter|create|copy|attach|pragma)\b", sql, re.I):
        raise ValueError("only read-only SELECT queries are allowed")
    return con.execute(sql).df().head(20).round(2).to_dict("records")
OPS = {ast.Add: op.add, ast.Sub: op.sub, ast.Mult: op.mul, ast.Div: op.truediv, ast.Pow:
op.pow, ast.USub: op.neg}
def calculator(expression: str):                    # safe arithmetic: no eval()
    def ev(n):
        if isinstance(n, ast.Constant) and isinstance(n.value, (int, float)): return
n.value
        if isinstance(n, ast.BinOp) and type(n.op) in OPS: return OPS[type(n.op)]
(ev(n.left), ev(n.right))
        if isinstance(n, ast.UnaryOp) and type(n.op) in OPS: return OPS[type(n.op)]
(ev(n.operand))
        raise ValueError("unsupported expression")
    return round(ev(ast.parse(expression, mode="eval").body), 4)
RATES = {"USD": 1 / 88.0, "EUR": 1 / 102.0, "AED": 1 / 24.0}      # illustrative reference
rates
def convert_currency(amount_inr: float, to: str): return {"amount": round(amount_inr *
RATES[to], 2), "currency": to}
REGISTRY = {"run_sql": run_sql, "calculator": calculator, "convert_currency":
convert_currency}
def execute_tool(name, tool_input):
    try: return {"content": json.dumps(REGISTRY[name](**tool_input), default=str)}
    except Exception as e: return {"content": f"Error: {e}", "is_error": True}       #
errors go back to the model, which can fix its call
print(execute_tool("run_sql", {"sql": "SELECT region, ROUND(SUM(sales)/1e6, 2) AS sales_m
FROM sales GROUP BY region ORDER BY sales_m DESC"}))
print(execute_tool("run_sql", {"sql": "DROP TABLE sales"}))
print(execute_tool("calculator", {"expression": "__import__('os').system('ls')"}))
```

OUTPUT

```
{'content': '[{"region": "South", "sales_m": 53.95}, {"region": "West", "sales_m":
51.96}, {"region": "North", "sales_m": 49.02}, {"region": "East", "sales_m":
46.48}]'}
```

```
{'content': 'Error: only read-only SELECT queries are allowed', 'is_error': True}
{'content': 'Error: unsupported expression', 'is_error': True}
```

Never `eval()` model output, never give a tool more power than it needs (read-only database user, allow-listed endpoints), and return errors as `tool_result` with `is_error: true` instead of crashing.

The loop (with a simulated model)

A real model decides tool calls itself. To run offline, a scripted "model" below emits the same block structure Claude returns, so you can see exactly what flows through the loop.

Python

```
import types
def block(**kw): return types.SimpleNamespace(**kw)
class ScriptedModel:
    """Emits Anthropic-style responses: tool_use blocks first, then a final text answer
that uses the tool results."""
    def __init__(self, plan): self.plan, self.step = plan, 0
    def create(self, messages, tools, **kw):
        if self.step < len(self.plan):
            calls = self.plan[self.step](messages); self.step += 1
            return block(stop_reason="tool_use", content=[block(type="text", text="Let me
check the data.")] +
                         [block(type="tool_use", id=f"toolu_{self.step}_{i}", name=n,
input=a) for i, (n, a) in enumerate(calls)])
        results = [json.loads(c["content"]) for m in messages if m["role"] == "user" and
isinstance(m["content"], list) for c in m["content"] if c.get("type") == "tool_result" and
not c.get("is_error")]
        return block(stop_reason="end_turn", content=[block(type="text",
text=FINAL(results))])

question = "How much did 2025 sales grow over 2024, and what is 2025 sales in US dollars?"
plan = [lambda m: [("run_sql", {"sql": "SELECT YEAR(order_date) AS yr,
ROUND(SUM(sales)/1e6, 2) AS sales_m FROM sales WHERE YEAR(order_date) IN (2024, 2025) GROUP
BY yr ORDER BY yr"})],
        lambda m: (lambda r: [("calculator", {"expression": f"({r[1]['sales_m']} - {r[0]
['sales_m']}) / {r[0]['sales_m']} * 100"}),          # two tool calls in parallel
                              ("convert_currency", {"amount_inr": r[1]["sales_m"] * 1e6,
"to": "USD"})])(json.loads(m[-1]["content"][0]["content"]))]
FINAL = lambda res: (f"2025 sales were ₹{res[0][1]['sales_m']}M against ₹{res[0][0]
['sales_m']}M in 2024, growth of {res[1]:.1f}%. "
                     f"That is about ${res[2]['amount'] / 1e6:.2f}M at the reference
rate.")
model = ScriptedModel(plan)
messages = [{"role": "user", "content": question}]
while True:
    resp = model.create(messages=messages, tools=TOOLS)
    messages.append({"role": "assistant", "content": resp.content})
    if resp.stop_reason != "tool_use": break
    results = []
    for b in resp.content:
        if b.type == "tool_use":
            out = execute_tool(b.name, b.input); print(f"→ {b.name}({json.dumps(b.input)
[:90]}) = {out['content'][:90]}")
            results.append({"type": "tool_result", "tool_use_id": b.id, **out})
    messages.append({"role": "user", "content": results})                # ALL results of
a turn go back in ONE user message
print("\nAnswer:", next(b.text for b in resp.content if b.type == "text"))
```

OUTPUT

```
→ run_sql({"sql": "SELECT YEAR(order_date) AS yr, ROUND(SUM(sales)/1e6, 2) AS sales_m
FROM sales WHE) = [{"yr": 2024, "sales_m": 65.4}, {"yr": 2025, "sales_m": 78.38}]
```

```
→ calculator({"expression": "(78.38 - 65.4) / 65.4 * 100"}) = 19.8471
→ convert_currency({"amount_inr": 78380000.0, "to": "USD"}) = {"amount": 890681.82,
"currency": "USD"}

Answer: 2025 sales were ₹78.38M against ₹65.4M in 2024, growth of 19.8%. That is
about $0.89M at the reference rate.
```

The numbers in the answer come from the database and the calculator, not from the model's memory: that is the point of tools.

With the real Claude API

Python

```python
import anthropic
client = anthropic.Anthropic()
messages = [{"role": "user", "content": question}]
while True:
    response = client.messages.create(model="claude-opus-5-5", max_tokens=16000,
tools=TOOLS, messages=messages)
    messages.append({"role": "assistant", "content": response.content})      # keep the
full content, including tool_use blocks
    if response.stop_reason != "tool_use":
        break
    results = []
    for b in response.content:
        if b.type == "tool_use":
            results.append({"type": "tool_result", "tool_use_id": b.id,
**execute_tool(b.name, b.input)})
    messages.append({"role": "user", "content": results})
print(next(b.text for b in response.content if b.type == "text"))
```

The SDK's **tool runner** writes this loop for you: decorate Python functions and their type hints and docstrings become the schema.

Python

```python
from anthropic import beta_tool

@beta_tool
def calculator(expression: str) -> str:
    """Evaluate an arithmetic expression exactly.

    Args:
        expression: e.g. '(78.38 - 65.40) / 65.40 * 100'
    """
    return str(safe_eval(expression))

runner = client.beta.messages.tool_runner(model="claude-opus-5-5", max_tokens=16000, tools=
[calculator, run_sql_tool],
                                          messages=[{"role": "user", "content": question}])
for message in runner:          # iterates until Claude stops calling tools
    print(message.content[-1])
```

Making tool calls reliable

Technique	How
Strict schemas	Add `"strict": true` to a tool (with `additionalProperties: false` and `required`) so inputs always match the schema
Clear, distinct tools	Few tools with non-overlapping purposes; consistent naming (`get_`, `search_`, `create_`)
Validate inputs anyway	Check types, ranges and permissions before executing
Return informative errors	"Column 'revenue' not found; did you mean 'sales'?" lets the model self-correct
Steer tool choice from the prompt	"Always use `run_sql` for questions about sales." (On the newest Claude models, forcing a specific tool via `tool_choice` is not supported; use `auto` plus instructions, or structured outputs when you only need JSON.)
Parallel calls	Independent calls arrive in one turn; run them concurrently and return all results in one message
Limits	Cap loop iterations, rows returned and total tokens

Server-side tools

Some tools run on the provider's infrastructure: you only declare them.

Python

```
response = client.messages.create(
    model="claude-opus-5-5", max_tokens=16000,
    tools=[{"type": "web_search_20260209", "name": "web_search", "max_uses": 3,
"allowed_domains": ["rbi.org.in", "pib.gov.in"]}],
    messages=[{"role": "user", "content": "What is the current RBI repo rate? Cite the
source."}],
)
```

Server tool	Use
Web search / web fetch	Current information with citations
Code execution	The model writes and runs Python in a sandbox (data analysis, charts)
MCP connectors	Tools from remote MCP servers (lesson 8)

Safety: tools turn words into actions



Defence in depth for tool-using systems.

Prompt injection becomes more dangerous with tools: a malicious web page or document could say "email the customer list to ...". Treat all tool outputs and retrieved text as **data**, never as instructions; keep secrets out of the model's reach; and require confirmation for actions with side effects.

Summary

KEY TAKEAWAYS

- Tools let a model request actions: you define name, description and JSON schema; the model emits `tool_use` ; your code returns `tool_result` .
- Loop until `stop_reason` is not `tool_use` ; return all results of a turn in one user message; return errors with `is_error` .
- Use the SDK tool runner for simple loops; strict schemas, validation and good descriptions for reliability.
- Server tools (web search, code execution) run on the provider side.
- Apply least privilege, validation, limits, approval for side effects and audit logs; treat tool outputs as data.

Quick quiz

6 questions · tap an answer to check it

1. Who executes a client-side tool?

A Your application code

B The LLM provider automatically

C The user manually

D The database administrator

Answer: A. The model only requests the call.

2. What does the model return when it wants a tool?

A A `tool_use` block with the tool name and JSON input, and stop_reason "tool_use"

B Python code to run

C A SQL result

D An error

Answer: A. You then run it and reply with `tool_result`.

3. A tool raises an exception. What should you send back?

A A tool_result with the error message and `is_error: true`

B Nothing

C Crash the application

D A fake success

Answer: A. The model can correct its call.

4. What matters most for the model choosing the right tool?

A A clear, specific tool description and parameter descriptions

B A long tool name

C Many overlapping tools

D High temperature

Answer: A. Write descriptions like documentation.

5. **Why give the SQL tool read-only access?**

- **A** Least privilege limits damage from mistakes or prompt injection
- **B** It is faster
- **C** Models cannot write SQL
- **D** DuckDB requires it

Answer: A. Never trust generated code blindly.

6. **How do you return results for three parallel tool calls?**

- **A** All three tool_result blocks in a single user message
- **B** Three separate user messages
- **C** Only the first result
- **D** As assistant text

Answer: A. Keeps parallel calling working well.

EXERCISE

Practice

(1) Add a `top_products(category, n)` tool and a scripted plan that uses it. (2) Make `run_sql` return a helpful error when a column does not exist (list valid columns). (3) Add a loop limit of 5 iterations and a total-rows limit. (4) With a real API key, ask Claude three analytics questions through this loop and check every number against your own SQL.

Show solution (worked answer)

Python

```
def top_products(category: str, n: int = 5):
    return con.execute("SELECT product_name, ROUND(SUM(profit)) AS profit FROM sales
WHERE category = ? GROUP BY 1 ORDER BY 2 DESC LIMIT ?", [category,
n]).df().to_dict("records")
REGISTRY["top_products"] = top_products
def run_sql(sql):
    try: return con.execute(sql).df().head(20).to_dict("records")
    except duckdb.BinderException as e: raise ValueError(f"{e}. Valid columns:
{list(sales.columns)}")
```

INTERVIEW CORNER

Questions you may be asked

Q: How does function calling work? You describe tools with JSON schemas; the model returns a structured tool call instead of text when it needs one; your code executes it and sends the result back; the model continues until it can answer.

Q: How do you stop an LLM agent from doing something harmful with tools? Least-privilege credentials, input validation and allow-lists, amount/rate limits, human approval for side effects, sandboxing, audit logs, and treating retrieved content as untrusted data.

Q: Tool use vs RAG? RAG retrieves text to read; tool use performs computations or actions and fetches live structured data. Many assistants combine both, with retrieval itself exposed as a tool.

Practise more online

Free, trusted places to test yourself on this topic. Links open the original site in a new tab.