STATISTICS & MACHINE LEARNING · LESSON 19 OF 30

Ensembles II: Gradient Boosting, XGBoost, LightGBM and CatBoost

The algorithm family that wins most tabular-data problems. Boosting intuition (AdaBoost to gradient boosting), fitting trees to residuals by hand, learning rate and number of trees, early stopping, scikit-learn's HistGradientBoosting, XGBoost and LightGBM APIs and key hyperparameters, categorical features and CatBoost, and a tuned comparison on churn and house prices.

ML track (added) · ✦ XGBoost 3.x · LightGBM 4.x · scikit-learn 1.7+ · Advanced · ⏱ 120 min

By the end of this lesson you can


- Explain sequential boosting and how gradient boosting fits trees to residuals (gradients)
- Implement a few boosting rounds by hand to see the mechanism
- Tune learning rate, number of trees, depth, subsampling and regularisation with early stopping
- Use HistGradientBoosting, XGBoost and LightGBM with native categorical handling
- Decide when boosting is worth its extra complexity

Datasets used

`telecom_churn.csv` `house_prices.csv`

Boosting: learn from mistakes

Bagging trains trees **independently** and averages them (reduces variance). **Boosting** trains small trees **sequentially**: each new tree focuses on what the current ensemble gets wrong (reduces bias).



Gradient boosting adds trees one at a time, each correcting the remaining error.

- **AdaBoost** (1995) reweights misclassified rows so the next learner focuses on them.
- **Gradient boosting** (Friedman, 2001) fits each new tree to the **negative gradient of the loss**; for squared error, that is simply the residual.

$$F_m(x) = F_{m-1}(x) + \nu\, h_m(x), \qquad h_m \approx -\frac{\partial L(y, F_{m-1})}{\partial F_{m-1}}$$

Boosting by hand

Python

```
import numpy as np, pandas as pd
from sklearn.tree import DecisionTreeRegressor
from sklearn.model_selection import train_test_split
from sklearn.metrics import mean_absolute_error
h = pd.read_csv("house_prices.csv").dropna(subset=["area_sqft"]); h =
h[h.price_lakh.between(5, 300)]
Xh = pd.get_dummies(h.drop(columns=["house_id", "price_lakh"]),
drop_first=True).astype(float); yh = h.price_lakh
Xtr, Xte, ytr, yte = train_test_split(Xh, yh, test_size=0.2, random_state=0)
lr, pred_tr, pred_te = 0.3, np.full(len(ytr), ytr.mean()), np.full(len(yte), ytr.mean())
print(f"round 0 (mean only): test MAE {mean_absolute_error(yte, pred_te):.2f}")
for m in range(1, 31):
    resid = ytr - pred_tr                                    # negative gradient of
squared error
    tree = DecisionTreeRegressor(max_depth=3, random_state=0).fit(Xtr, resid)
    pred_tr += lr * tree.predict(Xtr); pred_te += lr * tree.predict(Xte)
    if m in (1, 2, 5, 10, 30): print(f"round {m:2d}: test MAE {mean_absolute_error(yte,
pred_te):.2f}")
```


OUTPUT

```
round 0 (mean only): test MAE 25.00
round  1: test MAE 19.07
round  2: test MAE 15.39
round  5: test MAE 10.61
```

```
round 10: test MAE 8.01
round 30: test MAE 6.95
```

Thirty shallow trees, each correcting the last, beat a single deep tree.

The learning rate and number of trees



Validation error by boosting round for different learning rates: small rates need more trees but often reach lower error; too many rounds can overfit.

Unlike random forests, boosting **can overfit** with too many rounds. Use a small learning rate (0.01–0.1) with **early stopping** on a validation set.

scikit-learn HistGradientBoosting

The fast, modern implementation in scikit-learn (inspired by LightGBM): bins features into histograms, handles missing values and categorical features natively, supports early stopping.

Python

```
from sklearn.ensemble import HistGradientBoostingClassifier
from sklearn.metrics import roc_auc_score
tc = pd.read_csv("telecom_churn.csv")
Xc = tc.drop(columns=["customer_id", "churn", "total_charges"]); yc = (tc.churn ==
"Yes").astype(int)
for col in ["contract", "internet_service", "payment_method"]: Xc[col] =
Xc[col].astype("category")
Xa, Xb, ya, yb = train_test_split(Xc, yc, test_size=0.3, stratify=yc, random_state=1)
hgb = HistGradientBoostingClassifier(learning_rate=0.05, max_iter=1000, max_depth=None,
max_leaf_nodes=15, min_samples_leaf=40, l2_regularization=1.0,
                                     categorical_features="from_dtype",
early_stopping=True, validation_fraction=0.15, n_iter_no_change=30, random_state=0).fit(Xa,
ya)
print(f"HistGradientBoosting: stopped after {hgb.n_iter_} trees | test AUC
{roc_auc_score(yb, hgb.predict_proba(Xb)[:, 1]):.3f}")
```

OUTPUT

```
HistGradientBoosting: stopped after 87 trees | test AUC 0.806
```

XGBoost

Python

```
import xgboost as xgb
Xa_tr, Xa_va, ya_tr, ya_va = train_test_split(Xa, ya, test_size=0.2, stratify=ya,
random_state=0)
xg = xgb.XGBClassifier(n_estimators=2000, learning_rate=0.03, max_depth=3, subsample=0.8,
colsample_bytree=0.8, min_child_weight=5, reg_lambda=1.0,
                       enable_categorical=True, tree_method="hist", eval_metric="auc",
early_stopping_rounds=100, random_state=0)
xg.fit(Xa_tr, ya_tr, eval_set=[(Xa_va, ya_va)], verbose=False)
print(f"XGBoost {xgb.__version__}: best iteration {xg.best_iteration} | test AUC
{roc_auc_score(yb, xg.predict_proba(Xb)[:, 1]):.3f}")
```

OUTPUT

```
XGBoost 3.4.1: best iteration 6 | test AUC 0.806
```

LightGBM

Python

```
import lightgbm as lgb
lg = lgb.LGBMClassifier(n_estimators=2000, learning_rate=0.03, num_leaves=15,
min_child_samples=40, subsample=0.8, subsample_freq=1, colsample_bytree=0.8,
reg_lambda=1.0, random_state=0, verbose=-1)
lg.fit(Xa_tr, ya_tr, eval_set=[(Xa_va, ya_va)], eval_metric="auc", callbacks=
[lgb.early_stopping(100, verbose=False)])
print(f"LightGBM {lgb.__version__}: best iteration {lg.best_iteration_} | test AUC
{roc_auc_score(yb, lg.predict_proba(Xb)[:, 1]):.3f}")
```

OUTPUT

```
LightGBM 4.7.0: best iteration 11 | test AUC 0.809
```

Early stopping chose very few trees for XGBoost and LightGBM here: with 2,000 training rows and a simple signal, validation AUC peaks early. On larger datasets the best iteration is typically in the hundreds or thousands.

LightGBM grows trees **leaf-wise** (it splits the leaf with the biggest gain), which is fast and accurate on large data; control complexity with `num_leaves` and `min_child_samples`. **CatBoost** uses ordered target statistics for categorical features and symmetric trees; it is often the best choice when there are many high-cardinality categories (`pip install catboost`).

Key hyperparameters (cheat sheet)

Idea	XGBoost	LightGBM	HistGradientBoosting	Typical
Number of trees	`n_estimators`	`n_estimators`	`max_iter`	Large + early stopping
Step size	`learning_rate`	`learning_rate`	`learning_rate`	0.01–0.1
Tree size	`max_depth`	`num_leaves`, `max_depth`	`max_leaf_nodes`, `max_depth`	depth 3–8 / 15–63 leaves
Leaf size	`min_child_weight`	`min_child_samples`	`min_samples_leaf`	5–100
Row sampling	`subsample`	`subsample` (+ `subsample_freq`)	—	0.6–0.9
Column sampling	`colsample_bytree`	`colsample_bytree`	`max_features`	0.5–0.9
Regularisation	`reg_lambda`, `reg_alpha`, `gamma`	`reg_lambda`, `reg_alpha`	`l2_regularization`	
Imbalance	`scale_pos_weight`	`is_unbalance`, `scale_pos_weight`	`class_weight`	ratio of negatives to positives

Tuning recipe: fix a learning rate (0.05), early-stop the number of trees, tune tree size and leaf size, then sampling and regularisation (Optuna works well), and finally lower the learning rate and raise trees for a last bit of accuracy.

Comparison on two problems

Python

```
from sklearn.model_selection import cross_val_score, StratifiedKFold, KFold
from sklearn.linear_model import LogisticRegression, Ridge
from sklearn.ensemble import RandomForestClassifier, RandomForestRegressor,
HistGradientBoostingRegressor
from sklearn.pipeline import make_pipeline
from sklearn.preprocessing import StandardScaler
Xd = pd.get_dummies(Xc, drop_first=True).astype(float)
cv = StratifiedKFold(5, shuffle=True, random_state=0)
cls = {"logistic regression": make_pipeline(StandardScaler(),
LogisticRegression(max_iter=2000)), "random forest": RandomForestClassifier(400,
min_samples_leaf=20, random_state=0, n_jobs=-1),
       "HistGradientBoosting": HistGradientBoostingClassifier(learning_rate=0.05,
max_iter=200, max_leaf_nodes=15, min_samples_leaf=40, random_state=0),
       "XGBoost": xgb.XGBClassifier(n_estimators=300, learning_rate=0.03, max_depth=3,
subsample=0.8, colsample_bytree=0.8, random_state=0),
       "LightGBM": lgb.LGBMClassifier(n_estimators=300, learning_rate=0.03, num_leaves=15,
min_child_samples=40, random_state=0, verbose=-1)}
print("Churn (5-fold ROC-AUC):")
for n, m in cls.items(): s = cross_val_score(m, Xd, yc, cv=cv, scoring="roc_auc"); print(f"
{n:22s} {s.mean():.3f} ± {s.std():.3f}")
reg = {"ridge": make_pipeline(StandardScaler(), Ridge()), "random forest":
RandomForestRegressor(400, min_samples_leaf=2, max_features=0.6, random_state=0,
n_jobs=-1),
       "HistGradientBoosting": HistGradientBoostingRegressor(learning_rate=0.05,
max_iter=500, random_state=0),
       "XGBoost": xgb.XGBRegressor(n_estimators=600, learning_rate=0.05, max_depth=4,
subsample=0.8, colsample_bytree=0.8, random_state=0),
       "LightGBM": lgb.LGBMRegressor(n_estimators=600, learning_rate=0.05, num_leaves=15,
random_state=0, verbose=-1)}
print("House prices (5-fold MAE, ₹ lakh):")
for n, m in reg.items(): s = -cross_val_score(m, Xh, yh, cv=KFold(5, shuffle=True,
random_state=0), scoring="neg_mean_absolute_error"); print(f"  {n:22s} {s.mean():.2f} ±
{s.std():.2f}")
```

OUTPUT

```
Churn (5-fold ROC-AUC):
  logistic regression    0.812 ± 0.015
  random forest          0.798 ± 0.014
  HistGradientBoosting   0.790 ± 0.016
  XGBoost                0.804 ± 0.012
  LightGBM               0.791 ± 0.010
House prices (5-fold MAE, ₹ lakh):
  ridge                  6.12 ± 0.25
  random forest          6.95 ± 0.36
  HistGradientBoosting   6.79 ± 0.25
```

```
XGBoost                 6.48 ± 0.31
LightGBM                6.73 ± 0.26
```

Read results honestly: on these clean, mostly additive datasets, linear models are competitive. Boosting's advantage grows with more data, more features, interactions, missing values and messy real-world signals, which is why it dominates tabular competitions and industry credit, fraud, pricing and ranking models.

Summary

KEY TAKEAWAYS

- Boosting adds shallow trees sequentially; gradient boosting fits each tree to the negative gradient (residuals for squared error).
- The learning rate scales each tree; small rates need more trees; use early stopping because boosting can overfit.
- HistGradientBoosting, XGBoost and LightGBM are fast histogram-based implementations with native missing-value and categorical support; CatBoost excels with many categories.
- Tune trees (via early stopping), tree/leaf size, sampling and regularisation.
- Always compare with simple baselines; boosting shines on large, messy, interaction-rich tabular data.

Quick quiz

6 questions · tap an answer to check it

1. How does boosting differ from bagging?

A Boosting trains models sequentially, each fixing the previous errors; bagging trains them independently

B Boosting uses bigger trees

C Bagging cannot do regression

D They are the same

Answer: A. Boosting reduces bias; bagging reduces variance.

2. For squared error, what does each new tree in gradient boosting fit?

- **A** The residuals of the current ensemble
- **B** The original target
- **C** Random noise
- **D** The features

Answer: A. Residuals are the negative gradient.

3. What does a smaller learning rate require?

- **A** More trees, often with better final accuracy
- **B** Fewer trees
- **C** No early stopping
- **D** Deeper trees only

Answer: A. Typical rates are 0.01–0.1.

4. Can gradient boosting overfit by adding too many trees?

- **A** Yes; use early stopping on validation data
- **B** No, never
- **C** Only for classification
- **D** Only with small learning rates

Answer: A. Unlike random forests.

5. What does LightGBM's `num_leaves` control?

- **A** The complexity of each leaf-wise tree
- **B** The number of trees
- **C** The learning rate
- **D** Row sampling

Answer: A. Larger = more complex.

6. When is CatBoost particularly useful?

- **A** Many high-cardinality categorical features
- **B** Images
- **C** Tiny datasets only
- **D** Linear relationships

Answer: A. Ordered target statistics handle categories well.

EXERCISE **Practice**

(1) Tune LightGBM on the bank loans data with early stopping; compare with logistic regression. (2) Use `scale_pos_weight` in XGBoost for the churn data and report recall at 0.5. (3) Plot validation AUC against boosting rounds from `xg.evals_result()`.

Show solution (worked answer)

Python

```
b = pd.read_csv("bank_loans.csv").dropna(subset=["default"]); fb = ["age", "ed",
"employ", "address", "income", "debtinc", "creddebt", "othdebt"]
print(cross_val_score(lgb.LGBMClassifier(n_estimators=300, learning_rate=0.03,
num_leaves=7, min_child_samples=30, verbose=-1), b[fb], b.default.astype(int), cv=cv,
scoring="roc_auc").mean())
from sklearn.metrics import recall_score
w = (ya == 0).sum() / (ya == 1).sum()
xw = xgb.XGBClassifier(n_estimators=300, learning_rate=0.03, max_depth=3,
scale_pos_weight=w, enable_categorical=True).fit(Xa, ya)
print(recall_score(yb, xw.predict(Xb)))
plt.plot(xg.evals_result()["validation_0"]["auc"])
```

INTERVIEW CORNER **Questions you may be asked**

Q: Explain gradient boosting in simple terms. Start with a simple prediction, look at the errors, train a small tree to predict those errors, add a fraction of it, and repeat; the ensemble gradually corrects itself.

Q: XGBoost vs LightGBM vs random forest? Random forests average independent deep trees (robust, little tuning); XGBoost and LightGBM build trees sequentially with regularisation and histogram speed-ups; LightGBM grows leaf-wise and is usually fastest on large data.

Q: How do you prevent overfitting in boosting? Lower learning rate with early stopping, shallow trees, minimum leaf size, row and column subsampling, and L1/L2 regularisation.

Practise more online

Free, trusted places to test yourself on this topic. Links open the original site in a new tab.