SQL FOR DATA ANALYSIS · LESSON 1 OF 20

Databases, RDBMS & SQL Basics

Understand what a database is, how relational databases organise data into tables, the vocabulary of SQL, the four families of SQL statements (DDL, DML, DCL, TCL), how SQL compares with Excel, and how to install SQL Server and SSMS and run your first query.

SQL class 1 | SQL Server 2022 / SSMS 21, 2026 | Beginner | 100 min

By the end of this lesson you can


- Explain what a database, a DBMS and an RDBMS are and why companies use them instead of spreadsheets
- Use the core vocabulary (table, row/record, column/field, schema, query, result set)
- Classify SQL statements into DDL, DML, DQL, DCL and TCL
- Compare Excel and SQL and know when to use each
- Install SQL Server Developer edition and SSMS, connect, create a database and run a first SELECT

Datasets used

`superstore_sales.csv` `customers.csv` `products.csv`

What is a database?

A **database** is an organised collection of data stored so that it can be found, updated and analysed efficiently and safely by many people at the same time. A **DBMS** (database management system) is the software that manages it. Your bank balance, every Swiggy order, every Aadhaar-linked record and every hospital appointment lives in a database.




Spreadsheets are personal tools; databases are shared systems built for scale, safety and many users.

Types of databases

Type	Organises data as	Examples	Typical use
Relational (RDBMS)	Tables with rows and columns, linked by keys	SQL Server, PostgreSQL, MySQL, Oracle, SQLite	Orders, payments, HR, finance: most business data
Document	JSON-like documents	MongoDB, Cosmos DB	Product catalogues, app content
Key-value	Key → value pairs	Redis, DynamoDB	Caching, sessions
Column-family / warehouse	Columns, built for analytics	Snowflake, BigQuery, Redshift, Databricks SQL	Analytics on huge data
Graph	Nodes and edges	Neo4j	Social networks, fraud rings
Vector	Number vectors (embeddings)	pgvector, Pinecone	AI search and RAG (GenAI track)

This track focuses on **relational databases** and **SQL**, the language almost every data role uses daily. You will practise in **Microsoft SQL Server** with **SSMS**, as in class. The SQL you learn transfers to PostgreSQL, MySQL, Snowflake and BigQuery with small differences in functions.

How a relational database organises data




The hierarchy inside SQL Server: a server holds databases, a database holds schemas, a schema holds tables and other objects.

The vocabulary

DEFINITION **Terms you will use every day**

Table (relation): a set of rows about one kind of thing, such as customers or orders. **Row (record, tuple)**: one item, such as one customer. **Column (field, attribute)**: one property, such as `city`. Every value in a column has the same data type. **Primary key**: the column (or columns) that uniquely identifies each row, such as `customer_id`. **Foreign key**: a column that refers to the primary key of another table, linking them. **Schema**: (1) the structure of the database (tables, columns, types, relationships); (2) in SQL Server, a named container of objects such as `dbo`. **Query**: a request for data written in SQL. Its output is a **result set**. **SQL**: Structured Query Language, the standard language for relational databases (ANSI/ISO standard since 1986–87). Pronounced "S-Q-L" or "sequel". **T-SQL**: Transact-SQL, Microsoft SQL Server's dialect with extra features (variables, TOP, procedures).

Here is the course's retail database. The order data is split into related tables instead of one wide sheet:



The course retail database. Each order belongs to one customer; each order has many order items; each item refers to one product.

Your first queries

A `SELECT` statement asks for columns `FROM` a table. Here are the first rows of the `customers` table:

SQL

```sql
SELECT TOP 6 customer_id, customer_name, segment, city, region
FROM customers;
```

RESULT

customer_id	customer_name	segment	city	region
C0001	Saanvi Khan	Corporate	Chandigarh	North
C0002	Meera Bose	Corporate	Delhi	North
C0003	Riya Shah	Consumer	Kolkata	East
C0004	Diya Fernandes	Corporate	Indore	West
C0005	Neha Sharma	Corporate	Hyderabad	South
C0006	Vikram Mehta	Consumer	Chandigarh	North

6 rows × 5 columns

How many rows are in each table?

SQL

```sql
SELECT 'customers' AS table_name, COUNT(*) AS row_count FROM customers
UNION ALL SELECT 'orders', COUNT(*) FROM orders
UNION ALL SELECT 'order_items', COUNT(*) FROM order_items
UNION ALL SELECT 'products', COUNT(*) FROM products;
```

RESULT

table_name	row_count
customers	800
orders	3200
order_items	6323
products	78

4 rows × 2 columns

A taste of what is coming: total sales by region in one statement (Lesson 7 explains `GROUP BY`):

SQL

```sql
SELECT c.region,
       COUNT(DISTINCT o.order_id) AS orders,
       ROUND(SUM(oi.sales), 0)     AS total_sales
FROM customers AS c
JOIN orders AS o       ON o.customer_id = c.customer_id
JOIN order_items AS oi ON oi.order_id = o.order_id
GROUP BY c.region
ORDER BY total_sales DESC;
```

RESULT

region	orders	total_sales
South	831	53,952,769
West	811	51,958,521
North	792	49,018,161
East	766	46,484,119


4 rows × 3 columns

> **TIP** **SQL reads almost like English**
>
> "Select the region, the number of distinct orders and the total sales, from customers joined to orders and order items, grouped by region, ordered by total sales descending." That readability is why SQL has lasted 50 years.

Properties of SQL

1. **Declarative**: you say *what* you want, not *how* to get it. The database's **query optimiser** decides the fastest way (which index, which join order).
2. **Set-based**: statements work on whole sets of rows at once, not one row at a time like a loop.
3. **Not case-sensitive for keywords**: `select`, `SELECT` and `Select` are the same. By convention, keywords are written in UPPERCASE. In SQL Server, text comparisons are usually case-insensitive too (default collation).
4. **Whitespace does not matter**: you can split a query over many lines; indent it for readability.
5. **Statements end with a semicolon ;** (optional in SQL Server for most statements, but a good habit).
6. **Standard, with dialects**: the core is an ANSI/ISO standard; each product adds its own functions (T-SQL, PL/pgSQL, MySQL).

The families of SQL statements



SQL statements fall into five families.

Family	Full name	What it does	Example
DDL	Data Definition Language	Creates and changes the **structure**: databases, tables, columns	`CREATE TABLE customers (...)`
DML	Data Manipulation Language	Adds, changes and removes **rows**	`INSERT INTO customers VALUES (...)`
DQL	Data Query Language	Reads data	`SELECT * FROM customers`
DCL	Data Control Language	Gives and removes **permissions**	`GRANT SELECT ON customers TO analyst`
TCL	Transaction Control Language	Groups changes so they succeed or fail together	`BEGIN TRAN … COMMIT`

Many books put SELECT inside DML; others separate it as DQL. Both are fine in interviews if you explain them.

Excel vs SQL

Task	Excel	SQL
See the data	Open the sheet	`SELECT * FROM table`
Filter rows	AutoFilter	`WHERE`
Sort	Sort dialog	`ORDER BY`
New calculated column	Formula in a new column	Expression in `SELECT`
Totals by group	Pivot table / SUMIFS	`GROUP BY` with `SUM`
Filter groups	Pivot value filter	`HAVING`
Lookup from another table	VLOOKUP / XLOOKUP	`JOIN`
Stack two tables	Copy-paste / Power Query Append	`UNION ALL`
Remove duplicates	Remove Duplicates	`DISTINCT`
Rank / running total	RANK, SUM(B2:B2)	Window functions `RANK() OVER`, `SUM() OVER`
Data size	~1 million rows per sheet	Billions of rows
Repeatability	Manual steps (unless Power Query)	Saved queries, views, procedures
Sharing	Files get copied	One source of truth with permissions

Use Excel for quick, small, ad-hoc analysis and presentation; use SQL to get, combine and summarise data at source. In practice analysts use both: SQL to extract the right data, Excel or Power BI to present it.

Installing SQL Server and SSMS

STEP BY STEP


Install on Windows (free)

1. Download **SQL Server 2022 Developer** edition (free, full-featured, for development and learning) from Microsoft's SQL Server downloads page. Choose **Basic** installation. Express edition is also free but limited to 10 GB per database.
2. Note the instance name shown at the end (for example `MSSQLSERVER` = default, or `SQLEXPRESS`).
3. Download and install **SQL Server Management Studio (SSMS)** from Microsoft Learn ("Download SSMS"). SSMS is the editor you write queries in.
4. Open SSMS → **Connect to Server**: Server type *Database Engine*; Server name `localhost` (or `localhost\SQLEXPRESS`); Authentication *Windows Authentication*; tick **Trust server certificate** → Connect.
5. In Object Explorer you will see Databases, Security and more. Click **New Query** (`Ctrl + N`).

NOTE

Mac or Linux?

SQL Server runs in **Docker** on Mac and Linux (`mcr.microsoft.com/mssql/server` image). Connect with **VS Code + the MSSQL extension** or Azure Data Studio's successor tools. Alternatively, practise the same SQL in **PostgreSQL** (pgAdmin) or **SQLite** (DB Browser); only a few functions differ.



The SSMS window: Object Explorer on the left, the query editor in the middle, results below.

Create a database and load data

```sql
-- 1. Create the database and switch to it
CREATE DATABASE RetailDB;
GO
USE RetailDB;
GO
-- 2. Check which database you are in
SELECT DB_NAME() AS current_database;
```

To load the course CSV files: right-click the database → **Tasks → Import Flat File** → choose `customers.csv` → check the column names and data types in the preview (make IDs `nvarchar`, dates `date`, amounts `decimal(12,2)`) → Finish. Repeat for the other files. Lesson 4 shows how to create tables with SQL and load them with `BULK INSERT`.

Running queries in SSMS

Action	Shortcut
Execute the whole window (or the selected text only)	F5 or `Ctrl + E`
New query window	`Ctrl + N`
Comment / uncomment selected lines	`Ctrl + K, Ctrl + C` / `Ctrl + K, Ctrl + U`
Show/hide results pane	`Ctrl + R`
IntelliSense refresh (after creating tables)	`Ctrl + Shift + R`
Results to grid / text / file	`Ctrl + D` / `Ctrl + T` / `Ctrl + Shift + F`
Estimated execution plan	`Ctrl + L`

> **TIP** **Select a part, run a part**
>
> Highlight just one statement and press F5 to run only that statement. This is how you test a long script step by step.

Summary

KEY TAKEAWAYS

- A **database** stores shared data safely; an **RDBMS** stores it in related **tables** of **rows** and **columns**.
- **Primary keys** identify rows; **foreign keys** link tables.
- SQL is declarative and set-based; keywords are not case-sensitive; statements end with `;`.
- Statement families: **DDL** (structure), **DML** (rows), **DQL** (SELECT), **DCL** (permissions), **TCL** (transactions).
- Excel is for quick analysis and presentation; SQL is for getting, combining and summarising data at scale.
- Practise in SQL Server Developer + SSMS (or Docker / PostgreSQL on Mac).

Quick quiz

6 questions · tap an answer to check it

1. Which statement family does `CREATE TABLE` belong to?

A DDL

B DML

C DCL

D TCL

Answer: A. DDL defines structure: CREATE, ALTER, DROP, TRUNCATE.

2. In a relational database, what links the orders table to the customers table?

A A merged cell

B A foreign key in orders that refers to the customer's primary key

C A pivot cache

D A shared file name

Answer: B. orders.customer_id is a foreign key that refers to customers.customer_id.

3. What does "SQL is declarative" mean?

A SQL must declare every variable

B You describe what result you want and the database decides how to get it

C SQL statements must be in capitals

D SQL can only define tables

Answer: B. The optimiser chooses the execution plan; you write the logic.

4. Which is NOT an advantage of a database over a spreadsheet?

A Many users at the same time

B Permissions on who sees what

C Constraints that protect data quality

D It is always faster to build a quick one-off chart

Answer: D. For quick one-off charts, Excel is usually faster. Databases win on scale, safety and sharing.

5. `GRANT SELECT ON orders TO analyst_role` is an example of:

A DDL

B DML

C DCL

D TCL

Answer: C. DCL controls permissions.

6. In SSMS, what does pressing F5 with part of the script highlighted do?

- **A** Runs only the highlighted statement(s)
- **B** Runs the whole script
- **C** Formats the code
- **D** Opens the execution plan

Answer: A. Highlighting limits execution to the selected text.

EXERCISE

Map the vocabulary

For the `orders` table in RetailDB, name: (a) one row; (b) one column; (c) the primary key; (d) the foreign key and the table it refers to; (e) the statement family of `INSERT INTO orders …`.

Show solution (worked answer)

(a) One order, for example the row for `IN-2023-00001`. (b) Any field, for example `ship_mode`. (c) `order_id`. (d) `customer_id`, which refers to `customers.customer_id`. (e) DML.

INTERVIEW CORNER

Questions you may be asked

Q: What is the difference between DBMS and RDBMS? A DBMS manages data in any form; an RDBMS stores data in tables with relationships defined by keys, enforces integrity with constraints and uses SQL. Examples: SQL Server, PostgreSQL, MySQL, Oracle.

Q: Explain DDL, DML, DCL and TCL with examples. DDL changes structure (CREATE, ALTER, DROP, TRUNCATE); DML changes rows (INSERT, UPDATE, DELETE); DCL manages permissions (GRANT, REVOKE); TCL manages transactions (COMMIT, ROLLBACK, SAVE TRANSACTION). SELECT is sometimes called DQL.

Q: Why would a company keep data in SQL Server instead of Excel files? Concurrency, scale, data integrity (constraints, transactions), security and auditing, backup and recovery, and a single source of truth for reports and applications.

Practise more online

Free, trusted places to test yourself on this topic. Links open the original site in a new tab.