SQL FOR DATA ANALYSIS · LESSON 3 OF 20

Data Types, Operators, NULLs, Variables & Comments

Choose the right SQL Server data type for every column, use arithmetic, comparison, logical and string operators correctly, understand NULL and three-valued logic, declare variables, follow naming rules and write readable, commented SQL.

SQL class 2 · SQL Server 2022, 2026 · Beginner · 100 min

By the end of this lesson you can

- Pick suitable numeric, text, date/time and other data types, and know why the choice matters
- Use arithmetic, comparison, logical and concatenation operators, including integer division and modulo
- Explain NULL, three-valued logic, IS NULL and COALESCE
- Declare and use T-SQL variables with DECLARE, SET and SELECT
- Follow identifier naming rules and conventions, and comment code


Datasets used

`superstore_sales.csv`

Why data types matter

Every column has exactly one **data type**. The type decides what values are allowed, how much storage they use, how they sort and compare, and which functions work on them. A column of dates stored as text sorts "01-02-2026" before "31-01-2025" and cannot be used for date arithmetic, the same problem you met in Excel.

SQL Server data types



The main families of SQL Server data types.

Numbers

Type	Range / precision	Storage	Use for
`TINYINT`	0 to 255	1 byte	Ratings, small codes
`SMALLINT`	−32,768 to 32,767	2 bytes	Small counts
`INT`	about ±2.1 billion	4 bytes	IDs, quantities (default choice)
`BIGINT`	about ±9.2 × 10^{18}	8 bytes	Very large IDs, event logs
`DECIMAL(p, s)` / `NUMERIC`	exact, p digits with s after the point	5–17 bytes	**Money**, rates: `DECIMAL(12,2)` holds up to 9,999,999,999.99
`MONEY`	exact, 4 decimals	8 bytes	Currency (DECIMAL is more portable)
`FLOAT`, `REAL`	**approximate** binary floating point	8 / 4 bytes	Scientific measurements, ML scores
`BIT`	0, 1 or NULL	1 bit	Yes/No flags

WATCH OUT **Never store money in FLOAT**

`FLOAT` cannot represent many decimal fractions exactly (0.1 + 0.2 is not exactly 0.3), so totals drift by tiny amounts. Use `DECIMAL(p, s)` for currency.

Text

Type	Description	Example
`CHAR(n)`	Fixed length, padded with spaces	`CHAR(2)` for state codes `MH`
`VARCHAR(n)`	Variable length, up to n bytes (n ≤ 8000)	`VARCHAR(100)` for names in English
`NVARCHAR(n)`	Variable length **Unicode** (Hindi, Tamil, emoji)	`NVARCHAR(100)` for names in any language
`VARCHAR(MAX)`, `NVARCHAR(MAX)`	Up to 2 GB	Long descriptions, JSON

Prefix Unicode string literals with `N`: `N'नमस्ते'`. Without `N`, non-Latin characters can turn into `?`.

Dates and times

Type	Stores	Example
`DATE`	Date only	`2026-04-27`
`TIME`	Time only	`14:30:00`
`DATETIME2(p)`	Date + time, precise (preferred)	`2026-04-27 14:30:15.1234567`
`DATETIME`	Older date + time (3.33 ms precision)	Legacy tables
`DATETIMEOFFSET`	Date + time + time zone	`2026-04-27 14:30 +05:30`
`SMALLDATETIME`	Date + time to the minute	Low-precision logs

Always write date literals in the unambiguous **ISO format** `'YYYY-MM-DD'` (`'2026-04-27'`). `'04/05/2026'` means April 5 or May 4 depending on the server's language settings.

Others

`UNIQUEIDENTIFIER` (GUIDs), `VARBINARY` (files, images), `XML`, JSON stored in `NVARCHAR(MAX)` with JSON functions, `GEOGRAPHY` (maps), and from SQL Server 2025 a native `VECTOR` type for AI embeddings.

Choosing types for the retail tables

Column	Good type	Why
`customer_id`	`VARCHAR(10)`	Codes like C0001 keep leading letters/zeros
`customer_name`	`NVARCHAR(100)`	Names in any language
`order_date`	`DATE`	No time needed
`quantity`	`INT` (or `SMALLINT`)	Whole numbers
`discount`	`DECIMAL(4,2)`	0.00 to 0.99 exactly
`sales`, `profit`	`DECIMAL(12,2)`	Money
`is_returned`	`BIT`	Yes/No

Here are the types DuckDB inferred when loading the CSV (SSMS's Import Flat File wizard does the same kind of guessing; always review its suggestions):

OUTPUT

	column_name	column_type
0	row_id	BIGINT
1	order_id	VARCHAR
2	order_date	DATE
3	ship_date	DATE
4	ship_mode	VARCHAR
5	customer_id	VARCHAR
6	customer_name	VARCHAR
7	segment	VARCHAR
8	city	VARCHAR
9	state	VARCHAR
10	region	VARCHAR
11	product_id	VARCHAR

19 rows × 2 columns (first 12 shown)

Operators

Arithmetic

Operator	Meaning	Example	Result in SQL Server
+	Add	`SELECT 7 + 2`	9
-	Subtract	`SELECT 7 - 2`	5
*	Multiply	`SELECT 7 * 2`	14
/	Divide	`SELECT 7 / 2`	**3** (integer ÷ integer = integer)
/	Divide	`SELECT 7 / 2.0`	3.500000
%	Modulo (remainder)	`SELECT 7 % 2`	1

COMMON MISTAKES

Integer division

In SQL Server, dividing two integers drops the decimals: `SELECT 1/3` returns 0, and `COUNT(...)/COUNT(...)` returns 0 or 1 instead of a percentage. Multiply by `1.0` or `CAST` one side: `SELECT 100.0 * returned / total` or `CAST(returned AS DECIMAL(10,2)) / total`. (PostgreSQL behaves the same way; MySQL and DuckDB return decimals.)

Calculated columns are written right in the SELECT list. Here is unit price and margin for a few order lines:

SQL

```sql
SELECT TOP 6
       order_id,
       quantity,
       sales,
       profit,
       ROUND(sales / quantity, 2)          AS unit_price,
       ROUND(100.0 * profit / sales, 1)    AS margin_pct
FROM superstore
ORDER BY row_id;
```

RESULT

order_id	quantity	sales	profit	unit_price	margin_pct
IN-2023-00001	2	36,000	3,472.55	18,000	9.6
IN-2023-00001	1	3,850	1,169.54	3,850	30.4
IN-2023-00001	4	62,080	6,044.47	15,520	9.7
IN-2023-00002	2	5,216	450.16	2,608	8.6
IN-2023-00003	3	24,591	-5,512.33	8,197	-22.4
IN-2023-00003	1	8,288	-1,598.43	8,288	-19.3

6 rows × 6 columns

Comparison

Operator	Meaning
=	Equal
<> or ≠	Not equal
> < ≥ ≤	Greater / less (than or equal)
BETWEEN a AND b	Inclusive range
IN (…)	Matches any value in a list
LIKE	Pattern match with % and _
IS NULL / IS NOT NULL	Tests for missing values

Logical

AND (both true), OR (at least one true), NOT (reverses). **Precedence**: NOT first, then AND, then OR. Use brackets to make intent obvious.

SQL

```sql
-- Without brackets, AND is evaluated first:
SELECT COUNT(*) AS rows_without_brackets
FROM superstore
WHERE region = 'North' OR region = 'South' AND category = 'Technology';
```

RESULT

rows_without_brackets
2025

1 rows × 1 columns

SQL

```
-- With brackets: (North or South) and Technology
SELECT COUNT(*) AS rows_with_brackets
FROM superstore
WHERE (region = 'North' OR region = 'South') AND category = 'Technology';
```

RESULT

rows_with_brackets
952

1 rows × 1 columns

The first query returns all North rows plus South Technology rows: probably not what was meant. Brackets fix it.

String concatenation

Method	Example	NULL behaviour
+	first_name + ' ' + last_name	Any NULL makes the whole result NULL
CONCAT()	CONCAT(first_name, ' ', last_name)	Treats NULL as empty text
CONCAT_WS()	CONCAT_WS(', ', city, state, 'India')	Separator; skips NULLs

SQL

```
SELECT TOP 4 customer_name,
       CONCAT(city, ', ', state)           AS city_state,
       CONCAT_WS(' | ', segment, region)   AS segment_region
FROM customers;
```

RESULT

customer_name	city_state	segment_region
Saanvi Khan	Chandigarh, Punjab	Corporate | North
Meera Bose	Delhi, Delhi	Corporate | North
Riya Shah	Kolkata, West Bengal	Consumer | East
Diya Fernandes	Indore, Madhya Pradesh	Corporate | West

4 rows × 3 columns

NULL: the missing value

`NULL` means **unknown or missing**. It is not zero and not an empty string. Any comparison with NULL returns **UNKNOWN**, not TRUE or FALSE. SQL uses **three-valued logic**:

Expression	Result
`NULL = NULL`	UNKNOWN
`NULL <> 5`	UNKNOWN
`5 + NULL`	NULL
`TRUE AND UNKNOWN`	UNKNOWN
`FALSE AND UNKNOWN`	FALSE
`TRUE OR UNKNOWN`	TRUE
`NOT UNKNOWN`	UNKNOWN

AND

	TRUE	FALSE	UNKNOWN
TRUE	TRUE	FALSE	UNKNOWN
FALSE	FALSE	FALSE	FALSE
UNKNOWN	UNKNOWN	FALSE	UNKNOWN

OR

	TRUE	FALSE	UNKNOWN
TRUE	TRUE	TRUE	TRUE
FALSE	TRUE	FALSE	UNKNOWN
UNKNOWN	TRUE	UNKNOWN	UNKNOWN

Three-valued logic. Any comparison involving NULL is UNKNOWN; WHERE keeps only TRUE rows.

`WHERE` keeps only rows where the condition is TRUE, so rows where it is UNKNOWN disappear silently. That is why you must test with `IS NULL`:

SQL

```sql
WITH t AS (
    SELECT 'A' AS item, 10 AS score UNION ALL
    SELECT 'B', NULL UNION ALL
    SELECT 'C', 30
)
SELECT
    (SELECT COUNT(*) FROM t WHERE score = NULL)   AS equals_null_rows,     -- always 0!
    (SELECT COUNT(*) FROM t WHERE score IS NULL)  AS is_null_rows,
    (SELECT COUNT(score) FROM t)                  AS count_score,          -- ignores NULL
    (SELECT COUNT(*) FROM t)                      AS count_star,
    (SELECT AVG(score * 1.0) FROM t)              AS avg_ignores_null,     -- (10+30)/2
    (SELECT AVG(COALESCE(score, 0) * 1.0) FROM t) AS avg_null_as_zero;     -- (10+0+30)/3
```

RESULT

equals_null_rows	is_null_rows	count_score	count_star	avg_ignores_null	avg_null_as_
0	1	2	3	20	13.33

1 rows × 6 columns

Function	What it does
`ISNULL(x, y)`	T-SQL: return y when x is NULL
`COALESCE(x, y, z, …)`	ANSI: the first non-NULL value; works in every database
`NULLIF(a, b)`	NULL if a = b, otherwise a. Classic use: `sales / NULLIF(qty, 0)` avoids divide-by-zero errors

Variables in T-SQL

T-SQL lets you store a value in a variable for the length of a batch. Variable names start with `@`.

```SQL
DECLARE @target_region VARCHAR(20) = 'West';     -- declare and assign
DECLARE @min_sales     DECIMAL(12,2);
SET @min_sales = 50000;                           -- assign with SET

SELECT order_id, city, sales
FROM superstore
WHERE region = @target_region AND sales ⩾ @min_sales;

DECLARE @total DECIMAL(14,2);
SELECT @total = SUM(sales) FROM superstore;       -- assign from a query
PRINT CONCAT('Total sales: ', @total);            -- message in the Messages tab
```

Variables make scripts reusable (change `'West'` once) and are the basis of stored procedures (Lesson 13). Other databases use different syntax (PostgreSQL `DO` blocks or `\set` in psql).

Identifiers: naming rules and conventions

Rules (SQL Server): - Start with a letter, _, @ (variables) or # (temporary tables). - Up to 128 characters; letters, digits, _, @, $, #. - Reserved words (`ORDER`, `GROUP`, `USER`) and names with spaces must be wrapped in `[square brackets]` (or `"double quotes"`): `[Order Details]`, `[order]`.

Conventions used in this handbook (pick one style and be consistent): - `snake_case`, lowercase table and column names: `order_items`, `customer_id`. - Plural table names (`customers`) or singular (`customer`): be consistent. - Primary key `id` or `<table>_id`; foreign keys named after the referenced key (`customer_id`). - Prefix views `vw_`, procedures `usp_`, indexes `ix_`. - Avoid spaces, special characters and reserved words, so you never need brackets.

Comments and formatting

```SQL
-- A single-line comment: everything after -- is ignored

/* A multi-line comment:
   Purpose : Top 10 customers by 2025 sales
   Author  : Varun Kumar
   Updated : 27-Apr-2026                          */

SELECT TOP 10
       customer_id,
       SUM(sales) AS total_sales          -- revenue in rupees
FROM   superstore
WHERE  order_date ⩾ '2025-01-01'
  AND  order_date <  '2026-01-01'         -- half-open range: safe with times
GROUP  BY customer_id
ORDER  BY total_sales DESC;
```

TIP **Readable SQL checklist**

One clause per line (`SELECT`, `FROM`, `WHERE`...), one column per line in long queries, consistent indentation, keywords in capitals, meaningful aliases, and a header comment explaining the purpose. Tools such as the "Format SQL" extension or SQLFluff format code automatically.

Summary

KEY TAKEAWAYS

- Choose types deliberately: `INT` for IDs and counts, `DECIMAL(p,s)` for money, `NVARCHAR` for names, `DATE`/`DATETIME2` for dates; never `FLOAT` for money.
- Write dates as `'YYYY-MM-DD'`.
- `7/2 = 3` in SQL Server: use `1.0 *` or `CAST` for decimal division; `%` gives the remainder.
- Precedence: NOT, AND, OR; use brackets.
- `NULL` is unknown: compare with `IS NULL`; aggregates ignore NULLs; `COALESCE`, `ISNULL` and `NULLIF` handle them.
- `CONCAT` treats NULL as empty; `+` with a NULL returns NULL.
- Variables: `DECLARE @x type = value`; name things consistently and comment your code.

Quick quiz

6 questions · tap an answer to check it

1. Which data type should store a product price in rupees and paise?

A FLOAT

B INT

C DECIMAL(10,2)

D VARCHAR(10)

Answer: C. DECIMAL stores exact decimal values, which money needs.

2. In SQL Server, what does `SELECT 9 / 4` return?

A 2

B 2.25

C 2.0

D 3

Answer: A. Integer divided by integer gives an integer (the fraction is dropped).

3. What does `WHERE discount = NULL` return?

A Rows where discount is missing

B No rows

C All rows

D An error

Answer: B. Comparisons with NULL are UNKNOWN, so WHERE keeps nothing. Use IS NULL.

4. Which expression returns 'Pune' when city is NULL?

A `city + 'Pune'`

B `COALESCE(city, 'Pune')`

C `NULLIF(city, 'Pune')`

D `city = 'Pune'`

Answer: B. COALESCE returns the first non-NULL value.

5. `WHERE a = 1 OR b = 2 AND c = 3` **is evaluated as:**

A `(a = 1 OR b = 2) AND c = 3`

B `a = 1 OR (b = 2 AND c = 3)`

C Left to right with equal precedence

D An error

Answer: B. AND has higher precedence than OR.

6. Why use NVARCHAR instead of VARCHAR for customer names?

A It is faster

B It stores Unicode characters such as Devanagari or Tamil correctly

C It allows numbers

D It is required for primary keys

Answer: B. NVARCHAR stores Unicode text; VARCHAR may lose characters outside the code page.

EXERCISE **Fix the query**

A colleague wrote: `SELECT order_id, profit/sales*100 AS margin FROM superstore WHERE category = 'Furniture' OR category = 'Technology' AND discount > 0.2 AND ship_mode = NULL;` List every problem and rewrite it.

Show solution (worked answer)

1. `AND` binds before `OR`, so the discount and ship-mode filters apply only to Technology: add brackets.
2. `ship_mode = NULL` never matches: use `IS NULL` (or remove it if not needed).
3. If profit and sales were integers, `profit/sales` would be integer division; use `100.0 * profit / sales` and guard against zero with `NULLIF(sales, 0)`. Rewritten: `SELECT order_id, ROUND(100.0 * profit / NULLIF(sales, 0), 1) AS margin_pct FROM superstore WHERE category IN ('Furniture', 'Technology') AND discount > 0.2;`

INTERVIEW CORNER **Questions you may be asked**

Q: What is the difference between CHAR, VARCHAR and NVARCHAR? CHAR is fixed length (padded), VARCHAR is variable length non-Unicode, NVARCHAR is variable length Unicode (two bytes per character for most scripts).

Q: How does SQL treat NULL? As unknown: comparisons return UNKNOWN, aggregates (except COUNT(*)) ignore NULLs, arithmetic with NULL returns NULL. Use IS NULL, COALESCE/ISNULL and NULLIF.

Q: Why does `SELECT 100 * returned / total` give 0? Integer division when both values are integers; cast to decimal or multiply by 100.0.

Q: DECIMAL vs FLOAT? DECIMAL is exact (money, rates); FLOAT is approximate binary (scientific values) and can introduce rounding errors.

Practise more online

Free, trusted places to test yourself on this topic. Links open the original site in a new tab.