AI & NO-CODE TOOLS LAB · LESSON 2 OF 3

n8n Complete Tutorial: Workflow Automation, Data Pipelines and AI Agents

Learn n8n, the open, self-hostable workflow-automation tool. Set it up on n8n Cloud or Docker, understand triggers, nodes, credentials, items and expressions, transform data with Edit Fields, IF, Switch, Merge, Loop and Code nodes, call any API with HTTP Request, handle errors and schedules, build AI agents with chat models, memory, tools and vector stores, and connect n8n to MCP. Four complete projects: lead capture, a daily sales report, an email-triage AI agent and a document Q&A bot.

✦ n8n 1.x (2026) | Beginner to Advanced | ⏱ 180 min

By the end of this lesson you can

- Install or sign up for n8n and build, test and activate a workflow
- Explain triggers, nodes, items and expressions, and transform data between apps
- Call REST APIs with HTTP Request and write JavaScript or Python in the Code node
- Add error handling, retries, schedules and webhooks for reliable automations
- Build AI-agent workflows with chat models, memory, tools, vector stores and MCP

What n8n is


n8n ("n-eight-n", from *nodemation*) connects apps and data with visual workflows. Each workflow starts with a **trigger** (a form is submitted, a schedule fires, a webhook is called) and passes data through **nodes** that read, transform and send it. Compared with Zapier and Make, n8n can be **self-hosted** (your data stays on your server), lets you write **code** in any step, and has strong **AI-agent** nodes.

	Zapier	Make	n8n
Hosting	Cloud only	Cloud only	Cloud **or self-hosted** (Docker, npm)
Pricing unit	Tasks (each step)	Operations	Workflow executions (cloud); free to self-host under its fair-code licence
Code	Code steps (limited)	Limited	Full JavaScript/Python Code node, npm packages when self-hosted
Best for	Quick app-to-app zaps	Visual scenarios with routers	Data pipelines, AI agents, privacy-sensitive automations

Getting n8n

Option	How
n8n Cloud	Sign up at n8n.io → free trial → you get `yourname.app.n8n.cloud`
Docker (recommended self-host)	`docker volume create n8n_data` then `docker run -it --rm -p 5678:5678 -v n8n_data:/home/node/.n8n docker.n8n.io/n8nio/n8n` and open http://localhost:5678
npm (quick local test)	`npx n8n` (needs Node.js)
Production self-host	Docker Compose with PostgreSQL, a domain with HTTPS (Caddy/Nginx), `N8N_ENCRYPTION_KEY` set and backed up, queue mode with Redis for scale

The editor and the core ideas



An n8n workflow: a trigger, then nodes that pass items from left to right.

Concept	Meaning
Workflow	The canvas of connected nodes; *Active* workflows run on their trigger
Trigger node	Starts the run: Manual, Schedule, Webhook, n8n Form, Chat, app triggers (Gmail, Google Sheets, Typeform, Stripe…)
Node	One step: an app action, a core utility, or an AI node
Credentials	Saved, encrypted logins/API keys (OAuth for Google, Slack, etc.), reused by nodes
Items	Data flows as a list of JSON items; most nodes run once **per item**
Expressions	`{{ $json.email }}`, `{{ $now.toFormat('yyyy-MM-dd') }}`, `{{ $('Form').item.json.name }}` to use data from earlier nodes
Executions	History of every run with the input/output of each node, for debugging and re-running

Items: the most important idea

Every node receives and outputs an **array of items**, each `{ "json": { … } }`. If a Google Sheets node returns 25 rows, the next Slack node runs **25 times**, once per item, unless you aggregate first.

Python

```python
import json
items = [{"json": {"name": "Asha", "email": "asha@example.com", "city": "Pune", "score": 82}},
         {"json": {"name": "Ravi", "email": "ravi@example.com", "city": "Delhi", "score": 45}},
         {"json": {"name": "Meera", "email": "meera@example.com", "city": "Pune", "score": 91}}]
# IF node: score ⩾ 60 goes to the "true" branch
true_branch = [i for i in items if i["json"]["score"] ⩾ 60]
# Edit Fields (Set) node: keep and add fields
shaped = [{"json": {"lead": i["json"]["name"], "email": i["json"]["email"], "priority": "hot" if i["json"]["score"] ⩾ 90 else "warm"}} for i in true_branch]
# Aggregate node: many items → one item with a list
aggregated = {"json": {"leads": [s["json"]["lead"] for s in shaped], "count": len(shaped)}}
print(json.dumps(shaped, indent=1)); print(aggregated)
```

OUTPUT

```
[
 {
  "json": {
   "lead": "Asha",
   "email": "asha@example.com",
   "priority": "warm"
  }
```

```
 },
 {
  "json": {
   "lead": "Meera",
   "email": "meera@example.com",
   "priority": "hot"
  }
 }
]
{'json': {'leads': ['Asha', 'Meera'], 'count': 2}}
```

Core nodes you will use every day

Node	Use
Edit Fields (Set)	Rename, add, remove or compute fields
IF / **Switch**	Route items by conditions (two branches / many branches)
Merge	Combine two inputs: append, match by a field (like a join), or by position
Filter	Drop items that do not match
Split Out	Turn a list inside one item into separate items
Aggregate / **Summarize**	Many items → one (list, sum, count, group by)
Loop Over Items (Split in Batches)	Process items in batches (APIs with rate limits)
Wait	Pause for a time or until a webhook/form resumes the run
HTTP Request	Call any REST API (GET/POST, headers, auth, pagination); import a cURL command
Code	JavaScript or Python over all items or each item
Date & Time, **Crypto**, **XML/HTML**, **Extract From File**, **Convert to File**	Utilities
Execute Workflow / **Execute Workflow Trigger**	Call one workflow from another (sub-workflows, reusable steps)
Respond to Webhook	Return a custom HTTP response (build simple APIs)

Code node example (JavaScript, "Run once for all items")

JAVASCRIPT

```
// Clean phone numbers and drop duplicates by email
const seen = new Set();
return $input.all()
  .filter(item => { const e = item.json.email.toLowerCase().trim(); if (seen.has(e)) return
false; seen.add(e); return true; })
  .map(item => ({ json: { ...item.json, phone: String(item.json.phone || '').replace(/\D/g,
'').slice(-10) } }));
```

The Python version of the same idea (Code node → Language: Python) uses `_input.all()` and returns a list of dicts with a `json` key.

HTTP Request: calling an API

Python

```
# What an HTTP Request node sends and how you map the answer back into items
request = {"method": "GET", "url": "https://api.example.com/v1/orders", "qs": {"status":
"paid", "limit": 2},
           "headers": {"Authorization": "Bearer {{ $credentials.apiKey }}"}}
response = {"data": [{"id": 101, "amount": 2499, "city": "Pune"}, {"id": 102, "amount":
899, "city": "Delhi"}], "next": None}
items = [{"json": o} for o in response["data"]]          # Split Out on "data"
print(request["method"], request["url"], request["qs"]); print(items)
```

OUTPUT

```
GET https://api.example.com/v1/orders {'status': 'paid', 'limit': 2}
[{'json': {'id': 101, 'amount': 2499, 'city': 'Pune'}}, {'json': {'id': 102,
'amount': 899, 'city': 'Delhi'}}]
```

Tips: use **Authentication → Predefined credential type** when n8n has the app, otherwise **Generic credential** (header auth, OAuth2); turn on **Pagination** for APIs with `next` links; add **Retry on fail** (Settings) for flaky APIs.


Reliability: errors, retries and scheduling

- **Settings per node**: *Retry on fail* (tries and wait), *Continue on fail* / error output branch, *Always output data*.
- **Error workflow**: Workflow settings → Error workflow → pick a workflow that starts with **Error Trigger** and sends you a Slack/WhatsApp/email alert with the failed node and message.

- **Schedule Trigger**: every X minutes, daily at 09:00 IST (set the workflow time zone to Asia/Kolkata), or a cron expression `0 9 * * 1-5`.
- **Pin data** while building: freeze a node's output so you do not call the API on every test.
- **Environment safety**: keep secrets in credentials, never in Code nodes; restrict who can edit workflows; use separate dev and prod instances for important flows.

AI agents in n8n

The **AI Agent** node runs a loop: a chat model reads the goal, decides which **tool** to call, reads the result and continues until it can answer.



An n8n AI agent and the sub-nodes plugged into it.

Other AI building blocks: **Basic LLM Chain**, **Text Classifier**, **Information Extractor** (pull fields from emails or PDFs into JSON), **Summarization Chain**, **Sentiment Analysis**, **Embeddings** + **Vector Store** nodes (Pinecone, Qdrant, Supabase, PGVector, in-memory) for RAG, and the **Chat Trigger** for a hosted chat window.

n8n and MCP

- **MCP Client Tool**: lets an n8n agent use tools from any MCP server.
- **MCP Server Trigger**: exposes your n8n workflows as MCP tools, so Claude or other MCP clients can call them (for example "create a lead in our CRM").

Four complete projects

1. Lead capture to Google Sheets and Slack

`n8n Form Trigger` (name, email, phone, course) → `Edit Fields` (clean phone, add timestamp) → `Google Sheets: Append row` → `IF course = "Data Engineer"` → `Slack: send message to #sales` (true) / `Gmail: send brochure` (false).

2. Daily sales report

`Schedule Trigger 09:00 IST` → `Postgres/HTTP Request: yesterday's orders` → `Summarize: sum sales by region` → `Code: build an HTML table` → `Gmail: send to managers` + `Slack` summary.

Python

```
import pandas as pd
orders = pd.DataFrame({"region": ["South", "West", "South", "North", "East", "West"],
"amount": [24990, 8999, 15500, 4300, 12000, 30500]})
summary = orders.groupby("region").amount.agg(["count", "sum"]).sort_values("sum",
ascending=False)
html = summary.to_html()            # the Code node builds the same table for the email
body
print(summary); print("HTML length for the email:", len(html), "characters")
```

OUTPUT

```
        count    sum
region
South       2  40490
West        2  39499
East        1  12000
North       1   4300
HTML length for the email: 571 characters
```

3. Email triage AI agent

`Gmail Trigger (new email)` → `Text Classifier` (Sales lead / Support / Invoice / Spam) → `Switch` → Sales: `Information Extractor` (name, company, budget) → `HubSpot/Sheets` + Slack ping; Support: `AI Agent` drafts a reply using a **Vector Store tool** over your FAQ and saves it as a **Gmail draft** for a human to send; Spam: archive.

4. Document Q&A bot (RAG)

Indexing workflow: `Google Drive Trigger (new PDF)` → `Default Data Loader` + `Recursive Text Splitter` → `Embeddings` → `Vector Store: insert`. Chat workflow: `Chat Trigger` → `AI Agent` with the vector store as a tool, a chat model and window memory → answer with sources. This is the RAG pattern from the GenAI track, built without code.

Summary

KEY TAKEAWAYS

- Workflows = trigger + nodes; data moves as a list of JSON items and most nodes run once per item.
- Expressions pull values from earlier nodes; Code and HTTP Request cover anything without a ready node.
- Reliability comes from retries, error branches, an error workflow, schedules with the right time zone and pinned test data.
- The AI Agent node combines a chat model, memory and tools; vector stores add RAG; MCP connects n8n to other AI tools both ways.

Quick quiz

6 questions · tap an answer to check it

1. A Google Sheets node returns 30 rows and a Slack node follows. What happens?

A The Slack node runs 30 times, once per item, unless you aggregate first

B It runs once with all rows

C It fails

D It runs twice

Answer: A. Most nodes execute per item.

2. Which expression reads the email field of the current item?

A {{ $json.email }}

B $email

C =email

D {email}

Answer: A. $json is the current item's data.

3. Which node calls any REST API that has no ready-made n8n node?

A HTTP Request

B Merge

C Wait

D Filter

Answer: A. You can also import a cURL command into it.

4. How do you get alerted when a production workflow fails?

A Set an Error workflow that starts with Error Trigger and sends a message

B Check executions every morning

C Use Pin data

D Disable retries

Answer: A. The error workflow runs whenever another workflow fails.

5. What is the main reason teams self-host n8n?

A Data stays on their own servers and code/npm packages are allowed

B It has no editor

C It only works offline

D Self-hosting is required

Answer: A. Cloud is easier; self-hosting gives control.

6. Which sub-nodes plug into an AI Agent node?

A A chat model, memory, tools and an optional output parser

B Only a Schedule Trigger

C Only a Merge node

D Only credentials

Answer: A. Tools can include HTTP, Sheets, other workflows and MCP.

EXERCISE **Build it**

Build project 1 (form → Sheets → Slack/Gmail) and add an error workflow that messages you on failure. Then extend it: use an Information Extractor to pull "experience in years" from a free-text field and route experienced leads to a different Slack channel.

Show solution (worked answer)

Form Trigger fields: name, email, phone, course, about_you. Edit Fields: `phone = {{ $json.phone.replace(/\D/g, '').slice(-10) }}`, `received = {{ $now.toISO() }}`. Information Extractor schema `{ "experience_years": number }` from `about_you`, then IF experience_years ≥ 3 → #senior-leads else #leads. Workflow settings → Error workflow → a workflow with Error Trigger → Slack "Workflow {{ $json.workflow.name }} failed at {{ $json.execution.lastNodeExecuted }}".

INTERVIEW CORNER **Questions you may be asked**

Q: n8n vs Zapier vs Make? Zapier is the simplest for app-to-app automations; Make adds visual branching and data mapping; n8n adds self-hosting, full code steps, sub-workflows and strong AI-agent features, which suits data and AI teams.

Q: How do you make an automation reliable? Retries with backoff, error branches and an error workflow with alerts, idempotent steps (check before creating), rate-limit batching, logging executions, separate test and production, and secrets in credentials.

Q: How would you build a support bot on company documents in n8n? An indexing workflow that loads documents, splits them, embeds them and stores them in a vector store; a chat workflow with Chat Trigger, an AI Agent with a chat model, memory and the vector store as a retrieval tool, with sources in answers and a human-handover path.

Learn more (official and free)

- n8n documentation
- n8n free courses, Level 1 and Level 2
- n8n workflow templates (thousands of ready examples)
- n8n community forum
- Advanced AI in n8n (agents, RAG, MCP)

Practise more online

Free, trusted places to test yourself on this topic. Links open the original site in a new tab.