AI FOR DATA ANALYSIS · LESSON 2 OF 4

AI with SQL: Text-to-SQL, Docker, Metabase & MinusX

Use AI to write, explain and debug SQL safely. Learn how text-to-SQL works and where it fails, give the model the right schema, protect your database with read-only access, install Docker, run Metabase on your own data, connect an AI assistant such as MinusX, and validate every generated query.

DVA with AI · class 2 | ✦ Docker, Metabase and AI assistants, 2026 | Intermediate | ⏱ 130 min

By the end of this lesson you can

- Explain how text-to-SQL works and why context (schema, definitions, examples) decides quality
- Write a schema-aware prompt and review generated SQL for the usual errors
- Install Docker and run Metabase locally; connect a database; build questions, models and dashboards
- Describe how an in-browser AI assistant such as MinusX works with Metabase, and its privacy trade-offs
- Apply guardrails: read-only roles, row limits, query review and result validation

Datasets used

`superstore_sales.csv` `customers.csv` `products.csv`

What is text-to-SQL?

Text-to-SQL turns a business question in plain language into a SQL query: "Which region had the highest profit in 2025?" → `SELECT region, SUM(profit) …`. LLMs are good at SQL syntax, but **correct SQL for *your* database** needs your context.



Text-to-SQL pipeline. Quality depends mostly on the context you supply, not on the model alone.

What goes wrong without context

Problem	Example	Prevention
Wrong tables/columns	Uses `customer_name` in `orders`, where it does not exist	Provide the schema (tables, columns, types, keys)
Wrong grain / fan-out	Joins orders to items and then `COUNT(*)` for "orders"	State the grain: "one row per order line"; add "count distinct order_id" rule
Wrong definitions	"Active customer", "net sales", "this year"	Provide a metric dictionary
Dialect mismatch	`LIMIT` instead of `TOP` in SQL Server	Name the database and version
Dates	Uses `YEAR(date) = 2025` (slow) or the wrong fiscal year	State calendar vs fiscal year and preferred patterns
Hallucinated values	`WHERE region = 'Northern'` when data says `North`	Provide sample values for categorical columns
Unsafe actions	`DELETE` / `DROP` suggestions	Read-only connection; review before running

A schema prompt that works

```text
You are a senior analytics engineer. Write SQL for Microsoft SQL Server 2022.

SCHEMA (all in dbo):
customers(customer_id PK, customer_name, segment, city, state, region)
  - segment in ('Consumer','Corporate','Home Office'); region in
('North','South','East','West')
orders(order_id PK, order_date DATE, ship_date DATE, ship_mode, customer_id FK →
customers)
order_items(item_id PK, order_id FK → orders, product_id FK → products, quantity,
discount, sales, profit)
  - one row per product line; sales and profit in rupees
products(product_id PK, product_name, category, sub_category, list_price)

DEFINITIONS:
- "Orders" = COUNT(DISTINCT orders.order_id). "Margin %" = SUM(profit) / SUM(sales).
- Financial year runs April-March. Use half-open date ranges (≥ start AND < next start).

QUESTION: For FY2025 (Apr 2025-Mar 2026), show margin % by category and by discount band
(0, 1-20%, >20%).

RULES: Return only SQL; add comments; no SELECT *; list any assumptions after the query.
```

Notice the pieces: dialect, schema with keys, valid values, grain, definitions, date convention and output rules. This is the difference between a lucky answer and a reliable one.

> **TIP** **Keep a reusable "context file"**
>
> Save your schema, definitions and sample queries in one text file (or in an AI **Project** / custom instructions). Paste it into every session. Many BI tools (Metabase, Power BI Copilot, Snowflake Cortex, Looker) call this a **semantic layer** or "AI context": descriptions, synonyms and verified queries.

Reviewing AI-generated SQL: a checklist

1. **Does every table/column exist?** (Run it; fix any "invalid column name".)
2. **Is the grain right?** After each join, did rows multiply? Are distinct counts used for orders and customers?
3. **Are filters correct?** Date ranges half-open? Status filters? NULL handling?
4. **Do aggregates match the definition?** `SUM(profit)/SUM(sales)` not `AVG(margin)`.
5. **Does the total reconcile?** Compare with a simple query: `SELECT SUM(sales) FROM order_items`.

6. **Is it safe and cheap?** No writes; a `TOP` / `LIMIT` while testing; no accidental cross join.
7. **Is it readable?** CTEs, aliases and comments you could explain in an interview.

Let's see this in practice. A typical AI answer to "profit margin by discount band" that forgets `SUM(profit)/SUM(sales)` and averages row margins instead:

SQL

```sql
SELECT CASE WHEN discount = 0 THEN '0%' WHEN discount ⩽ 0.2 THEN '1-20%' ELSE '>20%' END
AS discount_band,
       ROUND(AVG(profit / sales) * 100, 1) AS ai_margin_pct          -- average of row
margins (unweighted)
FROM order_items
GROUP BY CASE WHEN discount = 0 THEN '0%' WHEN discount ⩽ 0.2 THEN '1-20%' ELSE '>20%' END
ORDER BY discount_band;
```

RESULT

discount_band	ai_margin_pct
0%	18.2
1–20%	2.0
>20%	-20.5

3 rows × 2 columns

SQL

```sql
SELECT CASE WHEN discount = 0 THEN '0%' WHEN discount ⩽ 0.2 THEN '1-20%' ELSE '>20%' END
AS discount_band,
       ROUND(100.0 * SUM(profit) / SUM(sales), 1) AS correct_margin_pct     -- weighted:
total profit / total sales
FROM order_items
GROUP BY CASE WHEN discount = 0 THEN '0%' WHEN discount ⩽ 0.2 THEN '1-20%' ELSE '>20%' END
ORDER BY discount_band;
```

RESULT

discount_band	correct_margin_pct
0%	17.5
1–20%	1.2
>20%	-20.6

3 rows × 2 columns


The two queries differ in every band (18.2% vs 17.5% and 2.0% vs 1.2% for the first two) because large order lines matter more in the weighted version than small ones. Which one the business wants must be written in the **definitions** part of your prompt. The checklist question "does the aggregate match the definition?" catches this.

Guardrails for letting AI near a database

Guardrail	How
Read-only login	Create a database user with `SELECT` only on approved views (`GRANT SELECT ON …`); never give AI tools `db_owner`
Expose views, not raw tables	A `vw_sales_for_ai` view with clean names, no personal data columns
Row and time limits	Timeouts, `TOP 1000`, query cost limits
Masking	Hide phone, email, ID columns; use dynamic data masking
Human review	Show the SQL before running it; log queries
Verified questions	Keep a library of approved queries for key metrics
No secrets in prompts	Connection strings and passwords stay in the tool's secret store

Docker: running tools in containers

Docker packages an application and everything it needs into a **container**, so it runs the same on any machine. Instead of installing Java, a database and an app by hand, you run one command.



An image is a read-only template; a container is a running instance of it. Many containers can run from one image.

STEP BY STEP

Install Docker Desktop

1. Download **Docker Desktop** for Windows, Mac or Linux from the Docker website and install it. On Windows it uses **WSL 2** (Windows Subsystem for Linux); the installer enables it, and you may need to restart.
2. Start Docker Desktop and wait until it says "Engine running".
3. Open a terminal (PowerShell, Terminal) and check: `docker --version` and `docker run hello-world`.
4. Note your machine needs virtualisation enabled in BIOS and about 4 GB of free RAM for small tools.

Command	Meaning
`docker pull metabase/metabase:latest`	Download an image
`docker run -d -p 3000:3000 --name metabase metabase/metabase`	Run it in the background (`-d`), map port 3000, name it
`docker ps` / `docker ps -a`	List running / all containers
`docker logs -f metabase`	Follow its logs (see start-up progress)
`docker stop metabase` / `docker start metabase`	Stop / start again
`docker rm metabase`	Delete the container (not the image)
`docker images`	List downloaded images
`docker compose up -d`	Start everything defined in a `compose.yaml` file

Metabase: open-source BI for everyone

Metabase is an open-source business-intelligence tool: connect a database, ask questions with a point-and-click **question builder** (no SQL needed), or write SQL, then save charts into **dashboards**. It is popular in start-ups because non-technical colleagues can self-serve.

STEP BY STEP **Run Metabase and connect your data**

1. Start it: `docker run -d -p 3000:3000 --name metabase metabase/metabase`. First start takes a minute or two (check `docker logs -f metabase`).
2. Open **http://localhost:3000**, create the admin account, and choose **Add your data**.
3. Pick your database type (PostgreSQL, MySQL, SQL Server, BigQuery, Snowflake, SQLite files via drivers, CSV upload in newer versions), enter host, port, database name, username and password. **Use the read-only user.** If the database also runs on your PC, use the host `host.docker.internal` from inside the container.
4. Metabase scans the tables. Browse them under **Browse data**.
5. **New → Question**: choose a table, pick columns, add **Filter**, **Summarize** (`Sum of sales` by `region`), choose a visualisation, **Save**.
6. **New → Dashboard**: add saved questions, add filters (date, region) and connect them to the question fields.

For anything you want to keep, run Metabase with a proper application database instead of the default embedded one, and mount a volume, for example:

YAML

```yaml
# compose.yaml
services:
  metabase:
    image: metabase/metabase:latest
    ports: ["3000:3000"]
    environment:
      MB_DB_TYPE: postgres
      MB_DB_DBNAME: metabase
      MB_DB_PORT: 5432
      MB_DB_USER: metabase
      MB_DB_PASS: ${METABASE_DB_PASSWORD}      # from a .env file, never hard-coded
      MB_DB_HOST: postgres
    depends_on: [postgres]
  postgres:
    image: postgres:16
    environment:
      POSTGRES_USER: metabase
      POSTGRES_DB: metabase
      POSTGRES_PASSWORD: ${METABASE_DB_PASSWORD}
    volumes: ["pgdata:/var/lib/postgresql/data"]
volumes:
  pgdata:
```

Metabase concepts

Concept	Meaning
Question	A saved query (builder or SQL) with a visualisation
Model	A curated, cleaned table (a saved query with documented columns) for people to build on
Metric	A named, reusable calculation such as "Net revenue"
Dashboard	A page of questions with shared filters
Collection	Folders with permissions
Segment / filters	Reusable row filters
Permissions	Which groups see which databases and tables; row-level sandboxing (paid plans)
Metabot / AI features	Built-in AI assistance for questions and SQL in recent versions (availability depends on the edition and plan; check Metabase's current documentation)

Try it on the retail data: connect to your SQL Server `RetailDB`, then build three questions: *Sales by region*, *Monthly sales* (summarise by `order_date: Month`), and *Top 10 customers*. Then verify each one against this handbook's tables:

SQL

```
SELECT region, ROUND(SUM(sales), 0) AS sum_of_sales FROM superstore GROUP BY region ORDER BY sum_of_sales DESC;
```

RESULT

region	sum_of_sales
South	53,952,769
West	51,958,521
North	49,018,161
East	46,484,119

4 rows × 2 columns

MinusX: an AI assistant inside your BI tool

MinusX is an open-source AI assistant delivered as a **Chrome extension** that adds a chat sidebar to tools such as **Metabase** and **Jupyter notebooks**. Instead of copying your data into a chatbot, you work in Metabase and ask the sidebar things like *"Why did sales drop in March?"* or *"Write a query*

for monthly profit by category". According to its public description, it reads a simplified view of the page (metadata such as table and column names), then operates the tool by clicking, typing and writing queries, and lets you accept or reject its edits.

Aspect	How it behaves	What you should still do
Context	Sees the page, selected tables/columns and the query editor	Make sure the right database and tables are selected
Actions	Writes and runs SQL, edits questions, explains results	Read the SQL before accepting
Models	Supports several LLM providers (you may supply your own API key)	Check the provider's data policy
Privacy	Vendor says raw data is not sent; metadata and your prompts are	Verify the current policy; never expose sensitive tables
Cost	Free and paid plans; model API usage may cost	Check current pricing

STEP BY STEP

Using an AI assistant with Metabase

1. Install the Chrome extension from the Chrome Web Store (search "MinusX") and pin it; open your Metabase tab and open the sidebar.
2. Add your model/API key in settings if required.
3. Select the database/table in Metabase so the assistant knows the context.
4. Ask a precise question ("Monthly sales and profit by category for 2025, as a line chart; sales = SUM(sales), profit = SUM(profit)").
5. Review the generated SQL, run it, check totals against a simple query, then save it as a question.
6. Ask follow-ups: "Explain the biggest drop", "Break it down by region", "Why is Furniture negative?"

WATCH OUT

AI assistants and sensitive data

Anything the assistant can see, the model provider may receive. Use a **read-only role limited to non-sensitive views**, keep personal columns out of the connected schema, use an enterprise model agreement for company data, and keep a record of which prompts were run. If your company bans browser extensions that read pages, ask IT before installing any.

Other ways to use AI with SQL

Use	How
Explain a query	Paste the query (not the data) and ask for a line-by-line explanation and the business meaning
Optimise	Paste query + execution plan + table sizes; ask for rewrites and indexes; test each
Convert dialects	"Convert this SQL Server query to PostgreSQL; list functions that differ"
Generate test data	"Create INSERT statements for 20 fictional customers across four regions" (no real data)
Write documentation	Column descriptions, data dictionaries, comments
Data quality checks	"Write queries to find nulls, duplicates, orphans and out-of-range values for these tables"
Platform AI	Snowflake Cortex Analyst, BigQuery Gemini, Databricks Genie, SSMS Copilot, Azure Data Studio/VS Code Copilot, Fabric Copilot: all follow the same principle: context in, SQL out, you verify

2026 UPDATE **Trend: the semantic layer**

Teams that succeed with text-to-SQL do not rely on the raw schema: they define metrics (net sales, active customer) once in a **semantic layer** (dbt Semantic Layer, Cube, LookML, Power BI semantic models, Metabase models/metrics) and let AI query *that*. The AI then picks from governed metrics instead of reinventing definitions, which removes most wrong-number errors.

Summary

KEY TAKEAWAYS

- Text-to-SQL works when you provide **dialect, schema with keys, valid values, grain, metric definitions and date rules**.
- Review every query: columns exist, **grain** is right, filters correct, aggregates match the definition, totals reconcile, nothing writes.
- Protect the database with **read-only logins on curated views**, row limits and human review; never expose secrets or personal columns.
- **Docker** runs tools in containers (`docker run -d -p 3000:3000 metabase/metabase`); **Metabase** gives self-service questions, models and dashboards.
- An assistant such as **MinusX** adds an AI sidebar to Metabase; treat it as a fast junior analyst whose SQL you review, and check privacy terms.
- A governed **semantic layer** makes AI answers consistent.

Quick quiz

6 questions · tap an answer to check it

1. Why does giving the AI your schema and metric definitions improve results?

A It makes the model larger

B The model can use real table and column names and your definitions instead of guessing

C It speeds up the database

D It removes the need to review the SQL

Answer: B. Context is the main driver of text-to-SQL accuracy; review is still required.

2. Which command starts Metabase in a container on port 3000?

A `docker build metabase`

B `docker run -d -p 3000:3000 --name metabase metabase/metabase`

C `docker stop metabase`

D `metabase install`

Answer: B. `-d` runs detached and `-p 3000:3000` maps the port.

3. Which login is safest for an AI tool?

A The database owner

B A read-only user restricted to curated views

C The admin account

D An anonymous login

Answer: B. Least privilege limits damage if the AI makes a mistake.

4. A generated query averages `profit/sales` row by row to get a margin. Why is that risky?

A It is invalid SQL

B It is an unweighted average of ratios and may not match the business definition SUM(profit)/SUM(sales)

C It is slower

D It drops NULLs

Answer: B. Weighted vs unweighted aggregates differ; define the metric in the prompt.

5. What is a semantic layer?

A A type of chart

B A governed set of definitions for tables, metrics and relationships that BI and AI tools use

C A SQL function

D A backup system

Answer: B. It standardises metrics so every query uses the same logic.

6. What should you do before saving an AI-generated Metabase question?

A Nothing

B Read the SQL and reconcile at least one total against a simple independent query

C Share it with everyone

D Delete the database

Answer: B. Validation protects you from plausible but wrong numbers.

EXERCISE

Schema prompt and review

(1) Write a schema prompt for the `employees` table (HR data: emp_id, gender, age, department, job_title, education, hire_date, years_at_company, monthly_income, job_satisfaction, overtime, performance_rating, city, attrition) including at least three definitions. (2) Ask any AI assistant for a query that returns attrition % by department and overtime. (3) Review the result with the checklist and reconcile the overall attrition % (25.9%) with a simple query.

Show solution (worked answer)

Definitions to include: "Attrition %" = employees with attrition = 'Yes' ÷ all employees; `monthly_income` is in rupees; "tenure band" = 0–2, 3–5, 6+ years. Reconciliation query: `SELECT ROUND(100.0 * SUM(CASE WHEN attrition = 'Yes' THEN 1 ELSE 0 END) / COUNT(*), 1) FROM employees;` should return 25.9. The weighted total from the grouped result (sum of leavers ÷ sum of employees across all groups) must also equal 25.9.

INTERVIEW CORNER

Questions you may be asked

Q: How would you use AI to speed up SQL work safely? Provide schema, definitions and dialect; generate and explain queries; review for grain, filters and definitions; run read-only with limits; reconcile totals; keep verified queries in a library.

Q: What is Docker and why is it useful for data tools? A container platform that packages apps with their dependencies so the same setup runs anywhere; useful to spin up Metabase, databases or Jupyter in one command and share reproducible environments.

Q: What are the risks of connecting an AI assistant to a database? Data exposure to a model provider, destructive queries, wrong answers presented as facts, and prompt injection; mitigate with read-only access to curated views, masking, review and logging.

Q: What is Metabase? An open-source BI tool where users can ask questions with a visual builder or SQL, build dashboards and share them, with permission control by group.

Practise more online

Free, trusted places to test yourself on this topic. Links open the original site in a new tab.