SQL FOR DATA ANALYSIS · LESSON 7 OF 20

GROUP BY, HAVING, CASE WHEN, ROLLUP, CUBE & COALESCE

Turn rows into business summaries. Group with GROUP BY, filter groups with HAVING, create conditional columns and buckets with CASE WHEN, pivot data with conditional aggregation, and add subtotals and grand totals with ROLLUP, CUBE and GROUPING SETS, cleaning the labels with COALESCE and GROUPING().

● SQL class 4 · SQL–Power BI bridge ✦ SQL Server 2022, 2026 Intermediate ⏱ 130 min

By the end of this lesson you can


- Summarise data by one or more columns with GROUP BY and aggregate functions
- Filter groups with HAVING and explain WHERE vs HAVING
- Create conditional columns and buckets with CASE WHEN ... THEN ... ELSE ... END
- Build pivot-style reports with conditional aggregation
- Add subtotals and grand totals with ROLLUP, CUBE and GROUPING SETS, and label them with COALESCE and GROUPING()

Datasets used

`superstore_sales.csv` `hr_employees.csv`

GROUP BY: one row per group

`GROUP BY` collapses rows that share the same value(s) into one row, and aggregate functions summarise each group. It is the SQL version of a pivot table (Excel Lesson 8) and of `groupby()` in pandas.



GROUP BY region: rows with the same region are collected into one group, then SUM is computed for each group.

SQL

```sql
SELECT region,
       COUNT(DISTINCT order_id)              AS orders,
       ROUND(SUM(sales), 0)                  AS sales,
       ROUND(SUM(profit), 0)                 AS profit,
       ROUND(100.0 * SUM(profit) / SUM(sales), 1) AS margin_pct
FROM superstore
GROUP BY region
ORDER BY sales DESC;
```

RESULT

region	orders	sales	profit	margin_pct
South	831	53,952,769	4,702,012	8.7
West	811	51,958,521	4,719,833	9.1
North	792	49,018,161	4,555,830	9.3
East	766	46,484,119	4,374,490	9.4

4 rows × 5 columns

Grouping by several columns

SQL

```sql
SELECT category,
       sub_category,
       COUNT(*)              AS lines,
       ROUND(SUM(sales), 0)  AS sales,
       ROUND(SUM(profit), 0) AS profit
FROM superstore
GROUP BY category, sub_category
ORDER BY category, sales DESC;
```

RESULT

category	sub_category	lines	sales	profit
Furniture	Tables	505	14,046,224	-816,042
Furniture	Bookcases	477	11,274,849	-422,786
Furniture	Chairs	493	8,091,474	342,043
Furniture	Furnishings	442	1,429,307	78,632
Office Supplies	Appliances	492	6,333,529	944,927
Office Supplies	Storage	507	2,659,340	397,228
Office Supplies	Paper	559	493,232	75,040
Office Supplies	Binders	494	401,219	61,074
Office Supplies	Art	462	245,985	36,526
Technology	Copiers	468	78,749,926	8,436,141
Technology	Machines	491	42,590,335	5,186,711
Technology	Phones	488	31,919,223	3,663,117

13 rows × 5 columns (first 12 shown)

Grouping by an expression

SQL

```sql
SELECT YEAR(order_date)       AS order_year,
       COUNT(DISTINCT order_id) AS orders,
       ROUND(SUM(sales), 0)   AS sales
FROM superstore
GROUP BY YEAR(order_date)
ORDER BY order_year;
```

RESULT

order_year	orders	sales
2023	883	57,640,217
2024	1085	65,396,556
2025	1232	78,376,797

3 rows × 3 columns

WATCH OUT **The golden rule of GROUP BY**

Every column in SELECT must either be **in the GROUP BY** or **inside an aggregate function**. `SELECT region, city, SUM(sales) FROM superstore GROUP BY region` fails in SQL Server: "Column 'city' is invalid in the select list because it is not contained in either an aggregate function or the GROUP BY clause." Which city should it show for the North group? SQL refuses to guess.

HAVING: filtering groups

`WHERE` filters **rows before** grouping; `HAVING` filters **groups after** aggregation.

SQL

```sql
SELECT city,
       COUNT(DISTINCT order_id) AS orders,
       ROUND(SUM(profit), 0)    AS profit
FROM superstore
WHERE category = 'Furniture'          -- 1. keep only furniture rows
GROUP BY city                         -- 2. one row per city
HAVING SUM(profit) < 0                -- 3. keep only loss-making cities
ORDER BY profit;
```

RESULT

city	orders	profit
Chennai	100	-122,258
Delhi	101	-106,170
Chandigarh	92	-92,165
Lucknow	100	-87,616
Guwahati	77	-80,036
Kochi	93	-71,758
Bengaluru	101	-52,961
Bhubaneswar	80	-50,956
Ahmedabad	96	-50,770
Kolkata	111	-39,811
Patna	86	-38,624
Indore	102	-30,482

15 rows × 3 columns (first 12 shown)

	WHERE	HAVING
Runs	Before GROUP BY	After GROUP BY
Filters	Individual rows	Groups
Can use aggregates	No	Yes
Example	`WHERE region = 'West'`	`HAVING COUNT(*) > 100`
Performance	Reduces rows early (faster)	Applied to fewer, summarised rows

TIP **Filter as early as possible**

Put conditions that do not need aggregates in `WHERE`, not `HAVING`: `HAVING region = 'West'` works but makes the database group every region first and discard most of them.

CASE WHEN: conditional columns

`CASE` is SQL's IF/IFS (Excel Lesson 5). It returns a value for the first condition that is true.

SQL

```sql
CASE
    WHEN condition1 THEN result1
    WHEN condition2 THEN result2
    ELSE default_result          -- optional; without ELSE, unmatched rows get NULL
END
```

SQL

```sql
SELECT order_id, sales, discount, profit,
       CASE
           WHEN discount = 0    THEN 'No discount'
           WHEN discount ⩽ 0.2 THEN 'Up to 20%'
           ELSE 'Above 20%'
       END AS discount_band,
       CASE WHEN profit < 0 THEN 'Loss' ELSE 'Profit' END AS result
FROM superstore
ORDER BY row_id;
```

RESULT

order_id	sales	discount	profit	discount_band	result
IN-2023-00001	36,000	0.0	3,472.55	No discount	Profit
IN-2023-00001	3,850	0.0	1,169.54	No discount	Profit
IN-2023-00001	62,080	0.0	6,044.47	No discount	Profit
IN-2023-00002	5,216	0.2	450.16	Up to 20%	Profit
IN-2023-00003	24,591	0.3	-5,512.33	Above 20%	Loss
IN-2023-00003	8,288	0.3	-1,598.43	Above 20%	Loss
IN-2023-00003	2,100	0.0	510.43	No discount	Profit
IN-2023-00003	69,280	0.0	15,852.15	No discount	Profit

6,323 rows × 6 columns (first 8 shown)

The **simple** form compares one expression with values:

```sql
CASE ship_mode
    WHEN 'Same Day'    THEN 1
    WHEN 'First Class' THEN 2
    ELSE 3
END
```

CASE inside GROUP BY: buckets

```sql
SELECT CASE
           WHEN discount = 0    THEN '0%'
           WHEN discount ⩽ 0.2 THEN '1-20%'
           ELSE '>20%'
       END                                      AS discount_band,
       COUNT(*)                                 AS lines,
       ROUND(SUM(sales), 0)                     AS sales,
       ROUND(SUM(profit), 0)                    AS profit,
       ROUND(100.0 * SUM(profit) / SUM(sales), 1) AS margin_pct
FROM superstore
GROUP BY CASE
             WHEN discount = 0    THEN '0%'
             WHEN discount ⩽ 0.2 THEN '1-20%'
             ELSE '>20%'
         END
ORDER BY discount_band;
```

RESULT

discount_band	lines	sales	profit	margin_pct
0%	3480	123,936,290	21,718,963	17.5
1–20%	1943	57,729,097	697,141	1.2
>20%	900	19,748,182	-4,063,940	-20.6

3 rows × 5 columns

The same insight as the Excel crosstab and dashboard: discounts above 20% turn the margin sharply negative.

Conditional aggregation: pivoting with CASE

Put `CASE` inside an aggregate to turn row values into columns, which is how analysts build pivot-style reports in SQL:

SQL

```sql
SELECT region,
       ROUND(SUM(CASE WHEN category = 'Furniture'       THEN sales ELSE 0 END), 0) AS
furniture,
       ROUND(SUM(CASE WHEN category = 'Office Supplies' THEN sales ELSE 0 END), 0) AS
office_supplies,
       ROUND(SUM(CASE WHEN category = 'Technology'      THEN sales ELSE 0 END), 0) AS
technology,
       ROUND(SUM(sales), 0)                                                       AS total
FROM superstore
GROUP BY region
ORDER BY region;
```

RESULT

region	furniture	office_supplies	technology	total
East	7,942,093	2,719,513	35,822,514	46,484,119
North	7,975,869	2,219,543	38,822,750	49,018,161
South	9,593,302	2,468,888	41,890,579	53,952,769
West	9,330,590	2,725,361	39,902,570	51,958,521

4 rows × 5 columns

SQL

```sql
SELECT department,
       COUNT(*)                                                AS employees,
       SUM(CASE WHEN attrition = 'Yes' THEN 1 ELSE 0 END)       AS leavers,
       ROUND(100.0 * SUM(CASE WHEN attrition = 'Yes' THEN 1 ELSE 0 END) / COUNT(*), 1) AS
attrition_pct,
       ROUND(AVG(CASE WHEN overtime = 'Yes' THEN 1.0 ELSE 0 END) * 100, 1)             AS
overtime_pct
FROM employees
GROUP BY department
ORDER BY attrition_pct DESC;
```

RESULT

department	employees	leavers	attrition_pct	overtime_pct
Sales	414	126	30.4	26.6
R&D	389	101	26.0	32.1
IT	309	75	24.3	29.8
HR	83	19	22.9	31.3
Finance	154	35	22.7	20.1
Operations	151	33	21.9	32.5

6 rows × 5 columns

`AVG(CASE WHEN … THEN 1.0 ELSE 0 END)` is a neat way to get a percentage of rows meeting a condition.

NOTE **The PIVOT operator**

SQL Server also has a `PIVOT` operator:

```sql
SELECT region, [Furniture], [Office Supplies], [Technology]
FROM (SELECT region, category, sales FROM superstore) AS src
PIVOT (SUM(sales) FOR category IN ([Furniture], [Office Supplies], [Technology])) AS
p;
```

Conditional aggregation is more flexible (several measures, any conditions) and works in every database, so most analysts prefer it. `UNPIVOT` does the reverse, like Power Query's Unpivot (Excel Lesson 12).

Subtotals and grand totals: ROLLUP, CUBE, GROUPING SETS

ROLLUP

`GROUP BY ROLLUP (a, b)` returns the groups for `(a, b)`, **subtotals** for each a, and a **grand total**. Subtotal rows show NULL in the rolled-up columns.

SQL

```sql
SELECT region,
       category,
       ROUND(SUM(sales), 0) AS sales
FROM superstore
GROUP BY ROLLUP (region, category)
ORDER BY region, category;
```

RESULT

region	category	sales
East	Furniture	7,942,093
East	Office Supplies	2,719,513
East	Technology	35,822,514
East	NULL	46,484,119
North	Furniture	7,975,869
North	Office Supplies	2,219,543
North	Technology	38,822,750
North	NULL	49,018,161
South	Furniture	9,593,302
South	Office Supplies	2,468,888
South	Technology	41,890,579
South	NULL	53,952,769
West	Furniture	9,330,590
West	Office Supplies	2,725,361
West	Technology	39,902,570
West	NULL	51,958,521
NULL	NULL	201,413,569

17 rows × 3 columns

Cleaning the labels with COALESCE and GROUPING()

NULLs in subtotal rows are confusing. `COALESCE` replaces them with a label. If the data itself could contain NULL categories, use `GROUPING(col)`, which returns 1 only on rows where the column was rolled up:

SQL

```
SELECT CASE WHEN GROUPING(region) = 1 THEN 'All regions' ELSE region END            AS
region,
       CASE WHEN GROUPING(category) = 1 THEN 'Subtotal' ELSE category END           AS
category,
       ROUND(SUM(sales), 0)                                                         AS
sales
FROM superstore
GROUP BY ROLLUP (region, category)
ORDER BY GROUPING(region), region, GROUPING(category), category;
```

RESULT

region	category	sales
East	Furniture	7,942,093
East	Office Supplies	2,719,513
East	Technology	35,822,514
East	Subtotal	46,484,119
North	Furniture	7,975,869
North	Office Supplies	2,219,543
North	Technology	38,822,750
North	Subtotal	49,018,161
South	Furniture	9,593,302
South	Office Supplies	2,468,888
South	Technology	41,890,579
South	Subtotal	53,952,769
West	Furniture	9,330,590
West	Office Supplies	2,725,361
West	Technology	39,902,570
West	Subtotal	51,958,521
All regions	Subtotal	201,413,569

17 rows × 3 columns

The simple version used in class, `COALESCE(region, 'All regions')`, gives the same labels when the data has no real NULLs.

CUBE

`CUBE (a, b)` returns **every combination** of subtotals: by `(a, b)`, by `a`, by `b`, and the grand total. Use it when you need totals in both directions, like a pivot table with row and column grand totals.

SQL

```sql
SELECT COALESCE(segment, 'All segments')  AS segment,
       COALESCE(region, 'All regions')    AS region,
       COUNT(DISTINCT order_id)           AS orders
FROM superstore
GROUP BY CUBE (segment, region)
ORDER BY GROUPING(segment), segment, GROUPING(region), region;
```

RESULT

segment	region	orders
Consumer	East	355
Consumer	North	402
Consumer	South	385
Consumer	West	412
Consumer	All regions	1554
Corporate	East	245
Corporate	North	224
Corporate	South	269
Corporate	West	217
Corporate	All regions	955
Home Office	East	166
Home Office	North	166
Home Office	South	177
Home Office	West	182
Home Office	All regions	691
All segments	East	766
All segments	North	792
All segments	South	831
All segments	West	811
All segments	All regions	3200

20 rows × 3 columns

GROUPING SETS

`GROUPING SETS` lists exactly the groupings you want in one query:

```sql
SELECT COALESCE(category, '—')   AS category,
       COALESCE(ship_mode, '—')  AS ship_mode,
       ROUND(SUM(sales), 0)      AS sales
FROM superstore
GROUP BY GROUPING SETS ((category), (ship_mode), ())
ORDER BY category, ship_mode;
```

RESULT

category	ship_mode	sales
Furniture	—	34,841,853
Office Supplies	—	10,133,304
Technology	—	156,438,413
—	First Class	31,455,543
—	Same Day	10,082,430
—	Second Class	40,858,316
—	Standard Class	119,017,281
—	—	201,413,569

8 rows × 3 columns

This returns totals by category, totals by ship mode and the grand total, without the category × ship mode detail.

Syntax	Groupings produced for (a, b)
`GROUP BY a, b`	(a, b)
`ROLLUP (a, b)`	(a, b), (a), ()
`CUBE (a, b)`	(a, b), (a), (b), ()
`GROUPING SETS ((a), (b), ())`	exactly (a), (b), ()

TIP **Bridge to Power BI**

Power BI matrices compute these subtotals automatically, but ROLLUP/CUBE are perfect when you must deliver a fixed report table from SQL, feed a paginated report, or check that a dashboard's totals are right.

A complete analysis query

Question: *"For 2025, show each sub-category's sales, profit and margin, a performance label, and only sub-categories with at least ₹10 lakh sales, best margin first."*

SQL

```sql
SELECT sub_category,
       ROUND(SUM(sales), 0)                          AS sales,
       ROUND(SUM(profit), 0)                         AS profit,
       ROUND(100.0 * SUM(profit) / SUM(sales), 1)    AS margin_pct,
       CASE
           WHEN SUM(profit) < 0                       THEN 'Loss-making'
           WHEN 100.0 * SUM(profit) / SUM(sales) < 8  THEN 'Low margin'
           ELSE 'Healthy'
       END                                           AS status
FROM superstore
WHERE order_date ⩾ '2025-01-01' AND order_date < '2026-01-01'
GROUP BY sub_category
HAVING SUM(sales) ⩾ 1000000
ORDER BY margin_pct DESC;
```

RESULT

sub_category	sales	profit	margin_pct	status
Appliances	2,539,536	379,442	14.9	Healthy
Phones	12,935,910	1,708,007	13.2	Healthy
Machines	16,502,707	2,000,026	12.1	Healthy
Accessories	1,221,677	145,007	11.9	Healthy
Copiers	30,984,937	3,349,006	10.8	Healthy
Chairs	3,053,530	132,519	4.3	Low margin
Bookcases	3,918,269	-169,018	-4.3	Loss-making
Tables	5,297,064	-286,188	-5.4	Loss-making

8 rows × 5 columns

Summary

KEY TAKEAWAYS

- `GROUP BY` makes one row per group; every selected column must be grouped or aggregated.
- `WHERE` filters rows before grouping; `HAVING` filters groups after (can use aggregates).
- `CASE WHEN … THEN … ELSE … END` creates conditional columns and buckets; without ELSE, unmatched rows are NULL.
- Conditional aggregation (`SUM(CASE WHEN … THEN x ELSE 0 END)`) pivots rows into columns and computes percentages.
- `ROLLUP` adds hierarchical subtotals + grand total; `CUBE` adds all combinations; `GROUPING SETS` picks exactly the groupings you need.
- Label subtotal rows with `COALESCE` or, more robustly, `GROUPING()`.

Quick quiz

6 questions · tap an answer to check it

1. Why does `SELECT region, city, SUM(sales) FROM superstore GROUP BY region` fail?

A SUM needs a WHERE clause

B city is neither grouped nor aggregated

C region must be aggregated

D GROUP BY needs ORDER BY

Answer: B. Every selected column must appear in GROUP BY or in an aggregate.

2. Which clause keeps only customers with more than 10 orders?

A `WHERE COUNT(order_id) > 10`

B `HAVING COUNT(DISTINCT order_id) > 10`

C `ORDER BY COUNT(*) > 10`

D `GROUP BY COUNT(*) > 10`

Answer: B. Conditions on aggregates go in HAVING.

3. What does a CASE expression return when no WHEN matches and there is no ELSE?

A 0

B An empty string

C NULL

D An error

Answer: C. Without ELSE, unmatched rows return NULL.

4. `GROUP BY ROLLUP (region, category)` produces which groupings?

A (region, category), (region), and the grand total

B Every combination including (category) alone

C Only the grand total

D Only (region, category)

Answer: A. ROLLUP is hierarchical; CUBE would also include (category).

5. What does `AVG(CASE WHEN attrition = 'Yes' THEN 1.0 ELSE 0 END)` compute?

A The number of leavers

B The share (proportion) of employees who left

C The average salary of leavers

D NULL

Answer: B. The average of 1s and 0s is the proportion of 1s.

6. Which function tells you that a row is a subtotal created by ROLLUP?

A COALESCE

B ISNULL

C GROUPING

D NULLIF

Answer: C. GROUPING(col) returns 1 when col was aggregated away in that row.

EXERCISE **HR summary**

Using the `employees` table (HR data): (1) headcount, average monthly income and attrition % by department and gender, only for groups with at least 30 employees; (2) a column per education level showing headcount, one row per department; (3) average income by job satisfaction (1–4) with a grand total row using ROLLUP.

Show solution (worked answer)

SQL

```sql
-- (1)
SELECT department, gender, COUNT(*) AS headcount,
       ROUND(AVG(monthly_income * 1.0), 0) AS avg_income,
       ROUND(100.0 * SUM(CASE WHEN attrition = 'Yes' THEN 1 ELSE 0 END) / COUNT(*), 1)
AS attrition_pct
FROM employees GROUP BY department, gender HAVING COUNT(*) ⩾ 30 ORDER BY department,
gender;
-- (2)
SELECT department,
       SUM(CASE WHEN education = 'Diploma'    THEN 1 ELSE 0 END) AS diploma,
       SUM(CASE WHEN education = 'Bachelor''s' THEN 1 ELSE 0 END) AS bachelors,
       SUM(CASE WHEN education = 'Master''s'   THEN 1 ELSE 0 END) AS masters,
       SUM(CASE WHEN education = 'PhD'        THEN 1 ELSE 0 END) AS phd
FROM employees GROUP BY department;
-- (3)
SELECT COALESCE(CAST(job_satisfaction AS VARCHAR(5)), 'All') AS satisfaction,
       ROUND(AVG(monthly_income * 1.0), 0) AS avg_income
FROM employees GROUP BY ROLLUP (job_satisfaction) ORDER BY GROUPING(job_satisfaction),
job_satisfaction;
```

Note the doubled apostrophe in `'Bachelor''s'`: that is how you write a quote inside a SQL string.

INTERVIEW CORNER **Questions you may be asked**

Q: WHERE vs HAVING? WHERE filters rows before aggregation and cannot use aggregate functions; HAVING filters groups after GROUP BY and can.

Q: How do you pivot rows to columns in SQL? Conditional aggregation `SUM(CASE WHEN col = 'X' THEN value END)` per output column, or SQL Server's PIVOT operator.

Q: What are ROLLUP and CUBE? GROUP BY extensions that add subtotal and grand-total rows: ROLLUP follows the column hierarchy; CUBE produces all combinations. GROUPING() identifies the subtotal rows.

Q: Write a query to find the second-highest salary per department. Use DENSE_RANK() in a subquery/CTE (Lesson 11): `WHERE rnk = 2`.

Practise more online

Free, trusted places to test yourself on this topic. Links open the original site in a new tab.